

EXP 5

ARDUINO BASED MANUAL ELECTRONIC COUNTER USING PROTEUS

```
sketch_aug8c | Arduino IDE 2.3.10
File Edit Sketch Tools Help

Arduino UNO

sketch_aug8c.ino
1 int x0, x1, x2, x3, x4, x5, x6, x7, x8, x9;
2 int delay_time = 200;
3
4 void setup()
5 {
6   pinMode(12, INPUT_PULLUP);
7
8   pinMode(1, OUTPUT);
9   pinMode(2, OUTPUT);
10  pinMode(3, OUTPUT);
11  pinMode(4, OUTPUT);
12  pinMode(5, OUTPUT);
13  pinMode(6, OUTPUT);
14  pinMode(7, OUTPUT);
15
16  x0 = false;
17  x1 = false;
18  x2 = false;
19  x3 = false;
20  x4 = false;
21  x5 = false;
22  x6 = false;
23  x7 = false;
24  x8 = false;
25  x9 = false;
26 }
27
28 void loop()
29 {
30   int sensorVal = digitalRead(12);
31   if (sensorVal == LOW)
32   {
33     x0 = !x0;
34     x1 = !x1;
35     x2 = !x2;
36     x3 = !x3;
37     x4 = !x4;
38     x5 = !x5;
39     x6 = !x6;
40     x7 = !x7;
41     x8 = !x8;
42     x9 = !x9;
43     delay(delay_time);
44   }
45 }
```

Output

Sketch uses 2374 bytes (7%) of program storage space. Maximum is 32256 bytes.
Global variables use 29 bytes (1%) of dynamic memory, leaving 2019 bytes for local variables. Maximum is 2048 bytes.

Ln 304, Col 2 Arduino UNO [not connected]

