Handbook of Comparative World Steel Standards

Third Edition

John E. Bringas, Editor



Handbook of Comparative World Steel Standards

ASTM DS67B

Third Edition

John E. Bringas, Editor

Library of Congress Cataloging-in-Publication Data

Handbook of comparative world steel standards / John E. Bringas, editor. -2^{nd} ed.

p.cm – (ASTM data series; DS 67A)

"ASTM stock number: DS67A."

ISBN 0-8031-3042-2

 $1.\ Steel-Standards-Handbooks, manuals, etc., 2.\ Steel\ alloys-Standards-Handbooks,$

manuals, etc. I. Bringas, John E., 1953- II. ASTM data series publication; DS 67A.

TA472.H25 2002

620.1'7'0218—dc21 2001045950

CIP

Copyright © 2004 ASTM International, West Conshohocken, PA. All rights reserved. This material may not be reproduced or copied, in whole or in part, in any printed, mechanical electronic, film, or other distribution and storage media, without the written consent of the publisher.

Photocopy Rights

Authorization to photocopy items for internal, personal, or educational classroom use, or the internal personal, or education classroom use of specific clients, is granted by the American Society for Testing and Materials (ASTM International) provided that the appropriate fee is paid to the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923; Tel: 978-750-8400; online: http://www.copyright.com/.

Printed in USA August 2004

Acknowledgements

The author gratefully acknowledges the assistance of Michael Ling, P.Eng. and Denise Lamy, P.Eng., who were the Assistant Editors of the second (DS67A) and third (DS67B) editions of this handbook. They worked many long hours, weekends, and holidays to researching hundreds of standards and double-checking thousands of pieces of data. Their work in compiling the heat treatment terms for each standard and researching the new EN piping and tubing standards was of particular importance. They were also my main sounding boards when difficult technical decisions had to be made.

There were also several ASTM committee members contacted for their input during the progress of this handbook, including Ralph Davison, Frank Christensen, David Knupp, and John Mahaney. They added valuable insights into the history and technical aspects of the ASTM standards data found in this handbook. The ASTM publishing staff—including Kathy Dernoga, Roberta Storer and Margie Lawlor—was most supportive of my requests to obtain access to the hundreds of standards needed to write this book and assistance with editing. I appreciate their patience and confidence in me to complete the work. Thank you all.

The author also acknowledges the dedicated assistance of Steven Li and Nina Phan who assisted in the research and entered much of the data in the book with care and diligence. A special thank you to Christine Doyle who entered data almost endlessly into the late hours of the night for the second edition (DS67A), and to Debbie Knack—who kept the office running smoothly during the production of this handbook.

A special thanks is extended to IHS Engineering Products for use of their Engineering Resource Center (ERC).

One person could not have produced this handbook and the accompanying e-book. It took a dedicated team of professionals. These acknowledgments cannot adequately express the author's sincere appreciation and gratitude for everyone's assistance. Without it, this book would never have been completed.

Preface

This is the book I never wanted to write, but always wanted to own. As a metallurgical engineer and long time user of steel standards, author of the four CASTI Metals Data Books, and member of ASTM A01 and B02 standard committees, I knew all too well the many pitfalls and challenges of writing such a handbook. There were many steel standards from around the world that were new to me, which created far too many surprises and delays in completing this book.

Comparing steel standards is not an exact science, so the biggest challenge of preparing such a book was deciding on the "rules of comparison." Of the similar books on the market today, none explain in detail why one steel is comparable to another. They simply appear together in a list of steels. I kept a daily diary to help construct a workable set of comparison rules that I could share with other users to assist them in understanding how and why one steel is comparable to another.

To say the least, these rules changed from chapter to chapter while the book was being written. It wasn't until the last chapter and appendix were completed that I was able to finalize the rules of comparison. In the end, a complete review of the book was performed resulting in the reorganization of some chapters and the fine-tuning of others. There were too many occasions when I thought the book was finished, only to have to change, add, or delete a rule which made yet another review of the book necessary.

After more than two years of researching steel standards and gathering data from around the world for the 2nd and 3rd editions of this handbook, then developing a comparison order to more than 100,000 pieces of data, this handbook is an ongoing and expanding project. The addition of a fully searchable e-book on CD-ROM makes this product even more valuable, since trying to find one piece of data in more than 100,000 is not an easy task. The e-book makes searching for a comparable steel a quick and easy process. In some cases, the user may find out that the steel is non-comparable.

I hope you enjoy using this handbook as much as I will. Tie a chain to it and anchor it to your desk, because once others see it, they'll want to use your copy. I am interested in your comments and suggestions to improve this handbook, so I encourage you to send your feedback directly to ASTM.

John E. Bringas, P.Eng.

Getting Started With This Book

Comparing steel standards is not an exact science and there is no foolproof method. When you begin to use this book, you'll quickly discover that there is no such thing as "equivalent" steel standards. Then, consider the fact that not all steels have comparative counterparts and you'll begin to understand the methodology used in this book. Before proceeding directly to the contents of this book, it is strongly recommended that you read Chapter 1, which includes a detailed explanation of the "rules of comparison" used in this book.

Since there was insufficient space on one page to place both the chemical composition and mechanical properties tables, they were split into two separate tables. To assist the user in keeping track of which comparison criteria were used for a given steel, each table within a chapter was sequentially numbered and appended with either the letter A or B. Table numbers ending in the letter A designate that the table was the main criterion used for comparison; whereas table numbers ending with the letter B were "mirrored" from the A table.

Each group of steel data in the tables is separated by two types of horizontal lines: black and grey. Black lines separate groups of steels that are more closely comparable to each other, whereas grey lines separate steel data within a comparative group.

Caution: do not confuse the thinner dividing black line within a table, with the thicker black line that borders the outside of the table. The pages are formatted to keep comparative groups together as much as possible. However, when a group of comparative steels extends to more than one page, a note is place at the bottom of the page to indicate that the comparative group continues on the following page, i.e., NOTE: This section continues on the next page.

Getting Started With This CD-ROM

Minimum System Requirements

- Intel Pentium processor
- Microsoft Windows 98 Second Edition, Millennium Edition, Windows NT 4.0 (SP 6), 2000 (SP 2), XP Professional or XP Home Edition
- 32 MB RAM and 640 x 480 video resolution (higher resolution will improve readability)
- 60 MB hard disk space

Adobe Acrobat and Adobe Reader

In order to view the E-book of Comparative World Steel Standards you must have PDF viewing software (such as Adobe Acrobat or Adobe Reader) installed prior to running the CD-ROM.

If you already have PDF viewing software installed, insert the CD-ROM into your CD drive and click the "View E-book" button in the software menu to open the E-book.

If you need to install Adobe Reader, please visit the Adobe website at www.adobe.com to download and install the latest version of the software. The Adobe website has detailed information regarding Adobe software and its minimum system requirements. Please review the pertinent information regarding Adobe software before download and installation.

Getting Started

The E-book of Comparative World Steel Standards on CD-ROM is a fully searchable Adobe PDF file. Once the E-book is opened, a menu will appear with several options to navigate and search through the E-book. This menu contains links to the Table of Contents, all four Indexes, and to the Search function. Listings in the Table of Contents of the E-book are linked to their respective pages so that users may click on these listings to navigate directly to the desired page.

Starting the search tool can be done by clicking on the Search link in the main menu or by clicking on the Search button on the Acrobat/Reader tool bar. Please be aware that in some versions of Acrobat/Reader there is a Find tool and a Search tool. In general, the Search tool is a more powerful searching function. For more assistance with using Adobe Acrobat or Adobe Reader, click on the Help menu within the Adobe software.

Troubleshooting

If the main menu does not appear on your screen after the CD-ROM is inserted in your computer, the CD-ROM startup Autostart function for Windows 95/98/Me/NT/2000 is not setup. Please consult your OS manual for instructions to enable the Autostart function.

Table of Contents

1.			n to Comparing World Steel Standards	
			ethodology When Comparing Steel Standards	
			and Closest Match	
			1	
	Defi	nition ar	d Steel Terms	5
			Note	
			egarding the Rules of Comparison	
			rable Steels	
			Comparing Steels	
			parison Rules	
			ction to Steel Standards and Designation Systems	
	AST	M Desig	nation System	12
			ence Standards and Supplementary Requirements	
	SAE		ation System and Discontinued AISI Designation System	
			and Alloy Steels	
			ation System	
			andards Association (CSA)	
			to European Standard Steel Designation System	
	FIN		tandard Designation System for Steels	
			ames	
			umbers	
	Forr	ner ivati	onal Standards Replaced by CEN Standards	19
2	Carl	bon and	Alloy Steels for General Use	21
			cal Composition of Carbon Steels for General Use	
			cal Composition of High Manganese Carbon Steels for General Use	
			cal Composition of Alloy Steels for General Use	
		2.3.1	Chromium (Cr) Steels	
		2.3.2	Chromium-Molybdenum (Cr-Mo) Steels	
		2.3.3	Chromium-Nickel (Cr-Ni) Steels	
		2.3.4	Nickel-Chromium-Molybdenum (Ni-Cr-Mo) Steels	
		2.3.5	Chromium-Molybdenum-Aluminum (Cr-Mo-Al) Steels	40
		2.3.6	Boron (B) Steels	41
		2.3.7	Chromium-Vanadium (Cr-V) Steels	
	2.4	Non-Co	omparable Carbon and Alloy Steels for General Use	43
_				
3.			Steel Plates	
	3.1		Steels for Structural Steel Plates	
		3.1A	Mechanical Properties of Carbon Steels for Structural Steel Plates	
	0.0	3.1B	Chemical Composition of Carbon Steels for Structural Steel Plates	
	3.2		teels for Structural Steel Plates	
			Mechanical Properties of High-Strength Low-Alloy Structural Steel Plates	
			Chemical Composition of High-Strength Low-Alloy Structural Steel Plates	
			Mechanical Properties of Alloy Steels for Structural Steel Plates	
	3 3		Chemical Composition of Alloy Steels for Structural Steel Platesral Steels with Improved Atmospheric Corrosion-Resistance	
	3.3	3.3A	Mechanical Properties of Structural Steels with Improved Atmospheric	00
		3.3A	Corrosion-Resistance	00
		3.3B	Chemical Composition of Structural Steels with Improved Atmospheric	oc
		0.00	Correction Designation	0.4

	3.4	Non-Comparable Carbon Steels for Structural Steel Plates	97
	3.5	Non-Comparable Alloy Steels for Structural Steel Plates	98
	_	V 10: 15:	
٠		ssure Vessel Steel Plates	
	4. I	Carbon Steels for Pressure Vessel Plates	
		4.1A Mechanical Properties of Carbon Steel Pressure Vessel Plates	
	4.0	4.1B Chemical Composition of Carbon Steel Pressure Vessel Plates	
	4.2	Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C	113
		4.2A Mechanical Properties of Carbon Steels for Pressure Vessel Plates -	110
		With Impact Testing Below -20°C	113
		4.2B Chemical Composition of Carbon Steels for Pressure Vessel Plates -	115
	10	With Impact Testing Below -20°C	117
	4.3	4.3A Chemical Composition of ½Mo Alloy Steels for Pressure Vessel Plates	
	11	4.3B Mechanical Properties of ½Mo Alloy Steels for Pressure Vessel Plates Cr-Mo Alloy Steels for Pressure Vessel Plates	
	4.4	4.4.1A Chemical Composition of ³ / ₄ Cr-½Mo Alloy Steels for Pressure Vessel Plates	
		4.4.1B Mechanical Properties of ³ / ₄ Cr-½Mo Alloy Steel for Pressure Vessel Plates	
		4.4.2A Chemical Composition of 1Cr-½Mo Alloy Steels for Pressure Vessel Plates	
		4.4.2B Mechanical Properties of 1Cr-½Mo Alloy Steels for Pressure Vessel Plates	
		4.4.3A Chemical Composition of 1¼Cr-½Mo Alloy Steels for Pressure Vessel Plates	
		4.4.3B Mechanical Properties of 1½Cr-½Mo Alloy Steels for Pressure Vessel Plates	
		4.4.4A Chemical Composition of 2¼Cr-1Mo Alloy Steels for Pressure Vessel Plates	
		4.4.4B Mechanical Properties of 21/4Cr-1Mo Alloy Steels for Pressure Vessel Plates	
		4.4.5A Chemical Composition of 3Cr-1Mo Alloy Steels for Pressure Vessel Plates	
		4.4.5B Mechanical Properties of 3Cr-1Mo Alloy Steels for Pressure Vessel Plates	
		4.4.6A Chemical Composition of 5Cr-1/2Mo Alloy Steels for Pressure Vessel Plates	
		4.4.6B Mechanical Properties of 5Cr-1/2Mo Alloy Steels for Pressure Vessel Plates	
		4.4.7A Chemical Composition of 9Cr-1Mo Alloy Steels for Pressure Vessel Plates	
		4.4.7B Mechanical Properties of 9Cr-1Mo Alloy Steels for Pressure Vessel Plates	128
	4.5	Ni Alloy Steels for Pressure Vessel Plates	129
		4.5.1A Chemical Composition of ½Ni Alloy Steels for Pressure Vessel Plates	129
		4.5.1B Mechanical Properties of ½Ni Alloy Steels for Pressure Vessel Plates	129
		4.5.2A Chemical Composition of 1½Ni Alloy Steels for Pressure Vessel Plates	130
		4.5.2B Mechanical Properties of 1½Ni Alloy Steels for Pressure Vessel Plates	
		4.5.3A Chemical Composition of 2¼Ni Alloy Steels for Pressure Vessel Plates	
		4.5.3B Mechanical Properties of 21/4Ni Alloy Steels for Pressure Vessel Plates	
		4.5.4A Chemical Composition of 3½Ni Alloy Steels for Pressure Vessel Plates	
		4.5.4B Mechanical Properties of 3½Ni Alloy Steels for Pressure Vessel Plates	
		4.5.5A Chemical Composition of 5Ni Alloy Steels for Pressure Vessel Plates	
		4.5.5B Mechanical Properties of 5Ni Alloy Steels for Pressure Vessel Plates	
		4.5.6A Chemical Composition of 9Ni Alloy Steels for Pressure Vessel Plates	
		4.5.6B Mechanical Properties of 9Ni Alloy Steels for Pressure Vessel Plates	
	4.6	Ni-Mo Alloy Steels for Pressure Vessel Plates	
		4.6.1A Chemical Composition of ½Ni-½Mo Alloy Steels for Pressure Vessel Plates	
		4.6.1B Mechanical Properties of ½Ni-½Mo Alloy Steels for Pressure Vessel Plates	
		4.6.2A Chemical Composition of 3/Ni-1/2Mo Alloy Steels for Pressure Vessel Plates	
	4 7	4.6.2B Mechanical Properties of 3/4Ni-1/2Mo Alloy Steels for Pressure Vessel Plates	
	4.7	Ferritic and Martensitic Stainless Steels for Pressure Vessel Plates	141
		4.7A Chemical Composition of Ferritic and Martensitic Stainless Steels for	4 1 4
		Pressure Vessel Plates	141
		Pressure Vessel Plates	142
		LIESSUIE VESSELEIGIES	147

	4.8	Austeni	itic Stainless Steels for Pressure Vessel Plates	. 143
		4.8A	Chemical Composition of Austenitic Stainless Steels for Pressure Vessel Plates	
		4.8B	Mechanical Properties of Austenitic Stainless Steels for Pressure Vessel Plates	. 146
	4.9	Duplex	Stainless Steels for Pressure Vessel Plates	
		4.9A	Chemical Composition of Duplex (Ferritic-Austenitic) Stainless Steels for	
			Pressure Vessel Plates	. 151
		4.9B	Mechanical Properties of Duplex (Ferritic-Austenitic) Stainless Steels for	
			Pressure Vessel Plates	. 152
	4.10	Non-Co	omparable Carbon and Alloy Steels for Pressure Vessel Plates	. 153
	4.11	Non-Co	omparable Stainless Steels for Pressure Vessel Plates	. 156
5.			and Pipes	
	5.1		Steel Tubes for General and Structural Applications	. 165
		5.1A	Mechanical Properties of Carbon Steel Tubes for General and	
			Structural Applications	. 165
		5.1B	Chemical Composition of Carbon Steel Tubes for General and	
			Structural Applications	
	5.2		teel Tubes for General and Structural Applications	
		5.2A	Chemical Composition of Alloy Steel Tubes for General and Structural Applications	
		5.2B	Mechanical Properties of Alloy Steel Tubes for General and Structural Applications	
	5.3		ss Steel Tubes for General and Structural Applications	. 188
		5.3.1A	Chemical Composition of Ferritic and Martensitic Stainless Steel Tubes for	
			General and Structural Applications	. 188
		5.3.1B	Mechanical Properties of Ferritic and Martensitic Stainless Steel Tubes for	
			General and Structural Applications	. 189
		5.3.2A	Chemical Composition of Austenitic Stainless Steel Tubes for	
		5 0 OD	General and Structural Applications	. 190
		5.3.2B	Mechanical Properties of Austenitic Stainless Steel Tubes for	400
	- 4	O	General and Structural Applications	. 193
	5.4		Steel Tubes and Pipes for Low-Temperature Service	. 196
		5.4A	Mechanical Properties of Carbon Steel Tubes and Pipes -	100
		5.4B	With Impact Testing Below -20°C	. 190
		3.4D	With Impact Testing Below -20°C	100
	= =	Alloy C	teel Tubes and Pipes for Low-Temperature Service	
	5.5	5.5A	Chemical Composition of Alloy Steel Tubes and Pipes for Low-Temperature Service.	
		5.5A 5.5B	Mechanical Properties of Alloy Steel Tubes and Pipes for Low-Temperature Service.	
	5.6		Steel Tubes and Pipes for Pressure Purposes	
	5.0		Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes	
		5.6A 5.6B	Chemical Composition of Carbon Steel Tubes and Pipes for Pressure Purposes	
	5.7		Steel Tubes and Pipes for Pressure Purposes at High Temperatures	
	5.7	5.7A	Mechanical Properties of Carbon Steel Tubes and Pipes for	. 200
		J./ A	Pressure Purposes at High Temperatures	206
		5.7B	Chemical Composition of Carbon Steel Tubes and Pipes for	. 200
		J.7 D	Pressure Purposes at High Temperatures	210
	5.8	Allov S	teel Tubes and Pipes for Pressure Purposes at High Temperatures	
	5.0		Chemical Composition of 1/4Mo Alloy Steel Tubes and Pipes for	. 210
		0.0.171	Pressure Purposes at High Temperatures	213
		5 8 1R	Mechanical Properties of ¼Mo Alloy Steel Tubes and Pipes for	10
		5.5.15	Pressure Purposes at High Temperatures	213
		582A	Chemical Composition of ½Mo Alloy Steel Tubes and Pipes for	0
		J.J.Z/1	Pressure Purposes at High Temperatures	214
		5.8 2B	Mechanical Properties of ½Mo Alloy Steel Tubes and Pipes for	¬
		5.5.20	Pressure Purposes at High Temperatures	215

	5.8.3A	Chemical Composition of ½Cr-½Mo Alloy Steel Tubes and Pipes for	
		Pressure Purposes at High Temperatures	. 216
	5.8.3B		
		Pressure Purposes at High Temperatures	. 216
	5.8.4A	Chemical Composition of 1Cr-1/2Mo Alloy Steel Tubes and Pipes for	
		Pressure Purposes at High Temperatures	. 217
	5.8.4B	Mechanical Properties of 1Cr-1/2Mo Alloy Steel Tubes and Pipes for	
		Pressure Purposes at High Temperatures	. 218
	5.8.5A	Chemical Composition of 11/4Cr-1/2Mo Alloy Steel Tubes and Pipes for	
		Pressure Purposes at High Temperatures	. 219
	5.8.5B		
		Pressure Purposes at High Temperatures	. 219
	5.8.6A	Chemical Composition of 21/4-1Mo Alloy Steel Tubes and Pipes for	
		Pressure Purposes at High Temperatures	. 220
	5.8.6B	Mechanical Properties of 21/4-1Mo Alloy Steel Tubes and Pipes for	
		Pressure Purposes at High Temperatures	. 220
	5.8.7A	Chemical Composition of 5Cr-½Mo Alloy Steel Tubes and Pipes for	
	0.0	Pressure Purposes at High Temperatures	221
	5 8 7B	Mechanical Properties of 5Cr-½Mo Alloy Steel Tubes and Pipes for	
	0.0.7 D	Pressure Purposes at High Temperatures	221
	5 8 8A	Chemical Composition of 9Cr-1Mo Alloy Steel Tubes and Pipes for	
	0.0.071	Pressure Purposes at High Temperatures	222
	5 8 8B	Mechanical Properties of 9Cr-1Mo Alloy Steel Tubes and Pipes for	
	J.U.UD	Pressure Purposes at High Temperatures	222
5.9	Stainle	ss Steel Tubes and Pipes for Pressure Purposes and High Temperatures	
0.0		Chemical Composition of Ferritic and Martensitic Stainless Steel	. 220
	J.J. 1A	Tubes and Pipes for Pressure Purposes and High Temperatures	223
	501R	Mechanical Properties of of Ferritic and Martensitic Stainless Steel	. 220
	J.J. 1D	Tubes and Pipes for Pressure Purposes and High Temperatures	22/
	5 Q 2 A	Chemical Composition of Austenitic Stainless Steel Tubes and Pipes for	. 22-
	J.J.ZA	Pressure Purposes and High Temperatures	225
	5 0 2B	Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for	. 22
	J.3.ZD	Pressure Purposes and High Temperatures	22/
5 10	Lina Dir	pe Steels	
3.10		Mechanical Properties of Line Pipe Steels Without Notch Toughness Requirements	
		Chemical Composition of Line Pipe Steels Without Notch Toughness Requirements	
		Mechanical Properties of Line Pipe Steels With Notch Toughness Requirements	
		Chemical Composition of Line Pipe Steels With Notch Toughness Requirements	
5 11		omparable Carbon Steel Tubes for General and Structural Applications	
		omparable Alloy Steel Tubes for General and Structural Applications	
		omparable Stainless Steel Tubes for General and Structural Applications	
		omparable Carbon Steel Tubes and Pipes for Low Temperature Service	
		omparable Carbon Steel Tubes and Pipes for Low Temperature Service	
		omparable Carbon Steel Tubes and Pipes for Pressure Purposes at	. 200
5.16		emperatures	260
E 17		emperatures Imparable Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures .	
			. 20
5.10		omparable Stainless Steel Tubes and Pipes for Pressure Purposes and	060
T 10		emperatures	
ე. 19	Non-Co	omparable Line Pipe Steels	. ∠63
Steel	Forain	gs	. 265
		Steel Forgings	
		Mechanical Properties of Carbon Steel Forgings for General Use	
		Chemical Composition of Carbon Steel Forgings for General Use	
	· ·	1	

6.

	6.1.2A	Mechanio	cal Properties of Carbon Steel Forgings for Piping, Pressure Vessel	
			ponents	. 272
	6.1.2B	Chemica	Composition of Carbon Steel Forgings for Piping, Pressure Vessel	
		and Com	ponents	. 275
3.2	Alloy St	teel Forgir	ngs	. 277
	6.2.1A	Chemica	I Composition of 11/4 Cr-1/4 Mo Alloy Steel Forgings for General Use	. 277
	6.2.1B	Mechanic	cal Properties of 11/4Cr-1/4Mo Alloy Steel Forgings for General Use	. 278
	6.2.2	Alloy Ste	el Forgings for Piping, Pressure Vessel and Components	. 279
		6.2.2.1A	Chemical Composition of Mo Alloy Steel Forgings for Piping,	
				. 279
			Mechanical Properties of Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 279
			Chemical Composition of ½Cr-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 280
			Mechanical Properties of ½Cr-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 280
		6.2.2.3A	Chemical Composition of 1Cr-1/2Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 281
			Mechanical Properties 1Cr-1/2Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 281
		6.2.2.4A	Chemical Composition of 11/4Cr-1/2Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 282
			Mechanical Properties 1½Cr-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 282
			Chemical Composition of 21/4Cr-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 283
			Mechanical Properties of 2¼Cr-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 284
			Chemical Composition of 3Cr-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 285
			Mechanical Properties of 3Cr-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 285
			Chemical Composition of 5Cr-1/2Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 286
			Mechanical Properties of 5Cr-1/2Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 286
			Chemical Composition of 9Cr-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 287
			Mechanical Properties of 9Cr-1Mo Alloy Steel Forgings for Piping,	
				. 287
			Chemical Composition of 11Cr-½Ni-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 288
			Mechanical Properties of 11Cr-½Ni-1Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 288
			A Chemical Composition of Ni Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 289
		6.2.2.10E	B Mechanical Properties of Ni Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 290
		6.2.2.11 <i>A</i>	A Chemical Composition of Ni-Mn Alloy Steel Forgings for Piping,	- •
			Pressure Vessel and Components	. 291
		6.2.2.11E	B Mechanical Properties of Ni-Mn Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 291

			6.2.2.12A Chemical Composition of C\vNi-½Cr-Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 292
			6.2.2.12B Mechanical Properties of C\vNi-½Cr-Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 292
			6.2.2.13A Chemical Composition of C\vNi-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 293
			6.2.2.13B Mechanical Properties of C\vNi-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 293
			6.2.2.14A Chemical Composition 3¼Ni-1C\vCr-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 294
			6.2.2.14B Mechanical Properties 3¼Ni-1C\vCr-½Mo Alloy Steel Forgings for Piping,	
			Pressure Vessel and Components	. 294
	6.3		ss Steel Forgings	
		6.3.1A	Chemical Composition of Martensitic Stainless Steel Forgings	. 295
			Mechanical Properties of Martensitic Stainless Steel Forgings	
			Chemical Composition of Ferritic Stainless Steel Forgings	
			Mechanical Properties of Ferritic Stainless Steel Forgings	
			Chemical Composition of Austenitic Stainless Steel Forgings	
			Mechanical Properties of Austenitic Stainless Steel Forgings	
			Chemical Composition of Precipitation-Hardening Stainless Steel Forgings	
			Mechanical Properties of Precipitation-Hardening Stainless Steel Forgings	
			Chemical Composition of Duplex (Ferritic-Austenitic) Stainless Steel Forgings	
			Mechanical Properties of Duplex (Ferritic-Austenitic) Stainless Steel Forgings	
	6.4		omparable Carbon Steel Forgings for General Use	
	6.5		omparable Carbon Steel Forgings for Piping, Pressure Vessel and Components	
	6.6		omparable Alloy Steel Forgings for General Use	
	6.7		omparable Alloy Steel Forgings for Piping, Pressure Vessel and Components	
	6.8		omparable Stainless Steel Forgings	
7.	Stee	el Castir	ngs	. 315
	7.1		arbon Steels	
		7.1.1A	Mechanical Properties of Cast Carbon Steel for General and Structural Applications	. 319
			Chemical Composition of Cast Carbon Steel for General and Structural Applications.	
			Mechanical Properties of Cast Carbon Steel for Pressure Purposes at	
			High Temperatures	. 326
		7.1.2B	Chemical Composition of Cast Carbon Steel for Pressure Purposes at	
			High Temperatures	. 326
		7.1.3A	Mechanical Properties of Cast Carbon Steel for Pressure Purposes at	
			Low Temperatures	. 327
		7.1.3B	Chemical Composition of Cast Carbon Steel for Pressure Purposes at	
			Low Temperatures	. 327
	7.2	Cast M	anganese Steels	
		7.2A	Chemical Composition of Cast Manganese Steels	
		7.2B	Mechanical Properties of Cast Manganese Steels	
	7.3	Cast Al	loy Steels	
			Chemical Composition of Cast Alloy Steels for General and Structural Purposes	
			Mechanical Properties of Cast Alloy Steels for General and Structural Purposes	
			Chemical Composition of Cast Alloy Steels for Pressure Purposes at	50
			High Temperatures	. 335
		7.3 2B	Mechanical Properties of Cast Alloy Steels for Pressure Purposes at	. 550
			High Temperatures	. 336
		7 3 3A	Chemical composition of Cast Alloy Steels for Pressure Purposes at	. 550
		, , .	Low Temperatures	337
		7.3.3B	Mechanical Properties of Cast Alloy Steels for Pressure Purposes at	507
		۵.0.		
			Low Temperatures	338

	7.4	Cast St	ainless Steels	. 339
		7.4.1	Cast Stainless Steels for General and Corrosion Resistant Applications	. 339
			7.4.1.1A Chemical Composition of Martensitic and Ferritic Stainless Steels for	
			General and Corrosion Resistant Applications	. 339
			7.4.1.1B Mechanical Properties of Martensitic and Ferritic Stainless Steels for	
			General and Corrosion Resistant Applications	. 340
			7.4.1.2A Chemical Composition of Austenitic Stainless Steels for General and	
			Corrosion Resistant Applications	. 341
			7.4.1.2B Mechanical Properties of Austenitic Stainless Steels for General and	
			Corrosion Resistant Applications	. 344
		7.4.2	Cast Stainless Steels for Pressure Purposes	
			7.4.2.1A Chemical Composition of Martensitic and Ferritic Stainless Steels for	
			Pressure Purposes	. 347
			7.4.2.1B Mechanical Properties of Martensitic and Ferritic Stainless Steels for	
			Pressure Purposes	. 348
			7.4.2.2A Chemical Composition of Austenitic Stainless Steels for Pressure Purposes	
			7.4.2.2B Mechanical Properties of Austenitic Stainless Steels for Pressure Purposes	
	7.5	Cast He	eat Resistant Steels	
		7.5A	Chemical Composition of Cast Heat Resistant Steels	
		7.5B	Mechanical Properties of Cast Heat Resistant Steels	
	7.6		omparable Cast Carbon Steels	
	7.7		omparable Cast Manganese Steels	
	7.8		omparable Cast Alloy Steels	
	7.9		omparable Cast Stainless Steels for General and Corrosion Resistant Applications	
	_		omparable Cast Stainless Steels for Pressure Purposes	
			omparable Cast Heat Resistant Steels	
8.	Wro	ught St	ainless Steels	. 363
			ss Steels: Plate, Sheet and Strip	
			Chemical Composition of Martensitic Stainless Steels	
			Mechanical Properties of Martensitic Stainless Steels	
			Chemical Composition of Ferritic Stainless Steels	
			Mechanical Properties of Ferritic Stainless Steels	
			Chemical Composition of Austenitic Stainless Steels	
			Mechanical Properties of Austenitic Stainless Steels	
			Chemical Composition of Precipitation-Hardening Stainless Steels	
			Mechanical Properties of Precipitation-Hardening Stainless Steels	
		8.1.5A	Chemical Composition of Duplex (Ferritic-Austenitic) Stainless Steels	. 392
			Mechanical Properties of Duplex (Ferritic-Austenitic) Stainless Steels	
	8.2		ss Steels: Bar	
		8.2.1A	Chemical Composition of Martensitic Stainless Steels	. 394
			Mechanical Properties of Martensitic Stainless Steels	
			Chemical Composition of Ferritic Stainless Steels	
			Mechanical Properties of Ferritic Stainless Steels	
			Chemical Composition of Austenitic Stainless Steels	
			Mechanical Properties of Austenitic Stainless Steels	
			Chemical Composition of Precipitation-Hardening Stainless Steels	
			Mechanical Properties of Precipitation-Hardening Stainless Steels	
		8.2 5A		
			Chemical Composition of Duplex Stainless Steels	. 412
	8.3	8.2.5B		. 412 . 412

			pecial Use	
(9.1		achining Steels	420
		9.1.1	Chemical Composition of Resulfurized Carbon Steels for	
			Free-Machining Applications	420
		9.1.2	Chemical Composition of Rephosphorized and Resulfurized Carbon Steels for	
			Free-Machining Applications	422
		9.1.3	Chemical Composition of Resulfurized and Leaded Carbon Steels for	
			Free-Machining Applications	423
		9.1.4	Chemical Composition of Rephosphorized, Resulfurized, and	
			Leaded Carbon Steels for Free-Machining Applications	424
		9.1.5	Chemical Composition of Free-Machining Stainless Steels	
,	9.2	. •	Steels	425
		9.2.1	Chemical Composition of Cold Rolled Carbon Spring Steels	
		9.2.2	Chemical Composition of Hot Rolled Alloy Spring Steels	
			9.2.2.1 Chemical Composition of Hot Rolled Si Alloy Spring Steels	
			9.2.2.2 Chemical Composition of Hot Rolled Cr Alloy Spring Steels	
			9.2.2.3 Chemical Composition of Hot Rolled Cr-Si Alloy Spring Steels	
			9.2.2.4 Chemical Composition of Hot Rolled Cr-Mo Alloy Spring Steels	
			9.2.2.5 Chemical Composition of Hot Rolled Cr-V Alloy Spring Steels	
			9.2.2.6 Chemical Composition of Hot Rolled Cr-B Alloy Spring Steels	
,		9.2.3	Chemical Composition of Stainless Spring Steels	
,	9.3		eels	
		9.3.1	Chemical Composition of Carbon Tool Steels	
		9.3.2	Chemical Composition of High-Speed Tool Steels	
			9.3.2.1 Chemical Composition of Tungsten Type High Speed Tool Steels	
		0.00	9.3.2.2 Chemical Composition of Molybdenum Type High Speed Tool Steels	
		9.3.3	Chemical Composition of Cold Work Tool Steels	
		9.3.4	Chemical Composition of Hot Work Tool Steels	
,	· 4	9.3.5	Chemical Composition of Special Purpose Tool Steels	
,	9.4		g Steels	
,	٠.	9.4.1	Chemical Composition of Bearing Steels	
	9.5		omparable Free-Machining Steels	
	9.6		omparable Spring Steels	
	9.7		omparable Tool Steels	
,	9.8	Non-Co	omparable Bearing Steels	439
۸nı	an a	div 1 _ A	STM Ferrous Metal Standards	441
API	Jen	uix i - A	ISTM 1 errous metal Staridards	441
Apı	oen	dix 2 - A	STM Discontinued Ferrous Metal Standards	457
Apı	oen	dix 3 - J	IS Steel and Related Standards	469
Apı	oen	dix 4 - J	IS Discontinued Steel and Related Standards	475
Apı	oeno	dix 5 - C	EN Current Steel Standards	479
Δnı	nen (dix 6 - C	EN Standards with Superseded Former National Standards	485
			·	
			ormer National Standards Superseded by CEN Standards	
Apı	oen	díx 8 - IS	SO Iron and Steel Product Standards	523
Apı	oen		STM A 941-03 Terminology Relating to Steel, Stainless Steel, lelated Allovs. and Ferroallovs	531

	XVII
Appendix 10 - ASTM E 527–83 (2003) Numbering Metals and Alloys (UNS)	539
Appendix 11 - SI Quick Reference Guide	547
Steel Grade/Name Index	553
UNS Number Index	601
Steel Number Index	609
Specification Designation Index	617

1

INTRODUCTION TO COMPARING WORLD STEEL STANDARDS

Myth and Methodology When Comparing Steel Standards

When comparing steel standards from different national and international standard development organizations (SDOs), there is no such thing as *equivalent* steel standards. At best, one may be able to group *comparable* steel standards together based on some defined set of rules, which has been done in this handbook. For example, ASTM A 516/A 516M Grade 70 is *comparable* to JIS G 3118 symbol SGV 480 and to EN 10028-2 steel name P295GH, based on chemical compositions and mechanical properties. Yet they are not *equivalent* since there are differences in their chemical compositions and mechanical properties. Comparing steel standards is not an exact science and cannot be made into a mathematical equation where two sides of an equation are equal to one another, since there will always be differences between standards.

These differences may be significant to one user, but not significant to another user. Therefore, this handbook uses the term *comparative* to denote similar standards that have been compared to each other. Comparative is a relative word that is inevitably dependent upon the end user's requirements, who is ultimately responsible for selecting the appropriate steel for a specific application.

There are some steel standards that are shared by multiple SDOs. For example, EN ISO 4957 – Tool Steels, is a standard that is shared within the European Committee for Standardization (CEN) and the International Standards Organization (ISO) systems. Consequently, the data are equivalent in both systems, but there is only one standard.

There are also different standards that share the same grades of steel. For example, ASTM A 485 and EN ISO 683-17 share seven identical bearing steel grade chemical compositions, yet the body of each standard is different (that is, grain size, hardenability, microstructure and hardness, inspection, testing, etc.). As a result, these seven bearing steels within these two standards are not equivalent, but are comparable.

Comparative and Closest Match

There is also a difference between *comparative* and *closest match* when evaluating steel standards. While gathering the data for this handbook, it was difficult to decide whether to include data on a technically comparative basis or on a closest match basis as both have their merits and limitations (see 70 % rule in EN 10020 on page 6 for a more detailed discussion).

A technically comparative group of steels can assist the user with making a material selection based on technical merit. However, this may severely limit the number of steels that would be comparable. On the other hand, displaying the closest match data will usually increase the number of comparative steels for the user to consider, but at the risk of widening the technical comparison criteria. Likewise, a strict technical comparison will provide more accurate results, but a closest match comparison will provide more data to assist the user in searching for similar steels.

There are many instances in the handbook where it would be a disservice to the reader not to include the closest match steels, since there would be no comparisons otherwise. Since this broadens the technical comparison criteria, the user is warned that the data herein cannot substitute for education, experience, and sound engineering judgment after evaluating all of the specifications within each comparable standard.

In the end, there are no definitive rules that can be formulated to distinguish between *comparative* steels and *closest match* steels. Consequently, at the editor's discretion, both types of comparisons are used in this handbook. The following is one example of the comparison process, with technically comparative steels and closest match steels used in the table.

Table 1.1 lists the chemical compositions of nine grades of cast steels that are essentially Cr-Ni-Mo alloys, with nominally 0.30 % C. If a strict technical comparison was made based on their chemical composition, none of these alloys would be comparable since they would differ in either their carbon, manganese, chromium, nickel, or molybdenum contents. Try comparing these data yourself.

Table 1.1 List of Chemical Compositions of Cr-Ni-Mo Alloy Cast Steels Before Comparison

Standard	Grade, Class, Type	Steel	UNS	Weight, %, max, Unless Otherwise Specified								
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 958-00	SC 4330			0.28-0.33	0.60-0.90	0.30-0.60	0.035	0.040	0.70-0.90	1.65-2.00	0.20-0.30	
A31W A 930-00	SC 4340			0.38-0.43	0.60-0.90	0.30-0.60	0.035	0.040	0.70-0.90	1.65-2.00	0.20-0.30	
JIS G 5111:1991	SCNCrM 2			0.25-0.35	0.90-1.50	0.30-0.60	0.040	0.040	0.30-0.90	1.60-2.00	0.15-0.35	
	GS-25 CrNiMo 4	1.6515		0.22-0.29	0.60-1.00	0.60	0.020	0.015	0.80-1.20	0.80-1.20	0.20-0.30	
DIN 17205:1992	GS-34 CrNiMo 6	1.6582		0.30-0.37	0.60-1.00	0.60	0.020	0.015	1.40-1.70	1.40-1.70	0.20-0.30	
DIN 17205.1992	GS-30 CrNiMo 8 5	1.6570		0.27-0.34	0.60-1.00	0.60	0.015	0.010	1.10-1.40	1.80-2.10	0.30-0.40	
	GS-33 CrNiMo 7 4 4	1.8740		0.30-0.36	0.50-0.80	0.60	0.015	0.007	0.90-1.20	1.50-1.80	0.35-0.60	
AFNOR NF A 32-053:1992	20 NCD4-M			0.17-0.23	0.80-1.20	0.60	0.025	0.020	0.30-0.50	0.80-1.20	0.40-0.80	
AFNOR NF A 32-054:1994	G30NiCrMo8			0.33	1.00	0.60	0.030	0.020	0.80-1.20	1.70-2.30	0.30-0.60	

Five grades of steel were eventually eliminated from Table 1.1 after technical comparison. This produced Table 1.2, which was then divided into two separate comparative groups based on the differing molybdenum contents above and below 0.30–0.35 % Mo. The thin black line in Table 1.2 is the separator between the two comparative groups.

Table 1.2 List of Chemical Compositions of Cr-Ni-Mo Cast Alloy Steels After Comparison

Standard	Grade, Class, Type	Steel	UNS			Weigh	ıt, %, max,	Unless Oth	nerwise Spe	ecified		
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 958-00	SC 4330			0.28-0.33	0.60-0.90	0.30-0.60	0.035	0.040	0.70-0.90	1.65-2.00	0.20-0.30	
JIS G 5111:1991	SCNCrM 2			0.25-0.35	0.90-1.50	0.30-0.60	0.040	0.040	0.30-0.90	1.60-2.00	0.15-0.35	
DIN 17205:1992	GS-33 CrNiMo 7 4 4	1.8740		0.30-0.36	0.50-0.80	0.60	0.015	0.007	0.90-1.20	1.50-1.80	0.35-0.60	
AFNOR NF A 32-054:1994	G30NiCrMo8			0.33	1.00	0.60	0.030	0.020	0.80-1.20	1.70-2.30	0.30-0.60	

However, if strict technical comparison rules were applied, Grade SCNCrM 2 could be rejected based on its higher manganese content when comparing it to SC 4330. In that case, SC 4330 would be rejected since it would not have a comparative steel (that is, it takes two steels to make a comparison). The same argument could be made when comparing GS-33 CrNiMo 7 4 4 and G30NiCrMo8 in the second group, where the differing nickel contents could be a basis for rejection on a stricter comparison.

A classic closest match example is shown in Table 1.3, where compared to the three other steels in this group, the four grades within EN 10085 are different; and some may argue that, on this basis, it does not belong to this comparative group. However, the Cr-Al-Mo alloys in this group are typically used as nitriding steels, and the EN 10085 steels are the closest match for this group. So excluding them would be a disservice to the user, since they belong to the same application family and its inclusion in this group will direct the user to other similar nitriding alloys.

Table 1.3 Chromium-Molybdenum-Aluminum (Cr-Mo-Al) Steels for Nitriding

Standard	Grade, Class,	Steel	UNS			Weig	jht, %, ı	max, Ur	less Othe	rwise Spe	cified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 355-89 (2000)	A		K24065	0.38-0.43	0.50-0.70	0.15-0.35	0.035	0.040	1.40-180		0.30-0.40	Al 0.95-1.30
JIS G 4202:1979	SACM 645			0.40-0.50	0.60	0.15-0.50	0.030	0.030	1.30-1.70	0.25	0.15-0.30	Al 0.70-1.20, Cu 0.30
	32CrAlMo7-10	1.8505		0.28-0.35	0.40-0.70	0.40	0.025	0.035	1.50-1.80		0.20-0.40	Al 0.80-1.20
EN 10085:2001	34CrAlMo5-10	1.8507		0.30-0.37	0.40-0.70	0.40	0.025	0.035	1.00-1.30		0.15-0.25	Al 0.80-1.20
EN 10085:2001	34CrAlNi7-10	1.8550		0.30-0.37	0.40-0.70	0.40	0.025	0.035	1.50-1.80	0.85-1.15	0.15-0.25	Al 0.80-1.20
	41CrAlMo7-10	1.8509		0.38-0.45	0.40-0.70	0.40	0.025	0.035	1.50-1.80		0.20-0.35	Al 0.80-1.20
ISO 683-10:1987	41 CrAlMo 7 4			0.38-0.45	0.50-0.80	0.50	0.030	0.035	1.50-1.80		0.25-0.40	Al 0.80-1.20

4 Introduction to Comparing World Steel Standards Chapter 1

There are many opportunities to make technical errors that may lead to inappropriate steel comparisons. For example, when comparing stainless steels there are many technical decisions to make since it is not common to find identical chemical compositions within standards from different countries. Table 1.4 shows a list of comparative Cr-Ni-Mo wrought austenitic stainless steels from the USA, Japan, and European Union. Note the differences in the Cr, Ni, and Mo contents among all the standards and the N limit in the EN standard. These differences will affect the corrosion resistance performance in many applications, such that the user must be very careful when selecting a comparative steel based solely on data in this handbook.

Table 1.4 List of Comparative Cr-Ni-Mo Wrought Austenitic Stainless Steels

Standard Designation	Grade, Class, Type Symbol or Name	Steel Number	UNS Number	Weight, %, max, Unless Otherwise Specified								
				С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 276-03	316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 4303:1998	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
JIS G 4318:1998	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
EN 10088-3:1995	X2CrNiMo17-12-2	1.4404		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
	X2CrNiMo17-12-3	1.4432		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
	X2CrNiMo18-14-3	1.4435		0.030	2.00	1.00	0.045	0.030	17.00-19.00	12.00-15.00	2.50-3.00	N 0.11

In summary, if strict technical comparison is made to this type of data, no relationships or no associations between the various grades of steel would be established, which would serve no purpose. By widening the technical comparison criteria to find the closest match steels, the user must understand that these steels are not equivalent and cannot be indiscriminately substituted without first reviewing the complete current standards and securing competent technical advice prior to any decision-making.

To find a balance for comparison of steels by product form, use (application), mechanical properties, chemical compositions, related manufacturing processes (including heat treatment), etc., a methodology had to be put in place and rules had to be established. However, as much as methodology and rules were essential in preparing this handbook, there were many instances where they would not cover every variable and circumstance. Therefore, difficult comparison decisions as those described previously had to be made. There were literally hundreds, if not more than a thousand, such decisions made in this handbook. In these cases, the closest match comparison decisions were made at the discretion of the editor.

Organization

Two of the main variables in selecting a specific grade of steel are its intended application (use) and product form, which usually narrows the selection to a family of steels. Therefore, the remaining data chapters in this handbook were organized by product form and use, as follows:

Chapter No.	<u>Title</u>
2.	Carbon and Alloy Steels for General Use
3.	Structural Steel Plates
4.	Pressure Vessel Steel Plates
5.	Steel Tubes and Pipes
6.	Steel Forgings
7.	Steel Castings
8.	Wrought Stainless Steels
9.	Steels for Special Use

Although the above list at first glance looks rather straightforward, there were difficult decisions regarding the steel comparisons within each chapter. For example, ASTM has 9 definitions for *pipe* and 22 definitions for *tube*, depending on the standard's subject matter and application (see ASTM Dictionary of Engineering Science & Technology, 9th edition). In contrast, ISO 2604, Steel Products for Pressure Purposes - Quality Requirements - Part II: Wrought Seamless Tubes, notes that: "The word *tube* is synonymous with *pipe*."

Each standard is typically listed only in one chapter, but there are exceptions. For example, ASTM A 240/A 240M-04 on Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications, due to its dual role for pressure vessel and general applications (i.e., Chapter 4—Pressure Vessel Steel Plates and Chapter 8—Wrought Stainless Steels).

Definitions of Steel Terms

ASTM and CEN have established two separate standards for defining steel terms:

ASTM A 941-03 Terminology Relating to Steel, Stainless Steel, Related Alloys, and Ferroalloys (see Appendix 9) (defines the terms: carbon steel, alloy steel, low-alloy steel, and stainless steel);

EN 10020:2000 Definition and Classification of Grades of Steel;(defines the terms: non-alloy steels, other alloy steels (which include alloy quality steels and alloy special steels), and stainless steels).

Note that these two standards, from the USA and EU, differ in the terms used to describe the different types of steel. The user of comparative steel standards data must take into account that each national SDO has their own set of terms and definitions for steels and related products and, in some cases, may have multiple definitions. For example, three different definitions for carbon steel can be found in ASTM standards A 941-03, A 902-03, and F 1789-04.

A summary of the chemical element limits for ASTM A 941-03 alloy steel and EN 10020:2000 non-alloy steel is shown in Table 1.5. Although the limits seem to be the same, it is important to note the 70% rule in EN 10020, which states:

3.1.2 Where for elements other than manganese a maximum value only is specified in the product standard or specification for the ladle analysis, a value of 70 % of this maximum value shall be taken for classification as set out in Tables 1 and 2. For manganese see note a) of Table 1.

In some cases, this 70 % rule resulted in several steels being non-comparable. For example, EN 10028-3:2003, Flat Products Made of Steels for Pressure Purposes - Part 3: Weldable Fine Grain Steels, Normalized, contains steels with a nickel content of 0.50 % maximum (i.e., there is no minimum nickel requirement). Using the 70 % rule, this would define these steels to contain 0.35 % Ni, which is over the 0.30 % maximum limit for non-alloy steels (carbon steels), thereby making them alloy steels and becoming non-comparable with non-alloy steels.

ASTM A 941-03 and EN 10020:2000 share the same definition for stainless steel, as follows:

stainless steel—a steel that conforms to a specification that requires, by mass percent, a minimum chromium content of 10.5 or more, and a maximum carbon content of less than 1.20.

In this handbook, steels have been divided into three main categories:

- 1. Carbon Steels (Non-Alloy Steels)
- 2. Alloy Steels
- 3. Stainless Steels

ASTM A 941-03 and EN 10020:2000 were used as guidelines in developing these categories. Where practical, these steel categories were further divided into subcategories based on their product form, intended application, service requirement, or other similar criteria.

Symbol	Name	EN 10020:2000 ^b	ASTM A 941-03
Al	Aluminum	0.30	0.30
В	Boron	0.0008	0.0008
Bi	Bismuth	0.10	
Со	Cobalt	0.30	0.30
Cr	Chromium	0.30	0.30
Cu	Copper	0.40	0.40
La	Lanthanides	0.10	
Mn	Manganese	1.65 ^b	1.65
Мо	Molybdenum	0.08	0.08
Nb	Niobium	0.06	0.06
Ni	Nickel	0.30	0.30
Pb	Lead	0.40	0.40
Se	Selenium	0.10	
Si	Silicon	0.60	0.60
Те	Tellurium	0.10	
Ti	Titanium	0.05	0.05
V	Vanadium	0.10	0.10
W	Tungsten	0.30	0.30
Zr	Zirconium	0.05	0.05
	Other (except C, P, S, N)	0.10	0.10

Table 1.5 Limits for EN 10020:2000 and ASTM A 941-03 Between Carbon Steels/Non Alloy Steel and Alloy Steel^a (% by mass)

Cautionary Note

Many standard specifications include cautionary paragraphs that warn users about their responsibilities (e.g., see paragraph 1.5 from ASTM A 53/A 53M-02, shown below). Accordingly, it is the user's responsibility when comparing steel standards to perform an engineering review of each standard to ensure that it is suitable for their intended application.

1.5 The following precautionary caveat pertains only to the test method portion, Sections 9, 10, 11, 15, 16, and 17 of this specification: This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

^a Alloy steel when equal to or greater than the limit.

^b Where manganese is specified only as a maximum the limit value is 1.80 % and the 70 % rule does not apply (see 3.1.2 of EN 10020:2000).

Questions Regarding the Rules of Comparison

When comparing two or more steel standards, the following questions can be asked:

Should mechanical properties or chemical composition be the main criteria? If mechanical properties are compared, which property should be the first criteria for comparison, that is, yield strength, tensile strength, elongation, impact strength, hardness, etc.? Once having selected a primary criterion, say tensile strength, should there be a secondary criterion for ranking the comparative steels within this group, for example, yield strength, hardness, etc.? When mechanical properties or chemical compositions vary with section thickness for a given steel grade, which section thickness data should be selected as the criteria for comparison? When two steels have the same minimum tensile strength values, but have different yield strength values, are they no longer similar?

Should comparisons be based on the data's minimum values, maximum values, or average values of their min/max ranges? Should alloy steels and stainless steels be compared on their mechanical properties when they are generally selected for use based on their alloying elements' abilities to provide satisfactory service in their intended applications?

Is it reasonable to compare steels based only on their chemical compositions, regardless of their product form? That is, should forging steels be compared to steel plates or tubes because they have similar chemical compositions and is this type of comparative data useful in engineering practice?

Non-Comparable Steels

Not all steels have comparative counterparts. Knowing that a steel is non-comparable can be just as important as knowing that there are comparative steels. Otherwise, valuable time could be wasted searching for something that does not exist. All steel grades within the listed standards in this handbook are either designated as comparable or non-comparable to assist the user in finding data. Non-comparable steels can be found at the end of each chapter.

Criteria for Comparing Steels

The two major criteria for comparing steels in this type of handbook are mechanical properties and chemical compositions. For each given standard steel grade, there is typically only one chemical composition, which makes it ideal as a comparison criterion. However, there are several mechanical properties that can be used to compare standard steel grades and, to be consistent throughout a handbook of this type, only one property can be chosen. The decision was to use a steel's tensile strength as the second comparison criterion.

Having settled on chemical composition and tensile strength as the two main comparison criteria, the next step was to decide when to apply one or the other, or both. Since carbon steels are typically selected based on mechanical properties, it was decided that tensile strength would be the first

criterion used for comparing carbon steels. Likewise, since alloys steels and stainless steels are generally selected based on their chemistry, it was decided that chemical composition would be used to compare them.

An exception to the above methodology is for the structural steels data in Chapter 3, where the tensile strength was used as the main comparison criterion for carbon and alloy steels. This exception was made because structural steels are generally selected based on their mechanical properties. Also in this same chapter, high-strength low-alloy steels are treated as a subcategory to alloy steels, although ASTM A 941 defines them separately.

Since there was insufficient space on a page to place both the chemical composition and mechanical properties tables, they were split into two separate tables. To assist the user in keeping track of the comparison criteria used for a given steel, each table within a chapter was sequentially numbered and appended with the letter A or B. Table numbers ending in the letter A designate that it was the main criterion used for comparison, whereas table numbers ending with the letter B were "mirrored" from the A tables.

In this manner, the user must first consider the data in the A table, then see how well the data in the B table match the steels which are being compared.

This is not a foolproof methodology of comparison. For example, ASTM A 958 Grade SC 4330 has one chemical composition, but has 13 different strength classes based on heat treatment (see Chapter 7). So just because two steel grades have comparative chemical compositions does not mean that they are comparable in mechanical properties, and vice versa. Using data found in this handbook is only one step in finding suitable comparable steel for the intended application.

With this basic methodology in place, the following is a list of the comparison rules that were established to produce this handbook.

List of Comparison Rules

- 1. The first criterion of order for carbon (non-alloy) steels is based on tensile strength, followed by yield strength; that is, if two steels have the same tensile strength, then they are placed in ascending ordered by yield strength, and if yield strength is not required, it is placed at the top of the order.
- 2. Typically, comparative groups are made for every 50 MPa (50 N/mm² or 7.25 ksi) in tensile strength (that is, a black line divides comparative groups every 50 MPa (50 N/mm² or 7.25 ksi)). When an abundance of data is available, this limit may be reduced to improve the comparison accuracy.
- 3. Mechanical property subcategories, such as steels with impact testing below -20 $^{\circ}$ C (-4 $^{\circ}$ F), are used to further narrow the comparison process.
- 4. If a carbon steel's tensile strength varies with section thickness, the tensile strength of the lowest section thickness will be used as the governing comparison factor. There is no technical reason for choosing the lowest section thickness; it is just that one had to be chosen.
- 5. If a carbon steel standard does not contain mechanical properties, such as those found in Chapter 2 on Carbon and Alloy Steels for General Use, then the steels will be compared based on their carbon content.
- 6. The major criterion for alloy steel and stainless steel comparisons is chemical composition. Once these steels are placed in a comparative group by chemical composition, they are then arranged in ascending order within these groups by their tensile strength. Where possible, subcategories of alloy and stainless steel groups are made to further narrow the comparison process.
- 7. Chemical compositions listed are the heat analysis requirements in the standards (also called ladle or cast analysis). Product analyses are not listed.
- 8. The chemical composition and mechanical properties data for the same steel grades are not listed on the same page due to space limitations. Consequently, as a means of keeping the data consistent between these two sets of tables, each table is numbered, and each table number ends with either the letter A or B.
- 9. Each set of steel data in the tables is divided by two types of horizontal lines: black and grey. Black lines separate groups of steels that are more closely comparable to each other, whereas grey lines separate steel data within a comparative group. This does not mean that steels outside of these groups cannot be compared, since these horizontal lines are dependent upon all of the comparison rules in this list and can be subjective at times. Caution: do not confuse the thinner dividing black line within a table with the thicker black rule that borders the table. To assist in this regard, the pages were formatted to keep comparative groups together as much as practicable. However, when a group of comparative steels appears on more than one page, a note is placed at the bottom of the page to indicate that the comparative group continues on the following page, that is, "NOTE: this section continues on the next page."
- 10. Steel data in standards are not always mandatory. Some data are listed as typical values or informative values, or are found in supplementary requirements. This type of data is still very useful, and has been included in this handbook whenever possible. This type of data is identified with an explanatory note that appears in the list of standards at the beginning of the related chapter.

- 11. Some standards included multiple requirements for impact testing, for example, differing test temperatures or requirements for subsize specimens.
- 12. Where space permitted, as much data as possible were included. However, there are occasions when the phrase "see standard for impact test data" was used to indicate that more data could be found in the standard.
- 13. The phrase "see standard for impact test data" was also used when the standard did not specify a test temperature but did specify an absorbed energy value.
- 14. Impact testing values listed in the tables are typically for full-size specimens and for the minimum average result at the testing temperature, but do not include the minimum individual test piece requirement, if any.
- 15. For the purpose of this handbook, phrases found in standards like: "may be applied if necessary" or "may be applied by agreement between the purchaser and supplier" or "the manufacturer may find it necessary to" or "when specified" or " may be added if necessary" are not a part of the comparison process.
- 16. Data from footnotes in the chemical composition and mechanical properties tables of steel standards were considered during the comparison process, but were not always reported in the handbook due to lack of space in the tables or because they represented technical issues that were too complex to be represented in a tabular format. In these cases, the note "see standard" was used.
- 17. The same heat treatment terms used in each standard are listed them at the beginning of each chapter. Abbreviations in the tables were made based on the terms used in the standards. A concerted effort was made to make the abbreviations consistent from chapter to chapter, although there are exceptions, because each heat treatment abbreviation must be referred to in the list of heat treatment terms at the beginning of each chapter. There are many instances when the heat treatment requirements within a standard became very cumbersome to include in a small cell within a table. Consequently, the phrase "see standard" is used to direct the user to the standard to read all of the heat treatment details involved.
- 18. A determined effort was made to enter the data in this handbook in a manner identical to that listed in the related standard, including the use of Nb (niobium) or Cb (columbium). It should be noted that even within the same SDO, data were not always entered in the same manner from standard to standard; for example, TP304 versus TP 304, where a space between the letter P and the number 3 is listed in the data. This becomes significant when using the search engine on the accompanying e-book's CD-ROM.
- 19. When a steel grade was found to be non-comparable, it was included at the end of the chapter in the non-comparable list. Therefore, if a particular steel was found to be unique and did not have a comparable steel, the user would not have to search any further.

Brief Introduction to Steel Standards and Designation Systems

In the world of standardization, metals were at the forefront at the turn of the twentieth century. In 1895, the French government assigned a commission to formulate standard methods of testing materials of construction. Later that year, the European member countries of the International Association for Testing Materials (IATM) held their first conference in Zurich and the standardization of metals began.

By reviewing some examples of the more prominent metals designation systems, a direction is offered to assist those who use metal standards as a part of their work or study. This section is not all inclusive. The amount of information on this topic could easily make up a complete book.

ASTM Designation System

ASTM's designation system for metals consists of a letter (A for ferrous materials) followed by an arbitrary sequentially assigned number. These designations often apply to specific products, for example A 548 is applicable to cold-heading quality carbon steel wire for tapping or sheet metal screws. Metric ASTM standards have a suffix letter M.

Examples of the ASTM ferrous metal designation system, describing its use of specification numbers and letters, are as follows.

ASTM A 582/A 582M-95b (2000), Grade 303Se - Free-Machining Stainless Steel Bars:

- A describes a ferrous metal, but does not subclassify it as cast iron, carbon steel, alloy steel, tool steel, or stainless steel.
- 582 is a sequential number without any relationship to the metal's properties.
- M indicates that the standard A 582M is written in rationalized SI units (the "M" comes from the word "Metric"), hence together A 582/A 582M includes both inchpound and SI units.
- 95 indicates the year of adoption or last revision and a letter *b* following the year indicates the third revision of the standard in 1995.
- (2000), a number in parentheses, indicates the year of last reapproval.
- Grade 303Se indicates the grade of the steel, and in this case, it has a Se (selenium) addition.

In the steel industry, the terms *Grade*, *Type*, and *Class* are generally defined as follows: *Grade* is used to describe chemical composition; *Type* is used to define deoxidation practice; and *Class* is used to indicate other characteristics such as strength level or surface finish. However, within ASTM standards, these terms were adapted for use to identify a particular metal within a metal standard and are used without any "strict" definition, but essentially mean the same thing, although some loose rules do exist, as follows.

ASTM A 106-02a Grade A, Grade B, Grade C – Seamless Carbon Steel Pipe for High-Temperature Service:

- Typically an increase in alphabet (such as the letters A, B, C) results in higher tensile or yield strength steels, and if it is an unalloyed carbon steel, an increase in carbon content.
- In this case:

```
Grade A: 0.25 % C (max.), 48 ksi tensile strength (min.); Grade B: 0.30 % C (min.), 60 ksi tensile strength (min.); and Grade C: 0.35 % C, 70 ksi tensile strength (min.).
```

ASTM A 276-03, Type 304, 316, 410 – Stainless and Heat-Resisting Steel Bars and Shapes:

• Types 304, 316, 410 and others are based on the SAE designation system for stainless steels (see SAE and former AISI description that follows).

Another use of ASTM grade designators is found in pipe, tube, and forging products, where the first letter "P" refers to pipe, "T" refers to tube, "TP" may refer to tube or pipe, and "F" refers to forging. Examples are found in the following ASTM specifications:

- ASTM A 335/A 335M-03, Grade P22; Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service.
- ASTM A 213/A 213M-03a, Grade T22; Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes.
- ASTM A 312/A 312M-03, Grade TP304; Seamless and Welded Austenitic Stainless Steel Pipes.
- ASTM A 336/A 336M-03a, Class F22 Steel Forgings, Alloy, for Pressure and High-Temperature Parts.

ASTM Referenced Standards and Supplementary Requirements

ASTM standards contain a "Referenced Documents" section that lists other ASTM standards which are referenced in the text that either become a part of the original standard or its supplementary requirements. Supplementary requirements are listed at the end of the ASTM standards and do not apply unless specified in the purchase order, that is, they are optional.

SAE Designation System and Related AISI Designation System

Carbon and Alloy Steels

For many years, certain grades of carbon and alloy steels have been designated by a four-digit AISI/SAE numbering system that identified the grades according to standard chemical compositions. Since the American Iron and Steel Institute (AISI) does not write material specifications, the relationship between AISI and grade designations has been discontinued. Beginning with the 1995 edition of the Iron and Steel Society (ISS) Strip Steel Manual, the four-digit designations are referred to solely as SAE designations.

The SAE system uses a basic four-digit system to designate the chemical composition of carbon and alloy steels. Throughout the system, the last two digits give the carbon content in hundredths of a percent. Carbon steels are designated 10XX. For example, a carbon steel containing 0.45 % carbon is designated 1045 in this system.

Resulfurized carbon steels are designated within the series 11XX, resulfurized and rephosphorized carbon steels 12XX and steels having manganese contents between 0.9 and 1.5 %, but no other alloying elements are designated 15XX. Composition ranges for manganese and silicon and maximum percentages for sulfur and phosphorus are also specified.

For alloy steels, the first two digits of the SAE system describe the major alloying elements present in the material, the first digit giving the alloy group. For example the 43XX series steels contain 1.65-2.00~% Ni, 0.50-0.80~% Cr and 0.20-0.30~% Mo, along with composition ranges for manganese and silicon and maximums for sulfur and phosphorus.

Additional letters added between the second and third digits include "B" when boron is added (between 0.0005 and 0.003 %) for enhanced hardenability, and "L" when lead is added (between 0.15 and 0.35 %) for enhanced machinability. The prefix "M" is used to designate merchant quality steel (the least restrictive quality descriptor for hot-rolled steel bars used in noncritical parts of structures and machinery). The prefix "E" (electric-furnace steel) and the suffix "H" (hardenability requirements) are mainly applicable to alloy steels. The full series of classification groups is shown in Table 1.6.

Table 1.6 Types and Identifying Elements in Standard SAE Carbon and Alloy Steels

<u>Carbon Steels</u>	<u>Description</u>
10XX	non-resulfurized, 1.00 manganese maximum
11XX	resulfurized
12XX	rephosphorized and resulfurized
15XX	non-resulfurized, over 1.00 manganese maximum
Alloy Steels	<u>Description</u>
13XX	1.75 manganese
40XX	0.20 or 0.25 molybdenum or 0.25 molybdenum and 0.042 sulfur
41XX	0.50, 0.80, or 0.95 chromium and 0.12, 0.20, or 0.30 molybdenum
43XX	1.83 nickel, 0.50 to 0.80 chromium, and 0.25 molybdenum
46XX	0.85 or 1.83 nickel and 0.20 or 0.25 molybdenum
47XX	1.05 nickel, 0.45 chromium, 0.20 or 0.35 molybdenum
48XX	3.50 nickel and 0.25 molybdenum
51XX	0.80, 0.88, 0.93, 0.95, or 1.00 chromium
51XXX	1.03 chromium
52XXX	1.45 chromium
61XX	0.60 or 0.95 chromium and 0.13 or 0.15 vanadium minimum
86XX	0.55 nickel, 0.50 chromium, and 0.20 molybdenum
87XX	0.55 nickel, 0.50 chromium, and 0.25 molybdenum
88XX	0.55 nickel, 0.50 chromium, and 0.35 molybdenum
92XX	2.00 silicon or 1.40 silicon and 0.70 chromium
50BXX	0.28 or 0.50 chromium
51BXX	0.80 chromium
81BXX	0.30 nickel, 0.45 chromium, and 0.12 molybdenum
94BXX	0.45 nickel, 0.40 chromium, and 0.12 molybdenum

UNS Designation System

The Unified Numbering System (UNS) is an alphanumeric designation system consisting of a letter followed by five numbers. This system represents only the chemical composition for an individual metal or alloy and is not a metal standard or specification. For the most part, existing systems such as the SAE designations, were incorporated into the UNS so that some familiarity was given to the system where possible.

For example, the UNS prefix letter for carbon and alloy steels is "G," and the first four digits are the SAE designation, for example, SAE 1040 is UNS G10400. The intermediate letters "B" and "L" of the SAE system are replaced by making the fifth digit of the UNS designation 1 and 4, respectively, while the prefix letter "E" for electric furnace steels is designated in UNS system by making the fifth digit "6." The SAE steels, which have a hardenability requirement indicated by the suffix letter "H," are designated by the Hxxxxx series in the UNS system. Carbon and alloy steels not referred to in the SAE system are categorized under the prefix letter "K."

Where possible, the first letter in the system denotes the metal group, for instance "S" designates stainless steels. Of the five digits of the UNS designation for stainless steels, the first three are the SAE alloy classification, for example, S304XX. The final two digits are equivalent to the various modifications represented by suffix letters in the SAE system as given in the list of suffixes in Table 1.6. The UNS designations for ferrous metals and alloys are described in Table 1.7.

Table 1.7 UNS Designations for Ferrous Metals and Alloys

UNS Descriptor	<u>Ferrous Metals</u>
Dxxxxx	Specified mechanical properties steels
Fxxxxx	Cast irons
Gxxxxx	SAE and Former AISI carbon and alloy steels (except tool steels)
Hxxxxx	AISI H-steels
Jxxxxx	Cast steels
Kxxxxx	Miscellaneous steels and ferrous alloys
Sxxxxx	Heat and corrosion-resistant (stainless) steels
Txxxxx	Tool steels
UNS Descriptor	Welding Filler Metals
Wxxxxx	Welding filler metals, covered and tubular electrodes classified
	by weld deposit composition

Canadian Standards Association (CSA)

The Canadian Standards Association (CSA) has established metal standards for structural steels (CSA G40.20/40.21), pipeline steels (CSA Z245.1), corrugated steel pipe (G401), wire products (CSA G4, G12, G30.x, G279.2, G387), sprayed metal coatings (G189), and welding consumables (CSA W48.x).

Most CSA material standards use SI units, although some are available in both SI and Imperial units (for example, CSA G40.20/G40.21-04). When a CSA standard designation is followed by the letter "M," it uses SI units, and if the letter "M" is not present, it may use both units or use only Imperial units. The type of measurement units adopted in CSA standards are specific industry driven, with some industries moving faster towards the exclusive use of SI units than others, and thus the reason for these differences.

As far as practicable, rationalization with relevant International Standards Organization (ISO) standards has been achieved in CSA G4, Steel Wire Rope for General Purpose and for Mine Hoisting and for Mine Haulage. Similarly, the 2002 edition of CSA Z245.1, Steel Line Pipe, references requirements for ISO 1027:1993 on radiographic image indicators for non-destructive testing: principles and identification, as well as ISO 5579:1985 on nondestructive testing – radiographic examination of metallic materials by X- and gamma rays – basic rules.

Introduction to European (EN) Standard Steel Designation System

The Comité Européen de Normalisation (CEN) (European Committee for Standardization) was founded in 1961 by the national standards bodies in the European Economic Community and EFTA countries. Now CEN is contributing to the objectives of the European Union and European Economic Area with voluntary technical standards. CEN is a system of formal processes to produce standards, shared principally between:

- 28 national members and the representative expertise they assemble from each country. These members vote for and implement European Standards (EN);
- 8 associate members and two counsellors;
- The CEN Management Centre, Brussels.

It works closely with the European Committee for Electrotechnical Standardization (CENELEC), the European Telecommunications Standards Institute (ETSI), and the International Organization for Standardization (ISO). It also has close liaisons with European trade and professional organizations.

The principal task of CEN is to prepare and issue European standards (EN), defined as a set of technical specifications established and approved in collaboration with the parties concerned in the various member countries of CEN. They are established on the principle of consensus and adopted by the votes of weighted majority. Adopted standards must be implemented in their entirety as national standards by each member country, regardless of the way in which the national member voted, and any conflicting national standards must be withdrawn.

The identification of European standards in each member country begins with the reference letters of the country's national standards body, for example, BS for BSI in the United Kingdom, DIN for DIN in Germany, NF for AFNOR in France, etc. It is followed by the initials EN and a sequential number of up to five digits. For example, BS EN 10025, DIN EN 10025, or NF EN 10025 are all the same EN standard, which are available in English, French, and German.

An EN standard may contain one document or it may be made up of several parts. For example, EN 10028 Parts 1 through 8, where each part specifies a particular characteristic of the steel product, and may not include the word *part* in the designation, but rather replace it with a hyphen, e.g., EN 10028-1, meaning Part 1. The prefix "pr" preceding the EN designation identifies the document as a draft standard that has not yet been approved, e.g., prEN 10088-1.

EN 10027 Standard Designation System for Steels

The CEN designation system for steels is standardized in EN 10027, which is published in two parts:

- Part 1 Steel Names
- Part 2 Steel Numbers

The steel name is a combination of letters and numbers as described by EN 10027-1. Within this system, steel names are classified into two groups. The system is similar in some respects to, but not identical with, that outlined in an ISO technical report (ISO TR 4949:1989 (E) "Steel names based on letter symbols").

Steel Names

Steel Names Group 1 within EN 10027-1 refers to steels that are designated according to their application and mechanical or physical properties. These have names that are comprised of one or more letters, related to the application, followed by a number related to properties. For example, the name for structural steels begins with the letter S, line pipe steels begin with the letter L, rail steels begin with the letter R, and steels for pressure purposes begin with the letter P, such as EN 10028-3 Steel Name P275N.

Steel Names Group 2 is used for steels that are designated according to their chemical composition, and are further divided into four subgroups depending on alloy content. Examples of these Group 2 steel names are:

- EN 10222-2 Steel Name 13CrMo4-5
- EN 10250-4 Steel Name X2CrNi18-9

Steel Numbers

EN 10027-2 describes the system used for assigning steel numbers, which are complementary to the steel names described above. The number consists of a fixed number of digits and is hence more suitable than the name for data processing purposes. The number is in the form 1.XXXX, where the 1. refers to steel. The first two digits following the "1" represent the steel group number. Examples of steel numbers are as follows:

- EN 10222-2 Steel Name 13CrMo4-5, Steel Number 1.7335
- EN 10250-4 Steel Name X2CrNi18-9, Steel Number 1.4307

Former National Standards Superseded by CEN Standards

An increasing number of national European and UK standards are being withdrawn and superseded by EN standards. This transition, from old to new standards, has made it increasingly more difficult to compare the superseded national standards with current standards from other nations outside of Europe and the UK, let alone comparing them to the new EN standards. Appendix 6 lists the EN standards with the superseded national standards and Appendix 7 lists the national standards that were superseded by the current EN standards (that is, the reverse of Appendix 6).

For example, if you are looking up a former national standard such as DIN 17441, Appendix 7 shows that it has been superseded by EN 10028-7:2000. Appendix 6 shows this information in reverse order, so that no matter which standard designation you are interested in, that is, the superseded or current standard, you can find it in this handbook.

Superseded national standards may be replaced by more than one new EN standard and some may have been partially replaced. So, a superseded national standard could be replaced by 2, 3, 4, or more new EN standards, or it may be only partially replaced by these new EN standards. These details can be found in Appendixes 6 and 7.

Indexes in this Handbook

One of the easiest ways of using this handbook is to refer to one of the four indexes. If a user is looking for a comparable steel, then the information can be found in at least one of the indexes. The indexes are built around the steel designation systems described previously, namely:

- Steel Grade/Name Index
- UNS Number Index
- Steel Number Index
- Specification Designation

Chapter

2

CARBON AND ALLOY STEELS FOR GENERAL USE

22 Carbon and Alloy Steels for General Use – List of Standards Chapter 2

ASTM Standards

ASTM A 29/A 29M-03	Steel Bars, Carbon and Alloy, Hot-Wrought and Cold-Finished
ASTM A 108-03	Steel Bars, Carbon and Alloy, Cold-Finished
ASTM A 576-90b (2000)	Steel Bars, Carbon, Hot-Wrought, Special Quality
ASTM A 322-91 (2001)	Steel Bars, Alloy, Standard Grades
ASTM A 355-89 (2000)	Standard Specification for Steel Bars, Alloys, for Nitriding

SAE Standards

SAE J403 NOV01	Chemical Compositions of SAE Carbon Steels (Hot Rolled and Cold Finished Bars Only)
SAE J404 JUN00	Chemical Compositions of SAE Alloy Steels (Hot Rolled and Cold Finished Bars Only)

JIS Standards

JIS G 4051:1979	Carbon Steels for Machine Structural Use
JIS G 4053:2003	Low-alloyed Steels for Machine Structural Use
JIS G 4103:1979	Nickel Chromium Molybdenum Steels
JIS G 4105:1979	Chromium Molybdenum Steels
JIS G 4202:1979	Aluminium Chromium Molybdenum Steels

CEN Standards

EN 10016-2:1995	Non-Alloy Steel Rod for Drawing and/or Cold Rolling – Part 2: Specific Requirements for General Purposes Rod
EN 10016-4:1995	Non-Alloy Steel Rod for Drawing and/or Cold Rolling – Part 4: Specific Requirements for Rod for Special Applications
EN 10083-1:1991 A2:1999	Quenched and Tempered Steels – Technical Delivery Conditions for Special Steels (Amendment A2:1999)
EN 10083-2:1991 A1:1998	Quenched and Tempered Steels – Technical Delivery Conditions for Unalloyed Quality Steels (Amendment A1:1998)
EN 10083-3:1995	Quenched and Tempered Steels – Technical Delivery Conditions for Boron Steels
EN 10084:1998 A1:1998	Case Hardening Steels – Technical Delivery Conditions
EN 10085:2001	Nitriding Steels

ISO Standards

ISO 683-1:1987	Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels – Part 1: Direct-Hardening Unalloyed and Low-Alloyed Wrought Steel in Form of Different Black Products
ISO 683-10:1987	Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels – Part 10: Wrought Nitriding Steels
ISO 683-11:1987	Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels – Part 11: Wrought Case-Hardening Steels

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1005		G10050	0.06	0.35		0.040	0.050				
SAE J403 NOV01	1005		G10050	0.06	0.35		0.030	0.050				
EN 10016-2:1995	C4D	1.0300		0.06	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C3D2	1.1110		0.05	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1006		G10060	0.08	0.25-0.40		0.040	0.050				
SAE J403 NOV01	1006		G10060	0.08	0.25-0.40		0.030	0.050				
EN 10016-2:1995	C7D	1.0313		0.05-0.09	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C5D2	1.1111		0.07	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1008		G10080	0.10	0.30-0.50		0.040	0.050				
ASTM A 108-03	1008		G10080	0.10	0.30-0.50		0.040	0.050				
ASTM A 576-90b (2000)	1008		G10080	0.10	0.30-0.50		0.040	0.050				
SAE J403 NOV01	1008		G10080	0.10	0.30-0.50		0.030	0.050				
EN 10016-2:1995	C9D	1.0304		0.10	0.60	0.30	0.035	0.035	0.25	0.25	0.08	Cu 0.30
EN 10016-4:1995	C8D2	1.1113		0.06-0.10	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1010		G10100	0.08-0.13	0.30-0.60		0.040	0.050				
ASTM A 108-03	1010		G10100	0.08-0.13	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1010		G10100	0.08-0.13	0.30-0.60		0.040	0.050				
SAE J403 NOV01	1010		G10100	0.08-0.13	0.30-0.60		0.030	0.050				
JIS G 4051:1979	S 10 C			0.08-0.13	0.30-0.60	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
010 0 4001.1070	S 09 CK			0.07-0.12	0.30-0.60	0.10-0.35	0.025	0.025	0.20	0.20		Cu 0.25; Ni+Cr 0.30
EN 10016-2:1995	C10D	1.0310		0.08-0.13	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C10D2	1.1114		0.08-0.12	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
EN 10084:1998	C10E	1.1121		0.07-0.13	0.30-0.60	0.40	0.035	≤ 0.035				
LIV 10004.1990	C10R	1.1207		0.07-0.13	0.30-0.60	0.40	0.035	0.020-0.040				
ISO 683-11:1987	C 10			0.07-0.13	0.30-0.60	0.15-0.40	0.035	0.035				
ASTM A 29/A 29M-03	1012		G10120	0.10-0.15	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1012		G10120	0.10-0.15	0.30-0.60		0.040	0.050				
SAE J403 NOV01	1012		G10120	0.10-0.15	0.30-0.60		0.030	0.050				
JIS G 4051:1979	S 12 C			0.10-0.15	0.30-0.60	0.15-0.35	0.030	0.035	.20	.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C12D	1.0311		0.10-0.15	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C12D2	1.1124		0.10-0.14	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1015		G10150	0.13-0.18	0.30-0.60		0.040	0.050				
A3 1 W A 29/A 29 W - 03	1016		G10160	0.13-0.18	0.60-0.90		0.040	0.050				
ASTM A 108-03	1015		G10150	0.13-0.18	0.30-0.60		0.040	0.050				
ASTIVI A 100-03	1016		G10160	0.13-0.18	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1015		G10150	0.13-0.18	0.30-0.60		0.040	0.050				
ASTINIA 576-900 (2000)	1016		G10160	0.13-0.18	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1015		G10150	0.13-0.18	0.30-0.60		0.030	0.050				
SAE J403 NOVUT	1016		G10160	0.13-0.18	0.60-0.90		0.030	0.050				
UC O 4054.4070	S 15 C			0.13-0.18	0.30-0.60	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
JIS G 4051:1979	S 15 CK			0.13-0.18	0.30-0.60	0.15-0.35	0.025	0.025	0.20	0.20		Cu 0.25; Ni+Cr 0.30
EN 10016-2:1995	C15D	1.0413		0.12-0.17	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C15D2	1.1126		0.13-0.17	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
	C15E	1.1141		0.12-0.18	0.30-0.60	0.40	0.035	0.035				
EN 400044000	C15R	1.1140		0.12-0.18	0.30-0.60	0.40	0.035	0.020-0.040				
EN 10084:1998	C16E	1.1148		0.12-0.18	0.60-0.90	0.40	0.035	0.035				
	C16R	1.1208		0.12-0.18	0.60-0.90	0.40	0.035	0.020-0.040				
	C 15 E4			0.12-0.18	0.30-0.60	0.15-0.40	0.035	0.035				
100 000 11.1007	C 15 M2			0.12-0.18	0.30-0.60	0.15-0.40	0.035	0.020-0.040				
ISO 683-11:1987	C 16 E4			0.12-0.18	0.60-0.90	0.15-0.40	0.035	0.035				
	C 16 M2			0.12-0.18	0.60-0.90	0.15-0.40	0.035	0.020-0.040				
	1017		G10170	0.15-0.20	0.30-0.60		0.040	0.050				
ASTM A 29/A 29M-03	1018		G10180	0.15-0.20	0.60-0.90		0.040	0.050				
	1019		G10190	0.15-0.20	0.70-1.00		0.040	0.050				
ASTM A 108-03	1018		G10180	0.15-0.20	0.60-0.90		0.040	0.050				
	1017		G10170	0.15-0.20	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1018		G10180	0.15-0.20	0.60-0.90		0.040	0.050				
	1019		G10190	0.15-0.20	0.70-1.00		0.040	0.050				
SAE J403 NOV01	1017		G10170	0.15-0.20	0.30-0.60		0.030	0.050				
SAE J403 NOVUI	1018		G10180	0.15-0.20	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 17 C			0.15-0.20	0.30-0.60	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C18D	1.0416		0.15-0.20	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C18D2	1.1129		0.16-0.20	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
ASTM A 29/A 29M-03	1021		G10210	0.18-0.23	0.60-0.90		0.040	0.050				
	1022		G10220	0.18-0.23	0.70-1.00		0.040	0.050				
ASTM A 108-03	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
A31WI A 100-03	1022		G10220	0.18-0.23	0.70-1.00		0.040	0.050				
	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1021		G10210	0.18-0.23	0.60-0.90		0.040	0.050				
	1022		G10220	0.18-0.23	0.70-1.00		0.040	0.050				
	1020		G10200	0.18-0.23	0.30-0.60		0.030	0.050				
SAE J403 NOV01	1021		G10210	0.18-0.23	0.60-0.90		0.030	0.050				
	1022		G10220	0.18-0.23	0.70-1.00		0.030	0.050				
JIS G 4051:1979	S 20 C			0.18-0.23	0.30-0.60	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
313 G 4031.1979	S 20 CK			0.18-0.23	0.30-0.60	0.15-0.35	0.025	0.025	0.20	0.20		Cu 0.25; Ni+Cr 0.30
EN 10016-2:1995	C20D	1.0414		0.18-0.23	0.30-0.60	0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C20D2	1.1137		0.18-0.23	0.30-0.50	0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
EN 10083-1:1991	C22E	1.1151		0.17-0.24	0.40-0.70	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10003-1.1991	C22R	1.1149		0.17-0.24	0.40-0.70	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C22	1.0402		0.17-0.24	0.40-0.70	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Ni+Mo 0.63
ASTM A 29/A 29M-03	1023			0.20-0.25	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1023		G10230	0.20-0.25	0.30-0.60		0.040	0.050				
SAE J403 NOV01	1023		G10230	0.20-0.25	0.30-0.60		0.030	0.050				
JIS G 4051:1979	S 22 C			0.20-0.25	0.30-0.60	0.15-0.35	0.030	0.035	.20	.20		Cu 0.30; Ni+Cr 0.35

Standard	Grade, Class,	Steel	UNS					Weight, %, m	ax, Unles	s Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
ASTIVI A 29/A 29/VI-03	1026		G10260	0.22-0.28	0.60-0.90		0.040	0.050				
ASTM A 108-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
ASTINI A 576-900 (2000)	1026		G10260	0.22-0.28	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1025		G10250	0.22-0.28	0.30-0.60		0.030	0.050				
SAE J403 NOVUT	1026		G10260	0.22-0.28	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 25 C			0.22-0.28	0.30-0.60	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C26D	1.0415		0.24-0.29	0.50-0.80	0.10-0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C26D2	1.1139		0.24-0.29	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10000 1 1001	C25E	1.1178		0.22-0.29	0.40-0.70	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-1:1991	C25R	1.1179		0.22-0.29	0.40-0.70	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C25	1.0402		0.22-0.29	0.40-0.70	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 25			0.22-0.29	0.40-0.70	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 25 E 4			0.22-0.29	0.40-0.70	0.10-0.40	0.035	0.035				
	C 25 M 2			0.22-0.29	0.40-0.70	0.10-0.40	0.035	0.020-0.040				
ASTM A 29/A 29M-03	1029		G10290	0.25-0.31	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1029		G10290	0.25-0.31	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1029		G10290	0.25-0.31	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 28 C			0.25-0.31	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
ASTM A 29/A 29M-03	1030		G10300	0.28-0.34	0.60-0.90		0.040	0.050				
ASTM A 108-03	1030		G10300	0.28-0.34	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1030		G10300	0.28-0.34	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1030		G10300	0.28-0.34	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 30 C			0.27-0.33	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-4:1995	C32D2	1.1143		0.30-0.34	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 40000 4 4004	C30E	1.1178		0.27-0.34	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-1:1991	C30R	1.1179		0.27-0.34	0.50-0.80	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C30	1.0528		0.27-0.34	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 30			0.27-0.34	0.50-0.80	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 30 E 4			0.27-0.34	0.50-0.80	0.10-0.40	0.035	0.035				
	C 30 M 2			0.27-0.34	0.50-0.80	0.10-0.40	0.035	0.020-0.040				

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 4051:1979	S 33 C			0.30-0.36	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C32D	1.0530		0.30-0.35	0.50-0.80	0.10-0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
	1034		G10340	0.32-0.38	0.50-0.80		0.040	0.050				
ASTM A 29/A 29M-03	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
	1037		G10370	0.32-0.38	0.70-1.00		0.040	0.050				
ASTM A 108-03	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
A31WI A 376-900 (2000)	1037		G10350	0.32-0.38	0.70-1.00		0.040	0.050				
SAE J403 NOV01	1035		G10350	0.32-0.38	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 35 C			0.32-0.38	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-4:1995	C36D2	1.1145		0.34-0.38	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10083-1:1991	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10063-1.1991	C35R	1.1180		0.32-0.39	0.50-0.80	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C35	1.0501		0.32-0.39	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 35			0.32-0.39	0.50-0.80	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 35 E 4			0.32-0.39	0.50-0.80	0.10-0.40	0.035	0.035				
	C 35 M 2			0.32-0.39	0.50-0.80	0.10-0.40	0.035	0.020-0.040				
ASTM A 29/A 29M-03	1038		G10380	0.35-0.42	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1038		G10380	0.35-0.42	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1038		G10380	0.35-0.42	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 38 C			0.35-0.41	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C38D	1.0516		0.35-0.40	0.50-0.80	0.10-0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C38D2	1.1150		0.36-0.40	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1039		G10390	0.37-0.44	0.70-1.00		0.040	0.050				
A31W A 29/A 29W-03	1040		G10400	0.37-0.44	0.60-0.90		0.040	0.050				
ASTM A 108-03	1040		G10400	0.37-0.44	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1039		G10390	0.37-0.44	0.70-1.00		0.040	0.050				
ASTIVI A 576-900 (2000)	1040		G10400	0.37-0.44	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1039		G10400	0.37-0.44	0.70-1.00		0.030	0.050				
SAE J403 NOVUT	1040		G10400	0.37-0.43	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 40 C			0.37-0.43	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-4:1995	C40D2	1.1153		0.38-0.42	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10083-1:1991	C40E	1.1186		0.37-0.44	0.50-0.80	0.040	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10003-1.1991	C40R	1.1189		0.37-0.44	0.50-0.80	0.040	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C40	1.0511		0.37-0.44	0.50-0.80	0.040	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 40			0.37-0.44	0.50-0.80	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 40 E 4			0.37-0.44	0.50-0.80	0.10-0.40	0.035	0.035				
	C 40 M 2			0.37-0.44	0.50-0.80	0.10-0.40	0.035	0.020-0.040				
ASTM A 29/A 29M-03	1042		G10420	0.40-0.47	0.60-0.90		0.040	0.050				
ASTIVI A 29/A 29/VI-03	1043		G10430	0.40-0.47	0.70-1.00		0.040	0.050				
ASTM A 576-90b (2000)	1042		G10420	0.40-0.47	0.60-0.90		0.040	0.050				
ASTIVI A 576-900 (2000)	1043		G10430	0.40-0.47	0.70-1.00		0.040	0.050				
SAE J403 NOV01	1042		G10420	0.40-0.47	0.60-0.90		0.030	0.050				
SAE J4US NOVUI	1043		G10430	0.40-0.47	0.70-1.00		0.030	0.050				
JIS G 4051:1979	S 43 C			0.40-0.46	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C42D	1.0541		0.40-0.45	0.50-0.80	0.10-0.30	0.035	0.035	0.20	0.25	0.05	Cu 0.30; Al 0.01
EN 10016-4:1995	C42D2	1.1154		0.40-0.44	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	1044		G10440	0.43-0.50	0.30-0.60		0.040	0.050				
ASTM A 29/A 29M-03	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
	1046		G10460	0.43-0.50	0.70-1.00		0.040	0.050				
ASTM A 108-03	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
	1044		G10440	0.43-0.50	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
	1046		G10460	0.43-0.50	0.70-1.00		0.040	0.050				
	1044		G10440	0.43-0.50	0.30-0.60		0.030	0.050				
SAE J403 NOV01	1045		G10450	0.43-0.50	0.60-0.90		0.030	0.050				
	1046		G10460	0.43-0.50	0.70-1.00		0.030	0.050				
JIS G 4051:1979	S 45 C			0.42-0.48	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-4:1995	C46D2	1.1162		0.44-0.48	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10083-1:1991	C45E	1.1191		0.42-0.50	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-1:1991	C45R	1.1201		0.42-0.50	0.50-0.80	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C45	1.0503		0.42-0.50	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 45			0.42-0.50	0.50-0.80	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 45 E4			0.42-0.50	0.50-0.80	0.10-0.40	0.035	0.035				
	C 45 M2			0.42-0.50	0.50-0.80	0.10-0.40	0.035	0.020-0.040				
JIS G 4051:1979	S 48 C			0.45-0.51	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C48D	1.0517		0.45-0.50	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C48D2	1.1164		0.46-0.50	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, m	ax, Unles	s Otherwis	e Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	1049		G10490	0.46-0.53	0.60-0.90		0.040	0.050				
ASTM A 29/A 29M-03	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
	1053		G10530	0.48-0.55	0.70-1.00		0.040	0.050				
ASTM A 108-03	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
	1049		G10490	0.46-0.53	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
	1053		G10530	0.48-0.55	0.70-1.00		0.040	0.050				
	1049		G10490	0.46-0.53	0.60-0.90		0.030	0.050				
SAE J403 NOV01	1050		G10500	0.48-0.55	0.60-0.90		0.030	0.050				
	1053		G10530	0.48-0.55	0.70-1.00		0.030	0.050				
JIS G 4051:1979	S 50 C			0.47-0.53	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C50D	1.0586		0.48-0.53	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C50D2	1.1171		0.48-0.52	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10000 1.1001	C50E	1.1206		0.47-0.55	0.60-0.90	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-1:1991	C50R	1.1241		0.47-0.55	0.60-0.90	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C50	1.0540		0.47-0.55	0.60-0.90	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 50			0.47-0.55	0.60-0.90	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 50 E4			0.47-0.55	0.60-0.90	0.10-0.40	0.035	0.035				
	C 50 M2			0.47-0.55	0.60-0.90	0.10-0.40	0.035	0.020-0.040				
JIS G 4051:1979	S 53 C			0.50-0.56	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C52D	1.0588		0.50-0.55	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C52D2	1.1202		0.50-0.54	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, m	nax, Unles	s Otherwis	e Specified	ı
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1055		G10550	0.50-0.60	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1055		G10550	0.50-0.60	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1055		G10550	0.50-0.60	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 55 C			0.52-0.58	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C56D	1.0518		0.53-0.58	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C56D2	1.1220		0.54-0.58	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.05	Cu 0.15; Al 0.01; N 0.007
EN 10083-1:1991	C55E	1.1203		0.52-0.60	0.60-0.90	0.40	0.035	0.035	0.40	040	0.10	Cr+Mo+Ni 0.63
EN 10003-1.1991	C55R	1.1209		0.52-0.60	0.60-0.90	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C55	1.0835		0.52-0.60	0.60-0.90	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 55			0.52-0.60	0.60-0.90	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 55 E4			0.52-0.60	0.60-0.90	0.10-0.40	0.035	0.035				
	C 55 M2			0.52-0.60	0.60-0.90	0.10-0.40	0.035	0.020-0.040				
ASTM A 29/A 29M-03	1059		G10590	0.55-0.65	0.50-0.80		0.040	0.050				
A3 1 W A 29/A 29 W - 03	1060		G10600	0.55-0.65	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1060		G10600	0.55-0.65	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1060		G10600	0.55-0.65	0.60-0.90		0.030	0.050				
JIS G 4051:1979	S 58 C			0.55-0.61	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10016-2:1995	C58D	1.0609		0.55-0.60	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
LIN 10010-2.1995	C60D	1.0610		0.58-0.63	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C58D2	1.1212		0.56-0.60	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10016-4.1995	C60D2	1.1228		0.58-0.62	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10083-1:1991	C60E	1.1221		0.57-0.65	0.60-0.90	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
LIN 10003-1.1991	C60R	1.1223		0.57-0.65	0.60-0.90	0.40	0.035	0.020-0.040	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10083-2:1991	C60	1.0601		0.57-0.65	0.60-0.90	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni 0.63
	C 60			0.57-0.65	0.60-0.90	0.10-0.40	0.045	0.045				
ISO 683-1:1987	C 60 E 4			0.57-0.65	0.60-0.90	0.10-0.40	0.035	0.035				
	C 60 M 2			0.57-0.65	0.60-0.90	0.10-0.40	0.035	0.020-0.040				

Standard	Grade, Class,	Steel	UNS					Weight, %, ı	max, Unles	s Otherwis	e Specified	i
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1064		G10640	0.60-0.70	0.50-0.80		0.040	0.050				
A3 1 W A 29/A 29 W - U3	1065		G10650	0.60-0.70	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1065		G10650	0.60-0.70	0.60-0.90		0.030	0.050				
	C62D	1.0611		0.60-0.65	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-2:1995	C66D	1.0612		0.63-0.68	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
	C68D	1.0613		0.65-0.70	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
	C62D2	1.1222		0.60-0.64	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10016-4:1995	C66D2	1.1236		0.64-0.68	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
	C68D2	1.1232		0.66-0.70	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
	1069		G10690	0.65-0.75	0.40-0.70		0.040	0.050				
ASTM A 29/A 29M-03	1070		G10700	0.65-0.75	0.60-0.90		0.040	0.050				
	1071		G10710	0.65-0.70	75-1.05		0.040	0.050				
ASTM A 576-90b (2000)	1070		G10700	0.65-0.75	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1070		G10700	0.65-0.75	0.60-0.90		0.030	0.050				
EN 10010 0:1005	C70D	1.0615		0.68-0.73	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-2:1995	C72D	1.0617		0.70-0.75	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10010 4:1005	C70D2	1.1251		0.68-0.72	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.03	Cu 0.15; Al 0.01; N 0.007
EN 10016-4:1995	C72D2	1.1242		0.70-0.74	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
ACTM A 00/A 00M 00	1074		G10740	0.70-0.80	0.50-0.80		0.040	0.050				
ASTM A 29/A 29M-03	1075		G10750	0.70-0.80	0.40-0.70		0.040	0.050				
EN 10010 0 1005	C76D	1.0614		0.73-0.78	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-2:1995	C78D	1.0620		0.75-0.80	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10010 1 1005	C76D2	1.1253		0.74-0.78	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
EN 10016-4:1995	C78D2	1.1252		0.76-0.80	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1078		G10780	0.72-0.85	0.30-0.60		0.040	0.050				
ASTM A 576-90b (2000)	1078		G10780	0.72-0.85	0.30-0.60		0.040	0.050				
SAE J403 NOV01	1078		G10780	0.72-0.85	0.30-0.60		0.030	0.050				
EN 10010 0:1005	C80D	1.0622		0.78-0.83	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-2:1995	C82D	1.0626		0.80-0.85	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10010 1 1005	C80D2	1.1255		0.78-0.82	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
EN 10016-4:1995	C82D2	1.1262		0.80-0.84	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007

Standard	Grade, Class,	Steel	UNS					Weight, %, r	max, Unles	s Otherwis	e Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1080		G10800	0.75-0.88	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1080		G10800	0.75-0.88	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1080		G10800	0.75-0.88	0.60-0.90		0.030	0.050				
EN 10016-2:1995	C86D	1.0616		0.83-0.88	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C86D2	1.1265		0.84-0.88	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1084		G10840	0.80-0.93	0.60-0.90		0.040	0.050				
ASTIVI A 29/A 291VI-US	1086		G10860	0.80-0.93	0.30-0.50		0.040	0.050				
ASTM A 576-90b (2000)	1084		G10840	0.80-0.93	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1086		G10860	0.80-0.93	0.30-0.50		0.030	0.050				
EN 10016-2:1995	C88D	1.0628		0.85-0.90	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C88D2	1.1272		0.86-0.90	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1090		G10900	0.85-0.98	0.60-0.90		0.040	0.050				
ASTM A 576-90b (2000)	1090		G10900	0.85-0.98	0.60-0.90		0.040	0.050				
SAE J403 NOV01	1090		G10900	0.85-0.98	0.60-0.90		0.030	0.050				
EN 10016-2:1995	C92D	1.0618		0.90-0.95	0.50-0.80	0.10-0.30	0.035	0.035	0.15	0.20	0.05	Cu 0.25; Al 0.01
EN 10016-4:1995	C92D2	1.1282		0.90-0.95	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007
ASTM A 29/A 29M-03	1095		G10950	0.90-1.03	0.30-0.50		0.040	0.050				
ASTM A 108-03	1095		G10950	0.90-1.03	0.30-0.50		0.040	0.050				
ASTM A 576-90b (2000)	1095		G10950	0.90-1.03	0.30-0.50		0.040	0.050				
SAE J403 NOV01	1095		G10950	0.90-1.03	0.30-0.50		0.030	0.050				
EN 10016-4:1995	C98D2	1.1283		0.96-1.00	0.50-0.70	0.10-0.30	0.020	0.025	0.10	0.10	0.02	Cu 0.15; Al 0.01; N 0.007

2.2 Chemical Composition of High Manganese Carbon Steels for General Use

Standard	Grade, Class,	Steel	UNS					Weight, %,	max, Unless	Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1522		G15220	0.18-0.24	1.10-1.40		0.040	0.050				
ASTM A 576-90b (2000)	1522		G15220	0.18-0.24	1.10-1.40		0.040	0.050				
SAE J403 NOV01	1522		G15220	0.18-0.24	1.10-1.40		0.030	0.050				
JIS G 4053:2003	SMn 420			0.17-0.23	1.20-1.50	0.15-0.35	0.030	0.030	0.35	0.25		Cu 0.30
JIS G 4055.2005	SMnC 420			0.17-0.23	1.20-1.50	0.15-0.35	0.030	0.030	0.35-0.70	0.25		Cu 0.30
ISO 683-1:1987	22 Mn 6			0.19-0.26	1.30-1.60	0.10-0.40	0.035	0.035				
ASTM A 29/A 29M-03	1536		G15360	0.30-0.37	1.20-1.50		0.040	0.050				
ASTM A 576-90b (2000)	1536		G15360	0.30-0.37	1.20-1.50		0.040	0.050				
JIS G 4053:2003	SMn 433			0.30-0.36	1.20-1.50	0.15-0.35	0.030	0.030	0.35	0.25		Cu 0.30
EN 10083-1:1991	28Mn6			0.25-0.32	1.30-1.65	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Ni+Mo 0.63
ISO 683-1:1987	28 Mn 6			0.25-0.32	1.30-1.65	0.10-0.40	0.035	0.035				
SAE J403 NOV01	1541		G15410	0.36-0.44	1.35-1.65		0.030	0.050				
ASTM A 29/A 29M-03	1541		G15410	0.36-0.44	1.35-1.65		0.040	0.050				
ASTM A 576-90b (2000)	1541		G15410	0.36-0.44	1.35-1.65		0.040	0.050				
JIS G 4053:2003	SMn 438			0.35-0.41	1.35-1.65	0.15-0.35	0.030	0.030	0.35	0.25		Cu 0.30
SO 683-1:1987	36 Mn 6			0.33-0.40	1.35-1.65	0.10-0.40	0.035	0.035				
IIC C 4052-0002	SMn 443			0.40-0.46	1.35-1.65	0.15-0.35	0.030	0.030	0.35	0.25		Cu 0.30
JIS G 4053:2003	SMnC 443			0.40-0.46	1.35-1.65	0.15-0.35	0.030	0.030	0.35-0.70	0.25		Cu 0.30
SO 683-1:1987	42 Mn 6			0.39-0.46	1.30-1.65	0.10-0.40	0.035	0.035				

2.3 Chemical Composition of Alloy Steels for General Use

2.3.1 Chromium (Cr) Steels

Standard	Grade, Class,	Steel	UNS					Weight, %, r	nax, Unless	Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 4053:2003	SCr 415			0.13-0.18	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25		Cu 0.30
EN 10084:1998	17Cr3	1.7016		0.14-0.20	0.60-0.90	0.40	0.035	0.035	0.70-1.00			
LIN 10004.1990	17CrS3	1.7014		0.14-0.20	0.60-0.90	0.40	0.035	0.020-0.040	0.70-1.00			
ASTM A 29/A 29M-03	5120		G51200	0.17-0.22	0.70-0.90	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	Cu 0.35
ASTM A 322-91 (2001)	5120		G51200	0.17-0.22	0.70-0.90	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	Cu 0.35
SAE J404 JUN00	5120		G51200	0.17-0.22	0.70-0.90	0.15-0.35	0.030	0.040	0.70-0.90	0.25	0.06	Cu 0.35
JIS G 4053:2003	SCr 420			0.18-0.23	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25		Cu 0.30
ICO 600 11.1007	20 Cr 4			0.17-0.23	0.60-0.90	0.15-0.40	0.035	0.035	0.90-1.20			
ISO 683-11:1987	20 CrS 4			0.17-0.23	0.60-0.90	0.15-0.40	0.035	0.020-0.040	0.90-1.20			
ASTM A 29/A 29M-03	5130		G51300	0.28-0.33	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.06	Cu 0.35
ASTM A 322-91 (2001)	5130		G51300	0.28-0.33	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.06	Cu 0.35
SAE J404 JUN00	5130		G51300	0.28-0.33	0.70-0.90	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.06	Cu 0.35
JIS G 4053:2003	SCr 430			0.28-0.33	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25		Cu 0.30
EN 10001 1000	28Cr4	1.7030		0.24-0.31	0.60-0.90	0.40	0.035	0.035	0.90-1.20			
EN 10084:1998	28CrS4	1.7036		0.24-0.31	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20			
ASTM A 29/A 29M-03	5132		G51320	0.30-0.35	0.60-0.80	0.15-0.35	0.035	0.040	0.75-1.00	0.25	0.06	Cu 0.35
ASTM A 322-91 (2001)	5132		G51320	0.30-0.35	0.60-0.80	0.15-0.35	0.035	0.040	0.75-1.00	0.25	0.06	Cu 0.35
SAE J404 JUN00	5132		G51320	0.30-0.35	0.60-0.80	0.15-0.35	0.030	0.040	0.75-1.00	0.25	0.06	Cu 0.35
JIS G 4053:2003	SCr 435			0.33-0.38	0.60-0.85	0.15-0.35	0.035	0.030	0.90-1.20	0.25		Cu 0.30
EN 40000 4 4004	34Cr4	1.7033		0.30-0.37	0.60-0.90	0.40	0.035	0.035	0.90-1.20			
EN 10083-1:1991	34CrS4	1.7037		0.30-0.37	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20			
100 000 1.1007	34 Cr 4			0.30-0.37	0.60-0.90	0.10-0.40	0.035	0.035	0.90-1.20			
ISO 683-1:1987	34 CrS 4			0.30-0.37	0.60-0.90	0.10-0.40	0.035	0.020-0.040	0.90-1.20			
ASTM A 29/A 29M-03	5135		G51350	0.33-0.38	0.60-0.80	0.15-0.35	0.035	0.040	0.80-1.05	0.25	0.06	Cu 0.35
ASTM A 322-91 (2001)	5135		G51350	0.33-0.38	0.60-0.80	0.15-0.35	0.035	0.040	0.80-1.05	0.25	0.06	Cu 0.35
EN 40000 4 4004	37Cr4	1.7034		0.34-0.41	0.60-0.90	0.40	0.035	0.035	0.90-1.20			
EN 10083-1:1991	37CrS4	1.7038		0.34-0.41	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20			
100 000 1.1007	37 Cr 4			0.34-0.41	0.60-0.90	0.10-0.40	0.035	0.035	0.90-1.20			
ISO 683-1:1987	37 CrS 4			0.34-0.41	0.60-0.90	0.10-0.40	0.035	0.020-0.040	0.90-1.20			

2.3.1 Chromium (Cr) Steels (Continued)

Standard	Grade, Class,	Steel	UNS					Weight, %, r	nax, Unless	Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	5140		G51400	0.38-0.43	0.70-0.90	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	Cu 0.35
ASTM A 322-91 (2001)	5140		G51400	0.38-0.43	0.70-0.90	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	Cu 0.35
SAE J404 JUN00	5140		G51400	0.38-0.43	0.70-0.90	0.15-0.35	0.030	0.040	0.70-0.90	0.25	0.06	Cu 0.35
JIS G 4053:2003	SCr 440			0.38-0.43	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25		Cu 0.30
TN 40000 4.4004	41Cr4	1.7035		0.38-0.45	0.60-0.90	0.40	0.035	0.035	0.90-1.20			
EN 10083-1:1991	41CrS4	1.7039		0.38-0.45	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20			
SO 683-1:1987	41 Cr 4			0.38-0.45	0.60-0.90	0.10-0.40	0.035	0.035	0.90-1.20			
50 663-1.1967	41 CrS 4			0.38-0.45	0.60-0.90	0.10-0.40	0.035	0.020-0.040	0.90-1.20			
ASTM A 29/A 29M-03	5145			0.43-0.48	0.70-0.90	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	Cu 0.35
IS G 4053:2003	SCr 445			0.43-0.48	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25		Cu 0.35

2.3.2 Chromium-Molybdenum (Cr-Mo) Steels

Standard	Grade, Class,	Steel	UNS					Weight, %, m	ax, Unless C	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
	4118		G41180	0.18-0.23	0.70-0.90	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.08-0.15	Cu 0.35
ASTM A 29/A 29M-03	4120		G41200	0.18-0.23	0.90-1.20	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.13-0.20	Cu 0.35
	4121		G41210	0.18-0.23	0.75-1.00	0.15-0.35	0.035	0.040	0.45-0.65	0.25	0.20-0.30	Cu 0.35
	4118		G41180	0.18-0.23	0.70-0.90	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.08-0.15	Cu 0.35
ASTM A 322-91 (2001)			G41200	0.18-0.23	0.90-1.20	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.13-0.20	Cu 0.35
			G41210	0.18-0.23	0.75-1.00	0.15-0.35	0.035	0.040	0.45-0.65	0.25	0.20-0.30	Cu 0.35
SAE J404 JUN00	4118		G41180	0.18-0.23	0.70-0.90	0.15-0.35	0.030	0.040	0.40-0.60	0.25	0.08-0.15	Cu 0.35
SAE 1404 JUNOU	4120		G41200	0.18-0.23	0.90-1.20	0.15-0.35	0.030	0.040	0.40-0.60	0.25	0.13-0.20	Cu 0.35
	SCM 418			0.16-0.21	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
JIS G 4053:2003	SCM 420			0.18-0.23	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
JIS G 4053.2003	SCM 421			0.17-0.23	0.70-1.00	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
	SCM 822			0.20-0.25	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.35-0.45	Cu 0.30
	18CrMo4	1.7243		0.15-0.21	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.25	
	18CrMoS4	1.7244		0.15-0.21	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.25	
	22CrMoS3-5	1.7333		0.19-0.24	0.70-1.00	0.40	0.035	0.020-0.040	0.70-1.00		0.40-0.50	
EN 10084:1998	20MoCr3	1.7320		0.17-0.23	0.60-0.90	0.40	0.035	0.035	0.40-0.70		0.30-0.40	
	20MoCrS3	1.7319		0.17-0.23	0.60-0.90	0.40	0.035	0.020-0.040	0.40-0.70		0.30-0.40	
	20MoCr4	1.7321		0.17-0.23	0.70-1.00	0.40	0.035	0.035	0.30-0.60		0.40-0.50	
	20MoCrS4	1.7323		0.17-0.23	0.70-1.00	0.40	0.035	0.020-0.040	0.30-0.60		0.40-0.50	
ISO 683-11:1987	18 CrMo 4			0.15-0.21	0.60-0.90	0.15-0.40	0.035	0.035	0.90-1.20		0.15-0.25	
150 683-11:1987	18 CrMoS 4			0.15-0.21	0.60-0.90	0.15-0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.25	
ASTM A 29/A 29M-03	4130		G41300	0.28-0.33	0.40-0.60	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	4130		G41300	0.28-0.33	0.40-0.60	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
SAE J404 JUN00	4130		G41300	0.28-0.33	0.40-0.60	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
JIS G 4053:2003	SCM 425			0.23-0.28	0.60-0.90	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
IIC C 4050,0000	SCM 430			0.28-0.33	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
JIS G 4053:2003	SCM 432			0.27-0.37	0.30-0.60	0.15-0.35	0.030	0.030	1.00-1.50	0.25	0.15-0.30	Cu 0.30
EN 10000 1:1001	25CrMo4	1.7218		0.22-0.29	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
EN 10083-1:1991	25CrMoS4	1.7213		0.22-0.29	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.30	
100 000 1.1007	25 CrMo 4			0.22-0.29	0.60-0.90	0.10-0.40	0.035	0.035	0.90-1.20		0.15-0.30	
ISO 683-1:1987	25 CrMoS 4			0.22-0.29	0.60-0.90	0.10-0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.30	

2.3.2 Chromium-Molybdenum (Cr-Mo) Steels (Continued)

Standard	Grade, Class,	Steel	UNS					Weight, %, m	ax, Unless	Otherwise S	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	4137		G41370	0.35-0.40	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	4137		G41370	0.35-0.40	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
SAE J404 JUN00	4137		G41370	0.35-0.40	0.70-0.90	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
JIS G 4053:2003	SCM 435			0.33-0.38	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
EN 10000 1.1001	34CrMo4	1.7220		0.30-0.37	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
EN 10083-1:1991	34CrMoS4	1.7226		0.30-0.37	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.30	
ISO 683-1:1987	34 CrMo 4			0.30-0.37	0.60-0.90	0.10-0.40	0.035	0.035	0.90-1.20		0.15-0.30	
150 003-1:1907	34 CrMoS 4			0.30-0.37	0.60-0.90	0.10-0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.30	
ASTM A 29/A 29M-03	4140		G41400	0.38-0.43	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	4140		G41400	0.38-0.43	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
SAE J404 JUN00	4140		G41400	0.38-0.43	0.75-1.00	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
JIS G 4053:2003	SCM 440			0.38-0.43	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
EN 10083-1:1991	42CrMo4	1.7225		0.38-0.45	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
EN 10063-1.1991	42CrMoS4	1.7227		0.38-0.45	0.60-0.90	0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.30	
ISO 683-1:1987	42 CrMo 4			0.38-0.45	0.60-0.90	0.10-0.40	0.035	0.035	0.90-1.20		0.15-0.30	
150 003-1:1907	42 CrMoS 4			0.38-0.45	0.60-0.90	0.10-0.40	0.035	0.020-0.040	0.90-1.20		0.15-0.30	
ASTM A 29/A 29M-03	4145		G41450	0.43-0.48	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	4145		G41450	0.43-0.48	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
SAE J404 JUN00	4145		G41450	0.43-0.48	0.75-1.00	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
JIS G 4053:2003	SCM 445			0.43-0.48	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
ASTM A 29/A 29M-03	4150		G41500	0.48-0.53	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	4150		G41500	0.48-0.53	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
SAE J404 JUN00	4150		G41500	0.48-0.53	0.75-1.00	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.15-0.25	Cu 0.35
EN 10083-1:1991	50CrMo4	1.7228		0.46-0.54	0.50-0.80	0.40	0.035	0.035	0.90-1.20	1.30-1.70	0.15-0.30	
ISO 683-1:1987	50 CrMo 4			0.46-0.54	0.50-0.80	0.10-0.40	0.035	0.035	0.90-1.20		0.15-0.30	

2.3.3 Chromium-Nickel (Cr-Ni) Steels

Standard	Grade, Class,	Steel	UNS				٧	/eight, %, m	nax, Unless	Otherwise S	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ISO 683-11:1987	15 NiCr 13			0.12-0.18	0.35-0.65	0.15-0.40	0.035	0.035	0.60-0.90	3.00-3.50		
JIS G 4053:2003	SNC 815			0.12-0.18	0.35-0.65	0.15-0.35	0.30	0.30	0.60-1.00	3.00-3.50		Cu 0.30
EN 10084:1998	15NiCr13	1.5752		0.14-0.20	0.40-0.70	0.40	0.035	0.035	0.60-0.90	3.00-3.50		

2.3.4 Nickel-Chromium-Molybdenum (Ni-Cr-Mo) Steels

Standard	Grade, Class,	Steel	UNS					Weight, %,	max, Unle	ss Otherwis	se Specified	ı
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 4053:2003	SNCM 415			0.12-0.18	0.40-0.70	0.15-0.35	0.030	0.030	0.40-0.65	1.60-2.00	0.15-0.30	Cu 0.30
ISO 683-11:1987	17 NiCrMo 6			0.14-0.20	0.60-0.90	0.15-0.40	0.035	0.035	0.80-1.10	1.20-1.60	0.15-0.25	
ASTM A 29/A 29M-03	4320		G43200	0.17-0.22	0.45-0.65	0.15-0.35	0.035	0.040	0.40-0.60	1.65-2.00	0.20-0.30	Cu 0.35
ASTM A 322-91 (2001)	4320		G43200	0.17-0.22	0.45-0.65	0.15-0.35	0.035	0.040	0.40-0.60	1.65-2.00	0.20-0.30	Cu 0.35
SAE J404 JUN00	4320		G43200	0.17-0.22	0.45-0.65	0.15-0.35	0.030	0.040	0.40-0.60	1.65-2.00	0.20-0.30	Cu 0.35
JIS G 4053:2003	SNCM 420			0.17-0.23	0.40-0.70	0.15-0.35	0.030	0.030	0.40-0.65	1.60-2.00	0.15-0.30	Cu 0.30
EN 10084:1998	20NiCrMoS6-4	1.6571		0.16-0.23	0.50-0.90	0.40	0.035	0.020-0.040	0.60-0.90	1.40-1.70	0.25-0.35	
A C.T.M. A . O.O./A . O.O.M. O.O.	4340		G43400	0.38-0.43	0.60-0.80	0.15-0.35	0.035	0.040	0.70-0.90	1.65-2.00	0.20-0.30	Cu 0.35
ASTM A 29/A 29M-03	E4340		G43406	0.38-0.43	0.65-0.85	0.15-0.35	0.025	0.025	0.70-0.90	1.65-2.00	0.20-0.30	Cu 0.35
ACTM A 200 04 (0004)	4340		G43400	0.38-0.43	0.60-0.80	0.15-0.35	0.035	0.040	0.70-0.90	1.65-2.00	0.20-0.30	Cu 0.35
ASTM A 322-91 (2001)	E4340		G43406	0.38-0.43	0.65-0.85	0.15-0.35	0.025	0.025	0.70-0.90	1.65-2.00	0.20-0.30	Cu 0.35
CAE 1404 II INOO	4340		G43400	0.38-0.43	0.60-0.80	0.15-0.35	0.030	0.040	0.70-0.90	1.65-2.00	0.20-0.30	Cu 0.35
SAE J404 JUN00	E4340		G43406	0.38-0.43	0.65-0.85	0.15-0.35	0.025	0.025	0.70-0.90	1.65-2.00	0.20-0.30	Cu 0.35
JIS G 4053:2003	SNCM 439			0.36-0.43	0.60-0.90	0.15-0.35	0.030	0.030	0.60-1.00	1.60-2.00	0.15-0.30	Cu 0.30
ASTM A 29/A 29M-03	8620		G86200	0.18-0.23	0.70-0.90	0.15-0.35	0.035	0.04	0.40-0.60	0.40-0.70	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	8620		G86200	0.18-0.23	0.70-0.90	0.15-0.35	0.035	0.04	0.40-0.60	0.40-0.70	0.15-0.25	Cu 0.35
SAE J404 JUN00	8620		G86200	0.18-0.23	0.70-0.90	0.15-0.35	0.030	0.040	0.40-0.60	0.40-0.70	0.15-0.25	Cu 0.35
JIS G 4053:2003	SNCM 220			0.17-0.23	0.60-0.90	0.15-0.35	0.030	0.030	0.40-0.65	0.40-0.70	0.15-0.30	Cu 0.30
EN 10004-1000	20NiCrMo2-2	1.6523		0.17-0.23	0.65-0.95	0.40	0.035	0.035	0.35-0.70	0.40-0.70	0.15-0.25	
EN 10084:1998	20NiCrMoS2-2	1.6526		0.17-0.23	0.65-0.95	0.40	0.035	0.020-0.040	0.35-0.70	0.40-0.70	0.15-0.25	
100 000 11.1007	20 NiCrMo 2			0.17-0.23	0.65-0.95	0.15-0.40	0.035	0.035	0.30-0.65	0.40-0.70	0.15-0.25	
ISO 683-11:1987	20 NiCrMoS 2			0.17-0.23	0.65-0.95	0.15-0.40	0.035	0.020-0.040	0.30-0.65	0.40-0.70	0.15-0.25	
ASTM A 29/A 29M-03	8640		G86400	0.38-0.43	0.75-1.00	0.15-0.35	0.035	0.040	0.40-0.60	0.40-0.70	0.15-0.25	Cu 0.35
ASTM A 322-91 (2001)	8640		G86400	0.38-0.43	0.75-1.00	0.15-0.35	0.035	0.040	0.40-0.60	0.40-0.70	0.15-0.25	Cu 0.35
SAE J404 JUN00	8640		G86400	0.38-0.43	0.75-1.00	0.15-0.35	0.030	0.040	0.40-0.60	0.40-0.70	0.15-0.25	Cu 0.35
JIS G 4053:2003	SNCM 240			0.38-0.43	0.70-1.00	0.15-0.35	0.030	0.030	0.40-0.65	0.40-0.70	0.15-0.30	Cu 0.30
100 600 1.1007	41 CrNiMo 2			0.37-0.44	0.70-1.00	0.10-0.40	0.035	0.035	0.40-0.60	0.40-0.70	0.15-0.30	
ISO 683-1:1987	41 CrNiMoS 2			0.37-0.44	0.70-1.00	0.10-0.40	0.035	0.020-0.040	0.40-0.60	0.40-0.70	0.15-0.30	
ASTM A 29/A 29M-03	E9310		G93106	0.08-0.13	0.45-0.65	0.15-0.30	0.025	0.025	1.00-1.40	3.00-3.50	0.08-0.15	
EN 10084:1998	14NiCrMo13-4	1.6657		0.11-0.17	0.30-0.60	0.40	0.035	0.035	0.80-1.10	3.00-3.50	0.10-0.25	

2.3.5 Chromium-Molybdenum-Aluminum (Cr-Mo-Al) Steels

Standard	Grade, Class,	Steel	UNS					Weight, %	, max, Unle	ss Otherwis	e Specified	I
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 355-89 (2000)	Α		K24065	0.38-0.43	0.50-0.70	0.15-0.35	0.035	0.040	1.40-180		0.30-0.40	Al 0.95-1.30
JIS G 4202:1979	SACM 645			0.40-0.50	0.60	0.15-0.50	0.030	0.030	1.30-1.70	0.25	0.15-0.30	Al 0.70-1.20, Cu 0.30
EN 10085:2001	32CrAlMo7-10	1.8505		0.28-0.35	0.40-0.70	0.40	0.025	0.035	1.50-1.80		0.20-0.40	Al 0.80-1.20
EN 10085:2001	34CrAlNi7-10	1.8550		0.30-0.37	0.40-0.70	0.40	0.025	0.035	1.50-1.80	0.85-1.15	0.15-0.25	Al 0.80-1.20
EN 10085:2001	41CrAlMo7-10	1.8509		0.38-0.45	0.40-0.70	0.40	0.025	0.035	1.50-1.80		0.20-0.35	Al 0.80-1.20
EN 10085:2001	34CrAlMo5-10	1.8507		0.30-0.37	0.40-0.70	0.40	0.025	0.035	1.00-1.30		0.15-0.25	Al 0.80-1.20
ISO 683-10:1987	41 CrAlMo 7 4			0.38-0.45	0.50-0.80	0.50	0.030	0.035	1.50-1.80		0.25-0.40	Al 0.80-1.20

2.3.6 Boron (B) Steels

Standard	Grade, Class,	Steel	UNS					Weight, %	, max, Unles	s Otherwi	se Specifie	d
Designation	Type, Symbol or Name	Number	Number	C	Mn	Si	Р	s	Cr	Ni	Мо	Others
	50B44		G50441	0.43-0.48	0.75-1.00	0.15-0.35	0.035	0.040	0.20-0.60	0.25	0.06	B 0.0005-0.003; Cu 0.35
	50B46		G50461	0.44-0.49	0.75-1.00	0.15-0.35	0.035	0.040	0.20-0.35	0.25	0.06	B 0.0005-0.003; Cu 0.35
ASTM A 29/A 29M-03	50B50		G50501	0.48-0.53	0.75-1.00	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.06	B 0.0005-0.003; Cu 0.35
	50B60		G50601	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.06	B 0.0005-0.003; Cu 0.35
	51B60		G51601	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	B 0.0005-0.003; Cu 0.35
	50B44		G50441	0.43-0.48	0.75-1.00	0.15-0.35	0.035	0.040	0.20-0.60	0.25	0.06	B 0.0005-0.003; Cu 0.35
	50B46		G50461	0.44-0.49	0.75-1.00	0.15-0.35	0.035	0.040	0.20-0.35	0.25	0.06	B 0.0005-0.003; Cu 0.35
ASTM A 322-91 (2001)	50B50		G50501	0.48-0.53	0.75-1.00	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.06	B 0.0005-0.003; Cu 0.35
	50B60		G50601	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.40-0.60	0.25	0.06	B 0.0005-0.003; Cu 0.35
	51B60		G51601	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.70-0.90	0.25	0.06	B 0.0005-0.003; Cu 0.35
SAE J404 JUN00	50B46		G50461	0.44-0.49	0.75-1.00	0.15-0.35	0.030	0.040	0.20-0.35	0.25	0.06	B 0.0005-0.003; Cu 0.35
SAE J404 JUNOU	51B60		G51601	0.56-0.64	0.75-1.00	0.15-0.35	0.030	0.040	0.70-0.90	0.25	0.06	B 0.0005-0.003; Cu 0.35
	27MnCrB5-2	1.7182		0.24-0.30	1.10-1.40	0.40	0.035	0.040	0.30-0.60			B 0.0008-0.0050
EN 10083-3:1995	33MnCrB5-2	1.7185		0.30-0.36	1.20-1.50	0.40	0.035	0.040	0.30-0.60			B 0.0008-0.0050
	39MnCrB5-2	1.7189		0.36-0.42	1.40-1.70	0.40	0.035	0.040	0.30-0.60			B 0.0008-0.0050

2.3.7 Chromium-Vanadium (Cr-V) Steels

Standard	Grade, Class,	Steel	UNS	Weight, %, max, Unless Otherwise Specified									
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others	
ASTM A 29/A 29M-03	6150		G61500	0.48-0.53	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.06	V 0.15 min	
ASTM A 322-91 (2001)	6150		G61500	0.48-0.53	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10	0.25	0.06	V 0.15 min	
SAE J404 JUN00	6150		G61500	0.48-0.53	0.70-0.90	0.15-0.35	0.030	0.040	0.80-1.10	0.25	0.06	V 0.15 min	
EN 10083-1:1991	51CrV4	1.8159		0.47-0.55	0.70-1.10	0.40	0.035	0.035	0.90-1.20			V 0.10-0.25	
ISO 683-1:1987	51 CrV 4			0.47-0.55	0.60-1.00	0.10-0.40	0.035	0.035	0.80-1.10			V 0.10-0.25	

4 O T 14 4 00/4 0014												
ASTM A 29/A 29M-0												
Grade	1011	1013	1330	1335	1340	1345	1513	1518	1524	1525	1526	1527
UNS Number	G10110	G10130	G13300	G13350	G13400	G13450	G15300	G15180	G15240	G15250	G15260	G15270
Grade	1547	1548	1551	1552	1561	1566	1572	4012	4023	4024	4027	4028
UNS Number	G15470	G15480	G15510	G15520	G15610	G15660	G15720	G40120	G40230	G40240	G40270	G40280
Grade	4032	4037	4042	4047	4135	4142	4147	4161	4419	4422	4427	4615
UNS Number	G43320	G40370	G40420	G40470	G41350	G41420	G41470	G41670	G44190	G44220	G44270	G46150
Grade	4620	4621	4626	4715	4718	4720	4815	4817	4820	5015	5046	5115
UNS Number	G46200	G46210	G46260	G47150	G47180	G47200	G48150	G48170	G48200	G50150	G50460	G51150
Grade	5147	5150	5155	5160	6118	8115	8615	8617	8622	8625	8627	8630
UNS Number	G51470	G51500	G51550	G51600	G61180	G81150	G86150	G86170	G86220	G86250	G86270	G86300
Grade	8637	8642	8645	8650	8655	8660	8720	8740	8822	9254	9255	9259
UNS Number	G86370	G86420	G86450	G86500	G86550	G86600	G87200	G87400	G88200	G92540	G92550	G92590
Grade	9260	81B45	94B17	94B30								
UNS Number	G92600	G81451	G94171	G94301	G47150							
ASTM A 322-91 (20	01) Steel Bars,	Alloy, Standard	d Grades									
Grade	1330	1335	1340	1345	4023	4024	4027	4028	4037	4047	4142	4147
UNS Number	G13300	G13350	G13400	G13450	G40230	G40240	G40270	G40280	G40370	G40470	G41420	G41470
Grade	4161	4615	4620	4621	4626	4720	4815	4817	4820	5117	5150	5155
UNS Number	G41670	G46150	G46200	G46210	G46260	G47200	G48150	G48170	G48200	G51170	G51500	G51550
Grade	5160	6118	8615	8617	8622	8625	8627	8630	8637	8642	8645	8655
UNS Number	G51600	G61180	G86150	G86170	G86220	G86250	G86270	G86300	G86370	G86420	G86450	G86550
Grade	8720	8740	8822	9259	9260	81B45	94B17	94B30				
UNS Number	G87200	G87400	G88200	G92590	G92600	G81451	G94171	G94301				
ASTM A 355-89 (20	00) Standard S	pecification for	Steel Bars, Al	loys, for Nitrid	ng							
Grade	В	С	D									
UNS Number												
ASTM A 576-90b (2	000) Steel Bars	, Carbon, Hot-\	Wrought, Spec	ial Quality								
Grade	1513	1518	1524	1525	1526	1527	1547	1548	1551	1552	1561	1566
UNS Number	G15300	G15180	G15240	G15250	G15260	G15270	G15470	G15480	G15510	G15520	G15610	G15660
Grade	1572	1109	1110	1116	1117	1118	1119	1132	1137	1139	1140	1141
UNS Number	G15720	G11090	G11100	G11160	G11170	G11180	G11190	G11320	G11370	G11390	G11400	G11410
Grade	1144	1145	1146	1151	1211	1212	1213	1215	12L14			
UNS Number	G11440	G11450	G11460	G11510	G12110	G12120	G12130	G12150				

2.4 Non-Comparable Carbon and Alloy Steels for General Use (Continued)

SAE J403 NOV01 C	Chemical Comp	ositions of SA	E Carbon Steel	s (Hot Rolled a	nd Cold Finishe	ed Bars Only)						
Grade	1524	1526	1527	1548	1552	1566	1009	1013	1019	1033	1037	1074
UNS Number	G15240	G15260	G15270	G15480	G15520	G15660	G10090	G10130	G10190	G10330	G10370	G10740
Grade	1075	1084	1085	1536	1547							
UNS Number	G10750	G10840	G10850	G15360	G15470							
SAE J404 JUN00 C	hemical Comp	ositions of SAE	Alloy Steels (Hot Rolled and	Cold Finished	Bars Only)						
Grade	1330	1335	1340	1345	4023	4027	4037	4047	4135	4142	4615	4617
UNS Number	G13300	G13350	G13400	G13450	G40230	G40270	G40370	G40470	G41350	G41420	G46180	G46170
Grade	4620	4820	5115	5150	5160	E52100	8615	8617	8622	8625	8627	8630
UNS Number	G46200	G48200	G51150	G51500	G51600	G52986	G86150	G86170	G86220	G86250	G86270	G86300
Symbol of Class	8637	8645	8655	8720	8740	8822	9254	9259	9260			
UNS Number	G86370	G86450	G86550	G87200	G87400	G88200	G92540	G92590	G92600			
JIS G 4103:1979 Ni	ckel Chromium	Molybdenum	Steels									
Symbol of Class	SNCM 431	SNCM 447	SNCM 616	SNCM 625	SNCM 630	SNCM 815						
Previous Symbol	SNCM 1	SNCM 9	SNCM 26	SNCM 2	SNCM 5	SNCM 25						
JIS G 4105:1979 CI	nromium Molyb	denum Steels										
Symbol of Class	SCM 415											
Previous Symbol	SCM 21											
JIS G 4053:2003 Lo	w-alloyed Stee	els for Machine	Structural Use	•								
Symbol of Class	SNC 236	SNC 415	SNC 631	SNC 836	SCM 415	SNCM 431	SNCM 447	SNCM 616	SNCM 625	SNCM 630	SNCM 815	
Previous Symbol												
EN 10083-1:1991 Q	uenched and T	empered Steel	s – Technical [Delivery Conditi	ons for Special	l Steels						
Steel Name	36 CrNiMo 4	34 CrNiMo 6	30 CrNiMo 8	36 NiCrMo 16	38Cr2	38CrS2	46Cr4	46CrS4				
Steel Number	1.6511	1.6582	1.6580	1.6773	1.7003	1.7023	1.7033	1.7025				
EN 10083-3:1995 Q	uenched and T	empered Steel	s – Technical [Delivery Conditi	ons for Boron	Steels						
Steel Name	20MnB5	30MnB5	38MnB5									
Steel Number	1.5530	1.5531	1.5532									
EN 10084:1998 Cas	se Hardening S	teels - Technic	al Delivery Cor	ditions								
Steel Name	16MnCr5	16MnCrS5	16MnCrB5	20MnCr5	20MnCrS5	16NiCr4	16NiCrS4	10NiCr5-4	18NiCr5-4	17CrNi6-6	17NiCrMo6-4	17NiCrMoS6-4
Steel Number	1.7131	1.7139	1.7160	1.7147	1.7149	1.5714	1.5715	1.5805	1.5810	1.5918	1.6566	1.6569
Steel Name	18CrNiMo7-6											
Steel Number	1.6657											
EN 10085:2001 Niti	riding Steels											
Steel Name	24CrMo13-6	31CrMo12	31CrMoV9	33CrMoV12-9	40CrMoV13-9							
Steel Number	1.8516	1.8515	1.8519	1.8522	1.8523							

2.4 Non-Comparable Carbon and Alloy Steels for General Use (Continued)

ISO 683-1:1987 H	O 683-1:1987 Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels – Part 1: Direct-Hardening Unalloyed and Low-Alloyed Wrought Steel in Form of Different Black Products												
Type of Steel	36 CrNiMo 4	36 CrNiMo 6	31 CrNiMo 8	20 MnCr 5	20 MnCrS 5								
ISO 683-10:1987 I	O 683-10:1987 Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels – Part 10: Wrought Nitriding Steels												
Type of Steel	31 CrMo 12	33 CrAlMo 5 4											
ISO 683-11:1987 I	O 683-11:1987 Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels – Part 11: Wrought Case-Hardening Steels												
Type of Steel	16 MnCr 5	16 MnCrS 5	18 CrNiMo 7										

Chapter

3

STRUCTURAL STEEL PLATES

ASTM Standards

ASTM A 36/A 36M-03a	Carbon Structural Steel
ASTM A 242/A 242M-03a	High-Strength Low-Alloy Structural Steel
ASTM A 283/A 283M-03	Low and Intermediate Tensile Strength Carbon Steel Plates
ASTM A 514/A 514M-00a	High- Yield- Strength, Quenched and Tempered Alloy Steel Plate, Suitable for Welding
ASTM A 529/A 529M-03	High-Strength Carbon-Manganese Steel of Structural Quality
ASTM A 572/A 572M-03a	High-Strength Low-Alloy Columbium-Vanadium Structural Steel
ASTM A 573/A 573M-00a	Structural Carbon Steel Plates of Improved Toughness
ASTM A 588/A 588M-03a	High-Strength Low-Alloy Structural Steel With 50 ksi [345 MPa] Minimum Yield Point to 4 in. [100 mm] Thick
ASTM A 606-01	Steel, Sheet and Strip, High- Strength, Low-Alloy, Hot- Rolled and Cold- Rolled, with Improved Atmospheric Corrosion Resistance
ASTM A 633/A 633M-01	Normalized High-Strength Low-Alloy Structural Steel Plates
ASTM A 656/A 656M-03	Hot-Rolled Structural Steel, High-Strength Low-Alloy Plate with Improved Formability
ASTM A 678/A 678M-00a	Quenched-and-Tempered Carbon and High-Strength Low-Alloy Structural Steel Plates
ASTM A 709/A 709M-03a	Carbon and High-Strength Low-Alloy Structural Steel Shapes, Plates, and Bars and Quenched-and-Tempered Alloy Structural Steel Plates for Bridges
ASTM A 710/A 710M-02	Precipitation-Strengthened Low-Carbon Nickel-Copper-Chromium-Molybdenum-Columbium Alloy Structural Steel Plates
ASTM A 852/A 852M-03	Quenched and Tempered Low-Alloy Structural Steel Plate with 70 ksi [485 MPa] Minimum Yield Strength to 4 in. [100 mm] Thick
ASTM A 871/A 871M-03	High-Strength Low-Alloy Structural Steel Plate with Atmospheric Corrosion Resistance
ASTM A 1011/A 1011M-03	Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-Strength Low-Alloy with Improved Formability

JIS Standards

JIS G 3101:1995	Rolled Steels for General Structure
JIS G 3106:1999	Rolled Steels for Welded Structure
JIS G 3136:1994	Rolled Steels for Building Structure
JIS G 3128:1999	High Yield Strength Steel Plates for Welded Structure
JIS G 3114:1998	Hot-Rolled Atmospheric Corrosion Resisting Steels for Welded Structure
JIS G 3125:1987	Superior Atmospheric Corrosion Resisting Rolled Steels

CEN Standards

EN 10025:1993	Hot Rolled Products of Non-Alloy Structural Steels - Technical Delivery Conditions
EN 10113-2:1993 A1: 1998	Hot-Rolled Products in Weldable Fine Grain Structural Steels - Part 2: Delivery Conditions for Normalized/Normalized Rolled Steels
EN 10113-3:1993	Hot-Rolled Products in Weldable Fine Grain Structural Steels - Part 3: Delivery Conditions for Thermomechanical Rolled Steels
EN 10137-2:1995	Plates and Wide Flats Made of High Yield Strength Structural Steels in the Quenched and Tempered or Precipitation Hardened Conditions - Part 2: Delivery Conditions for Quenched and Tempered Steels
EN 10137-3:1995	Plates and Wide Flats Made of High Yield Strength Structural Steels in The Quenched and Tempered or Precipitation Hardened Conditions - Part 3: Delivery Conditions for Precipitation Hardened Steels
EN 10155:1993	Structural Steels with Improved Atmospheric Corrosion Resistance - Technical Delivery Conditions

ISO Standards

ISO 630:1995	Structural Steels - Plates, Wide Flats, Bars, Sections and Profiles
ISO 4950-2:1995	High Yield Strength Flat Steel Products, Part 2: Products Supplied in the Normalized or Controlled Rolled
100 1000 2.1000	Condition
ISO 4950-3:1995	High Yield Strength Flat Steel Products, Part 3: Products Supplied in the Heat-Treated (Quenched + Tempered)
130 4930-3.1993	Condition
ISO 4952:2003	Structural Steels with Improved Atmospheric Corrosion Resistance - Second Edition
ISO 5952:1998	Continuously Hot-Rolled Steel Sheet of Structural Quality with Improved Atmospheric Corrosion Resistance

CSA Standards

CSA G40.21-04	Structural Quality Steel - Plates, Sheet, Floor Plates, Bars, and Welded Shapes

Heat Treatment Terms Applicable to this Chapter

Standard	Heat Treatment Terms
ASTM A 36/A 36M-03a	
ASTM A 242/A 242M-03a	
ASTM A 283/A 283M-03	
ASTM A 514/A 514M-00a	QT: quenched and tempered
ASTM A 529/A 529M-03	
ASTM A 572/A 572M-03a	
ASTM A 573/A 573M-00a	
ASTM A 588/A 588M-03a	
ASTM A 606-01	HR: hot-rolled (as-rolled); CR: cold-rolled; A: annealed; N: normalized
ASTM A 633/A 633M-01	N: normalized; N+N: double normalized
ASTM A 656/A 656M-03	HR: hot-rolled
ASTM A 678/A 678M-00a	QT: quenched and tempered
ASTM A 709/A 709M-03a	; QT: quenched and tempered
ASTM A 710/A 710M-02	PH: precipitation heat treatment; N+PH: normalized followed by precipitation heat treatment;
AOTNA A 050/A 050NA 00	Q+PH: quenched followed by precipitation heat treatment
ASTM A 852/A 852M-03	QT: quenched and tempered
ASTM A 871/A 871M-03	HR: hot-rolled (as rolled); N: normalized; QT: quenched and tempered
ASTM A 1011/A 1011M-03	HR: hot-rolled
JIS G 3101:1995	HR: hot-rolled
JIS G 3106:1999	HR: hot-rolled
JIS G 3114:1998	HR: hot-rolled
JIS G 3125:1987	CR: cold-rolled; HR: hot-rolled
JIS G 3128:1999	QT: quenched and tempered
JIS G 3136:1994	HR: hot-rolled
EN 10025:1993	HR: hot-rolled; N: normalized rolled
EN 10113-2:1998	N: normalized or normalized rolled treatment
EN 10113-3:1993	TMCP: thermomechanically rolled
EN 10137-2:1995	QT: quenched and tempered
EN 10137-3:1995	PH: precipitation hardened
EN 10155:1993	HR: hot-rolled; N: normalized or normalized rolled
ISO 630:1995	AR: as rolled; N: normalized or equivalent (obtained by controlled rolling); AD: as delivered
ISO 4950-2:1995	N: normalized; NT: normalized and tempered; CTR: controlled rolled condition
ISO 4950-3:1995	QT: quenched and tempered
ISO 4952:2003	AR: as rolled; N: normalized or equivalent (obtained by controlled rolling)
ISO 5952:1998	HR: hot-rolled
CSA G40.21-98	: not specified; AR: as-rolled; QT: quenched and tempered

Impact Testing Notes Applicable to this Chapter

see standard for supplementary impact testing: the standard includes impact testing as a supplementary requirement (optional to the purchaser). see standard for impact data: impact testing requirements are listed in the standard for multiple test temperatures.

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Heat Treatment	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ISO 630:1995	E 185			AR	≤ 16		185		300-540		18	
130 030.1993	L 165			An	$16 < t \le 40$		175		300-340		10	
ASTM A 283/A 283M-03	Α						165	24	310-415	45-60	30	
					< 3		185		310-540			
EN 10005-1000	S185	1 0005		HR	3 ≤ t ≤ 16		185		290-510		16	
EN 10025:1993	3103	1.0035			16 < t ≤ 40		175		290-510			
					40 < t ≤ 100				290-510			
				HR	≤ 16		205				21	
JIS G 3101:1995	SS330				16 < t ≤ 40		195		330-430		26	
					> 40		175				28	
			K02502	HR	0.65 ≤ t < 1.6	0.025 ≤ t < 0.064	205			49	21	
ASTM A 1011/A 1011M-03	30 [205]				1.6 ≤ t < 2.5	0.064 ≤ t < 0.097		30	340		24	
	- -				2.5 ≤ t < 6.0	0.097 ≤ t < 0.230					25	

NOTE: This section continued on next page.

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS Number	Heat Treatment	Section Th	ickness	Yield Strei	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number			t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		235				26	
					16 < t ≤ 40		225				26	
					40 < t ≤ 63		215				25	
	E 235 A			AR	63 < t ≤ 80		215		340-470		24	
					80 < t ≤ 100		215				24	
					100 < t ≤ 150		195				22	
					150 < t ≤ 200		185				21	
	E 235 B			AR	≤ 16		235		340-470		26	
	L 200 B			An	16 < t ≤ 25		225		340-470		20	
					≤ 16		235				26	
					16 < t ≤ 40		225				26	
				AR	40 < t ≤ 63		215				25	
	E 235 B NF				63 < t ≤ 80		215		340-470		24	27 J at 20°C
					80 < t ≤ 100		215				24	
ISO 630:1995					100 < t ≤ 150		195				22	
130 030.1993					150 < t ≤ 200		185				21	
				AR	≤ 16		235		340-470		26	
					16 < t ≤ 40		225				26	27 J at 0°C
					40 < t ≤ 63		215				25	
	E 235 C				63 < t ≤ 80		215				24	
					80 < t ≤ 100		215				24	
					100 < t ≤ 150		195				22	
					150 < t ≤ 200		185				21	
					≤ 16		235				26	
					16 < t ≤ 40		225				26	
				D ₁ : N	40 < t ≤ 63		215				25	-
	E 235 D				63 < t ≤ 80		215		340-470		24	27 J at -20°C
				D ₂ : AD	80 < t ≤ 100		215				24	
					100 < t ≤ 150		195				22	
			_	150 < t ≤ 200		185				21		
ASTM A 283/A 283M-03	В						185	27	345-450	50-65	28	

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat Treatment	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					18	
ASTM A 1011/A 1011M-03	33 [230]		K02502	HR	1.6 ≤ t < 2.5	0.064 ≤ t < 0.097	230	33	360	52	22	
					2.5 ≤ t < 6.0	0.097 ≤ t < 0.230					23	
					< 3		235		360-510			
	S235JR 1.0	1 0007		HR	3 ≤ t ≤ 16		235				24	27 J at 20°C
	5235JH	1.0037		пн	16 < t ≤ 40		225		340-470			
					40 < t ≤ 100							
					< 3		235		360-510			
	S235JRG1	1 0000		LID	3 ≤ t ≤ 16		235				24	27 J at 20°C
	5235JRG1	1.0036		HR	16 < t ≤ 40		225		340-470			
					40 < t ≤ 100							
					< 3		235		360-510			
				1	3 ≤ t ≤ 16		235				24	
		1.0038			16 < t ≤ 40		225				24	
	S235JRG2 1.0			HR	40 < t ≤ 63		215		340-470		23	27 J at 20°C
EN 10025:1993					$63 < t \le 80$		215		340-470		22	27 J at 20 C
LIN 10025.1995					$80 < t \le 100$		215				22	_
					100 < t ≤ 150		195				22	
					$150 < t \le 200$		185		320-470		21	23 J at 20°C
					$200 < t \le 250$		175		320-470		21	23 J at 20 C
					< 3		235		360-510			
					$3 \le t \le 16$		235				24	
					$16 < t \le 40$		225				24	
					$40 < t \le 63$		215		340-470		23	27 J at 0°C
	S235J0	1.0114		HR	$63 < t \le 80$		215		340-470		22	27 J at 0 C
					$80 < t \le 100$		215				22	
					100 < t ≤ 150		195		-		22	
					150 < t ≤ 200		185		320-470		21	23 J at 0°C
					200 < t ≤ 250		175		320-470		21	

NOTE: This section continued on next page.

53

3.1 Carbon Steels for Structural Steel Plates

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					< 3		235		360-510			
					$3 \le t \le 16$		235				24	
	S235J2G3 1.011				$16 < t \le 40$		225				24	
					$40 < t \le 63$		215		340-510		23	27 J at -20°C
EN 10025:1993		1.0116		N	63 < t ≤ 80		215				22	27 J at -20 C
					80 < t ≤ 100		215				22	
					100 < t ≤ 150		195		340-470		22	
					$150 < t \le 200$		185		320-470		21	23 J at -20°C
					$200 < t \le 250$		175		320-470		21	23 J at -20 C
(Continued)					< 3		235		360-510			
				HR	$3 \le t \le 16$		235		340-470		24	27 J at -20°C
					$16 < t \le 40$		225				24	
					$40 < t \le 63$		215				23	
	S235J2G4	1.0117			63 < t ≤ 80		215				22	
					80 < t ≤ 100		215				22	
					$100 < t \le 150$		195				22	
					$150 < t \le 200$		185		320-470		21	00 1-4 0000
					$200 < t \le 250$		175		320-470		21	23 J at -20°C
	00 [050]				0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					17	
ASTM A 1011/A 1011M-03	36 [250]		- K02502	HR	1.6 ≤ t < 2.5	0.064 ≤ t < 0.097		36	365	53	21	
		1			2.5 ≤ t < 6.0	0.097 ≤ t < 0.230					22	

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,		
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other	
ASTM A 283/A 283M-03	С		K02401				205	30	380-515	55-75	25		
					0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					15		
ASTM A 1011/A 1011M-03	40 [275]		K02502	HR	1.6 ≤ t < 2.5	0.064 ≤ t < 0.097	275	40	380	55	20		
					2.5 ≤ t < 6.0	0.097 ≤ t < 0.230	•				21		
			K02595										
			K02596										
ASTM A 36/A 36M-03a			K02597				250	36	400-550	58-80	23		
			K02598 K02599	-									
					0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					16.0		
	36 [250] Type 2		K02502	HR	1.6 ≤ t < 2.5	0.064 ≤ t < 0.097	250	36	400-550	58-80	20.0		
	Type 2				2.5 ≤ t < 6.0	0.097 ≤ t < 0.230					21.0		
ASTM A 573/A 573M-00a	58 [400]		K02301		≤ 40	≤ 1.5	220	32	400-490	58-71	24		
ASTM A 709/A 709M-03a	36 [250]				≤ 100	≤ 4	250	36	400-550	58-80	23		
	SS400					≤ 16		245				17	
JIS G 3101:1995				HR	16 < t ≤ 40		235		400-510		21		
					> 40		215				23		
					≤ 16		245				18		
					16 < t ≤ 40		235				22		
	SM400A			HR	40 < t ≤ 75		215		400-510		24		
	31VI40UA			I III	75 < t ≤ 100		215		400-510		24		
					100 < t ≤ 160		205				24		
JIS G 3106:1999					160 < t ≤ 200		195				24		
JIS G 3100:1999					≤ 16		245				18		
					16 < t ≤ 40		235				22		
	SM400B			ПБ	40 < t ≤ 75		215		400 540		24	07 1 0+ 000	
	3IVI4UUD			HR _	75 < t ≤ 100		215		400-510		24	27 J at 0°C	
					100 < t ≤ 160		205			24			
				160 < t ≤ 200		195				24			

NOTE: This section continued on next page.

55

3.1 Carbon Steels for Structural Steel Plates

Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section 7	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		245				18	
JIS G 3106:1999 (Continued)					$16 < t \le 40$		235				22	
	SM400C			HR	$40 < t \le 75$		215		400-510		24	47 J at 0°C
					$75 < t \le 100$		215				24	
					100 < t ≤ 200						24	
				HR ≤ 16 235 400-5 16 < t ≤ 40 235 400-5 40 < t ≤ 100 215	≤ 16		235				17	
	SN400A				16 < t ≤ 40		235		400-510		21	
							23					
					≤ 16		235-355				18	
JIS G 3136:1994	SN400B			HR	$16 < t \le 40$		235-355		400-510		22	27 J at 0°C
					40 < t ≤ 100		215-335				24	
				HR	≤ 16						18	27 J at 0°C
	SN400C	400C			$16 < t \le 40$		235-355		400-510		22	
					$40 < t \le 100$		215-335				24	

56

Chapter 3

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		275				00	
					16 < t ≤ 40		265				22	
					40 < t ≤ 63		255				21	
	E 275 A			AR	63 < t ≤ 80		245		410-540		20	
					80 < t ≤ 100		235				20	
					100 < t ≤ 150		225				18	
					150 < t ≤ 200		215				17	
					≤ 16		275				22	
					16 < t ≤ 40		265				22	
100 000 1005	E 275 B				40 < t ≤ 63		255				21	27 J at 20°C
				AR	63 < t ≤ 80		245		410-540		20	
					80 < t ≤ 100		235				20	
				_	100 < t ≤ 150		225				18	
					150 < t ≤ 200		215				17	
ISO 630:1995					≤ 16		275				22	
	E 275 C				16 < t ≤ 40		265					
				AR	40 < t ≤ 63		255		410-540		21	
					63 < t ≤ 80		245				20	27 J at 0°C
					80 < t ≤ 100		235				20	_
					100 < t ≤ 150		225				18	
					150 < t ≤ 200		215				17	
					≤ 16		275				00	
					16 < t ≤ 40		265				22	
				D ₁ : N	40 < t ≤ 63		255				21	
	E 275 D				63 < t ≤ 80		245		410-540		20	27 J at -20°C
				D ₂ : AD	80 < t ≤ 100		235				20	
					100 < t ≤ 150		225				18	
					150 < t ≤ 200		215				17	
ASTM A 283/A 283M-03	D		K02702				230	33	415-550	60-80	23	
					0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					13.0	
ASTM A 1011/A 1011M-03	45 [310]		K02507		1.6 ≤ t < 2.5	0.064 ≤ t < 0.097	310	310 45	415	60	18.0	
					нн	2.5 ≤ t < 6.0	0.097 ≤ t < 0.230		45			19.0

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					< 3		275		430-580			
					$3 \le t \le 16$		275				20	
					16 < t ≤ 40		265				20	
					40 < t ≤ 63		255		410-560		19	27 J at 20°C
	S275JR	1.0044		HR	63 < t ≤ 80		245				18	27 J at 20°C
					80 < t ≤ 100		235				18	
					100 < t ≤ 150		225		400-540		18	
					150 < t ≤ 200		215		380-540		17	02 Lat 20°C
					200 < t ≤ 250		205		380-540		17	23 J at 20°C
					< 3		275		430-580			
					$3 \le t \le 16$		275				20	
					16 < t ≤ 40		265		410-560		20	
				HR	40 < t ≤ 63		255				19	07 1 -+ 000
EN 10025:1993	S275J0	1.0143			63 < t ≤ 80		245				18	27 J at 0°C
					80 < t ≤ 100		235				18	
					100 < t ≤ 150		225		400-540		18	
					150 < t ≤ 200		215		222 542		17	00.1 -+ 000
					200 < t ≤ 250		205		380-540		17	23 J at 0°C
					< 3		275		430-580			
					$3 \le t \le 16$		275				20	
					16 < t ≤ 40		265				20	
					40 < t ≤ 63		255		410-560		19	27 J at -20°C
	S275J2G3	1.0144		N	63 < t ≤ 80		245				18	
					80 < t ≤ 100		235				18	1
					100 < t ≤ 150		225		400-540		18	
					150 < t ≤ 200		215				17	00.1.1.5555
					200 < t ≤ 250		205		380-540		17	23 J at -20°C

NOTE: This section continued on next page.

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					< 3		275		430-580			
					3 ≤ t ≤ 16		275				20	
					16 < t ≤ 40		265		410-560		20	
					40 < t ≤ 63		255			19	27 J at -20°C	
EN 10025:1993 (Continued)	S275J2G4	1.0145		HR	63 < t ≤ 80		245				18	21 J at -20 C
(Continued)					80 < t ≤ 100		235				18	
					100 < t ≤ 150		225		400-540		18	
					150 < t ≤ 200		215		200 540		17	00 Let 000C
					200 < t ≤ 250		205		380-540		17	23 J at -20°C
					0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					11.0	
ASTM A 1011/A 1011M-03	50 [340]		K02507	HR	1.6 ≤ t < 2.5	0.064 ≤ t < 0.097	340	50	450 65	65	16.0	
					2.5 ≤ t < 6.0	0.097 ≤ t < 0.230					17.0	
ASTM A 573/A 573M-00a	65 [450]		K02404		≤ 40	≤ 1.5	240	35	450-530	65-77	23	

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	- Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 529/A 529M-03	50 [345]		K02703		≤ 25	≤ 1	345	50	405.000	70-100	21	
ASTIVI A 529/A 529IVI-U3	55 [380]		K02703		≤ 25	≤ 1	380	55	485-690	70-100	20	
					0.65 ≤ t < 1.6	0.025 ≤ t < 0.064					9.0	
ASTM A 1011/A 1011M-03	55 [380]		K02507	HR	1.6 ≤ t < 2.5	0.064 ≤ t < 0.097	380	55	480	70	14.0	
					2.5 ≤ t < 6.0	0.097 ≤ t < 0.230					15.0	
ASTM A 573/A 573M-00a	70 [485]		K02701		≤ 40	≤ 1.5	290	42	485-620	70-90	21	
ASTM A 678/A 678M-00a	А		K01600	QT	≤ 20	≤ 3⁄4	345	50	485-620	70-90	22	
ASTIVI A 070/A 070IVI-00a	A		KUTOUU	Qi	20 < t ≤ 40	3⁄4 < t ≤ 11⁄2	345	50	465-620	70-90	22	
					≤ 16		285				15	
JIS G 3101:1995	SS490			HR	16 < t ≤ 40		275		490-610		19	
					> 40		255				21	
					≤ 16		325				17	
					$16 < t \le 40$		315				21	
	SM490A			HR	$40 < t \le 75$		295		490-610		23	
	31V149UA			III	$75 < t \le 100$		295		490-610		23	
					$100 < t \le 160$		285				23	
					$160 < t \le 200$		275				23	
					≤ 16		325				17	
					$16 < t \le 40$		315				21	
JIS G 3106:1999	SM490B			HR	$40 < t \le 75$		295		490-610		23	27 J at 0°C
	310149015			III	$75 < t \le 100$		295		490-610		23	27 J at 0 C
					$100 < t \le 160$		285				23	
					$160 < t \le 200$		275				23	
					≤ 16		325				17	
					16 < t ≤ 40		315				21	
	SM490C			HR	40 < t ≤ 75		295		490-610		23	47 J at 0°C
					75 < t ≤ 100		295				23	
					100 < t ≤ 200						23	

NOTE: This section continued on next page.

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section Th	ickness	Yield Strei	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		365				15	
	SM490YA			HR	16 < t ≤ 40		355		400.040		19	
	51V149U Y A			пп	40 < t ≤ 75		335		490-610		21	
JIS G 3106:1999					75 < t ≤ 100		325				21	
(Continued)					≤ 16		365				15	
	SM490YB			HR	16 < t ≤ 40		355		490-610		19	27 J at 0°C
	3101490116			пп	40 < t ≤ 75		335		490-610		21	27 J at 0°C
					75 < t ≤ 100		325				21	
					≤ 16		325-445				17	
	SN490B			HR	16 < t ≤ 40		325-445		490-610		21	27 J at 0°C
JIS G 3136:1994					40 < t ≤ 100		295-415				23	
JIS G 3130.1994					≤ 16						17	
	SN490C			HR	16 < t ≤ 40		325-445		490-610		21	27 J at 0°C
					40 < t ≤ 100		295-415				23	
					< 3		295		490-660			
					3 ≤ t ≤ 16		295				18	
					16 < t ≤ 40		285				18	
					40 < t ≤ 63		275		470-610		17	
EN 10025:1993	E 295	1.0050		HR	63 < t ≤ 80		265				16	
					80 < t ≤ 100		255				16	
					100 < t ≤ 150		245		450-610		15	
					150 < t ≤ 200		235		440-610		14	
					200 < t ≤ 250		225		440-610		14	
					≤ 16		355				22	
					16 < t ≤ 40		345				22	
					40 < t ≤ 63		335				21	
ISO 630:1995	E 355 C			AR	63 < t ≤ 80		325		490-640		20	27 J at 0°C
					80 < t ≤ 100		315				20	
					100 < t ≤ 150		295				18	
					150 < t ≤ 200		285		7		17	

NOTE: This section continued on next page.

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		355				22	
					16 < t ≤ 40		345				22	
				D₁: N	40 < t ≤ 63		335				21	
ISO 630:1995 (Continued)	E 355 D				63 < t ≤ 80		325		490-640		20	27 J at -20°C
(Oorininaca)				D ₂ : AD	80 < t ≤ 100		315				20	
					100 < t ≤ 150		295				18	
					150 < t ≤ 200		285				17	

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section Th	nickness	Yield Strei	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					< 3		355		510-680			
					$3 \le t \le 16$		355				20	
					16 < t ≤ 40		345				20	
					40 < t ≤ 63		335		490-630		19	27 J at 20°C
	S355JR	1.0045		HR	63 < t ≤ 80		325				18	27 J at 20 C
					80 < t ≤ 100		315				18	
					100 < t ≤ 150		295		470-630		18	
					150 < t ≤ 200		285		450,000		17	00 1 -+ 0000
					200 < t ≤ 250		275		450-630		17	23 J at 20°C
					< 3		355		510-680			
					$3 \le t \le 16$		355				20	
					16 < t ≤ 40		345				20	
					40 < t ≤ 63		335		490-630		19	07 1 -+ 000
EN 10025:1993	S355J0	1.0553		HR	63 < t ≤ 80		325				18	27 J at 0°C
					80 < t ≤ 100		315				18	
					100 < t ≤ 150		295		470-630		18	
					150 < t ≤ 200		285		450,620		17	00 1 at 000
					200 < t ≤ 250		275		450-630		17	23 J at 0°C
					< 3		355		510-680			
					$3 \le t \le 16$		355				20	
					16 < t ≤ 40		345				20	
					40 < t ≤ 63		335		490-630		19	07 Let 0000
	S355J2G3	1.0570		N	63 < t ≤ 80		325				18	27 J at -20°C
					80 < t ≤ 100		315				18	1
					100 < t ≤ 150		295		470-630		18	1
					150 < t ≤ 200		285		450,000		17	00 1 -1 0000
					200 < t ≤ 250		275		450-630		17	23 J at -20°C

NOTE: This section continued on next page.

3.1A Mechanical Properties of Carbon Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section Th	nickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					< 3		355		510-680			
					3 ≤ t ≤ 16		355				20	
					16 < t ≤ 40		345				20	
					40 < t ≤ 63		335		490-630		19	27 J at -20°C
	S355J2G4	1.0577		HR	63 < t ≤ 80		325				18	27 J at -20 C
					80 < t ≤ 100		315				18	
					100 < t ≤ 150		295		470-630		18	
					150 < t ≤ 200		285		450-630		17	23 J at -20°C
					200 < t ≤ 250		275		450-630		17	23 J at -20°C
					< 3		355		510-680			
					3 ≤ t ≤ 16		355				20	
					16 < t ≤ 40		345				20	
=					40 < t ≤ 63		335		490-630		19	40 J at -20°C
EN 10025:1993 (Continued)	S355K2G3	1.0595		HR	63 < t ≤ 80		325				18	40 J at -20°C
(Continued)					80 < t ≤ 100		315				18	
					100 < t ≤ 150		295		470-630		18	
					150 < t ≤ 200		285		450-630		17	33 J at -20°C
					200 < t ≤ 250		275		450-630		17	33 J at -20°C
					< 3		355		510-680			
					3 ≤ t ≤ 16		355				20	
					16 < t ≤ 40		345				20	
					40 < t ≤ 63		335		490-630		19	40 1 -+ 0000
	S355K2G4	1.0596		HR	63 < t ≤ 80		325				18	40 J at -20°C
					80 < t ≤ 100		315				18	
					100 < t ≤ 150		295		470-630		18	1
					150 < t ≤ 200		285		450,000		17	00 1 -1 0000
					200 < t ≤ 250		275		450-630		17	33 J at -20°C

NOTE: This section continued on next page.

Standard	Grade, Class,	Steel	UNS	Heat	Section 1	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		365				15	
	SM520B			HR	$16 < t \le 40$		355		520-640		19	27 J at 0°C
	310132013			III	$40 < t \le 75$		335		520-640		21	27 J at 0 C
JIS G 3106:1999					$75 < t \le 100$		325				21	
013 G 3100.1999					≤ 16		365				15	
	SM520C			HR	16 < t ≤ 40		355		520-640		19	47 J at 0°C
	31015200			ПN	40 < t ≤ 75		335		520-640		21	47 J at 0°C
					75 < t ≤ 100		325				21	
					≤ 16		400				13	
JIS G 3101:1995	SS540			HR	16 < t ≤ 40		390		540		17	
					> 40							
					t ≤ 20	t ≤ ¾						
STM A 678/A 678M-00a	В		K00000	QT	20 < t ≤ 40	³⁄4 < t ≤ 1½	415	60	550-690	80-100	22	
ASTIVI A 0/0/A 0/01VI-0Ua	В		K02002	Q1	40 < t ≤ 50	1½ < t ≤ 2	415	00	550-690	60-100	22	
					50 < t ≤ 65	2 < t ≤ 2½						

Chapter 3

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		460				19	
					16 < t ≤ 20		450				26	
JIS G 3106:1999	SM570			HR	20 < t ≤ 40		450		570-720		20	47 J at -5°C
					40 < t ≤ 75		430				20	
					75 < t ≤ 100		420				20	
					< 3		335		590-770			
					3 ≤ t ≤ 16		335				14	
					16 < t ≤ 40		325				14	
					40 < t ≤ 63		315		570-710		13	
EN 10025:1993	E 335	1.0060		HR	63 < t ≤ 80		305				12	
					80 < t ≤ 100		295				12	
					100 < t ≤ 150		275		550-710		11	
					150 < t ≤ 200		265		540-710		10	
					200 < t ≤ 250		255		540-710		10	
					t ≤ 20	t ≤ ¾	515	75	655-790	95-115		
ASTM A 678/A 678M-00a	С		K02204	QT	$20 < t \le 40$	3⁄4 < t ≤ 11⁄2	485	70	620-760	90-110	19	
					$40 < t \le 50$	$1\frac{1}{2} < t \le 2$	450	65	585-720	85-105		
					< 3		360		690-900			
					$3 \le t \le 16$		360				10	
					$16 < t \le 40$		355				10	
					40 < t ≤ 63		345		670-830		9	
EN 10025:1993	E 360	1.0070		HR	63 < t ≤ 80		335				8	
					80 < t ≤ 100		325				8	
					100 < t ≤ 150		305		650-830		7	
					150 < t ≤ 200		295		640-830		6	
					200 < t ≤ 250		285		040-030		6	

3.1 Carbon Steels for Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	6, Maximuı	n, Unless	Otherwise	Specified	I
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ISO 630:1995	E 185													
ASTM A 283/A 283M-03	Α			≤ 40	≤ 1.5	0.14	0.90	0.40	0.035	0.04				
A3 1 W A 203/A 203W-03	A			> 40	> 1.5	0.14	0.90	0.15-0.40	0.035	0.04				
EN 10025:1993	S185	1.0035		≤ 16										
JIS G 3101:1995	SS330								0.050	0.050				
ASTM A 1011/A 1011M-03	30 [205]		K02502	≤ 6.0	≤ 0.229	0.25	0.90	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
	E 235 A					0.22			0.050	0.050				
				≤ 16		0.17	1.40	0.40	0.045	0.045				
	E 235 B			16 < t ≤ 25		0.20	1.40	0.40	0.045	0.045				
ISO 630:1995	E 230 B		1	≤ 40		0.17	1.40	0.40	0.045	0.045				Non-rimming
				> 40		0.20	1.40	0.40	0.045	0.045				Non-rimming
	E 235 C					0.17	1.40	0.40	0.040	0.040				Non-rimming
	E 235 D					0.17	1.40	0.40	0.035	0.035				Fine-grained
ASTM A 283/A 283M-03	В			≤ 40	≤ 1.5	0.17	0.90	0.40	0.035	0.04				
MO I IVI M 200/M 2001VI-U3	D			> 40	> 1.5	0.17	0.90	0.15-0.40	0.035	0.04				

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	6, Maximu	m, Unless	Otherwise	e Specified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 1011/A 1011M-03	33 [230]		K02502	≤ 6.0	≤ 0.229	0.25	0.90	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
	S235JR	1.0037		≤ 16		0.17	1.40		0.045	0.045				N 0.009
	32330H	1.0037		$16 < t \le 40$		0.20	1.40		0.045	0.045				N 0.009
	S235JRG1	1.0036		≤ 16		0.17	1.40		0.045	0.045				N 0.007
	3233JNG1	1.0036		16 < t ≤ 40		0.20	1.40		0.045	0.045				N 0.007
				≤ 16		0.17	1.40		0.045	0.045				N 0.009
	S235JRG2	1.0038		16 < t ≤ 40		0.17	1.40		0.045	0.045				N 0.009
				> 40		0.20	1.40		0.045	0.045				N 0.009
EN 40005-4000				≤ 16		0.17	1.40		0.040	0.040				N 0.009
EN 10025:1993	S235J0	1.0114		16 < t ≤ 40		0.17	1.40		0.040	0.040				N 0.009
				> 40		0.17	1.40		0.040	0.040				N 0.009
				≤ 16		0.17	1.40		0.035	0.035				
	S235J2G3	1.0116		16 < t ≤ 40		0.17	1.40		0.035	0.035				
				> 40		0.17	1.40		0.035	0.035				
				≤ 16		0.17	1.40		0.035	0.035				
	S235J2G4	1.0117		16 < t ≤ 40		0.17	1.40		0.035	0.035				
				> 40		0.17	1.40		0.035	0.035				
ASTM A 1011/A 1011M-03	36 [250] Type 1		K02502	≤ 6.0	≤ 0.229	0.25	0.90	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard

3.1 Carbon Steels for Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	%, Maximur	n, Unless	Otherwise	Specifie	d
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 283/A 283M-03	С		K02401	≤ 40	≤ 1.5	0.24	0.90	0.40	0.035	0.04				
A3 1 W A 203/A 203 W - U3	C		K02401	> 40	> 1.5	0.24	0.90	0.15-0.40	0.035	0.04				
ASTM A 1011/A 1011M-03	40 [275]		K02502	≤ 6.0	≤ 0.229	0.25	0.90	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
			K02595	≤ 20	≤ 3/4	0.25		0.40	0.04	0.05				
			K02596	20 < t ≤ 40	³ ⁄ ₄ < t ≤ 1½	0.25	0.80-1.20	0.40	0.04	0.05				
ASTM A 36/A 36M-03a			K02597	40 < t ≤ 65	1½ < t ≤ 2½	0.26	0.80-1.20	0.15-0.40	0.04	0.05				
			K02598	65 < t ≤ 100	2½ < t ≤ 4	0.27	0.85-1.20	0.15-0.40	0.04	0.05				
			K02599-	> 100	> 4	0.29	0.85-1.20	0.15-0.40	0.04	0.05				
ASTM A 1011/A 1011M-03	36 [250] Type 2		K02502	≤ 6.0	≤ 0.229	0.25	1.35	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Si, Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
ASTM A 573/A 573M-00a	58 [400]		K02301	≤ 13	≤ 1/2	0.23	0.60-0.90	0.10-0.35	0.035	0.04				
A31101 A 373/A 373001-00a	30 [400]		102301	13 < t ≤ 40	½ < t ≤ 1½	0.23	0.60-0.90	0.10-0.35	0.035	0.04				
				≤ 20	≤ 3/4	0.25		0.40	0.04	0.05				
ASTM A 709/A 709M-03a	36 [250]			20 < t ≤ 40	$\frac{3}{4} < t \le 1\frac{1}{2}$	0.25	0.80-1.20	0.40	0.04	0.05				
AO 1101 A 709/A 709101-00a	30 [230]			40 < t ≤ 65	1½< t ≤2½	0.26	0.80-1.20	0.15-0.40	0.04	0.05				
				65 < t ≤ 100	$2\frac{1}{2} < t \le 4$	0.27	0.85-1.20	0.15-0.40	0.04	0.05				
JIS G 3101:1995	SS400								0.050	0.050				
	SM400A			≤ 50		0.23	2.5xC min		0.035	0.035				
	OWHOOA			50 < t ≤ 200		0.25	2.5xC min		0.035	0.035				
JIS G 3106:1999	SM400B			≤ 50		0.20	0.60-1.40	0.35	0.035	0.035				
	31414000			50 < t ≤ 200		0.22	0.60-1.40	0.35	0.035	0.035				
	SM400C			≤ 100		0.18	1.40	0.35	0.035	0.035				
	SN400A			6 ≤ t ≤ 100		0.24			0.050	0.050				
	SN400B			6 ≤ t ≤ 50		0.20	0.60-1.40	0.35	0.030	0.015				
JIS G 3136:1994	3114000			50 < t ≤ 100		0.22	0.60-1.40	0.35	0.030	0.015				
	SN400C			16 ≤ t ≤ 50		0.20	0.60-1.40	0.35	0.020	0.008				
	3144000			50 < t ≤ 100		0.22	0.60-1.40	0.35	0.020	0.008				

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	, Maximu	m, Unless	Otherwise	Specified	I
Designation	Type, Symbol or Name		Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	E 275 A					0.24			0.050	0.050				
	E 075 D			≤ 40		0.21	1.50	0.40	0.045	0.045				Non-rimming
ISO 630:1995	E 275 B			> 40		0.22	1.50	0.40	0.045	0.045				Non-rimming
	E 275 C					0.20	1.50	0.40	0.040	0.040				Non-rimming
	E 275 D					0.20	1.50	0.40	0.035	0.035				Fine-grained
ASTM A 283/A 283M-03	<u> </u>		K02702	≤ 40	≤ 1.5	0.27	0.90	0.40	0.035	0.04				
ASTM A 283/A 283M-03	D		K02702	> 40	> 1.5	0.27	0.90	0.15-0.40	0.035	0.04				
ASTM A 1011/A 1011M-03	45 [310]		K02507	≤ 6.0	≤ 0.229	0.25	1.35	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
				≤ 16		0.21	1.50		0.045	0.045				N 0.009
	S275JR	1.0044		16 < t ≤ 40		0.21	1.50		0.045	0.045				N 0.009
				> 40		0.22	1.50		0.045	0.045				N 0.009
				≤ 16		0.18	1.50		0.040	0.040				N 0.009
	S275J0	1.0143		16 < t ≤ 40		0.18	1.50		0.040	0.040				N 0.009
EN 10025:1993				> 40		0.18	1.50		0.040	0.040				N 0.009
EN 10025:1993				≤ 16		0.18	1.50		0.035	0.035				
	S275J2G3	1.0144		16 < t ≤ 40		0.18	1.50		0.035	0.035				
				> 40		0.18	1.50		0.035	0.035				
				≤ 16		0.18	1.50		0.035	0.035				
	S275J2G4	1.0145		16 < t ≤ 40		0.18	1.50		0.035	0.035				
				> 40		0.18	1.50		0.035	0.035				
ASTM A 1011/A 1011M-03	50 [340]		K02507	≤ 6.0	≤ 0.229	0.25	1.35	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
ASTM A 573/A 573M-00a	65 [450]		K02404	≤ 13	≤ 1/2	0.24	0.85-1.20	0.15-0.40	0.035	0.04				
10 1 W A 37 0/A 37 0W-00a	03 [430]		1102404	13 < t ≤ 40	½ < t ≤ 1½	0.26	0.85-1.20	0.15-0.40	0.035	0.04				

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	6, Maximu	n, Unless	Otherwise	Specified	i
Designation	Type, Symbol or Name		Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 529/A 529M-03	50 [345]		K02703	≤ 25	≤1	0.27	1.35	0.40	0.04	0.05				
ASTIVI A 529/A 529/VI-03	55 [380]		K02703	≤ 25	≤ 1	0.27	1.35	0.40	0.04	0.05				
ASTM A 1011/A 1011M-03	55 [380]		K02507	≤ 6.0	≤ 0.229	0.25	1.35	report value	0.035	0.04	0.15	0.20	0.06	Cb 0.008; V 0.008; Al report value; Cu see standard; Cu + Ni + Cr + Mo 0.50; Cr + Mo see standard
ASTM A 573/A 573M-00a	70 [485]		K02701	≤ 13	≤ 1/2	0.27	0.85-1.20	0.15-0.40	0.035	0.04				
ASTIVI A 575/A 575/VI-00a	70 [465]		K02701	13 < t ≤ 40	½ < t ≤ 1½	0.28	0.85-1.20	0.15-0.40	0.035	0.04				
ASTM A 678/A 678M-00a	Α		K01600	≤ 40	≤ 1½	0.16	0.90-1.50	0.15-0.50	0.035	0.04				
JIS G 3101:1995	SS490								0.050	0.050				
	SM490A			≤ 50		0.20	1.60	0.55	0.035	0.035				
	SIVI490A			50< t ≤ 200		0.22	1.60	0.55	0.035	0.035				
	SM490B			≤ 50		0.18	1.60	0.55	0.035	0.035				
JIS G 3106:1999	SIVI490B			50< t ≤ 200		0.20	1.60	0.55	0.035	0.035				
	SM490C			≤ 100		0.18	1.60	0.55	0.035	0.035				
	SM490YA			≤ 100		0.20	1.60	0.55	0.035	0.035				
	SM490YB			≤ 100		0.20	1.60	0.55	0.035	0.035				
	SN490B			6 ≤ t ≤ 50		0.18	1.60	0.55	0.030	0.015				
110 0 0400 4004	SIN490D			50 < t ≤ 100		0.20	1.60	0.55	0.030	0.015				
JIS G 3136:1994	CNI400C			16 ≤ t ≤ 50		0.18	1.60	0.55	0.020	0.008				
	SN490C			50 < t ≤ 100		0.20	1.60	0.55	0.020	0.008				
EN 10025:1993	E295	1.0050							0.045	0.045				N 0.009
	E 355 C			≤ 30		0.20	1.60	0.55	0.040	0.040				non-rimming
ICO 620-100E	E 355 C			> 30		0.22	1.60	0.55	0.040	0.040				non-rimming
ISO 630:1995	E 355 D			≤ 30		0.20	1.60	0.55	0.035	0.035				fine-grained
	E 333 D			> 30		0.22	1.60	0.55	0.035	0.035				fine-grained

Standard	Grade, Class,	Steel	UNS	Section 1	Thickness			,	Weight, %	, Maximur	n, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
				≤ 16		0.24	1.60	0.55	0.045	0.045				N 0.009
	S355JR	1.0045		16 < t ≤ 40		0.24	1.60	0.55	0.045	0.045				N 0.009
				> 40		0.24	1.60	0.55	0.045	0.045				N 0.009
				≤ 16		0.20	1.60	0.55	0.040	0.040				N 0.009
	S355J0	1.0553		16 < t ≤ 40		0.20	1.60	0.55	0.040	0.040				N 0.009
				> 40		0.22	1.60	0.55	0.040	0.040				N 0.009
				≤ 16		0.20	1.60	0.55	0.035	0.035				
	S355J2G3	1.0570		16 < t ≤ 40		0.20	1.60	0.55	0.035	0.035				
EN 10025:1993				> 40		0.22	1.60	0.55	0.035	0.035				
EN 10025.1995				≤ 16		0.20	1.60	0.55	0.035	0.035				
	S355J2G4	1.0577		16 < t ≤ 40		0.20	1.60	0.55	0.035	0.035				
				> 40		0.22	1.60	0.55	0.035	0.035				
				≤ 16		0.20	1.60	0.55	0.035	0.035				
	S355K2G3	1.0595		16 < t ≤ 40		0.20	1.60	0.55	0.035	0.035				
				> 40		0.22	1.60	0.55	0.035	0.035				
				≤ 16		0.20	1.60	0.55	0.035	0.035				
	S355K2G4	1.0596		16 < t ≤ 40		0.20	1.60	0.55	0.035	0.035				
				> 40		0.22	1.60	0.55	0.035	0.035				
JIS G 3106:1999	SM520B			≤ 100		0.20	1.60	0.55	0.035	0.035				
015 G 3106.1999	SM520C			≤ 100		0.20	1.60	0.55	0.035	0.035				
JIS G 3101:1995	SS540					0.30	1.60		0.040	0.040				
ASTM A 678/A 678M-00a	В		K02002	≤ 40	≤ 1½	0.20	0.70-1.35	0.15-0.50	0.035	0.04				
ASTIVI A 0/0/A 0/01VI-0Ua	В		K02002	40 < t ≤ 65	1½ < t ≤ 2½	0.20	1.00-1.60	0.15-0.50	0.035	0.04				
JIS G 3106:1999	SM570			≤ 100		0.18	1.60	0.55	0.035	0.035				
EN 10025:1993	E 335	1.0060							0.045	0.045				N 0.009
ASTM A 678/A 678M-00a	С		K02204	≤ 40	≤ 1½	0.22	1.00-1.60	0.20-0.50	0.035	0.04				
A3 I IVI A 0/0/A 0/0IVI-UUA			NU22U4	40 < t ≤ 65	1½ < t ≤ 2½	0.22	1.00-1.60	0.20-0.50	0.035	0.04				
EN 10025:1993	E 360	1.0070							0.045	0.045				N 0.009

Mechanical Properties of High-Strength Low-Alloy Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Florestion	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
					≤ 65	≤ 2½	260	38				
	260WT (38WT)				65 < t ≤ 100	2½ < t ≤ 4	250	36	410-590	60-85	23	see standard for impact data
	, ,				100 < t ≤ 150	4 < t ≤ 6	250	36				ior impact data
CSA G40.21-04					≤ 65	≤ 2½	260	38				
	000144 (00144)				65 < t ≤ 100	2½ < t ≤ 4	250	36	440.500	00.05		
	260W (38W)				100 < t ≤ 150	4 < t ≤ 6	250	36	410-590	60-85	23	
					150 < t ≤ 200	6 < t ≤ 8	250	36				
	45 [310]			LID	< 2.5	< .097	040	45	110	00	23.0	
ACTM A 4044/A 4044M 00	Class 1			HR	> 2.5	> .097	310	45	410	60	25.0	
ASTM A 1011/A 1011M-03	50 [340]			HR	< 2.5	< .097	340		440		20.0	
	Class 2			пн	> 2.5	> .097	340	50	410	60	22.0	
ASTM A 572/A 572M-03a	42 [290]				≤ 150	≤ 6	290	42	415	60	24	
ASTM A 656/A 656M-03	50 [345]			HR	≤ 50	≤ 2	345	50	415	60	23	
					≤ 65	≤ 2.5						see standard for
ASTM A 633/A 633M-01	А		K01802	N	65 < t ≤ 100	2.5 < t ≤ 4	290	42	430-570	63-83	23	supplementary impact testing
ASTM A 709/A 709M-03a	50 [345]				≤ 100	≤ 4	345	50	450	65	21	
ASTM A 572/A 572M-03a	50 [345]				≤ 100	≤ 4	345	50	450	65	21	
	50 [340]			HR	< 2.5	< .097	340	50	450	65	20.0	
ASTM A 1011/A 1011M-03	Class 1			III	> 2.5	> .097	340	50	450	65	22.0	
ASTIVI A TOTT/A TOTTIVI-US	55 [380]			HR	< 2.5	< .097	380	55	450	65	18.0	
	Class 2			пн	> 2.5	> .097	360	55	450	65	20.0	
					t ≤ 16		355					
	S355M	1.8823		TMCP	16 < t ≤ 40		345		450-610		22	see standard for impact data
EN 10113-3:1993					40 < t ≤ 63		335					ioi iiipaoi data
EN 10113-3.1993					t ≤ 16		355					
	S355ML	1.8834		TMCP	16 < t ≤ 40		345		450-610		22	see standard for impact data
					40 < t ≤ 63		335					ioi iiipaci uala
					≤ 65	≤ 2½	300	44				
(300WT (44WT)				65 < t ≤ 100	2½ < t ≤ 4	280	40	450-620	65-90	23	see standard for impact data
					100 < t ≤ 150	4 < t ≤ 6	280	40				ioi iiipaci uala
CSA G40.21-04					≤ 65	≤ 2½	300	44				
	00014/ (4.4140				65 < t ≤ 100	2½ < t ≤ 4	280	40	450.000	05.00	00	
	300W (44W)				100 < t ≤ 150	4 < t ≤ 6	280	40	450-620	65-90	23	
					150 < t ≤ 200	6 < t ≤ 8	280	40				

Mechanical Properties of High-Strength Low-Alloy Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					t ≤ 16		355					
					16 < t ≤ 40		345					
	S355N	1.0545		N	40 < t ≤ 63		335		470-630		22	see standard
	232211	1.0545		IN	63 < t ≤ 80		325				22	for impact data
					80 < t ≤ 100		315					
EN 10113-2:1998					100 < t ≤ 150		295		450-600			
EN 10113-2:1996					t ≤ 16		355					
					16 < t ≤ 40		345					
	0055811	4.05.40		N.	40 < t ≤ 63		335		470-630		22	see standard
	S355NL	1.0546		N	63 < t ≤ 80		325					for impact data
					80 < t ≤ 100		315					
					100 < t ≤ 150		295		450-600			
					t ≤ 20	t ≤ 3⁄4	345	50	480	70		
ASTM A 242/A 242M-03a			K11510		20 < t ≤ 40	³ ⁄ ₄ < t ≤ 1½	315	46	460	67	21	
					40 < t ≤ 100	1½ < t ≤ 4	290	42	435	63		
	55 [380]			HR	< 2.5	< .097	380	55	480	70	18.0	
ASTM A 1011/A 1011M-03	Class 1			пп	> 2.5	> .097	380	55	460	70	20.0	
AOTIMA TOTTIA TOTTIM OO	60 [410]			HR	< 2.5	< .097	410	60	480	70	16.0	
	Class 2				> 2.5	> .097			100	, 0	18.0	
	350WT (50WT)				≤ 65	≤ 2½	350	50	480-650	70-95	22	see standard
	,				65 < t ≤ 150	2½ < t ≤ 6	320	46	.00 000	7000		for impact data
CSA G40.21-04					≤ 65	≤ 21/2	350	50				
	350W (50W)				65 < t ≤ 100	2½ < t ≤ 4	320	46	450-650	65-95	22	
	00014/ (5514/)				100 < t ≤ 150	4 < t ≤ 6	320	46	400.050	70.05	04	
AOTM A 570/A 570M 00-	380W (55W)				≤ 65	≤ 2½	380	55	480-650	70-95	21	
ASTM A 572/A 572M-03a	55 [380]				≤ 50	≤ 2	380	55	485	70	20	
ASTM A 656/A 656M-03	60 [415]		 K11430	HR	≤ 40	≤ 1½	415	60	485	70	20	
AOTNA A 500/A 500N4 00	A B		K11430 K12043		t ≤ 100	t ≤ 4	345	50	485	70	-	
ASTM A 588/A 588M-03a	C		K11538		100 < t ≤ 125	4 < t ≤ 5	315	46	460	67	21	
	K				125 < t ≤ 200	5 < t ≤ 8	290	42	435	63		

NOTE: This section continued on next page.

Mechanical Properties of High-Strength Low-Alloy Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section	n Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	С		K12000	N	≤ 65	≤ 2.5	345	50	485-620	70-90	23	see standard for
ACTM A COO/A COOM O4			K12000	IN .	$65 < t \le 100$	$2.5 < t \leq 4$	315	46	450-590	65-85	23	supplementary impact testing
ASTM A 633/A 633M-01	_				≤ 65	≤ 2.5	345	50	485-620	70-90		see standard for
	D		K12037	N	65 < t ≤ 100	2.5 < t ≤ 4	315	46	450-590	65-85	23	supplementary impact testing
					t ≤ 16		420					
	S420M	1.8825		TMCP	16 < t ≤ 40		400		500-660		19	see standard for impact data
EN 10110 0:1000					40 < t ≤ 63		390					Tor impact data
EN 10113-3:1993					t ≤ 16		420					
	S420ML	1.8836		TMCP	16 < t ≤ 40		400		500-660		19	see standard for impact data
					40 < t ≤ 63		390					Tor impact data
ASTM A 572/A 572M-03a	60 [415]				≤ 32	≤ 11⁄4	415	60	520	75	18	
	60 [410]			HR	< 2.5	< .097	410	60	520	75	16.0	
ASTM A 1011/A 1011M-03	Class 1			III	> 2.5	> .097	410		320	75	18.0	
ASTIMATOTI/ATOTIM-03	65 [450]			HR	< 2.5	< .097	410	60	520	75	16.0	
	Class 2				> 2.5	> .097			020		18.0	
CSA G40.21-04	400WT (60WT)			AR	≤ 65	≤ 2½	400	60	520-690	75-100	20	see standard for impact data
	400W (60W)				≤ 65	≤ 2½	400	60	520-690	75-100	18	
ASTM A 572/A 572M-03a	65 [450]				≤ 32	≤ 11⁄4	450	65	550	80	17	
A CTM A COO/A COOM O4	_		K10000	N < 3 in.	t ≤ 100	t ≤ 4	415	60	550-690	80-100	23	see standard for
ASTM A 633/A 633M-01	E		K12202	N+N > 3 in. (75 mm)	100 < t ≤ 150	4 < t ≤ 6	380	55	515-655	75-95	23	supplementary impact testing
ASTM A 656/A 656M-03	70 [485]			HR	≤ 25	≤ 1	485	70	550	80	17	
	65 [450]			HB	< 2.5	< .097	450	65	550	80	14.0	
ASTM A 1011/A 1011M-03	Class 1			1111	> 2.5	> .097	450		330		16.0	
7.3.1 7. 1011/7. 1011W 00	70 [480]			HR	< 2.5	< .097	480	70	550	80	12.0	
	Class 2				> 2.5	> .097	.00	. •			14.0	

3.2.1B Chemical Composition of High-Strength Low-Alloy Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, 9	%, Maximu	m, Unless	Otherwise	e Specifie	d
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	s	Cr	Ni	Мо	Others
	260WT (38WT)					0.20	0.80-1.50	0.15-0.40	0.03	0.04				grain refining elements 0.10
CSA G40.21-04	260W (38W)			≤ 40 > 40	≤ 1½ > 1½	0.20	0.50-1.50	0.40	0.04	0.05				grain refining elements 0.10
	,			>100	> 4	0.22		0.15-0.40						3 3
	42 [290] Type 1			≤ 40 40 < t ≤ 150	≤ 1½ 1½ < t ≤ 6	0.21	1.35	0.40 0.15-0.40	0.04	0.05				Cb 0.005-0.05
				40 < t ≤ 130 ≤ 40	172 < 1 ≤ 0 ≤ 1½			0.13-0.40						
	42 [290] Type 2			± 40 40 < t ≤ 150		0.21	1.35	0.15-0.40	0.04	0.05				V 0.01-0.15
ASTM A 572/A 572M-03a	42 [290] Type 3			≤ 40 40 < t ≤ 150	≤ 1½ 1½ < t ≤ 6	0.21	1.35	0.40 0.15-0.40	0.04	0.05				Cb 0.005-0.05; V 0.01-0.15; Cb + V 0.02-0.15
	42 [290] Type 4			≤ 40 40 < t ≤ 150	≤ 1½ 1½ < t ≤ 6	0.21	1.35	0.40 0.15-0.40	0.04	0.05				V 0.01-0.15; N 0.015 V:N > 4:1
	42 [290] Type 5			≤ 40 40 < t ≤ 150	≤ 1½ 1½ < t ≤ 6	0.21	1.35	0.40 0.15-0.40	0.04	0.05				Ti 0.006-0.04; N 0.003-0.015; V 0.06
ASTM A 656/A 656M-03	50 [345] Type 3					0.18	1.65	0.60	0.025	0.035				V 0.08; N 0.020; Cb 0.008-0.10
ASTIVI A 656/A 656/VI-05	50 [345] Type 7					0.18	1.65	0.60	0.025	0.035				V 0.15; N 0.020; Cb 0.10
ASTM A 633/A 633M-01	Α		K01802	≤ 100	≤ 4	0.18	1.00-1.35	0.15-0.50	0.035	0.04				Cb 0.05
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				Cb 0.005-0.05
	Type 1			40 < t ≤ 100		0.23	1.35	0.15-0.40	0.04	0.05				
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				V 0.01-0.15
	Type 2			40 < t ≤ 100		0.23	1.35	0.15-0.40	0.04	0.05				
ASTM A 709/A 709M-03a	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				Cb 0.005-0.05; V 0.01-0.15;
rio i in ri rioo, ri rioomi ood	Type 3			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.35	0.15-0.40	0.04	0.05				Cb + V 0.02-0.15
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				V 0.01-0.15; N 0.015
	Type 4			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.35	0.15-0.40	0.04	0.05				V:N > 4:1
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				Ti 0.006-0.04; V 0.01-0.15;
Tell	Type 5			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.35	0.15-0.40	0.04	0.05				N 0.015

NOTE: This section continued on next page

3.2.1B Chemical Composition of High-Strength Low-Alloy Structural Steel Plates (Continued)

Standard	Grade, Class,		UNS	Section T	hickness				Weight, 9	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				Cb 0.005-0.05
	Type 1			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.33	0.15-0.40	0.04	0.05		_ 		CD 0.005-0.05
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				V 0.01-0.15
	Type 2			40 < t ≤ 100	1½ < t ≤ 4	0.20	1.00	0.15-0.40	0.04	0.00				V 0.01-0.13
A CTAA A 570/A 570M 00-	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				Cb 0.005-0.05; V 0.01-0.15;
ASTNI A 5/2/A 5/2NI-03a	M A 572/A 572M-03a Type 3			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.33	0.15-0.40	0.04	0.03				Cb + V 0.02-0.15
50	50 [345]			≤ 40	≤ 11/2	0.00	4.05	0.40	0.04	0.05				V 0.01-0.15; N 0.015
	Type 4			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.35	0.15-0.40	0.04	0.05				V:N > 4:1
	50 [345]			≤ 40	≤ 1½	0.23	1.35	0.40	0.04	0.05				Ti 0.006-0.04; N 0.003-0.015;
	Type 5			40 < t ≤ 100	1½ < t ≤ 4	0.23	1.35	0.15-0.40	0.04	0.05				V 0.06
EN 10112 2:1002	S355M	1.8823		≤ 63		0.14	1.60	0.50	0.035	0.030		0.30	0.20	Nb 0.05; V 0.10; Al 0.02 min; Ti 0.05; N 0.015
N 10113-3:1993 S355ML	1.8834		≤ 63		0.14	1.60	0.50	0.030	0.025		0.30	0.20	Nb 0.05; V 0.10; Al 0.02 min; Ti 0.05; N 0.015	
	300WT (44WT)					0.22	0.80-1.50	0.15-0.40	0.03	0.04				grain refining elements 0.10
CSA G40.21-04				≤ 40	≤ 1½	0.22		0.40						
55. 5 10.21 01	300W (44W)			> 40	> 1½	0.22	0.50-1.50	0.15-0.40	0.04	0.05				grain refining elements 0.10
				>100	> 4	0.23		0.10 0.40						

3.2.1B Chemical Composition of High-Strength Low-Alloy Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, 9	%, Maximu	ım, Unless	Otherwise	Specifie	d
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10113-2:1998	S355N	1.0545		≤ 150		0.20	0.90-1.65	0.50	0.035	0.030	0.30	0.30	0.10	Nb 0.05; V 0.05; Al 0.02 min; Ti 0.03; Cu 0.35; N 0.015
LN 10113-2.1990	S355NL	1.0546		≤ 150		0.18	0.90-1.65	0.50	0.030	0.025	0.30	0.50	0.10	Nb 0.05; V 0.12; Al 0.02 min; Ti 0.03; Cu 0.35; N 0.015
ASTM A 242/A 242M-03a	1		K11510	≤ 100	≤ 4	0.15	1.00		0.15	0.05				Cu 0.20
	350WT (50WT)					0.22	0.80-1.50	0.15-0.40	0.03	0.04				grain refining elements 0.10
CSA G40.21-04	350W (50W)			≤ 40 > 40	≤ 1½ > 1½	0.23	0.50-1.50	0.40 0.15-0.40	0.04	0.05				grain refining elements 0.10
	55 [380] Type 1			≤ 40 40 < t ≤ 50	≤ 1½ 1½ < t ≤ 2	0.25	1.35	0.40 0.15-0.40	0.04	0.05				Cb 0.005-0.05
	55 [380] Type 2			≤ 40 40 < t ≤ 50	≤ 1½ 1½ < t ≤ 2	0.25	1.35	0.40 0.15-0.40	0.04	0.05				V 0.01-0.15
ASTM A 572/A 572M-03a	55 [380] Type 3			≤ 40 40 < t ≤ 50	≤ 1½ 1½ < t ≤ 2	0.25	1.35	0.40 0.15-0.40	0.04	0.05				Cb 0.005-0.05; V 0.01-0.15; Cb + V 0.02-0.15
	55 [380] Type 4			≤ 40 40 < t ≤ 50	≤ 1½ 1½ < t ≤ 2	0.25	1.35	0.40 0.15-0.40	0.04	0.05				V 0.01-0.15; N 0.015
	55 [380] Type 5			≤ 40 40 < t ≤ 50	≤ 1½ 1½ < t ≤ 2	0.25	1.35	0.40 0.15-0.40	0.04	0.05				Ti 0.006-0.04; N 0.003-0.015; V 0.06
ASTM A 656/A 656M-03	60 [415] Type 3			≤ 40	≤ 1½	0.18	1.65	0.60	0.025	0.035				V 0.08; N 0.020; Cb 0.008-0.10
ASTIVI A 656/A 656WI-05	60 [415] Type 7			≤ 40	≤ 1½	0.18	1.65	0.60	0.025	0.035				V 0.15; N 0.020; Cb 0.10
	Α		K11430	≤ 200	≤ 8	0.19	0.80-1.25	0.30-0.65	0.04	0.05	0.40-0.65	0.40		Cu 0.25-0.40; V 0.02-0.10
ASTM A 588/A 588M-03a	В		K12043	≤ 200	≤ 8	0.20	0.75-1.35	0.15-0.50	0.04	0.05	0.40-0.70	0.50		Cu 0.20-0.40; V 0.01-0.10
	С		K11538	≤ 200	≤ 8	0.15	0.80-1.35	0.15-0.40	0.04	0.05	0.30-0.50	0.25-0.50		Cu 0.20-0.50; V 0.01-0.10
	K			≤ 200	≤ 8	0.17	0.50-1.20	0.25-0.50	0.04	0.05	0.40-0.70	0.40	0.10	Cu 0.30-0.50; Cb 0.005-0.05
	С		K12000	≤ 100	≤ 4	0.20	1.15-1.50	0.15-0.50	0.035	0.04				Cb 0.01-0.05
ASTM A 633/A 633M-01	D		K12037	≤ 40	≤ 1½	0.20	0.70-1.35	0.15-0.50	0.035	0.04	0.25	0.25	0.08	Cu 0.35
			1007	40 < t ≤ 100	1½ < t ≤ 4	0.20	1.00-1.60	0.15-0.50	0.035	0.04	0.25	0.25	0.08	Cu 0.35
EN 10113-3:1993	S420M	1.8825		≤ 63		0.16	1.70	0.50	0.035	0.030		0.30	0.20	Nb 0.05; V 0.12; Al 0.02 min; Ti 0.05; N 0.020
214 10110 0.1000	S420ML	1.8836		≤ 63		0.16	1.70	0.50	0.030	0.025		0.30	0.20	Nb 0.05; V 0.12; Al 0.02 min; Ti 0.05; N 0.020

3.2.1B Chemical Composition of High-Strength Low-Alloy Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section 1	Thickness				Weight, 9	%, Maximu	m, Unless	Otherwise	e Specifie	d
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	60 [415] Type 1			32	11/4	0.26	1.35	0.40	0.04	0.05				Cb 0.005-0.05
	60 [415] Type 2			32	11/4	0.26	1.35	0.40	0.04	0.05				V 0.01-0.15
ASTM A 572/A 572M-03a	60 [415] Type 3			32	11⁄4	0.26	1.35	0.40	0.04	0.05				Cb 0.005-0.05; V 0.01-0.15; Cb + V 0.02-0.15
	60 [415] Type 4			32	11/4	0.26	1.35	0.40	0.04	0.05				V 0.01-0.15; N 0.015
	60 [415] Type 5			32	11/4	0.26	1.35	0.40	0.04	0.05				Ti 0.006-0.04; N 0.003-0.015; V 0.06
	400WT (60WT)					0.22	0.80-1.50	0.15-0.40	0.03	0.04				grain refining elements 0.10
CSA G40.21-04	400W (60W)			≤ 40 > 40	≤ 1½ > 1½	0.23	0.50-1.50	0.40 0.15-0.40	0.04	0.05				grain refining elements 0.10
	65 [450]			≤ 13	≤ 1/2	0.26	1.35	0.40	0.04	0.05				01 0 005 0 05
	Type 1			> 13-32	> ½-1¼	0.23	1.65	0.40	0.04	0.05				Cb 0.005-0.05
	65 [450]			≤ 13	≤ 1/2	0.26	1.35	0.40	0.04	0.05				V 0 04 0 45
	Type 2			> 13-32	> ½-1¼	0.23	1.65	0.40	0.04	0.05				V 0.01-0.15
AOTA A 570/A 570M 00-	65 [450]			≤ 13	≤ 1/2	0.26	1.35	0.40	0.04	0.05				Cb 0.005-0.05; V 0.01-0.15;
ASTM A 572/A 572M-03a	Type 3			> 13-32	> ½-1¼	0.23	1.65	0.40	0.04	0.05				Cb + V 0.02-0.15
	65 [450]			≤ 13	≤ 1/2	0.26	1.35	0.40	0.04	0.05				V 0 04 0 45, N 0 045
	Type 4			> 13-32	> ½-1¼	0.23	1.65	0.40	0.04	0.05				V 0.01-0.15; N 0.015
	65 [450]			≤ 13	≤ 1/2	0.26	1.35	0.40	0.04	0.05				Ti 0.006-0.04; N 0.003-0.015;
	Type 5			> 13-32	> ½-1¼	0.23	1.65	0.40	0.04	0.05				V 0.06
ASTM A 633/A 633M-01	Е		K12202	≤ 150	≤ 6	0.22	1.15-1.50	0.15-0.50	0.035	0.04				V 0.04-0.11; N 0.03
ASTM A 656/A 656M-03	70 [485] Type 3			≤ 25	≤1	0.18	1.65	0.60	0.025	0.035				V 0.08; N 0.020; Cb 0.008-0.10
AS I IVI A 000/A 000IVI-U3	70 [485] Type 7			≤ 25	≤ 1	0.18	1.65	0.60	0.025	0.035				V 0.15; N 0.020; Cb 0.10

Standard	Grade, Class,	Steel	UNS	Heat	Section	n Thickness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					t ≤ 16		355					
					16 < t ≤ 35		345		470,600			
					35 < t ≤ 50		335		470-630			
	E 355 DD			N or NT or CTR	50 < t ≤ 70		325				22	39 J at -20°C
				OTIT	70 < t ≤ 100		305		450-610			
					100 < t ≤ 125		295		440-600			
ISO 4950-2:1995					125 < t ≤ 150		285		430-590			
150 4950-2:1995					t ≤ 16		355					
					16 < t ≤ 35		345		470.000			
					35 < t ≤ 50		335		470-630			
	E 355 E			N or NT or CTR	50 < t ≤ 70		325				22	27 J at -50°C
				OIII	70 < t ≤ 100		305		450-610		1	
					100 < t ≤ 125		295		440-600		1	
					125 < t ≤ 150		285		430-590		1	
ASTM A 709/A 709M-03a -	50W [345W] Type A, B, C				≤ 100	≤ 4	345	50	485	70	21	
					≤ 25	≤ 1	450	65				
					25 < t ≤ 30	1 < t ≤ 11⁄4	445	00	495	72		
	Grade A Class 2		K20747	N + PH	30 < t ≤ 50	11⁄4 < t ≤ 2	415	60			20	
	Olass Z				50 < t ≤ 100	2 < t ≤ 4	380	55	450	65	1	
					> 100	> 4	345	50	415	60	1	

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					3 ≤ t ≤ 50		460		550 700			
	S460Q	1.8908		QT	50 < t ≤ 100		440		550-720		17	see standard for impact data
					100 < t ≤ 150		400		500-670			ioi iiripaci dala
					3 ≤ t ≤ 50		460		550 700			
EN 10137-2:1996	S460QL	1.8906		QT	50 < t ≤ 100		440		550-720		17	see standard for impact data
					100 < t ≤ 150		400		500-670			ioi iiripaci data
					3 ≤ t ≤ 50		460		550 700			
	S460QL1	1.8916		QT	50 < t ≤ 100		440		550-720		17	see standard for impact data
					100 < t ≤ 150		400		500-670			ioi iiripaci data
	E 460 DD			QT	t ≤ 50		460		F70 700		17	00 1 -+ 0000
ISO 4950-3:1995	E 460 DD			QI	50 < t ≤ 70		440		570-720		17	39 J at -20°C
150 4950-3.1995	E 460 E			QT	t ≤ 50		460		F70 700		17	07 1 -4 5000
	E 460 E			Q1	50 < t ≤ 70		440		570-720		17	27 J at -50°C
ASTM A 709/A 709M-03a	HPS 70W [HPS 485W]			QT	≤ 100	≤ 4	485	70	585-760	85-110	19	
					t ≤ 30	≤ 11/4	550	80	585	85		
ASTM A 710/A 710M-02	Grade A		K20747	Q + PH	30 < t ≤ 50	11⁄4 < t ≤ 2	515	75	585	85	20	
ASTIVI A / TU/A / TUIVI-UZ	Class 3		K20/4/	Q+PH	50 < t ≤ 100	2 < t ≤ 4	450	65	515	75	20	
					> 100	> 4	415	60	485	70		
					$3 \le t \le 50$		500		590-770			
	S500Q	1.8924		QT	50 < t ≤ 100		480		590-770		17	see standard for impact data
					100 < t ≤ 150		440		540-720			lor impact data
					3 ≤ t ≤ 50		500		590-770			
EN 10137-2:1996	S500QL	1.8909		QT	50 < t ≤ 100		480		590-770		17	see standard for impact data
					100 < t ≤ 150		440		540-720			Tor impact data
					$3 \le t \le 50$		500		E00 770			
	S500QL1	1.8984		QT	50 < t ≤ 100		480		590-770		17	see standard for impact data
					100 < t ≤ 150		440		540-720			ioi iiiipaoi data
CSA G40.21-04	480WT (70WT)				≤ 65	≤ 2½	480	70	590-790	85-115	17	see standard for impact data

Standard	Grade, Class,	Steel	UNS	Heat	Section 1	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	S500A	1.8980		PH	$3 \le t \le 50$		500		600-700		17	see standard
EN 10137-3:1996	3500A	1.0900		FII	$50 < t \le 70$		480		600-700		17	for impact data
LIV 10137-3.1990	S500AL	1.8990		PH	$3 \le t \le 50$		500		600-700		17	see standard
	SSOUAL	1.0990		FII	$50 < t \le 70$		480		600-700		17	for impact data
ASTM A 710/A 710M-02	Grade A		K20747	PH	≤ 8	≤ 5/16	585	85	620	90	20	L: 27 J at -45°C
A31W A / 10/A / 10W-02	Class 1		N20747	FII	$8 < t \le 20$	5⁄16 < t ≤ 3⁄4	550	80	620	90	20	T: 20 J at -45°C
ASTM A 852/A 852M-03			K12043	QT	≤ 100	≤ 4	485	70	620-760	90-110	19	27 J at 10°C
CSA G40.21-04	550WT (80WT)				≤ 65	≤ 2½	550	80	620-860	90-125	15	see standard for impact data
					$3 \le t \le 50$		550		640,000			
	S550Q	1.8904		QT	50 < t ≤ 100		530		640-820		16	see standard for impact data
					100 < t ≤ 150		490		590-770			Tor impaor data
					$3 \le t \le 50$		550		640-820			
EN 10137-2:1996	S550QL	1.8926		QT	50 < t ≤ 100		530		640-820		16	see standard for impact data
					100 < t ≤ 150		490		590-770			Tor impaor data
					$3 \le t \le 50$		550		640-820			
	S550QL1	1.8986		QT	50 < t ≤ 100		530		640-820		16	see standard for impact data
					100 < t ≤ 150		490		590-770			Tor impaor data
	S550A	1.8991		PH	$3 \le t \le 50$		550		650-820		16	see standard
EN 10127 2:1006	SSSUA	1.6991		rn	50 < t ≤ 70		530		000-020		10	for impact data
N 10137-3:1996	S550AL	1.8992		PH	$3 \le t \le 50$		550		650-820		16	see standard
	SOOUAL	1.0992		rn	50 < t ≤ 70		530		000-020		10	for impact data

Standard	Grade, Class,	Steel	UNS	Heat	Section 1	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					$3 \le t \le 50$		620		700,000			
	S620Q	1.8914		QT	50 < t ≤ 100		580		700-890		15	see standard for impact data
					100 < t ≤ 150		560		650-830			ioi iiiipaci data
					$3 \le t \le 50$		620		700,000			
EN 10137-2:1996	S620QL	1.8927		QT	50 < t ≤ 100		580		700-890		15	see standard for impact data
					100 < t ≤ 150		560		650-830			ioi iiiipaci data
					$3 \le t \le 50$		620		700-890			
	S620QL1	1.8987		QT	50 < t ≤ 100		580		700-890		15	see standard for impact data
					100 < t ≤ 150		560		650-830			ioi iiiipaot data
	S620A	1.8993		PH	$3 \le t \le 50$		620		710-880		15	see standard
EN 10137-3:1996	3020A	1.0993		FN	50 < t ≤ 70		580		710-880		15	for impact data
EN 10137-3:1996	S620AL	1.8994		PH	$3 \le t \le 50$		620		710 000		15	see standard
	3020AL	1.0994		FN	50 < t ≤ 70		580		710-880		15	for impact data
ASTM A 514/A 514M-00a	all grades			QT	≤ 65	≤ 2½	690	100	760-895	110-130	18	
A311VI A 314/A 3141VI-00a	all grades			Qi	65 < t ≤ 150	2½ < t ≤ 6	620	90	690-895	100-130	16	
	100 [690]			QT	≤ 65	≤ 2½	690	100	760-895	110-130	18	
ASTM A 709/A 709M-03a	100 [090]			Qi	$65 < t \le 100$	2½ < t ≤ 4	620	90	690-895	100-130	16	
A3 1 W A 709/A 709 W -03a	100W [690W]			QT	≤ 65	≤ 2½	690	100	760-895	110-130	18	
	10000 [09000]			Qi	$65 < t \le 100$	2½ < t ≤ 4	620	90	690-895	100-130	16	
	S690A	1.8995		PH	$3 \le t \le 50$		690		760-930		14	see standard
EN 10137-3:1996	3030A	1.0993		111	$50 < t \leq 70$		650		700-930		14	for impact data
LIN 10137-3.1990	S690AL	1.8996		PH	$3 \le t \le 50$		690		760-930		14	see standard
	JUJUAL	1.0990		111	$50 < t \leq 70$		650		700-930		14	for impact data
					$3 \le t \le 50$		690		770-940			
	S690Q	1.8931		QT	$50 < t \le 100$		650		760-930		14	see standard for impact data
N 10137-2:1996					$100 < t \le 150$		630		710-900			To mpast data
					$3 \le t \le 50$		690		770-940			
	S690QL	1.8928		QT	$50 < t \le 100$		650		760-930		14	see standard for impact data
					100 < t ≤ 150		630		710-900			paor data
					$3 \le t \le 50$		690		770-940			
	S690QL1	1.8988		QT	50 < t ≤ 100		650		760-930		14	see standard for impact data
					100 < t ≤ 150		630		710-900			Impaot data

Standard	Grade, Class,	Steel	UNS	Heat	Section 1	Thickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	SHY 685			QT	≤ 50		685		780-930		see standard	47 J at -20°C
	3111 003			Qı	$50 < t \le 100$		665		760-910		see standard	47 J at -20 C
JIS G 3128:1999	SHY 685 N			QT	≤ 50		685		780-930		see standard	47 J at -20°C
013 G 3126.1999	3111 003 N			Qi	$50 < t \le 100$		665		760-910		see standard	47 J at -20 C
	SHY 685 NS			QT	≤ 50		685		780-930		see standard	47 J at -40°C
	3111 003 113			Qi	$50 < t \le 100$		665		760-910		see standard	47 J at -40 C
	700Q (100Q)			QT	t ≤ 65	t ≤ 2½	700	100	760-895	110-130	18	
CSA G40.21-04	7000 (1000)			QI	65 < t ≤ 100	2½ < t ≤ 4	620	90	760-695	110-130	10	
USA G40.21-04	700QT			QT	t ≤ 65	t ≤ 2½	700	100	760-895	110-130	18	see standard
	(100QT)			QI	65 < t ≤ 100	2½ < t ≤ 4	620	90	700-693	110-130	10	for impact data

3.2 Alloy Steels for Structural Steel Plates

3.2.2B Chemical Composition of Alloy Steels for Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight,	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ISO 4950-2:1995	E 355 DD					0.18	0.9-1.6	0.50	0.030	0.030	0.25	0.30	0.10	Nb 0.015-0.060; V 0.02-0.10; Al 0.020 min; Ti 0.02-0.20; Cu 0.35
130 4930-2.1995	E 355 E					0.18	0.9-1.6	0.50	0.025	0.025	0.25	0.30	0.10	Nb 0.015-0.060; V 0.02-0.10; Al 0.020 min; Ti 0.02-0.20; Cu 0.35
	50W [345W] Type A					0.19	0.80-1.25	0.30-0.65	0.04	0.05	0.40-0.65	0.40		Cu 0.25-0.40; V 0.02-0.10
ASTM A 709/A 709M-03a	50W [345W] Type B					0.20	0.75-1.35	0.15-0.50	0.04	0.05	0.40-0.70	0.50		Cu 0.20-0.40; V 0.01-0.10
	50W [345W] Type C					0.15	0.80-1.35	0.15-0.40	0.04	0.05	0.30-0.50	0.25-0.50		Cu 0.20-0.50; V 0.01-0.10
ASTM A 710/A 710M-02	Grade A Class 2		K20747			0.07	0.40-0.70	0.40	0.025	0.025	0.60-0.90	0.70-1.00	0.15-0.25	Cu 1.00-1.30; Cb 0.02 min
	S460Q	1.8908				0.20	1.70	0.80	0.025	0.015	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-2:1996	S460QL	1.8906				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
	S460QL1	1.8916				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
ISO 4950-3:1995	E 460 DD					0.20	0.7-1.7	0.55	0.035	0.035	see std	see std	see std	see standard
150 4950-3.1995	E 460 E					0.20	0.7-1.7	0.55	0.030	0.030	see std	see std	see std	see standard
ASTM A 709/A 709M-03a	HPS 70W [HPS 485W]					0.11	1.10-1.35	0.30-0.50	0.020	0.006	0.45-0.70	0.25-0.40	0.02-0.08	N 0.015; Cu 0.25-0.40; V 0.04-0.08; Al 0.010-0.040
ASTM A 710/A 710M-02	Grade A Class 3		K20747			0.07	0.40-0.70	0.40	0.025	0.025	0.60-0.90	0.70-1.00	0.15-0.25	Cu 1.00-0.30; Cb 0.02 min
	S500Q	1.8924				0.20	1.70	0.80	0.025	0.015	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-2:1996	S500QL	1.8909				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
	S500QL1	1.8984				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
CSA G40.21-04	480WT (70WT)			≤ 65	≤ 2½	0.26	0.80-1.50	0.15-0.40	0.03	0.04				grain refining elements 0.10; N 0.01-0.02 if N < 0.25 Va

3.2 Alloy Steels for Structural Steel Plates

Standard	Grade, Class,	Steel	UNS	Section TI	nickness				Weight, '	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10137-3:1996	S500A	1.8980		$3 \le t \le 70$		0.03-0.12	0.30-1.80	0.50	0.025	0.015	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
LN 10137-3.1990	S500AL	1.8990		$3 \le t \le 70$		0.03-0.12	0.30-1.80	0.50	0.020	0.010	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
ASTM A 710/A 710M-02	Grade A Class 1		K20747	≤ 20	≤ 3/4	0.07	0.40-0.70	0.40	0.025	0.025	0.60-0.90	0.70-1.00	0.15-0.25	Cu 1.00-1.30; Cb 0.02 min
ASTM A 852/A 852M-03			K12043	≤ 100	≤ 4	0.19	0.80-1.35	0.20-0.65	0.035	0.04	0.40-0.70	0.50		Cu 0.20-0.40; V 0.02-0.10
CSA G40.21-04	550WT (80WT)			≤ 65	≤ 2 ½	0.15	1.75	0.15-0.40	0.03	0.04				grain refining elements 0.15; N 0.01-0.02 if N < 0.25 Va
	S550Q	1.8904				0.20	1.70	0.80	0.025	0.015	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-2:1996	S550QL	1.8926				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
	S550QL1	1.8986				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-3:1996	S550A	1.8991		$3 \le t \le 70$		0.03-0.12	0.30-1.80	0.50	0.025	0.015	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
EN 10137-3.1990	S550AL	1.8992		3 ≤ t ≤ 70		0.03-0.12	0.30-1.80	0.50	0.020	0.010	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080

Chemical Composition of Alloy Steels for Structural Steel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section TI	nickness				Weight, 9	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	S620Q	1.8914				0.20	1.70	0.80	0.025	0.015	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-2:1996	S620QL	1.8927				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
	S620QL1	1.8987				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-3:1996	S620A	1.8993		$3 \le t \le 70$		0.03-0.12	0.30-1.80	0.50	0.025	0.015	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
LN 10137-3.1990	S620AL	1.8994		$3 \le t \le 70$		0.03-0.12	0.30-1.80	0.50	0.020	0.010	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
	Α		K11856	≤ 32	≤ 11/4	0.15-0.21	0.80-1.10	0.40-0.80	0.035	0.035	0.50-0.80		0.18-0.28	Zr 0.05-0.15; B 0.0025
	В		K11630	≤ 32	≤ 11/4	0.12-0.21	0.70-1.00	0.20-0.35	0.035	0.035	0.40-0.65		0.15-0.25	V 0.03-0.08; Ti 0.01-0.03; B 0.0005-0.005
	С		K11511	≤ 32	≤ 11/4	0.10-0.20	1.10-1.50	0.15-0.30	0.035	0.035			0.15-0.30	B 0.001-0.005
	Е		K21604	≤ 150	≤ 6	0.12-0.20	0.40-0.70	0.20-0.40	0.035	0.035	1.40-2.00		0.40-0.60	Ti 0.01-0.10; B 0.001-0.005
	F		K11576	≤ 65	≤ 2½	0.10-0.20	0.60-1.00	0.15-0.35	0.035	0.035	0.40-0.65	0.70-1.00	0.40-0.60	V 0.03-0.08; Cu 0.15-0.50; B 0.0005-0.006
	Н		K11646	≤ 50	≤ 2	0.12-0.21	0.95-1.30	0.20-0.35	0.035	0.035	0.40-0.65	0.30-0.70	0.20-0.30	V 0.03-0.08; B 0.0005-0.005
ASTM A 514/A 514M-00a	J		K11625	≤ 32	≤ 11/4	0.12-0.21	0.45-0.70	0.20-0.35	0.035	0.035			0.50-0.65	B 0.001-0.005
	K			≤ 50	≤ 2	0.10-0.20	1.10-1.50	0.15-0.30	0.035	0.035			0.45-0.55	B 0.001-0.005
	М		K11683	≤ 50	≤ 2	0.12-0.21	0.45-0.70	0.20-0.35	0.035	0.035		1.20-1.50	0.45-0.60	B 0.001-0.005
	Р		K21650	≤ 150	≤ 6	0.12-0.21	0.45-0.70	0.20-0.35	0.035	0.035	0.85-1.20	1.20-1.50	0.45-0.60	B 0.001-0.005
	Q			≤ 150	≤ 6	0.14-0.21	0.95-1.30	0.15-0.35	0.035	0.035	1.00-1.50	1.20-1.50	0.40-0.60	V 0.03-0.08
	R			≤ 65	≤ 2½	0.15-0.20	0.85-1.15	0.20-0.35	0.035	0.035	0.35-0.65	0.90-1.10	0.15-0.25	V 0.03-0.08
	S			≤ 65	≤ 2½	0.11-0.21	1.10-1.50	0.15-0.45	0.035	0.020			0.10-0.60	V 0.06; B 0.001-0.005; Cb0.06
	Т			≤ 50	≤ 2	0.08-0.14	1.20-1.50	0.40-0.60	0.035	0.010			0.45-0.60	V 0.03-0.08; B 0.001-0.005
	Gr. 100 [690] & 100W [690W] Type A			≤ 32	≤ 11⁄4	0.15-0.21	0.80-1.10	0.40-0.80	0.035	0.035	0.50-0.80		0.18-0.28	Zr 0.05-0.15; B 0.0025
ASTM A 709/A 709M-03a	Gr. 100 [690] &			≤ 32	≤ 11⁄4	0.12-0.21	0.70-1.00	0.20-0.35	0.035	0.035	0.40-0.65		0.15-0.25	V 0.03-0.08; Ti 0.01-0.03; B 0.0005-0.005
	Gr. 100 [690] & 100W [690W] Type C			≤ 32	≤ 11⁄4	0.10-0.20	1.10-1.50	0.15-0.30	0.035	0.035			0.15-0.30	B 0.001-0.005

Note: This section continued on next page

Chemical Composition of Alloy Steel Structural Steel Plate (Continued)

Standard	Grade, Class,	Steel	UNS	Section Th	nickness				Weight, S	%, Maximu	m, Unless (Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	Gr. 100 [690] & 100W [690W] Type E			≤ 100	≤ 4	0.12-0.20	0.40-0.70	0.20-0.40	0.035	0.035	1.40-2.00		0.40-0.60	Ti 0.01-0.10; B 0.001-0.005
	Gr. 100 [690] & 100W [690W] Type F			≤ 65	≤ 2½	0.10-0.20	0.60-1.00	0.15-0.35	0.035	0.035	0.40-0.65	0.70-1.00	0.40-0.60	V 0.03-0.08; Cu 0.15-0.50; B 0.0005-0.006
	Gr. 100 [690] & 100W [690W] Type H			≤ 50	≤2	0.12-0.21	0.95-1.30	0.20-0.35	0.035	0.035	0.40-0.65	0.30-0.70	0.20-0.30	V 0.03-0.08; B 0.0005-0.005
ASTM A 709/A 709M-03a (Continued)	Gr. 100 [690] & 100W [690W] Type J			≤ 32	≤ 11⁄4	0.12-0.21	0.45-0.70	0.20-0.35	0.035	0.035			0.50-0.65	B 0.001-0.005
	Gr. 100 [690] & 100W [690W] Type M			≤ 50	≤2	0.12-0.21	0.45-0.70	0.20-0.35	0.035	0.035		1.20-1.50	0.45-0.60	B 0.001-0.005
	Gr. 100 [690] & 100W [690W] Type P			≤ 100	≤ 4	0.12-0.21	0.45-0.70	0.20-0.35	0.035	0.035	0.85-1.20	1.20-1.50	0.45-0.60	B 0.001-0.005
	Gr. 100 [690] & 100W [690W] Type Q			≤ 100	≤ 4	0.14-0.21	0.95-1.30	0.15-0.35	0.035	0.035	1.00-1.50	1.20-1.50	0.40-0.60	V 0.03-0.08
EN 10107 0:1000	S690A	1.8995		3 ≤ t ≤ 70		0.03-0.12	0.30-1.80	0.50	0.025	0.015	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
EN 10137-3:1996	S690AL	1.8996		3 ≤ t ≤ 70		0.03-0.12	0.30-1.80	0.50	0.020	0.010	0.3	2	0.5	N 0.015; Cu 2; Nb 0.060; Ti 0.10; V 0.10; Al 0.080
	S690Q	1.8931				0.20	1.70	0.80	0.025	0.015	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
EN 10137-2:1996	S690QL	1.8928				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
	S690QL1	1.8988				0.20	1.70	0.80	0.020	0.010	1.50	2.0	0.70	N 0.015; B 0.0050; Cu 0.50; Nb 0.06; Ti 0.05; V 0.12; Zr 0.15
	SHY 685			6 ≤ t ≤ 100		0.18	1.50	0.55	0.03	0.025	1.20		0.60	Cu 0.50; V 0.10; B 0.005
JIS G 3128:1999	SHY 685 N			6 ≤ t ≤ 100		0.18	1.50	0.55	0.030	0.025	0.80	0.30-1.50	0.60	Cu 0.50; V 0.10; B 0.005
	SHY 685 NS			6 ≤ t ≤ 100		0.14	1.50	0.55	0.015	0.015	0.80	0.30-1.50	0.60	Cu 0.50; V 0.05; B 0.005
	700Q (100Q)					0.20	1.50	0.15-0.40	0.03	0.04				B 0.0005-0.005
CSA G40.21-04	700QT (100QT)					0.20	1.50	0.15-0.40	0.03	0.04				B 0.0005-0.005

3.3 Structural Steels with Improved Atmospheric Corrosion Resistance

3.3A Mechanical Properties of Structural Steels with Improved Atmospheric Corrosion-Resistance

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ISO 5952:1998	Gr. HSA 235W			HR	< 3		235		360-510		20	
130 5952. 1996	Class B, D			пп	≥ 3		235		340-470		22	
					t ≤ 3		235		360-510			
					3 < t ≤ 16		235				26	
	S235J0W	1.8958		HR	16 < t ≤ 40		225				26	27 J at 0°C
	S235JUW	1.8958		HK	40 < t ≤ 63		215		340-470		25	27 J at 0°C
					63 < t ≤ 80		215				24	
EN 10155-1000					80 < t ≤ 100		215		360-510		24	
EN 10155:1993					t ≤ 3		235		360-510			
					3 < t ≤ 16		235				24	
	S235J2W	1.8961		N.	16 < t ≤ 40		225				24	07 1 -+ 0000
	32333244	1.0901		N	40 < t ≤ 63		215		340-470		23	27 J at -20°C
					63 < t ≤ 80		215				22	
					80 < t ≤ 100		215				22	
	0 = 00=144				t < 16		235				26	
	Gr. Fe 235W Quality B			AR	16 < t ≤ 40		225		340-470		26	27 J at 20°C
	Quality D				40 < t ≤ 63		215				25	
					t < 16		235				26	
ISO 4952:2003	O 4952:2003 Gr. Fe 235W Quality C			AR	16 < t ≤ 40		225		340-470		26	27 J at 0°C
	Quality O				40 < t ≤ 63		215				25	
					t < 16		235				26	
	Gr. Fe 235W Quality D			AR or N	16 < t ≤ 40		225		340-470		26	27 J at -20°C
	Quality D				40 < t ≤ 63		215		7		25	

3.3A Mechanical Properties of Structural Steels with Improved Atmospheric Corrosion-Resistance (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section TI	nickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ISO 5952:1998	Gr. HSA 245W			HR	< 3		245		400-540		20	
130 5952.1996	Class B, D			ПП	≥ 3		245		400-540		22	
					≤ 16		245 max				17	
					16 < t ≤ 40		235 max				21	
	SMA400AW			HR	40 < t ≤ 100		215 max		400-540			
					100 < t ≤ 160		205 max				23	
					160 < t ≤ 200		195 max					
					≤ 16		245 max				17	
	SMA400BW				16 < t ≤ 40		235 max				21	
				HR	40 < t ≤ 100		215 max		400-540			27 J at 0°C
					100 < t ≤ 160		205 max				23	
					160 < t ≤ 200		195 max					
					≤ 16		245 max				17	
	SMA400CW			HR	16 < t ≤ 40		235 max		400-540		21	47 J at 0°C
JIS G 3114:1998					40 < t ≤ 100		215 max				23	
010 G 0114.1990					≤ 16		245 max				17	
					16 < t ≤ 40		235 max				21	
	SMA400AP			HR	40 < t ≤ 100		215 max		400-540			
					100 < t ≤ 160		205 max				23	
					160 < t ≤ 200		195 max					
					≤ 16		245 max				17	
					16 < t ≤ 40		235 max				21	
	SMA400BP			HR	40 < t ≤ 100		215 max		400-540			27 J at 0°C
					100 < t ≤ 160		205 max				23	
					160 < t ≤ 200		195 max					
					≤ 16		245 max				17	
	SMA400CP			HR	16 < t ≤ 40		235 max		400-540		21	47 J at 0°C
					40 < t ≤ 100		215 max				23	

Mechanical Properties of Structural Steels with Improved Atmospheric Corrosion-Resistance (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile St	rength, min	Elengation	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
JIS G 3125:1987	SPA-C			CR			315		450		26	
					t < 16		355				22	
	Gr. Fe 355W Quality 2B			AR	16 < t ≤ 40		345		470 - 630		22	27 J at 20°C
	Quality 2D				40 < t ≤ 63		335				21	-
					t < 16		355				22	
ISO 4952:2003	Gr. Fe 355W Quality 2C			AR	16 < t ≤ 40		345		470 - 630		22	27 J at 0°C
	Quality 20				40 < t ≤ 63		335				21	
					t < 16		355				22	
	Gr. Fe 355W Quality 2D			AR or N	16 < t ≤ 40		345		470 - 630		22	27 J at -20°C
	Quality 2D				40 < t ≤ 63		335				21	
				HR			340	50	480	70	22	
ASTM A 606-01	Type 2 and Type 4			HR, A or N			310	45	450	65	22	
	,			CR			310	45	450	65	22	
ISO 4952:2003	Gr. Fe 355W Quality 1A			AR	t < 12		355		470 - 630		21	
130 4932.2003	Gr. Fe 355W Quality 1D			AR or N	t < 12		355		470 - 630		21	27 J at -20°C
	350R (50R)				≤ 65	≤ 2½	350	50	480-650	70-95	21	
CSA G40.21-04	350A (50A)				≤ 100	≤ 4	350	50	480-650	70-95	21	
	350AT (50AT)				≤ 100	≤ 4	350	50	480-650	70-95	21	see standard for impact data
JIS G 3125:1987	SPA-H			HR	≤ 6.0		345		480		22	
013 G 3125.1907	SFA-II			l lin	> 6.0		355		460		15	
					≤ 16		365 max				15	
					16 < t ≤ 40		355 max				19	
JIS G 3114:1998	3114:1998 SMA490AW			HR	40 < t ≤ 75		335 max		490-610		21	
JIS G 3114:1998				HK	75 < t ≤ 100		325 max		490-610		21	
					100 < t ≤ 160		305 max				21	1
					160 < t ≤ 200		295 max				21	1

Note: This section continued on next page

3.3A Mechanical Properties of Structural Steels with Improved Atmospheric Corrosion-Resistance (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section Th	ickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		365 max				15	
					16 < t ≤ 40		355 max				19	
	SMA490AP			HR	40 < t ≤ 75		335 max		100.010		21	
	SWA490AP			пп	75 < t ≤ 100		325 max		490-610		21	
					100 < t ≤ 160		305 max				21	
					160 < t ≤ 200		295 max				21	
					≤ 16		365 max				15	
					16 < t ≤ 40		355 max				19	
	SMA490BW			HR	40 < t ≤ 75		335 max		400.010		21	07 1 -+ 000
	SIVIA49UDVV			пп	75 < t ≤ 100		325 max		490-610		21	27 J at 0°C
					100 < t ≤ 160		305 max				21	
					160 < t ≤ 200		295 max				21	
JIS G 3114:1998					≤ 16		365 max				15	
(Continued)					16 < t ≤ 40		355 max				19	
	SMA490BP			HR	40 < t ≤ 75		335 max		490-610		21	27 J at 0°C
	SIVIA490DF			l III	75 < t ≤ 100		325 max		490-610		21	27 J at 0 C
					100 < t ≤ 160		305 max				21	
					160 < t ≤ 200		295 max				21	
					≤ 16		365 max				15	
	SMA490CW			HR	16 < t ≤ 40		355 max		490-610		19	47 J at 0°C
	SIVIA490CVV			пп	40 < t ≤ 75		335 max		490-610		21	47 J at 0°C
					75 < t ≤ 100		325 max				21	
					≤ 16		365 max				15	
	SMA490CP			HR	16 < t ≤ 40		355 max		400 610		19	47 Let 0°C
	SIVIA490CP			пп	40 < t ≤ 75		335 max		490-610		21	47 J at 0°C
					75 < t ≤ 100		325 max				21	
ISO 5952:1998	Gr. HSA 365W			HR	< 3		365		400 610		15	
190 9992:1990	Class B, D			пп	≥ 3		365		490-610		19	

Mechanical Properties of Structural Steels with Improved Atmospheric Corrosion-Resistance (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section Th	nickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					t ≤ 3		355		510-680			
	S355J0WP	1.8945		HR	3 < t ≤ 16		355				20	27 J at 0°C
	3333000	1.0345		III	16 < t ≤ 40		345		490-630		20	27 J at 0 C
					40 < t ≤ 100		345					
					t ≤ 3		355		510-680			
	S355J2WP	1.8946		N	3 < t ≤ 16		355				20	27 J at 0°C
	3333JZVVF	1.0940		IN	16 < t ≤ 40		345		490-630		20	27 J at 0°C
					40 < t ≤ 100		345					
					t ≤ 3		355		510-680			
					3 < t ≤ 16		355				20	
	S355J0W 1.89	1 0050		HR	16 < t ≤ 40		345				20	27 J at 0°C
		1.6959		пп	40 < t ≤ 63		335		490-630		19	27 J at 0°C
					63 < t ≤ 80		325				18	
					80 < t ≤ 100		315				18	
					t ≤ 3		355		510-680			
EN 10155:1993					3 < t ≤ 16		355				20	
LIN 10100.1990	S355J2G1W	1.8963		N	16 < t ≤ 40		345				20	27 J at -20°C
	5355JZG I W	1.0903		IN	40 < t ≤ 63		335		490-630		19	27 J at -20°C
					63 < t ≤ 80		325				18	
					80 < t ≤ 100		315				18	
					t ≤ 3		355		510-680			
					3 < t ≤ 16		355				20	
	S355J2G2W	1.8965		HR	16 < t ≤ 40		345				20	27 J at -20°C
	5355JZGZW	1.0905		пп	40 < t ≤ 63		335		490-630		19	27 J at -20°C
					63 < t ≤ 80		325				18	
					80 < t ≤ 100		315				18	
					t ≤ 3		355		510-680			
					3 < t ≤ 16		355				20	
	S355K2G1W	1 0000		N.	16 < t ≤ 40		345				20	40 Let 0000
	5355K2G1W	1.8966		N	40 < t ≤ 63		335		490-630		19	40 J at -20°C
					63 < t ≤ 80		325				18	
					80 < t ≤ 100		315				18	

Note: This section continued on next page

3.3 Structural Steels with Improved Atmospheric Corrosion Resistance

3.3A Mechanical Properties of Structural Steels with Improved Atmospheric Corrosion-Resistance (Continued)

Standard	Grade, Class,	Steel	UNS	Heat	Section Th	nickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elemention	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
					t ≤ 3		355		510-680			
					3 < t ≤ 16		355				20	_
EN 10155:1993	S355K2G2W	1.8967		HR	16 < t ≤ 40		345				20	40 J at -20°C
(Continued)	3355K2G2W	1.0907		пп	40 < t ≤ 63		335		490-630		19	40 J at -20°C
					63 < t ≤ 80		325				18	
					80 < t ≤ 100		315				18	
	Gr. HSA355W1			HR	< 3		355		510-680		15	
ISO 5952:1998	Class A, D				≥ 3		000		490-630		19	
	Gr. HSA355W2			HR	< 3		355		510-680		18	
	Class C, D				≥ 3				490-630		22	
ASTM A 871/A 871M-03	60 [415]			HR, N or QT	≤ 12	≤ ½	415	60	520	75	18	20 J at -18°C
7.011017.0717.07110100	00 [410]			1111, 14 01 Q1	> 12	> ½	415	60	520	75	18	20 J at -29°C
	400A (60A)				≤ 65	≤ 2 ½	400	60	520-690	75-100	21	
CSA G40.21-04	400AT (60AT)				≤ 65	≤ 2½	400	60	520-690	75-100	21	see standard for impact data
ASTM A 871/A 871M-03	65 [450]			HR, N or QT	≤ 12	≤ ½	450	65	550	80	17	20 J at -18°C
A31W A 67 1/A 67 1W-03	05 [450]			TIN, N OF QT	> 12	> ½	450	65	550	80	17	20 J at -29°C
					≤ 16		460 max				19	
	SMA570W			HR	$16 < t \le 40$		450 max		570-720		26	47 J at -5°C
	SIVIAS/OVV			l III	40 < t ≤ 75		430 max		570-720		20	47 J at -5 C
JIS G 3114:1998					75 < t ≤ 100		420 max				20	
313 G 3114.1990					≤ 16		460 max				19	
	SMA570P			HR	$16 < t \le 40$		450 max		570-720		26	47 J at -5°C
	SIVIAS/0F			l III	40 < t ≤ 75		430 max		570-720		20	47 J at -5 C
					75 < t ≤ 100		420 max				20	
	480A (70A)				≤ 65	≤ 2 ½	480	70	590-790	85-115	17	
CSA G40.21-04	480AT (70AT)				≤ 65	≤ 2½	480	70	590-790	85-115	17	see standard for impact data
OOA 040.21-04	550A (80A)				≤ 65	≤ 2½	550	80	620-860	90-125	15	
	550AT (80AT)				≤ 65	≤ 2½	550	80	620-860	90-125	15	see standard for impact data

3.3B Chemical Composition of Structural Steels with Improved Atmospheric Corrosion-Resistance

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, ^c	%, Maximu	m, Unless (Otherwise S	pecified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ISO 5952:1998	Gr. HSA 235W Class B					0.13	0.20-0.60	0.10-0.40	0.040	0.035	0.40-0.80	0.65		Cu 0.25-0.55
130 3932.1996	Gr. HSA 235W Class D					0.13	0.20-0.60	0.10-0.40	0.040	0.035	0.40-0.80	0.65		Cu 0.25-0.55; Al 0.020 min
EN 10155:1993	S235J0W	1.8958		≤ 100		0.13	0.20-0.60	0.40	0.040	0.040	0.40-0.80	0.65		N 0.009; Cu 0.25-0.55
EN 10155.1995	S235J2W	1.8961		≤ 100		0.13	0.20-0.60	0.40	0.040	0.035	0.40-0.80	0.65		Cu 0.25-0.55; N binding el.
	Gr. Fe 235W Quality B					0.13	0.20-0.60	0.10-0.40	0.040	0.035	0.40-0.80	0.65		Cu 0.20-0.55
ISO 4952:2003	Gr. Fe 235W Quality C					0.13	0.20-0.60	0.10-0.40	0.040	0.035	0.40-0.80	0.65		Cu 0.20-0.55; grain-refining el.
	Gr. Fe 235W Quality D					0.13	0.20-0.60	0.10-0.40	0.040	0.035	0.40-0.80	0.65		Cu 0.20-0.55; grain-refining el.
ICO 5050:1000	HSA 245W-B					0.18	1.25	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50; Mo+Nb+Ti+V+Zr 0.15 Total
ISO 5952:1998	HSA 245W-D					0.18	1.25	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50; Al 0.020 min; Mo+Nb+Ti+V+Zr 0.15 Total
	SMA400AW			≤ 200		0.18	1.25	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50
	SMA400BW			≤ 200		0.18	1.25	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50
JIS G 3114:1998	SMA400CW			≤ 100		0.18	1.25	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50
JIS G 3114:1998	SMA400AP			≤ 200		0.18	1.25	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35
	SMA400BP			≤ 200		0.18	1.25	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35
	SMA400CP			≤ 100		0.18	1.25	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35

3.3 Structural Steels with Improved Atmospheric Corrosion Resistance

3.3B Chemical Composition of Structural Steels with Improved Atmospheric Corrosion-Resistance

Standard	Grade, Class,	Steel	UNS	Section Thi	ckness				Weight, %	, Maximu	m, Unless (Otherwise S	pecified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 3125:1987	SPA-C			$0.6 \le t \le 2.3$		0.12	0.20-0.50	0.25-0.75	0.070-0.150	0.040	0.30-1.25	0.65		Cu 0.25-0.60
	Gr. Fe 355W Quality 2B					0.19	0.50-1.50	0.50	0.040	0.035	0.40-0.80	0.65	0.30	Cu 0.20-0.55; Zr 0.15
ISO 4952:2003	Gr. Fe 355W Quality 2C					0.19	0.50-1.50	0.50	0.040	0.035	0.40-0.80	0.65	0.30	Cu 0.20-0.55; Zr 0.15; grain-refining elements
	Gr. Fe 355W Quality 2D					0.19	0.50-1.50	0.50	0.040	0.035	0.40-0.80	0.65	0.30	Cu 0.20-0.55; Zr 0.15; grain-refining elements
ASTM A 606-01	2					0.22	1.25			0.04				Cu 0.20 min; others as required
ASTIVI A 000-01	4					0.22	1.25			0.04				Others as required
ICO 4050,000	Gr. Fe 355W Quality 1A					0.12	< 1.00	0.20-0.75	0.06-0.15	0.035	0.30-1.25	0.65		Cu 0.25-0.55
SO 4952:2003	Gr. Fe 355W Quality 1D					0.12	< 1.00	0.20-0.75	0.06-0.15	0.035	0.30-1.25	0.65		Cu 0.25-0.55; grain-refining elements
	350R (50R)					0.16	0.75	0.75	0.05-0.15	0.04	0.30-1.25	0.90		grain refining elements 0.10; Cu 0.20-0.60
CSA G40.21-04	350A (50A)					0.20	0.75-1.35	0.15-0.50	0.03	0.04	0.70	0.90		grain refining elements 0.10; Cu 0.20-0.60
	350AT (50AT)					0.20	0.75-1.35	0.15-0.50	0.03	0.04	0.70	0.90		grain refining elements 0.10; Cu 0.20-0.60
JIS G 3125:1987	SPA-H			≤ 16		0.12	0.20-0.50	0.25-0.75	0.070-0.150	0.040	0.30-1.25	0.65		Cu 0.25-0.60
	SMA490AW			≤ 200		0.18	1.40	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50
	SMA490AP			≤ 200		0.18	1.40	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35
IIC C 04444000	SMA490BW			≤ 200		0.18	1.40	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50
JIS G 3114:1998	SMA490BP			≤ 200		0.18	1.40	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35
	SMA490CW			≤ 100		0.18	1.40	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50
	SMA490CP			≤ 100		0.18	1.40	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35
100 5050 4000	Gr. HSA 365W Class B					0.18	1.40	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50; Mo+Nb+Ti+V+Zr 0.15 Total
ISO 5952:1998	Gr. HSA 365W Class D					0.18	1.40	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50; Al 0.020 min; Mo+Nb+Ti+V+Zr 0.15 Total

3.3 Structural Steels with Improved Atmospheric Corrosion Resistance

Chemical Composition of Structural Steels with Improved Atmospheric Corrosion-Resistance

Standard	Grade, Class,	Steel	UNS	Section TI	hickness	Weight, %, Maximum, Unless Otherwise Specified									
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others	
	S355J0WP	1.8945		≤ 12		0.12	1.0	0.75	0.06-0.15	0.040	0.30-1.25	0.65		N 0.009; Cu 0.25-0.55	
	S355J2WP	1.8946		≤ 12		0.12	1.0	0.75	0.06-0.15	0.035	0.30-1.25	0.65		Cu 0.25-0.55; N binding el.	
	S355J0W	1.8959		≤ 100		0.16	0.50-1.50	0.50	0.040	0.040	0.40-0.80	0.65		N 0.009; Cu 0.25-0.55; Mo 0.30; Zr 0.15	
EN 10155:1993	S355J2G1W	1.8963		≤ 100		0.16	0.50-1.50	0.50	0.035	0.035	0.40-0.80			Cu 0.25-0.55; N binding el.	
	S355J2G2W	1.8965		≤ 100		0.16	0.50-1.50	0.50	0.035	0.035	0.40-0.80			Cu 0.25-0.55; N binding el.	
	S355K2G1W	1.8966		≤ 100		0.16	0.50-1.50	0.50	0.035	0.035	0.40-0.80			Cu 0.25-0.55; N binding el.	
	S355K2G2W	1.8967		≤ 100		0.16	0.50-1.50	0.50	0.035	0.035	0.40-0.80			Cu 0.25-0.55; N binding el.	
	HSA 355W1-A					0.12	1.00	0.20-0.75	0.06-0.15	0.035	0.30-1.25	0.65		Cu 0.25-0.55	
	HSA 355W1-D					0.12	1.00	0.20-0.75	0.06-0.15	0.035	0.30-1.25	0.65		Cu 0.25-0.55; Al 0.020 min	
ISO 5952:1998	HSA 355W2-C					0.16	0.50-1.50	0.50	0.035	0.035	0.40-0.80	0.65	0.30	Cu 0.25-0.55; Zr 0.15	
	HSA 355W2-D					0.16	0.50-1.50	0.50	0.035	0.035	0.40-0.80	0.65	0.30	Cu 0.25-0.55; Zr 0.15; Al 0.020 min	
	Gr. 65 Type I					0.19	0.80-1.35	0.30-0.65	0.04	0.05	0.40-0.70	0.40		Cu 0.25-0.40; V 0.02-0.10	
ASTM A 871/A 871M-03	Gr. 65 Type II					0.20	0.75-1.35	0.15-0.50	0.04	0.05	0.40-0.70	0.50		Cu 0.20-0.40; V 0.01-0.10	
ASTM A 8/ I/A 8/ IMI-03	Gr. 65 Type III					0.15	0.80-1.35	0.15-0.40	0.04	0.05	0.30-0.50	0.25-0.50		Cu 0.20-0.50; V 0.01-0.10	
	Gr. 65 Type IV					0.17	0.50-1.20	0.25-0.50	0.04	0.05	0.40-0.70	0.40	0.10	Cu 0.30-0.50; Cb 0.005-0.05	
CSA G40.21-04	400A (60A)					0.20	0.75-1.35	0.15-0.50	0.03	0.04	0.70	0.90		grain refining elements 0.10; Cu 0.20-0.60	
CSA G40.21-04	400AT (60AT)					0.20	0.75-1.35	0.15-0.50	0.03	0.04	0.70	0.90		grain refining elements 0.10; Cu 0.20-0.60	
	Gr. 65 Type I					0.19	0.80-1.35	0.30-0.65	0.04	0.05	0.40-0.70	0.40		Cu 0.25-0.40; V 0.02-0.10	
ASTM A 871/A 871M-03	Gr. 65 Type II					0.20	0.75-1.35	0.15-0.50	0.04	0.05	0.40-0.70	0.50		Cu 0.20-0.40; V 0.01-0.10	
A31W1 A 67 1/A 67 1W1-03	Gr. 65 Type III					0.15	0.80-1.35	0.15-0.40	0.04	0.05	0.30-0.50	0.25-0.50		Cu 0.20-0.50; V 0.01-0.10	
	Gr. 65 Type IV					0.17	0.50-1.20	0.25-0.50	0.04	0.05	0.40-0.70	0.40	0.10	Cu 0.30-0.50; Cb 0.005-0.05	
JIS G 3114:1998	SMA570W			≤ 100		0.18	1.40	0.15-0.65	0.035	0.035	0.45-0.75	0.05-0.30		Cu 0.30-0.50	
JIO G 3114.1990	SMA570P			≤ 100		0.18	1.40	0.55	0.035	0.035	0.30-0.55			Cu 0.20-0.35	
CSA G40.21-04	480A (70A)					0.20	1.00-1.60	0.15-0.50	0.025	0.035	0.70	0.25-0.50		grain refining elements 0.12; Cu 0.20-0.60	
	480AT (70AT)					0.20	1.00-1.60	0.15-0.50	0.025	0.035	0.70	0.25-0.50		grain refining elements 0.12; Cu 0.20-0.60	
	550A (80A)					0.15	1.75	0.15-0.50	0.025	0.035	0.70	0.25-0.50		grain refining elements 0.15; Cu 0.20-0.60	
	550AT (80AT)					0.15	1.75	0.15-0.40	0.025	0.035	0.70	0.25-0.50		Cu 0.20-0.60	

3.4 Non-Comparable Carbon Steels for Structural Steel Plates

ASTM A 678/A 678I	VI-00a Quench	ed-and-Temper	ed Carbon and	l High-Strength	Low-Alloy Str	uctural Steel P	lates						
Grade, Class, Type Symbol or Name	D												
UNS Number	K12202												
ASTM A 709/A 709	ASTM A 709/A 709M-03a Carbon and High-Strength Low-Alloy Structural Steel Shapes, Plates, and Bars and Quenched-and-Tempered Alloy Structural Steel Plates for Bridges												
Grade, Class, Type Symbol or Name	50S [345S]	HPS 50W [HPS 345W]											
UNS Number													
ASTM A 1011/A 101	11M-03 Steel, \$	Sheet and Strip	, Hot-Rolled, C	arbon, Structu	ral, High-Streng	gth Low-Alloy	and High-Stren	gth Low-Alloy	with Improved	Formability			
Grade, Class, Type Symbol or Name	45 [310] Class 2	70 [480] Class 1	CS Type A	CS Type B	CS Type C	DS Type A	DS Type B						
UNS Number													
ISO 4950-2:1995 Hi	gh Yield Stren	gth Flat Steel P	roducts - Part	2: Products Su	upplied in the N	ormalized or C	ontrolled Rolle	ed Condition					
Grade, Class, Type Symbol or Name	E 460 CC	E 460 DD	E 460 E										
UNS Number													
ISO 4950-3:1995 Hi	gh Yield Stren	gth Flat Steel P	roducts - Part	3: Products Su	upplied in the H	eat-treated (Qu	uenched + Tem	pered) Conditi	on				
Grade, Class, Type Symbol or Name	E 550 DD	E 550 E	E 690 DD	E 690 E									
UNS Number													

98

3.5 Non-Comparable Alloy Steels for Structural Steel Plates

ASTM A 656/A 656	M-03 Hot-Rolle	d Structural Ste	eel, High-Stren	gth Low-Alloy	Plate with Imp	oved Formabil	ity					
Grade, Class, Type Symbol or Name	80											
UNS Number												
ASTM A 710/A 710	M-02 Precipitat	ion-Strengthen	ed Low-Carbo	n Nickel-Coppe	er-Chromium-N	lolybdenum-Co	lumbium Alloy	Structural Ste	el Plates			
Grade, Class, Type Symbol or Name	Grade B											
UNS Number												
CSA G40.21-04 Str	uctural Quality	Steel										
Grade, Class, Type Symbol or Name	480W (70W)	550W (80W)										
UNS Number												
EN 10113-2:1998 H	ot-rolled Produ	ucts in Weldabl	e Fine Grain S	tructural Steels	s - Part 2: Deliv	ery Conditions	for Normalized	/Normalized R	olled Steels			
Grade, Class, Type Symbol or Name	S275N	S275NL	S420N	S420NL	S460N	S460NL						
Steel Number	1.0490	1.0491	1.8902	1.8912	1.8901	1.8903						
EN 10113-3:1993 H	ot-rolled Produ	ucts in Weldabl	e Fine Grain S	tructural Steels	s - Part 3: Deliv	ery Conditions	for Thermome	chanical Rolled	d Steels			
Grade, Class, Type Symbol or Name	S275M	S275ML	S460M	S460ML								
Steel Number	1.8818	1.8819	1.8827	1.8838								
EN 10137-2:1996 P	lates and Wide	Flats Made of	High Yield Stre	ength Structura	I Steels in the	Quenched and	Tempered or P	recipitation Ha	ardened Condi	tions -	'	
Part 2: Delivery Co	nditions for Qu	uenched and Te	empered Steels	3								
Grade, Class, Type Symbol or Name	S890Q	S890QL	S890QL1	S960Q	S960QL							
Steel Number	1.8940	1.8983	1.8925	1.8941	1.8933							
		· · · · · · · · · · · · · · · · · · ·										

Chapter

4

PRESSURE VESSEL STEEL PLATES

ASTM Standards

ASTM A 203/A 203M-97 (2003) Pressure Vessel Plates, Alloy Steel, Molybdenum ASTM A 204/A 204M-03 ASTM A 240/A 240M-03c Chromium and Chromium-Nickel Stainless Steel Plate, Steel, Manganese-Vanadium-Nickel ASTM A 285/A 285M-03 Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength ASTM A 294/A 299M-02 Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength ASTM A 293/A 299M-02 Pressure Vessel Plates, Carbon Steel, Manganese-Silicon ASTM A 302/A 302M-03 Pressure Vessel Plates, Carbon Steel, Manganese-Silicon ASTM A 302/A 302M-03 Pressure Vessel Plates, Carbon Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 353/A 353M-93 (1999) Pressure Vessel Plates, Alloy Steel, Steel, Chromium-Molybdenum ASTM A 455/A 455M-03 Pressure Vessel Plates, Carbon Steel, High Strength Manganese ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, For Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Chromium-Molybdenum-Vanadium ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 642/A 642M-99 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Wi	ASTM A 202/A 202M-03	Pressure Vessel Plates, Alloy Steel, Chromium-Manganese-Silicon
ASTM A 204/A 204M-03 ASTM A 225/A 225M-03 Pressure Vessel Plates, Alloy Steel, Molybdenum ASTM A 240/A 240M-03c Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications ASTM A 289/A 298M-02 Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength Pressure Vessel Plates, Carbon Steel, Manganese-Silicon ASTM A 302/A 302M-03 Pressure Vessel Plates, Carbon Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum ASTM A 456/A 455M-03 Pressure Vessel Plates, Carbon Steel, High Strength Manganese ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, Figh Strength, Quenched and Tempered, Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Chromium-Molybdenum-Vandebunum		
ASTM A 240/A 240M-03c ASTM A 240/A 240M-03c Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications ASTM A 285/A 285M-03 Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength Pressure Vessel Plates, Carbon Steel, Manganese-Gilicon ASTM A 302/A 302M-03 Pressure Vessel Plates, Carbon Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 387/A 363M-93 (1999) Pressure Vessel Plates, Alloy Steel, Benzel Nickel, Double-Normalized and Tempered Pressure Vessel Plates, Alloy Steel, Percent Nickel, Double-Normalized and Tempered ASTM A 516/A 455M-03 Pressure Vessel Plates, Carbon Steel, High Strength Manganese ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, If Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Intermediate- and Tempered, Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-AsTM A 542/A 542M-99 MSTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Percent Nickel Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, Pressu	, ,	
ASTM A 240/A 240M-03c Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength Pressure Vessel Plates, Carbon Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 353/A 353M-93 (1999) Pressure Vessel Plates, Alloy Steel, Percent Nickel, Double-Normalized and Tempered Pressure Vessel Plates, Alloy Steel, Percent Nickel, Double-Normalized and Tempered Pressure Vessel Plates, Carbon Steel, Itigh Strength Manganese ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, Itigh Strength Manganese Pressure Vessel Plates, Carbon Steel, Itigh Strength Manganese Pressure Vessel Plates, Carbon Steel, Itigh Strength, Quenched and Tempered, Pressure Vessel Plates, Alloy Steel, Unenched and Tempered, Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Vanadhum Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Chromium-Molybdenum-Vanadhum Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadhum Pressure Vessel Plates, Alloy Steel, Quenched and Tempered S and 9 Percent Nickel Pressure Vessel Plates, Carbon Steel, Manganese-Tilinium for Glass or Diffused Metallic Coatings ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon Steel, High Strength, Icon Metallic Coatings ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon Steel, High Strength, Icon-Alloy Steel, Quenched and Tempered, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressu		
ASTM A 285/A 285M-03 Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength ASTM A 299/A 299M-02 Pressure Vessel Plates, Carbon Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 302/A 302M-03 ASTM A 303/A 353M-93 (1999) Pressure Vessel Plates, Alloy Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 387/A 387M-03 Pressure Vessel Plates, Alloy Steel, Percent Nickel, Double-Normalized and Tempered ASTM A 455/A 455M-03 Pressure Vessel Plates, Carbon Steel, Irigh Strength Manganese-Molybdenum ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, Irigh Strength Manganese-Molybdenum ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, for Moderate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Manganese-Molybdenum-Vanadium ASTM A 542/A 542M-99 Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon Steel, High-Strength, Low-Alloy Steel, Quenched-and-Tempered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grunder and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybden	A31W A 223/A 223W-03	
ASTM A 302/A 302M-02 Pressure Vessel Plates, Carbon Steel, Manganese-Silicon ASTM A 302/A 302M-03 Pressure Vessel Plates, Alloy Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered ASTM A 367/A 367M-03 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum ASTM A 456/A 455M-03 Pressure Vessel Plates, Carbon Steel, High Strength Manganese ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, For Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered, Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Specially Heat Treated Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Ouenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Ouenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybdenum-Columbium And Nickel-Copper-Manganese-Molybdenum-Columbium	ASTM A 240/A 240M-03c	General Applications
ASTM A 302/A 302M-03 ASTM A 353/A 353M-93 (1999) Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered ASTM A 353/A 353M-93 (1999) Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum ASTM A 455/A 455M-03 ASTM A 515/A 515M-03 Pressure Vessel Plates, Carbon Steel, Irigh Strength Manganese ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Intermediate- and Lower-Temperature Service ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service ASTM A 516/A 516M-93 Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service ASTM A 516/A 517M-93 (1999) Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered, Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-AstM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grunched and Tempered, Noderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grunched and Tempered, Noderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, Pressure Vessel Plates, Low-Carbon	ASTM A 285/A 285M-03	
ASTM A 337/A 353M-93 (1999) Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered ASTM A 387/A 387M-03 Pressure Vessel Plates, Carbon Steel, Chromium-Molybdenum Pressure Vessel Plates, Carbon Steel, For Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service Pressure Vessel Plates, Alloy Steel, High-Strength, Canched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Edip-Strength, Canched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched- and Tempered, Chromium-Molybdenum-NaSTM A 542/A 542M-99 Pressure Vessel Plates, Alloy Steel, Quenched- and Tempered, Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Steel, High Strength, Tor Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon Manganese-Silicon Steel, Ondocrate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Ondocrate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, or Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium Alloy Steel Pres	ASTM A 299/A 299M-02	Pressure Vessel Plates, Carbon Steel, Manganese-Silicon
ASTM A 387/A 387M-03 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum ASTM A 455/A 455M-03 Pressure Vessel Plates, Carbon Steel, High Strength, Manganese ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service ASTM A 516/A 516M-01 Pressure Vessel Plates, Alloy Steel, for Moderate- and Lower-Temperature Service Pressure Vessel Plates, Alloy Steel, Guenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum-Vanadium ASTM A 542/A 542M-99 Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel ASTM A 563/A 553M-95 (2000) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Gre Moderate and Lower Temperature Service ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Or Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Hi	ASTM A 302/A 302M-03	Pressure Vessel Plates, Alloy Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel
ASTM A 555/A 455M-03 ASTM S 516/A 515M-03 ASTM A 515/A 515M-03 ASTM A 516/A 515M-03 ASTM A 516/A 515M-03 Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service ASTM A 517/A 517M-93 (1999) Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered, ASTM A 533/A 533M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum, and Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 645/A 645M-99a Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grunched and Tempered for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grunched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel Pressure Vessel Plates, Low-Carbon Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plate	ASTM A 353/A 353M-93 (1999)	Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered
ASTM A 515/A 515M-03 Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service ASTM A 517/A 517M-93 (1999) Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered, Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum-Nickel ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched- and Tempered, Manganese-Molybdenum-Nickel Pressure Vessel Plates, Alloy Steel, Quenched- and-Tempered, Chromium-Molybdenum, and Chromium-Molybdenum-Vanadium ASTM A 542/A 542M-99 Pressure Vessel Plates, Alloy Steel, Quenched- and-Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 645/A 645M-99a Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Guenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Guenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Heat-Treated, Carb	ASTM A 387/A 387M-03	Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum
ASTM A 516/A 516M-01 Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service ASTM A 517/A 517M-93 (1999) Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered, ASTM A 533/A 533M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum, and Chromium-Molybdenum-Vanadium ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, For Moderate and Lower Temperature Service ASTM A 724/A 724M-99 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Ouenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched-and-Tempered ASTM A 734/A 734 M-87a (2003) Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 736/A 736M-03 Pressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 738/A 738M-030 Pressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 738/A 738M-030 Pressure Vessel Plates, Carbon-Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 782/A 782M-90 (2001) Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 832/A 832M-99 Pressure Vessel Pl	ASTM A 455/A 455M-03	Pressure Vessel Plates, Carbon Steel, High Strength Manganese
ASTM A 517/A 517M-93 (1999) Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered, Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum, and Chromium-Molybdenum-Vanadium ASTM A 543/A 542M-99 ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, Oressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, Oressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel, Fressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 736/A 736M-03 Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Plates, Plates, Plates, Plates, Plates, Plates, Plates, Pla	ASTM A 515/A 515M-03	Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service
ASTM A 533/A 533M-93 (1999) ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 542/A 542M-99 ASTM A 542M-99 ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum-Vanadium ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 645/A 645M-99a Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 662/A 662M-90 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grecially Heat Treated ASTM A 724/A 724M-99 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 735M-03 ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 737/A 737M-99 Pressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 738/A 738M-03a Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessel Plates, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 516/A 516M-01	
ASTM A 533/A 533M-93 (1999) ASTM A 537/A 537M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel ASTM A 542/A 542M-99 ASTM A 542M-99 ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum-Vanadium ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum-Vanadium ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 645/A 645M-99a Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 662/A 662M-90 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Grecially Heat Treated ASTM A 724/A 724M-99 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 735M-03 ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 737/A 737M-99 Pressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 738/A 738M-03a Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessel Plates, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 517/A 517M-93 (1999)	Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered,
ASTM A 537/A 537M-95 (2000) ASTM A 542/A 542M-99 ASTM A 543/A 543M-93 (1999) ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum, and Chromium-Molybdenum-Vanadium ASTM A 543/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 ASTM A 645/A 645M-99a Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, Quenched-and-Tempered ASTM A 734/A 734 M-87a (2003) Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 736/A 736M-03 ASTM A 738/A 738M-03a Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 82/A 82M-99 Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 533/A 533M-93 (1999)	Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-
ASTM A 542/A 543M-99 ASTM A 543/A 543M-93 (1999) ASTM A 553/A 543M-93 (1999) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service Pressure Vessel Plates, Five Percent Nickel Alloy Steel, Specially Heat Treated ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 735M-03 ASTM A 736/A 736M-03 ASTM A 736/A 736M-03 ASTM A 737/A 737M-99 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 738/A 738M-03a Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 537/A 537M-95 (2000)	,
ASTM A 543/A 543M-93 (1999) ASTM A 553/A 553M-95 (2000) ASTM A 553/A 553M-95 (2000) Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 645/A 645M-99a Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 735M-03 Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 738/A 738M-03a Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 542/A 542M-99	Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum, and Chromium-
ASTM A 553/A 553M-95 (2000) ASTM A 562/A 562M-90 (2001) ASTM A 612/A 612M-03 ASTM A 645/A 645M-99a ASTM A 662/A 662M-03 ASTM A 662/A 662M-03 ASTM A 724/A 724M-99 ASTM A 734/A 735M-03 ASTM A 735/A 735M-03 ASTM A 736/A 736M-03 ASTM A 736/A 738M-03a ASTM A 738/A 738M-03a ASTM A 782/A 782M-99 (2001) ASTM A 782/A 782M-99 (2001) ASTM A 782/A 782M-99 (2001) ASTM A 782/A 882M-99 ASTM A 782/A 882M-99 ASTM A 832/A 882M-99 ASTM A 832/A 882M-99 ASTM A 841/A 841M-03a Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Bressure Vessel Plates, Carbon-Manganese-Silicon Steel, Guenched and Tempered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 736M-03 ASTM A 737/A 737M-99 ASTM A 738/A 738M-03a ASTM A 738/A 738M-03a ASTM A 738/A 738M-03a ASTM A 782/A 782M-90 (2001) ASTM A 882/A 882M-99 ASTM A 882/A 882M-99 ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 543/A 543M-93 (1999)	,
ASTM A 562/A 562M-90 (2001) Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings ASTM A 612/A 612M-03 Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service ASTM A 645/A 645M-99a Pressure Vessel Plates, Five Percent Nickel Alloy Steel, Specially Heat Treated ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 724/A 724M-99 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Alloy Steel and High-Strength Low-Alloy Steel, Quenched-and-Tempered ASTM A 734/A 735M-03 Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 737/A 737M-99 Pressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 738/A 738M-03a Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 782/A 782M-90 (2001) Pressure Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	,	
ASTM A 612/A 612M-03 ASTM A 645/A 645M-99a ASTM A 645/A 645M-99a ASTM A 662/A 662M-03 ASTM A 724/A 724M-99 ASTM A 734/A 734 M-87a (2003) ASTM A 735/A 735M-03 ASTM A 736/A 736M-03 ASTM A 736/A 737M-99 ASTM A 737/A 737M-99 ASTM A 738/A 738M-03a ASTM A 738/A 738M-03 ASTM A 782/A 782M-90 (2001) ASTM A 832/A 832M-99 ASTM A 841/A 841M-03a Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	, ,	
ASTM A 645/A 645M-99a Pressure Vessel Plates, Five Percent Nickel Alloy Steel, Specially Heat Treated ASTM A 662/A 662M-03 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 724/A 724M-99 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessels ASTM A 734/A 734 M-87a (2003) Pressure Vessel Plates, Alloy Steel and High-Strength Low-Alloy Steel, Quenched-and-Tempered ASTM A 735/A 735M-03 Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 737/A 737M-99 Pressure Vessel Plates, High-Strength, Low-Alloy Steel ASTM A 738/A 738M-03a Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 782/A 782M-90 (2001) Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	` ,	
ASTM A 662/A 662M-03 ASTM A 724/A 724M-99 ASTM A 724/A 724M-99 ASTM A 734/A 734 M-87a (2003) ASTM A 735/A 735M-03 ASTM A 736/A 736M-03 ASTM A 737/A 737M-99 ASTM A 737/A 737M-99 ASTM A 738/A 738M-03a ASTM A 782/A 782M-90 (2001) ASTM A 782/A 832/A 832M-99 ASTM A 841/A 841M-03a Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessel Plates, Alloy Steel and High-Strength Low-Alloy Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium Alloy Steel Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel Pressure-Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)		
ASTM A 724/A 724M-99 Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered Pressure Vessels ASTM A 734/A 734 M-87a (2003) Pressure Vessel Plates, Alloy Steel and High-Strength Low-Alloy Steel, Quenched-and-Tempered Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel ASTM A 737/A 737M-99 Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 782/A 782M-90 (2001) Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 662/A 662M-03	
ASTM A 735/A 735M-03 Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 724/A 724M-99	Pressure Vessel Plates, Carbon-Manganese-Silicon Steel, Quenched and Tempered, for Welded Layered
Lower Temperature Service ASTM A 736/A 736M-03 ASTM A 736/A 736M-03 ASTM A 736/A 736M-03 ASTM A 737/A 737M-99 ASTM A 738/A 738M-03a ASTM A 738/A 738M-03a ASTM A 782/A 782M-90 (2001) ASTM A 832/A 832M-99 ASTM A 841/A 841M-03a Lower Temperature Service Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 734/A 734 M-87a (2003)	Pressure Vessel Plates, Alloy Steel and High-Strength Low-Alloy Steel, Quenched-and-Tempered
ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 735/A 735M-03	
ASTM A 737/A 737M-99 Pressure Vessel Plates, High-Strength, Low-Alloy Steel Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium ASTM A 832/A 832M-99 ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 736/A 736M-03	Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium
ASTM A 738/A 738M-03a Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service ASTM A 782/A 782M-90 (2001) Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 737/A 737M-99	, , , , ,
ASTM A 832/A 832M-99 ASTM A 841/A 841M-03a ASTM A 841/A 841/A ASTM A 841/A A	ASTM A 738/A 738M-03a	Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower
ASTM A 832/A 832M-99 Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 782/A 782M-90 (2001)	
ASTM A 841/A 841M-03a Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)	ASTM A 832/A 832M-99	
	ASTM A 841/A 841M-03a	
	ASTM A 844/A 844M-93 (1999)	

JIS Standards

JIS G 3103:1987	Carbon Steel and Molybdenum Alloy Steel Plates for Boilers and Other Pressure Vessels
JIS G 3115:2000	Steel Plates for Pressure Vessels for Intermediate Temperature Service
	·
JIS G 3115-1:1995	Steel Plates for Pressure Vessels for Intermediate Temperature Service-Part 1: Thicker Plates
JIS G 3118:2000	Carbon Steel Plates for Pressure Vessels for Intermediate and Moderate Temperature Service
JIS G 3119:1987	Manganese-Molybdenum Alloy and Manganese-Molybdenum-Nickel Alloy Steel Plates for Boilers and Other
JIS G 3119.1967	Pressure Vessels
JIS G 3120:1987	Manganese-Molybdenum and Manganese-Molybdenum-Nickel Alloy Steel Plates Quenched and Tempered
JIS G 3120.1967	for Pressure Vessels
JIS G 3124:1987	High Strength Steel Plates for Pressure Vessel for Intermediate and Moderate Temperature Service
JIS G 3126:2000	Carbon Steel Plates for Pressure Vessels for Low Temperature Service
JIS G 3127:2000	Nickel Steel Plates for Pressure Vessels for Low Temperature Service
JIS G 4109:1987	Chromium-Molybdenum Alloy Steel Plates for Boilers and Pressure Vessels
US C 4440:4003	High Strength Chromium-Molybdenum Alloy Steel Plates for Pressure Vessels Under High-Temperature
JIS G 4110:1993	Service

CEN Standards

EN 10028-2:2003	Flat Products Made of Steels for Pressure Purposes - Part 2: Non-Alloy and Alloy Steels With Specified Elevated Temperature Properties
EN 10028-3:2003	Flat Products Made of Steels for Pressure Purposes - Part 3: Weldable Fine Grain Steels, Normalized
EN 10028-4:2003	Flat Products Made of Steels for Pressure Purposes - Part 4: Nickel Alloy Steels With Specified Low Temperature Properties
EN 10028-5:2003	Flat Products Made of Steels for Pressure Purposes - Part 5: Weldable Fine Grain Steels, Thermomechanically Rolled
EN 10028-6:2003	Flat Products Made of Steels for Pressure Purposes - Part 6: Weldable Fine Grain Steels, Quenched and Tempered
EN 10028-7:2000	Flat Products Made of Steels for Pressure Purposes - Part 7: Stainless Steels

ISO Standards

ISO 9328-2:1991	Steel Plates and Strips for Pressure Purposes - Technical Delivery Conditions - Part 2: Unalloyed and Low- Alloyed Steels With Specified Room Temperature and Elevated Temperature Properties
ISO 9328-3:1991	Steel Plates and Strips for Pressure Purposes - Technical Delivery Conditions - Part 3: Nickel-Alloyed Steels With Specified Low Temperature Properties
ISO 9328-4:1991	Steel Plates and Strips for Pressure Purposes - Technical Delivery Conditions - Part 4: Weldable Fine Grain Steels With High Proof Stress Supplied In The Normalized or Quenched and Tempered Condition
ISO 9328-5:1991	Steel Plates and Strips for Pressure Purposes - Technical Delivery Conditions - Part 5: Austenitic Steels

Heat Treatment Terms Applicable to this Chapter

Standard	Heat Treatment Terms
ASTM A 203/A 203M-97 (2003)	N: normalized; QT: quenched and tempered
ASTM A 204/A 204M-03	AR: as-rolled; N: normalized
ASTM A 240/A 240M-03c	See standard
ASTM A 302/A 302M-03	AR: as-rolled: N: normalized
ASTM A 353/A 353M-93 (1999)	NNT: double-normalized and tempered
ASTM A 387/A 387M-03	A: annealed; NT: normalized and tempered
ASTM A 515/A 515M-03	AR: as-rolled; N: normalized
ASTM A 516/A 516M-03	AR: as-rolled; N: normalized
ASTM A 533/A 533M-93 (1999)	QT: quenched and tempered
ASTM A 537/A 537M-95	N: normalized; QT: quenched and tempered
ASTM A 553/A 553M-93	QT: quenched and tempered
ASTM A 612/A 612M-03	AR: as-rolled
ASTM A 662/A 662M-03	AR: as-rolled; N: normalized
ASTM A 737/A 737M-99	N: normalized
ASTM A 738/A 738M-03a	N: normalized; QT: quenched and tempered
ASTM A 841/A 841M-03a	TMCP: thermo-mechanical control process
ASTM A 844/A 844M-93 (1999)	Direct QT: direct quenched and tempered (quenched directly after rolling)
JIS G 3103:1987	AR: as-rolled; N: normalized
JIS G 3115:2000	AR: as-rolled
JIS G 3115-1:1995	AR: as-rolled
JIS G 3118:2000	AR: as-rolled; N: normalized
JIS G 3119:1987	AR: as-rolled; N: normalized
JIS G 3120:1987	QT: quenched and tempered
JIS G 3124:1987	R: as-rolled; N: normalized; NT: normalized and tempered; P: annealed
JIS G 3126:2000	N: normalized; QT: quench hardened and tempered; TMCP: thermo-mechanical control process
JIS G 3127:2000	N: normalized; QT: quench hardened and tempered; NNT: double normalized and tempered
JIS G 4109:1987	A: annealed; NT: normalized and tempered
JIS G 4110:1993	NT: normalized and tempered; QT: quench and tempered
EN 10028-2:2003	N: normalized; T: tempered; QA: air quenched; QL: liquid quenched
EN 10028-3:2003	N: normalized
	N: normalized; NT: normalized and tempered; NNT: double normalized and tempered;
EN 10028-4:2003	QT: quenched and tempered; HT640: NNT or QT (tempering at specified temperature);
	HT680: quenched followed by tempering at specified temperature
EN 10028-5:2003	TMCP: thermo-mechanical control process
EN 10028-6:2003	QT: quenched and tempered
EN 10028-7:2000	CR St, A: cold-rolled strip, annealed; HR St, A: hot-rolled strip, annealed; AT: solution annealed;
	HR PI, A: hot-rolled plate, annealed; HR PI, QT: hot-rolled plate, quenched and tempered
ISO 9328-2:1991	N: normalized; NT: normalized and tempered
ISO 9328-3:1991	N: normalized; NT: normalized and tempered; NNT: double-normalized and tempered;
	QT: quenched and tempered
ISO 9328-4:1991	N: normalized; N(+T): normalized and (if appropriate) tempered
ISO 9328-5:1991	Q: quenched

Impact Testing Notes Applicable to this Chapter

see standard for supplementary impact testing: the standard includes impact testing as a supplementary requirement (optional to the purchaser). see standard for impact data: impact testing requirements are listed in the standard for multiple test temperatures.

Standard	Grade, Class, Type,	Steel	UNS	Heat Treatment	Section T	hickness	Yield Strer	ngth, min	Tensile Strength, min		Elongation,	
Designation	Symbol or Name	Number			t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
					≤ 16		235				24	
EN 10000 0:0000					16 < t ≤ 40		225		360-480		24	27 J at 0°C
	P235GH	1.0345		N	40 < t ≤ 60		215		300-400		24	
EN 10028-2:2003	F235GF1	1.0345		IN	60 < t ≤ 100		200		350-480		24	
					100 < t ≤ 150		185				24	
					150 < t ≤ 250		170		340-480	0	24	
					$3 \le t \le 16$		235				25	
					16 < t ≤ 40		225		000 400		25	
ISO 9328-2:1991	P 235 PH 235			N	40 < t ≤ 60		215		360-480		25	27 J at 0°C
	F11 233				60 < t ≤ 100		200			24		
					100 < t ≤ 150		185 350-	350-480		24		

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section Th	nickness	Yield Strer	ngth, min	Tensile Strength, min		Elongation,	
Designation	Symbol or Name	Number			t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
					≤ 16		275					see standard for impact data
					16 < t ≤ 40		265		390-510		24	
EN 10028-3:2003	P275NH	1.0487		N	40 < t ≤ 60		255					
EN 10026-3:2003	P2/SINFI	1.0467		IN	60 < t ≤ 100		235		370-490			
					100 < t ≤ 150		225		360-480		23	
					150 < t ≤ 250		215		350-470			
					6 ≤ t ≤ 50		235				≤16 mm: 17	
JIS G 3115:2000	SPV235			AR	50 < t ≤ 100		215		400-510		>16 mm: 21	47 J at 0°C
					100 < t ≤ 150		195				>40 mm: 24	
JIS G 3103:1987	SB 410			AR	6 ≤ t ≤ 50		225		410-550		≤ 50 mm: 21	
	36 410			N	50 < t ≤ 200		225		410-550		> 50 mm: 25	
JIS G 3118:2000	SGV410			AR	6 ≤ t ≤ 38		225		410-490		≤ 50 mm: 21	
313 G 31 16.2000	367410			N	38 < t ≤ 200		225		410-490		> 50 mm: 25	
	P265GH				≤ 16		265				22	
		1.0425		N	16 < t ≤ 40		255		410-530		22	
EN 10028-2:2003					40 < t ≤ 60		245		410-330		22	27 J at 0°C
LN 10020-2.2003		1.0423			60 < t ≤ 100		215				22	27 J at 0 C
					100 < t ≤ 150		200		400-530		22	
					150 < t ≤ 250		185		390-530		22	
					3 ≤ t ≤ 16		265				24	
	D 005				16 < t ≤ 40		255		410-530		24	
ISO 9328-2:1991	P 265 PH 265			N	40 < t ≤ 60		245		410-330		23	27 J at 0°C
					60 < t ≤ 100		215				22	
					100 < t ≤ 150		200		400-530		22	
ASTM A 515/A 515M-03	60 [415]		K02401	AR	≤ 50	≤ 2	220	32	415-550	60-80	25	
A3 TW A 3 T3/A 3 T3W-03	00 [415]		N02401	N	> 50	> 2	220	32	415-550	00-00	25	
ASTM A 516/A 516M-03	60 [415]		K02100	AR	≤ 40	≤ 1.5	220	32	415-550	60-80	25	
ASTIVI A STO/A STOVI-US	00 [415]		102100	N	> 40	> 1.5	220	32	410-000	00-00	25	
	P 315 TN				≤ 35		315					
ISO 9328-4:1991	PH 315 TN			N	35 < t ≤ 50		305			23	23	see standard for impact data
	PL 315 TN				50 < t ≤ 70		295					iiiipaot data

4.1A Mechanical Properties of Carbon Steels for Pressure Vessel Plates (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile Strength, min		Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 515/A 515M-03	65 [450]		K02800	AR	≤ 50	≤ 2	240	35	450-585	65-85	23	
ASTIVI A 313/A 313IVI-U3	65 [450]		KU2800	N	> 50	> 2	240	35	450-565	65-85	23	
ASTM A 516/A 516M-03	65 [450]		K02403	AR	≤ 40	≤ 1.5	240	35	450-585	65-85	23	
ASTM A STO/A STOM-03	65 [450]		KU24U3	N	> 40	> 1.5	240	35	430-363	00-00	23	
JIS G 3103:1987	SB 450			AR	6 ≤ t ≤ 50		245		450-590		≤ 50 mm: 19	
313 G 3103.1987	36 450			N	50 < t ≤ 200		245		450-590		> 50 mm: 23	
JIS G 3118:2000	SGV450			AR	$6 \le t \le 38$		245		450-540		≤ 50 mm: 19	
313 G 31 18.2000	30,450			N	38 < t ≤ 200		245		450-540		> 50 mm: 23	
					≤ 16		295				21	
					16 < t ≤ 40		290		460-580		21	
EN 10028-2:2003	P295GH	1.0481		N	$40 < t \leq 60$		285		400-300		21	27 J at 0°C
LN 10020-2.2003		1.0461		IN .	$60 < t \le 100$		260				21	27 J at 0 C
					$100 < t \le 150$		235		440-570		21	
					$150 < t \leq 250$		220		430-570		21	
					$3 \le t \le 16$		290				22	
					$16 < t \leq 40$		285		460-580		22	
ISO 9328-2:1991	P 290 PH 290			N	$40 < t \leq 60$		280		400-300		22	27 J at 0°C
	200				$60 < t \leq 100$		255				21	
					$100 < t \leq 150$		230		440-570		21	
JIS G 3103:1987	SB 480			AR	$6 \le t \le 50$		265		480-620		≤ 50 mm: 17	
010 0 0100.1007	OB 400			N	$50 < t \le 200$		200		400 020		> 50 mm: 21	
JIS G 3118:2000	SGV480			AR	$6 \le t \le 38$		265		480-590		≤ 50 mm: 17	
010 0 01 10.2000	000			N	$38 < t \le 200$		200		400 000		> 50 mm: 21	
ASTM A 515/A 515M-03	70 [485]		K03101	AR	≤ 50	≤ 2	260	38	485-620	70-90	21	
AGTIVI A GTO/A GTOWN OU	70 [700]		1.00101	N	> 50	> 2	200		-100-020	70-30		
ASTM A 516/A 516M-03	70 [485]		K02700	AR	≤ 40	≤ 1.5	260	38	485-620	70-90	21	
AGTIVIA GTO/A GTOWN OU	70 [700]		1.02700	N	> 40	> 1.5	200		100 020	70-30		
ASTM A 537/A 537M-95 (2000)	10)		K12437	N	≤ 65	≤ 21/2	345	50	485-620	70-90	22	
7.0 11VI A 301/A 301 IVI-33 (2000)	ı ı		1112407	IN	$65 < t \le 100$	$2\frac{1}{2} < t \le 4$	310	45	450-585	65-85		
ASTM A 737/A 737M-99	В		K12001	N			345	50	485-620	70-90	23	

NOTE: This section continued on next page.

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section TI	nickness	Yield Strer	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name			Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					$6 \le t \le 50$		315				≤16 mm: 16	
JIS G 3115:2000	SPV315			AR	50 < t ≤ 100		295		490-610		>16 mm: 20	47 J at 0°C
					$100 < t \le 150$		275				>40 mm: 23	
					≤ 16		355					
					$16 < t \le 40$		345		490-630		22	
EN 10028-3:2003	P355N	1.0562		N	40 < t ≤ 60		335					see standard for
	P355NH	1.0565		IN	60 < t ≤ 100		315		470-610			impact data
					100 < t ≤ 150		305		460-600		21	
					150 < t ≤ 250		295		450-590			
					3 ≤ t ≤ 16		315				21	
					16 < t ≤ 40		310		400.610		21	
ISO 9328-2:1991	P 315 PH 315			N	40 < t ≤ 60		305		490-610		21	27 J at 0°C
	111010				60 < t ≤ 100		280		1		20	
					100 < t ≤ 150		255		470-600		20	

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section TI	hickness	Yield Strer	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number			t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 50		370		510-650		16	
JIS G 3124:1987	SEV 245			R, N, NT	50 < t ≤ 100		355		310-030		20	31 J at 0°C
515 G 5124.1967	3LV 243			or P	100 < t ≤ 125		345		500-640		20	31 J at 0 C
					125 < t ≤ 150		335		490-630		20	
					≤ 16		355					
					16 < t ≤ 40		345		510-650			
EN 10028-2:2003	P355GH	1.0473		N	40 < t ≤ 60		335				20	07 Let 0°C
EN 10026-2.2003	Рэээсп	1.0473		IN	60 < t ≤ 100		315		490-630		20	27 J at 0°C
					100 < t ≤ 150		295		480-630			
					150 < t ≤ 250		280		470-630			
					3 < t ≤ 16		355				21	
					16 < t ≤ 40		345		510-650		21	
	P 355			N	40 < t ≤ 60		335		1		21	27 J at 0°C
					60 < t ≤ 100		315		500-650		20	
100 0000 0:1001					100 < t ≤ 150		295		490-640		20	
ISO 9328-2:1991					3 < t ≤ 16		355				21	
					16 < t ≤ 40		345		510-650		21	
	PH 355			N	40 < t ≤ 60		335		1		21	27 J at 0°C
					60 < t ≤ 100		315		500-650		20	
					100 < t ≤ 150		295		490-640		20	
ASTM A 738/A 738M-03a	A		K12447	N or QT	≤ 65	≤ 2½	310	45	515-655	7E 0E	20	
ASTIVI A 130/A 1301VI-U3A	A		K12447	QT	> 65	> 21/2	310	45	313-033	75-95	20	
					6 ≤ t ≤ 50		355				≤16 mm: 14	
JIS G 3115:2000	SPV 355			AR	50 < t ≤ 100		335		520-640		>16 mm: 18	47 J at 0°C
					100 < t ≤ 150		315		1		>40 mm: 21	

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Stren	gth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 65	≤ 2½	415	60	550-690	80-100	22	
	2		K12437	QT	65 < t ≤ 100	$2\frac{1}{2} < t \le 4$	380	55	515-655	75-95	22	
ASTM A 537/A 537M-95 (2000)					100 < t ≤ 150	4 < t ≤ 6	315	46	485-620	70-90	20	
ASTIVI A 557/A 557WI-95 (2000)					≤ 65	≤ 2½	380	55	550-690	80-100	22	
	3		K12437	QT	65 < t ≤ 100	$2\frac{1}{2} < t \le 4$	345	50	515-655	75-95	22	
					100 < t ≤ 150	4 < t ≤ 6	275	40	485-620	70-90	20	
ASTM A 737/A 737M-99	С		K12202	N			415	60	550-690	80-100	23	
					≤ 65	≤ 2½	415	60	550-690	80-100	22	
ASTM A 738/A 738M-03a	С			QT	65 < t ≤ 100	2½ < t ≤ 4	380	55	515-655	75-95	22	
					> 100	> 4	315	46	485-620	70-90	20	
					6 < t ≤ 50		410					
JIS G 3115:2000	SPV410			TMCP	50 < t ≤ 100		390		550-670		see standard	47 J at -10°C
					100 < t ≤ 150		370					
ASTM A 612/A 612M-03			K02900	AR	≤ 12.5	≤ 1/2	345	50	570-725	83-105	22	
ASTIVI A 612/A 612IVI-03			K02900	An	12.5 < t ≤ 25	½ < t ≤ 1	345	50	560-695	81-101	22	
					6 < t ≤ 50		450					
JIS G 3115:2000	SPV450			QT	50 < t ≤ 100		430		570-700		see standard	47 J at -10°C
					100 < t ≤ 150		410					
ASTM A 738/A 738M-03a	В		K12001	QT			415	60	585-705	85-102	20	

4.1B Chemical Composition of Carbon Steel Pressure Plates

Standard	Grade, Class,	Steel	UNS	Section Th	ickness				Weight, 9	%, Maximu	m, Unless	Otherwise	Specified	d
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10028-2:1992	P235GH	1.0345				0.16	0.60-1.20	0.35	0.025	0.015	0.30	0.30	0.08	Cu 0.30; Nb 0.020; Ti 0.03; V 0.02; Al ≥ 0.020; N 0.012; Cr+Cu+Mo+Ni 0.70
ISO 9328-2:1991	P 235 PH 235					0.17	0.40-1.20	0.35	0.035	0.030	0.30	0.30	0.08	Cu 0.30; Al ≥ 0.020; Cr+Cu+Mo+Ni 0.70
EN 10028-3:2003	P275NH	1.0487				0.16	0.80-1.50	0.40	0.025	0.015	0.30	0.30	0.08	Cu 0.30; Nb 0.05; Ti 0.03; V 0.05; N 0.012; Al ≥ 0.020; Nb+Ti+V 0.05; Cr+Cu+Mo0.45
JIS G 3115:2000	SPV235			≤ 100		0.18	1.40	0.15-0.35	0.030	0.030				
315 G 31 15:2000	5PV235			> 100		0.20	1.40	0.15-0.35	0.030	0.030				
				≤ 25		0.24	0.90	0.15-0.30	0.035	0.040				
JIS G 3103:1987	SB 410			25 < t ≤ 50		0.27	0.90	0.15-0.30	0.035	0.040				
				50 < t ≤ 200		0.30	0.90	0.15-0.30	0.035	0.040				
				≤ 12.5		0.21	0.85-1.20	0.15-0.40	0.030	0.030				
WO O 0440 0000	001/440			12.5 < t ≤ 50		0.23	0.85-1.20	0.15-0.40	0.030	0.030				
JIS G 3118:2000	SGV410			50 < t ≤ 100		0.25	0.85-1.20	0.15-0.40	0.030	0.030				
				100 < t ≤ 200		0.27	0.85-1.20	0.15-0.40	0.030	0.030				
EN 10028-2:2003	P265GH	1.0425				0.20	0.80-1.40	0.40	0.025	0.015	0.30	0.30	0.08	Cu 0.30; Nb 0.020; Ti 0.03; V 0.02; Al ≥ 0.020; N 0.012; Cr+Cu+Mo+Ni 0.70
ISO 9328-2:1991	P 265 PH 265					0.20	0.50-1.40	0.35	0.035	0.030	0.30	0.30	0.08	Cu 0.30; Al ≥ 0.020; Cr+Cu+Mo+Ni 0.70
				≤ 25	≤ 1	0.24	0.90	0.15-0.40	0.035	0.035				
				25 < t ≤ 50	1 < t ≤ 2	0.27	0.90	0.15-0.40	0.035	0.035				
ASTM A 515/A 515M-03	60 [415]		K02401	50 < t ≤ 100	2 < t ≤ 4	0.29	0.90	0.15-0.40	0.035	0.035				
				$100 < t \le 200$	4 < t ≤ 8	0.31	0.90	0.15-0.40	0.035	0.035				
				> 200	> 8	0.31	0.90	0.15-0.40	0.035	0.035				
				≤ 12.5	≤ 1/2	0.21	0.60-0.90	0.15-0.40	0.035	0.035				
				12.5 < t ≤ 50	½ < t ≤ 2	0.23	0.85-1.20	0.15-0.40	0.035	0.035				
ASTM A 516/A 516M-03	60 [415]		K02100	50 < t ≤ 100	2 < t ≤ 4	0.25	0.85-1.20	0.15-0.40	0.035	0.035				
				100 < t ≤ 200	4 < t ≤ 8	0.27	0.85-1.20	0.15-0.40	0.035	0.035				
				> 200	> 8	0.27	0.85-1.20	0.15-0.40	0.035	0.035				
ISO 9328-4:1991	P 315 TN PH 315 TN					0.18	0.70-1.50	0.10-0.40	0.035	0.035	0.30	0.30	0.08	Cu 0.30; Nb 0.05; Ti 0.03; V 0.05; N 0.020; Al ≥ 0.020;
	PL 315 TN					0.16	0.70-1.50	0.10-0.40	0.030	0.030				Nb+Ti+V 0.05; Cr+Cu+Mo 0.45

4.1B Chemical Composition of Carbon Steel Pressure Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section Th	ickness				Weight, 9	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol, or Name	Number		t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
				≤ 25	≤ 1	0.28	0.90	0.15-0.40	0.035	0.035				
				25 < t ≤ 50	1 < t ≤ 2	0.31	0.90	0.15-0.40	0.035	0.035				
ASTM A 515/A 515M-03	65 [450]		K02800	50 < t ≤ 100	2 < t ≤ 4	0.33	0.90	0.15-0.40	0.035	0.035				
				100 < t ≤ 200	4 < t ≤ 8	0.33	0.90	0.15-0.40	0.035	0.035				
				> 200	> 8	0.33	0.90	0.15-0.40	0.035	0.035				
				≤ 12.5	≤ 1/2	0.24	0.85-1.20	0.15-0.40	0.035	0.035				
				12.5 < t ≤ 50	½ < t ≤ 2	0.26	0.85-1.20	0.15-0.40	0.035	0.035				
ASTM A 516/A 516M-03	65 [450]		K02403	50 < t ≤ 100	$2 < t \le 4$	0.28	0.85-1.20	0.15-0.40	0.035	0.035				
				$100 < t \le 200$	$4 < t \le 8$	0.29	0.85-1.20	0.15-0.40	0.035	0.035				
				> 200	> 8	0.29	0.85-1.20	0.15-0.40	0.035	0.035				
				≤ 25		0.28	0.90	0.15-0.30	0.035	0.040				
JIS G 3103:1987	SB 450			25 < t ≤ 50		0.31	0.90	0.15-0.30	0.035	0.040				
				50 < t ≤ 100		0.33	0.90	0.15-0.40	0.035	0.040				
				≤ 12.5		0.24	0.85-1.20	0.15-0.40	0.030	0.030				
JIS G 3118:2000	SGV450			$12.5 < t \le 50$		0.26	0.85-1.20	0.15-0.40	0.030	0.030				
JIS G 31 16.2000	307450			50 < t ≤ 100		0.28	0.85-1.20	0.15-0.40	0.030	0.030				
				$100 < t \le 200$		0.29	0.85-1.20	0.15-0.40	0.030	0.030				
EN 10028-2:2003	P295GH	1.0481				0.08-0.20	0.90-1.50	0.40	0.025	0.015	0.30	0.30	0.08	Cu 0.30; Nb 0.020; Ti 0.03; V 0.02; Al ≥ 0.020; N 0.012; Cr+Cu+Mo+Ni 0.70
ISO 9328-2:1991	P 290					0.20	0.90-1.50	0.40	0.035	0.030	0.30	0.30	0.08	Cu 0.30; Al ≥ 0.020;
130 9320-2.1991	PH 290					0.14-0.20	0.90-1.50	0.40	0.033	0.030	0.30	0.30	0.06	Cr+Cu+Mo+Ni 0.70
				≤ 25		0.31	0.90	0.15-0.30	0.035	0.040				
JIS G 3103:1987	SB 480			25 < t ≤ 50		0.33	0.90	0.15-0.30	0.035	0.040				
				50 < t ≤ 200		0.35	0.90	0.15-0.30	0.035	0.040				
				≤ 12.5		0.27	0.85-1.20	0.15-0.40	0.030	0.030				
JIS G 3118:2000	SGV480			12.5 < t ≤ 50		0.28	0.85-1.20	0.15-0.40	0.030	0.030				
013 G 31 10.2000	30 7400			50 < t ≤ 100		0.30	0.85-1.20	0.15-0.40	0.030	0.030				
				100 < t ≤ 200		0.31	0.85-1.20	0.15-0.40	0.030	0.030				

NOTE: This section continued on next page.

4.1B Chemical Composition of Carbon Steel Pressure Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section Th	ickness			W	/eight, %,	Maximum,	Unless O	therwise S	pecified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
				≤ 25	≤ 1	0.31	1.20	0.15-0.40	0.035	0.035				
				25 < t ≤ 50	$1 < t \le 2$	0.33	1.20	0.15-0.40	0.035	0.035				
ASTM A 515/A 515M-03	70 [485]		K03101	50 < t ≤ 100	$2 < t \le 4$	0.35	1.20	0.15-0.40	0.035	0.035				
				$100 < t \le 200$	$4 < t \leq 8$	0.35	1.20	0.15-0.40	0.035	0.035				
				> 200	> 8	0.35	1.20	0.15-0.40	0.035	0.035				
				≤ 12.5	≤ 1/2	0.27	0.85-1.20	0.15-0.40	0.035	0.035				
				$12.5 < t \le 50$	$1/2 < t \le 2$	0.28	0.85-1.20	0.15-0.40	0.035	0.035				
ASTM A 516/A 516M-03	70 [485]		K02700	50 < t ≤ 100	$2 < t \leq 4$	0.30	0.85-1.20	0.15-0.40	0.035	0.035				
				$100 < t \le 200$	$4 < t \leq 8$	0.31	0.85-1.20	0.15-0.40	0.035	0.035				
				> 200	> 8	0.31		0.15-0.40	0.035	0.035				
ASTM A 537/A 537M-95 (2000)	1		K12437	≤ 40	≤ 1½	0.24	0.70-1.35	0.15-0.50	0.035	0.035	0.25	0.25	0.08	Cu 0.35
	·			> 40	> 1½	V.= .	1.00-1.60	0.10		0.000		0.20	0.00	000
ASTM A 737/A 737M-99	В		K12001			0.20	1.15-1.50	0.15-0.50	0.035	0.030				Cb 0.05
JIS G 3115:2000	SPV315					0.18	1.60	0.15-0.55	0.030	0.030				
ISO 9328-2:1991	P 315					0.20	0.00.1.60	0.10-0.50	0.035	0.030	0.30	0.30	0.08	Cu 0.30; Al ≥ 0.020;
130 3320-2.1331	PH 315					0.15-0.20	0.90-1.00	0.10-0.50	0.035	0.030	0.30	0.30	0.06	Cr+Cu+Mo+Ni 0.70

4.1B Chemical Composition of Carbon Steel Pressure Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section Th	ickness			V	Veight, %,	Maximum	, Unless O	therwise S	Specified	
Designation	Type, Symbol, or Name	Number		t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 3124:1987	SEV 245			6 ≤ t ≤ 150		0.20	0.80-1.60	0.15-0.60	0.035	0.035			0.35	Cu 0.35; Nb 0.05; V 0.10
EN 10028-2:2003	P355GH	1.0473				0.10-0.22	1.10-1.70	0.60	0.025	0.015	0.30	0.30	0.08	Cu 0.30; Nb 0.020; Ti 0.03; V 0.02; Al ≥ 0.020; N 0.012 Cr+Cu+Mo+Ni 0.70
ISO 9328-2:1991	P 355					0.22	0.90-1.60	0.10-0.50	0.035	0.030	0.30	0.30	0.08	Al 0.020; Cu 0.30
150 9328-2:1991	PH 355					0.15-0.22	0.90-1.60	0.10-0.50	0.035	0.030	0.30	0.30	0.08	Al 0.020; Cu 0.30
A CTAA A 700/A 700M 00-			K12447	≤ 65	≤ 2½	0.24	1.50	0.15-0.50	0.035	0.035	0.25	0.50	0.08	Cu 0.35; V 0.07; Cb 0.04; Cb+V 0.08
ASTM A 738/A 738M-03a	A		K12447	> 65	> 2½	0.24	1.60	0.15-0.50	0.035	0.035	0.25	0.50	0.08	Cu 0.35; V 0.07; Cb 0.04; Cb+V 0.08
JIS G 3115:2000	SPV 355					0.20	1.60	0.15-0.55	0.030	0.030				
	2		K12437	≤ 40	≤ 1½	0.24	0.70-1.35	0.15-0.50	0.035	0.035	0.25	0.25	0.08	Cu 0.35
ACTM A 527/A 527M OF (2000)	2		K12437	> 40	> 1½	0.24	1.00-1.60	0.15-0.50	0.035	0.035	0.25	0.25	0.06	Cu 0.55
ASTM A 537/A 537M-95 (2000)	3		K12437	≤ 40	≤ 1½	0.24	0.70-1.35	0.15-0.50	0.035	0.005	0.25	0.05	0.08	Cu 0.35
	3		K12437	> 40	> 1½	0.24	1.00-1.60	0.15-0.50	0.035	0.035	0.25	0.25	0.08	Cu 0.35
ASTM A 737/A 737M-99	С		K12202			0.22	1.15-1.50	0.10-0.55	0.035	0.030				V 0.04-0.11; N 0.03
ACTNA A 700/A 700NA 00-	0			≤ 65	≤ 2½	0.20	1.50	0.45.0.50	0.005	0.005	0.05	0.50	0.00	O., 0.05, V.0.05
ASTM A 738/A 738M-03a	С			> 65	> 2½	0.20	1.60	0.15-0.50	0.025	0.025	0.25	0.50	0.08	Cu 0.35; V 0.05
JIS G 3115:2003	SPV410					0.18	1.60	0.15-0.75	0.030	0.030				
ASTM A 612/A 612M-03			K02900			0.25	1.00-1.50	0.15-0.50	0.035	0.025	0.25	0.25	0.08	Cu 0.35; V 0.08
JIS G 3115:2003	SPV450					0.18	1.60	0.15-0.75	0.030	0.030				
				≤ 40	≤ 1½	0.20	0.90-1.50	0.15-0.55	0.030	0.030	0.30	0.60	0.20	
ASTM A 738/A 738M-03a	В		K12001	40 ≤ t ≤ 65	1½ ≤ t ≤ 2½	0.20	0.90-1.50	0.15-0.55	0.030	0.030	0.30	0.60	0.30	Cu 0.35; V 0.07; Cb 0.04; Cb+V 0.08
				> 65	> 2½	0.20	0.90-1.60	0.15-0.55	0.030	0.030	0.30	0.60	0.30	

4.2 Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C

Mechanical Properties of Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section TI	hickness	Yield Strei	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name			Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	P 255 TN				≤ 35		255					
ISO 9328-4:1991	PH 255 TN			N	35 < t ≤ 50		245		360-480		25	see standard for impact data
	PL 255 TN				50 < t ≤ 70		235					impaot data
					≤ 16		275					
					16 < t ≤ 40		265		390-510		24	
EN 10028-3:2003	P275NL1	1.0488		N	40 < t ≤ 60		255		370-490			see standard for
EN 10020-3.2003	P275NL2	1.1104		IN	60 < t ≤ 100		235					impact data
					100 < t ≤ 150		225		360-480		23	
					150 < t ≤ 250		215		360-480 350-470			
	P 285 TN				≤ 35		285					
ISO 9328-4:1991	PH 285 TN			N	35 < t ≤ 50		275		390-510		24	see standard for impact data
	PL 285 TN				50 < t ≤ 70		265					impaot data
ASTM A 662/A 662M-03	А		K01701	N			275	40	400-540	58-78	23	see standard for supplementary impact testing
					≤ 40		235				6-16 mm: 18	see standard for
JIS G 3126:2000	SLA 235 A, B			N	>40		215		400-510		>16 mm: 22 >40 mm: 24	impact data
010 0 0120.2000	SLA 325 A			N			325		440-560		6-16 mm: 22	see standard for
	SLA 325 B			QT			325		440-560		>16 mm: 30 >20 mm: 22	impact data

Mechanical Properties of Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name			Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	В		K02203	AR	≤ 40	≤ 1½	275	40	450-585	65-85	23	
ASTM A 662/A 662M-03	D		KU22U3	N	> 40	> 1½	2/5	40	450-565	65-85	23	
ASTIVI A 002/A 002IVI-US	С		K02007	AR	≤ 40	≤ 1½	295	40	485-620	70-90	22	
	C		K02007	N	> 40	> 1½	295	43	460-620	70-90	22	
ASTM A 841/A 841M-03a	A D C Class 1			TMCP	≤ 65	≤ 2½	345	50	480-620	70-90	22	00 1 -1 4000
ASTIVI A 641/A 6411VI-USA	A, B, C, Class 1			TIVICE	> 65	> 21/2	310	45	450-585	65-85	22	20 J at -40°C
					≤ 16		355					
	P355N	1.0562			16 < t ≤ 40		345				22	
EN 10000 0.0000	P355NH	1.0565		N	40 < t ≤ 60		335					see standard for
EN 10028-3:2003	P355NL1	1.0566		IN .	60 < t ≤ 100		315					impact data
	P355NL2	1.1106			100 < t ≤ 150		305		460-600		21	
					150 < t ≤ 250		295		450-590			
	P 355 TN				≤ 35		355					
ISO 9328-4:1991	PH 355 TN PL 355 TN			N(+T)	35 < t ≤ 50		345		490-610		22	see standard for impact data
	PLH 355 TN				50 < t ≤ 70		325					impaci data
JIS G 3126:2000	SLA 365			QT			365		490-610		6-16 mm: 20 >16 mm: 28 >20 mm: 20	see standard for impact data
JIS G 3126:2000	SLA 410			QT or TMCP			410		520-640		6-16 mm: 18 >16 mm: 26 >20 mm: 18	see standard for impact data
ASTM A 841/A 841M-03a	A, B, C, Class 2			TMCP	≤ 65	≤ 21/2	415	60	550-690	80-100	22	20 J at -40°C
AG 1 W A 04 1/A 04 1 W-03d	A, D, O, Olass 2			TIVIOF	> 65	> 21/2	380	55	515-655	75-95	22	20 J at -40 C

4.2 Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C

4.2B Chemical Composition of Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C

Standard	Grade, Class,		UNS	Section T	hickness			V	Veight, %,	Maximum,	Unless O	therwise S	pecified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ISO 9328-4:1991	P 255 TN PH 255 TN					0.17	0 50-1 40	0.10-0.35	0.035	0.035	0.30	0.30	0.08	Cu 0.30; Nb 0.05; Ti 0.03; V 0.05; N 0.020; Al ≥ 0.020;
100 0020 4.1001	PL 255 TN					0.15	0.30 1.40	0.10 0.00	0.030	0.030	0.00	0.00	0.00	Nb+Ti+V 0.05; Cr+Cu+Mo 0.45
EN 10028-3:2003	P275NL1	1.0488				0.16	0.80-1.50	0.40	0.025	0.015	0.30	0.30	0.08	Cu 0.30; Nb 0.05; Ti 0.03; V 0.05; N 0.012; Al ≥ 0.020;
214 10020 0:2000	P275NL2	1.1104				0.10	0.00 1.00	0.10	0.020	0.010	0.00	0.00	0.00	Nb+Ti+V 0.05; Cr+Cu+Mo 0.45
ISO 9328-4:1991	P 285 TN PH 285 TN					0.18	0 50-1 40	0.10-0.40	0.035	0.035	0.30	0.30	0.08	Cu 0.30; Nb 0.05; Ti 0.03; V 0.05; N 0.020; Al ≥ 0.020;
100 0020 4.1001	PL 285 TN					0.16	0.00 1.40	0.10 0.40	0.030	0.030	0.00	0.00	0.00	Nb+Ti+V 0.05; Cr+Cu+Mo 0.45
ASTM A 662/A 662M-03	Α		K01701			0.14	0.90-1.35	0.15-0.40	0.035	0.035				
JIS G 3126:2000	SLA 235 A,B			6 ≤ t ≤ 50		0.15	0.70-1.50	0.15-0.30	0.030	0.025				
013 G 3120.2000	SLA 325 A,B			$6 \le t \le 32$		0.16	0.80-1.60	0.15-0.55	0.030	0.025				

4.2 Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C

4.2B Chemical Composition of Carbon Steels for Pressure Vessel Plates - With Impact Testing Below -20°C

Standard	Grade, Class,	STEEL	UNS	Section T	hickness			V	Veight, %,	Maximum	, Unless O	therwise S	pecified	
Designation	Type, Symbol, or Name	Number		t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 662/A 662M-03	В		K02203			0.19	0.85-1.50	0.15-0.40	0.035	0.035				
ASTIVI A 002/A 002/VI-03	С		K02007			0.20	1.00-1.60	0.15-0.50	0.035	0.035				
	A, Class 1			≤ 40	≤ 1½	0.20	0.70-1.35	0.15-0.50	0.030	0.030	0.25	0.25	0.08	Cu 0.35; V 0.06; Cb 0.03;
	A, Class I			> 40	> 1½	0.20	1.00-1.60	0.15-0.50	0.030	0.030	0.25	0.23	0.06	AI ≥ 0.020
ASTM A 841/A 841M-03a	B, Class 1			≤ 40	≤ 1½	0.15	0.70-1.35	0.15-0.50	0.030	0.025	0.25	0.60	0.30	Cu 0.35; V 0.06; Cb 0.03;
ASTIVI A 641/A 641IVI-USA	b, Class I			> 40	> 1½	0.15	1.00-1.60	0.15-0.50	0.030	0.025	0.25	0.60	0.30	AI ≥ 0.020
	C, Class 1			≤ 40	≤ 1½	0.10	0.70-1.60	0.15-0.50	0.030	0.015	0.25	0.25	0.08	Cu 0.35; V 0.06; Cb 0.06;
	C, Class I			> 40	> 1½	0.10	1.00-1.60		0.030	0.015	0.25	0.25	0.06	Ti 0.006-0.02
	P355N	1.0562												Cu 0.30; Nb 0.05; Ti 0.03;
EN 10028-3:2003	P355NH	1.0565				0.18	1.10-1.70	0.50	0.025	0.015	0.30	0.50	0.08	V 0.10; N 0.012; Al ≥ 0.020;
LIN 10020-3.2003	P355NL1	1.0566				0.16	1.10-1.70	0.50			0.30	0.50	0.00	Nb+Ti+V 0.12;
	P355NL2	1.1106							0.020	0.010				Cr+Cu+Mo 0.45
ISO 9328-4:1991	P 355 TN PH 355 TN					0.20	0.00.1.7	0.10-0.50	0.035	0.035	0.30	0.30	0.08	Cu 0.30; Nb 0.05; Ti 0.03; N 0.020; V 0.10; Al ≥ 0.020;
130 9326-4.1991	PL 355 TN PLH 355 TN					0.18	0.90-1.7	0.10-0.50	0.030	0.030	0.30	0.30	0.06	Nb+Ti+V 0.12; Cr+Cu+Mo 0.45
JIS G 3126:2000	SLA 365			6 ≤ t ≤ 32		0.18	0.80-1.60	0.15-0.55	0.030	0.025				
JIS G 3126:2000	SLA 410			6 ≤ t ≤ 32		0.18	0.80-1.60	0.55	0.030	0.025				
	A Class 0			≤ 40	≤ 1½	0.20	0.70-1.35	0.15-0.50	0.030	0.030	0.25	0.25	0.08	Cu 0.35; V 0.06; Cb 0.03;
	A, Class 2			> 40	> 1½	0.20	1.00-1.60	0.15-0.50	0.030	0.030	0.25	0.25	0.08	AI ≥ 0.020
ACTM A 041/A 041M 00-	D. Olasa O			≤ 40	≤ 1½	0.15	0.70-1.35	0.45.0.50	0.000	0.005	0.05	0.00	0.30	Cu 0.35; V 0.06; Cb 0.03;
ASTM A 841/A 841M-03a	B, Class 2			> 40	> 1½	0.15	1.00-1.60	0.15-0.50	0.030	0.025	0.25	0.60	0.30	AI ≥ 0.020
	O Olass O			≤ 40	≤ 1½	0.10	0.70-1.60	0.45.0.50	0.000	0.015	0.05	0.05	0.00	Cu 0.35; V 0.06; Cb 0.06;
	C, Class 2			> 40	> 1½	0.10	1.00-1.60	0.15-0.50	0.030	0.015	0.25	0.25	0.08	Ti 0.006-0.02

4.3A Chemical Composition of $\frac{1}{2}$ Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section Th	ickness				Weight, 9	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	S	Cr	Ni	Мо	Others
EN 10028-2:2003	16Mo3	1.5415				0.12-0.20	0.40-0.90	0.35	0.025	0.010	0.30	0.30	0.25-0.35	N 0.012; Cu 0.30; Al/N>2
ISO 9328-2:1991	16 Mo 3					0.12-0.20	0.40-0.90	0.35	0.035	0.030	0.30		0.25-0.35	Cu 0.30
EN 10028-2:2003	18MnMo4-5	1.5414				0.20	0.90-1.50	0.40	0.015	0.005	0.30	0.30	0.45-0.60	N 0.012; Cu 0.30
				≤ 25	≤ 1	0.18								
ASTM A 204/A 204M-03	Α		K11820	25 < t ≤ 50	1 < t ≤ 2	0.21	0.90	0.15-0.40	0.035	0.035			0.45-0.60	
ASTIVI A 204/A 204IVI-03	A		K11620	50 < t ≤ 100	2 < t ≤ 4	0.23	0.90	0.15-0.40	0.035	0.035			0.45-0.60	
				> 100	> 4	0.25	1							
				≤ 25		0.18								
	SB 450 M			25 < t ≤ 50		0.21	0.90	0.15-0.30	0.035	0.040			0.45-0.60	
	36 430 W			50 < t ≤ 100		0.23	0.90	0.15-0.30	0.033	0.040			0.45-0.60	
JIS G 3103:1987				100 < t ≤ 150		0.25	1							
015 G 3103:1967				≤ 25		0.20								
	SB 480 M			25 < t ≤ 50		0.23	0.90	0.15-0.30	0.035	0.040			0.45-0.60	
	3D 400 W			50 < t ≤ 100		0.25	0.90	0.15-0.30	0.033	0.040			0.45-0.60	
				100 < t ≤ 150		0.27								
				≤ 25	≤ 1	0.20								
ASTM A 204/A 204M-03	В		K12020	25 < t ≤ 50	1 < t ≤ 2	0.23	0.90	0.15-0.40	0.035	0.035			0.45-0.60	
ASTIVI A 204/A 204IVI-03	Ь		K12020	50 < t ≤ 100	$2 < t \le 4$	0.25	0.90	0.15-0.40	0.055	0.033			0.45-0.00	
				> 100	> 4	0.27								
				≤ 25	≤ 1	0.23								
ASTM A 204/A 204M-03	С		K12320	25 < t ≤ 50	1 < t ≤ 2	0.26	0.90	0.15-0.40	0.035	0.035			0.45-0.60	
ASTIVI A 204/A 204IVI-03	C		K12320	50 < t ≤ 100	$2 < t \le 4$	0.28	0.90	0.15-0.40	0.055	0.033			0.45-0.00	
				> 100	> 4	0.28								
				≤ 25	≤ 1	0.20								
ASTM A 302/A 302M-03	Α		K12021	25 < t ≤ 50	$1 < t \le 2$	0.23	0.95-1.30	0.15-0.40	0.035	0.035			0.45-0.60	
				> 50	> 2	0.25								
				≤ 25		0.20								
JIS G 3119:1987	SBV 1 A			25 < t ≤ 50		0.23	0.95-1.30	0.15-0.30	0.035	0.040			0.45-0.60	
				50 < t ≤ 150		0.25								
JIS G 3124:1987	SEV 295			6 ≤ t ≤ 150		0.19	0.80-1.60	0.15-0.60	0.035	0.035			0.10-0.40	Cu 0.35; Nb 0.05; V 0.10

4.3A Chemical Composition of ½Mo Alloy Steels for Pressure Vessel Plates (Continued)

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight,	%, Maximu	m, Unless	Otherwis	e Specified	
Designation	Type, Symbol, or Name		Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
				≤ 25		0.20								
JIS G 3119:1987	SBV 1 B			25 < t ≤ 50		0.23	1.15-1.50	0.15-0.30	0.035	0.040			0.45-0.60	
				50 < t ≤ 150		0.25								
				≤ 25	≤ 1	0.20								
ASTM A 302/A 302M-03	В		K12022	25 < t ≤ 50	1 < t ≤ 2	0.23	1.15-1.50	0.15-0.40	0.035	0.035			0.45-0.60	
				> 50	> 2	0.25								
JIS G 3120:1987	SQV 1 A					0.25	1.15-1.50	0.15-0.30	0.035	0.040			0.45-0.60	
ASTM A 533/A 533M-93 (1999)	Type A, Class 1		K12521			0.25	1.15-1.50	0.15-0.40	0.035	0.035			0.45-0.60	
JIS G 3124:1987	SEV 345			6 ≤ t ≤ 150		0.19	0.80-1.70	0.15-0.60	0.035	0.035			0.15-0.50	Cu 0.35; Nb 0.05; V 0.10
JIS G 3120:1987	SQV 1 B					0.25	1.15-1.50	0.15-0.30	0.035	0.040			0.45-0.60	
ASTM	Type A, Class 2		K12521			0.25	1 15 1 50	0.15-0.40	0.035	0.035			0.45-0.60	
A 533/A 533M-93 (1999)	Type A, Class 3		K12521			0.25	1.15-1.50	0.15-0.40	0.035	0.035			0.45-0.60	

Mechanical Properties of ½Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section Th	nickness	Yield Strei	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
					≤ 16		275		440-590			
					16 < t ≤ 40		270		440-590			
EN 10028-2:2003	16Mo3	1.5415		N, NT	40 < t ≤ 60		260		440-590		22	04 -+ 0000
EN 10026-2:2003	TOIVIOS	1.5415		IN, IN I	60 < t ≤ 100		240		430-560		22	31 J at 20°C
					100 < t ≤ 150		220		420-570			
					150 < t ≤ 250		210		410-570			
					3 < t ≤ 16		280				24	
					16 < t ≤ 40		270		450-600		24	31 J at 20°C
SO 9328-2:1991	16 Mo 3			N, NT	40 < t ≤ 60		260				23	
					60 < t ≤ 100		240		430-580		22	07.1 -+ 0000
					100 < t ≤ 150		220		420-570		19	27 J at 20°C
				NT	t ≤ 60		345		510-650		20	
EN 10028-2:2003	18MnMo4-5	1.5414		NT	60 < t ≤ 150		325		510-650		20	see standard for impact data
				QT	150 < t ≤ 250		310		480-620		20	impaci dala
ACTM A 004/A 004M 00	Δ.		K11000	AR	≤ 40	≤ 1.5	055	07	450 505	05.05	00	
ASTM A 204/A 204M-03	A		K11820	N	> 40	> 1.5	255	37	450-585	65-85	23	
JIS G 3103:1987	SB 450 M			≤ 38: AR > 38: N	6 ≤ t ≤ 150		255		450-590		23	
JIS G 3103:1987	SB 480M			≤ 38: AR > 38: N	6 ≤ t ≤ 150		275		480-620		21	
ASTM A 204/A 204M-03	В		K12020	AR	≤ 40	≤ 1.5	275	40	485-620	70.00	21	
ASTIVI A 204/A 204IVI-03	Б		K12020	N	> 40	> 1.5	2/5	40	465-620	70-90	21	
ASTM A 204/A 204M-03			K12320	AR	≤ 40	≤ 1.5	295	40	515-655	75.05	20	
43 I W A 204/A 204W-03	С		K12320	N	> 40	> 1.5	295	43	515-655	75-95	20	
ASTM A 302/A 302M-03	Α		K12021	AR	≤ 50	≤ 2	310	45	515-655	75-95	19	
43 FIVI A 302/A 302IVI-03	^		K12021	N	> 50	> 2	310	40	313-033	75-95	19	
JIS G 3119:1987	SBV 1 A			AR	≤ 50		315		520-660		19	
JIO G 0118.1807	3DV I A			N	> 50		313		320-000		15	
					≤ 50		420		540-690		15	
JIS G 3124:1987	SEV 295			R, N, NT	50 < t ≤ 100		400		340-090			31 J at 0°C
JIO G 0124.1301	3LV 233			or P	100 < t ≤ 125		390		530-680		19	SI J al U C
					125 < t ≤ 150		380		520-670			

4.3B Mechanical Properties of ½Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Symbol or Name			Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3119:1987	SBV 1 B			AR or N	≤ 50		345		550-690		18	
013 4 31 19.1907	35015			AITOIN	> 50		040		330-030		10	
ASTM A 302/A 302M-03	В		K12022	AR	≤ 50	≤ 2	345	50	550-690	80-100	18	
A3 1 W A 302/A 302 W - 03	D		KIZUZZ	N	> 50	> 2	343	50	550-090	80-100	10	
JIS G 3120:1987	SQV 1 A			QT			345		550-690		18	see standard for impact data
ASTM A 533/A 533M-93 (1999)	Type A, Class 1		K12521	QT	> 6.5	> 0.25	345	50	550-690	80-100	18	
					≤ 50		430		590-740		14	
JIS G 3124:1987	SEV 345			R, N, NT	50 < t ≤ 100		430		390-740			31 J at 0°C
013 G 3124.1967	3EV 345			or P	100 < t ≤ 125		420		580-730		18	31 J at 0°C
					125 < t ≤ 150		410		570-720			
JIS G 3120:1987	SQV 1 B			QT			480		620-790		16	see standard for impact data
ASTM A 532/A 533M 03 (1000)	Type A, Class 2		K12521	QT	> 6.5	> 0.25	485	70	620-795	90-115	16	
ASTM A 533/A 533M-93 (1999)	Type A, Class 3		K12521	QT	6.5 < t ≤ 65	$0.25 < t \le 2\frac{1}{2}$	570	83	690-860	100-125	16	

4.4.1A Chemical Composition of 3/4Cr-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	6, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 387/A 387M-03	Grade 2 Class 1		K12143			0.05-0.21	0.55-0.80	0.15-0.40	0.035	0.035	0.50-0.80		0.45-0.60	
JIS G 4109:1987	SCMV 1 Div 1					0.21	0.55-0.80	0.40	0.030	0.030	0.50-0.80		0.45-0.60	
JIS G 4109.1907	SCMV 1 Div 2					0.21	0.55-0.80	0.40	0.030	0.030	0.50-0.80		0.45-0.60	
ASTM A 387/A 387M-03	Grade 2 Class 2		K12143			0.05-0.21	0.55-0.80	0.15-0.40	0.035	0.035	0.50-0.80		0.45-0.60	

Mechanical Properties of 3/4Cr-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Symbol or Name		Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 387/A 387M-03	Grade 2 Class 1		K12143	A or NT			230	33	380-550	55-80	22	
	SCMV 1 Div 1			A or NT	$6 \le t \le 50$		225		380-550		18	
JIS G 4109:1987	SCIVIV I DIV I			AUINI	50 < t ≤ 200		225		360-330		22	
JIS G 4109:1987	COMV 4 Div 0			NIT	6 ≤ t ≤ 50		045		400.000		18	
	SCMV 1 Div 2			NT	50 < t ≤ 200		315		480-620		22	
ASTM A 387/A 387M-03	Grade 2 Class 2		K12143	A or NT			310	45	485-620	70-90	22	

Chemical Composition of 1Cr-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section 1	Thickness				Weight, %	%, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ASTM A 387/A 387M-03	Grade 12 Class 1		K11757			0.05-0.17	0.40-0.65	0.15-0.40	0.035	0.035	0.80-1.15		0.45-0.60	
JIS G 4109:1987	SCMV 2 Div 1					0.17	0.40-0.65	0.40	0.030	0.030	0.80-1.15		0.45-0.60	
ASTM A 387/A 387M-03	Grade 12, Class 2		K11757			0.05-0.17	0.40-0.65	0.15-0.40	0.035	0.035	0.80-1.15		0.45-0.60	
JIS G 4109:1987	SCMV 2 Div 2					0.17	0.40-0.65	0.40	0.030	0.030	0.80-1.15		0.45-0.60	
EN 10028-2:2003	13CrMo4-5	1.7335				0.08-0.18	0.40-1.00	0.35	0.025	0.010	0.70-1.15		0.40-0.60	Cu 0.30; N 0.012
ISO 9328-2:1991	14 CrMo 4 5					0.08-0.18	0.40-1.00	0.35	0.035	0.030	0.70-1.15		0.40-0.60	Cu 0.30

4.4.2B Mechanical Properties of 1Cr-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Symbol or Name		Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 387/A 387M-03	Grade 12 Class 1		K11757	A or NT			230	33	380-550	55-80	22	
JIS G 4109:1987	SCMV 2 Div. 1			A or NT	$6 \le t \le 50$		225		380-550		19	
015 G 4109.1967	SCIVIV 2 DIV. I			AUINI	50 < t ≤ 200		225		360-550		22	
ASTM A 387/A 387M-03	Grade 12, Class 2		K11757	A or NT			275	40	450-585	65-85	22	
JIS G 4109:1987	SCMV 2 Div. 2			NT	$6 \le t \le 50$		275		450-590		18	
013 G 4109.1907	GOIVIV 2 DIV. 2			INI	50 < t ≤ 200		273		450-590		22	
				NT	≤ 16		300		450-600			31 J at 20°C
				INI	$16 < t \le 60$		290		430-000			31 J at 20 C
EN 10028-2:2003	13CrMo4-5	1.7335		NT	60 < t ≤ 100		270		440-590		19	27 J at 20°C
				NT or QT	100 < t ≤ 150		255		430-580			
				QT	150 < t ≤ 250		245		420-570			
					$3 \le t \le 16$						20	
				'	16 < t ≤ 40		300		450-600		20	31 J at 20°C
ISO 9328-2:1991	14 CrMo 4 5			NT	40 < t ≤ 60						19	
					60 < t ≤ 100		275		440-590		18	27 J at 20°C
					100 < t ≤ 150		255		430-580		10	21 J at 20 C

4.4.3A Chemical Composition of 11/4 Cr-1/2 Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section 1	hickness				Weight, %	6, Maximu	ım, Unless	Otherwise	Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	ø	Cr	Ni	Мо	Others
JIS G 4109:1987	SCMV 3 Div 1					0.17	0.40-0.65	0.50-0.80	0.030	0.030	1.00-1.50		0.45-0.65	
ASTM A 387/A 387M-03	Grade 11 Class 1		K11789			0.05-0.17	0.40-0.65	0.50-0.80	0.035	0.035	1.00-1.50		0.45-0.65	
EN 10028-2:2003	13CrMoSi5-5	1.7336				0.17	0.40-0.65	0.50-0.80	0.015	0.005	1.00-1.50	0.30	0.45-0.65	Cu 0.30; N 0.012
ASTM A 387/A 387M-03	Grade 11 Class 2		K11789			0.05-0.17	0.40-0.65	0.50-0.80	0.035	0.035	1.00-1.50		0.45-0.65	
JIS G 4109:1987	SCMV 3 Div 2					0.17	0.40-0.65	0.50-0.80	0.030	0.030	1.00-1.50		0.45-0.65	

Mechanical Properties of 11/4 Cr-1/2 Mo Alloy Steels for Pressure Vessel Plates 4.4.3B

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 4109:1987	SCMV 3 Div. 1			A or NT	$6 \le t \le 50$		235		410-590		19	
013 G 4109.1907	SCIVIV 3 DIV. 1			AUINI	50 < t ≤ 200		233		410-390		22	
ASTM A 387/A 387M-03	Grade 11 Class 1		K11789	A or NT			240	35	415-585	60-85	22	
				NT	t ≤ 60		310		510-690		20	
				NT	60 < t ≤ 100		300		480-660		20	
EN 10028-2:2003	13CrMoSi5-5	1.7336		QT	t ≤ 60		400		510-690		20	see standard for impact data
				QT	60 < t ≤ 100		390		500-680		20	impaci data
				QT	100 < t ≤ 250		380		490-670		20	
ASTM A 387/A 387M-03	Grade 11 Class 2		K11789	A or NT			310	45	515-690	75-100	22	
JIS G 4109:1987	SCMV 3 Div. 2			NT	6 ≤ t ≤ 50		315		520-690		18	
JIS G 4109.1907	SCIVIV 3 DIV. 2			INI	50 < t ≤ 200		315		520-690		22	

4.4.4A Chemical Composition of 21/4 Cr-1 Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	%, Maximu	ım, Unless (Otherwis	e Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 4109:1987	SCMV 4 Div 1					0.17	0.30-0.60	0.50	0.030	0.030	2.00-2.50		0.90-1.10	
ASTM A 387/A 387M-03	Grade 22, Class 1		K21590			0.05-0.15	0.30-0.60	0.50	0.035	0.035	2.00-2.50		0.90-1.10	
ASTIVI A 367/A 367/VI-U3	Grade 22 L, Class 1		K21590			0.10	0.30-0.60	0.50	0.035	0.035	2.00-2.50		0.90-1.10	
EN 10028-2:2003	10CrMo9-10	1.7380				0.08-0.14	0.40-0.80	0.50	0.020	0.010	2.00-2.50		0.90-1.10	Cu 0.30; N 0.012
ISO 9328-2:1991	13 CrMo 9 10 T1					0.08-0.15	0.40-0.70	0.50	0.035	0.030	2.00-2.50		0.90-1.10	Cu 0.30
ASTM A 387/A 387M-03	Grade 22, Class 2		K21590			0.05-0.15	0.30-0.60	0.50	0.035	0.035	2.00-2.50		0.90-1.10	
JIS G 4109:1987	SCMV 4 Div 2					0.17	0.30-0.60	0.50	0.030	0.030	2.00-2.50		0.90-1.10	
ISO 9328-2:1991	13 CrMo 9 10 T2					0.08-0.15	0.40-0.70	0.50	0.035	0.030	2.00-2.50		0.90-1.10	Cu 0.30
JIS G 4110:1993	SCMQ4E					0.17	0.30-0.60	0.50	0.015	0.015	2.00-2.50		0.90-1.10	V 0.03

Mechanical Properties of 21/4 Cr-1 Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section Th	nickness	Yield Strei	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 4109:1987	SCMV 4 Div 1			A or NT	6 ≤ t ≤ 300		205		410-590		18	
ASTM A 387/A 387M-03	Grade 22, Class 1		K21590	A, or NT			205	30	415-585	60-85	18	
ASTIVI A 307/A 307/VI-US	Grade 22 L, Class 1		K21590	A, OI INT			205	30	415-565	00-00	10	
					≤ 16		310					
				NT	16 < t ≤ 40		300		480-630		18	31 J at 20°C
EN 10028-2:2003	10CrMo9-10	1.7380			40 < t ≤ 60		290					
EN 10020-2.2003	10011009-10	1.7300		NT or QT	60 < t ≤ 100		280		470-620			
				QT	100 < t ≤ 150		260		460-610		17	27 J at 20°C
				QI	150 < t ≤ 250		250		450-600			
					3 ≤ t ≤ 16		275					
					16 < t ≤ 40		265		480-620		18	31 J at 20°C
ISO 9328-2:1991	13 CrMo 9 10 T1			NT	40 < t ≤ 60		205					
130 9320-2.1991	13 011/10 9 10 11			INI	60 < t ≤ 100		260		470-620		17	
					100 < t ≤ 150		250		460-610		16	27 J at 20°C
					150 < t ≤ 300		240		450-600		16	
ASTM A 387/A 387M-03	Grade 22, Class 2		K21590	A or NT			310	45	515-690	75-100	18	
JIS G 4109:1987	SCMV 4 Div 2			NT	6 ≤ t ≤ 300		315		520-690		18	
					3 ≤ t ≤ 16							
ISO 9328-2:1991	13 CrMo 9 10 T2			NT	16 < t ≤ 40		310		520-670		18	31 J at 20°C
130 3320-2.1331	13 01100 9 10 12			INI	40 < t ≤ 60		310		320-070			
					60 < t ≤ 100						17	27 J at 20°C
JIS G 4110:1993	SCMQ4E			NT, QT			380		580-760		18	54 J at -18°C

4.4.5A Chemical Composition of 3Cr-1Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, 9	%, Maximu	ım, Unless (Otherwis	e Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 4109:1987	SCMV 5 Div 1					0.17	0.30-0.60	0.50	0.030	0.030	2.75-3.25		0.90-1.10	
	Grade 21, Class 1					0.05-0.15								
ASTM A 387/A 387M-03	Grade 21 L, Class 1		K31545			0.10	0.30-0.60	0.50	0.035	0.035	2.75-3.25		0.90-1.10	
	Grade 21, Class 2					0.05-0.05								
JIS G 4109:1987	SCMV 5 Div 2					0.17	0.30-0.60	0.50	0.030	0.030	2.75-3.25		0.90-1.10	

4.4.5B Mechanical Properties of 3Cr-1Mo Alloy Steels for Pressure Vessel Plates

Standard Designation	Grade, Class, Type,	Steel	UNS Number	Heat Treatment	Section T	hickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Other
	Symbol or Name				t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	
JIS G 4109:1987	SCMV 5 Div 1			A or NT	6 ≤ t ≤ 300		205		410-590		18	
	Grade 21, Class 1			A NIT			205	00	415-585	CO 05	18	
ASTM A 387/A 387M-03	Grade 21 L, Class 1		K31545	A or NT			205	30	415-565	60-85	10	
	Grade 21, Class 2			A or NT			310	45	515-690	75-100	18	
JIS G 4109:1987	SCMV 5 Div 2			NT	6 ≤ t ≤ 300		315		520-690		18	

4.4.6A Chemical Composition of 5Cr-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section T	hickness				Weight, %	%, Maximu	ım, Unless (Otherwise	e Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	s	Cr	Ni	Мо	Others
JIS G 4109:1987	SCMV 6 Div 1					0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
ASTM A 387/A 387M-03	Grade 5, Class 1		K41545 S50100 S50200			0.15	0.30-0.60	0.50	0.035	0.030	4.00-6.00		0.45-0.65	
EN 10028-2:2003	X12CrMo5	1.7362				0.10-0.15	0.30-0.60	0.50	0.020	0.005	4.00-6.00	0.30	0.45-0.65	Cu 0.30; N 0.012;
ASTM A 387/A 387M-03	Grade 5, Class 2		K41545 S50100 S50200			0.15	0.30-0.60	0.50	0.035	0.030	4.00-6.00		0.45-0.65	
JIS G 4109:1987	SCMV 6 Div 2					0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	

4.4.6B Mechanical Properties of 5Cr-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name				t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 4109:1987	SCMV 6 Div 1			A or NT	6 ≤ t ≤ 300		205		410-590		18	
ASTM A 387/A 387M-03	Grade 5, Class 1		K41545 S50100 S50200	A or NT			205	30	415-585	60-85	18	
				NT	t ≤ 60		320		510-690		20	
EN 10028-2:2003	X12CrMo5	1.7362		NT	60 < t ≤ 150		300		480-690		20	see standard for impact data
				QT	150 < t ≤ 250		300		450-690		20	impaci data
ASTM A 387/A 387M-03	Grade 5, Class 2		K41545 S50100 S50200	A or NT			310	45	515-690	75-100	18	
JIS G 4109:1987	SCMV 6 Div 2			NT	6 ≤ t ≤ 300		315		520-690		18	

4.4.7A Chemical Composition of 9Cr-1Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS Number	Section Thickness		Weight, %, Maximum, Unless Otherwise Specified										
Designation	Type, Symbol, or Name	Number		t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others		
ASTM A 387/A 387M-03	Grade 91 Class 2		K90901			0.08-0.12	0.30-0.60	0.20-0.50	0.020	0.010	8.00-9.50	0.40	0.85-1.05	N 0.030-0.070; Cb 0.06-0.10; V 0.18-0.25; B 0.0003-0.006; Al 0.04		
EN 10028-2:2003	X10CrMoVNb9-1	1.4903				0.08-0.12	0.30-0.60	0.50	0.020	0.005	8.00-9.50	0.30	0.85-1.05	N 0.030-0.070; Cu 0.30; Nb 0.6-0.10; V 0.18-0.25		
ASTM A 387/A 387M-03	Grade 911 Class 2					0.09-0.13	0.30-0.60	0.10-0.50	0.020	0.010	8.50-10.50	0.40	0.90-1.10	Cb 0.06-0.10; V 0.18-0.25; Al 0.04; N 0.04-0.09; W 0.90-1.10		

4.4.7B Mechanical Properties of 9Cr-1Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	IING	JNS Heat	Tensile Str	ength, min	n Elongation,					
Designation	Symbol or Name				t, mm	t, in.		ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 387/A 387M-03	Grade 91 Class 2		K90901	NT			415	60	585	760	18	
				NT	t ≤ 60		445		580-760			
EN 10028-2:2003	X10CrMoVNb9-1	1.4903		NT	60 < t ≤ 150		435		550-730		18	see standard for impact data
				QT	150 < t ≤ 250		435		520-700			impact data
ASTM A 387/A 387M-03	Grade 911 Class 2			NT			440	64	620	840	18	

4.5.1A Chemical Composition of ½Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section Th	nickness				Weight, %	6, Maximu	m, Unless	Otherwise	Specified	
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10028-4:2003	11MnNi5-3	1.6212				0.14	0.70-1.50	0.50	0.025	0.015		0.30-0.80		V 0.05; Nb 0.05; Al 0.020
EN 10026-4.2003	13MnNi6-3	1.6217				0.16	0.85-1.70	0.50	0.025	0.015		0.30-0.85		V 0.05; Nb 0.05; Al 0.020
ISO 9328-3:1991	11 MnNi 5 3			$3 \le t \le 50$		0.14	0.70-1.50	0.50	0.030	0.025		0.30-0.80		V 0.05; Nb 0.05; Al 0.020
13 MnNi 6 3			$3 \le t \le 50$		0.16	0.85-1.65	0.50	0.030	0.025		0.30-0.85		V 0.05; Nb 0.05; Al 0.020	

4.5.1B Mechanical Properties of ½Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number			t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 30		285					
	11MnNi5-3	1.6212		NT 30 < t ≤ 50 275 420 50 < t ≤ 80 265	420-530	24	see standard for impact data					
EN 10028-4:2003					$50 < t \leq 80$		265					impaor data
EN 10028-4.2003	13MnNi6-3			NT $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$								
		1.6217			30 < t ≤ 50		345		490-610		22	see standard for impact data
					50 < t ≤ 80		335					iiiipaci uata
	11 MnNi 5 3			NT	3 < t ≤ 30		285		420-530		24	see standard for
O 0000 0:1001	I I WITHNI 5 3			INI	30 < t ≤ 50		275		420-530		24	impact data
ISO 9328-3:1991	10 MpNi C 0			NT	3 < t ≤ 30		355		490-610		22	see standard for
	13 MnNi 6 3			IN I	$30 < t \le 50$		345		490-610		22	impact data

4.5.2A Chemical Composition of 1½Ni Alloy Steels for Pressure Vessel Plates

i Standard I	Type Symbol or I	Steel	UNS	Section Th	nickness				Weight, %	%, Maximu	m, Unless	Otherwise	Specified	
Designation		Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10028-4:2003	15NiMn6	1.6228				0.18	0.80-1.50	0.35	0.025	0.015		1.30-1.70		V 0.05
ISO 9328-3:1991	15 NiMn 6			$3 \le t \le 50$		0.18	0.80-1.50	0.35	0.025	0.020		1.30-1.70		V 0.05

4.5.2B Mechanical Properties of 1½Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type, Symbol or Name	Steel	UNS	Heat Treatment	Section T	hickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,		
Designation			Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other	
					≤ 30		355						
EN 10028-4:2003	15NiMn6	1.6228		N or NT or QT $30 < t \le 50$ 345 $50 < t \le 80$ 335	345		490-640	22	see standard for impact data				
					50 < t ≤ 80		335		-			impaot data	
ISO 0200 2:1001	15 NiMo 6			N or NT or	3 < t ≤ 30		355		400.640		00	see standard for	
SO 9328-3:1991 15 N	15 NiMn 6			QT	$30 < t \le 50$		345		490-640		22	impact data	

4.5.3A Chemical Composition of 2¼Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section Th	ickness				Weight, 9	%, Maximu	ım, Unles	s Otherwis	e Specif	ied
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 3127:2000	SL2N255			6 ≤ t ≤ 50		0.17	0.70	0.30	0.025	0.025		2.10-2.50		
				≤ 50	≤2	0.17	0.70	0.15-0.40	0.035	0.035		2.10-2.50		
	Α		K21703	50 < t ≤ 100	$2 < t \le 4$	0.20	0.80	0.15-0.40	0.035	0.035		2.10-2.50		
ASTM A 203/A 203M-97 (2003)				> 100	> 4	0.23	0.80	0.15-0.40	0.035	0.035		2.10-2.50		
ASTIVI A 203/A 203IVI-97 (2003)				≤ 50	≤2	0.21	0.70	0.15-0.40	0.035	0.035		2.10-2.50		
	В		K22103	50 < t ≤ 100	2 < t ≤ 4	0.24	0.80	0.15-0.40	0.035	0.035		2.10-2.50		
				> 100	> 4	0.25	0.80	0.15-0.40	0.035	0.035		2.10-2.50		

4.5.3B Mechanical Properties of 2½Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name		Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					$6 \le t \le 16$						24	
JIS G 3127:1990	SL2N255			N	> 16		255		450-590		29	see standard for impact data
O d o127.1000					> 20						24	impaot data
	Α		K21703	N	≤ 50	≤ 2	255	37	450-585	65-85	23	
A CTM A 202/A 202M 07 (2022)			K21703	IN	> 50	> 2	255	3/	450-565	00-00	23	
STM A 203/A 203M-97 (2003)	В		K22103	N	≤ 50	≤ 2	275	40	485-620	70.00	21	
	D		N22103	IN	> 50	> 2	2/5	40	400-020	70-90	۷۱	

4.5.4A Chemical Composition of 3½Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section Th	ickness				Weight, 9	⁄₀, Maximu	ım, Unles	s Otherwis	se Specifi	ed
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	Ø	Cr	Ni	Мо	Others
JIS G 3127:2000	SL3N255			6 ≤ t ≤ 50		0.15	0.70	0.30	0.025	0.025		3.25-3.75		
ASTM A 203/A 203M-97 (2003)	D		K31718	≤ 50	≤2	0.17	0.70	0.15-0.40	0.035	0.035		3.25-3.75		
ASTIVI A 203/A 203IVI-97 (2003)			K31710	$50 < t \le 100$	$2 < t \leq 4$	0.20	0.80	0.15-0.40	0.035	0.035		3.25-3.75		
ISO 9328-3:1991	12 Ni 14 G1			$3 \le t \le 50$		0.15	0.30-0.80	0.35	0.025	0.020		3.25-3.75		V 0.05
130 9326-3.1991	12 Ni 14 G2			$3 \le t \le 50$		0.15	0.30-0.80	0.35	0.025	0.020		3.25-3.75		V 0.05
JIS G 3127:2000	SL3N275			6 ≤ t ≤ 50		0.17	0.70	0.30	0.025	0.025		3.25-3.75		
ASTM A 203/A 203M-97 (2003)	Е		K32018	≤ 50	≤2	0.20	0.70	0.15-0.40	0.035	0.035		3.25-3.75		
ASTIVI A 203/A 203IVI-97 (2003)			K32010	50 < t ≤ 100	$2 < t \le 4$	0.23	0.80	0.15-0.40	0.035	0.035		3.25-3.75		
EN 10028-4:2003	12Ni14	1.5637				0.15	0.30-0.80	0.35	0.020	0.010		3.25-3.75		V 0.05
JIS G 3127:2000	SL3N440			6 ≤ t ≤ 50		0.15	0.70	0.30	0.025	0.025		3.25-3.75		
ASTM A 203/A 203M-97 (2003)	F			≤ 50	≤2	0.20	0.70	0.15-0.40	0.035	0.035		3.25-3.75		
ASTIVI A 203/A 203/VI-97 (2003)	Г			$50 < t \le 100$	$2 < t \leq 4$	0.23	0.80	0.15-0.40	0.035	0.035		3.25-3.75		

Mechanical Properties of 3½Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section 1	hickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					6 ≤ t ≤ 16						24	
JIS G 3127:2000	SL3N255			N	> 16		255		450-590		29	see standard for impact data
					> 20						24	impact data
ASTM A 202/A 202M 07 (2002)	D		K31718	N	≤ 50	≤ 2	255	37	450-585	65-85	23	
ASTM A 203/A 203M-97 (2003)	U		K31/16	IN I	> 50	> 2	255	3/	450-565	65-85	23	
	12 Ni 14 G1			N or NT or QT	3 < t ≤ 30		285		450-600		23	see standard for
ISO 9328-3:1991	12 NI 14 GT			N OF INT OF QT	30 < t ≤ 50		275		450-600		23	impact data
150 9326-3.1991	12 Ni 14 G2			N or NT or QT	$3 < t \le 30$		355		470-620		22	see standard for
	12 NI 14 G2			N OF INT OF QT	30 < t ≤ 50		345		470-620		22	impact data
					6 ≤ t ≤ 16						22	
JIS G 3127:2000	SL3N275			N	> 16		275		480-620		26	see standard for impact data
					> 20						22	impact data
ASTM A 202/A 202M 07 (2002)	E		K32018	N	≤ 50	≤ 2	275	40	485-620	70-90	21	
ASTM A 203/A 203M-97 (2003)	-		N32016	IN I	> 50	> 2	2/5	40	465-620	70-90	21	
					≤ 30		355					
EN 10028-4:2003	12Ni14	1.5637		N or NT or QT	30 < t ≤ 50		345		490-640		22	see standard for impact data
					50 < t ≤ 80		335					impact data
					6 ≤ t ≤ 16						21	
JIS G 3127:2000	SL3N440			QT	> 16		440		540-690		25	see standard for impact data
					> 20		7				21	impact data
ACTM A 000/A 000M 07 (0000)	Г			ОТ	≤ 50	≤ 2	55	380	550-690	80-100	20	
ASTM A 203/A 203M-97 (2003)	F			QT	> 50	> 2	50	345	515-655	75-95	20	

Chemical Composition of 5Ni Alloy Steels for Pressure Vessel Plates

i Standard	Grade, Class,	STEEL	UNS	Section Th	ickness				Weight, 9	%, Maximu	ım, Unles	s Otherwis	se Specifi	ed
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	C	Mn	Si	P	s	Cr	Ni	Мо	Others
EN 10028-4:2003	X12Ni5	1.5680				0.15	0.30-0.80	0.35	0.020	0.010		4.75-5.25		V 0.05
JIS G 3127:2000	SL5N590			$6 \le t \le 50$		0.13	1.50	0.30	0.025	0.025		4.75-6.00		

Mechanical Properties of 5Ni Alloy Steels for Pressure Vessel Plates 4.5.5B

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number			t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10028-4:2003	X12Ni5	1.5680		N or NT or QT	≤ 30		390		530-710		20	see standard for
LN 10028-4.2003	ATZINIS	1.5000		NOINT OF Q	$30 < t \leq 50$		380		330-710		20	impact data
					$6 \le t \le 16$						21	
JIS G 3127:2000	G 3127:2000 SL5N590			QT	> 16		590		690-830		25	see standard for impact data
					> 20						21	impaot data

4.5.6A Chemical Composition of 9Ni Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,	STEEL	UNS	Section Th	ickness				Weight, 9	%, Maximu	ım, Unl	ess Otherwis	se Specif	ied
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ISO 9328-3:1991	X 8 Ni 9			$3 \le t \le 50$		0.10	0.30-0.80	0.35	0.025	0.020		8.5-10.0	0.10	V 0.05
EN 10028-4:2003	X8Ni9	1.5662				0.10	0.30-0.80	0.35	0.020	0.010		8.50-10.00	0.10	V 0.05
EN 10028-4.2003	X7Ni9	1.5663				0.10	0.30-0.80	0.35	0.015	0.005		8.50-10.00	0.10	V 0.01
JIS G 3127:2000	SL9N520			$6 \le t \le 50$		0.12	0.90	0.30	0.025	0.025		8.50-9.50		
ASTM A 353/A 353M-93 (1999)			K81340			0.13	0.90	0.15-0.40	0.035	0.035		8.50-9.50		
ACTM A FEQ/A FEQM OF (0000)	Type I		K81340			0.13	0.90	0.15-0.40	0.035	0.035		8.50-9.50		
ASTM A 553/A 553M-95 (2000)	Type II		K71340			0.13	0.90	0.15-0.40	0.035	0.035		7.50-8.50		
JIS G 3127:2000	SL9N590			6 ≤ t ≤ 50		0.12	0.90	0.30	0.025	0.025		8.50-9.50		
ASTM A 844/A 844M-93 (1999)			K81340			0.13	0.90	0.15-0.40	0.020	0.020		8.50-9.50		

Mechanical Properties of 9Ni Alloy Steels for Pressure Vessel Plates

Standard	Crade Class Tyre	Steel	UNS	Heat	Section T	hickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Grade, Class, Type, Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ISO 9328-3:1991	X 8 Ni 9			NNT or QT	$3 \le t \le 30$		490		640-840		18	see standard for
130 9320-3.1991	X O INI 9			ININT OF QT	$30 < t \le 50$		480		040-040		10	impact data
				NT640:	≤ 30		490		640-840		18	see standard for
				N or NT	$30 < t \le 50$		480		040-040		10	impact data
	X8Ni9	1.5662		QT640: QT	≤ 30		585		680-820			
EN 10028-4:2003	VOINIA	1.3002		Q1040. Q1	$30 < t \le 50$		575		000-020		18	see standard for
LN 10028-4.2003				QT680: QT	≤ 30		585		680-820		10	impact data
				Q1000. Q1	$30 < t \le 50$		575		000-020			
	X7Ni9	1.5663		QT	≤ 30		585		680-820		18	see standard for
	ATINIS	1.5005		Q1	$30 < t \le 50$		575		000-020		10	impact data
					6 ≤ t ≤ 16						21	
JIS G 3127:2000	SL9N520			NNT	> 16		520		690-830		25	see standard for impact data
					> 20						21	impaot data
ASTM A 353/A 353M-93 (1999)			K81340	NNT			515	75	690-825	100-120	20.0	see standard for supplementary impact testing
AOTA A 550/A 550M 05 (0000)	Type I		K81340	O.T.			505		200 005		00.0	see standard for
ASTM A 553/A 553M-95 (2000)	Type II		K71340	QT			585	85	690-825	100-120	20.0	supplementary impact testing
					$6 \le t \le 16$						21	
JIS G 3127:2000	SL9N590			QT	> 16		590		690-830		25	see standard for impact data
					> 20						21	impaot data
ASTM A 844/A 844M-93 (1999)			K81340	Direct QT	≤ 50	≤2	585	85	690-825	100-120	20.0	see standard for supplementary impact testing

4.6.1A Chemical Composition of ½Ni-½Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,		UNS	Section Th	ickness				Weight, 9	%, Maximu	ım, Unles	s Otherwi	se Specifi	ed
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 533/A 533M-93 (1999)	Type B Class 1		K12539			0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.40-0.70	0.45-0.60	
JIS G 3120:1987	SQV 2 A					0.25	1.15-1.50	0.15-0.30	0.035	0.040		0.40-0.70	0.45-0.60	
				≤ 25		0.20								
JIS G 3119:1987	SBV 2			25 < t ≤ 50		0.23	1.15-1.50	0.15-0.30	0.035	0.040		0.40-0.70	0.45-0.60	
				50 < t ≤ 150		0.25								
				≤ 25	≤ 1	0.20								
ASTM A 302/A 302M-03	С		K12039	25 < t ≤ 50	1 < t ≤ 2	0.23	1.15-1.50	0.15-0.40	0.035	0.035		0.40-0.70	0.45-0.60	
				> 50	> 2	0.25								
EN 10028-2:2003	20MnMoNi4-5	1.6311				0.15-0.23	1.00-1.50	0.40	0.020	0.010	0.20	0.40-0.80	0.45-0.60	N 0.012; Cu 0.20; V 0.02
ASTM A 533/A 533M-93 (1999)	Type B Class 2		K12539			0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.40-0.70	0.45-0.60	
JIS G 3120:1987	SQV 2 B					0.25	1.15-1.50	0.15-0.30	0.035	0.040		0.40-0.70	0.45-0.60	
ASTM A 533/A 533M-93 (1999)	Type B Class 3		K12539			0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.40-0.70	0.45-0.60	

4.6.1B Mechanical Properties of ½Ni-½Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strei	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 533/A 533M-93 (1999)	Type B Class 1		K12539	QT	> 6.5	> 0.25	345	50	550-690	80-100	18	
JIS G 3120:1987	SQV 2 A			QT			345		550-690		18	see standard for impact data
JIS G 3119:1987	SBV 2			AR	6 ≤ t ≤ 50		345		550-690		17	
JIS G 3119.1967	3BV 2			N	50 < t ≤ 150		345		550-690		20	
ASTM A 302/A 302M-03	С		K12039	AR	$6.5 \le t \le 50$	$\frac{1}{4} \le t \le 2$	345	50	550-690	80-100	20	
ASTIVI A 302/A 302IVI-03	C		K12039	N	> 50	> 2	343	50	550-690	80-100	20	
				QT	t ≤ 40		470		590-750		18	
				QT	40 < t ≤ 60		460		590-730		18	
EN 10028-2:2003	20MnMoNi4-5	1.6311		QT	60 < t ≤ 100		450		570-710		18	see standard for impact data
				QT	100 < t ≤ 150		440		570-710		18	impaot data
				QT	150 < t ≤ 250		400		560-700		18	
ASTM A 533/A 533M-93 (1999)	Type B Class 2		K12539	QT	> 6.5	> 0.25	485	70	620-795	90-115	16	
JIS G 3120:1987	SQV 2 B			QT			480		620-790		16	see standard for impact data
ASTM A 533/A 533M-93 (1999)	Type B Class 3		K12539	QT	$6.5 \le t \le 65$	$\frac{1}{4} \le t \le 2\frac{1}{2}$	570	83	690-860	100-125	16	

4.6.2A Chemical Composition of 3/4Ni-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class,		UNS	Section Th	ickness				Weight, 9	%, Maximu	ım, Unles	s Otherwi	se Specifi	ed
Designation	Type, Symbol, or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 533/A 533M-93 (1999)	Type C, Class 1		K12554			0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.70-1.00	0.45-0.60	
				≤ 25		0.20	1.15-1.50	0.15-0.30	0.035	0.040		0.70-1.00	0.45-0.60	
JIS G 3119:1987	SBV 3			25 < t ≤ 50		0.23	1.15-1.50	0.15-0.30	0.035	0.040		0.70-1.00	0.45-0.60	
				50 < t ≤ 150		0.25	1.15-1.50	0.15-0.30	0.035	0.040		0.70-1.00	0.45-0.60	
				≤ 25	≤ 1	0.20	1.15-1.50	0.15-0.40	0.035	0.035		0.70-1.00	0.45-0.60	
ASTM A 302/A 302M-03	D		K12054	25 < t ≤ 50	1 < t ≤ 2	0.23	1.15-1.50	0.15-0.40	0.035	0.035		0.70-1.00	0.45-0.60	
				> 50	> 2	0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.70-1.00	0.45-0.60	
JIS G 3120:1987	SQV 3 A					0.25	1.15-1.50	0.15-0.30	0.035	0.040		0.70-1.00	0.45-0.60	
EN 10028-2:2003	15NiCuMoNb 5-6-4	1.6368				0.17	0.80-1.20	0.25-0.50	0.025	0.010	0.30	1.00-1.30	0.25-0.50	N 0.020; Cu 0.50-0.80; Nb 0.015-0.045
ASTM A 533/A 533M-93 (1999)	Type C, Class 2		K12554			0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.70-1.00	0.45-0.60	
JIS G 3120:1987	SQV 3 B					0.25	1.15-1.50	0.15-0.30	0.035	0.040		0.70-1.00	0.45-0.60	
ASTM A 533/A 533M-93 (1999)	Type C, Class 3		K12554			0.25	1.15-1.50	0.15-0.40	0.035	0.035		0.70-1.00	0.45-0.60	

Mechanical Properties of 3/4Ni-1/2Mo Alloy Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 533/A 533M-93 (1999)	Type C, Class 1		K12554	QT	> 6.5	> 0.25	345	50	550-690	80-100	18	
JIS G 3119:1987	SBV 3			AR	$6 \le t \le 50$		345		550-690		17	
JIS G 3119.1967	3BV 3			N	50 < t ≤ 150		345		550-690		20	
ASTM A 302/A 302M-03	D		K12054	AR	6.5 ≤ t ≤ 50	½ ≤ t ≤ 2	345	50	550-690	80-100	20	
ASTIVI A 502/A 502IVI-05	Ь		K12054	N	> 50	> 2	345	50	550-690	80-100	20	
JIS G 3120:1987	SQV 3 A			QT			345		550-690		18	see standard for impact data
				NT	t ≤ 40		460		610-780		16	·
				NT	40 < t ≤ 60		440		610-780		16	
EN 10028-2:2003	15NiCuMoNb5-6-4	1.6368		NT	60 < t ≤ 100		430		600-760		16	see standard for impact data
				NT or QT	100 < t ≤ 150		420		590-740		16	impaot data
				QT	150 < t ≤ 250		410		580-740		16	
ASTM A 533/A 533M-93 (1999)	Type C, Class 2		K12554	QT	> 6.5	> 0.25	485	70	620-795	90-115	16	
JIS G 3120:1987	SQV 3 B			QT			480		620-790		16	see standard for impact data
ASTM A 533/A 533M-93 (1999)	Type C, Class 3		K12554	QT	6.5 ≤ t ≤ 65	1⁄4 ≤ t ≤ 21⁄2	570	83	690-860	100-125	16	

4.7 Ferritic and Martensitic Stainless Steels for Pressure Vessel Plates

4.7A Chemical Composition of Ferritic and Martensitic Stainless Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Section 1	hickness				Weight, %	, Maximu	m, Unless O	therwise S	pecified	
Designation	Type, Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	405		S40500			0.08	1.00	1.00	0.040	0.030	11.5-14.5	0.60		Al 0.10-0.30
EN 10028-7:2000	X2CrNi12	1.4003				0.030	1.50	1.00	0.040	0.015	10.50-12.50	0.30-1.00		N 0.030
ASTM A 240/A 240M-03c			S40975			0.030	1.00	1.00	0.040	0.030	10.5-11.7	0.50-1.00		N 0.030; Ti 6 x (C+N) to 0.75
EN 10028-7:2000	X6CrNiTi12	1.4516				0.08	1.50	0.70	0.040	0.015	10.50-12.50	0.50-1.50		Ti 0.05-0.35
ASTM A 240/A 240M-03c			S41500			0.05	0.50-1.00	0.60	0.030	0.030	11.5-14.0	3.5-5.5	0.50-1.00	
EN 10028-7:2000	X3CrNiMo13-4	1.4313				0.05	1.50	0.70	0.040	0.015	12.00-14.00	3.50-4.50	0.30-0.70	N 0.020
ASTM A 240/A 240M-03c	439		S43035			0.030	1.00	1.00	0.040	0.030	17.0-19.0	0.50		Ti [0.20+4(C+N)] to 1.10 N 0.030; Al 0.15
EN 10028-7:2000	X3CrTi17	1.4510				0.05	1.00	1.00	0.040	0.015	16.00-18.00			Ti [4 x (C+N)+0.15] to 0.80
ASTM A 240/A 240M-03c			S43932			0.030	1.00	1.00	0.040	0.030	17.0-19.0	0.50		(Ti+Cb) [0.20+4(C+N)] to 0.75 N 0.030; Al 0.15
A31W A 240/A 240W-03C			S43940			0.030	1.00	1.00	0.040	0.015	17.5-18.5			Ti 0.10-0.60; Cb [0.30+(3 x C)] min
EN 10028-7:2000	X2CrTiNb18	1.4509				0.030	1.00	1.00	0.040	0.015	17.50-18.50			Ti 0.10-0.60; Nb [3 x C+0.30] to 1.00
ASTM A 240/A 240M-03c	444		S44400			0.025	1.00	1.00	0.040	0.030	17.5-19.5	1.00	1.75-2.50	(Ti+Cb) [0.20+4(C+N)] to 0.80; N 0.035
EN 10028-7:2000	X2CrMoTi18-2	1.4521				0.025	1.00	1.00	0.040	0.015	17.00-20.00		1.80-2.50	Ti [4 x (C+N)+0.15] to 0.80; N 0.030

4.7B Mechanical Properties of Ferritic and Martensitic Stainless Steels for Pressure Vessel Plates

Standard	Grade, Class,	Steel	UNS	Heat	Section T	hickness	Yield Streng	gth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 240/A 240M-03c	405		S40500				170	25	415	60	20.0	
				CR St, A	≤ 6		280 L; 320 T				20	
EN 10028-7:2000	X2CrNi12	1.4003		HR St, A	≤ 12		260 L, 320 T		450-650		20	see standard for impact data
				HR PI, A	≤ 25		250 L; 280 T				18	impaor data
ASTM A 240/A 240M-03c			S40975				275	40	415	60	20.0	
				CR St, A	≤ 6		280 L; 320 T				23	
EN 10028-7:2000	X6CrNiTi12	1.4516		HR St, A	≤ 12		200 L, 320 T		450-650		23	see standard for impact data
				HR PI, A	≤ 25		250 L; 280 T				20	impaor data
ASTM A 240/A 240M-03c			S41500				620	90	795	115	15.0	
EN 10028-7:2000	X3CrNiMo13-4	1.4313		HR PI, QT	≤ 75		650		780-980		14	see standard for impact data
ASTM A 240/A 240M-03c	439		S43035				205	30	415	60	22.0	
EN 10028-7:2000	X3CrTi17	1.4510		CR St, A	≤ 3		230 L; 240 T		420-600		23	see standard for impact data
ASTM A 240/A 240M-03c			S43932				205	30	415	60	22.0	
A3 1 W A 240/A 240W-03C			S43940				250	36	430	62	18	
EN 10028-7:2000	X2CrTiNb18	1.4509		CR St, A	≤ 2.5		230 L; 250 T		430-630		18	see standard for impact data
ASTM A 240/A 240M-03c	444		S44400				275	40	415	60	20.0	
EN 10028-7:2000	X2CrMoTi18-2	1.4521		CR St, A	≤ 2.5		300 L; 320 T		420-640		20	see standard for impact data

4.8A Chemical Composition of Austenitic Stainless Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Section 7	Thickness				Weigh	t, %, Max	imum, Unles	ss Otherwise	Specified	
Designation	Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	301LN		S30153			0.03	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.07-0.20
EN 10028-7:2000	X2CrNiN18-7	1.4318				0.030	2.00	1.00	0.045	0.015	16.50-18.50	6.00-8.00		N 0.10-0.20
ASTM A 240/A 240M-03c	304		S30400			0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10
EN 10028-7:2000	X5CrNi18-10	1.4301				0.07	2.00	1.00	0.045	0.015	17.00-19.50	8.00-10.50		N 0.11
ISO 9328-5:1991	X 5 CrNi 18 9					0.07	2.00	1.00	0.045	0.030	17.00-19.00	8.00-11.00		
ASTM A 240/A 240M-03c	304H		S30409			0.04-0.10	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		
EN 10028-7:2000	X6CrNi18-10	1.4948				0.04-0.08	2.00	1.00	0.035	0.015	17.00-19.00	8.00-11.00		N 0.11
ISO 9328-5:1991	X 7 CrNi 18 9					0.04-0.10	2.00	1.00	0.045	0.030	17.00-19.00	8.00-11.00		
ASTM A 240/A 240M-03c	304L		S30403			0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10
EN 10028-7:2000	X2CrNiN18-9	1.4307				0.030	2.00	1.00	0.045	0.015	17.50-19.50	8.00-10.00		N 0.11
EN 10026-7:2000	X2CrNi19-11	1.4306				0.030	2.00	1.00	0.045	0.015	18.00-20.00	10.00-12.00		N 0.11
ISO 9328-5:1991	X 2 CrNi 18 10					0.030	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		
ASTM A 240/A 240M-03c	304N		S30451			0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
EN 10028-7:2000	X5CrNiN19-9	1.4315				0.06	2.00	1.00	0.045	0.015	18.00-20.00	8.00-11.00		N 0.12-0.22
ASTM A 240/A 240M-03c	304LN		S30453			0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10-0.16
EN 10028-7:2000	X2CrNiN18-10	1.4311				0.030	2.00	1.00	0.045	0.015	17.00-19.50	8.50-11.50		N 0.12-0.22
ISO 9328-5:1991	X 2 CrNiN 18 10					0.030	2.00	1.00	0.045	0.030	17.00-19.00	8.50-11.50		N 0.12-0.22
ASTM A 240/A 240M-03c	309H		S30909			0.04-0.10	2.00	0.75	0.045	0.030	22.0-24.0	12.0-15.0		
EN 10028-7:2000	X6CrNi23-13	1.4950				0.04-0.08	2.00	0.70	0.035	0.015	22.00-24.00	12.00-15.00		N 0.11
ASTM A 240/A 240M-03c	310H		S31009			0.04-0.10	2.00	0.75	0.045	0.030	24.0-26.0	19.0-22.0		
EN 10028-7:2000	X6CrNi25-20	1.4951				0.04-0.08	2.00	0.70	0.035	0.015	24.00-26.00	19.00-22.00		N 0.11
ASTM A 240/A 240M-03c	316		S31600			0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
EN 10028-7:2000	X5CrNiMo17-12-2	1.4401				0.07	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10020-7.2000	X3CrNiMo17-13-3	1.4436				0.05	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
ISO 9328-5:1991	X 5 CrNiMo 17 12					0.07	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	
190 9358-2:1981	X 5 CrNiMo 17 13					0.07	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.50-3.00	

4.8A Chemical Composition of Austenitic Stainless Steels for Pressure Vessel Plates (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Section 7	Thickness				Weight	t, %, Max	rimum, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	316L		S31603			0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
	X2CrNiMo17-12-2	1.4404				0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10028-7:2000	X2CrNiMo17-12-3	1.4432				0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
	X2CrNiMo18-14-3	1.4435				0.030	2.00	1.00	0.045	0.015	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
ISO 9328-5:1991	X 2 CrNiMo 17 12					0.030	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.00-2.50	
130 9320-5.1991	X 2 CrNiMo 17 13					0.030	2.00	1.00	0.045	0.030	16.50-18.50	11.50-14.50	2.50-3.00	
ASTM A 240/A 240M-03c	316H		S31609			0.04-0.10	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ISO 9328-5:1991	X 7 CrNiMo 17 12					0.04-0.10	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	
ASTM A 240/A 240M-03c	316Ti		S31635			0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	Ti 5 x (C+N) min, 0.70 max; N 0.10;
EN 10028-7:2000	X6CrNiMoTi17-12-2	1.4571				0.08	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.50	2.00-2.50	Ti 5 x C - 0.70
ISO 9328-5:1991	X 6 CrNiMoTi 17 12					0.08	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.00-2.50	Ti 5 X C to 0.80
ASTM A 240/A 240M-03c	316Cb		S31640			0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	Cb 10 x C to 1.10; N 0.10
EN 10028-7:2000	X6CrNiMoNb17-12-2	1.4580				0.08	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.50	2.00-2.50	Nb 10 x C to 1.00
ISO 9328-5:1991	X 6 CrNiMoNb 17 12					0.08	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.00-2.50	Nb 10 x C to 1.00
ASTM A 240/A 240M-03c	316LN		S31653			0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10-0.16
EN 10028-7:2000	X2CrNiMoN17-11-2	1.4406				0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-12.00	2.00-2.50	N 0.12-0.22
LN 10028-7.2000	X2CrNiMoN17-13-3	1.4429				0.030	2.00	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22
ISO 9328-5:1991	X 2 CrNiMoN 17 12					0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	N 0.12-0.22
130 9320-3.1991	X 2 CrNiMoN 17 13					0.030	2.00	1.00	0.045	0.030	16.50-18.50	11.50-14.50	2.50-3.00	N 0.12-0.22
ASTM A 240/A 240M-03c	317L		S31703			0.030	2.00	0.75	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	N 0.10
EN 10028-7:2000	X2CrNiMo18-15-4	1.4438				0.030	2.00	1.00	0.045	0.015	17.50-19.50	13.00-16.00	3.00-4.00	N 0.11
ISO 9328-5:1991	X 3 CrNiMo 18 16 4					0.030	2.00	1.00	0.045	0.030	17.50-19.50	14.00-17.00	3.00-4.00	
ASTM A 240/A 240M-03c	317LN		S31753			0.030	2.00	0.75	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	N 0.10-0.22
EN 10028-7:2000	X2CrNiMoN18-12-4	1.4434				0.030	2.00	1.00	0.045	0.015	16.50-19.50	10.50-14.00	3.00-4.00	N 0.10-0.20

4.8A Chemical Composition of Austenitic Stainless Steels for Pressure Vessel Plates (Continued)

Standard	Grade, Class, Type,	Steel	UNS		tion kness				Weight	, %, Max	rimum, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	317LMN		S31726			0.030	2.00	0.75	0.045	0.030	17.0-20.0	13.5-17.5	4.0-5.0	N 0.10-0.20
EN 10028-7:2000	X2CrNiMoN17-13-5	1.4439				0.030	2.00	1.00	0.045	0.015	16.50-18.50	12.50-14.50	4.00-5.00	N 0.12-0.22
ISO 9328-5:1991	X 2 CrNiMoN 17 13 5					0.030	2.00	1.00	0.045	0.025	16.50-18.50	12.50-14.50	4.00-5.00	N 0.12-0.22
ASTM A 240/A 240M-03c	321		S32100			0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x (C+N) to 0.70; N 0.10
EN 10028-7:2000	X6CrNiTi18-10	1.4541				0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
ISO 9328-5:1991	X 6 CrNiTi 18 10					0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
ASTM A 240/A 240M-03c	321H		S32109			0.04-0.10	2.00	0.75	0.045	0.030	17.0-19.0	9.0-12.0		Ti 4 x (C+N) to 0.70
EN 10028-7:2000	X6CrNiTiB18-10	1.4941				0.04-0.08	2.00	1.00	0.035	0.015	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80; B 0.0015-0.0050
ISO 9328-5:1991	X 7 CrNiTi 18 10					0.04-0.10	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
ASTM A 240/A 240M-03c	347		S34700			0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.0-13.0		Cb 10 x C to 1.00
EN 10028-7:2000	X6CrNiNb18-10	1.4550				0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ISO 9328-5:1991	X 6 CrNiNb 18 10					0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ASTM A 240/A 240M-03c	347H		S34709			0.04-0.10	2.00	0.75	0.045	0.030	17.0-19.0	9.0-13.0		Cb 8 x C to 1.00
EN 10028-7:2000	X8CrNiNb16-13	1.4961				0.04-0.10	1.50	0.30-0.60	0.035	0.015	15.00-17.00	12.00-14.00		Nb 10 x C to 1.20
ISO 9328-5:1991	X 7 CrNiNb 18 10					0.04-0.10	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Nb 10 x C to 1.20
ASTM A 240/A 240M-03c	904L		N08904			0.020	2.00	1.00	0.045	0.035	19.0-23.0	23.0-28.0	4.0-5.0	Cu 1.0-2.0; N 0.10
EN 10028-7:2000	X1NiCrMoCu25-20-5	1.4539				0.020	2.00	0.70	0.030	0.010	19.00-21.00	24.00-26.00	4.00-5.00	Cu 1.20-2.00; N 0.15
ISO 9328-5:1991	X 2 NiCrMoCu 25 20 5					0.025	2.00	1.00	0.035	0.025	19.00-22.00	24.00-27.00	4.00-5.00	Cu 1.00-2.00
ASTM A 240/A 240M-03c			N08926			0.020	2.00	0.50	0.030	0.010	19.0-21.0	24.0-26.0	6.0-7.0	Cu 0.5-1.5; N 0.15-0.25
EN 10028-7:2000	X1NiCrMoCuN25-20-7	1.4529				0.020	1.00	0.50	0.030	0.010	19.00-21.00	24.00-26.00	6.00-7.00	Cu 0.50-1.50; N 0.15-0.25
ASTM A 240/A 240M-03c			S31277			0.020	3.00	0.50	0.030	0.010	20.5-23.0	26.0-28.0	6.5-8.0	Cu 0.50-1.50; N 0.30-0.40
ASTM A 240/A 240M-03c	800		N08800			0.10	1.50	1.00	0.045	0.015	19.0-23.0	30.0-35.0		Cu 0.75; Ti 0.15-0.60 Al 0.15-0.60; Fe 39.5 min;
ISO 9328-5:1991	X 7 NiCrAlTi 32 21 TQ1 X 7 NiCrAlTi 32 21 TQ2					0.10	2.00	1.00	0.030	0.020	19.00-23.00	30.00-35.00		Cu 0.75; Ti 0.15-0.60; Al 0.15-0.60
ASTM A 240/A 240M-03c	800H		N08810			0.05-0.10	1.50	1.00	0.045	0.015	19.0-23.0	30.0-35.0		Cu 0.75; Ti 0.15-0.60; Al 0.15-0.60; Fe 39.5 min
AGTIVI A 240/A 240/VI-030			N08811			0.06-0.10	1.50	1.00	0.040	0.015	19.0-23.0	30.0-35.0		Cu 0.75; Ti 0.15-0.60; Al 0.15-0.60; Fe 39.5 min
EN 10028-7:2000	X8NiCrAlTi32-21	1.4959				0.05-0.10	1.50	0.70	0.015	0.010	19.00-22.00	30.00-34.00		Cu 0.50; Ti 0.25-0.65;N 0.030; Al 0.25-0.65; Co 0.50; Ni+Co 30.00-34.00
ISO 9328-5:1991	X 8 NiCrAlTi 32 21 TQ1 X 8 NiCrAlTi 32 21 TQ2					0.05-0.10	2.00	1.00	0.030	0.020	19.00-23.00	30.00-35.00		Cu 0.75; Ti 0.15-0.60; Al 0.15-0.60

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section 7	Thickness	Yield Stren	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
ASTM A 240/A 240M-03c	301LN		S30153				240	35	550	80	45	
				CR St, AT	≤ 6		350					
EN 10028-7:2000	X2CrNi18-7	1.4318		HR St, AT	≤ 12		330		650-850		40	see standard for impact data
				HR PI, AT	≤ 75		330					impaor data
ASTM A 240/A 240M-03c	304		S30400				205	30	515	75	40	
				CR St, AT	≤ 6		230		540-750			
EN 10028-7:2000	X5CrNi18-10	1.4301		HR St, AT	≤ 12		210		520-720		45	see standard for impact data
				HR PI, AT	≤ 75		210		320-720			impaor data
ISO 9328-5:1991	X 5 CrNi 18 9			Q			195		500-700		40	
ASTM A 240/A 240M-03c	304H						205	30	515	75	40	
				CR St, AT	≤ 6		230		530-740			
EN 10028-7:2000	X6CrNi18-10	1.4948		HR St, AT	≤ 12		210		510-710		45	see standard for impact data
				HR PI, AT	≤ 75		190		310-710			impaor data
ISO 9328-5:1991	X 7 CrNi 18 9			Q			195		490-690		40	
ASTM A 240/A 240M-03c	304L		S30403				170	25	485	70	40	
				CR St, AT	≤ 6		220		520-670			
	X2CrNiN18-9	1.4307		HR St, AT	≤ 12		200		320-070		45	see standard for impact data
EN 10028-7:2000				HR PI, AT	≤ 75		200		500-650			past data
LIN 10020-7.2000				CR St, AT	≤ 6		220		520-670			
	X2CrNi19-11	1.4306		HR St, AT	≤ 12		200		320-070		45	see standard for impact data
				HR PI, AT	≤ 75		200		500-650			past data
ISO 9328-5:1991	X 2 CrNi 18 10			Q			180		480-680		40	
ASTM A 240/A 240M-03c	304N		S30451				240	35	550	80	30	
				CR St, AT	≤ 6		290					
EN 10028-7:2000	X5CrNiN19-9	1.4315		HR St, AT	≤ 12		270		550-750		40	see standard for impact data
				HR PI, AT	≤ 75		270					impaor data
ASTM A 240/A 240M-03c	304LN		S30453				205	30	515	75	40	
				CR St, AT	≤ 6		290					
EN 10028-7:2000	X2CrNiN18-10	1.4311		HR St, AT	≤ 12		270		550-750		40	see standard for impact data
				HR PI, AT	≤ 75		270		7			impaot data
ISO 9328-5:1991	X 2 CrNiN 18 10			Q			270		550-750		35	

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section 7	Thickness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 240/A 240M-03c	309H		S30909				205	30	515	75	40	
				CR St, AT	≤ 6		220		530-730			
EN 10028-7:2000	X6CrNi23-13	1.4950		HR St, AT	≤ 12		200		510-710		35	see standard for impact data
				HR PI, AT	≤ 75		200		510-710			impaot data
ASTM A 240/A 240M-03c	310H		S31009				205	30	515	75	40	
				CR St, AT	≤ 6		220		530-730			
EN 10028-7:2000	X6CrNi25-20	1.4951		HR St, AT	≤ 12		200		510-710		35	see standard for impact data
				HR PI, AT	≤ 75		200		510-710			impaot data
ASTM A 240/A 240M-03c	316		S31600				205	30	515	75	40	
				CR St, AT	≤ 6		240		530-680		40	
	X5CrNiMo17-12-2	1.4401		HR St, AT	≤ 12		220		530-660		40	see standard for impact data
EN 10028-7:2000				HR PI, AT	≤ 75		220		520-670		45	impaot data
LN 10020-7.2000				CR St, AT	≤ 6		240		550-700			
	X3CrNiMo17-13-3	1.4436		HR St, AT	≤ 12		220		330-700		40	see standard for impact data
				HR PI, AT	≤ 75		220		530-730			impaor data
ISO 9328-5:1991	X 5 CrNiMo 17 12			Q			205		510-710		40	
130 9320-3.1991	X 5 CrNiMo 17 13			Q			205		510-710		40	
ASTM A 240/A 240M-03c	316L		S31603				170	25	485	70	40	
				CR St, AT	≤ 6		240		530-680		40	
	X2CrNiMo17-12-2	1.4404		HR St, AT	≤ 12		220		300 000		40	see standard for impact data
				HR PI, AT	≤ 75		220		520-670		45	paor aata
				CR St, AT	≤ 6		240		550-700		40	
EN 10028-7:2000	X2CrNiMo17-12-3	1.4432		HR St, AT	≤ 12		220		330 700		40	see standard for impact data
				HR PI, AT	≤ 75		220		520-670		45	
				CR St, AT	≤ 6		240		550-700		40	
	X2CrNiMo18-14-3	1.4435		HR St, AT	≤ 12		220		330 700		40	see standard for impact data
				HR PI, AT	≤ 75		220		520-670		45	
ISO 9328-5:1991	X 2 CrNiMo 17 12			Q			190		490-690		40	
100 3020-3.1991	X 2 CrNiMo 17 13			Q			190		490-690		40	
ASTM A 240/A 240M-03c	316H						205	30	515	75	40	
ISO 9328-5:1991	X 7 CrNiMo 17 12			Q			205		510-710		40	

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section 1	Thickness	Yield Strer	ngth, min	Tensile Str	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
ASTM A 240/A 240M-03c	316Ti		S31635				205	30	515	75	40	
				CR St, AT	≤ 6		240		540-690			
EN 10028-7:2000	X6CrNiMoTi17-12-2	1.4571		HR St, AT	≤ 12		220		340-090		40	see standard for impact data
				HR PI, AT	≤ 75		220		520-670			impaor data
ISO 9328-5:1991	X 6 CrNiMoTi 17 12			Q			210		510-710		35	
ASTM A 240/A 240M-03c	316Cb		S31640				205	30	515	75	30	
EN 10028-7:2000	X6CrNiMoNb17-12-2	1.4580		HR PI, AT	≤ 75		220		520-720		40	see standard for impact data
ISO 9328-5:1991	X 6 CrNiMoNb 17 12			Q			215		510-710		30	
ASTM A 240/A 240M-03c	316LN		S31653				205	30	515	75	40	
				CR St, AT	≤ 6		300					
	X2CrNiMoN17-11-2	1.4406		HR St, AT	≤ 12		280		580-780		40	see standard for impact data
EN 10028-7:2000				HR PI, AT	≤ 75		280					impaot data
EN 10026-7:2000				CR St, AT	≤ 6		300				35	
	X2CrNiMoN17-13-3	1.4429		HR St, AT	≤ 12		280		580-780		33	see standard for impact data
				HR PI, AT	≤ 75		280				40	impaor data
ISO 9328-5:1991	X 2 CrNiMoN 17 12			Q			280		580-780		35	
130 9320-3.1991	X 2 CrNiMoN 17 13			Q			280		580-780		35	
ASTM A 240/A 240M-03c	317L		S31703				205	30	515	75	40	
				CR St, AT	≤ 6		240		550-700		35	
EN 10028-7:2000	X2CrNiMo18-15-4	1.4438		HR St, AT	≤ 12		220		330-700		33	see standard for impact data
				HR PI, AT	≤ 75		220		520-720		40	past aata
ISO 9328-5:1991	X 3 CrNiMo 18 16 4			Q			195		490-690		35	
ASTM A 240/A 240M-03c	317LN		S31753				240	35	550	80	40	
				CR St, AT	≤ 6		290		570-770		35	
EN 10028-7:2000	X2CrNiMoN18-12-4	1.4434		HR St, AT	≤ 12		270		370-770		33	see standard for impact data
				HR PI, AT	≤ 75		270		540-740		40	
ASTM A 240/A 240M-03c	317LMN		S31726				240	35	550	80	40	
				CR St, AT	≤ 6		290				35	
EN 10028-7:2000	X2CrNiMoN17-13-5	1.4439		HR St, AT	≤ 12		270		580-780		33	see standard for impact data
				HR PI, AT	≤ 75		270				40	psst said
ISO 9328-5:1991	X 2 CrNiMoN 17 13 5			Q			285		580-800		35	

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section 7	Thickness	Yield Stren	gth, min	Tensile Str	rength, min	Elongation,	
Designation	Symbol or Name		Number	Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	min, %,	Other
ASTM A 240/A 240M-03c	321		S32100				205	30	515	75	40	
				CR St, AT	≤ 6		220		520-720			
EN 10028-7:2000	X6CrNiTi18-10	1.4541		HR St, AT	≤ 12		200		320-720		40	see standard for impact data
				HR PI, AT	≤ 75		200		500-700			impaor data
ISO 9328-5:1991	X 6 CrNiTi 18 10			Q			200		510-710		35	
ASTM A 240/A 240M-03c	321H		S32109				205	30	515	75	40	
				CR St, AT	≤ 6		220		510-710			
EN 10028-7:2000	X6CrNiTiB18-10	1.4941		HR St, AT	≤ 12		200		310-710		40	see standard for impact data
				HR PI, AT	≤ 75		200		490-690			past aata
ISO 9328-5:1991	X 7 CrNiTi 18 10			Q			175		490-690		35	
ASTM A 240/A 240M-03c	347		S34700				205	30	515	75	40	
EN 10028-7:2000	X6CrNiNb18-10	1.4550		HR PI, AT	≤ 75		200		500-700		40	see standard for impact data
ISO 9328-5:1991	X 6 CrNiNb 18 10			Q			205		510-710		30	
ASTM A 240/A 240M-03c	347H		S34709				205	30	515	75	40	
EN 10028-7:2000	X8CrNiNb16-13	1.4961		HR PI, AT	≤ 75		200		510-690		35	see standard for impact data
ISO 9328-5:1991	X 7 CrNiNb 18 10			Q			205		510-710		30	
ASTM A 240/A 240M-03c	904L		N08904				220	31	490	71	35	
				CR St, AT	≤ 6		240		530-730			
EN 10028-7:2000	X1NiCrMoCu25-20-5	1.4539		HR St, AT	≤ 12		220		330-730		35	see standard for impact data
				HR PI, AT	≤ 75		220		520-720			paot aata
ISO 9328-5:1991	X 2 NiCrMoCu 25 20 5						220		520-720		35	
ASTM A 240/A 240M-03c			N08926				295	43	650	94	35	
EN 10028-7:2000	X1NiCrMoCuN25-20-7	1.4529		HR PI, AT	≤ 75		300		650-850		40	see standard for impact data
ASTM A 240/A 240M-03c			S31277				360	40	770	112	40	
ASTM A 240/A 240M-03c	800		N08800				205	30	520	75	30	
ISO 9328-5:1991	X 7 NiCrAlTi 32 21 TQ1			Q1			165		430-680		25	
100 0020-0.1001	X 7 NiCrAlTi 32 21 TQ2			Q2			210		500-750		22	

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	hickness	Yield Strer	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %,	Other
ASTM A 240/A 240M-03c	800H		N08810				170	25	450	65	30	
ASTIVI A 240/A 240/VI-03C			N08811				170	25	450	65	30	
EN 10028-7:2000	X8NiCrAlTi32-21	1.4959		HR PI, AT	≤ 75		170		500-750		30	see standard for impact data
ISO 9328-5:1991	X 8 NiCrAlTi 32 21 TQ1			Q1			165		430-680		25	
130 9320-3.1991	X 8 NiCrAlTi 32 21 TQ2			Q2			210		500-750		22	

4.9 Duplex Stainless Steels for Pressure Vessel Plates

4.9A Chemical Composition of Duplex (Ferritic-Austenitic) Stainless Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS		tion kness				Weight,	%, Maxin	num, Unless (Otherwise	Specified	
Designation	Symbol or Name	Number	Number	t, mm	t, in.	С	Mn	Si	P	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	2205		S32205			0.030	2.00	1.00	0.030	0.020	22.0-23.0	4.5-6.5	3.0-3.5	N 0.14-0.20
EN 10028-7:2000	X2CrNiMoN22-5-3	1.4462				0.030	2.00	1.00	0.035	0.015	21.00-23.00	4.50-6.50	2.50-3.50	N 0.10-0.22
ASTM A 240/A 240M-03c	2304		S32304			0.030	2.50	1.00	0.040	0.030	21.5-24.5	3.0-5.5	0.05-0.60	N 0.05-0.20; Cu 0.05-0.60
EN 10028-7:2000	X2CrNiN23-4	1.4362				0.030	2.00	1.00	0.035	0.015	22.00-24.00	3.50-5.50	0.10-0.60	N 0.05-0.20; Cu 0.10-0.60
ASTM A 240/A 240M-03c			S32520			0.030	1.50	0.80	0.035	0.020	24.0-26.0	5.5-8.0	3.0-4.0	N 0.20-0.35; Cu 0.50-2.00
EN 10028-7:2000	X2CrNiMoCuN25-6-3	1.4507				0.030	2.00	0.70	0.035	0.015	24.00-26.00	5.50-7.50	2.70-4.00	N 0.15-0.30; Cu 1.00-2.50
ASTM A 240/A 240M-03c	2507		S32750			0.030	1.20	0.80	0.035	0.020	24.0-26.0	6.0-8.0	3.0-5.0	N 0.24-0.32; Cu 0.50
EN 10028-7:2000	X2CrNiMoN25-7-4	1.4410				0.030	2.00	1.00	0.035	0.015	24.00-26.00	6.00-8.00	3.00-4.50	N 0.20-0.35
ASTM A 240/A 240M-03c			S32760			0.030	1.00	1.00	0.030	0.010	24.0-26.0	6.0-8.0	3.0-4.0	N 0.20-0.30; Cu 0.50-1.00; W 0.50-1.00
EN 10028-7:2000	X2CrNiMoCuWN25-7-4	1.4501				0.030	1.00	1.00	0.035	0.015	24.00-26.00	6.00-8.00	3.00-4.00	N 0.20-0.30; Cu 0.50-1.00; W 0.50-1.00

4.9 Duplex Stainless Steels for Pressure Vessel Plates

4.9B Mechanical Properties of Duplex (Ferritic-Austenitic) Stainless Steels for Pressure Vessel Plates

Standard	Grade, Class, Type,	Steel	UNS	Heat	Section T	nickness	Yield Strer	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
ASTM A 240/A 240M-03c	2205		S32205				450	65	655	95	25	
				CR St, AT	t ≤ 6; w < 300		465				20	
				OH St, AT	t ≤ 6; w ≥ 300		480		660-950		20	
EN 10028-7:2000	X2CrNiMoN22-5-3	1.4462		HR St, AT	$t \le 12; w < 300$		445		000 330		25	see standard for
LIV 10020 7.2000	AZON MINIONZZ 3 0	1.4402		Till Ot, Al	t ≤ 12; w ≥ 300		460				25	impact data
				HR PI, AT	t ≤ 75; w < 300		445		640-840		25	
				11111, 71	t ≤ 75; w ≥ 300		460		040 040		25	
ASTM A 240/A 240M-03c	2304		S32304				400	58	600	87	25	
				CR St, AT	t ≤ 6; w < 300		405					
					t ≤ 6; w ≥ 300		420		600-850		20	
EN 10028-7:2000	X2CrNiN23-4	1.4362		HR St, AT	t ≤ 12; w < 300		385		000 000		20	see standard for
214 10020 7.2000	ALOHAIN 4	1.4002			t ≤ 12; w ≥ 300		400					impact data
				HR PI, AT	t ≤ 75; w < 300		385		630-800		25	
					t ≤ 75; w ≥ 300		400		000 000			
ASTM A 240/A 240M-03c			S32520				550	80	770	112	25	
				CR St, AT	t ≤ 6; w < 300		495					
					t ≤ 6; w ≥ 300		510		690-940		20	
EN 10028-7:2000	X2CrNiMoCuN25-6-3	1.4507		HR St. AT	t ≤ 12; w < 300		475					see standard for
	7.20				t ≤ 12; w ≥ 300		490					impact data
				HR PI, AT	t ≤ 75; w < 300		475		690-890		25	
					t ≤ 75; w ≥ 300		490					
ASTM A 240/A 240M-03c	2507		S32750				550	80	795	116	15	
				CR St, AT	t ≤ 6; w < 300		535					
					t ≤ 6; w ≥ 300		550		750-1000			
EN 10028-7:2000	X2CrNiMoN25-7-4	1.4410		HR St, AT	t ≤ 12; w < 300		515				20	see standard for
	7.2011				t ≤ 12; w ≥ 300		530					impact data
				HR PI, AT	t ≤ 75; w < 300		515		730-930			
				,	t ≤ 75; w ≥ 300		530					
ASTM A 240/A 240M-03c			S32760				550	80	750	108	25	
EN 10028-7:2000	X2CrNiMoCuWN25-7-4	1.4501		HR PI, AT	t ≤ 75; w < 300		515		730-930		25	see standard for
				-,	t ≤ 75; w ≥ 300		530					impact data

4.10 Non-Comparable Carbon and Alloy Steels for Pressure Vessel Plates

ASTM A 202/A 202	M-03 - Prossur	o Voscol Blatos	Alloy Stool C	hromium Man	ganasa Siliaan							
Grade, Class, Type		B										
UNS Number	K11742	K12542										
ASTM A 225/A 225			<u> </u>									
Grade, Class, Type		D										
UNS Number	K12524											
ASTM A 285/A 285				Manganese-S	Silicon							
Grade, Class, Type		В	С									
UNS Number	K01700	K02200	K02801									
ASTM A 299/A 299	M-02 - Pressur	e Vessel Plates	, Carbon Steel,	Manganese-S	Silicon							
Grade, Class, Type												
UNS Number	K02803											
ASTM A 387/A 387	M-03 - Pressur	e Vessel Plates	s, Alloy Steel, C	hromium-Moly	ybdenum							
Grade, Class, Type	Grade 9 Class 1, 2											
UNS Number	S50400											
ASTM A 455/A 455	M-03 - Pressur	e Vessel Plates	, Carbon Steel,	High-Strength	h Manganese							
Grade, Class, Type												
UNS Number	K03300											
ASTM A 516/A 516	M-03 - Pressur	e Vessel Plates	, Carbon Steel,	for Moderate-	and Lower-Ten	nperature Serv	ice					
Grade, Class, Type	55 [380]											
UNS Number	K01800											
ASTM A 517/A 517	M-93 (1999) - P	ressure Vessel	Plates, Alloy S	teel, High-Stre	ength, Quenche	d and Tempere	ed					
Grade, Class, Type	Α	В	С	E	F	Н	J K	М	Р	Q	S	Т
UNS Number	K11856	K11630	K11511	K21604 P	K11576 K1	1646 K11	625	K11683	3 K21650			
ASTM A 533/A 533	M-93 (1999) - P	ressure Vessel	Plates, Alloy S	teel, Quenche	d and Tempere	d, Manganese-	Molybdenum aı	nd Manganese-I	Molybdenum-N	lickel	'	1
Grade, Class, Type	Type D Class 1, 2, 3											
UNS Number	K12529											
ASTM A 542/A 542	M-99 - Pressur	e Vessel Plates	, Alloy Steel, Q	uenched-and-	Tempered, Chro	omium-Molybd	enum, and Chr	omium-Molybde	enum-Vanadiu	m		
Grade, Class, Type	Type A, Cl. 1, 2, 3, 4, 4a	Type B, Cl. 1, 2, 3, 4, 4a	Type C, Cl. 1, 2, 3, 4, 4a	Type D, Cl. 1, 2, 3, 4, 4a	Type E, Cl. 4, 4a							
UNS Number	K21590	K21590	K31830									
ASTM A 543/A 543	M-93 (1999) - P	ressure Vessel	Plates, Alloy S	teel, Quenche	ed and Tempere	d Nickel-Chron	nium-Molybden	um				
Grade, Class, Type	Tuno D	Type C,										
UNS Number	K42339	K11224										
					1							

ASTM A 562/A 562I	M-90 (2001) - P	ressure Vessel	Plates, Carbor	n Steel, Mangai	nese-Titanium	for Glass or Dif	fused Metallic	Coatings				
Grade, Class, Type												
UNS Number												
ASTM A 645/A 645I	M-99a - Pressu	re Vessel Plate	s, Five Percent	t Nickel Alloy S	teel, Specially	Heat Treated						
Grade, Class, Type												
UNS Number	K41583											
ASTM A 724/A 724I	M-99 - Pressure	e Vessel Plates	, Carbon-Mang	janese-Silicon	Steel, Quenche	ed and Tempere	ed, for Welded I	ayered Pressi	ure Vessels			
Grade, Class, Type	Α	В	С									
UNS Number	K11831	K12031	K12037									
ASTM A 734/A 734I	M-87a (2003) - I	Pressure Vesse	l Plates, Alloy	Steel and High	-Strength Low	-Alloy Steel, Qu	enched-and-Te	empered				
Grade, Class, Type	Α	В										
UNS Number	K21205	K11720										
ASTM A 735/A 735I	M-03 - Pressure	e Vessel Plates	, Low-Carbon	Manganese-Mo	lybdenum-Coli	umbium Alloy S	Steel, for Moder	ate and Lower	Temperature S	Service		
Grade, Class, Type	1, 2, 3, 4											
UNS Number	K10623											
	ASTM A 736/A 736M-03 Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy										bium Alloy	
Steel	Our de A	0 1 0		1	I				1	1	I	
Grade, Class, Type	Grade A Class 1, 2, 3	Grade C Class 1, 3										
UNS Number	K20747											
ASTM A 738/A 738I	M-03a – Pressu	ire Vessel Plate	es, Heat-Treate	d, Carbon-Man	ganese-Silicon	Steel, for Mod	erate and Lowe	r Temperature	Service			
Grade, Class, Type	Grade D	Grade E										
UNS Number												
ASTM A 782/A 782I	M-90 (2001) - P	ressure-Vessel	Plates Quench	ned-and-Tempe	ered, Manganes	se-Chromium-M	lolybdenum-Sil	icon Zirconiun	n Alloy Steel			
Grade, Class, Type	Class 1, 2, 3											
UNS Number												
ASTM A 832/A 832I	M-99 - Pressur	e Vessel Plates	, Alloy Steel, C	hromium-Moly	bdenum-Vanad	dium						
Grade, Class, Type	21V	22V	23V									
UNS Number	K31830	K31830	K31830									
ASTM A 841/A 841	M-03a - Steel P	lates for Press	ure Vessels, Pi	roduced by The	ermo-Mechanic	al Control Proc	ess (TMCP)					
Grade, Class, Type	Grade D Class 3	Grade E, Class 4	Grade E, Class 5	Grade F, Class 6	Grade F, Class 7	Grade F, Class 8						
UNS Number												

4.10 Non-Comparable Carbon and Alloy Steels for Pressure Vessel Plates (Continued)

JIS G 3115:2000 -	Steel Plates for	Pressure Vess	sels for Interme	diate Temperat	ture Service							
Symbol	SPV490											
Previous Symbol	SPV 50											
JIS G 3120:1987 -	IS G 3120:1987 - Carbon Steel and Molybdenum Alloy Steel Plates for Boilers and Other Pressure Vessels											
Steel Name	SB 42	SB 46	SB 49	SB 46 M	SB 49 M							
Previous Symbol												
JIS G 3124:1987 -	High Strength S	Steel Plates for	Pressure Vess	el for Intermed	iate and Moder	ate Temperatu	re Service					
Symbol	SEV 25	SEV 30	SEV 35									
Previous Symbol												
JIS G 4110:1993 -	High Strength C	Chromium-Moly	ybdenum Alloy	Steel Plates fo	r Pressure Ves	sels Under Hig	h-Temperature	Service				
Symbol	SCMQ4V	SCMQ5V										
Previous Symbol												
EN 10028-2:2003 -	Flat Products N	lade of Steels	for Pressure Pu	urposes - Part	2: Non-Alloy ar	d Alloy Steels	With Specified	Elevated Temp	erature Prope	rties		
Steel Name	X12CrMo9-10	13CrMoV9-10	12CrMoV12-10									
Steel Number	1.7375	1.7703	1.7767									
EN 10028-3:2003 -	Flat Products N	lade of Steels	for Pressure Pu	ırposes – Part	3: Weldable Fi	ne Grain Steels	, Normalized					
Steel Name	P460NH	P460NL1	P460NL2									
Steel Number	1.8935	1.8915	1.8918									
EN 10028-5:2003 -	Flat Products N	Made of Steels	for Pressure Pu	urposes – Part	6: Weldable Fi	ne Grain Steels	, Thermomech	anically Rolled				
Steel Name	P355M	P355M1	P355M2	P420M	P420M1	P420M2	P460M	P460M1	P460M2			
Steel Number	1.8821	1.8832	1.8833	1.8824	1.8835	1.8828	1.8826	1.8837	1.8831			
EN 10028-6:2003 -	Flat Products N	Made of Steels	for Pressure Pu	ırposes – Part	6: Weldable Fi	ne Grain Steels	, Quenched an	d Tempered				
Steel Name	P355Q	P355QH	P355QL1	P355QL2	P460Q	P460QH	P460QL1	P460QL2	P500Q	P500QH	P500QL1	P500QL2
Steel Number	1.8866	1.8867	1.8868	1.8869	1.8870	1.8871	1.8872	1.8864	1.8873	1.8874	1.8875	1.8865
Steel Name	P690Q	P690QH	P690QL1	P690QL2								
Steel Number	1.8879	1.8880	1.8881	1.8888								
ISO 9328-4:1991 -	Steel Plates and	d Strips for Pre	ssure Purpose	s – Part 4: Wel	dable Fine Gra	in Steels with F	ligh Proof Stre	ss Supplied in	the Normalized	d or Quenched	and Tempered	Condition
Steel Type	P 390 TN	PH 390 TN	PL 390 TN	PLH 390 TN	P 420 TN	PH 420 TN	PL 420 TN	PLH 420 TN	P 460 TN	PH 460 TN	PL 460 TN	PLH 460 TN
Steel Type	P 460 TQ	PH 460 TQ	PL 460 TQ	PLH 460 TQ	P 500 TQ	PH 500 TQ	PL 500 TQ	PLH 500 TQ	P 550 TQ	PH 550 TQ	PL 550 TQ	PLH 550 TQ
Steel Type	P 620 TQ	PH 620 TQ	PL 620 TQ	PLH 620 TQ	P 690 TQ	PH 690 TQ	PL 690 TQ	PLH 690 TQ				

4.11 Non-Comparable Stainless Steels for Pressure Vessel Plates

ASTM A 240/A 240I	VI-03c Chromi	ium and Ch	romium-Nickel S	tainless Stee	l Plate, Shee	et, and Strip for	Pressu	re Ves	sels and for Ge	neral Applic	ations			
Grade, Class, Type							41	10		410S				429
UNS Number	S32803	S40910	S40920	S40930	S40945	S40977	S41	000	S41003	S41008	S41045	S41050	S4203	35 S42900
Grade, Class, Type	430	434	436		XM-33	XM-27								
UNS Number	S43000	S43400	S43600	S44500	S44626	S44627	S44	635	S44660	S44700	S44735	S44800	S4680	00
Grade, Class, Type			201-1, 201-2				20)2		XM-19	XM-31	XM-17	XM-1	8
UNS Number	N08020	N08367	S20100	S20103	S20153	S20161	S20	200	S20400	S20910	S21400	S21600	S2160)3 S21800
Grade, Class, Type	XM-29	301	301L	302		XM-21	30)5					3099	309Cb
UNS Number	S24000	S30100	S30103	S30200	S30415	S30452	S30	500	S30600	S30601	S30615	S30815	S3090	08 S30940
Grade, Class, Type	309HCb	310S	310Cb	310HCb	310MoLN			-	316N	317	317LM			
UNS Number	S30941	S31008	S31040	S31041	S31050	S31254	S31	266	S31651	S31700	S31725	S32050	S326	15 S32654
Grade, Class, Type		334		348	348H			-		XM-15				
UNS Number	S33228	S33400	S34565	S34800	S34809	S35045	S35	135	S35315	S38100	S31200)		
Grade, Class, Type				255	329			-						
UNS Number	S31260	S31803	S32001	S32550	S32900	S32950		-						
EN 10028-7:2000 FI	at Products N	lade of Ste	els for Pressure I	Purposes - P	art 7: Stainle	ss Steels								
Steel Name	X1CrNiMoN2	25-22-2	X4CrNiMo16-5-1	X1CrNiMo	CuN25-25-5	X1CrNiMoCuN2	20-18-7	X3CrN	NiMoBN17-13-3	X1NiCrMo0	Cu31-27-4	X5NiCrAlTi31-20	(+RA)	X1CrNi25-21
Steel Number	1.4466	6	1.4418	1.	4537	1.4547			1.4910	1.45	63	1.4958 (+RA)	1.4335
Steel Name	X2CrTi	17									-			
Steel Number	1.4520)									-			
ISO 9328-5:1991 St	eel Plates and	d Strips for	Pressure Purpos	es - Technic	al Delivery C	onditions - Part	t 5: Aus	stenitic	Steels				-	
Steel Type	X 7 CrNiMoE	3 17 12									-			

Chapter

5

STEEL TUBES AND PIPES

ASTM Standards

ASTM A 53/A 53M-02	Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless
ASTM A 106-02a	Seamless Carbon Steel Pipe for High-Temperature Service
ASTM A 135-01	Electric-Resistance-Welded Steel Pipe
ASTM A 139-00	Electric-Fusion (Arc)-Welded Steel Pipe (NPS 4 and Over)
ASTM A 178/A 178M-02	Electric-Resistance-Welded Carbon Steel and Carbon-Manganese Steel Boiler and Superheater Tubes Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 179/A 179M-90a (2001)	Seamless Cold-Drawn Low-Carbon Steel Heat-Exchanger and Condenser Tubes Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 192/A 192-02	Seamless Carbon Steel Boiler Tubes for High-Pressure Service Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 209/A 209-03	Seamless Carbon-Molybdenum Alloy-Steel Boiler and Superheater Tubes
ASTM A 210/A 210M-02	Seamless Medium-Carbon Steel Boiler and Superheater Tubes
ASTM A 213/A 213M-03a	Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes
ASTM A 214/A 214M-96 (2001)	Electric-Resistance-Welded Carbon Steel Heat-Exchanger and Condenser Tubes
ASTM A 249/A 249M-03	Welded Austenitic Steel Boiler, Superheater, Heat-Exchanger, and Condenser Tubes
ASTM A 250/A 250M-95 (2001)	Electric-Resistance-Welded Ferritic Alloy-Steel Boiler and Superheater Tubes
ASTM A 268/A 268M-03	Seamless and Welded Ferritic and Martensitic Stainless Steel Tubing for General Service
ASTM A 269-02a	Seamless and Welded Austenitic Stainless Steel Tubing for General Service
ASTM A 312/A 312M-03	Seamless and Welded Austenitic Stainless Steel Pipes
ASTM A 333/A 333M-99	Seamless and Welded Steel Pipe for Low-Temperature Service
ASTM A 334/A 334M-99	Seamless and Welded Carbon and Alloy-Steel Tubes for Low-Temperature Service
ASTM A 335/A 335M-03	Seamless Ferritic Alloy-steel Pipe for High-Temperature Service
ASTM A 358/A 358M-01	Electric-Fusion–Welded Austenitic Chromium-Nickel Alloy Steel Pipe for High-Temperature Service
ASTM A 376/A 376M-02a	Seamless Austenitic Steel Pipe for High-Temperature Central-Station Service
ASTM A 409/A 409M-01	Welded Large Diameter Austenitic Steel Pipe for Corrosive or High-Temperature Service
ASTM A 500-03	Cold-Formed Welded and Seamless Carbon Steel Structural Tubing in Rounds and Shapes
ASTM A 501-01	Hot-Formed Welded and Seamless Carbon Steel Structural Tubing
	Seamless Stainless Steel Mechanical Tubing
ASTM A 511-96	Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 512-96 (2001)	Cold-Drawn Buttweld Carbon Steel Mechanical Tubing Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 513-00	Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 519-03	Seamless Carbon and Alloy Steel Mechanical Tubing Note: Mechanical properties data are supplementary requirements, provided for information only. Data are "typical" values.
ASTM A 554-03	Welded Stainless Steel Mechanical Tubing Note: Mechanical properties data are supplementary requirements, provided for information only.
ASTM A 556/A 556M-96 (2001)	Seamless Cold-Drawn Carbon Steel Feedwater Heater Tubes
ASTM A 595-98 (2002)	Steel Tubes, Low-Carbon, Tapered for Structural Use
ASTM A 632-02a	Seamless and Welded Austenitic Stainless Steel Tubing (Small-Diameter) for General Service
ASTM A 688/A 688M-03	Welded Austenitic Stainless Steel Feedwater Heater Tubes
ASTM A 778-01	Welded, Unannealed Austenitic Stainless Steel Tubular Products
ASTM A 803/A 803M-03	Welded Ferritic Stainless Steel Feedwater Heater Tubes
ASTM A 984/A 984M-03	Steel Line Pipe, Black, Plain-End, Electric-Resistance-Welded
ASTM A 1005/A 1005M-00	Steel Line Pipe, Black, Plain End, Longitudinal and Helical Seam, Double Submerged-Arc Welded
7.0 TW 7. 1000/A 1000W 00	Stool Enter type, Black, Frant Ente, Edityitaania and Fichea Geans, Bouble Gubinetgeu-Ale Welden

SAE Standard

SAE J526 JAN00	Welded Low-Carbon Steel Tubing

API Standard

API 5L-2004	Specification for Line Pipe	
-------------	-----------------------------	--

CSA Standard

CSA 2245.1-2002 Steel Line Pipe		Steel Line Pipe
---------------------------------	--	-----------------

JIS Standards

JIS G 3441:1988	Alloy Steel Tubes for Machine Purposes
JIS G 3444:1994	Carbon Steel Tubes for General Structural Purposes
JIS G 3445:1988	Carbon Steel Tubes for Machine Structural Purposes
JIS G 3446:1994	Stainless Steel Pipes for Machine and Structural Purposes
JIS G 3452:1997	Carbon Steel Pipes for Ordinary Piping
JIS G 3454:1988	Carbon Steel Pipes for Pressure Service
JIS G 3455:1988	Carbon Steel Pipes for High Pressure Service
JIS G 3456:1988	Carbon Steel Pipes for High Temperature Service
JIS G 3457:1988	Arc Welded Carbon Steel Pipes
JIS G 3458:1988	Alloy Steel Pipes
JIS G 3459:1997	Stainless Steel Pipes
JIS G 3460:1988	Steel Pipes for Low Temperature Service
JIS G 3461:1988	Carbon Steel Boiler and Heat Exchanger Tubes
JIS G 3462:1988	Alloy Steel Boiler and Heat Exchanger Tubes
JIS G 3463:1994	Stainless Steel Boiler and Heat Exchanger Tubes
JIS G 3464:1988	Steel Heat Exchanger Tubes for Low Temperature Service
JIS G 3467:1988	Steel Tubes for Fired Heater
JIS G 3468:1994	Large Diameter Welded Stainless Steel Pipes
JIS G 3472:1988	Electric Resistance Welded Carbon Steel Tubes for Automobile Structural Purposes
JIS G 3473:1988	Carbon Steel Tubes for Cylinder Barrels
JIS G 3474:1995	High Tensile Strength Steel Tubes for Tower Structural Purposes

BSI Standards

BSI BS 3604-2:1991	Steel Pipes and Tubes for Pressure Purposes: Ferritic Alloy Steel with Specified Elevated Temperature
D31 D3 3004-2.1991	Properties – Specification for Longitudinally Arc Welded Tubes
BSI BS 3605-1:1991 AMD 2:1997	Austenitic Stainless Steel Pipes and Tubes for Pressure Purposes
DSI DS 3005-1:1991 AIVID 2:1997	Part 1: Specification for Seamless Tubes
BSI BS 3605-2:1992 AMD 1:1997	Austenitic Stainless Steel Pipes and Tubes for Pressure Purposes
BSI BS 3005-2.1992 AMD 1.1997	Part 2: Specification for Longitudinally Welded Tubes
BSI BS 6323-8:1982	Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes
DSI DS 0323-0.1982	Part 8: Specific Requirements for Longitudinally Welded Stainless Steel Tubes

DIN Standards

DIN 1615:1984	Welded Circular Unalloyed Steel Tubes Not Subject to Special Requirements
DIN 1630:1984	High Performance Seamless Circular Unalloyed Steel Tubes
DIN 17455:1999	General Purpose Welded Circular Stainless Steel Tubes - Technical Delivery Conditions
DIN 17456:1999	General Purpose Seamless Circular Stainless Steel Tubes - Technical Delivery Conditions
DIN 17457:1985	Welded Circular Austenitic Stainless Steel Tubes Subject to Special Requirements - Technical Delivery Conditions
DIN 17458:1985	Seamless Circular Austenitic Stainless Steel Tubes Subject to Special Requirements - Technical Delivery Conditions
DIN 17459:1992	Seamless Circular High-Temperature Austenitic Steel Tubes - Technical Delivery Conditions
DIN 28180:1985	Seamless Steel Tubes for Tubular Heat Exchangers; Dimensions, Dimensional Deviations and Materials
DIN 28181:1985	Welded Steel Tubes for Tubular Heat Exchangers; Dimensions, Dimensional Deviations and Materials

AFNOR Standards

AFNOR NF A 49-141:1978	Welded Plain End Tubes of Commercial Quality for General Purposes at Mean Pressure Dimensions - Technical Delivery Conditions
AFNOR NF A 49-214:1978	Seamless Austenitic Steel Tubes for Use at High Temperatures. Dimensions (With Normal Tolerances) - Technical Conditions of Delivery
AFNOR NF A 49-217:1987	Seamless Tubes for Heat Exchangers - Stainless Ferritic, Austenic or Ferritic-Austenitic Steel Grades Dimensions - Technical Delivery Conditions
AFNOR NF A 49-220:1990	Grooved Seamless Steel Tubes for Use at High Temperature - Dimensions - Technical Delivery Conditions
AFNOR NF A 49-244:1993	Welded Austenitic Stainless and Austenitic Ferritic Steel Rolled Tubes for Pressure Service - Dimensions, Technical Conditions for Delivery
AFNOR NF A 49-247:1981	Tubes Welded Longitudinally for Heat Exchangers - Austenitic Stainless Steels Dimensions - Technical Delivery Conditions
AFNOR NF A 49-250:1979	Welded Plain End Tubes of Commercial Quality with or without Special Delivery Conditions Dimensions (D Superior or Equal to 168.3 mm) - Technical Delivery Conditions

AFNOR Standards (Continued)

AFNOR NF A 49-317:1980	Seamless Plain End Tubes for Engineering Use. Austenitic Stainless Steels Dimensions - Technical Delivery Conditions
	Structural Welded Tubes, Circular, Square, Rectangular or Oval, in Ferritic or Austenitic Stainless Steels Dimensions - Technical Delivery Conditions

CEN Standards

EN 10000 1 100E	
EN 10208-1:1997	Steel Pipes for Pipelines for Combustible Fluids – Technical Delivery Conditions – Part 1: Pipes of Requirement Class A
EN 10208-2:1996	Steel Pipes for Pipelines for Combustible Fluids – Technical Delivery Conditions – Part 2: Pipes of Requirement Class B
EN 10216-1:2002	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 1: Non-alloy steel tubes with specified room temperature properties
EN 10216-2:2002	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 2: Non-alloy and alloy steel tubes with specified elevated temperature properties
EN 10216-3:2002	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 3: Alloy fine grain steel tubes
EN 10216-4:2002	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 4: Non-alloy and alloy steel tubes with specified low temperature properties
EN 10217-1:2002	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 1: Non-alloy steel tubes with specified room temperature properties
EN 10217-2:2002	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 2: Electric welded non-alloy and alloy steel tubes with specified elevated temperature properties
EN 10217-3:2002	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 3: Alloy fine grain steel tubes
EN 10217-4:2002	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 4: Electric welded non-alloy steel tubes with specified low temperature properties
EN 10217-5:2002	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 5: Submerged arc welded non- alloy and alloy steel tubes with specified elevated temperature properties
EN 10217-6:2002	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 6: Submerged arc welded non- alloy steel tubes with specified low temperature properties
EN 10296-1:2003	Welded circular steel tubes for mechanical and general engineering purposes – Technical delivery conditions – Part 1: Non-alloy and alloy steel tubes
EN 10297-1:2003	Seamless circular steel tubes for mechanical and general engineering purposes – Technical delivery conditions – Part 1: Non-alloy and alloy steel tubes
EN 10305-1:2002	Steel tubes for precision applications – Technical delivery conditions – Part 1: Seamless cold drawn tubes
EN 10305-2:2002	Steel tubes for precision applications – Technical delivery conditions – Part 2: Welded cold drawn tubes
EN 10305-3:2002	Steel tubes for precision applications – Technical delivery conditions – Part 3: Welded cold sized tubes

ISO Standards

ISO 2604-II:1975	Steel Products for Pressure Purposes - Quality Requirements - Part 2: Wrought Seamless Tubes
ISO 2604-III:1975	Steel Products for Pressure Purposes - Quality Requirements - Part 3: Electric Resistance and Induction-Welded Tubes
ISO 2604-V:1978	Steel Products for Pressure Purposes - Quality Requirements - Part 5: Longitudinally Welded Austenitic Stainless Steel Tubes
ISO 2937:1974	Plain End Seamless Steel Tubes for Mechanical Application
ISO 3183-1:1996	Steel Pipe for Pipelines - Technical Delivery Conditions - Part 1: Pipes of Requirement Class A
ISO 3183-2:1996	Steel Pipe for Pipelines - Technical Delivery Conditions - Part 2: Pipes of Requirements Class B
ISO 3304:1985	Plain End Seamless Precision Steel Tubes - Technical Conditions for Delivery
ISO 3305:1985	Plain End Welded Precision Steel Tubes - Technical Conditions for Delivery
ISO 3306:1985	Plain End As-Welded and Sized Precision Steel Tubes - Technical Conditions for Delivery
ISO 9329-3:1997	Seamless Steel Tubes for Pressure Purposes. Technical Delivery Conditions
130 9329-3.1997	Part 3: Unalloyed and Alloyed Steels with Specified Low Temperature Properties
ISO 9330-3:1997	Welded Steel Tubes for Pressure Purposes. Technical Delivery Conditions. Part 3: Electric Resistance and
100 9000-0.1997	Induction Welded Unalloyed and Alloyed Steel Tubes with Specified Low Temperature Properties
ISO 9330-5:2000	Welded Steel Tubes for Pressure Purposes - Technical Delivery Conditions
100 0000 0.2000	Part 5: Submerged Arc-Welded Unalloyed and Alloyed Steel Tubes with Specified Low Temperature Properties

5.1 Tubes for General and Structural Applications

Standard	Heat Treatment Terms
AFNOR NF A 49-141:1978	HR: hot rolled; CF + T: cold finished and tempered
AFNOR NF A 49-250:1979	AM: as manufactured
AFNOR NF A 49-317:1980	HQ: hyperquenched
AFNOR NF A 49-647:1979	AM: as manufactured
ASTM A 268/A 268M-03	HT: heat treat
ASTM A 269-02a	HT: heat treat
ASTM A 500-03	CF: cold formed; SR: stress relieved; A: annealed; HT: heat treated
ASTM A 501-01	HF: hot formed
ASTM A 511-96	A: annealed
ASTM A 512-96 (2001)	SA: soft-annealed; SR A: stress relief annealed
ASTM A 513-03a	AW: as-welded; N: normalized; SD: sink-drawn; MD: mandrel-drawn; MD SR: mandrel-drawn stress-relieved
ASTM A 519-03	HR: hot rolled; CW: cold worked; SR: stress relieved; A: annealed; N: normalized; AM: as manufactured
ASTM A 554-03	A: annealed
ASTM A 595-98 (2002)	RCCM: roll compressed cold on a mandrel
ASTM A 632-02a	HT: heat treat
ASTM A 778-01	AM: as manufacture
DIN 1615:1984	AD: as delivered
DIN 17455:1999	A: annealed; SA+Q: solution annealed and quenched
DIN 17456:1999	A: annealed; SA+Q: solution annealed and quenched; SA+Q (HW): solution annealed and quenched, suitable for hot worked tubes
EN 10296-1:2003	CR: cold rolled; A: annealed; N: full tube normalized; NW: normalized weld zone; U: see standard; TMR: thermomechanically rolled
EN 10297-1:2003	AR: as rolled; N: normalized; QT: quenched and tempered
EN 10305-1:2002	A: annealed; C: cold drawn, hard; LC: cold drawn, soft; N: normalized; SR: cold drawn and stress relieved
EN 10305-2:2002	A: annealed; C: cold drawn, hard; LC: cold drawn, soft; N: normalized; SR: cold drawn and stress relieved
EN 10305-3:2002	A: annealed; N: normalized; CR1: welded and cold sized, suitable for final annealing; CR2: welded and cold sized, not intended for heat treatment after welding and resizing
EN 10305-4:2003	N: normalized
EN 10305-5:2003	A: annealed; N: normalized; CR1: welded and cold sized, suitable for final annealing; CR2: welded and cold sized, not intended for heat treatment after welding and resizing
ISO 2937:1974	HF: hot finished
ISO 3304:1985	BK: cold-finished, as drawn; BKW: lightly cold-worked condition; GBK and GZF (A): annealed; NBK and NZF (N): normalized
ISO 3305:1985	BK: cold-finished, as drawn; BKW: lightly cold-worked condition; GBK and GZF (A): annealed; NBK and NZF (N): normalized
ISO 3306:1985	KM: as-welded and sized; GKM and GZF (A): annealed; NKM and NZF (N): normalized
JIS G 3441:1988	AM: as manufactured; CF: cold finished; A: annealed
JIS G 3444:1994	AM: as manufactured
JIS G 3445:1988	AM: as manufactured; CF: cold formed; AHT: appropriate heat treatment
JIS G 3446:1994	ST: solution treatment; AM: as manufactured; A: annealed
JIS G 3472:1988	See standard
JIS G 3473:1988	AM: as manufactured; CF, SR: cold formed and stress relieved
JIS G 3474:1995	AM: as manufactured
SAE J526 JAN00	See standard

Heat Treatment Terms Applicable to this Chapter (Continued)

5.2 Tubes for Heat Transfer Applications

Standard	Heat Treatment Terms										
AFNOR NF A 49-217:1987	HF + CR + T: hot formed + cold rolled + tempered; HF + CR + Q (HY): hot formed + cold rolled +										
AFNOR NF A 49-217.1907	hyperquenched										
AFNOR NF A 49-247:1981	Q (HY): hyperquenched										
ASTM A 178/A 178M-02	See standard										
ASTM A 179/A 179M-90a (2001)	CD + 1200°F min: cold drawn + heat treated at 1200°F or higher										
ASTM A 192-02	HF: hot finished; CF + 1200°F min: cold finished + heat treated at 1200°F or higher										
ASTM A 209-98	See standard										
ASTM A 210/A 210M-02	HF: hot finished; cf: cold finished; SA: subcritical anneal; A: full anneal; N: normalizing										
ASTM A 213/A 213M-03a	A: annealed; IA: isothermal annealed; NT: normalized and tempered										
ASTM A 214/A 214M-96 (2001)	See standard										
ASTM A 249/A 249M-03	H + RC: heat + rapid cool; ST: solution treated; H + WQ or RC: heat + water quench or rapid cool										
ASTM A 250/A 250M-95 (2001)	A: full annealed; IA: isothermal annealed; N: normalized; NT: normalized and tempered										
ASTM A 556/A 556M-96 (2001)	CD + 1200°F min: cold drawn + heat treated to 1200°F or higher										
ASTM A 688/A 688M-03	SA: solution-annealed										
ASTM A 803/A 803M-03	SA: solution-annealed										
DIN 28180:1985	N: normalized; V (QT): quenched and tempered; see standard; SA & Q: solution annealed and quenched										
DIN 28181:1985	N: normalized; NG: normalized starting product, weld only normalized; AD: as delivered; see standard; SA & Q: solution annealed and quenched										
ISO 2604-2:1975	HF: hot finished; SCA: subcritical annealed; A: annealed; N: normalized; T: tempered; Q: quenched										
ISO 2604-3:1975	A: annealed; HR: hot-reduced; N: normalized; SCA: subcritical annealed; T: tempered; W: welded										
ISO 2604-5:1978	Q: quenched										
EN 10216-1:2002	HF: hot formed; HFCF: hot formed cold finished; AF: as formed; N: normalized; NF: normalizing formed;										
EN 10216-2:2002	I: isothermal annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered										
EN 10217-1:2002	See standard										
EN 10217-2:2002	See standard										
JIS G 3461:1988	See standard										
JIS G 3462:1988	LTA: low temperature annealing; IA: isothermal annealing; A: full annealing; N: normalizing; NT: normalizing and tempering										
JIS G 3463:1994	A: annealed; ST: solution treatment										
JIS G 3467:1988	HFS: hot finished seamless; CFS: cold finished seamless; AM: as manufactured; LTA: low temperature annealing; IA: isothermal annealing; A: full annealing; N: normalizing; NT: normalizing and tempering; ST: solution treatment;										

5.3 Tubes for Low Temperature Service

Standard	Heat Treatment Terms								
ASTM A 334/A 334M-99	N: normalized; NT: normalized and tempered; QT: quenched and tempered; NNT: double normalized and tempered								
ISO 9329-3:1997	N: normalized; QT: quenched and tempered								
ISO 9330-3:1997	N: normalizing; QT: quenching and tempering								
ISO 9330-5:2000	N: normalizing; QT: quenching and tempering								
EN 10216-4:2002	N: normalized; NT: normalized and tempered; QT: quenched and tempered								
EN 10217-4:2002	See standard								
JIS G 3464:1988	N: normalizing; NT: normalizing and tempering; NNT: double normalizing and tempering; QT: quenching an tempering								

Heat Treatment Terms Applicable to this Chapter (Continued)

5.4 Tubes and Pipes for Pressure Service

Standard	Heat Treatment Terms
ASTM A 53/A 53M-99b	AM: as manufactured; T: tempered
ASTM A 106-99	HF: hot finished; CD + 1200°F min: cold drawn + heat treated at 1200°F or higher
ASTM A 135-97c	AM: as manufactured; T: tempered
ASTM A 139-00	See standard
ASTM A 312/A 312M-00	HF: hot finished; CF: cold finished; A: annealed
ASTM A 333/A 333M-99	See standard; QT: quenched and tempered; NNT: double normalized and tempered;
ASTM A 335/A 335M-99	FA: full annealed; IA: isothermal annealed; NT: normalized and tempered
ASTM A 358/A 358M-98	H: heat at specified temperature and water quench or rapid cool; HT: a final heat treatment temperature under 1900°F; HT-O: no final heat treatment of pipe fabricated of plate that has been solution treated at temperatures required by this specification; HT-SO: No final heat treatment of pipe fabricated of plate that has not been heat treated
ASTM A 376/A 376M-98	See standard
ASTM A 409/A 409M-95a	H: heat at specified temperature and water quench or rapid cool; HT: a final heat treatment temperature under 1900°F; HT-O: no final heat treatment of pipe fabricated of plate that has been solution treated at temperatures required by this specification; HT-SO: No final heat treatment of pipe fabricated of plate that has not been heat treated
BS 1387:1985	See standard
BS 3604-2:1991	See standard
BS 3605-1: 1991	ST: solution treated; HF: hot finished
BS 3605-2: 1992	AW: as welded; ST: solution treated
DIN 1615:1984	AD: as delivered
DIN 1630:1984	AD: as delivered
DIN 17457:1985	SA & Q: solution annealed and quenched
DIN 17458:1985	SA & Q: solution annealed and quenched
DIN 17459:1992	SHT: solution heat treated; A/R: annealed for recrystallization
EN 10216-1:2002	HF: hot formed; HFCF: hot formed cold finished; AF: as formed; N: normalized; NF: normalizing formed;
EN 10216-2:2002	I: isothermal annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered; NF: normalizing formed
EN 10216-3:2002	HF: hot finished; HRCF: hot rolled and cold finished; N: normalized; NF: normalizing formed; QT: quenched and tempered
EN 10216-4:2002	N: normalized; NT: normalized and tempered; QT: quenched and tempered
JIS G 3452:1997	AM: as manufactured; CF + A: cold finished and annealed
JIS G 3454:1988	AM: as manufactured; CF + A: cold finished and annealed
JIS G 3455:1988	HFS: AM: hot-finished seamless: as manufactured; CFS: LTA or N: cold-finished seamless: low temperature annealed or normalized
JIS G 3456:1988	See standard
JIS G 3457:1988	AW: As welded; ACE: as cold expanded
JIS G 3458:1988	LTA: low temperature annealing; IA: isothermal annealing; FA: full annealing; N: normalized; NT: normalized and tempered
JIS G 3459:1997	ST: solution treatment; CF: cold finished; HF: hot finished
JIS G 3460:1988	N: normalized; NT: normalized and tempered; N1N2T: double normalized and tempered; QT: quenched and tempered
JIS G 3468:1994	AM: as manufactured
NF A 49-214:1978	L: hot finished; F: cold finished; H + RC: heat + rapid cool
NF A 49-220:1990	N: normalized; T: tempered
NF A 49-244:1993	ST: no thermal treatment; TT: with thermal treatment

164 Steel Tubes and Pipes – Heat Treatment Terms Chapter 5

Heat Treatment Terms Applicable to this Chapter (Continued)

5.5 Line Pipe Steels

Standard	Heat Treatment Terms
ASTM A 1005/A 1005M-00	See standard
ASTM A 984/A 984M-00	See standard
API 5L - 2000	See standard
CSA Z245.1 - 2000	See standard
EN 10208-1:1998	See standard
EN 10208-2:1996	See standard
ISO 3183-1:1996	See standard S/NE/CE: seamless, non-expanded or cold expanded S/NE: seamless, non-expanded S/CE: seamless, cold expanded W/EW/CW: welded, electric-welded or continuous welded W/NE/CE: welded, non-expanded or cold expanded W/NE: welded, non-expanded W/CE: welded, cold expanded
ISO 3183-2:1996	See standard

Impact Testing Notes Applicable to this Chapter

see standard for impact data: impact testing requirements are listed in the standard for multiple test temperatures.

5.1 Carbon Steel Tubes for General and Structural Applications

5.1A Mechanical Properties of Carbon Steel Tubes for General and Structural Applications

Chamdand	Out to Ole to Tour	Steel Number	LINIO	Product Form/ - r Heat Treatment	Thickness		Yield Strength, min		Tensile Strength, min			
Standard Designation	Grade, Class, Type, Symbol or Name		UNS Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
EN 10296-1:2003	E155	1.0033		Α					260		28	
EN 10305-3:2002	E155	1.0033		Α					260		28	see standard
EN 10305-2:2002	E155	1.0033		Α			130		260		28	see standard
ASTM A 513-03a*	1008		G10080	N			159	23	262	38	30	65 HRB max
ISO 3304:1985	R28			GBK & GZF					270		30	
ISO 3305:1985	R28			GBK & GZF					270		30	
ISO 3306:1985	R28			GKM & GZF					270		30	
EN 10305-2:2002	E155	1.0033		N			155		270-410		28	see standard
EN 10305-3:2002	E155	1.0033		N			155		270-410		28	see standard
EN 10296-1:2003	E155	1.0033		N			155		270		28	
LIV 10290-1.2003	E190	1.0031		CR			190		270		26 L; 24 T	
EN 10305-3:2002	E190	1.0031		CR2			190		270		26	see standard
ASTM A 512-96 (2001)*	MT 1010		G10100	SA			138	20	276	40	35	40-65 HRB
ASTM A 513-03a*	1010		G10100	N			172	25	276	40	30	65 HRB max
EN 10305-1:2002	E215	1.0212		Α			140		280		30	see standard
ISO 3304:1985	R28			NBK & NZF			155		280		28	
ISO 3305:1985	R28			NBK & NZF			155		280		28	
ISO 3306:1985	R28			NKM & NZF			155		280		28	
JIS G 3444:1994	STK290			AM					290		30	
JIS G 3445:1988	STKM 11 A			AM, CF, or AHT					290		35	
JIS G 3452:1997	SGP			see standard					290		30 L; 25 T	
EN 10305-3:2002	E155	1.0033		CR1					290		15	see standard
EN 10305-3.2002	E195	1.0034		Α					290		28	see standard
EN 10305-2:2002	E195	1.0034		Α			145		290		28	see standard
SAE J526 JAN 00			G10080 G10100				170		290		14	65 HR30T max
EN 10296-1:2003	E155	1.0033		U, NW			175		290		15	
UC C 0470-1000	STAM 290 GA			see standard	≤ 25		175		290		40	
JIS G 3472:1988	STAM 290 GB			see standard			175		290		35	
DIN 1615:1984	St 33	1.0035		AD	≤ 25		175		290-540		17 L; 15 T	
ASTM A 513-03a*	1008		G10080	AW			207	30	290	42	15	50 HRB min
EN 10305-1:2002	E215	1.0212		N			215		290-430		30	see standard
ASTM A 512-96 (2001)*	MT 1015		G10150	SA			172	25	296	43	34	40 HRB min

^{*:} See "List of Standards" at the beginning of the chapter.

5.1 Carbon Steel Tubes for General and Structural Applications

Mechanical Properties of Carbon Steel Tubes for General and Structural Applications (Continued) 5.1A

Standard Designation	Grade, Class, Type, Symbol or Name	Steel	UNS Number	Product Form/ – Heat Treatment	Thickness		Yield Strength, min		Tensile Strength, min		Florenstion	
		Number			t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
EN 10305-3:2002	E195	1.0034		N			195		300-440		28	see standard
EN 10296-1:2003	E235	1.0308		N			235		300		25	
ISO 3306:1985	R28			KM					300		10	
ASTM A 512-96 (2001)*	1015		G10150									
ASTM A 513-03a*	1015		G10150	N			207	30	310	45	30	70 HRB max
EN 10305-3:2002	E220	1.0215		CR2			220		310		23	see standard
ASTM A 513-03a*	1010		G10100	AW			221	32	310	45	15	55 HRB min
ASTM A 512-96 (2001)*	1012											
ASTM A 500-03	Α		K03000	CF, SR, A			228	33	310	45	25	
EN 10296-1:2003	E220	1.0215		CR			220		310		23 L; 21 T	
LN 10290-1.2003	E235	1.0308		Α					315		25	
EN 10305-3:2002	E235	1.0308		Α					315		25	see standard
EN 10305-1:2002	E235	1.0308		Α			158		315		25	see standard
ISO 3304:1985	R33			GBK & GZF					320		27	
ISO 3305:1985	R33			GBK & GZF					320		27	
ISO 3306:1985	R33			GKM & GZF					320		27	
ISO 3304:1985	R33			NBK & NZF			195		320		25	
ISO 3305:1985	R33			NBK & NZF			195		320		25	
ISO 3306:1985	R33			NKM & NZF			195		320		25	
EN 10296-1:2003	E195	1.0034		Α					300		28	
EN 10296-1.2003	E195	1.0034		N			195		300		28	
EN 10305-2:2002	E195	1.0034		N			195		300-440		28	see standard
EN 10305-2.2002	E235	1.0308		Α			158		315		25	see standard
ISO 2937:1974	TS 1			HF			195		320-440		25	
ISO 3306:1985	R33			KM					330		8	
EN 10305-3:2002	E195	1.0034		CR1					330		8	see standard
EN 10296-1:2003	E195	1.0034		U, NW			250		330		8	
ASTM A 519-03	1020		G10200	A			193	28	331	48	30	50 HRB
ACTM A 510 00-*	1015		G10150	AW			241	35	331	48	15	58 HRB min
ASTM A 513-03a*	1008		G10080	SD			262	38	331	48	8	65 HRB min
ISO 3304:1985	R37			GBK & GZF					340		26	
ISO 3305:1985	R37			GBK & GZF					340		26	
ISO 3306:1985	R37			GKM & GZF					340		26	
JIS G 3445:1988	STKM 12 A			AM, CF, or AHT			175		340		35	
JIS G 3472:1988	STAM 340 G			see standard			195		340		35	
EN 10305-1:2002	E235	1.0308		N			235		340-480		25	see standard
EN 10305-2:2002	E235	1.0308		N			235		340-480		25	see standard

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

5.1A Mechanical Properties of Carbon Steel Tubes for General and Structural Applications (Continued)

Oten dend	Out de Olere Tour	041		Duraturat Farmer	Thick	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	Florenskins	
Standard Designation	Grade, Class, Type, Symbol or Name	Steel Number	UNS Number	Product Form/ Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
EN 10305-3:2002	E235	1.0308		N			235		340-550		25	see standard
EN 10296-1:2003	E260	1.0220		CR			260		340		21 L; 19 T	
EN 10305-3:2002	E260	1.0220		CR2			260		340		21	see standard
ASTM A 519-03	1020		G10200	HR			221	32	345	50	25	55 HRB
	1020		G10200	N			241	35	345	50	25	75 HRB max
ASTM A 513-03a*	1021		G10210	N			241	35	345	50	25	78 HRB max
	1010		G10100	SD			276	40	345	50	8	65 HRB min
ASTM A 512-96 (2001)*	MT 1020		G10200	SA			207	30	345	50	32	50 HRB min
ISO 3304:1985	R28			BKW					350		10	
ISO 3305:1985	R28			BKW					350		10	
EN 10305-2:2002	F155	1.0033		LC			245		350		10	ana atandard
EN 10305-2:2002	E155	1.0033		SR			245		350		18	see standard
ASTM A 513-03a*	1020		G10200	AW			262	38	359	52	12	62 HRB min
ISO 2937:1974	TS 4			HF			215		360-480		24	
ISO 3304:1985	R37			NBK & NZF			215		360		24	
ISO 3305:1985	R37			NBK & NZF			215		360		24	
ISO 3306:1985	R37			NKM & NZF			215		360		24	
AFNOR NF A 49-141:1978	TS 37-a			HR or CF+T			235		360		25	
AFNOR NF A 49-250:1979	TS E 24-a			AM			235		360		23	
					≤ 16		235		360			
					16 < t ≤ 40		225		360			
EN 10297-1:2003	E235	1.0308		AR+N	40 < t ≤ 65		215		360		25 L; 23 T	
					65 < t ≤ 80		205		040			
					80 < t ≤ 100		195		340			
ASTM A 519-03	1025		G10250	Α			207	30	365	53	25	57 HRB
ISO 3304:1985	R33			BKW					370		10	
ISO 3305:1985	R33			BKW					370		10	
JIS G 3473:1988	STC 370			AM			215		370		30	
JIS G 3445:1988	STKM 13 A			AM, CF, or AHT			215		370		30	
EN 10005 0 0000	F405	4 0004		LC			259		370		10	
EN 10305-2:2002	E195	1.0034		SR			260		370		18	see standard
EN 10296-1:2003	E275K2	1.0456			≤ 16		275		370		041.00 T	40 J at -20°C
EN 10296-1:2003	E2/5K2	1.0456			>16		265		3/0		24 L; 22 T	40 J at -20°C
ASTM A 513-03a*	1021		G10210	AW			276	40	372	54	12	62 HRB min
ASTM A 519-03	1020		G10200	N			234	34	379	55	22	60 HRB
ASTM A 512-96 (2001)*	MT 1025		G10250	SA			241	35	379	55	32	55 HRB min

^{*:} See "List of Standards" at the beginning of the chapter.

NOTE: This section continued on next page

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickn	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 519-03	1025		G10250	HR			241	35	379	55	25	60 HRB
ASTWIA 519-03	1025		G10250	N			248	36	379	55	22	60 HRB
	1025		G10250	N			255	37	379	55	25	80 HRB max
ASTM A 513-03a*	1008		G10080	MD SR			310	45	379	55	12	68 HRB min
ASTWIA 515-05a	1010		G10100	MD SR			310	45	379	55	12	68 HRB min
	1015		G10150	SD			310	45	379	55	8	67 HRB min
EN 10305-1:2002	E215	1.0212		LC SR			266 280		380 380		12 16	see standard
ASTM A 513-03a*	1025		G10250	AW			276	40	386	56	12	65 HRB min
EN 10296-1:2003	E275	1.0225		Α					390		21	
EN 10305-1:2002	E255	1.0408		C					390		21	see standard
	E275	1.0225		A					390		21	000 0141.144.14
EN 10305-3:2002	E235	1.0308		CR1					390		7	see standard
EN 10305-2:2002	E275	1.0225		A			195		390		21	see standard
EN 10296-1:2003	E235	1.0308		U, NW			300		390		7	
JIS G 3472:1988	STAM 390 G			see standard			235		390		30	
JIS G 3445:1988	STKM 12 B			AM, CF, or AHT			275		390		25	
010 4 0440.1000	R28			BK					400		8	
ISO 3304:1985	R37			BKW					400		9	
100 000 11 1000	R44			GBK & GZF					400		24	
	R28			BK					400		8	
ISO 3305:1985	R37			BKW					400		9	
	R44			GBK & GZF					400		24	
ISO 3306:1985	R37			KM					400		7	
150 3306:1965	R44			GKM & GZF					400		24	
EN 10305-2:2002	E155	1.0033		С			320		400		6	see standard
JIS G 3444:1994	STK400			AM			235		400		23	
ASTM A 500-03	D			HT			250	36	400	58	23	
ASTM A 501-01			K03000	HF			250	36	400	58	23	
ASTM A 500-03	В		K03000	CF, SR, A			290	42	400	58	23	
EN 10296-1:2003	E275	1.0225		N			275		410		21	
214 10230 1.2000	2270	1.0220		14	≤ 16		275		410			
					16 < t ≤ 40		265		410			
N 10297-1:2003	E275	1.0225		AR+N	40 < t ≤ 65		255		410		22 L; 20 T	
					65 < t ≤ 80		245		000			
					80 < t ≤ 100		235		380			

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

Others desired	Owede Olese Trees	041	LINIO	Duraturat France/	Thickr	ness	Yield Strei	ngth, min	Tensile Stre	ength, min	Elemention	
Standard Designation	Grade, Class, Type, Symbol or Name	Steel Number	UNS Number	Product Form/ Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	Elongation, min, %	Other
EN 10305-2:2002	E275	1.0225		N			275		410-550		21	see standard
AFNOR NF A 49-250:1979	TS E 26-b			AM			255		410-490		23	
EN 10305-3:2002	E275	1.0225		N			275		410-550		21	see standard
EN 10296-1:2003	E320	1.0237		CR			320		410		19 L; 17 T	
EN 10305-3:2002	E320	1.0237		CR2			320		410		19	see standard
					≤ 16		275		410			
					16 < t ≤ 40		265		410			1. 40 1-4 0000
EN 10297-1:2003	E275K2	1.0456		N	40 < t ≤ 65		255		410		22 L; 20 T	L: 40 J at -20°C T: 27 J at -20°C
					65 < t ≤ 80		245		000			1: 27 J at -20 C
					80 < t ≤ 100		235		380			
ISO 2937:1974	TS 9			HF			235		410-530		22	
JIS G 3445:1988	STKM 14 A			AM, CF, or AHT			245		410		25	
ASTM A 519-03	1035		G10350	Α			228	33	414	60	25	67 HRB
	1026		G10260	N			276	40	414	60	25	85 HRB max
	1030		G10300	N			276	40	414	60	25	85 HRB max
AOTM A 540 00 *	1008		G10080	MD			345	50	414	60	5	73 HRB min
ASTM A 513-03a*	1010		G10100	MD			345	50	414	60	5	73 HRB min
	1015		G10150	MD SR			345	50	414	60	12	72 HRB min
	1020		G10200	SD			345	50	414	60	8	70 HRB min
ISO 3304:1985	R33			BK					420		6	
ISO 3305:1985	R33			BK					420		6	
EN 10305-1:2002	E235	1.0308		LC			294		420		10	see standard
EN 10305-2:2002	E195	1.0034		С			336		420		6	see standard
EN 10305-1:2002	E235	1.0308		SR			350		420		16	
ASTM A 513-03a*	1026		G10260	AW			310	45	427	62	12	68 HRB min
A31W A 313-03a	1030		G10300	AW			310	45	427	62	10	70 HRB min
ASTM A 500-03	С		K02705	CF, SR, A			317	46	427	62	21	
ASTM A 513-03a*	1021		G10210	SD			359	52	428	62	7	70 HRB min
					≤ 16		240		430		24 L; 22 T	
EN 10297-1:2003	C22E	1.1151		N	16 < t ≤ 40		210		410		25 L; 23 T	see standard
					40 < t ≤ 80		210		410		25 L; 23 T	
ISO 3306:1985	R44			KM					430		6	
ISO 3304:1985	R44			NBK & NZF			255		430		22	
ISO 3305:1985	R44			NBK & NZF			255		430		22	
ISO 3306:1985	R44			NKM & NZF			255		430		22	
EN 10305-1:2002	E215	1.0212		С			344		430		8	see standard
ASTM A 512-96 (2001)*	MT 1010		G10100	SR A			400	58	434-689	63-100	15	70-90 HRB

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

Mechanical Properties of Carbon Steel Tubes for General and Structural Applications (Continued) 5.1A

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickr	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10305-1:2002	C35E	1.1181		Α					440		22	see standard
EN 10305-3:2002	E275	1.0225		CR1					440		6	see standard
EN 10305-1:2002	E255	1.0408		С			255		440-570		21	see standard
=,,,,,,,,,				LC			308		440		10	
EN 10305-2:2002	E235	1.0308		SR			325		440		14	see standard
EN 10296-1:2003	E275	1.0225		U, NW			340		440		6	
JIS G 3445:1988	STKM 18 A			AM, CF, or AHT			275		440		25	
JIS G 3445:1988	STKM 13 B			AM, CF, or AHT			305		440		20	
JIS G 3472:1988	STAM 440 G			see standard			305		440		25	
JIS G 3473:1988	STC 440			CF, SR			305		440		10	
JIS G 3472:1988	STAM 440 H			see standard			355		440		20	
	1045		G10450	Α			241	35	448	65	20	72 HRB
ASTM A 519-03	1035		G10350	HR			276	40	448	65	20	72 HRB
	1035		G10350	N			276	40	448	65	20	72 HRB
AOTM A 540 00-+	1035		G10350	N			310	45	448	65	20	88 HRB max
ASTM A 513-03a*	1040		G10400	N			310	45	448	65	20	90 HRB max
ASTM A 519-03	1020		G10200	SR			345	50	448	65	10	72 HRB
	1015		G10150	MD			379	55	448	65	5	77 HRB min
ASTM A 513-03a*	1020		G10200	MD SR			379	55	448	65	10	75 HRB min
	1025		G10250	SD			379	55	448	65	7	72 HRB min
A CTNA A 510 00 (0001)*	MT 1030		G10300	SA			276	40	448	65	30	60 HRB min
ASTM A 512-96 (2001)*	1011		G10110	SR A			407	59	448-689	65-100	13	70-100 HRB
ASTM A 512-96 (2001)*	1110		G11100	SR A			407	59	448-689	65-100	13	70-100 HRB
ISO 3304:1985	R37			BK					450		6	
130 3304.1965	R44			BKW					450		8	
ISO 3305:1985	R37			BK					450		6	
150 5505.1905	R44			BKW					450		8	
EN 10305-3:2002	E355	1.0580		Α					450		22	see standard
EN 10305-1:2002	E355	1.0580		Α			225		450		22	see standard
EN 10305-2:2002	E355	1.0580		Α			225		450		22	see standard
					≤ 16		315		450			
					16 < t ≤ 40		305		450			l
EN 10297-1:2003	E315	1.0236		AR+N	40 < t ≤ 65		295		450		21L; 19 T	
					$65 < t \le 80$		280		420			l
					80 < t ≤ 100		270		720			

*: See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickr	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10305-3:2002	E370	1.0261		CR2			370		450		15	see standard
EN 10296-1:2003	E370	1.0261		CR			370		450		15 L; 13 T	
ASTM A 595-98 (2002)	Α		K02004	RCCM			380	55	450	65	23.0	
	1035		G10350	AW			345	50	455	66	10	75 HRB min
ASTM A 513-03a*	1524		G15240	AW			345	50	455	66	10	75 HRB min
	1040		G10400	AW			345	50	455	66	10	75 HRB min
ASTM A 512-96 (2001)*	MT 1015		G10150	SR A			414	60	455-689	66-100	14	70-100 HRB
EN 10305-1:2002	C35E	1.1181		N			280		460		21	see standard
ASTM A 512-96 (2001)*	1016		G10160	SR A			421	61	462-689	67-100	13	70-100 HRB
ASTM A 312-90 (2001)	MT 1017		G10170	SR A			427	62	462-689	67-100	13	72-100 HRB
ASTM A 519-03	1050		G10500	Α			262	38	469	68	18	74 HRB
ASTM A 513-03a*	1021		G10210	MD SR			400	58	469	68	10	75 HRB min
ASTM A 512-96 (2001)*	1018		G10180	SR A			427	62	469-689	68-100	13	73-100 HRB
AFNOR NF A 49-341:1975	TS 42-a			BKW					470		8	
JIS G 3445:1988	STKM 15 A			AM, CF, or AHT			275		470		22	
JIS G 3472:1988	STAM 470 G			see standard			325		470		22	
JIS G 3445:1988	STKM 12 C			AM, CF, or AHT			355		470		20	
JIS G 3472:1988	STAM 470 H			see standard			410		470		18	
ISO 3304:1985	R50			GBK & GZF					480		23	
ISO 3305:1985	R50			GBK & GZF					480		23	
ISO 3306:1985	R50			GKM & GZF					480		23	
EN 10305-1:2002	E235	1.0308		С			384		480		6	see standard
ASTM A 595-98 (2002)	В		K02005	RCCM			410	60	480	70	21.0	
ASTM A 519-03*	1025		G10250	SR			379	55	483	70	8	75 HRB
ASTM A 513-03a*	1026		G10260	SD			379	55	483	70	7	77 HRB
AS 1 W A 313-03a	1020		G10200	MD			414	60	483	70	5	80 HRB min
ASTM A 519-03*	1020		G10200	CW			414	60	483	70	5	75 HRB
ACTM A 512 02c*	1025		G10250	MD SR			414	60	483	70	10	77 HRB min
ASTM A 513-03a*	1030		G10300	SD			427	62	483	70	7	78 HRB min
					≤ 16		355		490			
					16 < t ≤ 40		345		490			
EN 10297-1:2003	E355	1.0580		AR+N	40 < t ≤ 65		335		490		20 L; 18 T	
					65 < t ≤ 80		315		470			
					80 < t ≤ 100		295					
EN 10296-1:2003	E355	1.0580		Α					490		22	
ISO 3304:1985	R50			NBK & NZF			285		490		21	

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

Otan dand	Outside Olesea Terre	011	11110	Duraturat France/	Thick	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	5 1	
Standard Designation	Grade, Class, Type, Symbol or Name	Steel Number	UNS Number	Product Form/ Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	Elongation, min, %	Other
ISO 3305:1985	R50			NBK & NZF			285		490		21	
ISO 3306:1985	R50			NKM & NZF			285		490		21	
JIS G 3444:1994	STK490			AM			315		490		23	
JIS G 3445:1988	STKM 18 B			AM, CF, or AHT			315		490		23	
013 G 3443.1900	STKM 19 A			AM, CF, or AHT			315		490		23	
ISO 2937:1974	TS 18			HF			285		490-610		21	
EN 10296-1:2003	E355	1.0580		N			355		490		22	
EN 10305-1:2002	E355	1.0580		N			355		490-630		22	see standard
EN 10305-2:2002	E355	1.0580		N			355		490-630		22	see standard
EN 10305-3:2002	E355	1.0580		N			355		490-630		22	see standard
EN 10305-2:2002	E235	1.0308		С			392		490		6	see standard
EN 10305-3:2002	E420	1.0575		CR2			420		490		12	see standard
ASTM A 512-96 (2001)*	MT 1020		G10200	SR A			448	65	490-896	71-130	11	75 HRB-20 HRC
ASTM A 513-03a*	1021		G10210	MD			427	62	496	72	5	80 HRB min
ASTM A 512-96 (2001)*	1025		G10250	SR A			462	67	496-896	72-130	11	78 HRB-20 HRC
					≤ 8		340		500		20 L; 18 T	
EN 10297-1:2003	C22E	1.1151		QT	$8 < t \le 20$		290		470		22 L; 20 T	
1.2000	OLLL	1.1101		Q 1	20 < t ≤ 50		270		440		22 L; 20 T	
					50 < t ≤ 80		260		420		2 L; 20	
JIS G 3444:1994	STK500			AM			355		500		15	
JIS G 3472:1988	STAM 500 G			see standard			355		500		18	
JIS G 3445:1988	STKM 14 B			AM, CF, or AHT			355		500		15	
JIS G 3472:1988	STAM 500 H			see standard			430		500		16	
EN 10305-1:2002	C45E	1.1191		Α					510		20	see standard
JIS G 3445:1988	STKM 16 A			AM, CF, or AHT			325		510		20	
EN 10305-2:2002	E275	1.0225		LC			357		510		8	see standard
LIV 10003 2.2002	LETS	1.0225		SR			375		510		12	300 Staridard
JIS G 3445:1988	STKM 13 C			AM, CF, or AHT			380		510		15	
010 G 0440.1900	STKM 18 C			AM, CF, or AHT			380		510		15	
JIS G 3473:1988	STC 510A			CF or SR			380		510		10	
010 G 0470.1800	STC 510B			SR			380		510		15	
ASTM A 519-03	1045		G10450	HR			310	45	517	75	15	80 HRB
AG TWI A 318-00	1045		G10430	N			331	48	517	75	15	80 HRB

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickr	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 513-03a*	1025		G10250	MD			448	65	517	75	5	82 HRB min
A31W A 313-03a	1026		G10260	MD SR			448	65	517	75	10	80 HRB min
ASTM A 519-03	1025		G10250	CW			448	65	517	75	5	80 HRB
A31W A 319-03	1035		G10350	SR			448	65	517	75	8	80 HRB
EN 10305-1:2002	E255	1.0408		С					520		8	see standard
	E410	1.0509		Α					520		22	occ startaara
ISO 3304:1985	R44			BK					520		5	
ISO 3305:1985	R44			BK					520		5	
ISO 3306:1985	R50			KM					520		5	
EN 10305-1:2002	E255	1.0408		SR			375		520		12	see standard
ASTM A 519-03	1050		G10500	N			345	50	538	78	12	82 HRB
EN 10305-1:2002	C35E	1.1181		LC					540		7	see standard
EN 10305-3:2002	E355	1.0580		CR1					540		5	see standard
ISO 2937:1974	C 35			HF			275		540-660		20	
EN 10305-1:2002	C45E	1.1191		N			340		540		18	see standard
JIS G 3444:1994	STK540			AM			390		540		20	
JIS G 3445:1988	STKM 20 A			AM, CF, or AHT			390		540		23	
JIS G 3473:1988	STC 540			AM			390		540		20	
JIS G 3474:1995	STKT 540			AM			390		540		20	
EN 10296-1:2003	E355	1.0580		U, NW			400		540		5	
JIS G 3472:1988	STAM 540 H			see standard			480		540		13	
ISO 3304:1985	R50			BKW					550		7	
ISO 3305:1985	R50			BKW					550		7	
					≤ 16		300		550		18 L; 16 T	
EN 10297-1:2003	C35E	1.1181		N	$16 < t \le 40$		270		520		19 L; 17 T	see standard
					$40 < t \le 80$		270		520		19 L; 17 T	
JIS G 3445:1988	STKM 17 A			AM, CF, or AHT			345		550		20	
EN 10305-1:2002	E410	1.0509		N			410		550-700		22	see standard
JIS G 3445:1988	STKM 14 C			AM, CF, or AHT			410		550		15	
513 G 5445.1966	STKM 19 C			AM, CF, or AHT			410		550		15	
ASTM A 519-03	1050		G10500	HR			345	50	552	80	10	85 HRB
ASTM A 512-96 (2001)*	1030		G10300	SR A			483	70	552-896	80-130	10	80 HRB-20 HRC
	1026		G10260	MD			483	70	552	80	5	85 HRB min
ASTM A 513-03a*	1030		G10300	MD SR			483	70	552	80	10	81 HRB min
	1035		G10350	SD			483	70	552	80	7	82 HRB min

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

04	Overde Olean Terre	041	11110	Duradical Farms	Thickr	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	F1	
Standard Designation	Grade, Class, Type, Symbol or Name	Steel Number	UNS Number	Product Form/ Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
ASTM A 519-03	1045		G10450	SR			483	70	552	80	8	85 HRB
EN 10305-2:2002	E275	1.0225		С			448		560		5	see standard
ASTM A 519-03	1050		G10500	SR			483	70	565	82	6	86 HRB
	E255	1.0408		С					580		5	
EN 10305-1:2002	E355	1.0580		LC			406		580		7	see standard
	E333	1.0560		SR			450		580		10	
JIS G 3445:1988	STKM 15 C			AM, CF, or AHT			430		580		12	
	1030		G10300	MD			517	75	586	85	5	87 HRB min
ACTNA A 510 00-*	1035		G10350	MD SR			517	75	586	85	10	85 HRB min
ASTM A 513-03a*	1040		G10400	MD SR			517	75	586	85	10	85 HRB min
	1524		G15240	MD SR			517	75	586	85	10	85 HRB min
ASTM A 519-03	1035		G10350	CW			517	75	586	85	5	88 HRB
EN 10305-1:2002	C35E	1.1181		С					590		5	see standard
EN 10305-2:2002	E355	1.0580		SR			435		590		10	see standard
JIS G 3474:1995	STKT 590			AM			440		590-740		20	
UO O 0.470 1000	STC 590A			CF or SR			490		590		10	
JIS G 3473:1988	STC 590B			SR			490		590		15	
EN 10305-2:2002	E355	1.0580		LC			513		590		6	see standard
					≤ 16		420		600			
					16 < t ≤ 40		400		560			
EN 10297-1:2003	E420J2	1.0599		N	40 < t ≤ 65		390		530		19 L; 17 T	L: 27J at -20°C T: 20 J at -20°C
					65 < t ≤ 80		370		500			1: 20 J at -20 C
					80 < t ≤ 100		360		500			
ISO 3304:1985	R50			BK					600		4	
ISO 3305:1985	R50			BK					600		4	
EN 10305-1:2002	E410	1.0509		LC					620		8	see standard
					≤ 16		340		620		14 L; 12 T	
EN 10297-1:2003	C45E	1.1181		N	16 < t ≤ 40		305		580		16 L; 14 T	see standard
					40 < t ≤ 80		305		580		16 L; 14 T	
JIS G 3445:1988	STKM 16 C			AM, CF, or AHT			460		620		12	
	1035		G10350	MD			552	80	621	90	5	90 HRB min
ASTM A 513-03a*	1040		G10400	MD			552	80	621	90	5	90 HRB min
	1524		G15240				552	80	621	90	5	90 HRB min
ASTM A 519-03	1045		G10450	CW			552	80	621	90	5	90 HRB

^{*:} See "List of Standards" at the beginning of the chapter. NOTE: This section continued on next page

Standard	Crede Class Ture	Steel	UNS	Product Form/	Thickr	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	Elemention	
Designation	Grade, Class, Type, Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
					≤ 8		430		630		17 L; 15 T	
EN 10297-1:2003	C35E	1.1181		N	8 < t ≤ 20		380		600		19 L; 17 T	
EN 10297-1.2003	C35E	1.1101		IN	20 < t ≤ 50		320		550		20 L; 18 T	
					50 < t ≤ 80		290		500		20 L; 18 T	
EN 10305-1:2002	E355	1.0580		С			512		640		4	see standard
EN 10305-2:2002	E355	1.0580		С			512		640		4	see standard
EN 10305-1:2002	26Mn5	1.1161		LC					650		7	see standard
					≤ 16		470		650			
					16 < t ≤ 40		430		600			
EN 10297-1:2003	E470	1.0536		AR	40 < t ≤ 65						17 L; 15 T	
					65 < t ≤ 80							
					80 < t ≤ 100							
JIS G 3445:1988	STKM 17 C			AM, CF, or AHT			480		650		10	
EN 10305-1:2002	C45E	1.1191		LC					670		6	see standard
					≤ 16		400		670		14 L; 12 T	
EN 10297-1:2003	38Mn6	1.1127		N	16 < t ≤ 40		380		620		15 L; 13 T	
					40 < t ≤ 80		360		570		16 L; 14 T	-
EN 10305-1:2002	E410	1.0509		SR			590		690		12	see standard
EN 10305-1:2002	26Mn5	1.1161		С					700		4	see standard
					≤ 8		490		700		14 L; 12 T	
	C45E	1.1181		QT	8 < t ≤ 45		430		650		16 L; 14 T	
	C45E	1.1161		Qi	20 < t ≤ 50		370		630		17 L; 15 T	
					50 < t ≤ 80		340		600		17 L; 15 T	-
EN 10297-1:2003					≤ 16		590		700			
					16 < t ≤ 40		540		650			
	E590K2	1.0644		QT	40 < t ≤ 65		480		570		16 L; 14 T	L: 40 J at -20°C T: 27 J at -20°C
					65 < t ≤ 80		455		500			1. 2/ J at -20 C
					80 < t ≤ 100		420		520			
EN 10305-1:2002	C45E	1.1191							720		4	ann atandard
EN 10305-1.2002	E410	1.0509		С					750		4	see standard

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	nax, Unles	s Otherwis	e Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10296-1:2003	E155	1.0033		0.11	0.70	0.35	0.045	0.045				
EN 10305-3:2002	E155	1.0033		0.11	0.70	0.35	0.025	0.025				
EN 10305-2:2002	E155	1.0033		0.11	0.70	0.05	0.025	0.025				
ASTM A 512-96 (2001)*	1008			0.10	0.50		0.040	0.045				
ASTM A 513-03a*	1008		G10080	0.10	0.50		0.035	0.035				
ISO 3304:1985	R28			0.10	0.30		0.040	0.040				
ISO 3305:1985	R28			0.13	0.60		0.050	0.050				
ISO 3306:1985	R28			0.13	0.60		0.050	0.050				
EN 10296-1:2003	E190	1.0031		0.10	0.70	0.35	0.045	0.045				
EN 10305-3:2002	E190	1.0031		0.10	0.70	0.35	0.025	0.025				
ASTM A 512-96 (2001)*	1010			0.08-0.13	0.30-0.60		0.040	0.045				
ASTM A 512-96 (2001)	MT 1010		G10100	0.05-0.15	0.30-0.60		0.04	0.045				
ASTM A 513-03a*	1010		G10100	0.08-0.13	0.30-0.60		0.035	0.035				
EN 10305-1:2002	E215	1.0212		0.10	0.70	0.05	0.025	0.025				AI 0.025 min
ASTM A 512-96 (2001)*	1012		G10120	0.10-0.15	0.30-0.60		0.040	0.045				
JIS G 3444:1994	STK290						0.050	0.050				
JIS G 3445:1988	STKM 11 A			0.12	0.60	0.35	0.040	0.040				
JIS G 3452:1997	SGP						0.040	0.040				
EN 10305-3:2002	E195	1.0034		0.15	0.70	0.35	0.025	0.025				
EN 10305-2:2002	E195	1.0034		0.15	0.70	0.35	0.025	0.025				
EN 10296-1:2003	E155	1.0033		0.11	0.70	0.35	0.045	0.045				
SAE J526 JAN 00			G10080	0.10	0.20-0.50		0.040	0.050				
GAL 3320 JAIN 00			G10100	0.08-0.13	0.30-0.60		0.040	0.050				
IIC C 2470:1000	STAM 290 GA			0.12	0.60	0.35	0.035	0.035				
JIS G 3472:1988	STAM 290 GB			0.12	0.60	0.35	0.035	0.035				
DIN 1615:1984	St 33	1.0035										
ASTM A 512-96 (2001)*	MT 1015		G10150	0.10-0.20	0.30-0.60		0.04	0.045				

^{*:} See "List of Standards" at the beginning of the chapter.

Chemical Composition of Carbon Steel Tubes for General and Structural Applications (Continued) 5.1B

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	nax, Unles	s Otherwis	e Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10296-1:2003	E235	1.0308		0.17	1.20	0.35	0.045	0.045				
ISO 3306:1985	R28			0.13	0.60		0.050	0.050				
ASTM A 512-96 (2001)*	1015		G10150	0.12-0.18	0.30-0.60		0.040	0.045				
ASTM A 513-03a*	1015		G10150	0.12-0.18	0.30-0.60		0.035	0.035				
EN 10305-3:2002	E220	1.0215		0.14	0.70	0.35	0.025	0.025				
ASTM A 513-03a*	1010		G10100	0.08-0.13	0.30-0.60		0.035	0.035				
ASTM A 512-96 (2001)*	1012			0.10-0.15	0.30-0.60		0.040	0.045				
ASTM A 500-03	Α		K03000	0.26	1.35		0.035	0.035				Cu 0.20 min
EN 10296-1:2003	E220	1.0215		0.14	0.70	0.35	0.045	0.045				
EN 10305-3:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
EN 10305-1:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
ISO 3304:1985	R33			0.16	0.70		0.050	0.050				
ISO 3305:1985	R33			0.16	0.70		0.050	0.050				
ISO 3306:1985	R33			0.16	0.70		0.050	0.050				
EN 10305-2:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
ISO 2937:1974	TS 1			0.16	0.30-0.70		0.050	0.050				
ASTM A 519-03	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
ASTM A 513-03a*	1015		G10150	0.12-0.18	0.30-0.60		0.035	0.035				
ASTM A 515-05a	1008		G10080	0.10	0.50		0.035	0.035				
ISO 3304:1985	R37			0.17	0.8	0.35	0.050	0.050				
ISO 3305:1985	R37			0.17	0.8	0.35	0.050	0.050				
ISO 3306:1985	R37			0.17	0.8	0.35	0.050	0.050				
JIS G 3445:1988	STKM 12 A			0.20	0.60	0.35	0.040	0.040				
JIS G 3472:1988	STAM 340 G			0.20	0.60	0.35	0.035	0.035				
EN 10296-1:2003	E260	1.0220		0.16	1.20	0.35	0.045	0.045				
EN 10305-3:2002	E260	1.0220		0.16	1.20	0.35	0.025	0.025				
ASTM A 513-03a*	1020		G10200	0.17-0.23	0.30-0.60		0.035	0.035				
AS TIVI A 313-038	1021		G10210	0.17-0.23	0.30-0.90		0.035	0.035				
ASTM A 512-96 (2001)*	MT 1020		G10200	0.15-0.25	0.30-0.60		0.04	0.045				
ISO 3304:1985	R28			0.10	0.30		0.040	0.040				
ISO 3305:1985	R28			0.13	0.60		0.050	0.050				
EN 10305-2:2002	E155	1.0033		0.11	0.70	0.05	0.025	0.025				
ASTM A 513-03a*	1020		G10200	0.17-0.23	0.30-0.60		0.035	0.035				
ISO 2937:1974	TS 4			0.17	0.40-0.80	0.35	0.045	0.045				

^{*:} See "List of Standards" at the beginning of the chapter.

NOTE: This section continued on next page.

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ISO 3304:1985	R37			0.17	0.8	0.35	0.050	0.050				
ISO 3305:1985	R37			0.17	0.8	0.35	0.050	0.050				
ISO 3306:1985	R37			0.17	0.8	0.35	0.050	0.050				
AFNOR NF A 49-250:1979	TS E 24-a			0.18	1.20		0.045	0.045				
EN 10297-1:2003	E235	1.0308		0.17	1.20	0.35	0.030	0.035				
ASTM A 519-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
ISO 3304:1985	R33			0.16	0.70		0.050	0.050				
ISO 3305:1985	R33			0.16	0.70		0.050	0.050				
JIS G 3473:1988	STC 370			0.25	0.30-0.90	0.35	0.040	0.040				
JIS G 3445:1988	STKM 13 A			0.25	0.30-0.90	0.35	0.040	0.040				
EN 10305-2:2002	E195	1.0034		0.15	0.70	0.35	0.025	0.025				
EN 10296-1:2003	E275K2	1.0456		0.20	0.50-1.40	0.40	0.035	0.030	0.30	0.30	0.10	Al 0.020 min; Cu 0.35; N 0.015; Nb 0.05; Ti 0.03; V 0.05
ASTM A 513-03a*	1021		G10210	0.17-0.23	0.30-0.90		0.035	0.035				
ASTM A 519-03	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
ASTM A 512-96 (2001)*	MT 1025		G10250									
ASTM A 519-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
	1025		G10250	0.22-0.28	0.30-0.60		0.035	0.035				
ASTM A 513-03a*	1008		G10080	0.10	0.50		0.035	0.035				
A31W A 313-03a	1010		G10100	0.08-0.13	0.30-0.60		0.035	0.035				
	1015		G10150	0.12-0.18	0.30-0.60		0.035	0.035				
ASTM A 512-96 (2001)*	1015		G10150	0.12-0.18	0.30-0.60		0.040	0.045				
AFNOR NF A 49-141:1978	TS 37-a (NE)			0.20	1.30		0.05	0.05				N 0.008
EN 10305-1:2002	E215	1.0212		0.10	0.70	0.05	0.025	0.025				Al 0.025 min
EN 10296-1:2003	E275	1.0225		0.21	1.40	0.35	0.045	0.045				
EN 10305-1:2002	E255	1.0408		0.21	0.40-1.10	0.35	0.025	0.025				V 0.08-0.15; Al 0.010-0.060; Nb 0.07; Ti 0.05; Nb+V 0.02
EN 10305-3:2002	E275	1.0225		0.21	1.40	0.35	0.025	0.025				
	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
EN 10305-2:2002	E275	1.0225		0.21	1.40	0.35	0.025	0.025				
EN 10296-1:2003	E235	1.0308		0.17	1.20	0.35	0.045	0.045				
JIS G 3472:1988	STAM 390 G			0.25	0.30-0.90	0.35	0.035	0.035				
JIS G 3445:1988	STKM 12 B			0.20	0.60	0.35	0.040	0.040				

5.1B Chemical Composition of Carbon Steel Tubes for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	R28			0.10	0.30		0.040	0.040				
ISO 3304:1985	R37			0.17	0.8	0.35	0.050	0.050				
	R44			0.21	1.2	0.35	0.050	0.050				
	R28			0.13	0.60		0.050	0.050				
ISO 3305:1985	R37			0.17	0.8	0.35	0.050	0.050				
	R44			0.21	1.2	0.35	0.050	0.050				
ISO 3306:1985	R37			0.17	0.8	0.35	0.050	0.050				
130 3300. 1903	R44			0.21	1.2	0.35	0.050	0.050				
EN 10305-2:2002	E155	1.0033		0.11	0.70	0.05	0.025	0.025				
JIS G 3444:1994	STK400			0.25			0.040	0.040				
ASTM A 500-03	D			0.26	1.35		0.035	0.035				Cu ≥ 0.20
ASTM A 501-01			K03000	0.26			0.035	0.035				Cu ≥ 0.20
ASTM A 500-03	В		K03000	0.26	1.35		0.035	0.035				Cu ≥ 0.20
EN 10296-1:2003	E275	1.0225		0.21	1.40	0.35	0.030	0.035				
EN 10297-1:2003	E275	1.0225		0.21	1.40	0.35	0.030	0.035				
EN 10305-2:2002	E275	1.0225		0.21	1.40	0.35	0.025	0.025				
AFNOR NF A 49-250:1979	TS E 26-b			0.20	1.30	0.40	0.045	0.045				
EN 10305-3:2002	E275	1.0225		0.21	1.40	0.35	0.025	0.025				
EN 10296-1:2003	E320	1.0237		0.20	1.40	0.35	0.045	0.045				
EN 10305-3:2002	E320	1.0237		0.20	1.40	0.35	0.025	0.025				
EN 10297-1:2003	E275K2	1.0456		0.20	0.50-1.40	0.40	0.030	0.030	0.30	0.30	0.10	Al 0.020 min; Cu 0.35; N 0.015; Nb 0.05; Ti 0.03; V 0.05
ISO 2937:1974	TS 9			0.21	0.40-1.20	0.35	0.045	0.045				
JIS G 3445:1988	STKM 14 A			0.30	0.30-1.00	0.35	0.040	0.040				
ASTM A 519-03	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
	1026		G10260	0.22-0.28	0.60-0.90		0.035	0.035				
	1030		G10300	0.27-0.34	0.60-0.90		0.035	0.035				
ASTM A 513-03a*	1008		G10080	0.10	0.50		0.035	0.035				
A31W A 313-03a	1010		G10100	0.08-0.13	0.30-0.60		0.035	0.035				
	1015		G10150	0.12-0.18	0.30-0.60		0.035	0.035				
	1020		G10200	0.17-0.23	0.30-0.60		0.035	0.035				
AFNOR NF A 49-141:1978	TS 37-a (NE)			0.20	1.30		≤ 0.05	≤ 0.05				N 0.008
ISO 3304:1985	R33			0.16	0.70		0.050	0.050				
ISO 3305:1985	R33			0.16	0.70		0.050	0.050				
EN 10305-1:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				

Note: this section continued on next page.

5.1B Chemical Composition of Carbon Steel Tubes for General and Structural Applications (Continued)

EN 10305-122002	Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless	Otherwise	Specified	
ASTM A 500-03	Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 513-03a* 1021	EN 10305-2:2002	E195	1.0034		0.15	0.70	0.35	0.025	0.025				
EN 10297-1:2003 EN 10305-1:2002 E215 1.0212	ASTM A 500-03	С		K02705	0.23	1.35		0.035	0.035				Cu ≥ 0.20
EN 10305-1:2002	ASTM A 513-03a*	1021		G10210	0.17-0.23	0.60-0.90		0.035	0.035				
ASTM A 512-96 (2001)* MT 1010 —————————————————————————————————	EN 10297-1:2003	C22E	1.1151		0.17-0.24	0.40-0.70	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
ASTM A 512-96 (2001)* 1110	EN 10305-1:2002	E215	1.0212		0.10	0.70	0.05	0.025	0.025				Al 0.025 min
EN 10305-1:2002	ACTM A 510 OC (2001)*	MT 1010		G10100	0.05-0.15	0.3060		0.04	0.045				
EN 10305-1:2002 E255 1.0408 0.21 0.40-1.10 0.35 0.025 0.025 V 0.08-0.15; Al 0.010-0.060; Nb 0.0 Ti 0.05; Nb 0.0 Ti 0.05	ASTM A 512-96 (2001)	1110		G11100	0.08-0.15	0.30-0.60		0.040	0.130				
EN 10305-122002	EN 10305-1:2002	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40		0.10	Cr+Mo+Ni 0.63
JIS G 3445:1988	EN 10305-1:2002	E255	1.0408		0.21	0.40-1.10	0.35	0.025	0.025				V 0.08-0.15; Al 0.010-0.060; Nb 0.07; Ti 0.05; Nb+V 0.02
JIS G 3445:1988	EN 10305-2:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
JIS G 3472:1988	JIS G 3445:1988	STKM 18 A			0.18	1.50	0.55	0.040	0.040				
JIS G 3473:1988	JIS G 3445:1988	STKM 13 B			0.25	0.30-0.90	0.35	0.040	0.040				
JIS G 3472:1988	JIS G 3472:1988	STAM 440 G			0.25	0.30-0.90	0.35	0.035	0.035				
ASTM A 519-03 1045	JIS G 3473:1988	STC 440			0.25	0.30-0.90	0.35	0.040	0.040				
ASTM A 519-03 1035	JIS G 3472:1988	STAM 440 H			0.25	0.30-0.90	0.35	0.035	0.035				
ASTM A 513-03a*	ASTM A 510 02	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
ASTM A 513-03a* 1040 G10400 0.36-0.44 0.60-0.90 0.040 0.050	ASTM A 519-03	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
ASTM A 519-03	ACTM A 512 020*	1035		G10350	0.31-0.38	0.60-0.90		0.035	0.035				
ASTM A 513-03a* 1025 G10250 0.22-0.28 0.30-0.60 0.035 0.035	ASTM A 515-05a	1040		G10400	0.36-0.44	0.60-0.90		0.040	0.050				
ASTM A 512-96 (2001)* MT 1030	ASTM A 519-03	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
ASTM A 512-96 (2001)* 1011 G10110	ASTM A 513-03a*	1025		G10250	0.22-0.28	0.30-0.60		0.035	0.035				
ASTM A 512-96 (2001)*	ACTNA A 540 00 (0004)*	MT 1030		G10300									
R37	ASTM A 512-96 (2001)"	1011		G10110									
R44	ASTM A 512-96 (2001)*	1110		G11100	0.08-0.15	0.30-0.60		0.040	0.130				
R44	100 0004:1005	R37			0.17	0.8	0.35	0.050	0.050				
R44	150 3304: 1965	R44			0.21	1.2	0.35	0.050	0.050				
R44 0.21 1.2 0.35 0.050 0.050 EN 10305-3:2002 E355 1.0580 0.22 1.60 0.55 0.025 EN 10305-1:2002 E355 1.0580 0.22 1.60 0.55 0.045 EN 10305-2:2002 E355 1.0580 0.22 1.60 0.55 0.025 0.025 EN 10297-1:2003 E315 1.0236 0.21 1.50 0.30 0.030 0.035	ISO 2205:1005	R37			0.17	0.8	0.35	0.050	0.050				
EN 10305-1:2002 E355 1.0580 0.22 1.60 0.55 0.045 0.045 EN 10305-2:2002 E355 1.0580 0.22 1.60 0.55 0.025 0.025 EN 10297-1:2003 E315 1.0236 0.21 1.50 0.30 0.030 0.035	150 3305: 1965	R44			0.21	1.2	0.35	0.050	0.050				
EN 10305-2:2002 E355 1.0580 0.22 1.60 0.55 0.025 0.025 EN 10297-1:2003 E315 1.0236 0.21 1.50 0.30 0.030 0.035	EN 10305-3:2002	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
EN 10297-1:2003 E315 1.0236 0.21 1.50 0.30 0.030 0.035	EN 10305-1:2002	E355	1.0580		0.22	1.60	0.55	0.045	0.045				
	EN 10305-2:2002	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
EN 1000F 0,0000	EN 10297-1:2003	E315	1.0236		0.21	1.50	0.30	0.030	0.035				
EN 10305-3:2002 E370 1.0261 0.21 1.60 0.55 0.025 0.025	EN 10305-3:2002	E370	1.0261		0.21	1.60	0.55	0.025	0.025				

^{*:} See "List of Standards" at the beginning of the chapter.

Note: this section continued on next page.

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10296-1:2003	E370	1.0261		0.21	1.60	0.55	0.045	0.045				
ASTM A 595-98 (2002)	Α		K02004	0.15-0.25	0.30-0.90		0.035	0.035				
	1035		G10350	0.31-0.38	0.60-0.90		0.035	0.035				
ASTM A 513-03a*	1524		G15240	0.18-0.25	1.35-1.65		0.040	0.050				
	1040		G10400	0.36-0.44	0.60-0.90		0.040	0.050				
ASTM A 512-96 (2001)*	MT 1015		G10150	0.10-0.20	0.30-0.60		0.04	0.045				
EN 10305-1:2002	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40		0.10	Cr+Mo+Ni 0.63
A OTA A 540 00 (0004)*	1016		G10160	0.12-0.18	0.60-0.90	0.040	0.045					
ASTM A 512-96 (2001)*	MT 1017		G10170									
ASTM A 519-03	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
ASTM A 513-03a*	1021		G10210	0.17-0.23	0.30-0.90		0.035	0.035				
ASTM A 512-96 (2001)*	1018		G10180	0.14-0.20	0.60-0.90		0.040	0.045				
JIS G 3445:1988	STKM 15 A			0.25-0.35	0.30-1.00	0.35	0.040	0.040				
JIS G 3472:1988	STAM 470 G			0.25	0.30-0.90	0.35	0.035	0.035				
JIS G 3445:1988	STKM 12 C			0.20	0.60	0.35	0.040	0.040				
JIS G 3472:1988	STAM 470 H			0.25	0.30-0.90	0.35	0.035	0.035				
ISO 3304:1985	R50			0.23	1.6	0.55	0.050	0.050				
ISO 3305:1985	R50			0.23	1.6	0.55	0.050	0.050				
ISO 3306:1985	R50			0.23	1.6	0.55	0.050	0.050				
EN 10305-1:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
ASTM A 595-98 (2002)	В		K02005	0.15-0.25	0.40-1.35		0.035	0.035				
ASTM A 519-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
A OTA A 540 00-4	1026		G10260	0.22-0.28	0.60-0.90		0.035	0.035				
ASTM A 513-03a*	1020		G10200	0.17-0.23	0.30-0.60		0.035	0.035				
ASTM A 519-03	1020		G10200	0.18-0.23	0.30-0.60		0.040	0.050				
A C.T.M. A. 540, 00-*	1025		G10250	0.22-0.28	0.30-0.60		0.035	0.035				
ASTM A 513-03a*	1030		G10300	0.27-0.34	0.60-0.90		0.035	0.035				
EN 10297-1:2003	E355	1.0580		0.22	1.60	0.55	0.030	0.035				
EN 10296-1:2003	E355	1.0580		0.22	1.60	0.55	0.045	0.045				
JIS G 3444:1994	STK 490			0.18	1.50	0.55	0.040	0.040				
WO O 0445 4000	STKM 18 B			0.18	1.50	0.55	0.040	0.040				
JIS G 3445:1988	STKM 19 A			0.25	1.50	0.55	0.040	0.040				
ISO 2937:1974	TS 18			0.23	0.80-1.50	0.35	0.045	0.045				

^{*:} See "List of Standards" at the beginning of the chapter. Note: this section continued on next page.

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10305-2:2002	E235	1.0308		0.17	1.20	0.35	0.025	0.025				
EN 10305-3:2002	E420	1.0575		0.16	1.70	0.50	0.025	0.025				
ASTM A 512-96 (2001)*	MT 1020		G10200	0.15-0.25	0.30-0.60		0.04	0.045				
ASTM A 513-03a*	1021		G10210	0.17-0.23	0.30-0.90		0.035	0.035				
ASTM A 519-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
EN 10297-1:2003	C22E	1.1151		0.17-0.24	0.40-0.70	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
JIS G 3444:1994	STK500			0.24	0.30-1.30	0.35	0.040	0.040				
JIS G 3472:1988	STAM 500 G			0.30	0.30-1.00	0.35	0.035	0.035				
JIS G 3445:1988	STKM 14 B			0.30	0.30-1.00	0.35	0.040	0.040				
JIS G 3472:1988	STAM 500 H			0.30	0.30-1.00	0.35	0.035	0.035				
EN 10305-1:2002	C45E	1.1191		0.42-0.55	0.50-0.80	0.40	0.035	0.035	0.40		0.10	Cr+Mo+Ni 0.63
JIS G 3445:1988	STKM 16 A			0.35-0.45	0.40-1.00	0.40	0.040	0.040				
EN 10305-2:2002	E275	1.0225		0.21	1.40	0.35	0.025	0.025				
JIS G 3445:1988	STKM 13 C			0.25	0.30-0.90	0.35	0.040	0.040				
JIS G 3445.1966	STKM 18 C			0.18	1.50	0.55	0.040	0.040				
JIS G 3473:1988	STC 510A			0.25	0.30-0.90	0.35	0.040	0.040				
JIS G 3473.1966	STC 510B			0.18	1.50	0.55	0.040	0.040				
ASTM A 519-03	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
ASTM A 513-03a*	1025		G10250	0.22-0.28	0.30-0.60		0.035	0.035				
ASTM A 519-03	1025		G10250	0.22-0.28	0.30-0.60		0.040	0.050				
ASTM A 513-03a*	1026		G10260	0.22-0.28	0.60-0.90		0.035	0.035				
ASTM A 519-03	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
EN 10305-1:2002	E255	1.0408		0.21	0.40-1.10	0.35	0.025	0.025				V 0.08-0.15; AI 0.010-0.060; Nb 0.07; Ti 0.05; Nb+V 0.02
	E410	1.0509		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035				
ISO 3304:1985	R44			0.21	1.2	0.35	0.050	0.050				
ISO 3305:1985	R44			0.21	1.2	0.35	0.050	0.050				
ISO 3306:1985	R50			0.23	1.6	0.55	0.050	0.050				
ASTM A 519-03	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
EN 10305-1:2002	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40		0.10	Cr+Mo+Ni 0.63
EN 10305-3:2002	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
ISO 2937:1974	C 35			0.32-0.39	0.50-0.80	0.15-0.40	0.035	0.035				
JIS G 3444:1994	STK540			0.23	1.50	0.55	0.040	0.040				
JIS G 3445:1988	STKM 20 A			0.25	1.60	0.55	0.040	0.040				Nb or V 0.15
JIS G 3473:1988	STC 540			0.25	1.60	0.55	0.040	0.040				Nb or V 0.15

^{*:} See "List of Standards" at the beginning of the chapter.

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 3474:1995	STKT 540			0.23	1.50	0.55	0.040	0.040				
EN 10296-1:2003	E355	1.0580		0.22	1.60	0.55	0.045	0.045				
JIS G 3472:1988	STAM 540 H			0.30	0.30-1.00	0.35	0.035	0.035				
ISO 3304:1985	R50			0.23	1.6	0.55	0.050	0.050				
ISO 3305:1985	R50			0.23	1.6	0.55	0.050	0.050				
EN 10297-1:2003	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
JIS G 3445:1988	STKM 17 A			0.45-0.55	0.40-1.00	0.40	0.040	0.040				
EN 10305-1:2002	E410	1.0509		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035				
JIS G 3445:1988	STKM 14 C			0.30	0.30-1.00	0.35	0.040	0.040				
JIS G 3445.1966	STKM 19 C			0.25	1.50	0.55	0.040	0.040				
ASTM A 519-03	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
ASTM A 513-03a*	1026		G10260	0.22-0.28	0.60-0.90		0.035	0.035				
ASTM A 512-96 (2001)*	1030		G10300	0.27-0.34	0.60-0.90		0.040	0.045				
ASTM A 513-03a*	1030		G10300	0.27-0.34	0.60-0.90		0.035	0.035				
ASTIVI A 513-03a	1035		G10350	0.31-0.38	0.60-0.90		0.035	0.035				
ASTM A 519-03	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
EN 10305-2:2002	E275	1.0225		0.21	1.40	0.35	0.025	0.025				
ASTM A 519-03	1050		G10500	0.48-0.55	0.60-0.90		0.040	0.050				
EN 10305-1:2002	E255	1.0408		0.21	0.40-1.10	0.35	0.025	0.025				V 0.08-0.15; AI 0.010-0.060; Nb 0.07; Ti 0.05; Nb+V 0.02
	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
JIS G 3445:1988	STKM 15 C			0.25-0.35	0.30-1.00	0.35	0.040	0.040				
ASTM A 513-03a*	1030		G10300	0.27-0.34	0.60-0.90		0.035	0.035				
ASTIVI A 513-03a	1035		G10350	0.31-0.38	0.60-0.90		0.035	0.035				
ASTM A 519-03	1035		G10350	0.32-0.38	0.60-0.90		0.040	0.050				
ACTM A 512 020*	1040		G10400	0.36-0.44	0.60-0.90		0.040	0.050				
ASTM A 513-03a*	1524		G15240	0.18-0.25	1.35-1.65		0.040	0.050				
EN 10305-1:2002	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40		0.10	Cr+Mo+Ni 0.63
EN 10305-2:2002	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
JIS G 3474:1995	STKT 590			0.12	2.00	0.40	0.030	0.030				Nb+V ≤ 0.15
JIS G 3473:1988	STC 590A			0.25	0.30-0.90	0.35	0.040	0.040				
013 G 3473:1900	STC 590B			0.25	1.50	0.55	0.040	0.040				

^{*:} See "List of Standards" at the beginning of the chapter.

Standard	Grade, Class, Type,	Steel	UNS				W	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10297-1:2003	E420J2	1.0599		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035	0.30	0.40	0.08	Al 0.010 min; Cu 0.30; N 0.020; Nb 0.07; Ti 0.05; V 0.08-0.15; Nb+V 0.20
ISO 3304:1985	R50			0.23	1.6	0.55	0.050	0.050				
ISO 3305:1985	R50			0.23	1.6	0.55	0.050	0.050				
EN 10305-1:2002	E410	1.0509		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035				
EN 10297-1:2003	C45E			0.42-0.50	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
JIS G 3445:1988	STKM 16 C			0.35-0.45	0.40-1.00	0.40	0.040	0.040				
	1035		G10350	0.31-0.38	0.60-0.90		0.035	0.035				
ASTM A 513-03a*	1040		G10400	0.36-0.44	0.60-0.90		0.040	0.050				
	1524		G15240	0.18-0.25	1.35-1.65		0.040	0.050				
ASTM A 519-03	1045		G10450	0.43-0.50	0.60-0.90		0.040	0.050				
EN 10297-1:2003	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10305-1:2002	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
EN 10305-2:2002	E355	1.0580		0.22	1.60	0.55	0.025	0.025				
EN 10305-1:2002	26Mn5	1.1161		0.20-0.30	1.20-1.50	0.40	0.035	0.035				
EN 10297-1:2003	E470	1.0536		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035				Al 0.010 min; N 0.020; Nb 0.07; V 0.15
JIS G 3445:1988	STKM 17 C			0.45-0.55	0.40-1.00	0.40	0.040	0.040				
EN 10305-1:2002	C45E	1.1191		0.42-0.55	0.50-0.80	0.40	0.035	0.035	0.40		0.10	Cr+Mo+Ni 0.63
EN 10297-1:2003	38Mn6	1.1127		0.34-0.42	1.40-1.65	0.15-0.35	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10305-1:2002	E410	1.0509		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035				
EN 10305-1:2002	26Mn5	1.1161		0.20-0.30	1.20-1.50	0.40	0.035	0.035				
	C45E	1.1181		0.42-0.50	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni 0.63
EN 10297-1:2003	E590K2	1.0644		0.16-0.22	1.30-1.70	0.10-0.50	0.030	0.035	0.30	0.40	0.08	Al 0.010 min; Cu 0.30; N 0.02; Nb 0.07; Ti 0.05; V 0.08-0.15; Nb+V 0.20

^{*:} See "List of Standards" at the beginning of the chapter.

5.2A Chemical Composition of Alloy Steel Tubes for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS				,	Weight, %, m	ax, Unless (Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 519-03	4028		G40280	0.25-0.30	0.70-0.90	0.15-0.35	0.040	0.035-0.050			0.20-0.30	
EN 10305-1:2002	26Mo2	1.5417		0.22-0.29	1.50	0.40	0.035	0.035		0.40	0.15-0.25	
JIS G 3441:1988	SCM 418 TK			0.16-0.21	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
JIS G 3441:1988	SCM 420 TK			0.18-0.23	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
EN 10297-1:2003	25CrMo4	1.7218		0.22-0.29	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
EN 10305-1:2002	25CrMo4	1.7218		0.22-0.29	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
ASTM A 513-03a*	4130		G41300	0.28-0.33	0.40-0.60	0.15-0.35	0.035	0.040	0.80-1.10		0.15-0.25	
ASTM A 519-03	4130		G41300	0.28-0.33	0.40-0.60	0.15-0.35	0.040	0.040	0.80-1.10		0.15-0.25	
EN 10297-1:2003	30CrMo4	1.7216		0.27-0.34	0.35-0.60	0.35	0.035	0.035	0.80-1.15		0.15-0.30	
JIS G 3441:1988	SCM 430 TK			0.28-0.33	0.60-0.85	0.25-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
ASTM A 519-03	4135		G41350	0.33-0.38	0.70-0.90	0.15-0.35	0.040	0.040	0.80-1.10		0.15-0.25	
JIS G 3441:1988	SCM 435 TK			0.33-0.38	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
EN 10297-1:2003	34CrMo4	1.7220		0.30-0.37	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
ASTM A 519-03	4137		G41370	0.35-0.40	0.70-0.90	0.15-0.35	0.040	0.040	0.80-1.10		0.15-0.25	
ASTM A 513-03a*	4140		G41400	0.38-0.43	0.75-1.00	0.15-0.35	0.035	0.040	0.80-1.10		0.15-0.25	
ASTM A 519-03	4140		G41400	0.38-0.43	0.75-1.00	0.15-0.35	0.040	0.040	0.80-1.10		0.15-0.25	
JIS G 3441:1988	SCM 440 TK			0.38-0.43	0.60-0.85	0.15-0.35	0.030	0.030	0.90-1.20	0.25	0.15-0.30	Cu 0.30
EN 10297-1:2003	42CrMo4	1.7225		0.38-0.45	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
EN 10305-1:2002	42CrMo4	1.7225		0.38-0.45	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-0.30	
ASTM A 519-03	4142		G41420	0.40-0.45	0.75-1.00	0.15-0.35	0.040	0.040	0.80-1.10		0.15-0.25	

^{*:} See "List of Standards" at the beginning of the chapter.

Mechanical Properties of Alloy Steel Tubes for General and Structural Applications 5.2B

01	Outside Olesea Terre	041	11110	Product	Thic	kness	Yield Strer	ngth, min	Tensile Str	ength, min	E1	
Standard Designation	Grade, Class, Type, Symbol or Name	Steel Number	UNS Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
ASTM A 519-03	4028		G40280									
				С					720		4	
				LC					670		6	
EN 10305-1:2002	26Mo2	1.5417		SR								
				Α								
				N								
JIS G 3441:1988	SCM 418 TK			AM, CF or A								
JIS G 3441.1900	SCM 420 TK			AM, CF or A								
				Α								212 HB
					≤ 8		700		900		12 L; 10 T	
EN 10297-1:2003	25CrMo4	1.7218		QT	$8 < t \leq 20$		600		800		14 L; 12 T	see standard for
				Qı	$20 < t \leq 50$		450		700		15 L; 13 T	impact data
					$50 < t \leq 80$		400		650		16 L; 14 T	
				С					720		4	
				LC					670		6	
EN 10305-1:2002	25CrMo4	1.7218		SR								
				Α								
				N								
				AW			379	55	496	72	10	80 HRB min
ASTM A 513-03a*	4130		G41300	N			345	50	483	70	20	100 HRB max
A01W/A 310 00a	4100		G+1000	MD			586	85	655	95	5	90 HRB min
				MD SR			552	80	621	90	10	87 HRB min
				HR			483	70	621	90	20	89 HRB
ASTM A 519-03	4130		G41300	SR			586	85	724	105	10	95 HRB
A01W/A 313 00	4100		G+1000	Α			379	55	517	75	30	81 HRB
				N			414	60	621	90	20	89 HRB
					≤ 8		1050		1250		9 L; 7 T	
				QT	$8 < t \leq 20$		1050		1250		9 L; 7 T	see standard for
EN 10297-1:2003	30CrMo4	1.7216		Q i	$20 < t \leq 50$		900		1100		10 L; 8 T	impact data
					$50 < t \le 80$		800		1000		11 L; 9 T	
				Α								223 HB
JIS G 3441:1988	SCM 430 TK			AM, CF or A								

^{*:} See "List of Standards" at the beginning of the chapter.

Standard	Crade Class Turns	Steel	UNS	Product	Thic	kness	Yield Strer	ngth, min	Tensile Str	ength, min	Florenstion	
Designation Designation	Grade, Class, Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
ASTM A 519-03	4135		G41350	AM								
JIS G 3441:1988	SCM 435 TK			AM, CF or A								
					≤ 8		800		1000		11 L; 9 T	
				QT	$8 < t \leq 20$		650		900		12 L; 10 T	see standard for
EN 10297-1:2003	34CrMo4	1.7220		Qı	20 < t ≤ 50		550		800		14 L; 12 T	impact data
					50 < t ≤ 80		500		750		15 L; 13 T	
				Α								223 HB
ASTM A 519-03	4137		G41370									
				AW			485	70	621	90	10	85 HRB min
ASTM A 513-03a*	4140		G41400	N			448	65	621	90	20	105 HRB max
A3 1W A 313-03a	4140		G41400	MD			690	100	758	110	5	90 HRB min
				MD SR			655	95	724	105	10	90 HRB min
				HR			621	90	855	120	15	100 HRB
ASTM A 519-03	4140		G41400	SR			689	100	855	120	10	100 HRB
A31WI A 319-03	4140		G41400	Α			414	60	552	80	25	85 HRB
				N			621	90	855	120	20	100 HRB
JIS G 3441:1988	SCM 440 TK			AM, CF or A								
					≤ 8		900		1100		10 L; 8 T	
				QT	$8 < t \le 20$		750		1000		11 L; 9 T	see standard for
EN 10297-1:2003	42CrMo4	1.7225		Q1	20 < t ≤ 50		650		900		12 L; 10 T	impact data
					50 < t ≤ 80		550		800		13 L; 11 T	
				Α								241 HB
				С					720		4	
				LC					670		6	
EN 10305-1:2002	42CrMo4	1.7225		SR								
				Α								
				N								
ASTM A 519-03	4142		G41420									

^{*:} See "List of Standards" at the beginning of the chapter.

5.3.1A Chemical Composition of Ferritic and Martensitic Stainless Steel Tubes for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS				W	eight, %, r	max, Unless C	therwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 268/A 268M-03	TP405		S40500	0.08	1.00	1.00	0.040	0.030	11.5-14.5	0.50		Al 0.10-0.30
ASTM A 511-96	MT 405			0.08	1.00	1.00	0.040	0.030	11.5-14.5	0.50		AI 0.10-0.30
DIN 17456:1999	X6CrAl13	1.4002		0.08	1.00	1.00	0.040	0.015	12.00-14.00			AI 0.10-0.30
ASTM A 268/A 268M-03	TP410		S41000	0.15	1.00	1.00	0.040	0.030	11.5-13.5			
ASTM A 511-96	MT 410			0.15	1.00	1.00	0.040	0.030	11.5-13.5	0.50		
JIS G 3446:1994	SUS410TKA			0.15	1.00	1.00	0.040	0.030	11.50-13.50			
JIS G 3446:1994	SUS410TKC			0.15	1.00	1.00	0.040	0.030	11.50-13.50			
DIN 17456:1999	X12Cr13	1.4006		0.08-0.15	1.50	1.00	0.040	0.015	11.50-13.50	0.75		
ASTM A 268/A 268M-03	TP409		S40900	0.08	1.00	1.00	0.045	0.030	10.5-11.7	0.50		Ti 6 x C to 0.75
BS 6323-8:1982 AMD 2:1989	LW 12			0.06	0.60	0.90	0.040	0.020	11.0-13.0	0.50		N 0.025; Ti 5 x C to 0.70
BS 6323-6: 1962 AMD 2: 1969	LW 19			0.08	1.00	1.00	0.040	0.030	10.5-12.5	1.00		Ti 6 x C to 1.00
DIN 17455:1999	X2CrTi12	1.4512		0.030	1.00	1.00	0.040	0.015	10.50-12.50			Ti 6 x (C+N) to 0.65
DIN 17456:1999	X2CrTi12	1.4512		0.030	1.00	1.00	0.040	0.015	10.50-12.50			Ti 6 x (C+N) to 0.65
ASTM A 268/A 268M-03	TP430		S43000	0.12	1.00	1.00	0.040	0.030	16.0-18.0			
ASTM A 554-03	MT-430			0.12	1.00	1.00	0.040	0.030	16.0-18.0	0.50		
ASTM A 511-96	MT 430			0.12	1.00	1.00	0.040	0.030	16.0-18.0	0.50		
JIS G 3446:1994	SUS430TKA			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
JIS G 3446:1994	SUS430TKC			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
DIN 17455:1999	X6Cr17	1.4016		0.08	1.00	1.00	0.040	0.015	16.00-18.00			Al 0.10-0.30
DIN 17456:1999	X6Cr17	1.4016		0.08	1.00	1.00	0.040	0.015	16.00-18.00			
AFNOR NF A 49-647:1979	TS Z 8 C 17			0.10	1.0	1.00	0.040	0.030	16-18	0.50		
ASTM A 268/A 268M-03	TP439		S43035	0.07	1.00	1.00	0.040	0.030	17.00-19.00	0.50		Al 0.15; N 0.04; Ti 0.20 + 4 (C + N) to 1.10
DIN 17455:1999	X3CrTi17	1.4510		0.05	1.00	1.00	0.040	0.015	16.00-18.00			Ti 4 x (C+N)+0.15 to 0.80
DIN 17456:1999	X3CrTi17	1.4510		0.05	1.00	1.00	0.040	0.015	16.00-18.00			Ti 4 x (C+N)+0.15 to 0.80

Mechanical Properties of Ferritic and Martensitic Stainless Steel Tubes for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS	Product	Thicl	kness	Yield Stren	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa min	ksi min	N/mm ² or MPa min	ksi min	min, %	Other
ASTM A 268/A 268M-03	TP405		S40500	HT			205	30	415	60	20	207 HB; 95 HRB max
ASTM A 511-96	MT 405		S40500	Α			207	30	414	60	20	207 HB; 95 HRB max
DIN 17456:1999	X6CrAl13	1.4002		Α			250		400-600		20 L; 15 T	185 HB max
ASTM A 268/A 268M-03	TP410		S41000	HT			215	30	415	60	20	207 HB; 95 HRB max
ASTM A 511-96	MT 410		S41000	Α			207	30	414	60	20	207 HB; 95 HRB max
JIS G 3446:1994	SUS410TKA			Α			205		410		20	
JIS G 3446: 1994	SUS410TKC			AM			205		410		20	
DIN 17456:1999	X12Cr13	1.4006		Α			250		450-650		20 L; 15 T	200 HB max
ASTM A 268/A 268M-03	TP409		S40900	HT			470	25	380	55	20	207 HB; 95 HRB max
BS 6323-8:1982 AMD 2:1989	LW 12			KM			300		400		10	
BS 0323-6.1902 AIVID 2.1909	LW 19			KM			300		400		10	
DIN 17455:1999	X2CrTi12	1.4512		Α			190		390-560		20 L; 18 T	175 HB max
DIN 17456:1999	X2CrTi12	1.4512		Α			190		390-560		30 L; 25 T	175 HB max
ASTM A 268/A 268M-03	TP430		S43000	HT			240	35	415	60	20	190 HB; 90 HRB max
ASTM A 554-03	MT 430		S43000	Α			241	35	414	60	20	190 HB; 90 HRB max
ASTM A 511-96	MT 430		S43000	Α			241	35	414	60	20	190 HB; 90 HRB max
JIS G 3446:1994	SUS430TKA			Α			245		410		20	
JIS G 3446:1994	SUS430TKC			AM			245		410		20	
DIN 17455:1999	X6Cr17	1.4016		Α			270		450-600		20 L; 18 T	185 HB max
DIN 17456:1999	X6Cr17	1.4016		Α			270		450-600		20 L; 15 T	185 HB max
AFNOR NF A 49-647:1979	TS Z 8 C 17			AM			300		450		16	
ASTM A 268/A 268M-03	TP439		S43035	HT			205	30	415	60	20	190 HB; 90 HRB max
DIN 17455:1999	X3CrTi17	1.4510		Α			270		430-600		20 L; 18 T	185 HB max
DIN 17456:1999	X3CrTi17	1.4510		Α			270		450-600		20 L; 15 T	185 HB max

^{*:} See "List of Standards" at the beginning of the chapter.

5.3.2A Chemical Composition of Austenitic Stainless Steel Tubes for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 269-02a	TP304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
ASTM A 511-96	MT 304			0.08	2.00	1.00	0.040	0.030	18.0-20.0	8.0-11.0		
ASTM A 554-03	MT-304			0.08	2.00	1.00	0.040	0.030	18.0-20.0	8.0-11.0		
ASTM A 632-02a	TP 304		S30400	0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-11.0		
JIS G 3446:1994	SUS304TKA			0.08	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3446.1994	SUS304TKC			0.08	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		
BS 6323-8:1982 AMD 2:1989	LW 21			0.06	2.00	1.00	0.045	0.030	17.5-19.0	8.0-11.0		
65 6323-6: 1962 AMD 2: 1969	LWCF 21			0.06	2.00	1.00	0.045	0.030	17.5-19.0	8.0-11.0		
DIN 17455:1999	X5CrNi18-10	1.4301		0.07	2.00	1.00	0.045	0.015	17.00-19.50	8.00-10.50		N 0.11
DIN 17456:1999	X5CrNi18-10	1.4301		0.07	2.0	1.00	0.045	0.015	17.00-19.50	8.00-10.50		N 0.11
AFNOR NF A 49-647:1979	TS Z 6 CN 18-09			0.07	2.0	1.0	0.040	0.030	18-20	8-12		
ASTM A 269-02a	TP304L		S30403	0.035	2.00	1.00	0.045	0.030	18.0-20.0	8.0-12.0		
ASTM A 511-96	MT 304L			0.035	2.00	1.00	0.040	0.030	18.0-20.0	8.0-13.0		
ASTM A 554-03	MT-304L			0.035	2.00	1.00	0.040	0.030	18.0-20.0	8.0-13.0		
ASTM A 632-02a	TP 304L		S30403	0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-13.0		
ASTM A 778-01	TP 304L		S30403	0.030	2.00	1.00	0.045	0.030	18.0-20.0	8.0-13.0		N 0.10
BS 6323-8:1982 AMD 2:1989	LW 20			0.03	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		
B3 0323-0.1902 AMD 2.1909	LWCF 20			0.03	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		
DIN 17455:1999	X2CrNi19-11	1.4306		0.030	2.00	1.00	0.045	0.015	18.00-20.00	10.00-12.00		N 0.11
DIN 17456:1999	X2CrNi19-11	1.4306		0.030	2.0	1.00	0.045	0.015	18.00-20.00	10.00-12.00		N 0.11
AFNOR NF A 49-317:1980	TU Z 2 CN 18-10			0.030	2.00	1.00	0.040	0.030	17-20.0	9-12.00		
AFNOR NF A 49-647:1979	TS Z 2 CN 18-10			0.030	2.0	1.0	0.040	0.030	18-20	8-12		
ASTM A 269-02a	TP304LN		S30453	0.035	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		N 0.10-0.16
DIN 17455:1999	X2CrNiN18-10	1.4311		0.030	2.00	1.00	0.045	0.015	17.00-19.50	8.50-11.50		N 0.12-0.22
DIN 17456:1999	X2CrNiN18-10	1.4311		0.030	2.0	1.00	0.045	0.015	17.00-19.50	8.50-11.50		N 0.12-0.22

5.3.2A Chemical Composition of Austenitic Stainless Steel Tubes for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 269-02a	TP316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 511-96	MT 316			0.08	2.00	1.00	0.040	0.030	16.0-18.0	11.0-14.0	2.0-3.0	
ASTM A 554-03	MT-316			0.08	2.00	1.00	0.040	0.030	16.0-18.0	10.0-14.0	2.0-3.0	
ASTM A 632-02a	TP 316		S31600	0.08	2.00	0.75	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	
JIS G 3446:1994	SUS316TKA			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
515 G 5446.1994	SUS316TKC			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
BS 6323-8:1982 AMD 2:1989	LW 23			0.07	2.00	1.00	0.045	0.030	16.5-18.5	11.0-14.0	2.5-3.0	
BS 0325-6.1962 AIVID 2.1969	LWCF 23			0.07	2.00	1.00	0.045	0.030	16.5-18.5	11.0-14.0	2.5-3.0	
DIN 17455:1999	X5CrNiMo17-12-2	1.4401		0.07	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
DIN 17455.1999	X3CrNiMo17-13-3	1.4436		0.05	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
DIN 17456:1999	X5CrNiMo17-12-2	1.4401		0.07	2.0	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
DIN 17456:1999	X3CrNiMo17-13-3	1.4436		0.05	2.0	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
AFNOR NF A 49-647:1979	TS Z 6 CND 17-11			0.08	2.0	1.0	0.040	0.030	16-18	10-12.5	2-2.5	
ASTM A 269-02a	TP316L		S31603	0.035	2.00	1.00	0.045	0.030	16.0-18.0	10.0-15.0	2.00-3.00	
ASTM A 511-96	MT 316L			0.035	2.00	1.00	0.040	0.030	16.0-18.0	10.0-15.0	2.0-3.0	
ASTM A 554-03	MT-316L			0.035	2.00	1.00	0.040	0.030	16.0-18.0	10.0-15.0	2.0-3.0	
ASTM A 632-02a	TP 316L		S31603	0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-15.0	2.00-3.00	
ASTM A 778-01	TP 316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
BS 6323-8:1982 AMD 2:1989	LW 22			0.03	2.00	1.00	0.045	0.030	16.5-18.5	11.5-14.5	2.5-3.0	
BS 6323-6.1962 AIVID 2.1969	LWCF 22			0.03	2.00	1.00	0.045	0.030	16.5-18.5	11.5-14.5	2.5-3.0	
DIN 17455:1999	X2CrNiMo17-12-2	1.4404		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
DIN 17455.1999	X2CrNiMo18-14-3	1.4435		0.030	2.00	1.00	0.045	0.015	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
DIN 17456:1999	X2CrNiMo17-12-2	1.4404		0.030	2.0	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
DIN 17456:1999	X2CrNiMo18-14-3	1.4435		0.030	2.0	1.00	0.045	0.015	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
AFNOR NF A 49-317:1980	TU Z 2 CND 17-12			0.030	2.00	1.00	0.040	0.030	16-18.0	10.5-13.00	2.00-2.40	
ASTM A 269-02a	TP316LN		S31653	0.035	2.00	1.00	0.045	0.030	16.0-18.0	10.0-13.0	2.00-3.00	N 0.10-0.16
DIN 17455:1999	X2CrNiMoN17-13-3	1.4429		0.030	2.00	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22
DIN 17456:1999	X2CrNiMoN17-13-3	1.4429		0.030	2.0	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22

5.3.2A Chemical Composition of Austenitic Stainless Steel Tubes for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 269-02a	TP321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x (C+N) to 0.70
ASTM A 511-96	MT 321			0.08	2.00	1.00	0.040	0.030	17.0-20.0	9.0-13.0		Ti 5 x C to 0.60
ASTM A 554-03	MT-321			0.08	2.00	1.00	0.040	0.030	17.0-20.0	9.0-13.0		Ti 5 x C to 0.60
ASTM A 632-02a	TP 321		S32100	0.08	2.00	0.75	0.045	0.030	17.0-20.0	9.0-13.0		Ti 5 x C to 0.60
ASTM A 778-01	TP 321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.70
JIS G 3446:1994	SUS321TKA			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
BS 6323-8:1982 AMD 2:1989	LW 24			0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
B3 0323-0.1902 AMD 2.1909	LWCF 24			0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
DIN 17455:1999	X6CrNiTi18-10	1.4541		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
DIN 17456:1999	X6CrNiTi18-10	1.4541		0.08	2.0	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
ASTM A 269-02a	TP347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Cb 10 x C min to 1.10
ASTM A 511-96	MT 347			0.08	2.00	1.00	0.040	0.030	17.0-20.0	9.0-13.0		Cb+Ta 10 x C to 1.00
ASTM A 554-03	MT-347			0.08	2.00	1.00	0.040	0.030	17.0-20.0	9.0-13.0		Cb+Ta 10 x C to 1.00
ASTM A 632-02a	TP 347		S34700	0.08	2.00	0.75	0.045	0.030	17.0-20.0	9.0-13.0		Cb+Ta 10 x C to 1.0
ASTM A 778-01	TP 347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Cb+Ta 10 x C to 1.10
JIS G 3446:1994	SUS347TKA			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
DIN 17455:1999	X6CrNiNb18-10	1.4550		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
DIN 17456:1999	X6CrNiNb18-10	1.4550		0.08	2.0	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ASTM A 269-02a			S31725	0.035	2.00	1.00	0.045	0.030	18.0-20.0	13.5-17.5	4.0-5.0	N 0.20 max
DIN 17455:1999	X2CrNiMoN17-13-5	1.4439		0.030	2.00	1.00	0.045	0.015	16.50-18.50	12.40-14.50	4.00-5.00	N 0.12-0.22
DIN 17456:1999	X2CrNiMoN17-13-5	1.4439		0.030	2.0	1.00	0.045	0.015	16.50-18.50	12.50-14.50	4.00-5.00	N 0.12-0.22

3.2B Mechanical Properties of Austenitic Stainless Steel Tubes for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS	Product	Thic	kness	Yield Strer	gth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa min	ksi min	N/mm ² or MPa min	ksi min	min, %	Other
ASTM A 269-02a	TP304		S30400	HT								192 HB 200 HV or 90 HRB max
ASTM A 511-96	MT 304			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 554-03	MT-304			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 632-02a	TP 304		S30400	HT			205	30	515	75	35	
JIS G 3446:1994	SUS304TKA			ST			205		520		35	
JIS G 3446: 1994	SUS304TKC			AM			205		520		35	
BS 6323-8:1982 AMD 2:1989	LW 21			KM			450		560		25	
BS 6323-6.1962 AMD 2.1969	LWCF 21			KM			450		560		25	
DIN 17455:1999	X5CrNi18-10	1.4301		SA & Q			195		500-720		40 L; 35 T	
DIN 17456:1999	X5CrNi18-10	1.4301		SA & Q			195		500-700		40 L; 35 T	
AFNOR NF A 49-647:1979	TS Z 6 CN 18-09			AM			400		600		35	
ASTM A 269-02a	TP304L		S30403	НТ								192 HB 200 HV or 90 HRB max
ASTM A 511-96	MT 304L			А			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 554-03	MT-304L			Α			172	25	483	70	35	192 HB; 90 HRB max
ASTM A 632-02a	TP 304L		S30403	HT			170	25	485	70	35	
ASTM A 778-01	TP 304L		S30403	AM			170	25	485	70	40	
BS 6323-8:1982 AMD 2:1989	LW 20			KM			420		520		25	
BS 6323-6.1962 AMD 2.1969	LWCF 20			KM			420		520		25	
DIN 17455:1999	X2CrNi19-11	1.4306		SA & Q			180		460-680		40 L; 35 T	
DIN 17456:1999	X2CrNi19-11	1.4306		SA & Q			180		460-680		40 L; 35 T	
AFNOR NF A 49-317:1980	TU Z 2 CN 18-10			HQ			175		470		45	
AFNOR NF A 49-647:1979	TS Z 2 CN 18-10			AM			400		600		35	
ASTM A 269-02a	TP304LN		S30453	HT								192 HB 200 HV or 90 HRB max
DIN 17455:1999	X2CrNiN18-10	1.4311		SA & Q			270		550-760		35 L; 30 T	
DIN 17456:1999	X2CrNiN18-10	1.4311		SA & Q			270		550-760		35 L; 30 T	

^{*:} See "List of Standards" at the beginning of the chapter.

5.3.2B Mechanical Properties of Austenitic Stainless Steel Tubes for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thic	kness	Yield Strer	igth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa min	ksi min	N/mm ² or MPa min	ksi min	min, %	Other
ASTM A 269-02a	TP316		S31600	HT								192 HB 200 HV or 90 HRB max
ASTM A 511-96	MT 316			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 554-03	MT-316			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 632-02a	TP 316		S31600	HT			205	30	515	75	35	
JIS G 3446:1994	SUS316TKA			ST			205		520		35	
JIS G 3446.1994	SUS316TKC			AM			205		520		35	
BS 6323-8:1982 AMD 2:1989	LW 23			KM			450		560		25	
65 6323-6:1962 AMD 2:1969	LWCF 23			KM			450		560		25	
DIN 17455:1999	X5CrNiMo17-12-2	1.4401		SA & Q			205		510-710		40 L; 35 T	
DIN 17455:1999	X3CrNiMo17-13-3	1.4436		SA & Q			205		510-710		40 L; 35 T	
DIN 17456:1999	X5CrNiMo17-12-2	1.4401		SA & Q			205		510-710		40 L; 30 T	
DIN 17456:1999	X3CrNiMo17-13-3	1.4436		SA & Q			205		510-710		40 L; 30 T	
AFNOR NF A 49-647:1979	TS Z 6 CND 17-11			AM			400		600		35	
ASTM A 269-02a	TP316L		S31603	HT								192 HB 200 HV or 90 HRB max
ASTM A 511-96	MT 316L			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 554-03	MT-316L			Α			172	25	483	70	35	192 HB; 90 HRB max
ASTM A 632-02a	TP 316L		S31603	HT			170	25	485	70	35	
ASTM A 778-01	TP 316L		S31603	AM					485	70		
BS 6323-8:1982 AMD 2:1989	LW 22			KM			420		520		25	
BS 6323-8:1982 AMD 2:1989	LWCF 22			KM			420		520		25	
DIN 47455 4000	X2CrNiMo17-12-2	1.4404		SA & Q			190		490-690		40 L; 35 T	
DIN 17455:1999	X2CrNiMo18-14-3	1.4435		SA & Q			190		490-690		40 L; 35 T	
DIN 17456:1999	X2CrNiMo17-12-2	1.4404		SA & Q			190		490-690		40 L; 30 T	
17430:1999	X2CrNiMo18-14-3	1.4435		SA & Q			190		490-690		40 L; 30 T	
AFNOR NF A 49-317:1980	TU Z 2 CND 17-12			HQ			175		470		45	
ASTM A 269-02a	TP316LN		S31653	HT								192 HB 200 HV or 90 HRB max
DIN 17455:1999	X2CrNiMoN17-13-3	1.4429		SA & Q			295		580-800		35 L; 30 T	
DIN 17456:1999	X2CrNiMoN17-13-3			SA & Q			295		580-800		35 L; 30 T	

^{*:} See "List of Standards" at the beginning of the chapter.

5.3.2B Mechanical Properties of Austenitic Stainless Steel Tubes for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thicl	kness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa min	ksi min	N/mm ² or MPa min	ksi min	min, %	Other
ASTM A 269-02a	TP321		S32100	HT								192 HB 200 HV or 90 HRB max
ASTM A 511-96	MT 321			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 554-03	MT-321			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 632-02a	TP 321		S32100	HT			205	30	515	75	35	
ASTM A 778-01	TP 321		S32100	AM					515	75		
JIS G 3446:1994	SUS321TKA			ST			205		520		35	
DO 0000 0 4000 AMD 0 4000	LW 24			KM			450		560		25	
BS 6323-8:1982 AMD 2:1989	LWCF 24			KM			450		560		25	
DIN 17455:1999	X6CrNiTi18-10	1.4541		SA & Q			200		500-730		35 L; 30 T	
DIN 17456:1999	X6CrNiTi18-10	1.4541		SA & Q			200		500-730		35 L; 30 T	
DIN 17456:1999	X6CrNiTi18-10	1.4541		SA & Q (HW) see standard			180		460-680		35 L; 30 T	
ASTM A 269-02a	TP347		S34700	HT								192 HB 200 HV or 90 HRB max
ASTM A 511-96	MT 347			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 554-03	MT-347			Α			207	30	517	75	35	192 HB; 90 HRB max
ASTM A 632-02a	TP 347		S34700	HT			205	30	515	75	35	
ASTM A 778-01	TP 347		S34700	AM					515	75		
JIS G 3446:1994	SUS347TKA			ST			205		520		35	
DIN 17455:1999	X6CrNiNb18-10	1.4550		SA & Q			205		510-740		35 L; 30 T	
DIN 17456:1999	X6CrNiNb18-10	1.4550		SA & Q			205		510-740		35 L; 30 T	
ASTM A 269-02a			S31725	HT								192 HB 200 HV or 90 HRB max
DIN 17455:1999	X2CrNiMoN17-13-5	1.4439		SA & Q			285		580-800		35 L; 30 T	
DIN 17456:1999	X2CrNiMoN17-13-5	1.4439		SA & Q			285		580-800		35 L; 30 T	

^{*:} See "List of Standards" at the beginning of the chapter.

5.4 Carbon Steel Tubes and Pipes for Low-Temperature Service

5.4A Mechanical Properties of Carbon Steel Tubes and Pipes - With Impact Testing Below -20°C

o		0		Product	Thickn	ess	Yield Stren	gth, min	Tensile Str	ength, min		
Standard Designation	Grade, Class, Type, Symbol or Name	Steel Number	UNS Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
EN 10216-4:2002	P215NL	1.0451		N	≤ 10		215		360-480		25 L; 23 T	see standard for impact data
EN 10217-4:2002	P215NL	1.0451		see standard	≤ 10		215		360-480		25 L; 23 T	see standard for impact data
EN 10217-6:2002	P215NL	1.0451		see standard	≤ 10		215		360-480		25 L; 23 T	see standard for impact data
ISO 9329-3:1997	PL 21			N	≤ 13		215		360-480		24	t ≤ 10 mm
100 3023 0.1337					13 < t ≤ 25		215					L: 40 J at -40°C
ISO 9330-3:1997	PL 21			N			215		360-480		24	L: 40 J at -40°C
ISO 9330-5:2000	PL 21			N	≤ 13		215		360-480		24	≤ 10 mm
130 9330-3.2000	FLZI			IN	13 < t ≤ 25		215		300-400		24	L: 40 J at -40°C
EN 10216-4:2002	P255QL	1.0452		QT	≤ 40		255		360-490		23 L; 21 T	see standard for impact data
					≤ 13		255					1.40 Let 50°C
ISO 9329-3:1997	PL 25			QT	13 < t ≤ 25		255		360-490		21	L: 40 J at -50°C
					25 < t ≤ 40		235					L: 40 J at -40°C
ISO 9330-3:1997	PL 25			QT			255		360-490		21	L: 40 J at -50°C
					≤ 13		255					
ISO 9330-5:2000	PL 25			N	13 < t ≤ 25		255		360-490		21	L: 40 J at -50°C
					25 < t ≤ 40		235					L: 40 J at -40°C
ASTM A 333/A 333M-99	1		K03008	see standard			205	30	380	55	≥ 8mm (⁵ / ₁₆ in) 35 L; 25 T	18 J at -45°C
ASTM A 334/A 334M-99	1		K03008	N, NT			205	30	380	55	t ≥ 5/16 in. (8 mm): 35	85 HRB max 163 HB max 18 J at -45°C
JIS G 3460:1988	STPL 380			N or NT			205		380		35	21 J at -45°C
					O.D. < 10						27	
JIS G 3464:1988	STBL 380			N or NT	10 ≤ O.D. < 20		205		380		30	21 J at -45°C
					O.D. ≥ 20						35	
					≤ 12		275		000 500			
					12 < t ≤ 20		275		390-530			
				LIE N	20 < t ≤ 40		275					
EN 10216-3:2002	P275NL2	1.1104		HF+N or HRCF+N	40 < t ≤ 50		265		390-510		24 L; 22 T	see standard for
				HRCF+N	50 < t ≤ 65		255		1			impact data
		65 < t ≤ 80 245 360-480										
			80 < t ≤ 100		235		360-480					

5.4 Carbon Steel Tubes and Pipes for Low-Temperature Service

Mechanical Properties of Carbon Steel Tubes and Pipes - With Impact Testing Below -20°C (Continued) 5.4A

Standard	Crade Class Tyre	Steel	UNS	Product	Thick	ness	Yield Strei	ngth, min	Tensile Stre	ength, min	Elemention	
Designation	Grade, Class, Type, Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
ISO 9330-3:1997	PL 23			N			235		410-530		22	L: 27 J at -50°C
ISO 9330-5:2000	PL 23			N	≤ 13		235		410-530		22	L: 27 J at -50°C
	. = =0				13 < t ≤ 25		235					
ISO 9329-3:1997	PL 23			N	≤ 13		235		410-530		22	L: 27 J at -50°C
100 0020 0.1007	1 2 20			1,	$13 < t \le 25$		235		410 000			L. 27 0 at 30 0
EN 10216-4:2002	P265NL	1.0453		N	≤ 25		265		410-570		24 L; 22 T	see standard for impact data
EN 10217-4:2002	P265NL	1.0453		see standard	≤ 16		265		410-570		24 L; 22 T	see standard for impact data
EN 10217-6:2002	P265NL	1.0453		see standard	≤ 25		265		410-570		24 L; 22 T	see standard for impact data
ASTM A 333/A 333M-99	6		K03006	see standard			240	35	415	60	≥ 8mm (5/16 in) 30 L; 16.5 T	18 J at -45°C
ASTM A 334/A 334M-99	6		K03006	N, NT			240	35	415	60	t ≥ 5/16 in. (8 mm): 30	90 HRB max 190 HB max 18 J at -45°C
ASTM A 333/A 333M-99	3		K31918	see standard			240	35	450	65	≥ 8mm (5/16 in) 30 L; 20 T	18 J at -100°C
JIS G 3460:1988	STPL 450			N or NT			245		450		30	21 J at -100°C
ASTM A 333/A 333M-99	8		K81340	QT or NNT			515	75	690	100	≥ 8mm (5/16 in) 22 L	see standard
JIS G 3460:1988	STPL 690			N1N2T or QT			520		690		21	21 J at -196°C

5.4 Carbon Steel Tubes and Pipes for Low-Temperature Service

5.4B Chemical Composition of Carbon Steel Tubes and Pipes - With Impact Testing Below -20°C

Standard	Grade, Class, Type,	Steel	UNS				We	ight, %, ma	x, Unless C	Otherwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10216-4:2002	P215NL	1.0451		0.15	0.40-1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.01; Ti 0.040; V 0.02
EN 10217-4:2002	P215NL	1.0451		0.15	0.40-1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.010; Ti 0.03; V 0.02
EN 10217-6:2002	P215NL	1.0451		0.15	0.40-1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.010; Ti 0.03; V 0.02
ISO 9329-3:1997	PL 21			0.17	0.40-1.00	0.35	0.030	0.025				Al 0.015 min
ISO 9330-3:1997	PL 21			0.17	0.40-1.00	0.35	0.030	0.025				Al 0.015 min
ISO 9330-5:2000	PL 21			0.17	0.40-1.00	0.35	0.030	0.025				Al 0.015 min
EN 10216-4:2002	P255QL	1.0452		0.17	0.40-1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.01; Ti 0.040; V 0.02
ISO 9329-3:1997	PL 25			0.17	0.40-1.00	0.35	0.030	0.025				Al 0.015 min
ISO 9330-3:1997	PL 25			0.17	0.60-1.20	0.35	0.030	0.025				Al 0.015 min
ISO 9330-5:2000	PL 25			0.17	0.40-1.00	0.35	0.030	0.025				Al 0.015 min
ASTM A 333/A 333M-99	1		K03008	0.30	0.40-1.06		0.025	0.025				
ASTM A 334/A 334M-99	1		K03008	0.30	0.40-1.06		0.025	0.025				
JIS G 3460:1988	STBL 380			0.25	1.35	0.35	0.035	0.035				
JIS G 3464:1988	STBL 380			0.25	1.35	0.35	0.035	0.035				
EN 10216-3:2002	P275NL2	1.1104		0.16	0.50-1.50	0.40	0.025	0.015				Al 0.020 min; Cu 0.30; N 0.020; Nb 0.05; Ti 0.040; V 0.05; Nb+Ti+V 0.05; Cr+Cu+Mo 0.45
ISO 9329-3:1997	PL 23			0.19	0.60-1.20	0.35	0.030	0.025				Al 0.015 min
ISO 9330-3:1997	PL 23			0.19	0.60-1.20	0.35	0.030	0.025				Al 0.015 min
ISO 9330-5:2000	PL 23			0.19	0.60-1.20	0.35	0.030	0.025				Al 0.015 min
EN 10216-4:2002	P265NL	1.0453		0.20	0.60-1.40	0.40	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.010; Ti 0.040; V 0.02
EN 10217-4:2002	P265NL	1.0453		0.20	0.60-1.40	0.40	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.010; Ti 0.03; V 0.02
EN 10217-6:2002	P265NL	1.0453		0.20	0.60-1.40	0.40	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.010; Ti 0.030; V 0.02
ASTM A 333/A 333M-99	6		K03006	0.30	0.29-1.06	0.10 min	0.025	0.025				
ASTM A 334/A 334M-99	6		K03006	0.30	0.29-1.06	0.10 min	0.025	0.025				
ASTM A 333/A 333M-99	3		K31918	0.19	0.31-0.64	0.18-0.37	0.025	0.025		3.18-3.82		
JIS G 3460:1988	STPL 450			0.18	0.30-0.60	0.10-0.35	0.030	0.030		3.20-3.80		
ASTM A 333/A 333M-99	8		K81340	0.13	0.90	0.13-0.32	0.025	0.025		8.40-9.60		
JIS G 3460:1988	STPL 690			0.13	0.90	0.10-0.35	0.030	0.030		8.50-9.50		

5.5 Alloy Steel Tubes and Pipes for Low-Temperature Service

5.5A Chemical Composition of Alloy Steel Tubes and Pipes for Low-Temperature Service

Standard	Grade, Class, Type,	Steel	UNS				We	ight, %, ma	x, Unless O	therwise S _l	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10216-4:2002	11MnNi5-3	1.6212		0.14	0.70-1.50	0.50	0.025	0.015		0.30-0.80		Al 0.020 min; Cu 0.30; Nb 0.05; V 0.05
ISO 9329-3:1997	11 MnNi 5-3			0.14	0.70-1.50	0.50	0.030	0.025		0.30-0.80		Al 0.020 min; V 0.05; Nb 0.05
ISO 9330-3:1997	11 MnNi 5-3			0.14	0.70-1.50	0.50	0.030	0.025		0.30-0.80		Al 0.020 min; V 0.05; Nb 0.05
ISO 9330-5:2000	11 MnNi 5-3			0.14	0.70-1.50	0.50	0.030	0.025		0.30-0.80		Al 0.020 min; V 0.05; Nb 0.05
EN 10216-4:2002	13MnNi6-3	1.6217		0.16	0.85-1.70	0.50	0.025	0.015		0.30-0.85		Al 0.020 min; Cu 0.30; Nb 0.05; V 0.05
ISO 9329-3:1997	13 MnNi 6-3			0.18	0.85-1.65	0.50	0.030	0.025		0.30-0.85		Al 0.020 min; V 0.05; Nb 0.05
ISO 9330-3:1997	13 MnNi 6-3			0.18	0.85-1.65	0.50	0.030	0.025		0.30-0.80		Al 0.020 min; V 0.05; Nb 0.05
ISO 9330-5:2000	13 MnNi 6-3			0.18	0.85-1.65	0.50	0.030	0.025		0.30-0.85		Al 0.020 min; V 0.05; Nb 0.05
ASTM A 333/A 333M-99	3		K31918	0.19	0.31-0.64	0.18-0.37	0.025	0.025		3.18-3.82		
ASTM A 334/A 334M-99	3		K31918	0.19	0.31-0.64	0.18-0.37	0.025	0.025		3.18-3.82		
JIS G 3460:1988	STPL 450			0.18	0.30-0.60	0.10-0.35	0.030	0.030		3.20-3.80		
JIS G 3464:1988	STBL 450			0.18	0.30-0.60	0.10-0.35	0.030	0.030		3.20-3.80		
EN 10216-4:2002	12Ni14	1.5637		0.15	0.30-0.80	0.15-0.35	0.025	0.010		3.25-3.75		Cu 0.30; V 0.05
ISO 9329-3:1997	12 Ni 14			0.15	0.30-0.85	0.15-0.35	0.025	0.020		3.25-3.75		V 0.05
ISO 9330-3:1997	12 Ni 14			0.15	0.30-0.85	0.15-0.35	0.025	0.020		3.25-3.75		V 0.05
ISO 9330-5:2000	12 Ni 14			0.15	0.3-0.8	0.35	0.025	0.020		3.25-3.75		V 0.05
EN 10216-4:2002	X12Ni5	1.5680		0.15	0.30-0.80	0.35	0.020	0.010		4.50-5.30		Cu 0.30; V 0.05
ISO 9329-3:1997	X 12 Ni 5			0.15	0.30-0.80	0.35	0.025	0.020		4.50-5.30		V 0.05
ISO 9330-3:1997	X 12 Ni 5			0.15	0.30-0.80	0.35	0.025	0.020		4.50-5.30		V 0.05
ISO 9330-5:2000	X 12 Ni 5			0.15	0.3-0.8	0.35	0.025	0.020		4.50-5.30		V 0.05
ASTM A 333/A 333M-99	8		K81340	0.13	0.90	0.13-0.32	0.025	0.025		8.40-9.60		
ASTM A 334/A 334M-99	8		K81340	0.13	0.90	0.13-0.32	0.025	0.025		8.40-9.60		
JIS G 3460:1988	STPL 690			0.13	0.90	0.10-0.35	0.030	0.030		8.50-9.50		
JIS G 3464:1988	STBL 690			0.13	0.90	0.10-0.35	0.030	0.030		8.50-9.50		
EN 10216-4:2002	X10Ni9	1.5682		0.13	0.30-0.80	0.15-0.35	0.020	0.010		8.50-9.50	0.10	Cu 0.30; V 0.05
ISO 9329-3:1997	X 10 Ni 9			0.13	0.30-0.80	0.15-0.35	0.025	0.020		8.50-9.50	0.10	V 0.05
ISO 9330-5:2000	X 10 Ni 9			0.13	0.3-0.8	0.35	0.025	0.020		8.50-9.50	0.10	V 0.05
EN 10216-4:2002	26CrMo4-2	1.7219		0.22-0.29	0.50-0.80	0.35	0.025	0.020	0.90-1.20		0.15-0.30	Cu 0.30
ISO 9329-3:1997	26 CrMo 4			0.22-0.29	0.50-0.80	0.35	0.030	0.025	0.90-1.20		0.15-0.30	

5.5 Alloy Steel Tubes and Pipes for Low-Temperature Service

Mechanical Properties of Alloy Steel Tubes and Pipes for Low-Temperature Service 5.5B

Standard	Grade, Class, Type,	Steel	UNS	Product	Thickn	ess	Yield Stren	gth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10216-4:2002	11MnNi5-3	1.6212		N	≤ 40		285		410-530		24 L; 22 T	see standard for impact data
					≤ 13		285					
ISO 9329-3:1997	11 MnNi 5-3			N	13 < t ≤ 25		275		410-530		22	L: 40 J at -60°C
					25 < t ≤ 40		265					
ISO 9330-3:1997	11 MnNi 5-3			N	≤ 13		285		410-530		22	L: 40 J at -60°C
					≤ 13		285					
ISO 9330-5:2000	11 MnNi 5-3			N	13 < t ≤ 25		275		410-530		22	L: 40 J at -60°C
					25 < t ≤ 40		265					
EN 10216-4:2002	13MnNi6-3	1.6217		N	≤ 40		355		490-610		22 L; 20 T	see standard for impact data
					≤ 13		355					
ISO 9329-3:1997	13 MnNi 6-3			N	13 < t ≤ 25		345		490-610		20	L: 40 J at -60°C
					25 < t ≤ 40		335					
ISO 9330-3:1997	13 MnNi 6-3			N	≤ 13		355		490-610		20	L: 40 J at -60°C
					≤ 13		355					
ISO 9330-5:2000	13 MnNi 6-3			N	13 < t ≤ 25		345		490-610		20	L: 40 J at -60°C
					25 < t ≤ 40		335					
ASTM A 333/A 333M-99	3		K31918	N, NT			240	35	450	65	30	
ASTM A 334/A 334M-99	3		K31918	N, NT			240	35	450	65	t ≥ 5/16 in. (8 mm): 30	90 HRB max 190 HB max 18 J at -100°C
JIS G 3460:1988	STPL 450			N, NT			245		450		see standard	see standard for impact data
					O.D. < 10						22	
JIS G 3464:1988	STBL 450			N or NT	10 ≤ O.D. < 20		245		450		25	21 J at -100°C
					O.D. ≥ 20						30	
EN 10216-4:2002	12Ni14	1.5637		NT, QT	≤ 40		345		440-620		22 L; 20 T	see standard for impact data
					≤ 13		245					L: 40 J at -100°C
ISO 9329-3:1997	12 Ni 14			QT	13 < t ≤ 25		245		440-590		16	L. 40 J at -100°C
					25 < t ≤ 40		245					L: 40 J at -90°C
ISO 9330-3:1997	12 Ni 14			QT	≤ 13		245		440-590		16	L: 40 J at -100°C
					≤ 13		245					L: 40 J at -100°C
ISO 9330-5:2000	12 Ni 14			QT	13 < t ≤ 25		245		440-590		16	L. 40 J at -100°C
					25 < t ≤ 40		245					L: 40 J at -90°C

Mechanical Properties of Alloy Steel Tubes and Pipes for Low-Temperature Service (Continued) 5.5B

Standard	Grade, Class, Type,	Steel	UNS	Product	Thickn	ess	Yield Strer	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10216-4:2002	X12Ni5	1.5680		NT, QT	≤ 40		390		510-710		21 L; 19 T	see standard for impact data
					≤ 13		390					L: 40 J at -120°C
ISO 9329-3:1997	X 12 Ni 5			QT	13 < t ≤ 25		390		510-710		17	
					25 < t ≤ 40		380					L: 40 J at -110°C
ISO 9330-3:1997	X 12 Ni 5			QT	≤ 13		390		510-710		17	L: 40 J at -120°C
					≤ 13		390					L: 40 J at -120°C
ISO 9330-5:2000	X 12 Ni 5			QT	13 < t ≤ 25		390		510-710		17	
					25 < t ≤ 40		380					L: 40 J at -110°C
ASTM A 333/A 333M-99	8		K81340	QT			515	75	690	100	22	see standard for impact data
ASTM A 334/A 334M-99	8		K81340	QT or NNT			520	75	690	100	t ≥ 5/16 in. (8 mm): 22	18 J at -195°C
JIS G 3460:1988	STPL 690			NNT or QT			520		690		see standard	see standard for impact data
					O.D. < 10						13	
JIS G 3464:1988	STBL 690			NNT or QT	10 ≤ O.D. < 20		520		690		16	21 J at -196°C
					O.D. ≥ 20						21	
AFNOR NF A 49-215:1981	TU Z 6 N 9			NT or WQT			520		650		16	60 J at -196°C
EN 10216-4:2002	X10Ni9	1.5682		QT, N, NT	≤ 40		510		690-840		20 L; 18 T	see standard for impact data
					≤ 13		510					
ISO 9329-3:1997	X 10 Ni 9			QT	13 < t ≤ 25		510		690-840		15	L: 40 J at -196°C
					25 < t ≤ 40		510		1			
					≤ 13		510					
ISO 9330-5:2000	X 10 Ni 9			QT	13 < t ≤ 25		510		690-840		15	L: 40 J at -196°C
					25 < t ≤ 40		510		1			
EN 10216-4:2002	26CrMo4-2	1.7219		QT	≤ 40		440		560-740		18 L; 16 T	see standard for impact data
					≤ 13		440					·
ISO 9329-3:1997	26 CrMo 4			QT	13 < t ≤ 25		440		560-740		16	L: 40 J at -60°C
3 0020 0.1007					25 < t ≤ 40		420					

5.6 Carbon Steel Tubes and Pipes for Pressure Purposes

Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes 5.6A

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Stren	gth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name				t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
				HF: AF, N or NF;	≤ 16		195					
	P195TR1	1.0107		HFCF: N	$16 < t \le 40$		185		320-440		27 L; 25 T	
EN 10216-1:2002				111 01 . 14	$40 < t \le 60$		175					
LIV 10210-1.2002				HF: N or NF:	≤ 16		195					
	P195TR2	1.0108		HFCF: N	$16 < t \le 40$		185		320-440		27 L; 25 T	see standard
				111 01 . 14	$40 < t \le 60$		175					
	P195TR1	1.0107		see standard	≤ 16		195		320-440		27 L; 25 T	
EN 10217-1:2002	FIBSINI	1.0107		See Standard	$16 < t \le 40$		185		320-440		27 L, 25 I	
EN 10217-1.2002	P195TB2	1.0108		see standard	≤ 16		195		320-440		27 L; 25 T	see standard
	F1931H2	1.0100		See Standard	16 < t ≤ 40		185		320-440		27 L, 25 I	see standard
	Type E Grade A		K02504	AM			205	30	330	48	see standard	
ASTM A 53/A 53M-02	Type F Grade A			AM			205	30	330	48	see standard	
	Type S Grade A		K02504	AM			205	30	330	48	see standard	
ASTM A 139-00	Α						205	30	330	48	≥ 7.9 mm (5/16 in) 35	
ASTM A 135-01	А			AM			207	30	331	48	≥ 7.9 mm (5/16 in) 35	
					≤ 16		235					
	P235TR1	1.0254		HF: AF, N or NF; HFCF: N	16 < t ≤ 40		225		360-500		25L; 23 T	
EN 10216-1:2002				TII CI . IN	40 < t ≤ 60		215					
EN 10216-1:2002				LIE NNE	≤ 16		235					
	P235TR2	1.0255		HF: N or NF; HFCF: N	16 < t ≤ 40		225		360-500		25 L; 23 T	see standard
				пгог. іх	40 < t ≤ 60		215					
	P235TR1	1.0254		ana atandard	≤ 16		235		360-500		05 L . 00 T	
EN 10017 1,0000	P2331111	1.0254		see standard	16 < t ≤ 40		225		300-500		25 L; 23 T	
EN 10217-1:2002	10217-1:2002	1 0055			≤ 16		235		000 500		05 L 00 T	
P235TR2	P2351R2	1.0255		see standard	16 < t ≤ 40		225		360-500		25 L; 23 T	see standard
JIS G 3454:1988	STPG 370			AM or CF+A			215		370		30	

5.6 Carbon Steel Tubes and Pipes for Pressure Purposes

Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes (Continued) 5.6A

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Strer	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3457:1988	STPY 400			AW or ACE			225		400		18	
					≤ 16		265					
	P265TR1	1.0258		HF: AF, N or NF; HFCF: N	16 < t ≤ 40		255		410-570		21 L; 19 T	
EN 10216-1:2002				TH CL. IN	40 < t ≤ 60		245					
EN 10210-1.2002				LIE. N. ov NIE.	≤ 16		265					
	P265TR2	1.0259		HF: N or NF; HFCF: N	16 < t ≤ 40		255		410-570		21 L; 19 T	see standard
				111 01 . 14	$40 < t \le 60$		245					
	P265TR1	1.0258		see standard	≤ 16		265		410-570		21 L; 19 T	
EN 10217-1:2002	F2001N1	1.0236		see standard	16 < t ≤ 40		255		410-570		21 L, 19 1	
EN 10217-1.2002	P265TR2	1.0259		see standard	≤ 16		265		410-570		21 L; 19 T	see standard
	F2001N2	1.0239		see standard	$16 < t \le 40$		255		410-570		21 L, 19 1	see standard
JIS G 3454:1988	STPG 410			AM or CF+A			245		410		25	
ASTM A 135-01	В			Tempered			241	35	414	60	≥ 7.9mm (5/16 in) 30	
ACTM A FO/A FOM OO	Type E Grade B		K03005	Tempered			240	35	415	60	see standard	
ASTM A 53/A 53M-02	Type S Grade B		K03005	AM			240	35	415	60	see standard	
	В		K03003				240	35	415	60	≥ 7.9mm (5/16 in) 30	
STM A 139-00	С		K03004				290	42	415	60	≥ 7.9mm (5/16 in) 25	
	D		K03010				315	46	415	60	≥ 7.9mm (5/16 in) 23	
	E		K03012				360	52	455	66	≥ 7.9mm (5/16 in) 22	

5.6 Carbon Steel Tubes and Pipes for Pressure Purposes

Chemical Composition of Carbon Steel Tubes and Pipes for Pressure Purposes 5.6B

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, max	k, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10216-1:2002	P195TR1	1.0107		0.13	0.70	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.04; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10216-1.2002	P195TR2	1.0108		0.13	0.70	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.02 min; Cu 0.30; Nb 0.010; Ti 0.04; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10217-1:2002	P195TR1	1.0107		0.13	0.70	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.01; Ti 0.040; V 0.02; Cr+Cu+Mo+Ni 0.70
LIV 10217-1.2002	P195TR2	1.0108		0.13	0.70	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.01; Ti 0.040; V 0.02; Cr+Cu+Mo+Ni 0.70
	Type E Grade A		K02504	0.25	0.95		0.05	0.045	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.00
ASTM A 53/A 53M-02	Type F Grade A			0.30	1.20		0.05	0.045	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.00
	Type S Grade A		K02504	0.25	0.95		0.05	0.045	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.00
ASTM A 139-00	Α			0.25	1.00		0.035	0.035				
ASTM A 135-01	A			0.25	0.95		0.035	0.035				
EN 10216-1:2002	P235TR1	1.0254		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.04; V 0.02;Cr+Cu+Mo+Ni 0.70
LIV 10210-1.2002	P235TR2	1.0255		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.02 min; Cu 0.30; Nb 0.010; Ti 0.04; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10217-1:2002	P235TR1	1.0254		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.01; Ti 0.040; V 0.02; Cr+Cu+Mo+Ni 0.70
LIV 1021/-1.2002	P235TR2	1.0255		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.01; Ti 0.040; V 0.02; Cr+Cu+Mo+Ni 0.70
JIS G 3454:1988	STPG 370			0.25	0.30-0.90	0.35	0.040	0.040				

5.6 Carbon Steel Tubes and Pipes for Pressure Purposes

Chemical Composition of Carbon Steel Tubes and Pipes for Pressure Purposes (Continued) 5.6B

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, max	k, Unless O	therwise S _l	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 3457:1988	STPY 400			0.25			0.040	0.040				
EN 10216-1:2002	P265TR1	1.0258		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.04; V 0.02;Cr+Cu+Mo+Ni 0.70
LN 10210-1.2002	P265TR2	1.0259		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Al 0.02 min; Cu 0.30; Nb 0.010; Ti 0.04; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10017 1:0000	P265TR1	1.0258		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.01; Ti 0.040; V 0.02; Cr+Cu+Mo+Ni 0.70
N 10217-1:2002	P265TR2	1.0259		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; Nb 0.01; Ti 0.040; V 0.02; Cr+Cu+Mo+Ni 0.70
JIS G 3454:1988	STPG 410			0.30	0.30-1.00	0.35	0.040	0.040				
ASTM A 135-01	В			0.30	1.20		0.035	0.035				
ASTM A 53/A 53M-02	Type E Grade B		K03005	0.30	1.20		0.05	0.045	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.00
A31W A 33/A 33W-02	Type S Grade B		K03005	0.30	1.20		0.05	0.045	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.00
	В		K03003	0.26	1.00		0.035	0.035				
ACTM A 120 00	С		K03004	0.28	1.20		0.035	0.035				
STM A 139-00	D		K03010	0.30	1.30		0.035	0.035				
	E		K03012	0.30	1.40		0.035	0.035				

5.7A Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Stren	gth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 214/A 214M-96 (2001)			K01807	see standard								72 HRB max
ASTM A 556/A 556M-96 (2001)	A2		K01807				180	26	320	47	35	72 HRB max
					≤ 16		195					L: 40 J at 0°C
EN 10216-2:2002	P195GH	1.0348		N, NF	16 < t ≤ 40				320-440		27 L; 25 T	L: 28 J at -10°C
					40 < t ≤ 60							T: 27 J at 0°C
EN 10217-2:2002	P195GH	1.0348		see standard	≤ 16		195		320-440		27 L; 25 T	see standard
ISO 0604 II:1075	TS 1			HF,SCA, A, N			195		320-440		25	
O 2604-II:1975	TS 2			HF, N			195		320-440		25	
ISO 2604-III:1975	TW 1			W, HR, SCA, A, N			195		320-440		25	
130 2004-111. 1975	TW 2			N			195		320-440		25	
ASTM A 178/A 178M-02*	Α		K01200	see standard			180	26	325	47	35	
ASTM A 179/A 179M-90a (2001)*			K01200	CD+1200°F min			180	26	325	47	35	72 HRB max
ASTM A 192/A 192M-02*			K01201	HF or CF + 1200°F min			180	26	325	47	35	5.1 mm (0.200 in) 137 HB max 77 HRB max
ASTM A 106-02a	Α		K02501	HF or CD + 1200°F min			205	30	330	48	35 L; 25 T	
JIS G 3461:1988	STB 340			see standard			175		340		35	
DIN 28180:1985	TTSt 35 N	1.0356		N	≤ 10		225		340-460		25 L; 23 T	L:40 J at -40°C
DIN 28181:1985	TTSt 35 N	1.0356		N or NG	≤ 10		225		340-460		25 L; 23 T	40 J at -40°C

^{*:} See "List of Standards" at the beginning of the chapter.

Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures (Continued) 5.7A

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 16		235					L:43 J at 20°C
DIN 1630:1984	St 37.4	1.0255		AD	$16 < t \le 40$		225		350-480		25 L; 23 T	T:27 J at 20°C
					> 40		215					1.27 J at 20 C
					≤ 16		235		350-480		25 L; 23 T	
DIN 28180:1985	St 37.0	1.0254		see standard	$16 < t \le 40$		225		350-480		25 L; 23 T	
					$40 < t \le 65$		215		350-480		25 L; 23 T	
DIN 28181:1985	St 37.0	1.0254		see standard	≤ 16		235		350-480		25 L; 23 T	
DIN 26161:1965	51 37.0	1.0254		see standard	16 < t ≤ 40		225		350-480		25 L; 23 T	
	TS 4			HF,SCA, A, N			215		360-480		24	
ISO 2604-II:1975	TS 5			HF, N			215		360-480		24	
	TS 6			HF, A, N			215		360-480		24	
	TW 4			W, HR, SCA, A, N			215		360-480		24	
ISO 2604-III:1975	TW 5			N			215		360-480		24	
	TW 6			A, N			215		360-480		24	
AFNOR NF A 49-220:1990	TU 37 C			N			220		360-460			32 J at 0°C
					≤ 16		235		360-480		25 L; 23 T	T: 34 J at RT
DIN 28180:1985	St 35.8	1.0305		N	16 < t ≤ 40		225		360-480		25 L; 23 T	T: 34 J at RT
					40 < t ≤ 60		215		360-480		25 L; 23 T	T: 34 J at RT
DIN 28181:1985	St 37.8	1.0315		AD	≤ 16		235		360-480		25 L; 23 T	
DIN 28180:1985	TTSt 35 N	1.0356		V (QT)	≤ 25		255		360-490		23 L; 21 T	L:45 J at -40°C T:30 J at -40°C
DIIV 20100.1903	113t35 N	1.0330		V (Q1)	25 < t ≤ 40		235		360-490		23 L; 21 T	L:40 J at -40°C T:27 J at -40°C
					≤ 16		235					L: 40 J at 0°C
EN 10216-2:2002	P235GH	1.0345		N, NF	16 < t ≤ 40		225		360-500		25 L; 23 T	L: 28 J at -10°C
				,	40 < t ≤ 60		215					T: 27 J at 0°C
EN 10217-2:2002	P235GH	1.0345		see standard	≤ 16		235		360-500		25 L; 23 T	see standard
EN 10017 5:0000	DOOFCLI	1 0045		aga atandard	≤ 16		235		260 500		05 L . 00 T	ann atamda ad
EN 10217-5:2002	P235GH	1.0345		see standard	16 < t ≤ 40		225		360-500		25 L; 23 T	see standard
JIS G 3455:1988	STS 370			HFS: AM CFS: LTA or N			215		370		30	
JIS G 3456:1988	STPT 370			see standard			215		370		30	

Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures (Continued) 5.7A

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
AFNOR NF A 49-220:1990	TU 42 C			N			235		410-510			32 J at 0°C
	TS 9			HF, N			235		410-530		22	
ISO 2604-II:1975	TS 9H			HF, N			235		410-530		22	
	TS 10			HF, A, N			235		410-530		22	
	TW 9			W, HR, SCA, A, N			235		410-530		22	
ISO 2604-III:1975	TW 9H			N			235		410-530		22	
	TW 10			A, N			235		410-530		22	
JIS G 3455:1988	STS 410			HFS: AM CFS: LTA or N			245		410		25	
JIS G 3456:1988	STPT 410			see standard			245		410		25	
JIS G 3467:1988	STF 410			HFS: AM CFS: LTA, N			245		410		25	
JIS G 3461:1988	STB 410			see standard			255		410		25	
ASTM A 556/A 556M-96 (2001)	B2		K02707	CD+1200°F min			260	37	410	60	30	79 HRB max
					≤ 16		265					L: 40 J at 0°C
EN 10216-2:2002	P265GH	1.0425		N, NF	16 < t ≤ 40		255		410-570		23 L; 21 T	L: 28 J at -10°C
					40 < t ≤ 60		245					T: 27 J at 0°C
EN 10217-2:2002	P265GH	1.0425		see standard	≤ 16		265		410-570		23 L; 21 T	see standard
EN 10217-5:2002	P265GH	1.0425		see standard	≤ 16		265		410-570		23 L; 21 T	see standard
LN 10217-3.2002	F 203GIT	1.0423		See Standard	16 < t ≤ 40		255		410-370		23 L, 21 1	See Standard
ASTM A 106-02a	В		K03006	HF or CD + 1200°F min			240	35	415	60	30 L; 16.5 T	
ASTM A 178/A 178M-02*	С		K03503	see standard			255	37	415	60	30	
ASTM A 210/A 210M-02	A-1		K02707	HF or CF + SA, A, N			255	37	415	60	30	79 HRB max 143 HB max
					≤ 16		275					1.40 Let 0000
N 1630:1984	St 44.4	1.0257		AD	16 < t ≤ 40		265		420-550		21 L; 19 T	L:43 J at 20°C T:27 J at 20°C
					40 < t ≤ 65		255					1.21 J at 20°C

^{*:} See "List of Standards" at the beginning of the chapter.

5.7A Mechanical Properties of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
AFNOR NF A 49-220:1990	TU 48 C			N			275		470-570			40 J at 0°C
JIS G 3455:1988	STS 480			LTA or N			275		480		25	
JIS G 3456:1988	STPT 480			see standard			275		480		25	
	TS 13			HF,SCA, A, N			265		460-580		21	
ISO 2604-II:1975	TS 14			HF, N			265		460-580		21	
	TS 15			HF, A, N			265		460-580		21	
	TW 13			W, HR, SCA, A, N			265		460-580		21	
ISO 2604-III:1975	TW 14			N			265		460-580		21	
	TW 15			A, N			265		460-580		21	
ASTM A 556/A 556M-26 (2001)	C2		K03006	CD+1200°F min			280	40	480	70	30	89 HRB max
ASTM A 178/A 178M-02*	D			see standard			275	40	485	70	30	
ASTM A 210/A 210M-02	С		K03501	HF or CF + SA, A, N			275	40	485	70	30	89 HRB max 179 HB max
ISO 2604-II:1975	TS 18			HF, N			285		490-610		21	
ASTM A 106-02a	С		K03501	HF or CD + 1200°F min			275	40	485	70	30 L; 16.5 T	
					≤ 16		355					1.40 1 -+ 0000
DIN 1630:1984	St 52.4	1.0581		AD	16 < t ≤ 40		345		500-650		21 L; 19 T	L:43 J at 20°C T:27 J at 20°C
					40 < t ≤ 65		335		1			1.27 J at 20°C
JIS G 3461:1988	STB 510			N			295		510		25	
AFNOR NF A 49-220:1990	TU 52 C			N			350		510-630			40 J at 0°C

^{*:} See "List of Standards" at the beginning of the chapter.

Chemical Composition of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures 5.7B

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	x, Unless C	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 214/A 214M-96 (2001)			K01807	0.18	0.27-0.63		0.035	0.035				
ASTM A 556/A 556M-96 (2001)	A2		K01807	0.18	0.27-0.63		0.035	0.035				
EN 10216-2:2002	P195GH	1.0348		0.13	0.70	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020; Cu 0.30; Nb 0.010; Ti 0.040; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10217-2:2002	P195GH	1.0348		0.13	0.70	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.03; V 0.02; Al 0.020 min; Cr+Cu+Mo+Ni 0.70
ISO 2604-II:1975	TS 1			0.16	0.30-0.70		0.050	0.050				
150 2004-11: 1975	TS 2			0.16	0.40-0.70		0.050	0.050				
ISO 2604-III:1975	TW 1			0.16	0.30-0.70		0.050	0.050				
150 2004-111: 1975	TW 2			0.16	0.30-0.70		0.050	0.050				
ASTM A 178/A 178M-02*	Α		K01200	0.06-0.18	0.27-0.63		0.035	0.035				
ASTM A 179/A 179M-90a (2001)*			K01200	0.06-0.18	0.27-0.63		0.035	0.035				
ASTM A 192/A 192M-02*			K01201	0.06-0.18	0.27-0.63	0.25	0.035	0.035				
ASTM A 106-02a	Α		K02501	0.25	0.27-0.93	≥ 0.10	0.035	0.035	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.0
JIS G 3461:1988	STB 340			0.18	0.30-0.60	0.35	0.035	0.035				
DIN 28180:1985	TTSt 35 N	1.0356		0.17	0.40	0.35	0.030	0.025				
DIN 28181:1985	TT St 35 N	1.0356		0.17	0.40	0.35	0.030	0.025				Al 0.020 min
DIN 1630:1984	St 37.4	1.0255		0.17	≥ 0.35	0.35	0.040	0.040				N fixing elements
DIN 28180:1985	St 37.0	1.0254		0.17			0.040	0.040				N 0.009
DIN 28181:1985	St 37.0	1.0254		0.17			0.040	0.040				N 0.009
	TS 4			0.17	0.40-0.80	0.35	0.045	0.045				
ISO 2604-II:1975	TS 5			0.17	0.40-0.80	0.35	0.045	0.045				
	TS 6			0.17	0.40-1.00	0.35	0.045	0.045				AI 0.015
	TW 4			0.17	0.40-0.80	0.35	0.045	0.045				
ISO 2604-III:1975	TW 5			0.17	0.40-0.80	0.35	0.045	0.045				
	TW 6			0.17	0.40-1.00	0.35	0.045	0.045				AI 0.015
AFNOR NF A 49-220:1990	TU 37 C			0.16	0.35-0.75		0.025	0.025				
DIN 28180:1985	St 35.8	1.0305		0.17	0.40-0.80		0.040	0.040				
DIN 28181:1985	St 37.8	1.0315		0.17	0.40-0.80	0.10-0.35	0.040	0.040				
DIN 28180:1985	TTSt 35 N	1.0356		0.17	0.40	0.35	0.030	0.025				Al 0.020 min
EN 10216-2:2002	P235GH	1.0345		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Al 0.020; Cu 0.30; Nb 0.010; Ti 0.040; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10217-2:2002	P235GH	1.0345		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.03; V 0.02; Al 0.020 min; Cr+Cu+Mo+Ni 0.70
EN 10217-5:2002	P235GH	1.0345		0.16	1.20	0.35	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.03; V 0.02; Al 0.020 min; Cr+Cu+Mo+Ni 0.70
JIS G 3455:1988	STS 370			0.25	0.30-1.10	0.10-0.35	0.035	0.035				
JIS G 3456:1988	STPT 370			0.25	0.30-0.90	0.10-0.35	0.035	0.035				

^{*:} See "List of Standards" at the beginning of the chapter.

Chemical Composition of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures (Continued) 5.7B

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, ma	x, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
AFNOR NF A 49-220:1990	TU 42 C			0.20	0.45-1.00	0.08-0.35	0.025	0.025				
	TS 9			0.21	0.40-1.20	0.35	0.045	0.045				
ISO 2604-II:1975	TS 9H			0.21	0.40-1.20	0.35	0.045	0.045				
	TS 10			0.19	0.60-1.20	0.35	0.045	0.045				AI 0.015
	TW 9			0.21	0.40-1.20	0.35	0.045	0.045				
ISO 2604-III:1975	TW 9H			0.21	0.40-1.20	0.35	0.045	0.045				
	TW 10			0.19	0.60-1.20	0.35	0.045	0.045				AI 0.015
JIS G 3455:1988	STS 410			0.30	0.30-1.40	0.10-0.35	0.035	0.035				
JIS G 3456:1988	STPT 410			0.30	0.30-1.00	0.10-0.35	0.035	0.035				
JIS G 3467:1988	STF 410			0.30	0.30-1.00	0.10-0.35	0.035	0.035				
JIS G 3461:1988	STB 410			0.32	0.30-0.80	0.35	0.035	0.035				
ASTM A 556/A 556M-96 (2001)	B2		K02707	0.27	0.29-0.93	0.10	0.035	0.035				
EN 10216-2:2002	P265GH	1.0425		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Al 0.020; Cu 0.30; Nb 0.010; Ti 0.040; V 0.02;Cr+Cu+Mo+Ni 0.70
EN 10217-2:2002	P265GH	1.0425		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.03; V 0.02; Al 0.020 min; Cr+Cu+Mo+Ni 0.70
EN 10217-5:2002	P265GH	1.0425		0.20	1.40	0.40	0.025	0.020	0.30	0.30	0.08	Cu 0.30; Nb 0.010; Ti 0.03; V 0.02; Al 0.020 min; Cr+Cu+Mo+Ni 0.70
ASTM A 106-02a	В		K03006	0.30	0.29-1.06	≥ 0.10	0.035	0.035	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.0
ASTM A 178/A 178M-02*	С		K03503	0.35	0.80		0.035	0.035				
ASTM A 210/A 210M-02	A-1		K02707	0.27	0.93	0.10	0.035	0.035				
DIN 1630:1984	St 44.4	1.0257		0.20	≥ 0.40	0.35	0.040	0.040				N fixing elements

^{*:} See "List of Standards" at the beginning of the chapter.

Chemical Composition of Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures (Continued) 5.7B

Standard	Grade, Class, Type,	Steel	UNS				We	ight, %, max	x, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
AFNOR NF A 49-220:1990	TU 48 C			0.22	0.65-1.25	0.10-0.35	0.025	0.025				
JIS G 3455:1988	STS 480			0.33	0.30-1.50	0.10-0.35	0.035	0.035				
JIS G 3456:1988	STPT 480			0.33	0.30-1.00	0.10-0.35	0.035	0.035				
	TS 13			0.22	0.60-1.40	0.35	0.045	0.045				
ISO 2604-II:1975	TS 14			0.22	0.80-1.40	0.35	0.045	0.045				
	TS 15			0.20	0.80-1.40	0.35	0.045	0.045				AI 0.015
	TW 13			0.22	0.60-1.40	0.35	0.045	0.045				
ISO 2604-III:1975	TW 14			0.22	0.80-1.40	0.35	0.045	0.045				
	TW 15			0.20	0.80-1.40	0.35	0.045	0.045				AI 0.015
ASTM A 556/A 556M-96 (2001)	C2		K03006	0.30	0.29-1.06	0.10	0.035	0.035				
ASTM A 178/A 178M-02*	D			0.27	1.00-1.50	0.10 min	0.030	0.015				
ASTM A 210/A 210M-02	С		K03501	0.35	0.29-1.06	0.10	0.035	0.035				
ISO 2604-II:1975	TS 18			0.23	0.80-1.50	0.35	0.045	0.045				
ASTM A 106-02a	С		K03501	0.35	0.29-1.06	≥ 0.10	0.035	0.035	0.40	0.40	0.15	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.0
DIN 1630:1984	St 52.4	1.0581		0.22	1.60	0.55	0.040	0.035				N fixing elements
JIS G 3461:1988	STB 510			0.25	1.00-1.50	0.35	0.035	0.035				
AFNOR NF A 49-220:1990	TU 52 C			0.20	1.00-1.50	0.15-0.50	0.025	0.025				

^{*:} See "List of Standards" at the beginning of the chapter.

5.8.1A Chemical Composition of ¼Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, max	κ, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
AFNOR NF A 49-220:1990	TU 15 D 3			0.12-0.20	0.50-0.80	0.15-0.35	0.025	0.025	0.30		0.25-0.35	
DIN 28180:1985	15 Mo 3	1.5415		0.12-0.20	0.40-0.80	0.10-0.35	0.035	0.035			0.25-0.35	
EN 10216-2:2002	16Mo3	1.5415		0.12-0.20	0.40-0.90	0.35	0.025	0.020	0.30	0.30	0.25-0.35	Al 0.040; Cu 0.30
EN 10217-2:2002	16Mo3	1.5415		0.12-0.20	0.40-0.90	0.35	0.025	0.020	0.30	0.30	0.25-0.35	Cu 0.30; Al 0.040
EN 10217-5:2002	16Mo3	1.5415		0.12-0.20	0.40-0.90	0.35	0.025	0.020	0.30	0.30	0.25-0.35	Cu 0.30; Al 0.040
ISO 2604-II:1975	TS 26			0.12-0.20	0.40-0.80	0.10-0.35	0.040	0.040			0.25-0.35	Al 0.012
ISO 2604-III:1975	TW 26			0.12-0.20	0.40-0.80	0.10-0.35	0.040	0.040			0.25-0.35	Al 0.012

5.8.1B Mechanical Properties of 1/4Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Strei	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
AFNOR NF A 49-220:1990	TU 15 D 3			heat + air cool			265		430-550		22	
					≤ 16		270		450-600		22 L; 20 T	
DIN 28180:1985	15 Mo 3	1.5415		+	16 < t ≤ 40		270		450-600		22 L; 20 T	T: 34 J at RT
					40 < t ≤ 60		260		450-600		22 L; 20 T	
					≤ 16		280					1.40.1-40000
EN 10216-2:2002	16Mo3	1.5415		N, NF	16 < t ≤ 40		270		450-600		22 L; 20 T	L: 40 J at 20°C T: 27 J at 20°C
					40 < t ≤ 60		260					1. 27 3 at 20 C
EN 10217-2:2002	16Mo3	1.5415		see standard	≤ 16		280		450-600		22 L; 20 T	see standard for impact data
EN 10217-5:2002	16Mo3	1.5415		aga atandard	≤ 16		280		450-600		22 L; 20 T	see standard for
EN 10217-5.2002	TOIVIOS	1.5415		see standard 1	16 < t ≤ 40		270		450-600		22 L, 20 I	impact data
ISO 2604-II:1975	TS 26			N, NT			250		450-600		22	
ISO 2604-III:1975	TW 26			N, NT			250		450-600		22	

5.8.2A Chemical Composition of ½Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				Wei	ght, %, max	x, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	T1		K11522	0.10-0.20	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
ASTM A 209/A 209M-03	T1a		K12023	0.15-0.25	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
	T1b		K11422	0.14	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
	T1		K11522	0.10-0.20	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
ASTM A 250/A 250M-95 (2001)	T1a		K12023	0.15-0.25	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
31W A 230/A 230W 33 (2001)	T1b		K11422	0.14	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
ASTM A 335/A 335M-03	P1		K11522	0.10-0.20	0.30-0.80	0.10-0.50	0.025	0.025			0.44-0.65	
JIS G 3458:1988	STPA 12			0.10-0.20	0.30-0.80	0.10-0.50	0.035	0.035			0.45-0.65	
JIS G 3462:1988	STBA 12			0.10-0.20	0.30-0.80	0.10-0.50	0.035	0.035			0.45-0.65	
JIS G 3467:1988	STFA 12			0.10-0.20	0.30-0.80	0.10-0.50	0.035	0.035			0.45-0.65	
JIS G 3462:1988	STBA 13			0.15-0.25	0.30-0.80	0.10-0.50	0.035	0.035			0.45-0.65	
EN 10216-2:2002	8MoB5-4	1.5450		0.06-0.10	0.60-0.80	0.10-0.35	0.025	0.020	0.20		0.40-0.50	Al 0.060; Cu 0.30; Ti 0.060; B 0.002-0.006

5.8.2B Mechanical Properties of ½Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	T1		K11522	see standard	< 5.1	< 0.200	205	30	380	55	30	80 HRB max
	11		K11522	See Standard	≥ 5.1	≥ 0.200	205	30	300	55	30	146 HB max
ASTM A 209/A 209M-03	T1a		K12023	see standard	< 5.1	< 0.200	220	32	415	60	30	81 HRB max
AS TIVI A 209/A 209IVI-03	l la		K12023	See Standard	≥ 5.1	≥ 0.200	220	32	415	00	30	153 HB max
	T1b		K11422	see standard	< 5.1	< 0.200	195	28	365	53	30	77 HRB max
	110		K11422	See Standard	≥ 5.1	≥ 0.200	195	20	303	55	30	137 HB max
	T1		K11522	A, IA, N or NT			205	30	380	55	30	146 HB max 80 HRB max
ASTM A 250/A 250M-95 (2001)	T1a		K12023	A, IA, N or NT			220	32	415	60	30	153 HB max 81 HRB max
	T1b		K11422	A, IA, N or NT			195	28	365	53	30	137 HB max 77 HRB max
ASTM A 335/A 335M-03	P1		K11522	FA, IA or NT			205	30	380	55	≥ 8mm (⁵ ⁄ ₁₆ in) 30 L; 20 T	
JIS G 3458:1988	STPA 12			LTA, IA, FA, N, or NT			205		380 min		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 12			LTA, IA, A, N or NT	10 ≤ O.D. < 20		205		380		25	
					O.D. ≥ 20						30	
JIS G 3467:1988	STFA 12			LTA, IA, A, N or NT			205		380		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 13			LTA, IA, A, N or NT	10 ≤ O.D. < 20		205		410		25	
					O.D. ≥ 20						30	
					≤ 16		400					L: 40 J at 20°C
EN 10216-2:2002	8MoB5-4	1.5450		N, NF	16 < t ≤ 40				540-690		19 L; 17 T	T: 27 J at 20°C
					40 < t ≤ 60							

Chemical Composition of ½Cr-½Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, ma	x, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	T2		K11547	0.10-0.20	0.30-0.61	0.10-0.30	0.025	0.025	0.50-0.81		0.44-0.65	
ASTM A 250/A 250M-95 (2001)	T2		K11547	0.10-0.20	0.30-0.61	0.10-0.30	0.025	0.020	0.50-0.81		0.44-0.65	
ASTM A 335/A 335M-03	P2		K11547	0.10-0.20	0.30-0.61	0.10-0.30	0.025	0.025	0.50-0.81		0.44-0.65	
AFNOR NF A 49-220:1990	TU 15 CD 2-05			0.10-0.18	0.50-0.90	0.10-0.35	0.025	0.025	0.40-0.65		0.45-0.60	
JIS G 3458:1988	STPA 20			0.10-0.20	0.30-0.60	0.10-0.50	0.035	0.035	0.50-0.80		0.40-0.65	
JIS G 3462:1988	STBA 20			0.10-0.20	0.30-0.60	0.10-0.50	0.035	0.035	0.50-0.80		0.40-0.65	
ISO 2604-II:1975	TS 33			0.10-0.18	0.40-0.70	0.10-0.35	0.040	0.040	0.30-0.60		0.50-0.70	Al 0.02; V 0.22-0.32
EN 10216-2:2002	14MoV6-3	1.7715		0.10-0.15	0.40-0.70	0.15-0.35	0.025	0.020	0.30-0.60	0.30	0.50-0.70	Al 0.040; Cu 0.30; V 0.22-0.28

5.8.3B Mechanical Properties of ½Cr-½Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	T2		K11547	A, IA, NT, SA			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 250/A 250M-95 (2001)	T2		K11547	A, IA, N or NT			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 335/A 335M-03	P2		K11547	FA, IA or NT			205	30	380	55	≥ 8mm (⁵ / ₁₆ in) 30 L; 20 T	
AFNOR NF A 49-220:1990	TU 15 CD 2-05			heat + air cool + T			275		440-570		22	32 J at 0°C
JIS G 3458:1988	STPA 20			LTA, IA, FA, or NT			205		410 min		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 20			LTA, IA, A, or NT	10 ≤ O.D. < 20		205		410		25	
					O.D. ≥ 20						30	
ISO 2604-II:1975	TS 33			NT			275		460-610		15	
					≤ 16		320					1 . 40 Lat 00°C
N 10216-2:2002	14MoV6-3	1.7715		NT, NF, QT	16 < t ≤ 40		320		460-610		20 L; 18 T	L: 40 J at 20°C T: 27 J at 20°C
					40 < t ≤ 60		310					1. 27 0 at 20 0

5.8.4A Chemical Composition of 1Cr-1/2Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				Wei	ght, %, ma	x, Unless O	herwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	T12		K11562	0.05-0.15	0.30-0.61	0.50	0.025	0.025	0.80-1.25		0.44-0.65	
ASTM A 250/A 250M-95 (2001)	T12		K11562	0.05-0.15	0.30-0.61	0.50	0.030	0.020	0.80-1.25		0.44-0.65	
ASTM A 335/A 335M-03	P12		K11562	0.05-0.15	0.30-0.61	0.50	0.025	0.025	0.80-1.25		0.44-0.65	
AFNOR NF A 49-220:1990	TU 13 CD 4-04			0.10-0.18	0.40-0.70	0.10-0.35	0.025	0.025	0.70-1.10		0.45-0.65	
BS 3604-2:1991	620			0.09-0.18	0.40-0.65	0.15-0.40	0.025	0.015	0.80-1.15	0.30	0.45-0.60	Cu 0.30; Al 0.02
JIS G 3458:1988	STPA 22			0.15	0.30-0.60	0.50	0.035	0.035	0.80-1.25		0.45-0.65	
JIS G 3462:1988	STBA 22			0.15	0.30-0.60	0.50	0.035	0.035	0.80-1.25		0.45-0.65	
JIS G 3467:1988	STFA 22			0.15	0.30-0.60	0.50	0.035	0.035	0.80-1.25		0.45-0.65	
DIN 28180:1985	13 CrMo 4 4	1.7335		0.10-0.18	0.40-0.70	0.10-0.35	0.035	0.035	0.70-1.10		0.45-0.65	
EN 10216-2:2002	13CrMo4-5	1.7335		0.10-0.17	0.40-0.70	0.35	0.025	0.020	0.70-1.15	0.30	0.40-0.60	Al 0.040; Cu 0.30
ISO 2604-II:1975	TS 32			0.10-0.18	0.40-0.70	0.10-0.35	0.040	0.040	0.70-1.10		0.45-0.65	Al 0.02
ISO 2604-III:1975	TW 32			0.10-0.18	0.40-0.70	0.10-0.35	0.040	0.040	0.70-1.10		0.45-0.65	Al 0.020

5.8.4B Mechanical Properties of 1Cr-½Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	T12		K11562	A, IA, NT, SA			220	32	415	60	30	163 HB max 85 HRB max
ASTM A 250/A 250M-95 (2001)	T12		K11562	A, IA, N or NT			220	32	415	60	30	163 HB max 85 HRB max
ASTM A 335/A 335M-03	P12		K11562	FA, IA or NT			220	32	415	60	≥ 8mm (5/16 in) 30 L; 20 T	
AFNOR NF A 49-220:1990	TU 13 CD 4-04			heat + air cool + T			290		440-590		22	32 J at 0°C
BS 3604-2:1991	620			see standard			340		480-600		18	
JIS G 3458:1988	STPA 22			LTA, IA, FA, or NT			205		410		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 22			LTA, IA, A, or NT	10 ≤ O.D. < 20		205		410		25	
					O.D. ≥ 20						30	
JIS G 3467:1988	STFA 22			LTA, IA, A or NT			205		410		30	
					≤ 16		290		440-590		22 L; 20 T	
DIN 28180:1985	13 CrMo 4 4	1.7335		see standard	16 < t ≤ 40		290		440-590		22 L; 20 T	T: 34 J at RT
					40 < t ≤ 60		280		440-590		22 L; 20 T	
					≤ 16		290					1 . 40 1 at 00°C
EN 10216-2:2002	13CrMo4-5	1.7335		NT, NF, QT	16 < t ≤ 40		290		440-590		22 L; 20 T	L: 40 J at 20°C T: 27 J at 20°C
					40 < t ≤ 60		280					1. 27 0 at 20 0
ISO 2604-II:1975	TS 32			NT			275		440-590		22	
ISO 2604-III:1975	TW 32			NT			275		440-590		22	

5.8.5A Chemical Composition of 11/4 Cr-1/2 Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, ma	x, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	T11		K11597	0.05-0.15	0.30-0.60	0.50-1.00	0.025	0.025	1.00-1.50		0.44-0.65	
ASTM A 250/A 250M-95 (2001)	T11		K11597	0.05-0.15	0.30-0.60	0.50-1.00	0.025	0.020	1.00-1.50		0.44-0.65	
ASTM A 335/A 335M-03	P11		K11597	0.05-0.15	0.30-0.60	0.50-1.00	0.025	0.025	1.00-1.50		0.45-0.65	
AFNOR NF A 49-220:1990	TU 10 CD 5-05			0.15	0.30-0.60	0.50-1.00	0.025	0.025	1.00-1.50		0.45-0.65	
BS 3604-2:1991	621			0.09-0.17	0.40-0.65	0.50-0.80	0.025	0.015	1.00-1.50	0.30	0.45-0.60	Cu 0.30; Al 0.02
EN 10216-2:2002	10CrMo5-5	1.7338		0.15	0.30-0.60	0.50-1.00	0.025	0.020	1.00-1.50	0.30	0.45-0.65	Al 0.040; Cu 0.30
JIS G 3462:1988	STBA 23			0.15	0.30-0.60	0.50-1.00	0.030	0.030	1.00-1.50		0.45-0.65	
JIS G 3467:1988	STFA 23			0.15	0.30-0.60	0.50-1.00	0.030	0.030	1.00-1.50		0.45-0.65	
JIS G 3458:1988	STPA 23			0.15	0.30-0.60	0.50-1.00	0.030	0.030	1.00-1.50		0.45-0.65	

5.8.5B Mechanical Properties of 11/4 Cr-1/2 Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	T11		K11597	A, IA, NT			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 250/A 250M-95 (2001)	T11		K11597	A, IA, N or NT			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 335/A 335M-03	P11		K11597	FA, IA or NT			205	30	415	60	≥ 8mm (⁵ / ₁₆ in) 30 L; 20 T	
AENOR NE A 40 200:1000	OR NF A 49-220:1990 TU 10 CD 5-05			see standard			225		440-590		22	
AFNOR NF A 49-220:1990	10 10 00 5-05			heat + air cool + T			325		440-640		20	32 J at 0°C
BS 3604-2:1991	621			see standard			340		515-690		18	
					≤ 16		275					1 . 40 1 -+ 0000
EN 10216-2:2002	10CrMo5-5	1.7338		NT, NF, QT	16 < t ≤ 40		275		410-560		22 L; 20 T	L: 40 J at 20°C T: 27 J at 20°C
					40 < t ≤ 60		265		1			1. 27 J at 20 C
					O.D. < 10						22	
JIS G 3462:1988	STBA 23			IA, A or NT	10 ≤ O.D. < 20		205		410		25	
				.,	O.D. ≥ 20						30	
JIS G 3467:1988	STFA 23			IA, A, or NT			205		410		30	
JIS G 3458:1988	STPA 23			IA, FA or NT			205		410		30	

5.8.6A Chemical Composition of 21/4-1Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				Wei	ight, %, ma	x, Unless Of	herwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	T22		K21590	0.05-0.15	0.30-0.60	0.50	0.025	0.025	1.90-2.60		0.87-1.13	
ASTM A 250/A 250M-95 (2001)	T22		K21590	0.15	0.30-0.60	0.50	0.025	0.020	1.90-2.60		0.87-1.13	
ASTM A 335/A 335M-03	P22		K21590	0.05-0.15	0.30-0.60	0.50	0.025	0.025	1.90-2.60		0.87-1.13	
AFNOR NF A 49-220:1990	TU 10 CD 9-10			0.15	0.30-0.60	0.10-0.50	0.025	0.025	2.00-2.50		0.90-1.10	
BS 3604-2:1991	622			0.09-0.15	0.30-0.60	0.50	0.025	0.015	2.00-2.50	0.30	0.90-1.10	Cu 0.30; Al 0.02
EN 10216-2:2002	10CrMo9-10	1.7380		0.08-0.14	0.30-0.70	0.50	0.025	0.020	2.00-2.50	0.30	0.90-1.10	Al 0.040; Cu 0.30
EN 10216-2:2002	11CrMo9-10	1.7383		0.08-0.15	0.40-0.80	0.50	0.025	0.020	2.00-2.50	0.30	0.90-1.10	Al 0.040; Cu 0.30
JIS G 3458:1988	STPA 24			0.15	0.30-0.60	0.50	0.030	0.030	1.90-2.60		0.87-1.13	
JIS G 3462:1988	STBA 24			0.15	0.30-0.60	0.50	0.030	0.030	1.90-2.60		0.87-1.13	
JIS G 3467:1988	STFA 24			0.15	0.30-0.60	0.50	0.030	0.030	1.90-2.60		0.87-1.13	
ISO 2604-II:1975	TS 34			0.08-0.15	0.40-0.70	0.50	0.040	0.040	2.00-2.50		0.90-1.20	Al 0.02

5.8.6B Mechanical Properties of 21/4-1 Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	T22		K21590	A, IA, NT			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 250/A 250M-95 (2001)	T22		K21590	A, IA, N or NT			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 335/A 335M-03	P22		K21590	FA, IA or NT			205	30	415	60	≥ 8mm (5/16 in) 30 L; 20 T	
AENOD NE A 40 000:1000	TU 10 CD 0 10			see standard			225		410-560		22	
AFNOR NF A 49-220:1990	TU 10 CD 9-10			heat + air cool + T			325		490-640		20	32 J at 0°C
BS 3604-2:1991	622			see standard			310		515-690		16	
					≤ 16		280					1.40 1-40000
	10CrMo9-10	1.7380		NT, NF, QT	16 < t ≤ 40		280		480-630		22 L; 20 T	L: 40 J at 20°C T: 27 J at 20°C
EN 10216-2:2002					40 < t ≤ 60		270					1. 27 J al 20 C
EN 10216-2:2002					≤ 16		355					1 40 1 -+ 0000
	11CrMo9-10	1.7383		QT	16 < t ≤ 40		355		540-680		20 L; 18 T	L: 40 J at 20°C T: 27 J at 20°C
					40 < t ≤ 60		355					1. 27 J al 20 C
JIS G 3458:1988	STPA 24			IA, FA or NT			205		410		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 24			IA, A or NT 1	10 ≤ O.D. < 20		205		410		25	
					O.D. ≥ 20						30	
JIS G 3467:1988	STFA 24			IA, A, or NT			205		410		30	
ISO 2604-II:1975	TS 34			Α			135		410-560		20	

5.8.7A Chemical Composition of 5Cr-1/2Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	s Otherwi	se Specifie	i
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	T5		K41545	0.15	0.30-0.60	0.50	0.025	0.025	4.00-6.00		0.45-0.65	
A3 TWI A 213/A 213WI-03a	T5b		K51545	0.15	0.30-0.60	1.00-2.00	0.025	0.025	4.00-6.00		0.45-0.65	
ASTM A 335/A 335M-03	P5		K41545	0.15	0.30-0.60	0.50	0.025	0.025	4.00-6.00		0.45-0.65	
	X11CrMo5+I	1.7362+I		0.08-0.15	0.30-0.60	0.15-0.50	0.025	0.020	4.00-6.00		0.45-0.65	Al 0.040; Cu 0.30
EN 10216-2:2002	X11CrMo5+NT1	1.7362+NT1		0.08-0.15	0.30-0.60	0.15-0.50	0.025	0.020	4.00-6.00		0.45-0.65	Al 0.040; Cu 0.30
	X11CrMo5+NT2	1.7362+NT2		0.08-0.15	0.30-0.60	0.15-0.50	0.025	0.020	4.00-6.00		0.45-0.65	Al 0.040; Cu 0.30
JIS G 3458:1988	STPA 25			0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
JIS G 3462:1988	STBA 25			0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
JIS G 3467:1988	STFA 25			0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
ISO 2604-II:1975	TS 37			0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	AI 0.02

5.8.7B Mechanical Properties of 5Cr-½Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ACTM A 010/A 010M 000	T5		K41545	A, IA, NT			205	30	415	60	30	163 HB max 85 HRB max
ASTM A 213/A 213M-03a	T5b		K51545	A, IA, NT			205	30	415	60	30	179 HB max 89 HRB max
ASTM A 335/A 335M-03	P5		K41545	FA, IA or NT			205	30	415	60	≥ 8mm (⁵ / ₁₆ in) 30 L; 20 T	
					≤ 16		175					
	X11CrMo5+I	1.7362+I		,	16 < t ≤ 40		175		430-580		00 L . 00 T	L: 40 J at 20°C
	X I I CIIVIOS+I	1./302+1		l l	40 < t ≤ 60		175		430-560		22 L; 20 T	T: 27 J at 20°C
					60 < t ≤ 100		175					
					≤ 16		280					
EN 10216-2:2002	X11CrMo5+NT1	1.7362+NT1		NT	16 < t ≤ 40		280		480-640		20 L; 18 T	L: 40 J at 20°C
LIN 10210-2.2002	XTTCHVIOS+NTT	1.7302+1111		INI	40 < t ≤ 60		280		460-040		20 L, 10 1	T: 27 J at 20°C
					60 < t ≤ 100		280					
					≤ 16		390					
	X11CrMo5+NT2	1.7362+NT2		NT, QT	16 < t ≤ 40		390		570-740		18 L; 16 T	L: 40 J at 20°C
	XTTGHVIO5+NTZ	1.7302+1112		INI, QI	40 < t ≤ 60		390		370-740		10 L, 10 1	T: 27 J at 20°C
					60 < t ≤ 100		390					
JIS G 3458:1988	STPA 25			IA, FA or NT			205		410		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 25			IA, A or NT 1	10 ≤ O.D. < 20		205		410		25	
				,	O.D. ≥ 20						30	
JIS G 3467:1988	STFA 25			IA, A, or NT			205		410		30	
ISO 2604-II:1975	TS 37			Α			205		410-560		20	

5.8.8A Chemical Composition of 9Cr-1Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				٧	/eight, %,	max, Unless	Otherwi	se Specifie	1
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	T9		S50400	0.15	0.30-0.60	0.25-1.00	0.025	0.025	8.00-10.00		0.90-1.10	
ASTM A 335/A 335M-03	P9		S50400	0.15	0.30-0.60	0.25-1.00	0.025	0.025	8.00-10.00		0.90-1.10	
EN 10216-2:2002	X11CrMo9-1+I	1.7386+I		0.08-0.15	0.30-0.60	0.25-1.00	0.025	0.020	8.00-10.00		0.90-1.10	Al 0.040; Cu 0.30
LN 10210-2.2002	X11CrMo9-1+NT	1.7386+NT		0.08-0.15	0.30-0.60	0.25-1.00	0.025	0.020	8.00-10.00		0.90-1.10	Al 0.040; Cu 0.30
JIS G 3458:1988	STPA 26			0.15	0.30-0.60	0.25-1.00	0.030	0.030	8.00-10.00		0.90-1.10	
JIS G 3462:1988	STBA 26			0.15	0.30-0.60	0.25-1.00	0.030	0.030	8.00-10.00		0.90-1.10	
JIS G 3467:1988	STFA 26			0.15	0.30-0.60	0.25-1.00	0.030	0.030	8.00-10.00		0.90-1.10	
ISO 2604-II:1975	TS 38			0.15	0.30-0.60	0.25-1.00	0.030	0.030	8.00-10.00		0.90-1.10	AI 0.02
ASTM A 213/A 213M-03a	T91			0.08-0.12	0.30-0.60	0.20-0.50	0.020	0.010	8.00-9.50	0.40	0.85-1.05	V 0.18-0.25; Cb 0.06-0.1; N 0.030-0.070; Al 0.04
EN 10216-2:2002	X10CrMoVNb9-1	1.4903		0.08-0.12	0.30-0.60	0.20-0.50	0.020	0.010	8.00-9.50	0.40	0.85-1.05	V 0.18-0.25; Nb 0.06-0.10; N 0.030-0.070; Al 0.040; Cu 0.30

5.8.8B Mechanical Properties of 9Cr-1Mo Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	T9		S50400	A, IA, NT			205	30	415	60	30	179 HB max 89 HRB max
ASTM A 335/A 335M-03	P9		S50400	FA, IA or NT			205	30	415	60	≥ 8mm (5/16 in) 30 L; 20 T	
					≤ 16		210					1.40 1.4000
	X11CrMo9-1+I	1.7386+I		I	16 < t ≤ 40		210		460-640		20 L; 18 T	L: 40 J at 20°C T: 27 J at 20°C
EN 10216-2:2002					40 < t ≤ 60		210					1. 27 3 at 20 0
LN 10210-2.2002	≤ 16 390					L: 40 J at 20°C						
	X11CrMo9-1+NT	1.7386+NT		NT, QT	16 < t ≤ 40		390		590-740		18 L; 16 T	T: 27 J at 20°C
					40 < t ≤ 60		390					1. 27 0 at 20 0
JIS G 3458:1988	STPA 26			IA, FA or NT			205		410		30	
					O.D. < 10						22	
JIS G 3462:1988	STBA 26			IA, A or NT	10 ≤ O.D. < 20		205		410		25	
					O.D. ≥ 20						30	
JIS G 3467:1988	STFA 26			IA, A, or NT			205		410		30	
ISO 2604-II:1975	TS 38			Α			135		410-560		20	
ASTM A 213/A 213M-03a	T91			NT			415	60	585	85	20	250 HB max 25 HRC max
					≤ 16		450					1 . 40 1 -+ 0000
EN 10216-2:2002	X10CrMoVNb9-1	1.4903		NT, QT	16 < t ≤ 40		450		630-830		19 L; 17 T	L: 40 J at 20°C T: 27 J at 20°C
					40 < t ≤ 60		450					1. 27 0 at 20 C

5.9.1A Chemical Composition of Ferritic and Martensitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				٧	Veight, %	, max, Unless	Otherwi	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 268/A 268M-03	TP409		S40900	0.08	1.00	1.00	0.045	0.030	10.5-11.7	0.50		Ti 6 x C to 0.75
ASTM A 803/A 803M-03	TP409		S40900	0.08	1.00	1.00	0.045	0.030	10.5-11.7	0.50		Ti 6 x C to 0.75
JIS G 3463:1994	SUS409TB			0.08	1.00	1.00	0.040	0.030	10.50-11.75			Ti 6 x C to 0.75
AFNOR NF A 49-217:1987	TU Z 12 C 13			0.15	1.00	1.00	0.040	0.030	11.50-13.50	0.50		
ASTM A 268/A 268M-03	TP410		S41000	0.15	1.00	1.00	0.040	0.030	11.5-13.5			
ISO 2604-II:1975	TS 39			0.08	1.00	1.00	0.040	0.030	11.5-14.0	0.50		
JIS G 3463:1994	SUS410TB			0.015	1.00	1.00	0.040	0.030	11.50-13.50			
AFNOR NF A 49-217:1987	TU Z 10 C 17			0.12	1.00	1.00	0.040	0.030	16.00-18.00	0.50		
ASTM A 268/A 268M-03	TP430		S43000	0.12	1.00	1.00	0.040	0.030	16.0-18.0			
JIS G 3463:1994	SUS430TB			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
JIS G 3463:1994	SUS430LXTB			0.030	1.00	0.75	0.040	0.030	16.00-19.00			Ti or Nb 0.10-1.00
ASTM A 803/A 803M-03	TP XM-27		S44627	0.01	0.40	0.40	0.02	0.02	25.0-27.5	0.5	0.75-1.50	Cu 0.20; N 0.015; Cb 0.05-0.20
JIS G 3463:1994	SUSXM27TB			0.010	0.40	0.40	0.030	0.020	25.00-27.50		0.75-1.50	N 0.015

Mechanical Properties of Ferritic and Martensitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
ASTM A 268/A 268M-03	TP409		S40900	HT			470	25	380	55	20	207 HB; 95 HRB max
ASTM A 803/A 803M-03	TP409		S40900	SA			205	30	380	55	20	207 HB max; 95 HRB max
					O.D. < 10						12	
JIS G 3463:1994	SUS409TB			Α	10 ≤ O.D. < 20		205		410		15	
					O.D. ≥ 20						20	
AFNOR NF A 49-217:1987	TU Z 12 C 13			HF + CR + T			210		420-670		17	
ASTM A 268/A 268M-03	TP410		S41000	нт			215	30	415	60	20	207 HB; 95 HRB max
SO 2604-II:1975	TS 39			Α			245		440-590		20	
J 2004-II: 1975	13 33			QT			390		590-740		18	
					O.D. < 10						12	
JIS G 3463:1994	SUS410TB			Α	10 ≤ O.D. < 20		205		410		15	
					O.D. ≥ 20						20	
AFNOR NF A 49-217:1987	TU Z 10 C 17			HF + CR + T			250		420-670		17	
ASTM A 268/A 268M-03	TP430		S43000	НТ			240	35	415	60	20	190 HB; 90 HRB max
					O.D. < 10						12	
JIS G 3463:1994	SUS430TB			Α	10 ≤ O.D. < 20		245		410		15	
					O.D. ≥ 20						20	
					O.D. < 10						12	
JIS G 3463:1994	SUS430LXTB			Α	10 ≤ O.D. < 20		175		360		15	
					O.D. ≥ 20						20	
ASTM A 803/A 803M-03	TP XM-27		S44627	SA			275	40	450	65	20	241 HB max; 100 HRB max
					O.D. < 10						12	
IS G 3463:1994	SUSXM27TB			Α	10 ≤ O.D. < 20		245		410		15	
					O.D. ≥ 20						20	

Standard	Grade, Class, Type,	Steel	UNS				٧	Veight, %	, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP304		S30400	0.08	2.00	0.75	0.040	0.030	18.0-20.0	8.00-11.0		
ASTM A 249/A 249M-03	TP304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
ASTM A 312/A 312M-03	TP304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
ASTM A 358/A 358M-01	304		S30400	0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10
ASTM A 376/A 376M-02a	TP304			0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.00-11.0		
ASTM A 409/A 409M-01	TP304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.00-11.0		
ASTM A 688/A 688M-03	TP304		S30400	0.08	2.00	0.75	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3459:1997	SUS304TP			0.08	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3463:1994	SUS304TB			0.08	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3467:1988	SUS 304 TF			0.08	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3468:1994	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
BS 3605-1:1991 AMD 2:1997	304S31			0.070	2.00	1.00	0.040	0.030	17.00-19.00	8.00-11.00		
BS 3605-2:1992 AMD 1:1997	304S31			0.070	2.00	1.00	0.04	0.03	17.00-19.00	8.00-11.00		
DIN 17457:1985	X 5 CrNi 18 10	1.4301		0.07					17.0-19.0	8.5-10.5		
DIN 17458:1985	X 5 CrNi 18 10	1.4301		0.07					17.0-19.0	8.5-10.5		
DIN 28180:1985	X 5 CrNi 18 10	1.4301		0.07					17.0-19.0	8.5-10.5		
DIN 28181:1985	X 5 CrNi 18 10	1.4301		0.07					17.0-19.0	8.5-10.5		
AFNOR NF A 49-217:1987	TU Z 6 CN 18 09			0.080	2.00	1.00	0.040	0.030	17.00-20.00	8.00-11.00		
AFNOR NF A 49-244:1993	X7CrNi18-9			0.070	2.00	0.75	0.040	0.015	17.0-19.0	8.0-10.0		
AFNOR NF A 49-247:1981	TS Z 6 CN 18-09			0.080	2.00	1.00	0.040	0.030	17-20.0	8-11.00		
ISO 2604-II:1975	TS 47			0.07	2.00	1.00	0.045	0.030	17.00-19.00	8.00-12.00		
ISO 2604-V:1978	TW 47			0.07	2.00	1.00	0.045	0.030	17.00-19.00	8.00-11.00		

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	s Otherwise S	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP304L		S30403	0.035	2.00	0.75	0.040	0.030	18.0-20.0	8.00-13.0		
ASTM A 249/A 249M-03	TP304L		S30403	0.035	2.00	1.00	0.045	0.030	18.0-20.0	8.0-13.0		
ASTM A 312/A 312M-03	TP304L		S30403	0.035	2.00	1.00	0.045	0.030	18.0-20.0	8.00-13.0		
ASTM A 358/A 358M-01	304L		S30403	0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10
ASTM A 409/A 409M-01	TP304L		S30403	0.035	2.00	1.00	0.045	0.030	18.0-20.0	8.00-12.0		
ASTM A 688/A 688M-03	TP304L		S30403	0.035	2.00	0.75	0.040	0.030	18.00-20.00	8.00-13.00		
JIS G 3459:1997	SUS304LTP			0.030	2.00	1.00	0.040	0.030	18.00-20.00	9.00-13.00		
JIS G 3463:1994	SUS304LTB			0.030	2.00	1.00	0.040	0.030	18.00-20.00	9.00-13.00		
JIS G 3468:1994	SUS304L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	9.00-13.00		
BS 3605-1:1991 AMD 2:1997	304S11			0.030	2.00	1.00	0.040	0.030	17.00-19.00	9.00-12.00		
BS 3605-2:1992 AMD 1:1997	304S11			0.030	2.00	1.00	0.04	0.03	17.00-19.00	9.00-12.00		
DIN 17457:1985	X 2 CrNi 19 11	1.4306		0.030					18.0-20.0	10.0-12.5		
DIN 17458:1985	X 2 CrNi 19 11	1.4306		0.030					18.0-20.0	10.0-12.5		
AFNOR NF A 49-217:1987	TU Z 2 CN 18 10			0.030	2.00	1.00	0.040	0.030	17.00-20.00	9.00-12.00		
AFNOR NF A 49-244:1993	X3CrNi18-10			0.030	2.00	0.75	0.040	0.015	17.0-19.0	9.0-11.0		
AFNOR NF A 49-247:1981	TS Z 2 CN 18-10			0.030	2.00	1.00	0.040	0.030	17-20.0	9-12.00		
ISO 2604-II:1975	TS 46			0.03	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		
ISO 2604-V:1978	TW 46			0.03	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		
ASTM A 213/A 213M-03a	TP304LN		S30453	0.035	2.00	0.75	0.040	0.030	18.0-20.0	8.00-11.0		N 0.10-0.16
ASTM A 249/A 249M-03	TP304LN		S30453	0.030	2.00	1.00	0.045	0.030	18.0	20.0		N 0.10-0.16
ASTM A 376/A 376M-02a	TP304LN			0.035	2.00	0.75	0.045	0.030	18.0-20.0	8.00-11.0		N 0.10-0.16
ASTM A 688/A 688M-03	TP304LN		S30453	0.035	2.00	0.75	0.040	0.030	18.00-20.00	8.00-13.00		N 0.10-0.16
DIN 17457:1985	X 2 CrNiN 18 10	1.4311		0.030					17.0-19.0	8.5-11.5		N 0.12-0.22
DIN 17458:1985	X 2 CrNiN 18 10	1.4311		0.030					17.0-19.0	8.5-11.5		N 0.12-0.22
AFNOR NF A 49-217:1987	TU Z 2 CN 18 10 AZ			0.030	2.00	1.00	0.040	0.030	17.00-19.00	9.00-11.00		N 0.10-0.20
AFNOR NF A 49-244:1993	X3CrNiN18-10			0.030	2.00	0.75	0.040	0.015	17.0-19.0	9.0-11.0		N 0.12-0.20
AFNOR NE A 49-244: 1993	X6CrNiN19-9			0.030	2.0	0.75	0.040	0.015	18.0-20.0	8.0-11.0		N 0.12-0.20

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	s Otherwise S	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP304H		S30409	0.04-0.10	2.00	0.75	0.040	0.030	18.0-20.0	8.00-11.0		
ASTM A 249/A 249M-03	TP304H		S30409	0.04-0.10	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
ASTM A 312/A 312M-03	TP304H		S30409	0.04-0.10	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
ASTM A 358/A 358M-01	304H		S30409	0.04-0.10	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		
ASTM A 376/A 376M-02a	TP304H		S30409	0.04-0.10	2.00	0.75	0.045	0.030	18.0-20.0	8.00-11.0		
JIS G 3459:1997	SUS304HTP			0.04-0.10	2.00	0.75	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3463:1994	SUS304HTB			0.04-0.10	2.00	0.75	0.040	0.030	18.00-20.00	8.00-11.00		
JIS G 3467:1988	SUS 304H TF			0.04-0.10	2.00	0.75	0.040	0.030	18.00-20.00	8.00-11.00		
BS 3605-1:1991 AMD 2:1997	304S51			0.04-0.10	2.00	1.00	0.040	0.030	17.00-19.00	8.00-11.00		
DIN 17459:1992	X 6 CrNi 18 11	1.4948		0.04-0.08	2.0	0.75	0.035	0.015	17.0-19.0	10.0-12.0		
AFNOR NF A 49-214:1978	Z 6 CN 19-10			0.04-0.08	2.0	1.0	0.035	0.030	18-20	8-11		
ISO 2604-II:1975	TS 48			0.04-0.09	2.00	0.75	0.045	0.030	17.00-20.00	8.00-12.00		
ASTM A 249/A 249M-03			S30615	0.16-0.24	2.00	3.2-4.0	0.030	0.030	17.0-19.5	13.5-16.0		
AFNOR NF A 49-217:1987	TU Z 1 CNS 18 15			0.015	2.00	3.50-4.50	0.030	0.020	16.50-18.50	13.80-16.00	0.50	
ASTM A 213/A 213M-03a	TP309S		S30908	0.08	2.00	0.75	0.045	0.030	24.0-26.0	12.00-15.00	0.75	
ASTM A 249/A 249M-03	TP309S		S30908	0.08	2.00	1.00	0.045	0.030	22.0-24.0	12.0-15.0		
ASTM A 312/A 312M-03	TP309S		S30908	0.08	2.00	1.00	0.045	0.030	22.0-24.0	12.0-15.0	0.75	
ASTM A 358/A 358M-01	309S		S30908	0.08	2.00	0.75	0.045	0.030	22.0-24.0	12.0-15.0		
JIS G 3459:1997	SUS309STP			0.08	2.00	1.00	0.040	0.030	22.00-24.00	12.00-15.00		
JIS G 3463:1994	SUS309STB			0.08	2.00	1.00	0.040	0.030	22.00-24.00	12.00-15.00		
JIS G 3468:1994	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
ASTM A 213/A 213M-03a	TP309H		S30909	0.04-0.10	2.00	0.75	0.045	0.030	22.00-24.00	12.00-15.00	0.75	
ASTM A 249/A 249M-03	TP309H		S30909	0.04-0.10	2.00	1.00	0.045	0.030	22.0-24.0	12.0-15.0		
JIS G 3459:1997	SUS309TP			0.15	2.00	1.00	0.040	0.030	22.00-24.00	12.00-15.00		
JIS G 3463:1994	SUS309TB			0.15	2.00	1.00	0.040	0.030	22.00-24.00	12.00-15.00		
AFNOR NF A 49-244:1993	X15CrNi24-13			0.15	2.00	0.75	0.035	0.015	22.0-24.0	12.0-14.0		
ASTM A 213/A 213M-03a	TP310S		S31008	0.08	2.00	0.75	0.045	0.030	24.00-26.00	19.00-22.00	0.75	
ASTM A 249/A 249M-03	TP310S		S31008	0.08	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0		
ASTM A 312/A 312M-03	TP310S		S31008	0.08	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0	0.75	
ASTM A 358/A 358M-01	310S		S31008	0.08	2.00	1.50	0.045	0.030	24.0-26.0	19.0-22.0		
JIS G 3459:1997	SUS310STP			0.08	2.00	1.50	0.040	0.030	24.00-26.00	19.00-22.00		
JIS G 3463:1994	SUS310STB			0.08	2.00	1.50	0.040	0.030	24.00-26.00	19.00-22.00		
JIS G 3468:1994	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		

5.9.2A Chemical Composition of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS				1	Weight, 9	%, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP310H		S31009	0.04-0.10	2.00	0.75	0.040	0.030	24.00-26.00	19.0-22.00		
AFNOR NF A 49-244:1993	X1CrNi25-20			0.015	2.00	0.40	0.025	0.010	24.0-26.0	19.0-22.0	0.5	
JIS G 3463:1994	SUS310TB			0.15	2.00	1.50	0.040	0.030	24.00-26.00	19.00-22.00		
JIS G 3467:1988	SUS310TF			0.15	2.00	1.50	0.040	0.030	24.00-26.00	19.00-22.00		
ISO 2604-II:1975	TS 68			0.15	2.00	0.75	0.045	0.030	24.00-26.00	19.00-22.00		
ASTM A 249/A 249M-03			S31050	0.030	2.00	0.40	0.030	0.015	24.0-26.0	21.0-23.0	2.00-3.00	0.10-0.16
AFNOR NF A 49-217:1987	TU Z 1 CND 25 22 AZ			0.020	1.50-2.00	0.40	0.020	0.015	24.50-26.00	21.50-23.00	1.90-2.40	N 0.10-0.15
ASTM A 249/A 249M-03			S31254	0.020	1.00	0.80	0.030	0.010	19.5-20.5	17.5-18.5	6.0-6.5	N 0.18-0.25; Cu 0.50-1.00
ASTM A 688/A 688M-03			S31254	0.020	1.00	0.80	0.030	0.010	19.5-20.5	17.5-18.5	6.0-6.5	N 0.18-0.22; Cu 0.50-1.00
AFNOR NF A 49-217:1987	TU Z 1 CNDU 20 18 06 AZ			0.020	1.00	0.80	0.030	0.010	19.50-20.50	17.50-18.50	6.00-6.50	Cu 0.50-1.00
ASTM A 213/A 213M-03a	TP316		S31600	0.08	2.00	0.75	0.040	0.030	16.0-18.0	11.0-14.0	2.00-3.00	
ASTM A 249/A 249M-03	TP316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 312/A 312M-03	TP316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	
ASTM A 358/A 358M-01	316		S31600	0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
ASTM A 376/A 376M-02a	TP316			0.08	2.00	0.75	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	
ASTM A 409/A 409M-01	TP316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 688/A 688M-03	TP316		S31600	0.08	2.00	0.75	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 3459:1997	SUS316TP			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 3463:1994	SUS316TB			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 3467:1988	SUS 316 TF			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 3468:1994	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
BS 3605-1:1991 AMD 2:1997	316S31			0.070	2.00	1.00	0.040	0.030	16.50-18.50	10.50-13.50	2.00-2.50	
BS 3005-1.1991 AMD 2.1997	316S33			0.070	2.00	1.00	0.040	0.030	16.50-18.50	11.00-14.00	2.50-3.00	
BS 3605-2:1992 AMD 1:1997	316S31			0.070	2.00	1.00	0.04	0.03	16.50-18.50	10.50-13.50	2.00-2.50	
B3 3003-2.1992 AMD 1.1991	316S33			0.070	2.00	1.00	0.04	0.03	16.50-18.50	11.00-14.00	2.50-3.00	
DIN 17457:1985	X 5 CrNiMo 17 12 2	1.4401		0.07					16.5-18.5	10.5-13.5	2.0-2.5	
DIN 17458:1985	X 5 CrNiMo 17 12 2	1.4401		0.07					16.5-18.5	10.5-13.5	2.0-2.5	
DIN 17457:1985	X 5 CrNiMo17 13 3	1.4436		0.07				0.025	16.5-18.5	11.0-14.0	2.5-3.0	
DIN 17458:1985	X 5 CrNiMo17 13 3	1.4436		0.07				0.025	16.5-18.5	11.0-14.0	2.5-3.0	
DIN 28180:1985	X 5 CrNiMo 17 12 2	1.4401		0.07					16.5-18.5	10.5-13.5	2.0-2.5	
DIN 28181:1985	X 5 CrNiMo 17 12 2	1.4401		0.07					16.5-18.5	10.5-13.5	2.0-2.5	
AFNOR NF A 49-217:1987	TU Z 6 CND 17 11			0.070	2.00	1.00	0.040	0.030	16.00-18.00	10.00-12.50	2.00-2.40	
AFNOR NF A 49-244:1993	X7CrNiMo17-11-2			0.070	2.00	0.75	0.040	0.015	16.0-18.0	10.0-12.0	2.00-2.50	
AFNOR NF A 49-247:1981	TS Z 6 CND 17-11			0.070	2.00	1.00	0.040	0.030	16-18.0	10-12.50	2.00-2.40	

NOTE: This section continued on next page

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ISO 2604-II:1975	TS 60			0.07	2.00	1.00	0.045	0.030	16.00-18.50	11.00-14.00	2.00-2.50	
150 2604-11: 1975	TS 61			0.07	2.00	1.00	0.045	0.030	16.00-18.50	11.00-14.50	2.50-3.00	
ISO 2604-V:1978	TW 60			0.07	2.00	1.00	0.045	0.030	16.00-18.50	10.50-14.00	2.00-2.50	
150 2604-1:1978	TW 61			0.07	2.00	1.00	0.045	0.030	16.00-18.50	11.00-14.50	2.50-3.00	
ASTM A 213/A 213M-03a	TP316L		S31603	0.035	2.00	0.75	0.040	0.030	16.0-18.0	10.0-15.0	2.00-3.00	
ASTM A 249/A 249M-03	TP316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 312/A 312M-03	TP316L		S31603	0.035	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 358/A 358M-01	316L		S31603	0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
ASTM A 409/A 409M-01	TP316L		S31603	0.035	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 688/A 688M-03	TP316L		S31603	0.035	2.00	0.75	0.040	0.030	16.00-18.00	10.00-15.00	2.00-3.00	
JIS G 3459:1997	SUS316LTP			0.030	2.00	1.00	0.040	0.030	16.00-18.00	12.00-16.00	2.00-3.00	
JIS G 3463:1994	SUS316LTB			0.030	2.00	1.00	0.040	0.030	16.00-18.00	12.00-16.00	2.00-3.00	
JIS G 3468:1994	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
BS 3605-1:1991 AMD 2:1997	316S11			0.030	2.00	1.00	0.040	0.030	16.50-18.50	11.00-14.00	2.00-2.50	
BS 3605-1:1991 AMD 2:1997	316S13			0.030	2.00	1.00	0.040	0.030	16.50-18.50	11.50-14.50	2.50-3.00	
BS 3605-2:1992 AMD 1:1997	316S11			0.030	2.00	1.00	0.04	0.03	16.50-18.50	11.00-14.00	2.00-2.50	
BS 3605-2:1992 AMD 1:1997	316S13			0.030	2.00	1.00	0.04	0.03	16.50-18.50	11.50-14.50	2.50-3.00	
DIN 17457:1985	X 2 CrNiMo 17 13 2	1.4404		0.030					16.5-18.5	11.0-14.0	2.0-2.5	
DIN 17458:1985	X 2 CrNiMo 17 13 2	1.4404		0.030					16.5-18.5	11.0-14.0	2.0-2.5	
DIN 17457:1985	X 2 CrNiMo 18 14 3	1.4435		0.030				0.025	17.0-18.5	12.5-15.0	2.5-3.0	
DIN 17458:1985	X 2 CrNiMo 18 14 3	1.4435		0.030				0.025	17.0-18.5	12.5-15.0	2.5-3.0	
AFNOR NF A 49-217:1987	TU Z 2 CND 17 12			0.030	2.00	1.00	0.040	0.030	16.00-18.00	10.50-13.00	2.00-2.40	
	X3CrNiMo17-11-2			0.030	2.00	0.75	0.040	0.015	16.0-18.0	10.0-12.0	2.00-2.50	
AFNOR NF A 49-244:1993	X3CrNiMo17-12-3			0.030	2.00	0.75	0.040	0.015	16.5-18.5	11.0-13.0	2.5-3.00	
AFNOR NF A 49-244:1993	X3CrNiMo18-12-3			0.030	2.00	0.75	0.040	0.015	16.5-18.5	11.0-13.0	2.25-2.75	
	TU Z 2 CND 18 14			0.030	2.00	1.00	0.020	0.015	17.00-18.50	13.00-16.00	2.20-3.00	
AFNOR NF A 49-247:1981	TS Z 2 CND 17-12			0.030	2.00	1.00	0.040	0.030	16-18.0	10.5-13.00	2.00-2.40	
100 0004 11:4075	TS 57			0.03	2.00	1.00	0.045	0.030	16.00-18.50	11.00-14.00	2.00-2.50	
ISO 2604-II:1975	TS 58			0.03	2.00	1.00	0.045	0.030	16.00-18.50	11.50-14.50	2.50-3.00	
ICO 0004 V:4070	TW 57			0.03	2.00	1.00	0.045	0.030	16.00-18.50	11.00-14.00	2.00-2.50	
O 2604-V:1978	TW 58			0.03	2.00	1.00	0.045	0.030	16.00-18.50	11.50-14.50	2.50-3.00	

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP316LN	-	S31653	0.035	2.00	0.75	0.040	0.030	16.0-18.0	11.0-14.0	2.00-3.00	0.10-0.16
ASTM A 249/A 249M-03	TP316LN		S31653	0.080	2.00	1.00	0.045	0.030	16.0-18.0	10.0-13.0	2.00-3.00	N 0.10-0.16
ASTM A 376/A 376M-02a	TP316LN			0.035	2.00	0.75	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	N 0.10-0.16
ASTM A 688/A 688M-03	TP316LN		S31653	0.035	2.00	0.75	0.040	0.030	16.00-18.00	10.00-15.00	2.00-3.00	N 0.10-0.16
DIN 17457:1985	X 2 CrNiMoN 17 13 3	1.4429		0.030				0.025	16.5-18.5	11.5-14.5	2.5-3.0	N 0.14-0.22
DIN 17458:1985	X 2 CrNiMoN 17 13 3	1.4429		0.030				0.025	16.5-18.5	11.5-14.5	2.5-3.0	N 0.14-0.22
AFNOR NF A 49-217:1987	TU Z 2 CND 17 12 AZ			0.030	2.00	1.00	0.040	0.030	16.00-18.00	11.00-13.50	2.00-2.40	N 0.10-0.20
AFNOR NF A 49-244:1993	X3CrNiMoN17-11			0.030	2.00	0.75	0.040	0.015	16.0-18.0	10.0-12.0	2.00-2.5	N 0.12-0.20
AFNON NF A 49-244.1995	X3CrNiMoN17-12			0.030	2.00	0.75	0.040	0.015	16.0-18.0	11.0-13.0	2.5-3.0	N 0.12-0.20
ASTM A 213/A 213M-03a	TP316H		S31609	0.04-0.10	2.00	0.75	0.040	0.030	186.0-18.0	11.0-14.0	2.00-3.00	
ASTM A 249/A 249M-03	TP316H		S31609	0.04-0.10	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 312/A 312M-03	TP316H		S31609	0.04-0.10	2.00	1.00	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	
ASTM A 358/A 358M-01	316H		S31609	0.04-0.10	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 376/A 376M-02a	TP316H		S31609	0.04-0.10	2.00	0.75	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	
JIS G 3459:1997	SUS316HTP			0.04-0.10	2.00	0.75	0.030	0.030	16.00-18.00	11.00-14.00	2.00-3.00	
JIS G 3463:1994	SUS316HTB			0.04-0.10	2.00	0.75	0.030	0.030	16.00-18.00	11.00-14.00	2.00-3.00	
JIS G 3467:1988	SUS 316H TF			0.04-0.10	2.00	0.75	0.030	0.030	16.00-18.00	11.00-14.00	2.00-3.00	
BS 3605-1:1991 AMD 2:1997	316S51			0.04-0.10	2.00	1.00	0.040	0.030	16.50-18.50	10.50-13.50	2.00-2.50	
DIN 17459:1992	X 6 CrNiMo 17 13	1.4919		0.04-0.08	2.0	0.75	0.035	0.015	16.0-18.0	12.0-14.0	2.0-2.5	
AFNOR NF A 49-214:1978	Z 6 CND 17-12 B			0.04-0.08	2.0	1.0	0.035	0.030	16-18	11-14	2.0-3.0	
ISO 2604-II:1975	TS 63			0.04-0.09	1.00-2.00	0.75	0.045	0.030	16.00-18.00	12.00-14.00	2.00-2.75	
BS 3605-1:1991 AMD 2:1997	316S52			0.04-0.10	2.00	1.00	0.040	0.030	16.50-18.50	10.50-13.50	2.00-2.50	B 0.0015-0.006
DIN 17459:1992	X 3 CrNiMoN 17 13	1.4910		0.04	2.0	0.75	0.035	0.015	16.0-18.0	12.0-14.0	2.0-2.8	B 0.0015-0.0050; N 0.10-0.18
JIS G 3459:1997	SUS316TiTP			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	Ti 5 x C min
JIS G 3463:1994	SUS316TiTB			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-1400	2.00-3.00	Ti 5 x C min
DIN 17457:1985	X 6 CrNiMoTi 17 12 2	1.4571		0.08					16.5-18.5	10.5-13.5	2.0-2.5	Ti 5 x C to 0.80
DIN 17458:1985	X 6 CrNiMoTi 17 12 2	1.4571		0.08					16.5-18.5	10.5-13.5	2.0-2.5	Ti 5 x C to 0.80
DIN 28180:1985	X 6 CrNiMoTi 17 12 2	1.4571		0.08					16.5-18.5	10.5-13.5	2.0-2.5	Ti 5 x C to 0.80
DIN 28181:1985	X 6 CrNiMoTi 17 12 2	1.4571		0.08					16.5-18.5	10.5-13.5	2.0-2.5	Ti 5 x C to 0.80
AFNOR NF A 49-214:1978	Z 8 CNDT 17-13 B			0.05-0.10	2.0	1.0	0.035	0.030	16-18	12-15	2.0-3.0	Ti 4 x C to 0.75
AFNOR NF A 49-244:1993	X6CrNiMo17-11-2			0.060	2.00	0.75	0.040	0.015	16.0-18.0	10.5-12.5	2.00-2.5	Ti 5 (C+N) to 0.70; Ti/C+N to 15

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP317		S31700	0.08	2.00	0.75	0.040	0.030	18.0-20.0	11.0-14.0	3.00-4.00	
ASTM A 249/A 249M-03	TP317		S31700	0.08	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
ASTM A 312/A 312M-03	TP317		S31700	0.08	2.00	1.00	0.045	0.030	18.0-20.0	11.0-14.0	3.0-4.0	
ASTM A 409/A 409M-01	TP317		S31700	0.08	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	
JIS G 3459:1997	SUS317TP			0.08	2.00	1.00	0.040	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 3463:1994	SUS317TB			0.08	2.00	1.00	0.040	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 3468:1994	SUS317			0.08	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
ASTM A 213/A 213M-03a	TP317L		S31703	0.035	2.00	0.75	0.040	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
ASTM A 249/A 249M-03	TP317L		S31703	0.030	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
ASTM A 312/A 312M-03	TP317L		S31703	0.035	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	
JIS G 3459:1997	SUS317LTP			0.030	2.00	1.00	0.040	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 3463:1994	SUS317LTB			0.030	2.00	1.00	0.040	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 3468:1994	SUS317L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
AFNOR NF A 49-244:1993	X3CrNiMo19-15-4			0.030	2.00	0.75	0.035	0.010	17.5-19.5	14.0-16.0	3.00-4.00	
AFNOR NF A 49-247:1981	TS Z 2 CND 19-15			0.030	2.00	1.00	0.040	0.030	17.5-19.5	14-16	3.0-4.0	
ASTM A 213/A 213M-03a	TP321		S32100	0.08	2.00	0.75	0.040	0.030	17.0-20.0	9.00-13.0		Ti 5 X C-0.60
ASTM A 249/A 249M-03	TP321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.00-12.0		N 0.10; Ti 5 x (C+N) to 0.70
ASTM A 312/A 312M-03	TP321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		N 0.10; Ti 5 x C to 0.70
ASTM A 358/A 358M-01	321		S32100	0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x (C+N) to 0.70; N 0.10
ASTM A 376/A 376M-02a	TP321			0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.00-13.0		Ti 5 x C to 0.70
ASTM A 409/A 409M-01	TP321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-20.0	9.00-12.0		Ti 5 x C to 0.70
JIS G 3459:1997	SUS321TP			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
JIS G 3463:1994	SUS321TB			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
JIS G 3467:1988	SUS 321 TF			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
JIS G 3468:1994	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
BS 3605-1:1991 AMD 2:1997	321S31			0.080	2.00	1.00	0.040	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
BS 3605-2:1992 AMD 1:1997	321S31			0.080	2.00	1.00	0.04	0.03	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
DIN 17457:1985	X 6 CrNiTi 18 10	1.4541		0.08					17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
DIN 17458:1985	X 6 CrNiTi 18 10	1.4541		0.08					17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
DIN 28180:1985	X 6 CrNiTi 18 10	1.4541		0.08					17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
DIN 28181:1985	X 6 CrNiTi 18 10	1.4541		0.08					17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
AFNOR NF A 49-217:1987	TU Z 6 CNT 18 10			0.080	2.00	1.00	0.040	0.030	17.00-20.00	9.00-12.00		Ti 5 x C to 0.6
AFNOR NF A 49-244:1993	X6CrNiTi18-10			0.060	2.00	0.75	0.040	0.015	17.0-19.0	9.0-11.0		Ti 5 x (C+N) to 0.70; Ti/C+N to 15
AFNOR NF A 49-247:1981	TS Z 6 CNT 18-10			0.080	2.00	1.00	0.040	0.030	17-20.0	9-12.00		Ti 5 x C to 0.6
ISO 2604-II:1975	TS 53			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti 5 x C to 0.80
ISO 2604-V:1978	TW 53			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP321H		S32109	0.04-0.10	2.00	0.75	0.040	0.030	17.0-20.0	9.00-13.0		Ti 4 X C-0.60
ASTM A 249/A 249M-03	TP321H		S32109	0.04-0.10	2.00	1.00	0.045	0.030	17.0-19.0	9.00-12.0		N 0.10; Ti 5 x (C+N) to 0.70
ASTM A 312/A 312M-03	TP321H		S32109	0.04-0.10	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.60
ASTM A 376/A 376M-02a	TP321H		S32109	0.04-0.10	2.00	0.75	0.040	0.030	17.0-19.0	9.00-13.0		Ti 4 x C to 0.70
JIS G 3459:1997	SUS321HTP			0.04-0.10	2.00	0.75	0.030	0.030	17.00-20.00	9.00-13.00		Ti 4 x C to 0.60
JIS G 3463:1994	SUS321HTB			0.04-0.10	2.00	0.75	0.030	0.030	17.00-20.00	9.00-13.00		Ti 4 x C to 0.60
JIS G 3467:1988	SUS 321H TF			0.04-0.10	2.00	0.75	0.030	0.030	17.00-20.00	9.00-13.00		Ti 4 x C to 0.60
BS 3605-1:1991 AMD 2:1997	321S51			0.04-0.10	2.00	1.00	0.040	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
AFNOR NF A 49-214:1978	Z 6 CNT 18-12 B			0.04-0.08	2.0	1.0	0.035	0.030	17-19	10-13		Ti 4 x C to 0.60
ISO 2604-II:1975	TS 54			0.04-0.10	2.00	0.20-0.80	0.045	0.030	17.00-20.00	9.00-13.00		Ti 4 x C to 0.60
JIS G 3463:1994	SUS329J3LTB			0.030	1.50	1.00	0.040	0.030	21.00-24.00	4.50-6.50	2.50-3.50	N 0.08-0.20
AFNOR NF A 49-217:1987	TU Z 2 CND 22 05 03			0.030	2.00	1.00	0.030	0.020	21.00-23.00	4.50-6.50	2.50-3.50	N 0.08-0.20
JIS G 3463:1994	SUS329J4LTB			0.030	1.50	1.00	0.040	0.030	24.00-26.00	5.50-7.50	2.50-3.50	N 0.08-0.30
AFNOR NF A 49-217:1987	TU Z 2 CND 25 07 03			0.030	1.70	0.70	0.030	0.020	23.50-25.50	5.50-7.50	2.50-3.50	N 0.15-0.25
ASTM A 213/A 213M-03a	TP347		S34700	0.08	2.00	0.75	0.040	0.030	17.0-20.0	9.00-13.0		Cb+Ta 10 X C -1.00
ASTM A 249/A 249M-03	TP347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.00-12.0		N 0.40-0.60; Cb 0.10; Cb 10 x C to 1.10
ASTM A 312/A 312M-03	TP347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-13.0		Cb 10 x C to 1.00
ASTM A 358/A 358M-01	347		S34700	0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.0-13.0		Cb 10 x C to 1.00
ASTM A 376/A 376M-02a	TP347			0.08	2.00	0.75	0.040	0.030	17.0-19.0	9.00-13.0		Cb 10 x C to 1.10
ASTM A 409/A 409M-01	TP347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.00-12.0		(Cb+Ta) 10 x C to 1.10
JIS G 3459:1997	SUS347TP			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
JIS G 3463:1994	SUS347TB			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
JIS G 3467:1988	SUS 347 TF			0.08	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
JIS G 3468:1994	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
BS 3605-1:1991 AMD 2:1997	347S31			0.080	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Nb 10 x C to 1.00
BS 3605-2:1992 AMD 1:1997	347S31			0.080	2.00	1.00	0.04	0.03	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
DIN 17457:1985	X 6 CrNiNb 18 10	1.4550		0.08					17.0-19.0	9.0-12.0		Nb 10 x C to 1.00
DIN 17458:1985	X 6 CrNiNb 18 10	1.4550		0.08					17.0-19.0	9.0-12.0		Nb 10 x C to 1.00
ISO 2604-II:1975	TS 50			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb 10 x C to 1.00
ISO 2604-V:1978	TW 50			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %				
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 213/A 213M-03a	TP347H		S34709	0.04-0.10	2.00	0.75	0.040	0.030	17.0-20.0	9.00-13.0		Cb+Ta 8 X C -1.0
ASTM A 249/A 249M-03	TP347H		S34709	0.04-0.10	2.00	1.00	0.045	0.030	17.0-19.0	9.00-12.0		Cb 8 x C to 1.0
ASTM A 312/A 312M-03	TP347H		S34709	0.04-0.10	2.00	1.00	0.045	0.030	17.0-19.0	9.0-13.0		Cb 8 x C to 1.00
ASTM A 376/A 376M-02a	TP347H		S34709	0.04-0.10	2.00	0.75	0.045	0.030	17.0-19.0	9.00-13.0		Cb 8 x C to 1.10
JIS G 3459:1997	SUS347HTP			0.04-0.10	2.00	1.00	0.030	0.030	17.00-20.00	9.00-13.00		Nb 8 x C to 1.00
JIS G 3463:1994	SUS347HTB			0.04-0.10	2.00	1.00	0.030	0.030	17.00-20.00	9.00-13.00		Nb 8 x C to 1.00
JIS G 3467:1988	SUS 347H TF			0.04-0.10	2.00	0.75	0.030	0.030	17.00-20.00	9.00-13.00		Nb 8 x C to 1.00
BS 3605-1:1991 AMD 2:1997	347S51			0.04-0.10	2.00	1.00	0.040	0.030	17.00-19.00	9.00-13.00		Nb 10 x C to 1.20
DIN 17459:1992	X 8 CrNiNb 16 13	1.4961		0.04-0.10	1.5	0.30-0.60	0.035	0.015	15.0-17.0	12.0-14.0		Nb 10 x C to 1.2
AFNOR NF A 49-214:1978	Z 6 CN Nb 18-12 B			0.04-0.08	2.0	1.0	0.035	0.030	17-19	10-13		(Nb+Ta) 8 x C to 1.00
ISO 2604-II:1975	TS 56			0.04-0.10	2.00	0.20-0.80	0.045	0.030	16.00-20.00	11.00-14.00		Nb 10 x C to 1.4
ASTM A 213/A 213M-03a			S31725	0.03	2.00	0.75	0.040	0.030	18.0-20.0	13.5-17.5	4.0-5.00	N 0.10; Cu 0.75
ASTM A 249/A 249M-03			S31725	0.03	2.00	1.00	0.045	0.030	18.0-20.0	13.5-17.5	4.0-5.0	N 0.20
ASTM A 312/A 312M-03			S31725	0.03	2.00	1.00	0.040	0.030	18.0-20.0	13.5-17.5	4.0-5.0	N 0.10; Cu 0.75
ASTM A 358/A 358M-01			S31725	0.030	2.00	0.75	0.045	0.030	18.0-20.0	13.5-17.5	4.0-5.0	N 0.20
ASTM A 376/A 376M-02a			S31725	0.030	2.00	0.75	0.045	0.030	18.0-20.0	13.5-17.5	4.0-5.0	N 0.20; Cu 0.75
ASTM A 409/A 409M-01			S31725	0.030	2.00	1.00	0.045	0.030	18.0-20.0	13.5-17.5	4.0-5.0	N 0.020
DIN 17457:1985	X 2 CrNiMoN 17 13 5	1.4439		0.030				0.025	16.5-18.5	12.5-14.5	4.0-5.0	N 0.12-0.22
DIN 17458:1985	X 2 CrNiMoN 17 13 5	1.4439		0.030				0.025	16.5-18.5	12.5-14.5	4.0-5.0	N 0.12-0.22
AFNOR NF A 49-244:1993	X3CrNiMoN18-14-5			0.030	2.00	0.75	0.035	0.010	17.0-19.0	13.0-15.0	4.0-5.0	N 0.12-0.20
ASTM A 358/A 358M-01			N08904	0.020	2.00	1.00	0.045	0.035	19.0-23.0	23.0-28.0	4.0-5.0	Cu 1.0-2.0; N 0.10
ASTM A 249/A 249M-03			N08904	0.020	2.00	1.00	0.040	0.030	19.0-23.0	23.0-28.0	4.0-5.0	N 0.10; Cu 1.00-2.00
JIS G 3459:1997	SUS890LTP			0.020	2.00	1.00	0.040	0.030	19.00-23.00	23.00-28.00	4.00-5.00	Cu 1.00-2.00
JIS G 3463:1994	SUS890LTB			0.020	2.00	1.00	0.040	0.030	19.00-23.00	23.00-28.00	4.00-5.00	Cu 1.00-2.00
AFNOR NF A 49-244:1993	X2NiCrMoCu25-20			0.020	2.00	0.40	0.035	0.010	19.0-21.0	24.0-26.0	4.0-5.0	Cu 1.00-2.00
ASTM A 240/A 240M-03c	800		N08800	0.10	1.50	1.00	0.045	0.015	19.0-23.0	30.0-35.0		Cu 0.75; Ti 0.15-0.60
JIS G 3467:1988	NCF 800 TF			0.10	1.50	1.00	0.030	0.015	19.00-23.00	30.00-35.00		Cu 0.75; Al 0.15-0.60; Ti 0.15-0.60
DIN 17459:1992	X 5 NiCrAlTi 31 20	1.4958		0.03-0.08	1.5	0.70	0.015	0.010	19.0-22.0	30.0-32.5		Al 0.20-0.50; Ti 0.20-0.50; Al+Ti 0.70;
AFNOR NF A 49-244:1993	X5NiCr32-21			0.05	1.50	0.75	0.035	0.015	19.0-24.0	30.0-33.0		Al 0.15-0.60; Ti 0.15-0.60
DIN 17459:1992	X 8 NiCrAlTi 32 21	1.4959		0.05-0.10	1.5	0.70	0.015	0.010	19.0-22.0	30.0-34.0		Al 0.25-0.65; Ti 0.25-0.65; Co 0.5;
ASTM A 240/A 240M-03c	800H		N08810	0.05-0.10	1.50	1.00	0.045	0.015	19.0-23.0	30.0-35.0		Cu 0.75; Ti 0.15-0.60;
JIS G 3467:1988	NCF 800H TF			0.05-0.10	1.50	1.00	0.030	0.015	19.00-23.00	30.00-35.00		Cu 0.75; Al 0.15-0.60; Ti 0.15-0.60
ASTM A 249/A 249M-03			N08367	0.030	2.00	1.00	0.040	0.030	20.0-22.0	23.5-25.5	6.0-7.0	N 0.18-0.25; Cu 0.75
A3 I WI A 249/A 249/VI-U3			N08926	0.020	2.00	0.50	0.030	0.010	19.0-21.0	24.0-26.0	6.0-7.0	N 0.15-0.25; Cu 0.50-1.50
ASTM A 312/A 312M-03			N08926	0.020	2.00	0.50	0.030	0.010	24.0-26.0	19.0-21.0	6.0-7.0	N 0.15-0.25; Cu 0.50-1.50
ASTM A 688/A 688M-03			N08367	0.030	2.00	1.00	0.040	0.030	20.00-22.00	23.50-25.50	6.00-7.00	N 0.18-0.25; Cu 0.75
A3 I W A 000/A 000WI-03			N08926	0.020	2.00	0.5	0.03	0.01	19.00-21.00	24.00-26.00	6.0-7.0	N 0.15-0.25; Cu 0.5-1.5
JIS G 3463:1994	SUS836LTB			0.030	2.00	1.00	0.040	0.030	19.00-24.00	24.00-26.00	5.00-7.00	N 0.25

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	TP304		S30400	ST			205	30	515	75	35	95 HRB
ASTM A 249/A 249M-03	TP304		S30400	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP304		S30400	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	304		S30400	H, HT, HT-O or HT-SO			205	30	515	75	40	
ASTM A 376/A 376M-02a	TP304			see standard			205	30	515	75	35	
ASTM A 409/A 409M-01	TP304		S30400	H, HT, HT-O or HT-SO			205	30	515	75		
ASTM A 688/A 688M-03	TP304		S30400	SA			205	30	515	75	35	90 HRB max
JIS G 3459:1997	SUS304TP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS304TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3467:1988	SUS 304 TF			ST			205		520		35	
JIS G 3468:1994	SUS304			AM			205		520		35	
BS 3605-1:1991 AMD 2:1997	304S31			ST or HF			230		490-690		35	
BS 3605-2:1992 AMD 1:1997	304S31			AW or ST			230		490-690		35	
DIN 17457:1985	X 5 CrNi 18 10	1.4301		SA & Q	≤ 50		195		500-720		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 5 CrNi 18 10	1.4301		SA & Q	≤ 50		195		500-700		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 28180:1985	X 5 CrNi 18 10	1.4301		SA & Q	≤ 50		195		500-700		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 28181:1985	X 5 CrNi 18 10	1.4301		SA & Q	≤ 50		195		500-720		40 L; 35 T	85 J at RT, L 55 J at RT, T
AFNOR NF A 49-217:1987	TU Z 6 CN 18 09			HF + CR + Q (HY)			200		490-740		45	90 HRB max
				, ,	< 3		215				40	1.00 1-4 10000
AFNOR NF A 49-244:1993	X7CrNi18-9			ST or TT	$3 \le t \le 5$		215		520-720		45	L: 90 J at -196°C T: 70 J at -196°C
					5 < t ≤ 75		205				45	1. 70 J at - 196°C
AFNOR NF A 49-247:1981	TS Z 6 CN 18-09			Q (HY)			215		530-730		40	
ISO 2604-II:1975	TS 47			Q			195		490-690		30	
ISO 2604-V:1978	TW 47			Q			195		490-690		30	

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	TP304L		S30403	ST			170	25	485	70	35	90 HRB
ASTM A 249/A 249M-03	TP304N		S30451	H + RC			240	35	550	80	35	90 HRB max
ASTM A 312/A 312M-03	TP304 L		S30403	HF or CF + A			170	25	485	70	35	
ASTM A 358/A 358M-01	304L		S30403	H, HT, HT-O or HT-SO			170	25	485	70	40	
ASTM A 409/A 409M-01	TP304L		S30403	H, HT, HT-O or HT-SO			170	25	485	70		
JIS G 3459:1997	SUS304LTP			ST			175		480		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS304LTB			ST	10 ≤ O.D. < 20		175		480		30	
					O.D. ≥ 20						35	
JIS G 3468:1994	SUS304L			AM			175		480		35	
BS 3605-1:1990 Issue 2, 1997	304S11			ST or HF			215		480-680		35	
BS 3605-2:1992 AMD 1:1997	304S11			AW or ST			215		480-680		35	
DIN 17457:1985	X 2 CrNi 19 11	1.4306		SA & Q	≤ 50		180		460-680		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 2 CrNi 19 11	1.4306		SA & Q	≤ 50		180		460-680		40 L; 35 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-217:1987	TU Z 2 CN 18 10			HF + CR + Q (HY)			175		470-720		45	90 HRB 100 J at -196°C
					< 3		280				40	
AFNOR NF A 49-244:1993	X3CrNiN18-10			ST or TT	3 ≤ t ≤ 5		280		570-770		45	L: 100 J at -196°C
				,	5 < t ≤ 75		270		1		45	T: 80 J at -196°C
AFNOR NF A 49-247:1981	TS Z 2 CN 18-10			Q (HY)			205		520-720		40	
ISO 2604-II:1975	TS 46			Q			175		490-690		30	
ISO 2604-V:1978	TW 46			Q			175		490-690		30	
ASTM A 213/A 213M-03a	TP304LN		S30453	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP304LN		S30453	H + RC			205	30	515	75	35	90 HRB max
ASTM A 376/A 376M-02a	TP304LN			see standard			205	30	515	75	35	
ASTM A 688/A 688M-03	TP304LN		S30453	SA			205	30	515	75	35	90 HRB max
DIN 17457:1985	X 2 CrNiN 18 10	1.4311		SA & Q	≤ 50		270		550-760		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 2 CrNiN 18 10	1.4311		SA & Q	≤ 50		270		550-760		35 L; 30 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-217:1987	TU Z 2 CN 18 10 AZ						240		550-800		40	

NOTE: This section continued on next page

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Stre	ngth, min	Tensile Str	ength, min	Florestion	
Designation	Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	## Elongation min, % ## 40 ## 45 ## 45 ## 45 ## 40 ## 45 ## 40 ## 35 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 40 ## 35 ## 35 ## 40 ## 35 ## 35 ## 35 ## 35 ## 35 ## 35 ## 35 ## 36 ## 36 ## 36 ## 36 ## 37 ## 30 ## 36 #	Other
					< 3		280				40	L: 100 J at -196°C
	X3CrNiN18-10			ST or TT	3 ≤ t ≤ 5		280		570-770		45	T: 80 J at -196°C
AFNOR NF A 49-244:1993					5 < t ≤ 75		270				45	
AFNOR NF A 49-244: 1993					< 3		300				35	1. 100 1 -1. 10000
	X6CrNiN19-9			ST or TT	3 ≤ t ≤ 5		300		590-790		40	L: 100 J at -196°C
					5 < t ≤ 75		290				40	T: 80 J at -196°C
ASTM A 213/A 213M-03a	TP304H		S30409	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP304H		S30409	ST			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP304H		S30409	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	304H		S30409	H, HT, HT-O or HT-SO			205	30	515	75	40	
ASTM A 376/A 376M-02a	TP304H		S30409	see standard			205	30	515	75	35	
JIS G 3459:1997	SUS304HTP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS304HTB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3467:1988	SUS 304H TF			ST			205		520		35	
BS 3605-1:1990 Issue 2, 1997	304S51			ST or HF			230		490-690		35	
DIN 17459:1992	X 6 CrNi 18 11	1.4948		SHT	≤ 50		185		500-700		40 L; 30 T	L: 90 J at RT T: 60 J at RT
AFNOR NF A 49-214:1978	Z 6 CN 19-10			L or F/H + RC			195		490-690		40	
ISO 2604-II:1975	TS 48			Q			195		490-690		30	
ASTM A 249/A 249M-03			S30615	H + RC			275	40	620	90	35	95 HRB max
AFNOR NF A 49-217:1987	TU Z 1 CNS 18 15			HF + CR + Q (HY)			220		540-740		40	
ASTM A 213/A 213M-03a	TP309S		S30908	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP309S		S30908	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP309S		S30908	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	309S		S30908	H, HT, HT-O or HT-SO			205	30	515	75	40	
JIS G 3459:1997	SUS309STP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS309STB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3468:1994	SUS309S			AM			205		520		35	

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ess	Yield Strength, min		Tensile Strength, min		Flongation	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, % 35 35 35 35 37 30 35 35 35 35 35 35 35 35 35 36 40 35 35 35 35 35 36 40 40 27 30 35 35 35 35 35 35 35 35 35 35 35 35 35	Other
ASTM A 213/A 213M-03a	TP309H		S30909	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP309H		S30909	ST			205	30	515	75		90 HRB max
JIS G 3459:1997	SUS309TP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS309TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
					< 3		240					
AFNOR NF A 49-244:1993	X15CrNi24-13			ST or TT	3 ≤ t ≤ 5		240		540-740		35	
					5 < t ≤ 75		240				min, % 35 35 35 35 37 30 35 30 35 35 35 35 35 35 35 36 37 30 35 35 35 35 35 35 35 35 35 35 35 35 35	
ASTM A 213/A 213M-03a	TP310S		S31008	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP310S		S31008	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP310S		S31008	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	310S		S31008	H, HT, HT-O or HT-SO			205	30	515	75	40	
JIS G 3459:1997	SUS310STP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS310STB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20		1				35	
JIS G 3468:1994	SUS310S			AM			205		520		35	
ASTM A 213/A 213M-03a	TP310H		S31009	ST			205	30	515	75	35	90 HRB
					< 3		205		480-680		35	
AFNOR NF A 49-244:1993	X1CrNi25-20			ST or TT	3 ≤ t ≤ 5		205				40	L: 90 J at -196°C
					5 < t ≤ 75		205				40	T: 70 J at -196°C
					O.D. < 10						27	
JIS G 3463:1994	SUS310TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20		1				35	
JIS G 3467:1988	SUS 310 TF			ST			205		520		35	
ISO 2604-II:1975	TS 68			Q			205		510-710			
AOTA A 040/A 040A 00			004050	50		t ≤ 0.25	270	39	580	84	25	95 HRB max
ASTM A 249/A 249M-03			S31050	H + RC		t > 0.25	255	37	540	78		95 HRB max
AFNOR NF A 49-217:1987	TU Z 1 CND 25 22 AZ			HF + CR + Q (HY)			260		540-740			
			004054	` ,		t ≤ 0.187	310	45	675	98	0.5	400 LIDD
ASTM A 249/A 249M-03			S31254	H + WQ or RC		t > 0.187	300	45	655	95	35	100 HRB max
ACTM A 000/A 000M 55			00405:			t ≤ 0.187	310	45	690	100	35	00 1100
ASTM A 688/A 688M-03			S31254	H + WQ or RC		t > 0.187	310	45	655	95		90 HRB max
AFNOR NF A 49-217:1987	TU Z 1 CNDU 20 18 06 AZ			HF + CR + Q (HY)			300		650-850			

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ss	Yield Stre	ngth, min	Tensile Stre	ength, min	Flongation	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	TP316		S31600	ST			205	30	515	75	35	90
ASTM A 249/A 249M-03	TP316		S31600	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP316		S31600	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	316		S31600	H, HT, HT-O or HT-SO			205	30	515	75	40	
ASTM A 376/A 376M-02a	TP316			see standard			205	30	515	75	35	
ASTM A 409/A 409M-01	TP316		S31600	H, HT, HT-O or HT-SO			205	30	515	75		
ASTM A 688/A 688M-03	TP316		S31600	SA			205	30	515	75	35	90 HRB max
JIS G 3459:1997	SUS316TP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS316TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35 35 35 35 40 35 35 35 27	
JIS G 3467:1988	SUS 316 TF			ST			205		520			
JIS G 3468:1994	SUS316			AM			205		520		35	
	316S31			ST or HF			240		510-710			
BS 3605-1:1990 Issue 2, 1997	316S33			ST or HF			240		510-710		35 35 35 40 35 35 35 35 35 35 35 35 35 35 35 35 35	
	316S31			AW or ST			240		510-710			
BS 3605-2:1992 AMD 1:1997	316S33			AW or ST			240		510-710			
DIN 17457:1985	X 5 CrNiMo 17 12 2	1.4401		SA & Q	≤ 50		205		510-710			L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 5 CrNiMo 17 12 2	1.4401		SA & Q	≤ 50		205		510-710		40 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17457:1985	X 5 CrNiMo17 13 3	1.4436		SA & Q	≤ 50		205		510-710		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 5 CrNiMo17 13 3	1.4436		SA & Q	≤ 50		205		510-710		40 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 28180:1985	X 5 CrNiMo 17 12 2	1.4401		SA & Q	≤ 50		205		510-710		40 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 28181:1985	X 5 CrNiMo 17 12 2	1.4401		SA & Q	≤ 50		205		510-710		40 L; 30 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-217:1987	TU Z 6 CND 17 11			HF + CR + Q (HY)			190		490-740		-	90 HRB max
					< 3		225				-	L: 90 J at -196°C
AFNOR NF A 49-244:1993	X7CrNiMo17-11-2			ST or TT	$3 \le t \le 5$		225		540-740			T: 70 J at -196°C
					5 < t ≤ 75		215					
AFNOR NF A 49-247:1981	TS Z 6 CND 17-11			Q (HY)			225		540-740			
ISO 2604-II:1975	TS 60			Q			205		510-710			
100 2004 11.1070	TS 61			Q			205		510-710			
ISO 2604-V:1978	TW 60			Q			205		510-710		min, % 35 35 35 36 40 35 35 35 35 35 37 30 35 35 35 35 35 35 35 40 L; 35 T 40 L; 30 T	
100 2004 1.1070	TW 61			Q			205		510-710		30	

5.9.2B Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ss	Yield Strer	ngth, min	Tensile Stre	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	TP316L		S31603	ST			170	25	485	70	35	90 HRB
ASTM A 249/A 249M-03	TP316L		S31603	H + RC			170	25	485	70	35	90 HRB max
ASTM A 312/A 312M-03	TP316L		S31603	HF or CF + A			170	25	485	70	35	
ASTM A 358/A 358M-01	316L		S31603	H, HT, HT-O or HT-SO			170	25	485	70	40	
ASTM A 409/A 409M-01	TP316L		S31603	H, HT, HT-O or HT-SO			170	25	485	70		
ASTM A 688/A 688M-03	TP316L		S31603	SA			175	25	485	70	35	90 HRB max
JIS G 3459:1997	SUS316LTP			ST			175		480		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS316LTB			ST	10 ≤ O.D. < 20		175		480		30	
					O.D. ≥ 20						35	
JIS G 3468:1994	SUS316L			AM			175		480		35	
DO 0005 4 4000 bears 0, 4007	316S11			ST or HF			225		490-690		35	
BS 3605-1:1990 Issue 2, 1997	316S13			ST or HF			225		490-690		35	
DO 0005 0 1000 AMD 1 1007	316S11			AW or ST			225		490-690		35	
BS 3605-2:1992 AMD 1:1997	316S13			AW or ST			225		490-690		35	
DIN 17457:1985	X 2 CrNiMo 17 13 2	1.4404		SA & Q	≤ 50		190		490-690		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 2 CrNiMo 17 13 2	1.4404		SA & Q	≤ 50		190		490-690		40 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17457:1985	X 2 CrNiMo 18 14 3	1.4435		SA & Q	≤ 50		190		490-690		40 L; 35 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 2 CrNiMo 18 14 3	1.4435		SA & Q	≤ 50		190		490-690		40 L; 30 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-217:1987	TU Z 2 CND 17 12			HF + CF + Q (HY)			175		470-720		45	90 HRB max
					< 3		215				40	1.00.1.1.40000
	X3CrNiMo17-11-2			ST or TT	$3 \le t \le 5$		215		510-710		45	L: 90 J at -196°C
					5 < t ≤ 75		205				45	T: 70 J at -196°C
					< 3		215				40	1 . 00 1 -1 . 10000
AFNOR NF A 49-244:1993	X3CrNiMo17-12-3			ST or TT	3 ≤ t ≤ 5		215		510-710		45	L: 90 J at -196°C
AFNOR NF A 49-244: 1993					5 < t ≤ 75		205				45	T: 70 J at -196°C
					< 3		215				40	1.00 1.4 4000
	X3CrNiMo18-12-3			ST or TT	3 ≤ t ≤ 5		215		510-710		45	L: 90 J at -196°C
				010111	5 < t ≤ 75		205		1		45	T: 70 J at -196°C
	TU Z 2 CND 18 14			HF + CF + Q (HY)			210		490-690		45	
AFNOR NF A 49-247:1981	TS Z 2 CND 17-12			Q (HY)			215		520-720		40	
ISO 2604-II:1975	TS 57			Q			185		490-690		30	
130 2004-11.19/5	TS 58			Q			185		490-690		30	
ISO 2604-V:1978	TW 57			Q			185		490-690		30	
130 2004-1.1970	TW 58			Q			185		490-690		30	

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ss	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	TP316LN		S31653	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP316LN		S31653	H + RC			205	30	515	75	35	90 HRB max
ASTM A 376/A 376M-02a	TP316LN			see standard			205	30	515	75	35	
ASTM A 688/A 688M-03	TP316LN		S31653	SA			205	30	515	75	35	90 HRB max
DIN 17457:1985	X 2 CrNiMoN 17 13 3	1.4429		SA & Q	≤ 50		295		580-800		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 2 CrNiMoN 17 13 3	1.4429		SA & Q	≤ 50		295		580-800		35 L; 30 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-217:1987	TU Z 2 CND 17 12 AZ			HF + CF + Q (HY)			280		600-800		40	
					< 3		290				35	1.100 1-4 10000
	X3CrNiMoN17-11			ST or TT	3 ≤ t ≤ 5		290		590-790		40	L: 100 J at -196°C T: 80 J at -196°C
AFNOR NF A 49-244:1993					5 < t ≤ 75		290				40	1. 60 J at -196 C
AFNOR NF A 49-244.1993					< 3		290				35	L: 100 J at -196°C
	X3CrNiMoN17-12			ST or TT	$3 \le t \le 5$		290		590-790		40	T: 80 J at -196°C
					5 < t ≤ 75		290				40	1. 60 J at -196 C
ASTM A 213/A 213M-03a	TP316H		S31609	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP316H		S31609	ST			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP316H		S31609	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	316H		S31609	H, HT, HT-O or HT-SO			205	30	515	75	40	
ASTM A 376/A 376M-02a	TP316H		S31609	see standard			205	30	515	75	35	
JIS G 3459:1997	SUS316HTP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS316HTB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3467:1988	SUS 316H TF			ST			205		520		35	
BS 3605-1:1990 Issue 2, 1997	316S51			ST or HF			240		510-710		35	
DIN 17459:1992	X 6 CrNiMo 17 13	1.4919		SHT	≤ 50		205		490-690		35 L; 30 T	L: 90 J at RT T: 60 J at RT
AFNOR NF A 49-214:1978	Z 6 CND 17-12 B			L or F/H + RC			195		490-690		40	
ISO 2604-II:1975	TS 63			Q			205		510-710		30	
BS 3605-1:1990 Issue 2, 1997	316S52			ST or HF			240		510-710		35	
DIN 17459:1992	X 3 CrNiMoN 17 13	1.4910		SHT	≤ 50		260		550-750		35 L; 30 T	L: 120 J at RT T: 80 J at RT

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ss	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3459:1997	SUS316TiTP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS316TiTB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
DIN 17457:1985	X 6 CrNiMoTi 17 12 2	1.4571		SA & Q	≤ 50		210		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 6 CrNiMoTi 17 12 2	1.4571		SA & Q	≤ 50		210		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIIV 17430.1300	X O GINIMOTI I7 12 2	1.4371		OA & Q	≤ 50		190		490-690		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 28180:1985	X 6 CrNiMoTi 17 12 2	1.4571		SA & Q	≤ 50		210		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIIV 20100.1300	X O OHVIIWOTI TY 12 Z	1.4371		SA & Q	≤ 50		190		490-690		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 28181:1985	X 6 CrNiMoTi 17 12 2	1.4571		SA & Q	≤ 50		210		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-214:1978	Z 8 CNDT 17-13 B			L or F/H + RC			195		540-740		40	
					< 3		225				35	L: 90 J at -196°C
AFNOR NF A 49-244:1993	X6CrNiMo17-11-2			ST or TT	$3 \le t \le 5$		225		540-740		40	T: 70 J at -196°C
					5 < t ≤ 75		215				40	
ASTM A 213/A 213M-03a	TP317		S31700	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP317		S31700	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP317		S31700	HF or CF + A			205	30	515	75	35	
ASTM A 409/A 409M-01	TP317		S31700	H, HT, HT-O or HT-SO			205	30	515	75		
JIS G 3459:1997	SUS317TP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS317TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3468:1994	SUS317			AM			205		520		35	
ASTM A 213/A 213M-03a	TP317L		S31703	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP317L		S31703	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP317L		S31703	HF or CF + A			205	30	515	75	35	
JIS G 3459:1997	SUS317LTP			ST			175		480		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS317LTB			ST	10 ≤ O.D. < 20		175		480		30	
					O.D. ≥ 20		7				35	
JIS G 3468:1994	SUS317L			AM			175		480		35	

NOTE: This section continued on next page

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thicknes	ss	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
					< 3		215				40	1 . 00 1 -1 40000
AFNOR NF A 49-244:1993	X3CrNiMo19-15-4			ST or TT	3 ≤ t ≤ 5		215		510-710		45	L: 90 J at -196°C
					5 < t ≤ 75		205				45	T: 70 J at -196°C
AFNOR NF A 49-247:1981	TS Z 2 CND 19-15			Q (HY)			225		520-720		35	
ASTM A 213/A 213M-03a	TP321		S32100	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP321		S32100	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP321 Seamless		S32100	Α		≤ 3/8	205	30	515	75	35	
ASTM A 358/A 358M-01	321		S32100	H, HT, HT-O or HT-SO			205	30	515	75	40	
ASTM A 376/A 376M-02a	TP321			see standard		≤ 3/8	205	30	515	75	35	
ASTM A 409/A 409M-01	TP321		S32100	H, HT, HT-O or HT-SO			205	30	515	75		
JIS G 3459:1997	SUS321TP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS321TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20		1				35	
JIS G 3467:1988	SUS 321 TF			ST			205		520		35	
JIS G 3468:1994	SUS321			AM			205		520		35	
BS 3605-1:1990 Issue 2, 1997	321S31			ST or HF			235		510-710		35	
BS 3605-2:1992 AMD 1:1997	321S31			AW or ST			235		510-710		35	
DIN 17457:1985	X 6 CrNiTi 18 10	1.4541		SA & Q	≤ 50		200		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 6 CrNiTi 18 10	1.4541		SA & Q	≤ 50		200		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17436.1963	X 6 CINITI 18 10	1.4541		SA & Q	≤ 50		180		460-680		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 28180:1985	X 6 CrNiTi 18 10	1.4541		SA & Q	≤ 50		200		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIIV 20100.1903	X 0 OINITI 10 10	1.4541		SA & Q	≤ 50		180		460-680		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 28181:1985	X 6 CrNiTi 18 10	1.4541		SA & Q	≤ 50		200		500-730		35 L; 30 T	L: 85 J at RT T: 55 J at RT
AFNOR NF A 49-217:1987	TU Z 6 CNT 18 10			HF + CR + Q (HY)			190		490-740		45	90 HRB max
					< 3		220				35	L: 90 J at -196°C
AFNOR NF A 49-244:1993	X6CrNiTi18-10			ST or TT	$3 \le t \le 5$		220		530-730		40	T: 70 J at -196°C
					5 < t ≤ 75		210				40	1.700 at -130 C
AFNOR NF A 49-247:1981	TS Z 6 CNT 18-10			Q (HY)			220		530-730		35	
ISO 2604-II:1975	TS 53			Q			195		510-710		30	
ISO 2604-V:1978	TW 53			Q			195		510-710		30	

5.9.2B Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thicknes	s	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 213/A 213M-03a	TP321H		S32109	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP321H		S32109	ST			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP321H Welded		S32109	HF or CF + A			205	30	515	75	35	
ASTM A 376/A 376M-02a	TP321H		C20100	oo o otondord		≤ 3/8	205	30	515	75	35	
ASTIVI A 376/A 376W-02a	1132111		S32109	see standard		> 3/8	170	25	480	70	35	
JIS G 3459:1997	SUS321HTP			CF or HF + ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS321HTB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3467:1988	SUS 321H TF			CF or HF,ST			205		520		35	
BS 3605-1:1990 Issue 2, 1997	321S51			ST or HF			235		510-710		35	
AFNOR NF A 49-214:1978	Z 6 CNT 18-12 B			L or F/H + RC			195		490-690		40	
ISO 2604-II:1975	TS 54			Q			155		490-690		30	
					O.D. < 10						10	
JIS G 3463:1994	SUS329J3LTB			ST	10 ≤ O.D. < 20		450		620		13	
					O.D. ≥ 20						18	
AFNOR NF A 49-217:1987	TU Z 2 CND 22 05 03			HF + CR + Q (HY)			450		680-880		25	
					O.D. < 10						10	
JIS G 3463:1994	SUS329J4LTB			ST	10 ≤ O.D. < 20		450		620		13	
					O.D. ≥ 20						18	
AFNOR NF A 49-217:1987	TU Z 2 CND 25 07 03			HF + CR + Q (HY)			450		700-900		25	
ASTM A 213/A 213M-03a	TP347		S34700	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP347		S34700	H + RC			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP347		S34700	HF or CF + A			205	30	515	75	35	
ASTM A 358/A 358M-01	347		S34700	H, HT, HT-O or HT-SO			205	30	515	75	40	
ASTM A 376/A 376M-02a	TP347		S34700	see standard			205	30	515	75	35	
ASTM A 409/A 409M-01	TP347		S34700	H, HT, HT-O or HT-SO			205	30	515	75		
JIS G 3459:1997	SUS347TP			ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS347TB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3467:1988	SUS 347 TF			ST			205		520		35	
JIS G 3468:1994	SUS347			AM			205		520		35	
BS 3605-1:1990 Issue 2, 1997	347S31			ST or HF			240		510-710		35	
BS 3605-2:1990 Issue 2, 1997	347S31			ST			240		510-710		35	

NOTE: This section continued on next page

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thicknes	SS	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
DIN 17457:1985	X 6 CrNiNb 18 10	1.4550		SA & Q	≤ 50		205		510-740		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 6 CrNiNb 18 10	1.4550		SA & Q	≤ 50		205		510-740		35 L; 30 T	L: 85 J at RT T: 55 J at RT
ISO 2604-II:1975	TS 50			Q			205		510-710		30	
ISO 2604-V:1978	TW 50			Q			205		510-710		30	
ASTM A 213/A 213M-03a	TP347H		S34709	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03	TP347H		S34709	ST			205	30	515	75	35	90 HRB max
ASTM A 312/A 312M-03	TP347H		S34709	HF or CF + A			205	30	515	75	35	
ASTM A 376/A 376M-02a	TP347H		S34709	see standard			205	30	515	75	35	
JIS G 3459:1997	SUS347HTP			CF or HF + ST			205		520		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS347HTB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	
JIS G 3467:1988	SUS 347H TF			CF or HF, ST			205		520		35	
BS 3605-1:1990 Issue 2, 1997	347S51			ST or HF			240		510-710		35	
DIN 17459:1992	X 8 CrNiNb 16 13	1.4961		SHT	≤ 50		205		510-690		35 L; 22 T	65 J at RT, L 45 J at RT, T
AFNOR NF A 49-214:1978	Z 6 CN Nb 18-12 B			L or F/H + RC			195		490-690		40	
ISO 2604-II:1975	TS 56			Q			205		510-710		30	
ASTM A 213/A 213M-03a			S31725	ST			205	30	515	75	35	90 HRB
ASTM A 249/A 249M-03			S31725	ST			205	30	515	75	35	90 HRB
ASTM A 312/A 312M-03			S31725	SA			205	30	515	75		
ASTM A 358/A 358-01			S31725	see standard			205	30	515	75		
ASTM A 376/A 376M-02a			S31725	HT			205	30	515	75	35	
ASTM A 409/A 409M-01			S31725	H, HT, HT-O or HT-SO			205	30	515	75		
DIN 17457:1985	X 2 CrNiMoN 17 13 5	1.4439		SA & Q	≤ 50		285		580-800		35 L; 30 T	L: 85 J at RT T: 55 J at RT
DIN 17458:1985	X 2 CrNiMoN 17 13 5	1.4439		SA & Q	≤ 50		285		580-800		35 L; 30 T	L: 85 J at RT T: 55 J at RT
					< 3		290				35	
AFNOR NF A 49-244:1993	X3CrNiMoN18-14-5			ST or TT	3 ≤ t ≤ 5		290		580-780		40	L: 100 J at -196°C
-INON INF A 49-244:1993					5 < t ≤ 75		280				40	T: 80 J at -196°C

Mechanical Properties of Austenitic Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickne	ss	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 358/A 358M-01			N08904	H, HT, HT-O or HT-SO			220	31	490	71	35	
ASTM A 249/A 249M-03			N08904	H + WQ or RC			215	31	490	71	35	90 HRB max
JIS G 3459:1997	SUS890LTP			ST			215		490		35	
					O.D. < 10						27	
JIS G 3463:1994	SUS890LTB			ST	10 ≤ O.D. < 20		215		490		30	
					O.D. ≥ 20						35	
					< 3		230				30	1.00 -1.10000
AFNOR NF A 49-244:1993	X2NiCrMoCu25-20			ST or TT	$3 \le t \le 5$		230		530-730		35	L: 90 J at -196°C T: 70 J at -196°C
					5 < t ≤ 75		230				35	1: 70 J at -196°C
ASTM A 240/A 240M-03c	800		N08800				205	30	520	75	30	
UC C 0467-1000	NCF 800 TF			CF, A			205		520		30	
JIS G 3467:1988	NCF 800 IF			HF, A			175		450		30	
DIN 17450-1000	X 5 NiCrAlTi 31 20 RK	1.4958 RK		A/R	≤ 50		210		500-750		35 L; 30 T	L: 120 J at RT T: 80 J at RT
DIN 17459:1992	X 5 NiCrAlTi 31 20	1.4958		SHT	≤ 50		170		500-750		35 L; 30 T	L: 120 J at RT T: 80 J at RT
					< 3		200				25	
AFNOR NF A 49-244:1993	X5NiCr32-21			ST or TT	3 ≤ t ≤ 5		200		490-690		30	
					5 < t ≤ 75		200		1		30	
DIN 17459:1992	X 8 NiCrAlTi 32 21	1.4959		SHT	≤ 50		170		500-750		35 L; 30 T	L: 120 J at RT T: 80 J at RT
ASTM A 240/A 240M-03c	800H		N08810				170	25	450	65	30	
JIS G 3467:1988	NCF 800H TF			S			175		450		30	
			NOOCT	SA		t ≤ 0.187	310	45	690	100	30	100 HRB max
ASTM A 249/A 249M-03			N08367	SA		t > 0.187	310	45	655	95	30	100 HRB max
			N08926	SA			295	43	650	94	35	100 HRB max
ASTM A 312/A 312M-03			N08926	HT			295	43	650	94	35	
			NOOOOT	0.4		t ≤ 0.187	310	45	655	95	30	
ASTM A 688/A 688M-03			N08367	SA		t > 0.187	310	45	655	95	30	100 HRB max
			N08926	SA			295	43	650	94	35	
				-	O.D. < 10					 -	27	
JIS G 3463:1994	SUS836LTB			ST	10 ≤ O.D. < 20		205		520		30	
					O.D. ≥ 20						35	

5.10 Line Pipe Steels

5.10.1A Mechanical Properties of Line Pipe Steels Without Notch Toughness Requirements

Standard	Crade Class Trus	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	Flowwation	
Designation	Grade, Class, Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
API 5L-2004	A25 Class I - PSL 1 A25 Class II - PSL 1			see standard			172	25	310	45	see standard	
ISO 3183-1:1996	L175, Class I L175, Class I			see standard			175		315		27	
API 5L-2004	A - PSL 1			see standard			207	30	331	48	see standard	
EN 10208-1:1997	L210GA	1.0319		see standard			210		335-475		25	
ISO 3183-1:1996	L210			see standard			210		335		25	
API 5L-2004	B - PSL 1			see standard			241	35	414	60	see standard	
CSA Z245.1-2002	241 - Category I			see standard			241-495		414-760		see standard	
EN 10208-1:1997	L245GA	1.0459		see standard			245		415-555		22	
ISO 3183-1:1996	L245			see standard			245		415		21	
API 5L-2004	X42 - PSL 1			see standard			290	42	414	60	see standard	
CSA Z245.1-2002	290 - Category I			see standard			290-495		414-760		see standard	
EN 10208-1:1997	L290GA	1.0483		see standard			290		415-555		21	
ISO 3183-1:1996	L290			see standard			290		415		21	
API 5L-2004	X46 - PSL 1			see standard			317	46	434	63	see standard	
CSA Z245.1-2002	317 - Category I			see standard			317		434		see standard	
ISO 3183-1:1996	L320			see standard			320		435		20	
API 5L-2004	X52 - PSL 1			see standard			359	52	455	66	see standard	
CSA Z245.1-2002	359 - Category I			see standard			359-530		455-760		see standard	
EN 10208-1:1997	L360GA	1.0499		see standard			360		460-620		20	
ISO 3183-1:1996	L360			see standard			360		460		19	
API 5L-2004	X56 - PSL 1			see standard			386	56	490	71	see standard	
CSA Z245.1-2002	386 - Category I			see standard			386-540		490-760		see standard	
ISO 3183-1:1996	L390			see standard			390		490		18	
API 5L-2004	X60 - PSL 1			see standard			414	60	517	75	see standard	
CSA Z245.1-2002	414 - Category I			see standard			414-565		517-760		see standard	
ISO 3183-1:1996	L415			see standard			415		520		17	
API 5L-2004	X65 - PSL 1			see standard			448	65	531	77	see standard	
CSA Z245.1-2002	448 - Category I			see standard			448-600		531-760		see standard	
ISO 3183-1:1996	L450			see standard			450		535		17	
API 5L-2004	X70 - PSL 1			see standard			483	70	565	82	see standard	
CSA Z245.1-2002	483 - Category I			see standard			483-620		565-760		see standard	
ISO 3183-1:1996	L485			see standard			485		570		16	
CSA Z245.1-2002	550 - Category I			see standard			550-690		620-830		see standard	
ISO 3183-1:1996	L555			see standard			555		625-825		15	27 J at 0°C see standard

5.10 Line Pipe Steels

5.10.1B Chemical Composition of Line Pipe Steels Without Notch Toughness Requirements

Standard	Grade, Class, Type,	Steel	UNS				We	ight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	A25, Class I, PSL 1 seamless			0.21	0.60		0.030	0.030				
API 5L-2004	A25, Class II, PSL 1 seamless			0.21	0.60		0.045-0.080	0.030				
AFI 3L-2004	A25, Class I, PSL 1 welded			0.21	0.60		0.030	0.030				
	A25, Class II, PSL 1 welded			0.21	0.60		0.045-0.080	0.030				
	L175, Class I S/NE/CE*			0.21	0.30-0.60		0.030	0.030				see standard
ISO 3183-1:1996	L175, Class II S/NE/CE*			0.21	0.30-0.60		0.045-0.080	0.030				see standard
130 3163-1.1990	L175, Class I W/EW/CW*			0.21	0.30-0.60		0.030	0.030				see standard
	L175, Class II W/EW/CW*			0.21	0.30-0.60		0.045-0.080	0.030				see standard
API 5L-2004	A, PSL 1 seamless			0.22	0.90		0.030	0.030				
AT 1 3E 2004	A, PSL 1 welded			0.22	0.90		0.030	0.030				
EN 10208-1:1997	L210GA	1.0319		0.21	0.90	0.40	0.030	0.030				AL 0.015-0.060; Nb+V+Ti 0.15
ISO 3183-1:1996	L210 S/NE/CE*			0.22	0.90		0.030	0.030				see standard
130 3103-1.1990	L210 W/NE/CE*			0.21	0.90		0.030	0.030				see standard
API 5L-2004	B, PSL 1 seamless			0.28	1.20		0.030	0.030				Cb+V 0.03; Ti 0.04; Cb+V+Ti 0.15
API 5L-2004	B, PSL 1 welded			0.26	1.20		0.030	0.030				Cb+V 0.03; Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	241 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
EN 10208-1:1997	L245GA	1.0459		0.20	1.15	0.40	0.030	0.030				AL 0.015-0.060; Nb+V+Ti 0.15
ISO 3183-1:1996	L245 S/NE/CE*			0.27	1.15		0.030	0.030				see standard
130 3103-1.1990	L245 W/NE/CE*			0.26	1.15		0.030	0.030				see standard
API 5L-2004	X 42, PSL 1 seamless			0.28	1.30		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
AFI 3L-2004	X 42, PSL 1 welded			0.26	1.30		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	290 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
EN 10208-1:1997	L290GA	1.0483		0.20	1.40	0.40	0.030	0.030				AL 0.015-0.060; Nb+V+Ti 0.15
	L290 S/NE*			0.29	1.25		0.030	0.030				see standard
ISO 3183-1:1996	L290 S/CE*			0.29	1.25		0.030	0.030				see standard
	L290 W/NE/CE*			0.28	1.25		0.030	0.030				see standard

^{*:} See "Heat Treatment Terms" table at the beginning of the chapter.

5.10 Line Pipe Steels

5.10.1B Chemical Composition of Line Pipe Steels Without Notch Toughness Requirements (Continued)

Standard	Grade, Class, Type,	Steel	UNS				W	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ADI EL 0004	X46, PSL 1 seamless			0.28	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
API 5L-2004	X46, PSL 1 welded			0.26	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	317 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
	L320, S/NE*			0.31	1.35		0.030	0.030				see standard
ISO 3183-1:1996	L320 S/CE*			0.29	1.25		0.030	0.030				see standard
130 3103-1.1990	L320 W/NE*			0.30	1.25		0.030	0.030				see standard
	L320 W/CE*			0.28	1.25		0.030	0.030				see standard
API 5L-2004	X52, PSL 1 seamless			0.28	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
API 5L-2004	X52, PSL 1 welded			0.26	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	359 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
EN 10208-1:1997	L360GA	1.0499		0.22	1.45	0.55	0.030	0.030				AL 0.015-0.060; Nb+V+Ti 0.15
	L 360 S/NE*			0.31	1.35		0.030	0.030				see standard
ISO 3183-1:1996	L360 S/CE*			0.29	1.25		0.030	0.030				see standard
150 3163-1:1996	L360 W/NE*			0.30	1.25		0.030	0.030				see standard
	L360 W/CE*			0.28	1.25		0.030	0.030				see standard
API 5L-2004	X56, PSL 1 seamless			0.28	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
API 5L-2004	X56, PSL 1 welded			0.26	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	386 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
ISO 3183-1:1996	L390, S/NE/CE*			0.26	1.35		0.030	0.030				see standard
130 3103-1.1990	L390, W/NE/CE*			0.26	1.35		0.030	0.030				see standard
API 5L-2004	X60, PSL 1 seamless			0.28	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
AFI 3L-2004	X60, PSL 1 welded			0.26	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	414 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
ISO 3183-1:1996	L415 S/NE/CE*			0.26	1.35		0.030	0.030				see standard
130 3103-1.1990	L415 W/NE/CE*			0.26	1.35		0.030	0.030				see standard
API 5L-2004	X65, PSL 1 seamless			0.28	1.40		0.030	0.030				Ti 0.06; Cb+V+Ti 0.15
AL 1 JL-2004	X65, PSL 1 welded			0.26	1.45		0.030	0.030				Ti 0.06; Cb+V+Ti 0.15
CSA Z245.1-2002	448 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
ISO 3183-1:1996	L450 S/NE/CE*								by agree	ment		
100 0100-1.1330	L450 W/NE/CE*			0.26	1.40		0.030	0.030				see standard

^{*:} See "Heat Treatment Terms" table at the beginning of the chapter.

5.10 Line Pipe Steels

5.10.1B Chemical Composition of Line Pipe Steels Without Notch Toughness Requirements (Continued)

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
API 5L-2004	X70, PSL 1 seamless			0.28	1.40		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
AFI 5L-2004	X70, PSL 1 welded			0.26	1.65		0.030	0.030				Ti 0.04; Cb+V+Ti 0.15
CSA Z245.1-2002	483 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
SO 3183-1:1996	L485, S/NE/CE*								by agree	ment		
150 3183-1.1996	L485 W/NE/CE*			0.23	1.60		0.030	0.030				see standard
CSA Z245.1-2002	550 - Category I			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001 CE 0.40 (see standard)
SO 3183-1:1996	L555 S/NE/CE*								by agree	ment		
	L555 W/NE/CE*			0.18	1.80		0.030	0.030				see standard

^{*:} See "Heat Treatment Terms" table at the beginning of the chapter.

5.10 Line Pipe Steels

5.10.2A Mechanical Properties of Line Pipe Steels With Notch Toughness Requirements

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thic	kness	Yield Strei	ngth, min	Tensile Stre	ength, min	Florestion	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
ASTM A 1005/A 1005M-00	35						240-450	35-65	415	60	see standard	see standard
API 5L-2004	B - PSL 2			see standard			241-448	35-65	414-758	60-110	see standard	L: 41 J at 0°C; T: 27 J at 0°C see standard
CSA Z245.1-2002	241 - Category II or III			see standard			241-495		414-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
ASTM A 984/A 984M-03	35			see standard		NPS < 8	240	35	415	60	see standard	see standard
A3 1 W A 964/A 964 W-03	33			See Standard		NPS ≤ 8	240-450	35-65	415	00	See Staridard	see standard
EN 10208-2:1996	L245NB L245MB	1.0457 1.0418		see standard			245-440		415		22	see standard
ISO 3183-2:1996	L245NB L245MB			see standard			245-440		415		22	see standard
API 5L-2004	X42 - PSL 2			see standard			290-496	42-72	414-758	60-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard
CSA Z245.1-2002	290 - Category II or III			see standard			290-495		414-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
EN 10208-2:1996	L290NB L290MB	1.0484 1.0429		see standard			290-440		415		21	see standard
ISO 3183-2:1996	L290NB L290MB			see standard			290-440		415		21	see standard
API 5L-2004	X46 - PSL 2			see standard			317-524	46-76	434-758	63-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard;
CSA Z245.1-2002	317 - Category II or III			see standard			317		434		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard

5.10 Line Pipe Steels

5.10.2A Mechanical Properties of Line Pipe Steels With Notch Toughness Requirements (Continued)

Standard	Crade Class Type	Steel	UNS	Product Form/	Thicl	kness	Yield Strei	ngth, min	Tensile Stre	ength, min	Florestion	
Designation	Grade, Class, Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
API 5L-2004	X52 - PSL 2			see standard			359-531	52-77	455-758	66-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard
CSA Z245.1-2002	359 - Category II or III			see standard			359-530		455-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
	L360NB	1.0582										
EN 10208-2:1996	L360QB	1.8948		see standard			360-510		460		20	see standard
	L360MB	1.0578										
	L360NB											
ISO 3183-2:1996	L360QB			see standard			360-510		460		20	see standard
	L360MB											
ASTM A 984/A 984M-03	50		se	see standard		NPS < 8	345	50	485	70	and atomdord	and atomical
ASTIVI A 964/A 964IVI-03	50			see standard		NPS ≤ 8	345-530	50-77	465	70	see standard	see standard
API 5L-2004	X56 - PSL 2			see standard			386-544	56-79	490-758	71-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard
CSA Z245.1-2002	386 - Category II or III			see standard			386-540		490-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
API 5L-2004	X60 - PSL 2			see standard			414-565	60-82	517-758	75-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard
CSA Z245.1-2002	414 - Category II or III			see standard			414-565		517-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
ASTM A 1005/A 1005M-00	60						415-550	60-80	515	75	see standard	see standard
	L415NB	1.8972										
EN 10208-2:1996	L415QB	1.8947		see standard			415-565		520		18	see standard
	L415MB	1.8973										
	L415NB											
ISO 3183-2:1996	L415QB			see standard			415-565		520		18	see standard
	L415MB											

5.10 Line Pipe Steels

5.10.2A Mechanical Properties of Line Pipe Steels With Notch Toughness Requirements (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thic	kness	Yield Strei	ngth, min	Tensile Stre	ength, min	Elemention	
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
API 5L-2004	X65 - PSL 2			see standard			448-600	65-87	531-758	77-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard
CSA Z245.1-2002	448 - Category II or III			see standard			448-600		531-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
ASTM A 984/A 984M-03	60			see standard		NPS < 8	415	60	515	75	see standard	see standard
A3 1 W A 964/A 964 W-03	60			See Standard		NPS ≤ 8	415-550	60-80	313	/5	see standard	see standard
EN 10208-2:1996	L450QB	1.8952		see standard			450-570		535		18	see standard
LIV 10208-2.1990	L450MB	1.8975		See Standard			430-370		555		10	see standard
ISO 3183-2:1996	L450QB L450MB			see standard			450-570		535		18	see standard
API 5L-2004	X70 - PSL 2			see standard			483-621	70-90	565-758	82-110	see standard	L: 41 J at 0°C; T: 27J at 0°C see standard
CSA Z245.1-2002	483 - Category II or III			see standard			483-620		565-760		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
ASTM A 1005/A 1005M-00	70						485-600	70-87	550	80	see standard	see standard
EN 10208-2:1996	L485QB L485MB	1.8955 1.8977		see standard			485-605		570		18	see standard
ISO 3183-2:1996	L485QB L485MB			see standard			485-605		570		18	see standard
ASTM A 984/A 984M-03	80			see standard		NPS < 8	550	80	620	90	see standard	see standard
ASTIVI A 964/A 964WI-03	80			see standard		NPS ≤ 8	550-670	80-97	620	90	see standard	see standard
CSA Z245.1-2002	550 - Category II or III			see standard			550-690		620-830		see standard	OD < 457 mm: 27 J at temp OD ≥ 457 mm: 40 J at temp see standard
API 5L-2004	X80 - PSL 2			see standard			552-690	80-100	621-827	90-120	see standard	L: 101 J at 0°C; T: 68 J at 0°C see standard
EN 10208-2:1996	L555QB	1.8957		see standard			555-675		625		18	see standard
EN 10206-2.1990	L555MB	1.8978		see standard			570-000		020		10	see standard
ISO 3183-2:1996	L555QB L555MB			see standard			555-675		625		18	see standard
ASTM A 1005/A 1005M-00	80						550-670	80-97	620	90	see standard	see standard

5.10 Line Pipe Steels

5.10.2B Chemical Composition of Line Pipe Steels With Notch Toughness Requirements

Standard	Grade, Class, Type,	Steel	UNS					Weight	t, %, max,	Unless O	therwise	Specified
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 1005/A 1005M-00	35			0.16								B 0.0007; CE 0.40 (see standard)
API 5L-2004	B, PSL 2 seamless			0.24	1.20		0.025	0.015				Cb+V+Ti 0.15; Cb+V 0.06; Ti 0.04
API 5L-2004	B, PSL 2 welded			0.22	1.20		0.025	0.015				Cb+V+Ti 0.15; Cb+V 0.06; Ti 0.04
CSA Z245.1-2002	241 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
ASTM A 984/A 984M-03	35			0.22			0.025	0.015				B 0.0007; CE 0.40 (see standard)
EN 10208-2:1996	L245NB seamless and welded	1.0457		0.16	1.1	0.40	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Al:N ≥ 2; CEV 0.42 (see standard)
LN 10200-2.1990	L245MB welded	1.0418		0.16	1.5	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; V 0.04; Nb 0.04; Al:N ≥ 2; CEV 0.40 (see standard)
ISO 3183-2:1996	L245NB seamless and welded			0.16	1.1	0.40	0.025	0.020	0.30	0.30	0.10	AI 0.015-0.060; N 0.0012; Cu 0.25; AI:N ≥ 2; CEV 0.42 (see standard)
150 3163-2.1996	L245MB welded			0.16	1.5	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; V 0.04; Nb 0.04; Al:N ≥ 2; CEV 0.40 (see standard)
API 5L-2004	X 42, PSL 2 seamless			0.24	1.30		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
API 5L-2004	X 42, PSL 2 welded			0.22	1.30		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
CSA Z245.1-2002	290 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
EN 10208-2:1996	L290NB seamless and welded	1.0484		0.17	1.2	0.40	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Nb 0.05; Al:N ≥ 2; CEV 0.42 (see standard)
EN 10206-2.1990	L290MB welded	1.0429		0.16	1.5	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; V 0.04; Nb 0.04; Al:N ≥ 2; CEV 0.40 (see standard)
ISO 3183-2:1996	L290NB seamless and welded			0.17	1.2	0.40	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Nb 0.05; Al:N ≥ 2; CEV 0.42 (see standard)
130 3163-2.1996	L290MB welded			0.16	1.5	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; V 0.04; Nb 0.04; Al:N ≥ 2; CEV 0.40 (see standard)
API 5L-2004	X46, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
AFI 3L-2004	X46, PSL 2 welded			0.22	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
CSA Z245.1-2002	317 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)

5.10 Line Pipe Steels

5.10.2B Chemical Composition of Line Pipe Steels With Notch Toughness Requirements (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weight	t, %, max,	, Unless C	therwise	Specified
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
API 5L-2004	X52, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
AFI 5L-2004	X52, PSL 2 welded			0.22	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
CSA Z245.1-2002	359 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
	L360NB seamless and welded	1.0582		0.20	1.6	0.45	0.025	0.020	0.30	0.30	0.30 CEV 0.45 (see standard) Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Al:N ≥ 2; CEV 0.42 (see standard) Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Al:N ≥ 2; CEV 0.42 (see standard)	
EN 10208-2:1996	L360QB seamless	1.8948		0.16	1.4	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Nb 0.05; Al:N ≥ 2; CEV 0.42 (see standard)
	L360MB welded	1.0578		0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Nb 0.05; Al:N ≥ 2; CEV 0.41 (see standard)
	L360NB seamless and welded			0.20	1.6	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.10; Nb 0.05; Al:N ≥ 2; CEV 0.45 (see standard)
ISO 3183-2:1996	L360QB seamless			0.16	1.4	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Nb 0.05; Al:N ≥ 2; Nb+V+Ti 0.15; CEV 0.42 (see standard)
	L360MB welded			0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Ti 0.04; V 0.05; Nb 0.05; Al:N ≥ 2; CEV 0.41 (see standard)
ASTM A 984/A 984M-03	50			0.22			0.025	0.015				B 0.0007; CE 0.40 (see standard)
API 5L-2004	X56, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
AF1 3L-2004	X56, PSL 2 welded			0.22	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
CSA Z245.1-2002	386 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)

5.10 Line Pipe Steels

5.10.2B Chemical Composition of Line Pipe Steels With Notch Toughness Requirements (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weigh	t, %, max	, Unless C	therwise	Specified
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
API 5L-2004	X60, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
AFI 5L-2004	X60, PSL 2 welded			0.22	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.04
CSA Z245.1-2002	414 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
ASTM A 1005/A 1005M-00	60			0.16								B 0.0007; CE 0.40 (see standard)
	L415NB seamless and welded	1.8972		0.21	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.04; V 0.15; Nb 0.05; Al:N ≥ 2; CEV by agreement (see standard)
EN 10208-2:1996	L415QB seamless	1.8947		0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.04; V 0.08; Nb 0.05; Al:N ≥ 2; CEV 0.43 (see standard)
	L415MB welded	1.8973		0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.08; Nb 0.05; Al:N ≥ 2; CEV 0.42 (see standard)
	L415NB seamless and welded			0.21	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.04; V 0.15; Nb 0.05; Al:N ≥ 2; CEV by agreement (see standard)
SO 3183-2:1996	L415QB seamless			0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.04; V 0.08; Nb 0.05; Al:N ≥ 2; CEV 0.43 (see standard)
	L415MB welded			0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.08 Nb 0.05; Al:N ≥ 2; CEV 0.42 (see standard)
API 5L-2004	X65, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.06
AFI 5L-2004	X65, PSL 2 welded			0.22	1.45		0.025	0.015				Cb+V+Ti 0.15; Ti 0.06
CSA Z245.1-2002	448 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
ASTM A 984/A 984M-03	60			0.22			0.025	0.015				B 0.0007; CE 0.40 (see standard)
EN 10208-2:1996	L450QB seamless	1.8952		0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; CEV 0.45 (see standard); Al:N ≥ 2;
EN 10200 2.1330	L450MB welded	1.8975		0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; CEV 0.43 (see standard); Al:N ≥ 2;
ISO 3183-2:1996	L450QB seamless			0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.09; Nb 0.05; Al:N ≥ 2; CEV 0.45 (see standard)
130 3103-2.1990	L450MB welded			0.16	1.6	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.10; Nb 0.05; Al:N ≥ 2; CEV 0.43 (see standard)

5.10 Line Pipe Steels

5.10.2B Chemical Composition of Line Pipe Steels With Notch Toughness Requirements (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weight	t, %, max,	Unless O	therwise	Specified
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
API 5L-2004	X70, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.06
AF1 5L-2004	X70, PSL 2 welded			0.22	1.65		0.025	0.015				Cb+V+Ti 0.15; Ti 0.06
CSA Z245.1-2002	483 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
ASTM A 1005/A 1005M-00	70			0.16								B 0.0007; CE 0.40 (see standard)
EN 10208-2:1996	L485QB seamless	1.8955		0.16	1.7	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.10; Nb 0.05; Al:N ≥ 2 CEV 0.45 (see standard)
LIN 10200-2.1990	L485MB welded	1.8977		0.16	1.7	0.45	0.025	0.020	0.30	0.30	0.10	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.10; Nb 0.06; Al:N ≥ 2 CEV 0.43 (see standard)
ISO 3183-2:1996	L485QB seamless			0.16	1.7	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.10; Nb 0.05; Al:N ≥ 2 CEV 0.45 (see standard)
130 3100-2.1990	L485MB welded			0.16	1.7	0.45	0.025	0.020	0.30	0.30	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15; Ti 0.06; V 0.10; Nb 0.06; Al:N ≥ 2 CEV 0.43 (see standard)
ASTM A 984/A 984M-03	80			0.22			0.025	0.015				B 0.0007; CE 0.40 (see standard)
CSA Z245.1-2002	550 - Category II or III			0.26	2.00	0.50	0.030	0.035				Nb 0.11; Ti 0.11; V 0.11; B 0.001; CE 0.40 (see standard)
API 5L-2004	X80, PSL 2 seamless			0.24	1.40		0.025	0.015				Cb+V+Ti 0.15; Ti 0.06
A113L-2004	X80, PSL 2 welded			0.22	1.85		0.025	0.015				Cb+V+Ti 0.15; Ti 0.06
	L555QB seamless	1.8957		0.16	1.8	0.45	0.025	0.020	0.50	0.60	0.35	Al 0.015-0.060; N 0.0012; Cu 0.25; Al:N ≥ 2; Nb+V+Ti 0.15; CEV by agreement (see standard)
EN 10208-2:1996	L555MB welded	1.8978		0.16	1.8	0.45	0.025	0.020	0.30	0.30	0.10	V 0.10; Nb 0.06; Ti 0.06; Al:N ≥ 2; Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15 CEV by agreement (see standard)
	L555QB seamless			0.16	1.8	0.45	0.025	0.020	0.50	0.60	0.35	V 0.10; Nb 0.05; Ti 0.06; Al:N ≥ 2; Nb+V+Ti 0.15; CEV by agreement (see standard)
SO 3183-2:1996	L555MB welded			0.16	1.8	0.45	0.025	0.020	0.30	0.30	0.10	V 0.10; Nb 0.06; Ti 0.06; Al:N ≥ 2; Al 0.015-0.060; N 0.0012; Cu 0.25; Nb+V+Ti 0.15 CEV by agreement (see standard)
ASTM A 1005/A 1005M-00	80			0.16								B 0.0007; CE 0.40 (see standard)

5.11 Non-Comparable Carbon Steel Tubes for General and Structural Applications

ASTM A 512-96 (20	01) – Cold-Dra	wn Buttweld Ca	arbon Steel Me	chanical Tubing	g							
Grade	10S10	15S10	18S10	37S10	1115	1117						
UNS Number	1.0711	1.0710	1.0712	1.0713	G11150	G11170						
ASTM A 519-03 – S	eamless Carbo	on and Alloy St	eel Mechanica	Tubing								
Grade, Class, Type	1330	1335	1340	1345	4145							
UNS Number	G13300	G13350	G13400	G13450	G41450							
ASTM A 595-98 (20	02) – Steel Tub	es, Low-Carbo	n, Tapered for	Structural Use								
Grade, Class, Type	С											
UNS Number												
EN 10296-1:2003 -	Welded Circul	ar Steel Tubes	for Mechanical	and General E	ngineering Pu	rposes- Techni	cal Delivery Co	nditions – Part	1: Non-alloy a	nd Alloy Steel	Tubes	
Steel Name	E275M	E355M	E355K2	E420M	E460M	E460K2						
Steel Number	1.8895	1.8896	1.0920	1.8897	1.8898	1.8891						
EN 10297-1:2003 -	Seamless Circ	ular Steel Tube	es for Mechanic	cal and General	Engineering F	Purposes - Tec	hnical Delivery	Conditons – Pa	art 1: Non-Alloy	and Alloy Ste	el Tubes	
Steel Name	C10E	C15E	C15R	C60E								
Steel Number	1.1121	1.1141	1.1140	1.1221								
EN 10305-1:2002 -	Steel Tubes fo	r Precision Ap	plications, Tecl	hnical Delivery	Conditions – F	Part 1: Seamles	s Cold Drawn 1	ubes				
Steel Name	C45E											
Steel Number	1.1191											

5.12 Non-Comparable Alloy Steel Tubes for General and Structural Applications

ASTM A 513-03a -	Electric-Resis	tance-Welded C	arbon and Alle	y Steel Mecha	nical Tubing							
Grade, Class, Type	4118	5130	8620	8630								
UNS Number	G41180	G51300	G86200	G86300								
ASTM A 519-03 - S	Seamless Carb	on and Alloy St	eel Mechanica	l Tubing								
Grade, Class, Type	3140	E3310	4012	4023	4024	4027	4037	4042	4047	4063	4118	4147
UNS Number	G31400	G33106	G40120	G40230	G40240	G40270	G40370	G40420	G40470	G40630	G41180	G41470
Grade, Class, Type	4150	4320	4337	E4337	4340	E4340	4422	4427	4520	4615	4617	4620
UNS Number	G41500	G43200	G43370	G43376	G43400	G43406	G44220	G44270	G45200	G46150	G46170	G46200
Grade, Class, Type	4621	4718	4720	4815	4817	4820	5015	5046	5115	5120	5130	5132
UNS Number	G46210	G47180	G47200	G48150	G48170	G48200	G50150	G50460	G51150	G51200	G51300	G51320
Grade, Class, Type	5135	5140	5145	5147	5150	5155	5160	E50100	E51100	E52100	6118	6120
UNS Number	G51350	G51400	G51450	G51470	G51500	G51550	G51600	G50986	G51986	G52986	G61180	G61200
Grade, Class, Type	6150	E7140	8115	8615	8617	8620	8622	8625	8627	8630	8637	8640
UNS Number	G61500	K24065	G81150	G86150	G86170	G86200	G86220	G86250	G86270	G86300	G86370	G86400
Grade, Class, Type	8642	8645	8650	8655	8660	8720	8735	8740	8742	8822	9255	9260
UNS Number	G86420	G86450	G86500	G86550	G86600	G87200	G87350	G87400	G87420	G88220	G92550	G92600
Grade, Class, Type	9262	E9310	9840	9850	50B40	50B44	50B46	50B50	50B60	51B61	81B45	86B45
UNS Number	G92620	G93106	G98400	G98500	G50401	G50441	G50461	G50501	G50601	G50611	G81451	G86451
Grade, Class, Type	94B15	94B17	94B30	94B40								
UNS Number	G94151	G94171	G94301	G94401								
EN 10297-1:2003 -	Seamless Circ	cular Steel Tube	es for Mechani	cal and Genera	l Engineering l	Purposes - Tech	nical Delivery	Conditons - Pa	art 1: Non-Allo	y and Alloy Stee	l Tubes	
Steel Name	E355K2	E460K2	E730K2	16MnCr5	16MnCrS5	20NiCrMo2-2	30CrNiMo8	36CrNiMo4	41Cr4	41NiCrMo7-3-2		
Steel Number	1.0920	1.8891	1.8893	1.7131	1.7139	1.6523	1.6580	1.6511	1.7035	1.6563		
EN 10305-1:2002 -	Steel Tubes fo	or Precision App	plications, Tec	hnical Delivery	Conditions - I	Part 1: Seamles	s Cold Drawn	Tubes				
Steel Name	1340											
Steel Number												
JIS G 3441:1988 – A	Alloy Steel Tul	bes for Machine	Purposes									
Grade Designation	S Cr 420 TK	S CM 415 TK										

5.13 Non-Comparable Stainless Steel Tubes for General and Structural Applications

ASTM A 268/A 268	M-03 – Seamle	ss and Welded	Ferritic and Ma	artensitic Stair	nless Steel Tubi	ng for General	Service					
Grade, Class, Type	TP403Ti	TP429	TP443	TP446-1	TP446-2	TP468	TPXM-27	TPXM-33	18Cr-2Mo	25-4-4	26-3-3	29-4
UNS Number	S43036	S42900	S44300	S44600	S44600	S46800	S44627	S44626	S44400	S44635	S44660	S44700
Grade, Class, Type	29-4-2											
UNS Number	S44800	S32803	S40800	S40977	S41500	S42035	S43940	S44735				
ASTM A 269-02a -	Seamless and	Welded Auster	nitic Stainless	Steel Tubing fo	or General Servi	ice						
Grade, Class, Type	TP317	TP348	TPXM-10	TPXM-11	TPXM-15	TPXM-19	TPXM29					
UNS Number	S31700	S34800	S21900	S21904	S38100	S20910	S24000	S31254	S31726	S30600	S24565	S32654
Grade, Class, Type												
UNS Number	S35045	N08367	N08926	N08904								
ASTM A 511-96 - 9	Seamless Stain	less Steel Mecl	hanical Tubing									
Grade, Class, Type	MT 302	MT 303Se	MT 305	MT 309S	MT 310S	MT 317	MT 403	MT 414	MT 416Se	MT 431	MT 440A	MT 429
UNS Number	S30200		S30500	S30908	S31008	S31700	S40300	S41400	S41623	S43100	S44002	S42900
Grade, Class, Type	MT 443	MT 446-1	MT 446-2	29-4	29-4-2							
UNS Number	S44300	S44600	S44600	S44700	S44800							
ASTM A 554-03 - \	Welded Stainles	ss Steel Mecha	nical Tubing									
Grade, Class, Type	MT-301	MT-302	MT-305	MT-309S	MT-309S-Cb	MT-310S	MT-317	MT-330	MT-429	MT-430-Ti		
UNS Number	S30100	S30200		S30908	S30940	S31008	S31700		S42900	S43036		
ASTM A 632-02a -	Seamless and	Welded Auster	nitic Stainless	Steel Tubing (S	Small-Diameter)	for General Se	ervice					
Grade, Class, Type	TP 310	TP 317	TP 348									
UNS Number	S31000	S31700	S34800									
ASTM A 778-01 - \	Welded, Unann	ealed Austeniti	c Stainless Ste	el Tubular Pro	ducts							
Grade, Class, Type	TP 317L											
UNS Number	S31703											
JIS G 3446:1994 –	Stainless Stee	l pipes for Macl	hine and Struc	tural Purposes	; }							
Symbol of Grade	SUS420J1TKA	SUS420J2TKA										
AFNOR NF A 49-64	47:1979 – Struc	tural Welded T	ubes, Circular,	Square, Recta	ingular or Oval,	in Ferritic or A	ustenitic Stain	less Steels - Di	imensions - Te	chnical Delivery	y Conditions	
Designation	TS Z 12 CN 17	-07										

5.14 Non-Comparable Carbon Steel Tubes and Pipes for Low-Temperature Service

EN 10216-3:2002 -	- Seamless Stee	el Tubes for Pre	essure Purpose	es, Technical De	livery Condtic	ons – Part 3: Al	loy Fine Grain	Steel Tubes				
Steel Name	P275NL1	P355N	P355NH	P355NL1	P355NL2	P460N	P460NH	P460NL1	P460NL2	P620Q	P620QH	P620QL
Steel Number	1.0488	1.0562	1.0565	1.1106	1.0566	1.8905	1.8935	1.8915	1.8918	1.8876	1.8877	1.8890
Steel Name	P690Q	P690QH	P690QL1	P690QL2								
Steel Number	1.8879	1.8880	1.8881	1.8888								

5.15 Non-Comparable Alloy Steel Tubes and Pipes for Low-Temperature Service

ASTM A 333/A 333I	VI-99 – Seamle	ss and Welded	Steel Pipe for	Low-Temperati	ıre Service							
Grade	4	7	9	10	11	P23	P92	P122	P911			
UNS Number	K11267	K21903	K22035			K41650	K92460	K92930	K91061			
ASTM A 334/A 334	VI-99 – Seamle	ss and Welded	Carbon and Al	loy-Steel Tube	s for Low-Tem	perature Servic	е					
Grade, Class, Type	7	9	11									
UNS Number	K21903	K22035										
ISO 9329-3:1997 – 9	Seamless Stee	I Tubes for Pre	ssure Purpose	s, Technical De	elivery condition	ons Part 3: Una	lloyed and Allo	yed Steels with	Specified Lov	v Temperature	Properties	
Type Number	PL 26											
ISO 9330-3:1997 – \ Specified Low Tem			ure Purposes,	Technical Con	ditions for Deli	very – Part 3: E	Electric Resista	nce and Induct	tion Wellded Ur	nalloyed and A	lloyed Steel Tu	e with
Type Number	PL 26											
ISO 9330-5:2000 – N Temperature Prope		ubes for Press	ure Purposes,	Technical Con	ditions for Deli	very – Part 5: S	Submerged Arc	-Welded Unallo	yed and Alloy	ed Steel Tube v	vith Specified L	ow
Type Number	PL 26											

5.16 Non-Comparable Carbon Steel Tubes and Pipes for Pressure Purposes at High Temperatures

JIS G 3467:1988 –	Steel Tubes for	Fired Heater								
Symbol of Class	SUS 309 TF							 	 	
ISO 2604-II:1975 –	Steel Products	for Pressure P	urposes - Qual	ity Requiremen	nts - Part 2 - W	rought Seamles	ss Tubes			
Steel Type	TS 40	TS 43	TS 45	TS 67	TS 69			 	 	

5.17 Non-Comparable Alloy Steel Tubes and Pipes for Pressure Purposes at High Temperatures

ASTM A 213/A 213	VI-03a – Seamle	ess Ferritic and	Austenitic Al	loy-Steel Boiler,	Superheater,	and Heat-Exc	nanger Tubes					
Grade, Class, Type	T5c	T17	T21	T23	T24	T92	T122	T911	TP201	TP202	TP304N	TP309Cb
UNS Number	K41245	K12047	K31545			K92460		K91061	S20100	S20200	S30451	S30940
Grade, Class, Type	TP309HCb	TP310Cb	TP310HCb	TP310HCbN	TP316N	TP347LN	TP347HFG	TP348	TP348H	XM-15	XM-19	
UNS Number	S30941	S31040	S31041	S31042	S31651	S34751		S34800	S34809	S38100	S20910	S21500
Grade, Class, Type												
UNS Number	S25700	S30432	S30615	S30815	S31002	S31050	S31254	S31272	S31726	S32050	S32615	S33228
Grade, Class, Type												
UNS Number	S34565	S44400										
ASTM A 335/A 335	VI-03 – Seamles	ss Ferritic Alloy	-steel Pipe fo	r High-Temperat	ure Service							
Grade	P5b	P5c	P15	P21	P91							
UNS Number	K51545	K41245	K11578	K31545	K91560							
EN 10216-2:2002 –	Seamless Stee	I Tubes for Pre	ssure Purpos	es, Technical De	livery Condito	ons – Part 2: N	on-Alloy and Al	loy Steel Tube	s with Specifie	ed elevated Tem	perature Prope	erties
Steel Name	15NiCuMoNb5-	6-4 20MnNb6	20CrMoV13	-5-5 X20CrMoV1	11-1 25CrN	104						
Steel Number	1.6368	1.0471	1.7779	1.4922	1.72	18						
EN 10217-3:2002 -	Welded Steel 1	ubes for Press	ure Purposes	, Technical Deliv	ery Condition	s – Part 3: All	oy Fine Grain S	teel Tubes				
Steel Name	P275NL1	P275NL2	P355N	P355NH	P355NL1	P355NL2	P460N	P460NH	P460NL1	P460NL2		
Steel Number	1.0488	1.1104	1.0562	1.0565	1.0566	1.1106	1.8905	1.8935	1.8915	1.8918		

5.18 Non-Comparable Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures

ASTM A 249/A 249N	N-03 – Welded	Austenitic Stee	el Boiler, Supe	rheater, Heat-E	xchanger, and	Condenser Tu	bes					
Grade, Class, Type	TP201	TP202	TP305	TP309Cb	TP309HCb	TP310Cb	TP310H	TP310HCb	TP316N	TP348	TP348H	TPXM-15
UNS Number	S20100	S20200	S30500	S30940	S30941	S31040	S31009	S31041	S31651	S34800	S34809	S38100
Grade, Class, Type	TPXM-19	TPXM-29										
UNS Number	S20910	S24000	S24565	S30415	S30815	S31726	S32050	S32654	S33228	S34565		
ASTM A 312/A 312	M-03 – Seamle	ss and Welded	Austenitic Sta	inless Steel Pip	oes							
Grade	TP304N	TP304LN	TP309Cb	TP309H	TP309HCb	TP310Cb	TP310H	TP310HCb	TP316N	TP316LN	TP347LN	TP348
UNS Number	S30451	S30453	S30940	S30909	S30941	S31040	S31009	S31041	S31651	S31653	S31751	S34800
Grade	TP348H	TPXM-10	TPXM-11	TPXM-15	TPXM-19	TPXM-29						
UNS Number	S34809	S21900	S21904	S38100	S20910	S24000	S20400	S30415	S30600	S30615	S30815	S31002
Grade												
UNS Number	S31050	S31254	S31272	S31635	S31726	S32615	S32654	S33228	S34565	S35045	S35315	N08367
Grade												
UNS Number	N08904											
ASTM A 358/A 358	M-01 – Electric	-Fusion-Welde	d Austenitic C	hromium-Nicke	el Alloy Steel Pi	pe for High-Te	mperature Ser	vice				
Grade	304N	304LN	309Cb	310Cb	316N	316LN	348	XM-19	XM-29			
UNS Number	S30451	S30453	S30940	S31040	S31651	S31653	S34800	S20910	S28300	S20400	S31254	S30815
Grade												
UNS Number	S30600	S31726	S24565	S30415	S32654	S31266	S32050	N08367	N08926	N08800	N08810	N08020
ASTM A 376/A 376	VI-02a – Seaml	ess Austenitic	Steel Pipe for I	ligh-Temperate	ure Central-Stat	ion Service						
Grade	TP316N	TP348	16-8-2H									
UNS Number	S31651	S34800	S16800	S31726	S34565							
ASTM A 409/A 4091	M-01 – Welded	Large Diamete	r Austenitic St	eel Pipe for Co	rrosive or High	-Temperature	Service					
Grade	TP309Cb	TP309S	TP310Cb	TP310S	TP348							
UNS Number	S30940	S30908	S31040	S31008	S34800	S31254	S30815	S31726	S24565	N08367		
ASTM A 688/A 688	N-03 – Welded	Austenitic Stai	inless Steel Fe	edwater Heater	Tubes							
Grade, Class, Type	TP XM-29	TP 316N										
UNS Number	S24000	S31651	S32654									
ASTM A 803/A 803	M-03 – Welded	Ferritic Stainle	ss Steel Feedv	vater Heater Tu	ıbes							
Grade, Class, Type	TP XM-33	25-4-4	26-3-3	29-4	29-4-2	18-2	29-4C	TP439				
UNS Number	S44626	S44635	S44660	S44700	S44800	S44400	S44735	S43035				
BS 3605-1:1991 AM	ID 2:1997 – Au	stenitic Stainle	ss Steel Pipes	and Tubes for	Pressure Purpo	ses. Part 1. S	pecification for	Seamless Tube	es			
Steel Type	215S15											
DIN 17458:1985 – S	eamless Circu	lar Austenitic S	Stainless Steel	Tubes Subject	to Special Req	uirements - Te	chnical Delive	ry Conditions				
Symbol	X 6 CrNiMo	Nb 17 12 2										
Material Number	1.4	580										
										-		

5.18 Non-Comparable Stainless Steel Tubes and Pipes for Pressure Purposes and High Temperatures (Continued)

DIN 17459:1992 – S	Seamless Circu	lar High-Temp	erature Austen	itic Steel Tube	s - Technical De	elivery Condition	ns					
Symbol	X 3 CrNi	iN 18 11	X 8 CrNi	Ti 18 10	X 8 CrNiM	X 8 CrNiMoNb 16 16		VNb 16 13				
Material Number	1.49	949	1.4941		1.49	981	1.4	988				
JIS G 3459: 1997 –	Stainless Stee	l Pipes										
Symbol of Grade	SUS310TP	SUS836LTP	SUS321J1TP	SUS321J3LTP	SUS321J4LTP	SUS405TP	SUS409LTP	SUS430TP	SUS430LXTP	SUS430J1LTP	SUS436LTP	SUS444TP
JIS G 3463:1994 –	Stainless Steel	Boiler and He	at Exchanger T	ubes								
Symbol of Class	SUSXM15J1TB	SUS329J1TB	SUS405TB	SUS409LTB	SUS410TiTB	SUS430J1LTB	SUS436LTB	SUS444TB	SUSXM8TB			
JIS G 3468:1994 –	Large Diameter	Welded Stain	less Steel Pipe	S								
Symbol of Grade	SUS329J1											
AFNOR NF A 49-21	14:1978 – Seam	less Austenitio	Steel Tubes fo	or Use at High	Temperatures.	Dimensions (W	ith Normal Tol	erances) - Tec	hnical Conditio	ns of Delivery		
Designation	Z 10 CNW	T 17-13 B										
AFNOR NF A 49-21	17:1987 – Seam	less Tubes for	Heat Exchange	ers - Stainless	Ferritic, Auster	ic or Ferritic-A	ustenitic Steel	Grades Dimen	sions - Technic	cal Delivery Cor	nditions	
Designation	TU Z 2 CN	Nb 25 20	TU Z 2 CN	NDU 17 16	TU Z 1 NC	OU 25 20 04	TU Z 1 NC	OU 31 27 03	TU Z 2 CN	D 18 05 03	TU Z 5 CNDU 21 08 02	
AFNOR NF A 49-24	14:1993 – Welde	ed Austenitic S	Stainless and A	ustenitic Ferrit	ic Steel Rolled	Tubes for Pres	sure Service - I	Dimensions, T	echnical Condi	tions for Delive	ry	
Designation	X3CrN	iN23-4	X3CrNiN	ЛоN22-5	X3CrNiN	/loN25-6	X3CrNiN	ЛоN25-7	X3CrNiM	loCu22-7	X3CrNiMe	oCuN25-6
Designation	X3CrNiMoCuN25-7 X3CrNiMoN19-14				X4CrMnNi18-8-7		X8CrNi25-20					
ISO 2604-V:1975 -	Steel Products	for Pressure I	Purposes - Qua	lity Requireme	nts - Part 5: Lo	ngitudinally We	elded Austeniti	c Stainless Ste	el Tubes			
Steel Type	TW 69											

5.19 Non-Comparable Line Pipe Steels

ASTM A 1005/A 10	05M-00 – Steel	Line Pipe, Blad	ck, Plain End, L	ongitudinal an	d Helical Seam	ı, Double Subm	nerged-Arc Wel	ded		
Grade	50								 	
UNS Number									 	
ASTM A 984/A 984	M-03 – Steel Li	ne Pipe, Black,	Plain-End, Ele	ctric-Resistano	e-Welded					
Grade, Class, Type	70								 	
UNS Number									 	
CSA Z245.1-2002 -	Steel Line Pip	е								
Grade	620 Catego	oryl, II or III	690 Catego	ory I, II or III					 	
EN 10208-1:1997-	Steel Pipes for	Pipelines for C	Combustible Flu	ids. Technical	Delivery Cond	itions. Part 1 :	Pipes of Requi	rement Class A		
Steel Name	L235GA								 	
Steel Number	1.0458								 	

Chapter

6

STEEL FORGINGS

ASTM Standards

ASTM A 105/A 105M-03	Carbon Steel Forgings for Piping Applications
ASTM A 181/A 181M-01	Carbon Steel Forgings, for General-Purpose Piping
ASTM A 182/A 182M-02	Forged or Rolled Alloy-Steel Pipe Flanges, Forged Fittings, and Valves and Parts for High-Temperature Service
ASTM A 266/A 266M-03a	Carbon Steel Forgings for Pressure Vessel Components
ASTM A 336/A 336M-03a	Alloy Steel Forgings for Pressure and High-Temperature Parts
ASTM A 350/A 350M-02b	Carbon and Low-Alloy Steel Forgings, Requiring Notch Toughness Testing for Piping Components
ASTM A 473-01	Stainless Steel Forgings
ASTM A 508/A 508M-03a	Quenched and Tempered Vacuum-Treated Carbon and Alloy Steel Forgings for Pressure Vessels
ASTM A 541/A 541M-95 (1999)	Quenched and Tempered Carbon and Alloy Steel Forgings for Pressure Vessel Components
ASTM A 668/A 668M-03	Steel Forgings, Carbon and Alloy, for General Industrial Use
ASTM A 705/A705M-95 (2000)	Age-Hardening Stainless Steel Forgings
ASTM A 965/A 965M-02	Steel Forgings, Austenitic, for Pressure and High Temperature Parts

JIS Standards

JIS G 3201:1988 (1991)	Carbon steel Forgings for General Use
JIS G 3202:1988 (1991)	Carbon Steel Forgings for Pressure Vessels
JIS G 3203:1988	Alloy Steel Forgings for Pressure Vessels for High-Temperature Service
JIS G 3204:1988	Quenched and Tempered Alloy Steel Forgings for Pressure Vessels
JIS G 3205:1988	Carbon and Alloy Steel Forgings for Pressure Vessels for Low-Temperature Service
JIS G 3206:1993	High Strength Chromium-Molybdenum Alloy Steel Forgings for Pressure Vessels Under High-Temperature Service
JIS G 3214:1991	Stainless Steel Forgings for Pressure Vessels
JIS G 3221:1988	Chromium Molybdenum Steel Forgings for General Use

CEN Standards

EN 10222-2:1999	Steel Forgings for Pressure Purposes - Part 2: Ferritic and Martensitic Steels with Specified Elevated Temperature Properties
EN 10222-3:1998	Steel Forgings for Pressure Purposes - Part 3: Nickel Steels with Specified Low-Temperature Properties
EN 10222-4:1998 A1: 2001	Steel Forgings for Pressure Purposes - Part 4: Weldable Fine-Grain Steels with High Proof Strength
EN 10222-5:1999	Steel Forgings for Pressure Purposes - Part 5: Martensitic, Austenitic and Austenitic-Ferritic Stainless Steels
EN 10250-2:1999	Open Die Steel Forgings for General Engineering Purposes - Part 2: Non-Alloy Quality and Special Steels
EN 10250-3:1999	Open Die Steel Forgings for General Engineering Purposes - Part 3: Alloy Special Steels
EN 10250-4:1999	Open Die Steel Forgings for General Engineering Purposes - Part 4: Stainless Steels

ISO Standards

ISO 9327-2:1999	Steel Forgings and Rolled or Forged Bars for Pressure Purposes. Technical Delivery Conditions. Part 2: Non-Alloy and Alloy (Mo, Cr and CrMo) Steels with Specified Elevated Temperature Properties
ISO 9327-3:1999	Steel Forgings and Rolled or Forged Bars for Pressure Purposes. Technical Delivery Conditions. Part 3: Nickel Steels with Specified Low Temperature Properties
ISO 9327-4:1999	Steel Forgings and Rolled or Forged Bars for Pressure Purposes. Technical Delivery Conditions. Part 4: Weldable Fine Grain Steels with High Proof Strength
ISO 9327-5:1999	Steel Forgings and Rolled or Forged Bars for Pressure Purposes. Technical Delivery Conditions. Part 5: Stainless Steels

Standard	Heat Treatment Terms
ASTM A 105/A 105M-03	
ASTM A 181/A 181M-01	
ASTM A 182/A 182M-02	A: annealed; NT: normalized and tempered; QT: quenched and tempered; ST+Q: solution treated and quenched
ASTM A 266/A 266M-03a	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
ASTM A 336/A 336M-03a	A: annealed; NT: normalized and tempered
ASTM A 350/A 350M-02b	N: normalized; NT: normalized and tempered; QT: quenched and tempered
ASTM A 473-01	ST: solution treated; NT: normalized and tempered
ASTM A 508/A 508M-03a	QT: quenched and tempered
ASTM A 541/A 541M-95 (1999)	QT: quenched and tempered
ASTM A 668/A 668M-03	A: annealed; N: normalized; NT: normalized and tempered; NNT: double-normalized and tempered; QT: quenched and tempered; NQT: normalized, quenched and tempered
ASTM A 705/A705M-95 (2000)	ST: solution treated; HXXXX: precipitation hardened at specified temperature
ASTM A 965/A 965M-02	ST solution treated; QT: quenched
JIS G 3201:1988	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
JIS G 3202:1988	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
JIS G 3203:1988	A: annealed; NT: normalized and tempered
JIS G 3204:1988	QT: quenched and tempered
JIS G 3205:1988	A: annealed; NT: normalized and tempered; QT: quenched and tempered
JIS G 3206:1993	NT: normalized and tempered; QT: quenched and tempered
JIS G 3214:1991	QT: quenched and tempered; S: solution treated; HXXXX: precipitation hardened at specified temperature
JIS G 3221:1988	HT: hardening and tempering
EN 10222-2:1999	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
EN 10222-3:1998	N: normalized; NT: normalized and tempered; QT: quenched and tempered
EN 10222-4:1998 A1:2001	N: normalized; QT: quenched and tempered
EN 10222-5:1999	QT: quenched and tempered; QT+T: quenched and double tempered; ST: solution treated
EN 10250-2:1999	N: normalized; NT: normalized and tempered; QT: quenched and tempered
EN 10250-3:1999	QT: quenched and tempered
EN 10250-4:1999	A: annealed; QTXXX: quenched, tempered at specified temperature; ST: solution annealed PXXX: precipitation hardened at specified temperature; SA: solution annealed
ISO 9327-2:1999	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
ISO 9327-3:1999	N: normalized; NT: normalized and tempered; NNT: double-normalized and tempered; N(+T): normalized and (if appropriate) tempered; QT: quenched and tempered
ISO 9327-4:1999	N: normalized; QT: quenched and tempered
ISO 9327-5:1999	Q: quenched

Impact Testing Notes Applicable to this Chapter

see standard for impact data: impact testing requirements are listed in the standard for multiple test temperatures.

6.1.1A Mechanical Properties of Carbon Steel Forgings for General Use

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 668/A 668M-03	Α				≤ 500	≤ 20			325	47		183 HB max
JIS G 3201:1988	SF 340 A			A, N, or NT			175		340-440		27	90 HB min
					≤ 100		215		340		24	35 J at -20°C
	S235JRG2	1.0038		N	100 < t ≤ 250		175		340		23	30 J at -20°C
EN 10250-2:1999					250 < t ≤ 500		165		340		23	27 J at -20°C
EN 10250-2:1999					≤ 100		215		340		24	35 J at -20°C
	S235J2G3	1.0116		N	100 < t ≤ 250		175		340		23	30 J at -20°C
					250 < t ≤ 500		165		340		23	27 J at -20°C
JIS G 3201:1988	SF 390 A			A, N, or NT			195		390-490		25	105 HB min
EN 10250-2:1999	C22	1.0402		N or NT	≤ 100		210		410		25	
					≤ 16		265				26	
					16 < t ≤ 40		255		410-530		26	1
ISO 9327-2:1999	PH 26			N or QT	40 < t ≤ 60		245		410-530		25	40 J at 0°C
				N or Q1	60 < t ≤ 100		215				24	
					100 < t ≤ 150		200		200 500		24	
					150 < t ≤ 250		200		390-520		23	
ASTM A 668/A 668M-03	В			A, N, or NT	≤ 508	≤ 20	205	30	415	60	24	120-174 HB
JIS G 3201:1988	SF 440 A			A, N, or NT			225		440-540		24	121 HB min
					≤ 100		230		440		23	35 J at 23°C
	C25	1.0406		N or NT	100 < t ≤ 250		210		420		23	30 J at 23°C
	025	1.0406			250 < t ≤ 500		190		400		23	25 J at 23°C
					500 < t ≤ 1000		180		390		22	20 J at 23°C
					≤ 100		230		440		23	35 J at 23°C
EN 10250-2:1999				N or NT	100 < t ≤ 250		210		420		23	30 J at 23°C
				IN OF INT	250 < t ≤ 500		190		400		23	25 J at 23°C
	C25E	1.1158			500 < t ≤ 1000		180		390		22	20 J at 23°C
					≤ 70		270		450		25	45 J at 23°C
				QT	70 < t ≤ 160		220		410		25	38 J at 23°C
					160 < t ≤ 330		210		390		24	33 J at 23°C
ASTM A 668/A 668M-03	С			A, N, or NT	≤ 203	≤ 12	230	33	455	66	23	137-183 HB
A3 I W A 000/A 000W-03				A, IN, UI IN I	305 < t ≤ 508	12 < t ≤ 20	230	33	455	66	22	137-183 HB
					≤ 16		290				24	
					16 < t ≤ 40		285		460 590		24	
ISO 9327-2:1999	PH 29			N or QT	40 < t ≤ 60		280		460-580		24	10 Let 000
130 9321-2.1999	PH 29			IN OF QT	60 < t ≤ 100		255		7		23	40 J at 0°C
					100 < t ≤ 150		230		440-570		23	
					150 < t ≤ 250		220		440-570		22	

6.1.1A Mechanical Properties of Carbon Steel Forgings for General Use (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10250-2:1999	C30	1.0528		N or NT	≤ 100		250		480		21	
EN 10250-2:1999	C30	1.0526		IN OF IN I	100 < t ≤ 250		230		460		21	
JIS G 3201:1988	SF 490 A			A, N, or NT			245		490-590		22	134 HB min
					≤ 16		315				23	
					16 < t ≤ 40		310		490-610		23	
ISO 9327-2:1999	PH 31			N or QT	40 < t ≤ 60		305		490-610		23	40 J at 0°C
130 9327-2.1999	гпы			NOIQI	60 < t ≤ 100		280				22	40 J at 0°C
					100 < t ≤ 150		255		470-600		22	
					150 < t ≤ 250		245		460-590		21	
					≤ 203	≤ 8					24	
ASTM A 668/A 668M-03	D			A, N, or NT	203 < t ≤ 305	$8 < t \le 12$	260	37.5	515	75	22	149-207 HB
ASTM A 668/A 668M-03	D			A, IN, OI INT	305 < t ≤ 508	12 < t ≤ 20	200	37.5	313	/5	20	149-207 ПБ
					≥ 508	≥ 20					19	
					≤ 100		270		520		19	30 J at 23°C
	C35	1.0501		N or NT	100 < t ≤ 250		245		500		19	25 J at 23°C
	035	1.0501		IN OF IN I	250 < t ≤ 500		220		480		19	20 J at 23°C
EN 10250-2:1999					500 < t ≤ 1000		210		470		18	17 J at 23°C
EN 10230-2.1999					≤ 100		270		520		19	30 J at 23°C
	C35E	1.1181		N or NT	100 < t ≤ 250		245		500		19	25 J at 23°C
	COSE	1.1101		IN OF INT	250 < t ≤ 500		220		480		19	20 J at 23°C
					500 < t ≤ 1000		210		470		18	17 J at 23°C
	SF 540 A			A, N, or NT			275		540-640		20	152 HB min
JIS G 3201:1988					< 100		335				21	
JIS G 3201.1900	SF 540 B			QT	100 ≤ t < 250		315		540-690		21	152 HB min
					250 ≤ t < 400		295				20	
					≤ 70		320		550		20	35 J at 23°C
	C35E	1.1181		QT	70 < t ≤ 160		290		490		22	31 J at 23°C
EN 10250-2:1999					160 < t ≤ 330		270		470		21	25 J at 23°C
	C40	1.0511		N or NT	≤ 100		290		550		17	
	C40	1.0511		IN OF IN I	100 < t ≤ 250		260		530		17	

6.1.1A Mechanical Properties of Carbon Steel Forgings for General Use (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,			
Designation	Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other		
					≤ 100		305		580		16			
	C45	1.0503		N or NT	100 < t ≤ 250		275		560		16	18 J at 23°C		
	U45	1.0503		IN OF IN I	250 < t ≤ 500		240		540		16	15 J at 23°C		
EN 10250-2:1999					500 < t ≤ 1000		230		530		15	12 J at 23°C		
EN 10250-2:1999					≤ 100		305		580		16			
	C45E	1.1191		N or NT	100 < t ≤ 250		275		560		16	18 J at 23°C		
	U43E	1.1191		IN OF IN I	250 < t ≤ 500		240		540		16	15 J at 23°C		
					500 < t ≤ 1000		230		530		15	12 J at 23°C		
					≤ 203	≤ 8	305	44	585	85	25			
ASTM A 668/A 668M-03	E			NT or NNT	203 < t ≤ 305	8 < t ≤ 12	295	43	570	83	23	174-217 HB		
					305 < t ≤ 508	12 < t ≤ 20	295	43	570	83	22			
	SF 590 A			A, N, or NT			295		590-690		18	167 HB min		
IIC C 0001.1000					< 100		360				19			
JIS G 3201:1988	SF 590 B			QT	100 ≤ t < 250		335		590-740			167 HB min		
					250 ≤ t < 400		325				18			
EN 10250-2:1999	C50	1.0540		N or NT	≤ 100		320		610		14			
EN 10250-2:1999	C50	1.0540		IN OF IN I	100 < t ≤ 250		290		590		14			
							≤ 102	≤ 4	380	55	620	90	20	187-235 HB
ASTM A 668/A 668M-03	F			QT or NQT	102 < t ≤ 178	4 < t ≤ 7	345	50	585	85	20	174-217 HB		
A3 I IVI A 000/A 000IVI-03	F				178 < t ≤ 254	7 < t ≤ 10	345	50	585	85	19	174-217 HB		
					254 < t ≤ 508	10 < t ≤ 20	330	48	565	82	19	174-217 HB		
					≤ 70		370		630		17	25 J at 23°C		
EN 10250-2:1999	C45E	1.1191		QT	70 < t ≤ 160		340		590		18	22 J at 23°C		
					160 < t ≤ 330		320		540		17	20 J at 23°C		
					< 100		390				16			
JIS G 3201:1988	SF 640 B			QT	100 ≤ t < 250		360		640-780		16	183 HB min		
					250 ≤ t < 400		345				15			
					≤ 100		330		640		12			
	C55	1.0505		N or NT	100 < t ≤ 250		300		620		12			
	Coo	1.0535		N or NT	250 < t ≤ 500		260		600		12			
EN 10050 0:1000					500 < t ≤ 1000		250		590		11			
EN 10250-2:1999					≤ 100		330		640		12			
	OFFE	1 0505		N. a., NIT	100 < t ≤ 250		300		620		12			
	C55E	1.0535		- N or NT	250 < t ≤ 500		260		600		12			
					500 < t ≤ 1000		250		590		11			

6.1.1B Chemical Composition of Carbon Steel Forgings for General Use

Standard	Grade, Class, Type,	Steel	UNS												
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others			
ASTM A 668/A 668M-03	Α				1.35		0.050	0.050							
JIS G 3201:1988	SF 340 A			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
EN 10050 0:1000	S235JRG2	1.0038		0.20	1.40	0.55	0.045	0.045	0.30	0.30	0.08	Al 0.020 min; Cr+Mo+Ni to 0.48			
EN 10250-2:1999	S235J2G3	1.0116		0.17	1.40	0.55	0.035	0.035	0.30	0.30	0.08	Al 0.020 min; Cr+Mo+Ni to 0.48			
JIS G 3201:1988	SF 390 A			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
EN 10250-2:1999	C22	1.0402		0.17-0.24	0.40-0.70	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
ISO 9327-2:1999	PH 26			0.20	0.50-1.40	0.35	0.035	0.030	0.30	0.30	0.08	Al 0.020; Cu 0.30; Cr+Cu+Mo+Ni to 0.70			
ASTM A 668/A 668M-03	В				1.35		0.050	0.050							
JIS G 3201:1988	SF 440 A			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
EN 10050 0:1000	C25	1.0406		0.22-0.29	0.40-0.70	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
EN 10250-2:1999	C25E	1.1158		0.22-0.29	0.40-0.70	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
ASTM A 668/A 668M-03	С				1.35		0.050	0.050							
ISO 9327-2:1999	PH 29			0.20	0.90-1.50	0.40	0.035	0.030	0.30	0.30	0.08	Al 0.020; Cu 0.30; Cr+Cu+Mo+Ni to 0.70			
EN 10250-2:1999	C30	1.0528		0.27-0.34	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
JIS G 3201:1988	SF 490 A			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
ISO 9327-2:1999	PH 31			0.20	0.90-1.60	0.10-0.50	0.035	0.030	0.30	0.30	0.08	Al 0.020; Cu 0.30; Cr+Cu+Mo+Ni to 0.70			
ASTM A 668/A 668M-03	D				1.35		0.050	0.050							
EN 10050 0:1000	C35	1.0501		0.32-0.39	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
EN 10250-2:1999	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
JIS G 3201:1988	SF 540 A			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
JIS G 3201:1966	SF 540 B			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
EN 10050 0:1000	C35E	1.1181		0.32-0.39	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
EN 10250-2:1999	C40	1.0511		0.37-0.44	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
EN 10050 0:1000	C45	1.0503		0.42-0.50	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
EN 10250-2:1999	C45E	1.1191		0.42-0.50	0.50-0.80	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
ASTM A 668/A 668M-03	Е				1.35		0.050	0.050							
IIC C 0001-1000	SF 590 A			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
JIS G 3201:1988	SF 590 B			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
EN 10250-2:1999	C50	1.0540		0.47-0.55	0.60-0.90	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
ASTM A 668/A 668M-03	F				1.35		0.050	0.050							
EN 10250-2:1999	C45E	1.1191		0.42-0.50	0.50-0.80	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
JIS G 3201:1988	SF 640 B			0.60	0.30-1.20	0.15-0.50	0.030	0.035							
EN 10050 0:1000	C55	1.0535		0.52-0.60	0.60-0.90	0.40	0.045	0.045	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			
EN 10250-2:1999	C55E	1.0535		0.52-0.60	0.60-0.90	0.40	0.035	0.035	0.40	0.40	0.10	Cr+Mo+Ni to 0.63			

6.1.2A Mechanical Properties of Carbon Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Strength, min		Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					70 < t ≤ 100		245					63 J at 20°C
	P285QH	1.0478		QT	100 < t ≤ 250		225		370-510		22	55 J at 0°C
EN 10000 4:1000 A1:0001	1 203011	1.0470		QI	250 < t ≤ 400		205		070-310		22	47 J at -20°C 34 J at -40°C
EN 10222-4:1998 A1:2001					≤ 16		285					55 J at 20°C
	P285NH	1.0477		N	16 < t ≤ 35		285		390-510		24	47 J at 0°C
	1 2001111	1.0477			35 < t ≤ 70		265					40 J at -20°C 28 J at -40°C
ISO 9327-4:1999				N	≤ 16		285		390-510		26	55 J at 22°C
	P 28, PH 28				16 < t ≤ 35		285					47 J at 0°C 40 J at -20°C
	PL 28			QT	35 < t ≤ 50		275		390-510		26	63 J at 22°C
150 9327-4.1999					50 < t ≤ 70		265				20	55 J at 0°C
					70 < t ≤ 100		245				25	47 J at -20°C
					100 < t ≤ 250		225		370-510		24	35 J at -40°C 27 J at -50°C
JIS G 3202:1988	SFVC 1			A, N, NT, or QT			205		410-560		21	
EN 10222-2:1999	P245GH	1.0352		A, N, NT, or QT	≤ 35		245		410-530		25	32 J at RT
EN 10222-2.1999	F245GH	1.0332		A, N, NI, OI QI	$35 < t \le 160$		220		410-530		25	32 J at RT
ASTM A 181/A 181M-01	60		K03502				205	30	415	60	22	
ASTM A 266/A 266M-03a	1			A, N, NT, or QT			205	30	415-585	60-85	23	
ASTM A 350/A 350M-02b	LF1, Class 1		K03009	N, NT, or QT			205	30	415-585	60-85	25	18 J at -29°C
JIS G 3205:1988	SFL 1			A, NT, or QT			225		440-590		22	21 J at -30°C

6.1.2A Mechanical Properties of Carbon Steel Forgings for Piping, Pressure Vessel and Components (Continued)

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10222-2:1999	P280GH	1.0426		N, NT, or QT	≤ 35		280		460-580		23	48 J at RT
LN 10222-2.1999	F200GI1	1.0420		IN, INT, OF QT	35 < t ≤ 160		255		460-580		23	48 J at RT
					70 < t ≤ 100		315					63 J at 20°C
EN 10222-4:1998 A1:2001	P355QH1	1.0571		QT	100 < t ≤ 250		295		470-630		21	55 J at 0°C
LN 10222-4.1990 A1.2001	F333QIII	1.0371		Qı	250 < t ≤ 400		275		470-030		21	47 J at -20°C 34 J at -40°C
ASTM A 541/A 541M-95 (1999)	1			QT	≤ 75	≤ 3	250	36	480-660	70-95	20	20 J at 4°C
ASTM A 541/A 541M-95 (1999)	1A			QT	≤ 75	≤ 3	250	36	480-660	70-95	20	20 J at 4°C
ASTM A 105/A 105M-03			K03504				250	36	485	70	22	187 HB max
ACTM A OCC/A OCCM OC-	2		K03506	A, N, NT, or QT			250	36	485-655	70-95	20	
ASTM A 266/A 266M-03a	4		K03017	A, N, NT, or QT			250	36	485-655	70-95	20	
ASTM A 181/A 181M-01	70		K03502				250	36	485	70	18	
ASTM A 350/A 350M-02b	LF2, Class 1 LF2, Class 2		K03011	N, NT, or QT			250	36	485-655	70-95	22	20 J at -46°C 27 J at -18°C
AOTA A 500/A 500M 00	1		K13502	QT	≤ 75	≤ 3	250	36	485-655	70-95	20	20 J at 4.4°C
ASTM A 508/A 508M-03a	1a		K13502	QT	≤ 75	≤ 3	250	36	485-655	70-95	20	20 J at 4.4°C
JIS G 3202:1988	SFVC 2 A			A, N, NT, or QT			245		490-640		18	
	SFVC 2 B			A, N, NT, or QT			245		490-640		18	27 J at 0°C
JIS G 3205:1988	SFL 2			A, NT, or QT			245		490-640		19	27 J at -45°C
	P305GH				≤ 35		305		490-610		22	
EN 10222-2:1999		1.0436		N or NT	35 < t ≤ 160		280		490-610		22	48 J at RT
				QT	≤ 70		285		510-630		22	48 J at RT
					≤ 16		355					55 J at 20°C
EN 10000 1:1000 A1:0001	DOCENIL	1.0565		N.	16 < t ≤ 35		355		400.000		00	47 J at 0°C
EN 10222-4:1998 A1:2001	P355NH			N	35 < t ≤ 70		335		490-630		23	40 J at -20°C 28 J at -40°C
				N.	≤ 16		355		490-610		22	55 J at 22°C
	P 35, PH 35			N	16 < t ≤ 35		355		490-610		22	47 J at 0°C
				QT	35 < t ≤ 50		345		490-610		22	40 J at -20°C
ISO 9327-4:1999					50 < t ≤ 70		325		490-610		22	63 J at 22°C
130 3327-4.1333					70 < t ≤ 100		315		470-610		21	55 J at 0°C
	PL 35, PLH 35			QT								47 J at -20°C
					$100 < t \le 250$		295		470-610		20	35 J at -40°C 27 J at -50°C

6.1.2A Mechanical Properties of Carbon Steel Forgings for Piping, Pressure Vessel and Components (Continued)

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Strength, min		Elongation,	Other
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or ksi		min, %	
					70 < t ≤ 100		365					63 J at 20°C
	P420QH	1.8936		QT	100 < t ≤ 250		345		510-670		18	55 J at 0°C
EN 40000 4 4000 A4 0004	1 420011	1.0000		Q1	250 < t ≤ 400		325		010 070		10	47 J at -20°C 34 J at -40°C
EN 10222-4:1998 A1:2001					≤ 16		420				20	55 J at 2°C
	P420NH	1.8932		N	16 < t ≤ 35		410		530-580			47 J at 0°C
	0	1.0002			35 < t ≤ 70		385					40 J at -20°C 28 J at -40°C
	P 42, PH 42			N	≤ 16		420		540-680		21	55 J at 22°C
					16 < t ≤ 35		410					47 J at 0°C 40 J at -20°C
ISO 9327-4:1999	PL 42, PLH 42				$35 < t \le 50$		400		540-680		21	63 J at 22°C
100 3027 4.1333				QT	50 < t ≤ 70		380		340-000			55 J at 0°C
					70 < t ≤ 100		365		510-670		20	47 J at -20°C
					100 < t ≤ 250		345		510-670		19	35 J at -40°C 27 J at -50°C

6.1.2B Chemical Composition of Carbon Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class, Type, Symbol or Name	Steel	UNS	Weight, %, max, Unless Otherwise Specified										
Designation			Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others		
EN 10222-4:1998 A1:2001	P285QH P285NH	1.0478 1.0477		0.18	0.60	0.40	0.025	0.015	0.30	0.30	0.08	Al 0.020-0.060; N 0.020; Cu 0.20; Nb 0.03; V 0.05; Nb+V 0.05		
	P 28, PH 28			0.18			0.035	0.030				Al 0.020 min; Cu 0.30; N 0.020; Nb0.05; Ti 0.03;		
ISO 9327-4:1999	PL 28			0.16	0.50-1.40	0.10-0.40	0.025	0.020	0.30	0.30	0.08	V 0.05; Cr+Cu+Mo to 0.45; Nb+Ti+V to 0.05		
JIS G 3202:1988	SFVC 1			0.30	0.40-1.35	0.35	0.030	0.030						
EN 10222-2:1999	P245GH	1.0352		0.08-0.20	0.50-1.30	0.40	0.025	0.015						
ASTM A 181/A 181M-01	60		K03502	0.35	1.10	0.10-0.35	0.05	0.05						
ASTM A 266/A 266M-03a	1			0.30	0.40-1.05	0.15-0.35	0.025	0.025						
ASTM A 350/A 350M-02b	LF1		K03009	0.30	0.60-1.35	0.15-0.30	0.035	0.040	0.30	0.40	0.12	Cu 0.40; Nb 0.02; V 0.08; Cu+Ni+Cr+Mo+V 1.00; Cr+Mo 0.32		
JIS G 3205:1988	SFL 1			0.30	1.35	0.35	0.030	0.030						
EN 10222-2:1999	P280GH	1.0426		0.08-0.20	0.90-1.50	0.40	0.025	0.015						
EN 10222-4:1998 A1:2001	P355QH	1.0571		0.20	0.90-1.65	0.10-0.50	0.025	0.015	0.30	0.30	0.08	Al 0.020-0.060; N 0.020; Cu 0.20; Nb 0.05; V 0.10; Nb+V 0.12		
ASTM A 541/A 541M-95 (1999)	1			0.35	0.40-0.90	0.15-0.35	0.025	0.025	0.25	0.40	0.10	V 0.05		
ASTIM A 541/A 541M-95 (1999)	1A			0.30	0.70-1.35	0.15-0.40	0.025	0.025	0.25	0.40	0.10	V 0.05		
ASTM A 105/A 105M-03			K03504	0.35	0.60-1.05	0.10-0.35	0.035	0.040	0.30	0.40	0.12	Cu 0.40; V 0.08; Cu+Ni+Cr+Mo+V 1.00; Cr+Mo 0.32		
ASTM A 266/A 266M-03a	2		K03506	0.35	0.40-1.05	0.15-0.35	0.025	0.025						
A31W A 200/A 200W-03a	4		K03017	0.30	0.80-1.35	0.15-0.40	0.025	0.025						
ASTM A 181/A 181M-01	70		K03502	0.35	1.10	0.10-0.35	0.05	0.05						
ASTM A 350/A 350M-02b	LF2		K03011	0.30	0.60-1.35	0.15-0.30	0.035	0.040	0.30	0.40	0.12	Cu 0.40; Nb 0.02; V 0.08; Cu+Ni+Cr+Mo+V 1.00; Cr+Mo 0.32		
ASTM A 508/A 508M-03a	1		K13502	0.35	0.40-1.05	0.15-0.40	0.025	0.025	0.25	0.40	0.10	V 0.05		
A3 I W A 506/A 506WI-03a	1A		K13502	0.30	0.70-1.35	0.15-0.40	0.025	0.025	0.25	0.40	0.10	V 0.05		
JIS G 3202:1988	SFVC 2 A			0.35	0.40-1.10	0.35	0.030	0.030						
JIS G 3202.1966	SFVC 2 B			0.30	0.70-1.35	0.35	0.030	0.030						
JIS G 3205:1988	SFL 2			0.30	1.35	0.35	0.030	0.030						
EN 10222-2:1999	P305GH	1.0436		0.15-0.20	0.90-1.60	0.40	0.025	0.015						
EN 10222-4:1998 A1:2001	P355NH	1.0565		0.20	0.90-1.65	0.10-0.50	0.025	0.015	0.30	0.30	0.08	Al 0.020-0.060; N 0.020; Cu 0.20; Nb 0.05; V 0.10; Nb+V 0.12		
ISO 9327-4:1999	P 35, PH 35 PL 35, PLH 35			0.20 0.18	0.90-1.70	0.10-0.50	0.035 0.025	0.030 0.020	0.30	0.30	0.08	Al 0.020 min; Cu 0.30; N 0.020; Nb 0.05; Ti 0.03; V 0.10: Cr+Cu+Mo 0.45: Nb+Ti+V 0.12		

6.1 Carbon Steel Forgings

6.1.2B Chemical Composition of Carbon Steel Forgings for Piping, Pressure Vessel and Components (Continued)

Standard	Grade, Class,	Steel	UNS				W	/eight, %, m	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
:N 10222-4:1998 A1:2001	P420QH	1.8936		0.20	1 00-1 70	0.10-0.60	0.025	0.015	0.30	1.00	0.10	Al 0.020-0.060; N 0.020; Cu 0.20;
LN 10222-4.1998 A1.2001	P420NH	1.8932		0.20	1.00-1.70	0.10-0.00	0.025	0.015	0.30	1.00	0.10	Nb 0.05; V 0.20; Nb+V 0.22
ISO 0227 4:1000	P 42 PH 42			0.20	1 00 1 70	0.10-0.60	0.035	0.030	0.30	1.00	0.10	AL 0.020 min; Cu 0.30; N 0.020; Nb 0.05;
SO 9327-4:1999 ⊢	PL 42, PLH 42			0.20	1.00-1.70	0.10-0.60	0.025	0.020	0.30	1.00	0.10	Ti 0.20; V 0.20; Nb+Ti+V 0.22

6.2 Alloy Steel Forgings

6.2.1A Chemical Composition of 11/4Cr-1/4Mo Alloy Steel Forgings for General Use

Standard	Grade, Class,	Steel	UNS				W	/eight, %, n	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 3221:1988	SFCM 690 S			0.48	0.30-0.85	0.15-0.35	0.030	0.030	0.90-1.50		0.15-0.30	
EN 10250-3:1999	25CrMo4	1.7218		0.22-0.29	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-30	
JIS G 3221:1988	SFCM 740 S			0.48	0.30-0.85	0.15-0.35	0.030	0.030	0.90-1.50		0.15-0.30	
EN 10250-3:1999	42CrMo4	1.7225		0.38-0.45	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-30	
JIS G 3221:1988	SFCM 780 S			0.48	0.30-0.85	0.15-0.35	0.030	0.030	0.90-1.50		0.15-0.30	
EN 10250-3:1999	34CrMo4	1.7220		0.30-0.37	0.60-0.90	0.40	0.035	0.035	0.90-1.20		0.15-30	
EN 10200-3.1999	50CrMo4	1.7228		0.46-0.54	0.50-0.80	0.40	0.035	0.035	0.90-1.20		0.15-30	

6.2 Alloy Steel Forgings

6.2.1B Mechanical Properties of 11/4 Cr-1/4 Mo Alloy Steel Forgings for General Use

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
				HT	< 200		460				17	see standard for
JIS G 3221:1988	SFCM 690 S			HT	200 ≤ t < 400		450		690-830		16	impact data,
				HT	400 ≤ t < 700		450				15	201 HB min
					≤ 70		450		700		15	50 J at RT
EN 10250-3:1999	25CrMo4	1.7218		QT	70 < t ≤ 160		400		650		17 L; 13 T	L: 45 J at RT T: 27 J at RT
					160 < t ≤ 330		380		600		18 L; 14 T	L: 38 J at RT T: 22 J at RT
				HT	< 200		510				16	see standard for
JIS G 3221:1988	SFCM 740 S			HT	200 ≤ t < 400		500		740-880		15	impact data,
				HT	400 ≤ t < 700		490				14	217 HB min
					≤ 160		500		750		14 L; 10 T	L: 30 J at RT T: 16 J at RT
N 10250-3:1999	42CrMo4	1.7225		QT	160 < t ≤ 330		460		700		15 L; 11 T	L: 27 J at RT T: 14 J at RT
					330 < t ≤ 500		390		600		16 L; 12 T	L: 22 J at RT T: 12 J at RT
				HT	< 200		560				15	see standard
JIS G 3221:1988	SFCM 780 S			HT	200 ≤ t < 400		550		780-930		14	for impact data,
				HT	400 ≤ t < 700		540				13	229 HB min
					≤ 70		550		800		14	45 J at RT
	34CrMo4	1.7220		QT	70 < t ≤ 160		450		700		15 L; 10 T	L: 40 J at RT T: 22 J at RT
					160 < t ≤ 330		410		650		16 L; 12 T	L: 33 J at RT T: 17 J at RT
N 10250-3:1999					≤ 160		550		800		13 L; 9 T	L: 25 J at RT T: 14 J at RT
	50CrMo4	1.7228		QT	160 < t ≤ 330		540		750		14 L; 10 T	L: 20 J at RT T: 12 J at RT
					330 < t ≤ 500		490		700		15 L; 11 T	L: 15 J at RT T: 10 J at RT

6.2 Alloy Steel Forgings

6.2.2 Alloy Steel Forgings for Piping, Pressure Vessel and Components

6.2.2.1A Chemical Composition of Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, m	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10222-2:1999	16Mo3	1.5415		0.12-0.20	0.40-0.90	0.35	0.025	0.015			0.25-0.35	
ISO 9327-2:1999	16Mo3			0.12-0.20	0.40-0.90	0.35	0.035	0.030	0.30		0.25-0.35	Cu 0.30
JIS G 3203:1988	SFVA F 1			0.30	0.60-0.90	0.35	0.030	0.030			0.45-0.65	
ASTM A 182/A 182M-02	F 1		K12822	0.28	0.60-0.90	0.15-0.35	0.045	0.045			0.44-0.65	
ASTM A 336/A 336M-03a	F1		K12520	0.20-0.30	0.60-0.80	0.20-0.35	0.025	0.025			0.40-0.60	

6.2.2.1B Mechanical Properties of Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
					≤ 35		295					L. FO. Let 0°C
				N, QT	35 < t ≤ 70		285		440-570		23 L; 21 T	L: 50 J at 0°C T: 34 J at 0°C
EN 10222-2:1999	16Mo3	1.5415			70 < t ≤ 100		275					1.343 at 0 C
				QT	≤ 250		265		440-570		23 L: 21 T	L: 50 J at 0°C
				Qı	250 < t ≤ 500		250		420-550		23 L, 21 1	T: 34 J at 0°C
				N.I.	≤ 40		270		450-600		26 L; 24 T	1 40 1 -1 0000
ISO 9327-2:1999	16Mo3			N or NT	40 < t ≤ 60		260		450-600		25 L; 23 T	L: 40 J at 20°C
130 9327-2.1999	TOIVIOS			or QT	60 < t ≤ 100		240		430-580		24 L; 22 T	T: 27 J at 20°C
				01 021	100 < t ≤ 250		220		420-570		21 L; 19 T	1. 27 3 at 20 C
JIS G 3203:1988	SFVA F 1			A or NT			275		480-660		18	
ASTM A 182/A 182M-02	F 1		K12822	A, NT			275	40	485	70	20.0	143-192 HB
ASTM A 336/A 336M-03a	F1		K12520	A, NT			275	40	485-660	70-95	20	

6.2.2 Alloy Steel Forgings for Piping, Pressure Vessel and Components

6.2.2.2A Chemical Composition of ½Cr-½Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, r	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number		С	Mn	Si	P	s	Cr	Ni	Мо	Others
JIS G 3203:1988	SFVA F 2			0.20	0.30-0.80	0.60	0.030	0.030	0.50-0.80		0.45-0.65	
ASTM A 182/A 182M-02	F2		K12122	0.05-0.21	0.30-0.80	0.10-0.60	0.040	0.040	0.50-0.81		0.44-0.65	

6.2.2.2B Mechanical Properties of ½Cr-½Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3203:1988	SFVA F 2			A or NT			275		480-660		18	
ASTM A 182/A 182M-02	F2		K12122	A, NT			275	40	485	70	20.0	143-192 HB

6.2.2.3A Chemical Composition of 1Cr-½Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, n	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number		С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10222-2:1999	13CrMo4-5	1.7335		0.08-0.18	0.40-1.00	0.35	0.025	0.015	0.70-1.15		0.40-0.60	
ISO 9327-2:1999	14CrMo4-5			0.08-0.18	0.40-1.00	0.35	0.035	0.030	0.70-1.15		0.40-0.60	Cu 0.30
JIS G 3203:1988	SFVA F 12			0.20	0.30-0.80	0.60	0.030	0.030	0.80-1.25		0.45-0.65	
ASTM A 182/A 182M-02	F 12, Class 2		K11564	0.10-0.20	0.30-0.80	0.10-0.60	0.040	0.040	0.80-1.25		0.44-0.65	
ASTM A 336/A 336M-03a	F12		K11564	0.10-0.20	0.30-0.80	0.10-0.60	0.025	0.025	0.80-1.10		0.45-0.65	

6.2.2.3B Mechanical Properties 1Cr-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
				NT	≤ 35		295		440-590		20 L; 18 T	L: 44 J at 0°C
				INI	$35 < t \le 70$		285		440-590		20 L, 10 1	T: 27 J at 0°C
EN 10222-2:1999	13CrMo4-5	1.7335			70 < t ≤ 100		275		440-590			1.44 1.4000
				NT or QT	100 < t ≤ 250		265		440-590		20 L; 18 T	L: 44 J at 0°C T: 27 J at 0°C
					$250 < t \le 500$		240		420-570			1.27 3 at 0 C
					≤ 40		300		450-600		22 L; 20 T	
ISO 9327-2:1999	14CrMo4-5			NT	40 < t ≤ 60		300		450-600		21 L; 19 T	L: 40 J at 20°C
130 9327-2.1999	14011104-5			or QT	60 < t ≤ 100		275		440-590		20 L; 18 T	T: 27 J at 20°C
				Q1	100 < t ≤ 250		255		430-580		20 L; 18 T	
JIS G 3203:1988	SFVA F 12			A or NT			275		480-660		18	
ASTM A 182/A 182M-02	F 12, Class 2		K11564	A, NT			275	40	485	70	20.0	143-207 HB
ASTM A 336/A 336M-03a	F12		K11564	A, NT			275	40	485-660	70-95	20	

6.2.2 Alloy Steel Forgings for Piping, Pressure Vessel and Components

6.2.2.4A Chemical Composition of 11/4Cr-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, r	nax, Unless (Otherwise	Specified	
Designation	Type, Symbol or Name	Number		С	Mn	Si	P	s	Cr	Ni	Мо	Others
JIS G 3203:1988	SFVA F 11 A			0.20	0.30-0.80	0.50-1.00	0.030	0.030	1.00-1.50		0.45-0.65	
ASTM A 182/A 182M-02	F 11, Class 2		K11572	0.10-0.20	0.30.0.90	0.50-1.00	0.040	0.040	1.00-1.50		0.44-0.65	
ASTIVI A 102/A 102IVI-02	F 11, Class 3		KIISIZ	0.10-0.20	0.30-0.60	0.50-1.00	0.040	0.040	1.00-1.50		0.44-0.05	
A C.T.M. A. 000 / A. 000 M. 00 -	F11, Class 2		V44570	0.10.0.00	0.00.0.00	0.50.4.00	0.005	0.005	1 00 1 50		0.45.0.05	
ASTM A 336/A 336M-03a	F11, Class 3		K11572	0.10-0.20	0.30-0.80	0.50-1.00	0.025	0.025	1.00-1.50		0.45-0.65	
JIS G 3203:1988	SFVA F 11 B			0.20	0.30-0.80	0.50-1.00	0.030	0.030	1.00-1.50		0.45-0.65	

6.2.2.4B Mechanical Properties 11/4Cr-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3203:1988	SFVA F 11 A			A or NT			275		480-660		18	
ASTM A 182/A 182M-02	F 11, Class 2		K11572	A. NT			275	40	485	70	20.0	143-207 HB
ASTIVI A 162/A 162W-02	F 11, Class 3		K11372	A, INI			310	45	515	75	30	156-207 HB
ASTM A 336/A 336M-03a	F11, Class 2		K11572	A NIT			275	40	485-660	70-95	20	
AST W A 330/A 330W-03a	F11, Class 3		K11372	572 A, NT			310	45	515-690	75-100	18	
JIS G 3203:1988	SFVA F 11 B			A or NT			315		520-690		18	

6.2.2.5A Chemical Composition of 21/4Cr-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, r	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	P	s	Cr	Ni	Мо	Others
JIS G 3203:1988	SFVA F 22 A			0.15	0.30-0.60	0.50	0.030	0.030	2.00-2.50		0.90-1.10	
ASTM A 182/A 182M-02	F 22, Class 1		K21590	0.05-0.15	0.30-0.60	0.50	0.040	0.040	2.00-2.50		0.87-1.13	
ASTM A 336/A 336M-03a	F22, Class 1		K21590	0.05-0.15	0.30-0.60	0.50	0.025	0.025	2.00-2.50		0.90-1.10	
EN 10222-2:1999	11CrMo9-10	1.7383		0.08-0.15	0.40-0.80	0.50	0.025	0.015	2.00-2.50		0.90-1.10	
ISO 9327-2:1999	13CrMo9-10			0.08-0.15	0.40-0.70	0.50	0.035	0.030	2.00-2.50		0.90-1.10	Cu 0.30
ASTM A 182/A 182M-02	F 22, Class 3		K21590	0.05-0.15	0.30-0.60	0.50	0.040	0.040	2.00-2.50		0.87-1.13	
ASTM A 336/A 336M-03a	F22, Class 3		K21590	0.05-0.15	0.30-0.60	0.50	0.025	0.025	2.00-2.50		0.90-1.10	
JIS G 3203:1988	SFVA F 22 B			0.15	0.30-0.60	0.50	0.030	0.030	2.00-2.50		0.90-1.10	
JIS G 3206:1993	SFVCM F22B			0.17	0.30-0.60	0.50	0.015	0.015	2.00-2.50		0.90-1.10	V 0.03
ASTM A 508/A 508M-03a	22, Class 3		K21590	0.11-0.15	0.30-0.60	0.50	0.015	0.015	2.00-2.50	0.25	0.90-1.10	V 0.02
ASTM A 541/A 541M-95 (1999)	22, Class 3		K21390	0.11-0.15	0.30-0.60	0.50	0.015	0.015	2.00-2.50	0.25	0.90-1.10	V 0.02
JIS G 3206:1993	SFVCM F22V			0.17	0.30-0.60	0.10	0.015	0.010	2.00-2.50		0.90-1.10	V 0.25-0.35
ASTM A 336/A 336M-03a	F22V			0.11-0.15	0.30-0.60	0.10	0.015	0.010	2.00-2.50	0.25	0.90-1.10	Cu 0.20; V 0.25-0.35; Cb 0.07; Ti 0.030; B 0.0020; Ca 0.015
ASTM A 541/A 541M-95 (1999)	22V			0.11-0.15	0.30-0.60	0.10	0.015	0.010	2.00-2.50	0.25	0.90-1.10	Cu 0.20; V 0.25-0.35; Cb 0.07; Ti 0.030; B 0.0020; Ca 0.015
ASTM A 182/A 182M-02	F 22V		K31835	0.11-0.15	0.30-0.60	0.10	0.015	0.010	2.00-2.50	0.25	0.90-1.10	Cu 0.20; V 0.25-0.35; Cb 0.07; Ti 0.030; B 0.002; Ca 0.015

6.2.2.5B Mechanical Properties of 21/4Cr-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thicl	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3203:1988	SFVA F 22 A			A or NT			205		410-590		18	
ASTM A 182/A 182M-02	F 22, Class 1		K21590	A, NT			205	30	415	60	20.0	170 HB max
ASTM A 336/A 336M-03a	F22, Class 1		K21590	A, NT			205	30	415-585	60-85	20	
EN 10222-2:1999	11CrMo9-10	1.7383		NT or QT	200 < t ≤ 500		265		450-600		23 L; 21 T	L: 50 J at RT 40 J at 0°C T: 34 J at RT 27 J at 0°C
					≤ 60		265		480-620		20 L; 18 T	
ISO 9327-2:1999	13CrMo9-10			NT or QT	60 < t ≤ 100		260		470-620		20 L; 18 T	L: 40 J at 20°C
150 9327-2: 1999	13Crivio9-10			NI Or QI	100 < t ≤ 150		250		460-610		20 L; 18 T	T: 27 J at 20°C
					150 < t ≤ 300		240		450-600		20 L; 18 T	1.27 J at 20 C
ASTM A 182/A 182M-02	F 22, Class 3			A, NT			310	45	515	75	20.0	156-207 HB
ASTM A 336/A 336M-03a	F22, Class 3			A, NT			310	45	515-690	75-100	19	
JIS G 3203:1988	SFVA F 22 B			A or NT			315		520-690		18	
EN 10222-2:1999	11CrMo9-10	1.7383		NT	≤ 200		310		520-670		20 L; 20 T	L: 60 J at RT 47 J at 0°C T: 50 J at RT 27 J at 0°C
JIS G 3206:1993	SFVCM F22B			QT			380		580-760		16	54 J at -18°C
ASTM A 508/A 508M-03a	22, Class 3		K21590	QT			380	55	585-760	85-110	18	
ASTM A 541/A 541M-95 (1999)	22, Class 3		K21390	QT			380	55	585-760	85-110	18	47 J at 4°C
JIS G 3206:1993	SFVCM F22V			NT			415		580-760		16	54 J at -18°C
ASTM A 336/A 336M-03a	F22V			A, NT			415	60	585-760	85-110	18	
ASTM A 541/A 541M-95 (1999)	22V			QT			415	60	585-760	85-110	18	55 J at -18°C
ASTM A 182/A 182M-02	F 22V		K31835	NT, QT			415	60	585-780	85-110	18.0	HB 174-237

6.2.2.6A Chemical Composition of 3Cr-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, ı	max, Unless	Otherwis	e Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 3203:1988	SFVA F 21 A			0.15	0.30-0.60	0.50	0.030	0.030	2.65-3.35		0.80-1.00	
ASTM A 336/A 336M-03a	F21, Class 1		K31545	0.05-0.15	0.30-0.60	0.50	0.025	0.025	2.7-3.3		0.80-1.06	
ASTM A 182/A 182M-02	F 21		K31545	0.05-0.15	0.30-0.60	0.50	0.040	0.040	2.7-3.3		0.80-1.06	
ASTM A 336/A 336M-03a	F21, Class 3		K31545	0.05-0.15	0.30-0.60	0.50	0.025	0.025	2.7-3.3		0.80-1.06	
JIS G 3203:1988	SFVA F 21 B			0.15	0.30-0.60	0.50	0.030	0.030	2.65-3.35		0.80-1.00	
JIS G 3206:1993	SFVCM F3V			0.17	0.30-0.60	0.10	0.015	0.010	2.75-3.25		0.90-1.10	V 0.20-0.30
ASTM A 182/A 182M-02	F 3V		K31830	0.05-0.18	0.30-0.60	0.10	0.020	0.020	2.8-3.2		0.90-1.10	V 0.20-0.30; Ti 0.015-0.035; B 0.001-0.003
ASTM A 336/A 336M-03a	F3V			0.10-0.15	0.30-0.60	0.10	0.020	0.020	2.7-3.3		0.90-1.10	V 0.20-0.30; Ti 0.015-0.035; B 0.001-0.003
ASTM A 508/A 508M-03a	3V		K31830	0.10-0.15	0.30-0.60	0.10	0.020	0.020	2.8-3.3		0.90-1.10	V 0.20-0.30; Ti 0.015-0.035; B 0.001-0.003
ASTM A 541/A 541M-95 (1999)	3V		K31830	0.10-0.15	0.30-0.60	0.10	0.020	0.020	2.8-3.3		0.90-1.10	V 0.20-0.30; Ti 0.015-0.035; B 0.001-0.003

6.2.2.6B Mechanical Properties of 3Cr-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3203:1988	SFVA F 21 A			A or NT			205		410-590		18	
ASTM A 336/A 336M-03a	F21, Class 1		K31545	A, NT			205	30	415-585	60-85	20	
ASTM A 182/A 182M-02	F 21		K31545	A, NT			310	45	515	75	20.0	156-207 HB
ASTM A 336/A 336M-03a	F21, Class 3		K31545	A, NT			310	45	515-690	75-100	19	
JIS G 3203:1988	SFVA F 21 B			A or NT			315		520-690		18	
JIS G 3206:1993	SFVCM F3V			NT			415		580-760		16	54 J at -18°C
ASTM A 182/A 182M-02	F 3V		K31830	A, NT			415	60	585-760	85-110	18	174-237 HB
ASTM A 336/A 336M-03a	F3V			A, NT			415	60	585-760	85-110	18	
ASTM A 508/A 508M-03a	3V		K31830	QT			415	60	585-760	85-110	18	
ASTM A 541/A 541M-95 (1999)	3V		K31830	QT			415	60	585-760	85-110	18	55 J at -18°C

6.2.2.7A Chemical Composition of 5Cr-½Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	Veight, %, i	max, Unless	Otherwise	e Specified	
Designation	Type, Symbol or Name			С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10222-2:1999	X16CrMo5-1	1.7366		0.18	0.30-0.80	0.40	0.025	0.015	4.00-6.00		0.45-0.65	
JIS G 3203:1988	SFVA F 5 A			0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
ASTM A 336/A 336M-03a	F5		K41545	0.15	0.30-0.60	0.50	0.025	0.025	4.0-6.0	0.50	0.45-0.65	
ISO 9327-2:1999	X12CrMo5-1			0.08-0.15	0.30-0.60	0.50	0.035	0.030	4.00-6.00		0.45-0.65	
JIS G 3203:1988	SFVA F 5 B			0.15	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
ASTM A 182/A 182M-02	F 5		K41545	0.15	0.30-0.60	0.50	0.030	0.030	4.0-6.0	0.50	0.44-0.65	
ASTM A 336/A 336M-03a	F5A		K42544	0.25	0.60	0.50	0.025	0.025	4.0-6.0	0.50	0.45-0.65	
JIS G 3203:1988	SFVA F 5 C			0.25	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
ASTM A 182/A 182M-02	F 5a		K42544	0.25	0.60	0.50	0.040	0.030	4.0-6.0	0.50	0.44-0.65	
JIS G 3203:1988	SFVA F 5 D			0.25	0.30-0.60	0.50	0.030	0.030	4.00-6.00		0.45-0.65	
EN 10222-2:1999	X16CrMo5-1	1.7366		0.18	0.30-0.80	0.40	0.025	0.015	4.00-6.00		0.45-0.65	

6.2.2.7B Mechanical Properties of 5Cr-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10222-2:1999	X16CrMo5-1	1.7366		Α	≤ 300		205		410-510		18 L; 16 T	L: 40 J at RT T: 27 J at RT
JIS G 3203:1988	SFVA F 5 A			A or NT			245		410-590		18	
ASTM A 336/A 336M-03a	F5		K41545	A, NT			250	30	415-585	60-85	20	
ISO 9327-2:1999	X12CrMo5-1			Α	≤ 150		175		430-580		20 L; 18 T	
JIS G 3203:1988	SFVA F 5 B			A or NT			275		480-660		18	
ASTM A 182/A 182M-02	F 5		K41545	A, NT			275	40	485	70	20.0	143-217 HB
ASTM A 336/A 336M-03a	F5A		K42544	A, NT			345	50	550-725	80-105	19	
JIS G 3203:1988	SFVA F 5 C			A or NT			345		550-730		18	
ASTM A 182/A 182M-02	F 5a		K42544	A, NT			450	65	620	90	22.0	187-248 HB
JIS G 3203:1988	SFVA F 5 D			A or NT			450		620-780		18	
EN 10222-2:1999	X16CrMo5-1	1.7366		NT	≤ 300		420		640-780		16 L; 14 T	L: 40 J at RT T: 27 J at RT

6.2.2.8A Chemical Composition of 9Cr-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 182/A 182M-02	F9		K90941	0.15	0.30-0.60	0.50-1.00	0.030	0.030	8.0-10.0		0.90-1.10	
ASTM A 336/A 336M-03a	F9			0.15	0.30-0.60	0.50-1.00	0.025	0.025	8.0-10.0		0.90-1.10	
JIS G 3203:1988	SFVA F 9			0.15	0.30-0.60	0.50-1.00	0.030	0.030	8.00-10.00		0.90-1.10	
EN 10222-2:1999	X10CrMoVNb9-1	1.4903		0.08-0.12	0.30-0.60	0.50	0.025	0.015	8.00-9.50	0.40	0.85-1.05	Nb 0.06-0.10; V 0.18-0.25; N 0.030-0.070; Al 0.040

6.2.2.8B Mechanical Properties of 9Cr-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 182/A 182M-02	F 9		K90941	A, NT			380	55	585	85	20.0	179-217 HB
ASTM A 336/A 336M-03a	F9			A, NT			380	55	585-760	85-110	20	
JIS G 3203:1988	SFVA F 9			A or NT			380		590-760		18	
EN 10222-2:1999	X10CrMoVNb9-1	1.4903		NT	≤ 130		450		630-730		19 L; 17 T	L: 40 J at RT T: 27 J at RT

6.2.2.9A Chemical Composition of 11Cr-½Ni-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %,	max, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10222-2:1999	X20CrMoV11-1	1.4922		0.17-0.23	0.30-1.00	0.40	0.025	0.015	10.00-12.50	0.30-0.80	0.80-1.20	V 0.20-0.35
ISO 9327-2:1999	X20CrMoV12-1			0.17-0.23	0.30-1.00	0.40	0.035	0.030	10.00-12.50	0.30-1.00	0.80-1.20	V 0.20-0.35; AI 0.025

6.2.2.9B Mechanical Properties of 11Cr-1/2Ni-1Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thickr	iess	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
					≤ 100		500		700-850		16 L; 14 T	L: 39 J at RT T: 27 J at RT
EN 10222-2:1999	X20CrMoV11-1	1.4922		QT	100 < t ≤ 250		500		700-850		16 L; 14 T	L: 31 J at RT T: 27 J at RT
					250 < t ≤ 350		500		700-850		16 L; 14 T	L: 27 J at RT T: 27 J at RT
					≤ 100		500		700-850		16 L; 14 T	L: 39 J at 20°C T: 27 J at 20°C
ISO 9327-2:1999	X20CrMoV12-1			NT or QT	100 < t ≤ 200		500		700-850		16 L; 14 T	L: 31 J at 20°C T: 27 J at 20°C
					200 < t ≤ 300		500		700-850		14 L; 14 T	L: 27 J at 20°C T: 24 J at 20°C

6.2.2.10A Chemical Composition of Ni Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				٧	Veight, %, n	nax, Unles	s Otherwise S	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
EN 10222-3:1998	15NiMn6	1.6228		0.18	0.80-1.50	0.35	0.025	0.015		1.30-1.70		V 0.05
ISO 9327-3:1999	15NiMn6			0.18	0.80-1.50	0.35	0.025	0.020		1.30-1.70		V 0.05
ISO 9327-3:1999	12Ni14G1			0.15	0.30-0.80	0.35	0.025	0.020		3.25-3.75		V 0.05
150 9327-3.1999	12Ni14G2			0.15	0.30-0.60	0.33	0.025	0.020		3.25-3.75		V 0.05
EN 10222-3:1998	12Ni14	1.5637		0.15	0.30-0.80	0.35	0.020	0.010		3.25-3.75		V 0.05
ASTM A 350/A 350M-02b	LF3		K32025	0.20	0.90	0.20-0.35	0.035	0.040	0.30	3.3-3.7	0.12	Cu 0.40; Cb 0.02; V 0.03; Cr+Mo 0.32
JIS G 3205:1988	SFL 3			0.20	0.90	0.35	0.030	0.030		3.25-3.75		
EN 10222-3:1998	X12Ni5	1.5680		0.15	0.30-0.80	0.35	0.020	0.010		4.75-5.25		V 0.05
ISO 9327-3:1999	12Ni19			0.15	0.30-0.80	0.35	0.025	0.020		4.50-5.30		V 0.05
EN 10222-3:1998	X8Ni9	1.5662		0.10	0.30-0.80	0.35	0.020	0.010		8.50-10.00	0.10	V 0.05
ISO 9327-3:1999	X8Ni9			0.10	0.30-0.80	0.35	0.025	0.020		8.00-10.00	0.10	V 0.05

6.2.2.10B Mechanical Properties of Ni Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Type, Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10222-3:1998	15NiMn6	1.6228		N, NT, QT	≤ 35		355		470-640		20	see standard
LIN 10222-3.1990	ISINIIVIIO	1.0220		IN, INT, QT	$35 < t \le 50$		345		470-040		20	for impact data
ISO 9327-3:1999	15NiMn6			N. NT. QT	≤ 30		355		490-640		22	see standard
130 9327-3.1999	TOMINITO			IN, INT, QT	$30 < t \leq 50$		345		490-040		22	for impact data
				N	≤ 30		285					see standard
ISO 9327-3:1999	12Ni14G1			NT QT	30 < t ≤ 50		275		450-600		23	for impact data
150 9327-3:1999				N	≤ 30		355					aga atandard
	12Ni14G2			NT QT	30 < t ≤ 50		345		470-620		22	see standard for impact data
				N	≤ 35		355					
EN 10222-3:1998	12Ni14	1.5637		NT	35 < t ≤ 50		345		470-640		20	see standard for impact data
				QT	50 < t ≤ 70		335					ioi iiipaci uala
ASTM A 350/A 350M-02b	LF3, Class 1		Kaanas	N. NT or QT			260	37.5	485-655	70-95	22	20 J at -101°C
A3 TW A 350/A 350W-02D	LF3, Class 2		K32023	IN, INT OF QT			200	37.5	400-000	70-95	22	27 J at -101°C
JIS G 3205:1988	SFL 3			A, NT or QT			255		490-640		19	27 J at -101°C
EN 10222-3:1998	X12Ni5	1.5680		N, NT	≤ 35		390		510-710		19	see standard
LIN 10222-3.1990	ATZINIS	1.5000		QT	$35 < t \le 50$		380		310-710		19	for impact data
ISO 9327-3:1999	12Ni19			N	≤ 30		390		510-710		19	see standard
130 9327-3.1999	1211119			NT, QT	$30 < t \le 50$		380		310-710		19	for impact data
				N, NT	≤ 35		490					see standard
EN 10222-3:1998	X8Ni9	1.5662		IN, INI	$35 < t \le 50$		480		640-840		18	for impact data
				QT	$50 < t \le 70$		470					ioi iiiipaoi data
ISO 9327-3:1999	X8Ni9	i9		NNT	≤ 30		490		640-840		18	see standard
100 3021-3.1999	AOINIO			QT	$30 < t \le 50$		480		040-040		10	for impact data

6.2.2.11A Chemical Composition of Ni-Mn Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, m	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ISO 9327-3:1999	11MnNi5-3			0.14	0.70-1.50	0.50	0.025	0.020		0.30-0.80		Nb 0.05; V 0.05
EN 10222-3:1998	13MnNi6-3	1.6217		0.16	0.85-1.70	0.50	0.025	0.0015		0.30-0.85		Nb 0.05; V 0.05
ISO 9327-3:1999	13MnNi6-3			0.16	0.85-1.65	0.50	0.025	0.020		0.30-0.85		Nb 0.05; V 0.05

6.2.2.11B Mechanical Properties of Ni-Mn Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thickr	iess	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ISO 9327-3:1999	11MnNi5-3			N (+T)	≤ 30		285		420-530		24	see standard
130 9327-3.1999	I HVIHIVIO-3			14 (+1)	$30 < t \le 50$		275		420-330		24	for impact data
					≤ 35		285					and atomdord
EN 10222-3:1998	13MnNi6-3	1.6217		NT	$35 < t \le 50$		275		420-610		22	see standard for impact data
					50 < t ≤ 70		265					ioi iiipaot data
100 0207 2:1000	13MnNi6-3			NI (. T)	≤ 30		355		490-610		22	see standard
SO 9327-3:1999 13Mnl	131/111/10-3			N (+T)	30 < t ≤ 50		345		490-610		22	for impact data

6.2.2 Alloy Steel Forgings for Piping, Pressure Vessel and Components

6.2.2.12A Chemical Composition of %Ni-½Cr-Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, n	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 541/A 541M-95 (1999)	2, Class 1 and 2		K12765	0.27	0.50-0.90	0.15-0.35	0.025	0.025	0.25-0.45	0.50-1.00	0.55-0.70	V 0.05
ASTM A 508/A 508M-03a	2, Class 1 and 2		K12766	0.27	0.50-1.00	0.15-0.40	0.025	0.025	0.25-0.45	0.50-1.00	0.55-0.70	V 0.05
JIS G 3204:1988	SFVQ 2A, 2B			0.27	0.50-1.00	0.40	0.030	0.030	0.25-0.45	0.50-1.00	0.55-0.70	V 0.05

6.2.2.12B Mechanical Properties of 3/Ni-1/2Cr-Mo Alloy Steels Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 541/A 541M-95 (1999)	2, Class 1		K12765	QT			340	50	550-720	80-105	18	41 J at 4°C
ASTM A 508/A 508M-03a	2, Class 1		K12766	QT			345	50	550-725	80-105	18	
JIS G 3204:1988 (1991)	SFVQ 2A			QT			345		550-730		16	40 J at 0°C
ASTM A 541/A 541M-95 (1999)	2, Class 2		K12765	QT			450	65	620-790	90-115	16	47 J at 21°C
JIS G 3204:1988	SFVQ 2B			QT			450		620-790		14	47 J at 20°C
ASTM A 508/A 508M-03a	2, Class 2		K12766	QT			450	65	620-795	90-115	16	

6.2.2 Alloy Steel Forgings for Piping, Pressure Vessel and Components

6.2.2.13A Chemical Composition of %Ni-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, m	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	P	8	Cr	Ni	Мо	Others
ASTM A 541/A 541M-95 (1999)	3, Class 1 and 2		K12045	0.25	1.20-1.50	0.15-0.35	0.025	0.025	0.25	0.40-1.00	0.45-0.60	V 0.05
ASTM A 508/A 508M-03a	3, Class 1 and 2		K12042	0.25	1.20-1.50	0.15-0.40	0.025	0.025	0.25	0.40-1.00	0.45-0.60	V 0.05
JIS G 3204:1988	SFVQ 1 A, 1 B			0.25	1.20-1.50	0.40	0.030	0.030	0.25	0.40-1.00	0.45-0.60	V 0.05

6.2.2.13B Mechanical Properties of %Ni-½Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 541/A 541M-95 (1999)	3, Class 1		K12045	QT			340	50	550-720	80-105	18	41 J at 4°C
ASTM A 508/A 508M-03a	3, Class 1		K12042	QT			345	50	550-725	80-105	18	
JIS G 3204:1988	SFVQ 1 A			QT			345		550-730		16	40 J at 0°C
ASTM A 541/A 541M-95 (1999)	3, Class 2		K12045	QT			450	65	620-790	90-115	16	47 J at 21°C
JIS G 3204:1988	SFVQ 1 B			QT			450		620-790		14	47 J at 20°C
ASTM A 508/A 508M-03a	3, Class 2		K12042	QT			450	65	620-795	90-115	16	

6.2.2 Alloy Steel Forgings for Piping, Pressure Vessel and Components

6.2.2.14A Chemical Composition of 31/4Ni-13/4Cr-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS				W	/eight, %, r	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ASTM A 541/A 541M-95 (1999)	4N, Class 3			0.23	0.20-0.40	0.30	0.025	0.025	1.25-2.00	2.8-3.9	0.40-0.60	V 0.03
JIS G 3204:1988	SFVQ 3			0.23	0.20-0.40	0.40	0.020	0.020	1.50-2.00	2.75-3.90	0.40-0.60	V 0.03
ASTM A 508/A 508M-03a	4N, Class 3			0.23	0.20-0.40		0.020	0.020	1.50-2.00	2.8-3.9	0.40-0.60	V 0.03

6.2.2.14B Mechanical Properties of 31/4Ni-13/4Cr-1/2Mo Alloy Steel Forgings for Piping, Pressure Vessel and Components

Standard	Grade, Class,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 541/A 541M-95 (1999)	4N, Class 3			QT			480	70	620-790	90-115	20	47 J at 4°C
JIS G 3204:1988	SFVQ 3			QT			490		620-790		18	47 J at -30°C
ASTM A 508/A 508M-03a	4N, Class 3			QT			485	70	620-795	90-115	20	

6.3.1A Chemical Composition of Martensitic Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	max, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 3214:1991	SUS F 410-A, B, C, D			0.15	1.00	1.00	0.040	0.030	11.50-13.50	0.50		
ASTM A 182/A 182M-02	F 6a		S41000	0.15	1.00	1.00	0.040	0.030	11.5-13.5	0.50		
ASTM A 473-01	410		S41000	0.15	1.00	1.00	0.040	0.030	11.5-13.5	0.75		
EN 10250-4:1999	X12Cr13	1.4006		0.08-0.15	1.50	1.00	0.040	0.030	11.50-13.50	0.75		
ASTM A 1021-02	Grade A		S41000	0.15	1.00	1.00	0.018	0.015	11.5-13.5	0.75		
ASTIVI A 1021-02	Grade B			0.10-0.15	0.25-0.80	0.50	0.018	0.015	11.5-13.5	0.50		
ASTM A 182/A 182M-02	F 6b		S41026	0.15	1.00	1.00	0.020	0.020	11.5-13.5	1.00-2.00	0.40-0.60	Cu 0.50
JIS G 3214:1991	SUS F 6B			0.15	1.00	1.00	0.020	0.020	11.50-13.50	1.00-2.00	0.40-0.60	Cu 0.50
EN 10250-4:1999	X3CrNiMo13-4	1.4313		0.05	1.50	0.70	0.040	0.015	12.00-14.00	3.50-4.50	0.30-0.70	N 0.020
EN 10222-5:1999	X3CrNiMo13-4	1.4313		0.05	1.50	0.70	0.040	0.015	12.00-14.00	3.50-4.50	0.30-0.70	N 0.020
ASTM A 182/A 182M-02	F 6NM		S41500	0.05	0.5-1.0	0.60	0.030	0.030	11.5-14.0	3.5-5.5	0.5-1.0	
JIS G 3214:1991	SUS F 6NM			0.05	0.50-1.00	0.60	0.030	0.030	11.50-14.00	3.50-5.50	0.50-1.00	
ASTM A 473-01			S41500	0.05	0.5-1.0	0.60	0.030	0.030	11.5-14.0	3.5-5.5	0.5-1.0	

6.3.1B Mechanical Properties of Martensitic Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	SUS F 410-A			QT			275		480		16	143-187 HB
JIS G 3214:1991	SUS F 410-B			QT			380		590		16	167-229 HB
313 G 3214.1991	SUS F 410-C			QT			585		760		14	217-302 HB
	SUS F 410-D			QT			760		900		11	262-321 HB
	F 6a, Class 1			NT			275	40	485	70	18	143-207 HB
ASTM A 182/A 182M-02	F 6a, Class 2		S41000	NT			380	55	585	85	18	167-229 HB
A31WA 102/A 102W-02	F 6a, Class 3		341000	NT			585	85	760	110	15	235-302 HB
	F 6a, Class 4			NT			760	110	895	130	12	263-321 HB
ASTM A 473-01	410		S41000	Α			275	40	485	70	20	223 HB max
EN 10250-4:1999	X12Cr13	1.4006		QT 650	≤ 160		450		650-850		15	25 J at RT
LIN 10230-4.1999	X120113	1.4000		Α					730 max			220 HB max
	Grade A, Class 1		S41000	QT			485	70	690	100	20	30 ft-lb at RT 255 HB/26 HRC
ASTM A 1021-02	Grade A, Class 2		S41000	QT			550	80	760	110	18	25 J at RT 269 HB/28 HRC
	Grade B, Class 1			QT			620	90	760	110	18	30 ft-lb at RT 269 HB/28 HRC
ASTM A 182/A 182M-02	F 6b		S41026	NT			620	90	760-930	110-135	16	235-285 HB
JIS G 3214:1991	SUS F 6B			QT			620		760-930		15	217-285 HB
				QT 650	≤ 450		520		650-830		15 L; 12 T	L: 70 J at RT T: 50 J at RT
EN 10250-4:1999	X3CrNiMo13-4	1.4313		QT 780	≤ 450		620		780-980		15 L; 12 T	L: 70 J at RT T: 50 J at RT
				QT 900	≤ 450		800		900-1100		12	L: 50 J at RT T: 40 J at RT
				Α					1100 max			320 HB max
EN 10000 5:1000	X3CrNiMo13-4	1 4010		QT+T	≤ 350		550		750-900		17 L; 16 T	L: 100 J at 20°C T: 80 J at 20°C
EN 10222-5:1999	A3Criviivio i 3-4	1.4313		QT	≤ 250		650		780-930		17 L; 15 T	L: 90 J at 20°C T: 70 J at 20°C
ASTM A 182/A 182M-02	F 6NM		S41500	NT			620	90	790	115	15	295 HB max
JIS G 3214:1991	SUS F 6NM			QT			620		790		14	295 HB max
ASTM A 473-01			S41500	NT			620	90	795	115	15	295 HB max

6.3.2A Chemical Composition of Ferritic Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS				V	/eight, %, r	nax, Unless (Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10250-4:1999	X6Cr17	1.4016		0.08	1.00	1.00	0.040	0.030	16.00-18.00			
ASTM A 182/A 182M-02	430		S43000	0.12	1.00	0.75	0.040	0.030	16.0-18.0	0.50		
ASTM A 473-01	430		S43000	0.12	1.00	1.00	0.040	0.030	16.0-18.0	0.75		

6.3.2B Mechanical Properties of Ferritic Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS	Product	Th	ickness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation			Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10250-4:1999	X6Cr17	1.4016		Α	≤ 100		240		400-630			200 HB max
ASTM A 182/A 182M-02	430		S43000	Α			240	35	415	60	20	190 HB max
ASTM A 473-01	430		S43000	Α			240	35	485	70	20	217 HB max

6.3.3A Chemical Composition of Austenitic Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10222-5:1999	X5CrNi18-10	1.4301		0.07	2.00	1.00	0.045	0.015	17.00-19.50	8.00-10.50		N 0.11
EN 10250-4:1999	X5CrNi18-10	1.4301		0.07	2.00	1.00	0.045	0.030	17.00-19.50	8.00-10.50		N 0.11
ISO 9327-5:1999	X5CrNi18-9			0.07	2.00	1.00	0.045	0.030	17.00-19.00	8.00-11.00		
ASTM A 182/A 182M-02	F 304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		N 0.10
ASTM A 473-01	304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		N 0.10
ASTM A 965/A 965M-02	F 304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		N 0.10
JIS G 3214:1991	SUS F 304			0.08	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		
EN 10250-4:1999	X2CrNi18-9	1.4307		0.030	2.00	1.00	0.045	0.030	17.50-19.50	8.00-10.00		N 0.11
EN 10250-4.1999	X2CrNi19-11	1.4306		0.030	2.00	1.00	0.045	0.030	18.00-20.00	10.00-12.00		N 0.11
JIS G 3214:1991	SUS F 304L			0.030	2.00	1.00	0.040	0.030	18.00-20.00	9.00-13.00		
ISO 9327-5:1999	X2CrNi18-10			0.030	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		
ASTM A 182/A 182M-02	F 304L		S30403	0.030	2.00	1.00	0.045	0.030	18.0-20.0	8.0-13.0		N 0.10
ASTM A 473-01	304L		S30403	0.030	2.00	1.00	0.045	0.030	18.0-20.0	8.0-13.0		N 0.10
ASTM A 965/A 965M-02	F 304L		S30403	0.030	2.00	1.00	0.045	0.030	18.0-20.0	8.0-13.0		N 0.10
EN 10222-5:1999	X2CrNi18-9	1.4307		0.030	2.00	1.00	0.045	0.015	17.50-19.50	8.00-10.00		N 0.11
EN 10222-5:1999	X6CrNi18-10	1.4948		0.04-0.08	2.00	1.00	0.035	0.015	17.00-19.00	8.00-11.00		N 0.11
ISO 9327-5:1999	X7CrNi18-9			0.04-0.10	2.00	1.00	0.045	0.030	17.00-19.00	8.00-11.00		
ASTM A 182/A 182M-02	F 304H		S30409	0.04-0.10	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
ASTM A 965/A 965M-02	F 304H		S30409	0.04-0.10	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
JIS G 3214:1991	SUS F 304H			0.04-0.10	2.00	1.00	0.040	0.030	18.00-20.00	8.00-12.00		
ASTM A 182/A 182M-02	F 304N		S30451	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
ASTM A 965/A 965M-02	F 304N		S30451	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
JIS G 3214:1991	SUS F 304N			0.08	2.00	0.75	0.040	0.030	18.00-20.00	8.00-11.00		N 0.10-0.16
ASTM A 182/A 182M-02	F 304LN		S30453	0.03	2.00	1.00	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
ASTM A 965/A 965M-02	F 304LN		S30453	0.03	2.00	1.00	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
JIS G 3214:1991	SUS F 304LN			0.03	2.00	1.00	0.040	0.030	18.00-20.00	8.00-11.00		N 0.10-0.16
EN 10222-5:1999	X2CrNiN18-10	1.4311		0.03	2.00	1.00	0.045	0.015	17.00-19.50	8.50-11.50		N 0.12-0.22
ISO 9327-5:1999	X2CrNiN18-10			0.03	2.00	1.00	0.045	0.030	17.00-19.00	8.50-11.50		N 0.12-0.22
EN 10250-4:1999	X2CrNiN18-10	1.4311		0.03	2.00	1.00	0.045	0.030	17.00-19.50	8.50-11.50		N 0.12-0.22

6.3.3A Chemical Composition of Austenitic Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ISO 9327-5:1999	X6CrNi25-21			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-23.00		
ASTM A 182/A 182M-02	F 310		S31000	0.25	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0		
ASTIVI A 102/A 102IVI-UZ	F310H		S31009	0.04-0.10	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0		
ASTM A 473-01	310		S31000	0.25	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0		
ASTM A 965/A 965M-02	F 310		S31000	0.25	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0		
ASTIVI A 903/A 903IVI-UZ	F310H		S31009	0.04-0.10	2.00	1.00	0.045	0.030	24.0-26.0	19.0-22.0		
JIS G 3214:1991	SUS F 310			0.15	2.00	1.00	0.040	0.030	24.00-26.00	19.00-22.00		
EN 10250-4:1999	X5CrNiMo17-12-2	1.4401		0.07	2.00	1.00	0.045	0.030	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10250-4.1999	X3CrNiMo17-13-3	1.4436		0.05	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
EN 10222-5:1999	X5CrNiMo17-12-2	1.4401		0.07	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10222-5.1999	X3CrNiMo17-13-3	1.4436		0.05	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
ISO 9327-5:1999	X5CrNiMo17-12			0.07	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	
150 9327-5.1999	X5CrNiMo17-13			0.07	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.50-3.00	
ASTM A 182/A 182M-02	F 316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 473-01	316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 965/A 965M-02	F 316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 3214:1991	SUS 316			0.08	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 3214:1991	SUS F 316L			0.030	2.00	1.00	0.040	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
ASTM A 182/A 182M-02	F 316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-15.0	2.0-3.0	
ASTM A 473-01	316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-15.0	2.0-3.0	
ASTM A 965/A 965M-02	F 316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-15.0	2.0-3.0	
EN 10222-5:1999	X2CrNiMo17-12-2	1.4404		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10222-5:1999	X2CrNiMo17-12-3	1.4432		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
ISO 9327-5:1999	X2CrNiMo17-12			0.030	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.00-2.50	
150 9327-5.1999	X2CrNiMo17-13			0.030	2.00	1.00	0.045	0.030	16.50-18.50	11.50-14.50	2.50-3.00	
EN 10250-4:1999	X2CrNiMo17-12-2	1.4404		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10250-4.1999	X2CrNiMo18-14-3	1.4435		0.030	2.00	1.00	0.045	0.030	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
EN 10222-5:1999	X2CrNiMo18-14-3	1.4435		0.030	2.00	1.00	0.045	0.015	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
ASTM A 182/A 182M-02	F 316N		S31651	0.08	2.00	1.00	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	N 0.10-0.16
ASTM A 965/A 965M-02	F 316N		S31651	0.08	2.00	1.00	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	N 0.10-0.16
JIS G 3214:1991	SUS F 316N			0.08	2.00	0.75	0.040	0.030	16.00-18.00	11.00-14.00	2.00-3.00	N 0.10-0.16

6.3.3A Chemical Composition of Austenitic Stainless Steel Forgings (Continued)

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unless	Otherwise S	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 182/A 182M-02	F 316LN		S31653	0.030	2.00	1.00	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	N 0.10-0.16
ASTM A 965/A 965M-02	F 316LN		S31653	0.030	2.00	1.00	0.045	0.030	16.0-18.0	11.0-14.0	2.00-3.00	N 0.10-0.16
JIS G 3214:1991	SUS F 316LN			0.030	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	N 0.10-0.16
EN 10222-5:1999	X2CrNiMoN17-11-2	1.4406		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-12.00	2.00-2.50	N 0.12-0.22
LIN 10222-3.1999	X2CrNiMoN17-13-3	1.4429		0.030	2.00	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22
ISO 9327-5:1999	X2CrNiMoN17-12			0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	N 0.12-0.22
130 9327-5.1999	X2CrNiMoN17-13			0.030	2.00	1.00	0.045	0.030	16.50-18.50	11.50-14.50	2.50-3.00	N 0.12-0.22
EN 10250-4:1999	X2CrNiMoN17-11-2	1.4406		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.00-12.00	2.00-2.50	N 0.12-0.22
EN 10250-4.1999	X2CrNiMo17-13-3	1.4429		0.030	2.00	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22
ISO 9327-5:1999	X7CrNiMo17-12			0.04-0.10	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	
ASTM A 182/A 182M-02	F 316H		S31609	0.04-0.10	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
ASTM A 965/A 965M-02	F 316H		S31609	0.04-0.10	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 3214:1991	SUS 316H			0.04-0.10	2.00	1.00	0.040	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
EN 10250-4:1999	X6CrNiMoTi17-12-2	1.4571		0.08	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.00-2.50	Ti 5 x C to 0.70
ISO 9327-5:1999	X6CrNiMoTi17-12			0.08	2.00	1.00	0.045	0.030	16.50-18.50	11.00-14.00	2.00-2.50	Ti 5 x C to 0.80
ASTM A 182/A 182M-02	F 317		S31700	0.08	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
ASTM A 473-01	317		S31700	0.08	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
JIS G 3214:1991	SUS 317			0.08	2.00	1.00	0.040	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
JIS G 3214:1991	SUS F 317L			0.030	2.00	1.00	0.040	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
ASTM A 182/A 182M-02	F 317L		S31703	0.030	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.00-4.00	
EN 10250-4:1999	X6CrNiTi18-10	1.4541		0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
EN 10222-5:1999	X6CrNiTi18-10	1.4541		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
ISO 9327-5:1999	X6CrNiTi18-10			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
ASTM A 182/A 182M-02	F 321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.70
ASTM A 473-01	321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.70
ASTM A 965/A 965M-02	F 321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.70
JIS G 3214:1991	SUS F 321			0.08	2.00	1.00	0.040	0.030	17.00 min	9.00-12.00		Ti 5 x C to 0.60
ISO 9327-5:1999	X7CrNiTi18-10			0.04-0.10	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.80
ASTM A 182/A 182M-02	F 321H		S32109	0.04-0.10	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 4 x C to 0.70
ASTM A 965/A 965M-02	F 321H		S32109	0.04-0.10	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 4 x C to 0.70
JIS G 3214:1991	SUS F 321H			0.04-0.10	2.00	1.00	0.040	0.030	17.0 min	9.00-12.00		Ti 4 x C to 0.60

6.3.3A Chemical Composition of Austenitic Stainless Steel Forgings (Continued)

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10222-5:1999	X6CrNiNb18-10	1.4550		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ISO 9327-5:1999	X6CrNiNb18-10			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ASTM A 182/A 182M-02	F 347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-20.0	9.0-13.0		Cb 10 x C to 1.10
ASTM A 473-01	347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-20.0	9.0-13.0		Cb 10 x C to 1.10
ASTM A 965/A 965M-02	F 347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-20.0	9.0-13.0		Cb 10 x C to 1.10
JIS G 3214:1991	SUS F 347			0.08	2.00	1.00	0.040	0.030	17.00-20.00	9.00-13.00		Nb 10 x C to 1.00
EN 10222-5:1999	X7CrNiNb18-10	1.4912		0.04-0.10	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.20
ISO 9327-5:1999	X7CrNiNb18-10			0.04-0.10	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Nb 10 x C to 1.20
ASTM A 182/A 182M-02	F 347H		S34709	0.04-0.10	2.00	1.00	0.045	0.030	17.0-20.0	9.0-13.0		Cb 8 x C to 1.10
JIS G 3214:1991	SUS F 347H			0.04-0.10	2.00	1.00	0.040	0.030	17.00-20.00	9.00-13.00		Nb 8 x C to 1.00
ISO 9327-5:1999	X2NiCrMoCu25-20-5			0.025	2.00	1.00	0.030	0.020	19.00-21.00	24.00-27.00	4.00-5.00	Cu 1.00-2.00; N 0.15
EN 10250-4:1999	X1NiCrMoCu25-20-5	1.4539		0.020	2.00	0.70	0.030	0.010	19.00-21.00	24.00-26.00	4.00-5.00	Cu 1.20-2.00; N 0.15

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10222-5:1999	X5CrNi18-10	1.4301		ST	≤ 250		200		500-700		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at-196°C
EN 10250-4:1999	X5CrNi18-10	1.4301		SA	≤ 250		190		500-700		35	L: 100 J at RT T: 60 J at RT
ISO 9327-5:1999	X5CrNi18-9			Q	≤ 250		195		500-700		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 304		S30400	ST+Q			205	30	515	75	30	
ASTM A 473-01	304		S30400	ST	≤ 127	≤ 5	205	30	515	75	40	
A31W A 473-01	304		330400	ST	> 127	> 5	205	30	485	70	40	
ASTM A 965/A 965M-02	F 304		S30400	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 304			S	< 130		205		520		43	187 HB max
313 G 3214.1991	3031 304			5	$130 \leq t \leq 200$		205		480		29	187 HB max
EN 10250-4:1999	X2CrNi18-9	1.4307		SA	≤ 250		175		450-680		35	L: 100 J at RT T: 60 J at RT
EN 10250-4.1999	X2CrNi19-11	1.4306		SA	≤ 250		180		460-680		35	L: 100 J at RT T: 60 J at RT
JIS G 3214:1991	SUS F 304L			S	< 130		175		480		29	187 HB max
JIS G 3214.1991	505 F 304L			5	130 ≤ t ≤ 200		175		450		29	187 HB max
ISO 9327-5:1999	X2CrNi18-10			Q	≤ 250		180		480-680		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 304L		S30403	ST+Q			170	25	485	70	30	
ASTM A 473-01	304L		S30403	ST			170	25	450	65	40	
ASTM A 965/A 965M-02	F 304L		S30403	ST+Q			170	25	450	65	30	
EN 10222-5:1999	X2CrNi18-9	1.4307		ST	≤ 250		200		500-700		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
EN 10222-5:1999	X6CrNi18-10	1.4948		ST	≤ 250		195		490-690		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C
ISO 9327-5:1999	X7CrNi18-9			Q	≤ 250		195		490-690		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 304H		S30409	ST+Q			205	30	515	75	30	
ASTM A 965/A 965M-02	F 304H		S30409	ST+Q			205	30	485	70	30	
UC C 2014:1001	CHC E 20411			c	< 130		205		520		43	187 HB max
JIS G 3214:1991	SUS F 304H			S	130 ≤ t ≤ 200		205		480		29	187 HB max
ASTM A 182/A 182M-02	F 304N		S30451	ST+Q			240	35	550	80	30	
ASTM A 965/A 965M-02	F 304N		S30451	ST+Q			240	35	550	80	25	
JIS G 3214:1991	SUS F 304N			S	< 130		240		550		29	217 HB max
JIS G 3214.1991	303 F 304N			0	130 ≤ t ≤ 200		240		550		24	217 HB max

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Stre	ngth, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 182/A 182M-02	F 304LN		S30453	ST+Q			205	30	515	75	30	
ASTM A 965/A 965M-02	F 304LN		S30453	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 304LN			S	< 130		205		520		29	187 HB max
010 0 0214.1001	0001 004LIV			U	$130 \leq t \leq 200$		205		480		29	187 HB max
EN 10222-5:1999	X2CrNiN18-10	1.4311		ST	≤ 250		270		550-750		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at-196°C
ISO 9327-5:1999	X2CrNiN18-10			Q	≤ 250		270		550-750		30 L; 30 T	L: 85 J at RT T: 55 J at RT
EN 10250-4:1999	X2CrNiN18-10	1.4311		SA	≤ 250		270		550-760		30	L: 100 J at RT T: 60 J at RT
ISO 9327-5:1999	X6CrNi25-21			Q	≤ 160		210		500-700		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 310		S31000	ST+Q			205	30	515	75	30	
ASTIVI A 102/A 102IVI-02	F310H		S31009	ST+Q			205	30	515	75	30	
ASTM A 473-01	310		S31000	ST			205	30	515	75	40	
ASTM A 965/A 965M-02	F 310		S31000	ST+Q			205	30	485	70	30	
ASTIVI A 965/A 965IVI-02	F310H		S31009	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 310			S	< 130		205		520		34	187 HB max
313 G 3214.1991	3031 310			3	$130 \le t \le 200$		205		480		29	187 HB max
EN 10250-4:1999	X5CrNiMo17-12-2	1.4401		SA	≤ 250		200		500-700		30	L: 100 J at RT T: 60 J at RT
EN 10250-4.1999	X3CrNiMo17-13-3	1.4436		SA	≤ 250		200		500-700		30	L: 100 J at RT T: 60 J at RT
EN 10222-5:1999	X5CrNiMo17-12-2	1.4401		ST	≤ 250		205		510-710		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at-196°C
ILIN 10222-3.1999	X3CrNiMo17-13-3	1.4436		ST	≤ 250		205		510-710		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at-196°C
ISO 9327-5:1999	X5CrNiMo17-12			Q	≤ 250		205		510-710		30 L; 30 T	L: 85 J at RT T: 55 J at RT
130 3321-3. 1333	X5CrNiMo17-13			Q	≤ 250		205		510-710		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 316		S31600	ST+Q			205	30	515	75	30	
ASTM A 473-01	316		S31600	ST	≤ 250	≤ 5	205	30	515	75	40	
AS 11VI A 4/3-U1	310		331000	ST	> 250	> 5	205	30	485	70	40	
ASTM A 965/A 965M-02	F 316		S31600	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS 316			S	< 130		205		520		43	187 HB max
010 G 0214.1991	303 310			3	130 ≤ t ≤ 200		205		480		29	187 HB max

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 3214:1991	SUS F 316L			S	< 130		175		480		29	187 HB max
313 G 3214.1991	3031 310L			3	$130 \le t \le 200$		175		450		29	187 HB max
ASTM A 182/A 182M-02	F 316L		S31603	ST+Q			170	25	485	70	30	
ASTM A 473-01	316L		S31603	ST			170	25	450	65	40	
ASTM A 965/A 965M-02	F 316L		S31603	ST+Q			170	25	450	65	30	
EN 10222-5:1999	X2CrNiMo17-12-2	1.4404		ST	≤ 250		190		490-690		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
LIN 10222 3.1000	X2CrNiMo17-12-3	1.4432		ST	≤ 250		190		490-690		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
ISO 9327-5:1999	X2CrNiMo17-12			Q	≤ 250		190		490-690		30 L; 30 T	L: 85 J at RT T: 55 J at RT
130 9327-5.1999	X2CrNiMo17-13			Q	≤ 250		190		490-690		30 L; 30 T	L: 85 J at RT T: 55 J at RT
EN 10050 4:1000	X2CrNiMo17-12-2	1.4404		SA	≤ 250		200		500-700		30	L: 100 J at RT T: 60 J at RT
EN 10250-4:1999	X2CrNiMo18-14-3	1.4435		SA	≤ 250		200		500-700		30	L: 100 J at RT T: 60 J at RT
EN 10222-5:1999	X2CrNiMo18-14-3	1.4435		ST	≤ 75		200		520-670		45 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
ASTM A 182/A 182M-02	F 316N		S31651	ST+Q			240	35	550	80	30	
ASTM A 965/A 965M-02	F 316N		S31651	ST+Q			240	35	550	80	25	
110 0 001 1 1001	0110 = 04011			0	< 130		240		550		29	217 HB max
JIS G 3214:1991	SUS F 316N			S	130 ≤ t ≤ 200		240		550		24	217 HB max

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 182/A 182M-02	F 316LN		S31653	ST+Q			205	30	515	75	30	
ASTM A 965/A 965M-02	F 316LN		S31653	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 316LN			S	< 130		205		520		29	187 HB max
313 G 3214.1991	3031 310LN			3	$130 \le t \le 200$		205		480		29	187 HB max
EN 10222-5:1999	X2CrNiMoN17-11-2	1.4406		ST	≤ 160		280		580-780		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
EN 10222-5.1999	X2CrNiMo17-13-3	1.4429		ST	≤ 160		280		580-780		45 L; 35 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
ISO 9327-5:1999	X2CrNiMoN17-12			Q	≤ 160		280		580-780		30 L; 30 T	L: 85 J at RT T: 55 J at RT
130 9327-5.1999	X2CrNiMoN17-13			Q	≤ 160		280		580-780		30 L; 30 T	L: 85 J at RT T: 55 J at RT
EN 10250-4:1999	X2CrNiMoN17-12-2	1.4406		SA	≤ 250		280		580-800		30	L: 100 J at RT T: 60 J at RT
EN 10230-4.1999	X2CrNiMoN17-13-3	1.4429		SA	≤ 400		280		580-800		30	L: 100 J at RT T: 60 J at RT
ISO 9327-5:1999	X7CrNiMo17-12			Q	≤ 250		205		510-710		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 316H		S31609	ST+Q			205	30	515	75	30	
ASTM A 965/A 965M-02	F 316H		S31609	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS 316H			S	< 130		205		520		43	187 HB max
010 G 0214.1991	303 31011			3	$130 \le t \le 200$		205		480		29	187 HB max
EN 10250-4:1999	X6CrNiMoTi17-12-2	1.4571		SA	≤ 450		200		500-700		30	L: 100 J at RT T: 60 J at RT
ISO 9327-5:1999	X6CrNiMoTi17-12			Q	≤ 450		210		510-710		30	
ASTM A 182/A 182M-02	F 317		S31700	ST+Q			205	30	515	75	30	
ASTM A 473-01	317		S31700	ST			205	30	515	75	40	
JIS G 3214:1991	SUS 317			S	< 130		205		520		29	187 HB max
010 G 0214.1331	303317				$130 \le t \le 200$		205		480		29	187 HB max
JIS G 3214:1991	SUS F 317L			S	< 130		175		480		29	187 HB max
010 G 0214.1991	303 F 31/L			s	$130 \le t \le 200$		175		450		29	187 HB max
ASTM A 182/A 182M-02	F 317L		S31703	ST+Q			170	25	485	70	30	

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	- Elongation,	
Designation Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10250-4:1999	X6CrNiTi18-10	1.4541		SA	≤ 450		190		500-700		30	L: 100 J at RT T: 60 J at RT
EN 10222-5:1999	X6CrNiTi18-10	1.4541		ST	≤ 450		200		510-710		40 L; 30 T	L: 100 J at 20°C T: 60 J at 20°C T: 60 J at -196°C
ISO 9327-5:1999	X6CrNiTi18-10			Q	≤ 450		200		510-710		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 321		S32100	ST+Q			205	30	515	75	30	
ASTM A 473-01	321		S32100	ST			205	30	515	75	40	
ASTM A 965/A 965M-02	F 321		S32100	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 321			S	< 130		205		520		43	187 HB max
JIS G 3214.1991	303 F 321			3	130 ≤ t ≤ 200		205		480		29	187 HB max
ISO 9327-5:1999	X7CrNiTi18-10			Q	≤ 450		175		490-690		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 321H		S32109	ST+Q			205	30	515	75	30	
ASTM A 965/A 965M-02	F 321H		S32109	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 321H			S	< 130		205		520		43	187 HB max
313 G 3214.1991	3031 32111			3	130 ≤ t ≤ 200		205		480		29	187 HB max
EN 10222-5:1999	X6CrNiNb18-10	1.4550		ST	≤ 450		205		510-710		40 L; 30 T	L: 100 J at 20°C T: 60 J at 20°C T: 40 J at -196°C
ISO 9327-5:1999	X6CrNiNb18-10			Q	≤ 450		205		510-710		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 347		S34700	ST+Q			205	30	515	75	30	
ASTM A 473-01	347		S34700	ST			205	30	515	75	40	
ASTM A 965/A 965M-02	F 347		S34700	ST+Q			205	30	485	70	30	
JIS G 3214:1991	SUS F 347			S	< 130		205		520		43	187 HB max
313 G 3214.1991	3031 347			3	$130 \le t \le 200$		205		480		29	187 HB max
EN 10222-5:1999	X7CrNiNb18-10	1.4912		ST	≤ 450		205		510-710		40 L; 30 T	L: 100 J at 20°C T: 60 J at 20°C T: 40 J at -196°C
ISO 9327-5:1999	X7CrNiNb18-10			Q	≤ 450		205		510-710		30 L; 30 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 347H		S34709	ST+Q			205	30	515	75	30	
JIS G 3214:1991	SUS F 347H			S	< 130		205		520		43	187 HB max
010 0 02 14. 1331	3031 34/11				130 ≤ t ≤ 200		205		480		29	187 HB max
ISO 9327-5:1999	X2NiCrMoCu25-20-5			Q	≤ 160		220		520-720		30	L: 85 J at RT T: 55 J at RT
EN 10250-4:1999	X1NiCrMoCu20-20-5	1.4539		SA	≤ 250		230		530-730		30	L: 100 J at RT T: 60 J at RT

6.3.4A Chemical Composition of Precipitation-Hardening Stainless Steel Forgings

Standard	Grade, Class,	Steel	UNS				W	/eight, %, r	nax, Unless	Otherwise	Specified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
JIS G 3214:1991	SUS F 630			0.07	1.00	1.00	0.040	0.030	15.00-17.50	3.00-5.00		Cu 3.00-5.00; Nb 0.15-0.45
ASTM A 705/A 705M-95(2000)	630		S17400	0.07	1.00	1.00	0.040	0.030	15.00-17.50	3.00-5.00		Cu 3.00-5.00; Cb+Ta 0.15-0.45
EN 10250-4:1999	X5CrNiCuNb16-4	1.4542		0.07	1.50	0.70	0.040	0.030	15.00-17.00	3.00-5.00	0.60	Cu 3.00-5.00; Nb 5 x C to 0.45

Chapter 6

6.3.4B Mechanical Properties of Precipitation-Hardening Stainless Steel Forgings

Standard	Grade, Class,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	
Designation	Type, Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
				H1075	≤ 200		860		1000		12	311 min HBS or HBW 27 J at 23°C
JIS G 3214:1991	SUS F 630			H1100	≤ 200		795		970		13	302 min HBS or HBW 34 J at 23°C
				H1150	≤ 200		725	930	15	277 min HBS or HBW 41 J at 23°C		
				ST								38 HRC 363 HB
				H900	≤ 200	≤8	1170	170	1310	190	10	40 HRC 388 HB
				H925	≤ 200	≤8	1070	155	1170	170	10	38 HRC 375 HB 6.8 J at 23°C
				H1025	≤ 200	≤8	1000	145	1070	155	12	35 HRC 331 HB 20 J at 23°C
ASTM A 705/A 705M-95(2000)	630		S17400	H1075	≤ 200	≤8	860	125	1000	145	13	32 HRC 311 HB 27 J at 23°C
				H1100	≤ 200	≤8	795	115	965	140	14	31 HRC 302 HB 34 J at 23°C
				H1150	≤ 200	≤8	725	105	930	135	16	28 HRC 277 HB 41 J at 23°C
				H1150M	≤ 200	≤8	520	75	795	115	18	24 HRC 255 HB 75 J at 23°C
				Α					1200 max			360 HB max
N 10250-4:1999	VEO ALIO ALIA A	4 4540		P 930	≤ 250		720		930		15 L; 12 T	L: 40 J at RT T: 30 J at RT
	X5CrNiCuNb16-4	1.4542		P 1070	≤ 250		1000		1070		12 L; 10 T	L: 20 J at RT T: 15 J at RT
				P 1300	≤ 250		1150		1300		8 L; 6 T	

6.3.5A Chemical Composition of Duplex (Ferritic-Austenitic) Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS				N	/eight, %,	max, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10250-4:1999	X3CrNiMoN27-5-2	1.4460		0.05	2.00	1.00	0.035	0.030	25.00-28.00	4.50-6.50	1.30-2.00	N 0.05-0.20
ASTM A 182/A 182M-02	F 50		S31200	0.030	2.00	1.00	0.045	0.030	24.0-26.0	5.5-6.5	1.20-2.00	N 0.14-0.20
ISO 9327-5:1999	X2CrNiMoN22-5-3			0.030	2.00	1.00	0.035	0.020	21.00-23.00	4.50-6.50	2.50-3.50	N 0.08-0.20
ASTM A 182/A 182M-02	F 51		S31803	0.030	2.00	1.00	0.030	0.020	21.0-23.0	4.5-6.5	2.5-3.5	N 0.08-0.20
EN 10250-4:1999	X2CrNiMoN22-5-3	1.4462		0.030	2.00	1.00	0.035	0.015	21.00-23.00	4.50-6.50	2.50-3.50	N 0.10-0.22
ASTM A 182/A 182M-02	F 60		S32205	0.030	2.00	1.00	0.030	0.020	22.0-23.0	4.5-6.5	3.0-3.5	N 0.14-0.20
EN 10222-5:1999	X2CrNiMoN22-5-3	1.4462		0.030	2.00	1.00	0.035	0.015	21.00-23.00	4.50-6.50	2.50-3.50	N 0.10-0.22
EN 10250-4:1999	X2CrNiMoN25-7-4	1.4410		0.030	2.00	1.00	0.035	0.015	24.0-26.0	6.0-8.0	3.00-4.50	N 0.20-0.35
ASTM A 182/A 182M-02	F 53		S32750	0.030	1.20	0.80	0.035	0.020	24.0-26.0	6.0-8.0	3.0-5.0	Cu 0.50; N 0.24-0.32
EN 10222-5:1999	X2CrNiMoN25-7-4	1.4410		0.030	2.00	1.00	0.035	0.015	24.0-26.0	6.0-8.0	3.00-4.50	N 0.20-0.35
EN 10250-4:1999	X2CrNiMoCuWN27-7-4	1.4501		0.030	1.00	1.00	0.035	0.015	24.00-26.00	6.00-8.00	3.00-4.00	Cu 0.50-1.00; N 0.20-0.30; W 0.50-1.00
ASTM A 182/A 182M-02	F 55		S32760	0.030	1.00	1.00	0.030	0.010	24.0-26.0	6.0-8.0	3.0-4.0	Cu 0.50-1.00; N 0.20-0.30; W 0.50-1.00
ASTM A 473-01			S32760	0.030	1.00	1.00	0.030	0.010	24.0-26.0	6.0-8.0	3.0-4.0	Cu 0.50-1.00; N 0.20-0.30; W 0.50-1.00
EN 10250-4:1999	X2CrNiMoCuN25-6-3	1.4507		0.030	2.00	0.70	0.035	0.015	24.00-26.00	5.50-7.50	2.70-4.00	Cu 1.00-2.50; N 0.15-0.30
ASTM A 473-01			S32550	0.040	1.50	1.00	0.040	0.030	24.0-27.0	4.5-6.5	2.9-3.9	Cu 1.50-2.50; N 0.10-0.25
ASTM A 182/A 182M-02	F 59		S32520	0.030	1.50	0.80	0.035	0.020	24.0-26.0	5.5-8.0	3.0-5.0	Cu 0.50-3.00; N 0.20-0.35
ISO 9327-5:1999	X2CrNiN23-4			0.030	2.50	1.00	0.035	0.020	22.00-24.00	3.50-5.00	0.60	Cu 0.60; N 0.05-0.20
EN 10250-4:1999	X2CrNiN23-4	1.4362		0.030	2.00	1.00	0.035	0.015	22.00-24.00	3.50-5.50	0.10-0.60	Cu 0.10-0.60; N 0.05-0.20

6.3.5B Mechanical Properties of Duplex (Ferritic-Austenitic) Stainless Steel Forgings

Standard	Grade, Class, Type,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
EN 10250-4:1999	X3CrNiMoN27-5-2	1.4460		ST	≤ 160		460		620-880		20 L; 15 T	L: 85 J at RT T: 50 J at RT
ASTM A 182/A 182M-02	F 50		S31200	ST+Q			450	65	690-900	100-130	25	
ISO 9327-5:1999	X2CrNiMoN22-5-3			Q	≤ 250		450		600-860		25 L; 20 T	L: 85 J at RT T: 55 J at RT
ASTM A 182/A 182M-02	F 51		S31803	ST+Q			450	65	620	90	25	
EN 10250-4:1999	X2CrNiMoN22-5-3	1.4462		ST	≤ 350		450		650-880		25 L; 20 T	L: 100 J at RT T: 60 J at RT
ASTM A 182/A 182M-02	F 60		S32205	ST+Q			485	70	655	95	25	
EN 10222-5:1999	X2CrNiMoN22-5-3	1.4462		ST	≤ 350		450		680-880		30 L; 25 T	L: 200 J at 20°C T: 100 J at 20°C
EN 10250-4:1999	X2CrNiMoN25-7-4	1.4410		ST	≤ 160		530		730-930		25 L; 20 T	L: 100 J at RT T: 60 J at RT
ASTM A 182/A 182M-02	F 53		S32750	ST+Q			550	80	800	116	15	
EN 10222-5:1999	X2CrNiMoN25-7-4	1.4410		ST	≤ 160		500		800-1000		30 L; 25 T	L: 200 J at 20°C T: 100 J at 20°C
EN 10250-4:1999	X2CrNiMoCuWN27-7-4	1.4501		ST	≤ 160		530		730-930		25 L; 20 T	L: 100 J at RT T: 60 J at RT
ASTM A 182/A 182M-02	F 55		S32760	ST+Q			550	80	750-895	109-130	25	
ASTM A 473-01			S32760	ST			550	80	750	109	25	290 HB
EN 10250-4:1999	X2CrNiMoCuN25-6-3	1.4507		ST	≤ 160		500		700-900		25 L; 20 T	L: 100 J at RT T: 60 J at RT
ASTM A 473-01			S32550	ST			550	80	750	109	25	290 HB
ASTM A 182/A 182M-02	F 59		S32520	ST+Q			550	80	770	112	25	
ISO 9327-5:1999	X2CrNiN23-4			Q	≤ 160		400		600-820		25 L; 20 T	L: 85 J at RT T: 55 J at RT
EN 10250-4:1999	X2CrNiN23-4	1.4362		ST	≤ 160		400		600-830		25 L; 20 T	L: 100 J at RT T: 60 J at RT

6.4 Non-Comparable Carbon Steel Forgings for General Use

EN 10250-2:1999 - Open Die Steel Forgings for General Engineering Purposes - Part 2: Non-Alloy Quality and Special Steels												
Steel Name	S355J2G3	C60	C60E									
Steel Number	1.0570	1.0601	1.1221									

6.5 Non-Comparable Carbon Steel Forgings for Piping, Pressure Vessel and Components

ASTM A 266/A 266M-03a - Carbon Steel Forgings for Pressure Vessel Components												
Grade, Class, Type	3											
UNS Number	K05001											
ISO 9327-4:1999 - Steel Forgings and Rolled or Forged Bars for Pressure Purposes. Technical Delivery Conditions. Part 4: Weldable Fine Grain Steels with High Proof Strength												
Steel Type	P 46	PH 46	PL 46	PLH 46								

6.6 Non-Comparable Alloy Steel Forgings for General Use

ASTM A 668/A 668	M-03 - Steel Fo	rgings, Carbon	and Alloy, for	General Indus	trial Use							
Grade, Class, Type	G (GH)	H (HH)	J (JH)	K (KH)	L (LH)	M (MH)	N (NH)					
UNS Number												
JIS G 3221:1988 - (Chromium Mol	ybdenum Steel	Forgings for G	eneral Use								
	SFCM 590 S	SFCM 640 S	SFCM 830 S	SFCM 880 S	SFCM 930 S	SFCM 980 S						
Type Symbol	SFCM 590 R	SFCM 640 R	SFCM 690 R	SFCM 740 R	SFCM 780 R	SFCM 830 R	SFCM 880 R	SFCM 930 R	SFCM 980 R			
	SFCM 590 D	SFCM 640 D	SFCM 690 D	SFCM 740 D	SFCM 780 D	SFCM 830 D	SFCM 880 D	SFCM 930 D	SFCM 980 D			
EN 10250-2:1999 -	Open Die Steel	Forgings for G	eneral Engine	ering Purposes	s - Part 2: Non-A	Alloy Quality ar	nd Special Stee	els				
Steel Name	28Mn6	20Mn5										
Steel Number	1.1170	1.1133										
EN 10250-3:1999 -	Open Die Steel	Forgings for G	eneral Engine	ering Purposes	s - Part 3: Alloy	Special Steels						
Steel Name	38Cr2	46Cr2	34Cr4	37Cr4	41Cr4	36CrNiMo4	34CrNiMo6	30CrNiMo8	36NiCrMo16	51CrV4	33NiCrMoV14-5	40CrMoV13-9
Steel Number	1.7003	1.7006	1.7033	1.7034	1.7035	1.6511	1.6582	1.6580	1.6773	1.8159	1.6956	1.8523
Steel Name	18CrMo4	20MnMoNi4-5	30CrMoV9	32CrMo12	28NiCrMoV8-5							
Steel Number	1.7243	1.6311	1.7707	1.7361	1.6932							

6.7 Non-Comparable Alloy Steel Forgings for Piping, Pressure Vessel and Components

Grade, Class, Type	F 91	F 92	F 911	F 11, Class 1	F 12, Class 1	F 3VCb	F 23	F 24	FR			
JNS Number	K 90901			K11597	K11562	K31835	K41650		K22035			
ASTM A 336/A 336	M-03a - Alloy S	teel Forgings fo	or Pressure an	d High-Temper	ature Parts	'		'	'	'		
Grade, Class, Type	F11, Class 1	F6	F91	F911	F3VCb							
JNS Number		S41000										
ASTM A 350/A 350	M-02b - Carbor	and Low-Alloy	Steel Forging	s, Requiring N	otch Toughnes	s Testing for Pi	ping Compone	ents				'
Grade, Class, Type	LF5	LF6	LF9	LF787								
JNS Number	K13050	K12202	K22036									
ASTM A 508/A 508	M-03a - Quencl	ned and Tempe	red Vacuum-T	reated Carbon	and Alloy Steel	Forgings for P	ressure Vesse	s	-			
Grade, Class, Type	4N, Class 1	4N, Class 2	5, Class 1	5, Class 2	3VCb							
JNS Number												
ASTM A 541/A 541	M-95 (1999) - Q	uenched and T	empered Carb	on and Alloy S	teel Forgings fo	or Pressure Ves	sel Componer	its				
Grade, Class, Type	1C	11, Class 4	22, Class 4	22, Class 5	4N, Class 1	4N, Class 2	5, Class 1	5, Class 2	3VCb			
JNS Number												
N 10222-2:1999 -	Steel Forgings	for Pressure P	urposes - Part	2: Ferritic and	Martensitic Ste	els with Specif	ied Elevated Te	emperature Pro	perties			
Steel Name	15MnMoV4-5	18MnMoNi5-5	14MoV6-3	15MnCrN	/loNiV5-3							
Steel Number	1.5402	1.6308	1.7715	1.6	920							
SO 9327-2:1999 - S	Steel Forgings	and Rolled or F	orged Bars fo	r Pressure Pur	oses. Part 2: N	lon-Alloy and A	lloy (Mo, Cr ar	d CrMo) Steels	with Specified	l Elevated Tem	perature Prope	erties
Steel Type	20MnMoNi5											

6.8 Non-Comparable Stainless Steel Forgings

Grade, Class, Type	F 122	F XM-270	Cb F 429	F 309H F	310MoLN	F 348	F 348H	F XM-11	F XM-19	F 10	F 20	F 44
UNS Number	K92930	S44627	7 S42900	S30909	S31050	S34800	S34809	S21904	S20910	S3310	00 N08020	S31254
Grade, Class, Type	F 45	F 46	F 47	F 48	F 49	F 52	F 54	F 56	F 57	F 58	F 61	F 62
UNS Number	S30815	S30600	S31725	S31726	S34565	S32950	S39274	S33228	S39277	S3126	66 S32550	N08367
EN 10222-5:1999 - S	Steel Forgings	for Pressu	ıre Purposes - Par	t 5: Martensitic, Au	stenitic and	Austenitic-Fe	rritic Stainless S	Steels				
Steel Name	X6CrNiTiB1	8-10 X3	3CrNiMoN17-13-3	X2CrNiCu19-10 X		Mo18-12-3						
Steel Number	1.4941		1.4910	1.4650	1.	4449						
EN 10250-4:1999 - (Open Die Stee	l Forgings f	for General Engine	eering Purposes - I	art 4: Stainl	ess Steels			•			
Steel Name	X6CrNiNb1	8-10 X1I	NiCrMoCu31-27-4	X1CrNiMoCuN20-1	3-7 X1NiMo	CuN25-20-7	X6CrAl13	X20Cr13	X30C	r13	X17CrNi16-2	X4CrNiMo16-5
Steel Number	1.4550		1.4563	1.4547	4	4529	1.4002	1.4021	1.40	00	1.4057	1.4418

Chapter

7

STEEL CASTINGS

316 Steel Castings – Heat Treatment Terms Chapter 7

AFNOR Standards

AFNOR NF A 32-053:1992	Cast Steels for Low Temperatures Purposes
AFNOR NF A 32-054:1994	Cast Steels for General Purpose in Mechanical Engineering
AFNOR NF A 32-058:1984	Cast Steels and White Cast Iron Resistant to Abrasion

ASTM Standards

ASTM A 27/A 27M-03	Steel Castings, Carbon, for General Application
ASTM A 128/A 128M-93 (2003)	Steel Castings, Austenitic Manganese
ASTM A 148/A 148 M-03	Steel Castings, High Strength, for Structural Purposes
ASTM A 216/A 216M-93 (2003)	Steel Castings, Carbon, Suitable for Fusion Welding, for High-Temperature Service
ASTM A 217/A 217M-02	Steel Castings, Martensitic Stainless and Alloy, for Pressure- Containing Parts, Suitable for High- Temperature Service
ASTM A 297/A 297M-97 (2003)	Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat Resistant, for General Application
ASTM A 351/A 351M-03	Castings, Austenitic, Austenitic-Ferritic (Duplex), for Pressure-Containing Parts
ASTM A 352/A 352M-03	Steel Castings, Ferritic and Martensitic, for Pressure-Containing Parts, Suitable for Low-Temperature Service
ASTM A 389/A 389M-03	Steel Castings, Alloy, Specially Heat-Treated, for Pressure-Containing Parts, Suitable for High-Temperature Service
ASTM A 447/A 447M-93 (2003)	Steel Castings, Chromium-Nickel-Iron Alloy (25-12 Class), for High-Temperature Service
ASTM A 487/A 487M-93 (2003)	Steel Castings Suitable for Pressure Service
ASTM A 608-02	Centrifugally Cast Iron-Chromium-Nickel High-Alloy Tubing for Pressure Application at High Temperatures
ASTM A 743/A 743M-03	Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion Resistant, for General Application
ASTM A 744/A 744M-00	Castings, Iron-Chromium-Nickel, Corrosion Resistant, for Severe Service
ASTM A 757/A 757M-00	Steel Castings, Ferritic and Martensitic, for Pressure-Containing and Other Applications, for Low- Temperature Service
ASTM A 958-00	Steel Castings, Carbon, and Alloy, with Tensile Requirements, Chemical Requirements Similar to Standard Wrought Grades

BSI Standards

BSI BS 3100:1991 AMD. 1:1992	Steel Castings for General Engineering Purposes

DIN Standards

DIN 1681:1985	Cast Steels for General Engineering Purposes
DIN 17205:1992	Quenched and Tempered Steel Castings for General Applications

CEN Standards

EN 10213-2:1995	Steel Castings for Pressure Purposes Part 2: Steel Grades for Use at Room Temperature and at Elevated Temperature
EN 10213-3:1995	Steel Castings for Pressure Purposes Part 3: Steel Grades for Use at Low Temperatures
EN 10213-4:1995	Steel Castings for Pressure Purposes Part 4: Austenitic and Austenitic-Ferritic Steel Grades
EN 10283:1998	Corrosion Resistant Steel Castings
EN 10295:2002	Heat Resistant Steel Castings

ISO 11972:1998	Corrosion-Resistant Cast Steels for General Applications
ISO 11973:1999	Heat-Resistant Cast Steels and Alloys for General Applications
ISO 13521:1999	Austenitic Manganese Steel Castings
ISO 3755:1991	Cast Carbon Steels for General Engineering Purposes
ISO 4991:1994	Steel Castings for Pressure Purposes

JIS Standards

JIS G 5101:1991	Carbon Steel Castings
JIS G 5102:1991	Steel Castings for Welded Structure
JIS G 5111:1991	High Tensile Strength Carbon Steel Castings and Low Alloy Steel Castings for Structural Purposes
JIS G 5121:2003	Stainless Steel Castings
JIS G 5122:2003	Heat Resisting Steel Castings
JIS G 5131:1991	High Manganese Steel Castings
JIS G 5151:1991	Steel Castings for High Temperature and High Pressure Service
JIS G 5152:1991	Steel Castings for Low Temperature and High Pressure Service

Heat Treatment Terms Applicable to this Chapter

Standard	Heat Treatment Terms
AFNOR NF A 32-053:1992	QT: quenched and tempered; Q (HY): hyperquenched
AFNOR NF A 32-054:1994	N: normalized; QT quenched and tempered; Q: quenched
AFNOR NF A 32-058:1984	Not specified
ASTM A 27/A 27M-03	AS: as cast; A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
ASTM A 128/A 128M-93 (2003)	See standard
ASTM A 148/A 148 M-03	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
ASTM A 216/A 216M-93 (2003)	A: annealed; N: normalized; NT: normalized and tempered
ASTM A 217/A 217M-02	NT: normalized and tempered
ASTM A 297/A 297M-97 (2003)	AS: as cast
ASTM A 351/A 351M-03	AS: as cast; S: solution treat and rapid cool
ASTM A 352/A 352M-03	NT: normalized and tempered; QT: guenched and tempered
ASTM A 389/A 389M-03	NT: normalized and tempered
ASTM A 447/A 447M-93 (2003)	AS: as cast
ASTM A 487/A 487M-93 (2003)	NT: normalized and tempered; QT: quenched and tempered
ASTM A 608-02	AS: as cast
ASTM A 743/A 743M-03	A: annealed; N: normalized; S: solution treat and rapid cool
ASTM A 744/A 744M-00	N: normalized; S: solution treat and rapid cool
ASTM A 757/A 757M-00	NT: normalized and tempered; QT: quenched and tempered
ASTM A 958-00	N: normalized; NT: normalized and tempered; QT: quenched and tempered
BSI BS 3100:1991 AMD. 1:1992	A: annealed; N: normalized; OQ: oil quenched; WQ: water quenched; AH: air hardened; T: tempered; ST: solution treated
DIN 1681:1985	
DIN 17205:1992	NT: air hardened and tempered
EN 10213-2:1995	N: normalized; Q: quenched; T: tempered
EN 10213-3:1995	N: normalized; Q: quenched; T: tempered
EN 10213-4:1995	AT + QW: solution annealed + water quenched
EN 10283:1998	Q: quenched; T: tempered; AT: solution annealed
EN 10295:2002	A: annealed
ISO 3755:1991	
100 4004 4004	A: annealed; N: normalized; Q: quenched; T: tempered; N _{ac} : heated, accelerated air cooling;
ISO 4991:1994	S: solution treated; (): brackets indicate that the treatment is only applied in special cases
ISO 11972:1998	AT: austenitize and temper; ST/Q: solution treat and quench
ISO 11973:1999	AS: as cast; A: annealed
ISO 13521:1999	ST + WQ: solution treated + water quenched
JIS G 5101:1991	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
JIS G 5102:1991	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
JIS G 5111:1991	NT: normalized and tempered; QT: quenched and tempered
JIS G 5121:2003	T: quenched and tempered; T1 or T2: tempered at specified temperature;
	S: solution heat treated and rapid cooling; HXXX: solution treated + age hardened.
JIS G 5122:2003	AS: as cast; A: annealed
JIS G 5131:1991	WT: water toughening
JIS G 5151:1991	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered
JIS G 5152:1991	A: annealed; N: normalized; NT: normalized and tempered; QT: quenched and tempered

Impact Testing Notes Applicable to this Chapter

see standard for impact data: impact testing requirements are listed in the standard for multiple test temperatures.

7.1.1A Mechanical Properties of Cast Carbon Steel for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Florgation	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, % 23 25 25 25 25 21 21 21 22 24 22 24 24 24 24 29 20 20 20 20 20 20 20 20 20 20 20 20 20	Other
JIS G 5101:1991	SC 360			A, N, NT, or QT			175		360		23	
DIN 1681:1985	GS-38	1.0420					200		380		25	
AFNOR NF A 32-054:1994	GE230			N	28 ≤ t < 50		230		400		25	
ALINOH NI A 32-034.1994	GLZ30			N	50 ≤ t <100		210		400		23	
ISO 2755:1001	200-400						200		400-550		25	
ISO 3755:1991 JIS G 5101:1991	200-400W						200		400-550		25	
JIS G 5101:1991	SC 410			A, N, NT, or QT			205		410		21	
JIS G 5102:1991	SCW 410			A, N, NT, or QT			235		410		21	27 J at 0°C
ASTM A 27/A 27M-03	U-60-30		J02500	AC			205	30	415	60	22	
ASTIVI A 27/A 27/VI-03	60-30		J03000	A, N, NT, or QT			205	30	415	60	24	
BS 3100:1991 AMD.1:1992	A1			A, N, NT, OQT or WQT			230		430		22	27 J at 20°C
AFNOR NF A 32-054:1994	G16Mn5			N	28 ≤ t < 50		250		430		24	
AFNOR NF A 32-054: 1994	GTOWITS			IN	50 ≤ t <100		230		430		24	
ASTM A 27/A 27M-03	65-35		J03001	A, N, NT, or QT			240	35	450	65	24	
	SC 1020, Class 65/35											
ASTM A 958-00	SC 1025, Class 65/35			N			240	35	450	65	24	
	SC 1030, Class 65/35											
JIS G 5101:1991	SC 450			A, N, NT, or QT			225		450		19	
JIS G 5102:1991	SCW 450			A, N, NT, or QT			255		450		20	27 J at 0°C
DIN 1681:1985	GS-45	1.0446					230		450		22	
ISO 3755:1991	230-450 230-450W						230		450-600		22	

7.1.1A Mechanical Properties of Cast Carbon Steel for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	e. Class. Type. Steel		Steel	Steel	UNS	Product	Thickn	ness	Yield Stre	ngth, min	Tensile St	rength, min	Flongation	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, % 20 18 17 20 18 22 22 22 22 22 24 18 18 18 18 18 11 14 17 16	Other			
AFNOR NF A 32-054:1994	GE280			N .	28 ≤ t < 50		280		480		-	30 J at RT			
71110111111 71 02 004.1004					50 ≤ t <100		260		480		18	25 J at RT			
JIS G 5101:1991	SC 480			A, N, NT, or QT			245		480		17				
JIS G 5102:1991	SCW 480			A, N, NT, or QT			275		480		20	27 J at 0°C			
ISO 3755:1991	270-480 270-480W						270		480-630		18				
ASTM A 27/A 27M-03	70-36		J03501	A, N, NT, or QT			250	36	485	70	22				
ASTIVI A 27/A 27/VI-03	70-40		J02501	A, N, NT, or QT			275	40	485	70	22				
ASTM A 958-00	SC 1020, Class 70/36 SC 1025, Class 70/36			N			250	36	485	70	18 17 20 18 22 22 22 22 22 24 18 18 18 18 11 14				
A3 1 W A 930-00	SC 1030, Class 70/36 SC 1040, Class 70/36			NT			250	30	465	70					
BS 3100:1991 AMD.1:1992	A2			A, N, NT, OQT or WQT			260		490		18	20 J at 20°C			
					28 ≤ t < 50		300		500		22	40 J at RT			
				N	50 ≤ t <100		280		500		22	30 J at RT			
				IN	100 ≤ t < 150		260		480		20	25 J at RT			
AFNOR NF A 32-054:1994	G20Mn6				150 ≤ t < 250		240		450						
					28 ≤ t < 50		360		500		24	60 J at RT			
				QT	50 ≤ t <100		300		500		24	40 J at RT			
					100 ≤ t < 150		280		500		22	30 J at RT			
AFNOR NF A 32-053:1992	20 M5-M			QT	≤ 30		300		500		24	27 J at -30°C			
DIN 1681:1985	GS-52	1.0552					260		520		18				
DIN 17205:1992	GS-30 Mn 5	1.1165		QT	≤ 400		260		520-670		18				
JIS G 5111:1991	SCC 3A			NT			265		520		13	143 HB			
BS 3100:1991 AMD.1:1992	А3			A, N, NT, OQT or WQT			295		540		14	18 J at 20°C			
JIS G 5111:1991	SCMn 1A			NT			275		540		17	143 HB			
BS 3100:1991 AMD.1:1992	A4			N, NT, OQT or WQT			320		540-690		16	30 J at 20°C			

7.1.1A Mechanical Properties of Cast Carbon Steel for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thickr	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 148/A 148M-03	80-40			A, N, NT, or QT			275	40	550	80	18	
ASTIVI A 146/A 146IVI-U3	80-50			A, N, NT, or QT			345	50	550	80	22	
	SC 1030, Class 80/40			QT								
	SC 1040, Class 80/40			NT			275	40	550	80	18	
ACTM A 050 00	SC 1045, Class 80/40			NT								
ASTM A 958-00	SC 1030, Class 80/50			QT								
	SC 1040, Class 80/50			NT			345	50	550	80	22	
	SC 1045, Class 80/50			NT	1							
JIS G 5102:1991	SCW 550			A, N, NT, or QT			355		550		18	27 J at 0°C
ISO 3755:1991	340-550 340-550W						340		550-700		15	
	05000				28 ≤ t < 50		320		560		16	25 J at RT
	GE320			N	50 ≤ t <100		300		560		14	22 J at RT
					28 ≤ t < 50		350		580		16	27 J at RT
AFNOR NF A 32-054:1994					50 ≤ t <100		300		550		16	24 J at RT
	G30Mn6			N	100 ≤ t < 150		280		550		14	24 J at RT
					150 ≤ t < 250		250		520		14	20 J at RT
	SCSiMn 2A			NT			295		590		13	163 HB
JIS G 5111:1991	SCMn 1B			QT			390		590		17	170 HB
0.0 0.0	SCMn 2A			NT			345		590		16	163 HB
DIN 1681:1985	GS-60	1.0558					300		600		15	
DIIV 1001.1303	GO 00	1.0000			28 ≤ t < 50		450		600		16	30 J at RT
					50 ≤ t < 100		450		600		16	30 J at RT
AFNOR NF A 32-054:1994	G30Mn6			QT2 (TR2)	100 ≤ t < 150		400		550		14	35 J at RT
					150 ≤ t < 250		250		520		14	35 J at RT
	SCC 5A			NT	150 ≤ t < 250		295		620		9	163 HB
JIS G 5111:1991	SCC 3B			QT			370		620		13	183 HB
BS 3100:1991 AMD.1:1992	A5			N, NT, OQT or WQT			370		620-770		13	25 J at 20°C
ASTM A 148/A 148M-03	90-60			A, N, NT, or QT			415	60	620	90	20	
	SC 1040 Class 90/60			NT								
ASTM A 958-00	SC 1045 Class 90/60			NT			415	60	620	90	18	
JIS G 5102:1991	SCW 620			A, N, NT, or QT			430		620		17	27 J at 0°C
	SCMn 3A			NT			370		640		13	170 HB
JIS G 5111:1991	SCMn 2B			QT			440		640		16	183 HB
	SCSiMn 2B			QT			440		640		17	183 HB

7.1.1A Mechanical Properties of Cast Carbon Steel for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
AFNOR NF A 32-054:1994	GE370			N	28 ≤ t < 50		370		650		12	20 J at RT
AI NON NI A 32-034.1994	GL370			IN .	50 ≤ t <100		320		650		10	18 J at RT
	SCMn 5A			NT			390		690		9	183 HB
JIS G 5111:1991	SCC 5B			QT			440		690		9	201 HB
	SCMn 3B			QT			490		690		13	197 HB
BS 3100:1991 AMD.1:1992	A6			OQT or WQT			495		690-850		13	25 J at 20°C
AFNOR NF A 32-054:1994	G30Mn6			QT1 (TR1)	28 ≤ t < 50		550		700		10	30 J at RT
AI NON NI A 32-034.1994	GOOMITO			QII (INI)	50 ≤ t <100		550		700		10	30 J at RT
ASTM A 148/A 148M-03	105-85		J31575	A, N, NT, or QT			585	85	725	105	17	
ASTM A 958-00	SC 1045 Class 105/85			NT			585	85	725	105	17	
JIS G 5111:1991	SCMn 5B			QT			540		740		9	212 HB

7.1.1B Chemical Composition of Cast Carbon Steel for General and Structural Applications

Standard	Grade, Class, Type,	Steel	UNS				٧	Veight, %, ı	max, Unles	s Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5101:1991	SC 360			0.20			0.040	0.040				
DIN 1681:1985	GS-38	1.0420										
AFNOR NF A 32-054:1994	GE 230			0.20	1.20	0.60	0.035	0.030				
ISO 3755:1991	200-400						0.035	0.035				
150 3755: 1991	200-400W			0.25	1.00	0.60	0.035	0.035	0.35	0.40	0.15	Cu 0.40; V 0.05; Ni+Cr+Mo+V 1.00
JIS G 5101:1991	SC 410			0.30			0.040	0.040				
JIS G 5102:1991	SCW 410			0.22	1.50	0.80	0.040	0.040				
ASTM A 27/A 27M-03	U-60-30		J02500	0.25	0.75	0.80	0.05	0.06				
ASTIVI A 27/A 27W-03	60-30		J03000	0.30	0.60	0.80	0.05	0.06				
BS 3100:1991 AMD.1:1992	A1			0.25	0.90	0.60	0.050	0.050	0.30	0.40	0.15	Cu 0.30; Cu+Ni+Cr+Mo 0.80
AFNOR NF A 32-054:1994	G16Mn5			0.13-0.20	1.60	0.60	0.030	0.025				
ASTM A 27/A 27M-03	65-35		J03001	0.30	0.70	0.80	0.05	0.06				
	SC 1020 Class 65/35			0.18-0.23	0.40-0.80	0.30-0.60	0.040	0.040				
ASTM A 958-00	SC 1025 Class 65/35			0.22-0.28	0.40-0.80	0.30-0.60	0.040	0.040				
	SC 1030 Class 65/35			0.28-0.34	0.50-0.90	0.30-0.60	0.040	0.040				
JIS G 5101:1991	SC 450			0.35			0.040	0.040				
JIS G 5102:1991	SCW 450			0.22	1.50	0.80	0.040	0.040				
DIN 1681:1985	GS-45	1.0446										
ISO 3755:1991	230-450						0.035	0.035				
150 3755: 1991	230-450W			0.25	1.20	0.60	0.035	0.035	0.35	0.40	0.15	Cu 0.40; V 0.05; Ni+Cr+Mo+V 1.00
AFNOR NF A 32-054:1994	GE280			0.25	1.20	0.60	0.035	0.030				
JIS G 5101:1991	SC 480			0.40			0.040	0.040				
JIS G 5102:1991	SCW 480			0.22	1.50	0.80	0.040	0.040	0.50	0.50		
ISO 3755:1991	270-480						0.035	0.035				
130 3755.1991	270-480W			0.25	1.20	0.60	0.035	0.035	0.35	0.40	0.15	Cu 0.40; V 0.05; Ni+Cr+Mo+V 1.00
ASTM A 27/A 27M-03	70-36		J03501	0.35	0.70	0.80	0.05	0.06				
A3 1 W A 2//A 2/ W-U3	70-40		J02501	0.25	1.20	0.80	0.05	0.06				
	SC 1020, Class 70/36			0.18-0.23	0.40-0.80	0.30-0.60	0.040	0.040				
ASTM A 958-00	SC 1025, Class 70/36			0.22-0.28	0.40-0.80	0.30-0.60	0.040	0.040				
A3 FIVE A 936-00	SC 1030, Class 70/36			0.28-0.34	0.50-0.90	0.30-0.60	0.040	0.040				
	SC 1040, Class 70/36			0.37-0.44	0.50-0.90	0.30-0.60	0.040	0.040				
BS 3100:1991 AMD.1:1992	A2			0.35	1.00	0.60	0.050	0.050				

7.1.1B Chemical Composition of Cast Carbon Steel for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %, r	max, Unles	s Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
AFNOR NF A 32-054:1994	G20Mn6			0.17-0.23	1.80	0.60	0.030	0.025				
AFNOR NF A 32-053:1992	20 M5-M			0.17-0.23	1.10-1.50	0.60	0.025	0.020				
DIN 1681:1985	GS-52	1.0552										
DIN 17205:1992	GS-30 Mn 5	1.1165		0.27-0.34	1.20-1.50	0.60	0.020	0.015				
JIS G 5111:1991	SCC 3			0.30-0.40	0.50-0.80	0.30-0.60	0.040	0.040				
BS 3100:1991 AMD.1:1992	A3			0.45	1.0	0.60	0.050	0.050				
JIS G 5111:1991	SCMn 1			0.20-0.30	1.00-1.60	0.30-0.60	0.040	0.040				
BS 3100:1991 AMD.1:1992	A4			0.18-0.25	1.2-1.6	0.60	0.050	0.050				
ASTM A 148/A 148M-03	80-40 80-50						0.05	0.06				
	SC 1030 Class 80/40 SC 1030 Class 80/50			0.28-0.34	0.40-0.80	0.30-0.60	0.040	0.040				
ASTM A 958-00	SC 1040 Class 80/40 SC 1040 Class 80/50			0.37-0.44	0.50-0.90	0.30-0.60	0.040	0.040				
	SC 1045 Class 80/40 SC 1045 Class 80/50			0.43-0.50	0.50-0.90	0.30-0.60	0.040	0.040				
JIS G 5102:1991	SCW 550			0.22	1.50	0.80	0.040	0.040	0.50	2.50	0.30	V 0.20
ISO 3755:1991	340-550						0.035	0.035				
130 3733.1991	340-550W			0.25	1.50	0.60	0.035	0.035	0.35	0.40	0.15	V 0.05; Cu+Ni+Cr+Mo+V 1.00
AFNOR NF A 32-054:1994	GE320			0.32	1.20	0.60	0.035	0.030				
AT NOTENIT A 32-034.1994	G30Mn6			0.25-0.32	1.80	0.60	0.030	0.025				
JIS G 5111:1991	SCSiMn 2			0.25-0.35	0.90-1.20	0.50-0.80	0.040	0.040				
JIS G 5111:1991	SCMn 1			0.20-0.30	1.00-1.60	0.30-0.60	0.040	0.040				
013 G 5111.1991	SCMn 2			0.25-0.35	1.00-1.60	0.30-0.60	0.040	0.040				
DIN 1681:1985	GS-60	1.0558										
AFNOR NF A 32-054:1994	G30Mn6			0.25-0.32	1.80	0.60	0.030	0.025				
JIS G 5111:1991	SCC 5			0.40-0.50	0.50-0.80	0.30-0.60	0.040	0.040				
013 G 3111.1991	SCC 3			0.30-0.40	0.50-0.80	0.30-0.60	0.040	0.040				
BS 3100:1991 AMD.1:1992	A5			0.25-0.33	1.2-1.6	0.60	0.05	0.05				
ASTM A 148/A 148M-03	90-60						0.05	0.06				
ASTM A 958-00	SC 1040 Class 90/60			0.37-0.44	0.50-0.90	0.30-0.60	0.040	0.040				
A3 FIVI A 930-00	SC 1045 Class 90/60			0.43-0.50	0.50-0.90	0.30-0.60	0.040	0.040				
JIS G 5102:1991	SCW 620			0.22	1.50	0.80	0.040	0.040	0.50	2.50	0.30	V 0.20
	SCMn 3			0.30-0.40	1.00-1.60	0.30-0.60	0.040	0.040				
JIS G 5111:1991	SCMn 2			0.25-0.35	1.00-1.60	0.30-0.60	0.040	0.040				
	SCSiMn 2			0.25-0.35	0.90-1.20	0.50-0.80	0.040	0.040				

7.1.1B Chemical Composition of Cast Carbon Steel for General and Structural Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS				V	/eight, %, r	nax, Unles	s Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
AFNOR NF A 32-054:1994	GE370			0.45	1.20	0.60	0.035	0.030				
	SCMn 5			0.40-0.50	1.00-1.60	0.30-0.60	0.040	0.040				
JIS G 5111:1991	SCC 5			0.40-0.50	0.50-0.80	0.30-0.60	0.040	0.040				
	SCMn 3			0.30-0.40	1.00-1.60	0.30-0.60	0.040	0.040				
BS 3100:1991 AMD.1:1992	A6			0.25-0.33	1.2-1.6	0.60	0.050	0.050				
ASTM A 148/A 148M-03	105-85		J31575				0.05	0.06				
ASTM A 958-00	SC 1045 Class 105/85			0.43-0.50	0.50-0.90	0.30-0.60	0.040	0.040				
IIS G 5111:1991	SCMn 5			0.40-0.50	1.00-1.60	0.30-0.60	0.040	0.040				

326

7.1 Cast Carbon Steels

7.1.2A Mechanical Properties of Cast Carbon Steel for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 5151:1991	SCPH 1			A, N, NT, or QT			205		410			
ASTM A 216/A 216M-93 (2003)	WCA		J02502	A, N, or NT			205	30	415-585	60-85	24	
	GP240GR	1.0621		N			240		420-600		22	27 J at RT
EN 10213-2:1995	GP240GH	1.0619		N QT			240		420-600		22	27 J at RT 40 J at RT
	C23-45A			A, N(T), or (QT)								
ISO 4991:1994	C23-45AH			N(T) or QT			240		450-600		22	
130 4991.1994	C23-45B			A, N(T), or (QT)			240		430-000		22	
	C23-45BH			N(T) or QT								
JIS G 5151:1991	SCPH 2			A, N, NT, or QT			245		480			
EN 10213-2:1995	GP280GH	1.0625		N QT			280		480-640		22	27 J at RT 35 J at RT
ACTNA A 046/A 046NA 00 (0000)	WCB		J03002	A, N, or NT			250	36	485-655	70-95	22	
ASTM A 216/A 216M-93 (2003)	WCC		J02503	A, N, or NT			275	40	485-655	70-95	22	
ISO 4991:1994	C26-52			A, N(T), or (QT)			280		520-670		18	
130 4331.1334	C26-52H			NT or QT			200		320-070		10	

7.1.2B Chemical Composition of Cast Carbon Steel for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				٧	/eight, %, r	nax, Unles	s Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5151:1991	SCPH 1			0.25	0.70	0.60	0.040	0.040	0.25	0.50	0.25	Cu+Ni+Cr+Mo 1.00
ASTM A 216/A 216M-93 (2003)	WCA		J02502	0.25	0.70	0.60	0.04	0.045	0.50	0.50	0.20	Cu 0.30; V 0.03; Cu+Ni+Cr+Mo+V 1.00
EN 10213-2:1995	GP240GP	1.0621		0.18-0.25	1.20	0.60	0.030	0.020				
EN 10213-2.1995	GP240GH	1.0619		0.18-0.23	0.50-1.20	0.60	0.030	0.020				
	C23-45A			0.025	1.20	0.60	0.035	0.035				
ISO 4991:1995	C23-45H			0.025	1.20	0.60	0.035	0.035				
150 4991:1995	C23-45B			0.20	1.00-1.60	0.60	0.030	0.030				
	C23-45BH			0.20	1.00-1.60	0.60	0.030	0.030				
JIS G 5151:1991	SCPH 2			0.30	1.00	0.60	0.040	0.040	0.25	0.50	0.25	Cu+Ni+Cr+Mo 1.00
EN 10213-2:1995	GP280GH	1.0625		0.18-0.25	0.80-1.20	0.60	0.030	0.020				
ASTM A 016/A 016M 02 (0002)	WCB		J03002	0.30	1.00	0.60	0.04	0.045	0.50	0.50	0.20	Cu 0.30; V 0.03; Cu+Ni+Cr+Mo+V 1.00
ASTM A 216/A 216M-93 (2003)	WCC		J02503	0.25	1.20	0.60	0.04	0.045	0.50	0.50	0.20	Cu 0.30; V 0.03; Cu+Ni+Cr+Mo+V 1.00
ISO 4001:1005	C26-52			0.05	1.20	0.60	0.020	0.000				
ISO 4991:1995	C26-52H			0.25	1.20	0.60	0.030	0.030				

7.1.3A Mechanical Properties of Cast Carbon Steel for Pressure Purposes at Low Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ASTM A 352/A 352M-03	LCA		J02504	NT or QT			205	30.0	415-585	60-85	24	18 J at -32°C
ASTM A 757/A 757M-00	A1Q		J03002	QT			240	35	450	65	24	17 J at -46°C
JIS G 5152:1991	SCPL 1			A, N, NT, or QT			245		450		21	18 J at -46°C
ISO 4991:1994	C23-45BL			(NT) or QT			240		450-600		22	27 J at -40°C
EN 10213-3:1995	G17Mn5	1.1131		QT	≤ 50		240		450-600		24	27 J at -40°C
ASTM A 352/A 352M-03	LCB		J03003	NT or QT			240	35	450-620	65.0-90.0	24	18 J at -46°C
EN 10213-3:1995	G20Mn5	1.6220		N	≤ 30		300		480-620		20	27 J at -30°C
ASTM A 757/A 757M-00	A2Q		J02503	QT			275	40	485	70	22	20 J at -46°C
ASTM A 352/A 352M-03	LCC		J02505	NT or QT			275	40.0	485-655	70.0-95.0	22	20 J at -46°C
EN 10213-3:1995	G20Mn5	1.6220		QT	≤ 100		300		500-650		22	27 J at -40°C
ISO 4991:1994	C26-52L			(NT) or QT			280		520-670		18	27 J at -35°C

7.1.3B Chemical Composition of Cast Carbon Steel for Pressure Purposes at Low Temperatures

Standard	Grade, Class, Type,	Steel	UNS				٧	/eight, %, r	nax, Unles	s Otherwis	e Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 352/A 352M-03	LCA		J02504	0.25	0.70	0.60	0.04	0.045	0.50	0.50	0.20	Cu 0.30; V 0.03; P+S+Ni+Cr+Mo+Cu+V 1.00
ASTM A 757/A 757M-00	A1Q		J03002	0.30	1.00	0.60	0.025	0.025	0.40	0.50	0.25	Cu 0.50; V 0.03; Ni+Cr+Mo+Cu+V 1.00
JIS G 5152:1991	SCPL 1			0.30	1.00	0.60	0.040	0.040	0.25	0.50		Cu 0.50; Cu+Ni+Cr 1.00
ISO 4991:1994	C23-45BL			0.20	1.00-1.60	0.60	0.030	0.030				
EN 10213-3:1995	G17Mn5	1.1131		0.15-0.20	1.00-1.60	0.60	0.020	0.020				
ASTM A 352/A 352M-03	LCB		J03003	0.30	1.00	0.60	0.04	0.045	0.50	0.50	0.20	Cu 0.30; V 0.03; P+S+Ni+Cr+Mo+Cu+V 1.00
EN 10213-3:1995	G20Mn5	1.6220		0.17-0.23	1.00-1.60	0.60	0.020	0.020		0.80		
ASTM A 757/A 757M-00	A2Q		J02503	0.25	1.20	0.60	0.025	0.025	0.40	0.50	0.25	Cu 0.50; V 0.03; Ni+Cr+Mo+Cu+V 1.00
ASTM A 352/A 352M-03	LCC		J02505	0.25	1.20	0.60	0.04	0.045	0.50	0.50	0.20	V 0.03; Ni+Cr+Mo+Cu+V 1.00
ISO 4991:1994	C26-52L			0.25	1.20	0.60	0.030	0.030				

7.2 Cast Manganese Steels

7.2A Chemical Composition of Cast Manganese Steels

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %,	max, Unles	s Otherwis	e Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
	SCMnH 1			0.90-1.30	11.00-14.00		0.100	0.050				
JIS G 5131:1991	SCMnH 2			0.90-1.20	11.00-14.00	0.80	0.070	0.040				
	SCMnH 3			0.90-1.20	11.00-14.00	0.30-0.80	0.050	0.035				
	Α		J91109	1.05-1.35	11.0	1.00	0.07					
	B-1		J91119	0.9-1.05	11.5-14.0	1.00	0.07					
ASTM A 128/A 128M-93 (2003)	B-2		J91129	1.05-1.2	11.5-14.0	1.00	0.07					
	B-3		J91139	1.12-1.28	11.5-14.0	1.00	0.07					
	B-4		J91149	1.2-1.35	11.5-14.0	1.00	0.07					
BS 3100:1991 AMD.1:1992	BW10			1.00-1.35	11.0	1.0	0.050	0.050				
AFNOR NF A 32-058:1984	Z120M12-M			1.1-1.4	11-14	1	0.08	0.030				
ISO 13521:1999	GX100Mn13			0.90-1.05	11-14	0.3-0.9	0.060	0.045				
130 13321.1999	GX120Mn13			1.05-1.35	11-14	0.3-0.9	0.060	0.045				
JIS G 5131:1991	SCMnH 11			0.90-1.30	11.00-14.00	0.80	0.070	0.040	1.50-2.50			
ASTM A 128/A 128M-93 (2003)	С		J91309	1.05-1.35	11.5-14.0	1.00	0.07		1.5-2.5			
AFNOR NF A 32-058:1984	Z120MC12-M			1.1-1.4	11-14	1	0.08	0.030	1-2.5			
ISO 13521:1999	GX120MnCr13-2			1.05-1.35	11-14	0.3-0.9	0.060	0.045	1.5-2.5			
ASTM A 128/A 128M-93 (2003)	D		J91459	0.7-1.3	11.5-14.0	1.00	0.07			3.0-4.0		
AFNOR NF A 32-058:1984	Z100MN13 4-M			0.7-1.3	12-15	1	0.08	0.030		2-5		
ISO 13521:1999	GX120MnNi13-3			1.05-1.35	11-14	0.3-0.9	0.060	0.045		3-4		
ASTM A 128/A 128M-93 (2003)	E-1		J91249	0.7-1.3	11.5-14.0	1.00	0.07				0.9-1.2	
AFNOR NF A 32-058:1984	Z110MD12 1-M			0.8-1.3	11-14	1	0.08	0.030			0.8-1.2	
ISO 13521:1999	GX110MnMo13-1			0.75-1.35	11-14	0.3-0.9	0.060	0.045			0.9-1.2	
ASTM A 128/A 128M-93 (2003)	E-2		J91339	1.05-1.45	11.5-14.0	1.00	0.07				1.8-2.1	
ISO 13521:1999	GX90MnMo14			0.70-1.00	13-15	0.3-0.6	0.070	0.045			1.0-1.8	
ASTM A 128/A 128M-93 (2003)	F		J91340	1.05-1.35	6.0-8.0	1.00	0.07				0.9-1.2	
AFNOR NF A 32-058:1984	Z100MD8 1-M			0.8-1.2	5-7	1	0.08	0.030			0.8-1.2	
ISO 13521:1999	GX120MnMo7-1			1.05-1.35	6-8	0.3-0.9	0.060	0.045			0.9-1.2	
AFNOR NF A 32-058:1984	Z120MC17 2-M			1.1-1.4	16-18	1	0.08	0.030	1.8-2.3			
ISO 13521:1999	GX120MnCr7-2			1.05-1.35	16-19	0.3-0.9	0.060	0.045	1.5-2.5			

7.2 Cast Manganese Steels

7.2B Mechanical Properties of Cast Manganese Steels

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	
Designation	Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	SCMnH 1			WT								
JIS G 5131:1991	SCMnH 2			WT					740			
	SCMnH 3			WT					740			
	Α		J91109	see standard								
	B-1		J91119	see standard								
ASTM A 128/A 128M-93 (2003)	B-2		J91129	see standard								
	B-3		J91139	see standard								
	B-4		J91149	see standard								
BS 3100:1991 AMD.1:1992	BW10			ST								
AFNOR NF A 32-058:1984	Z120M12-M											
100 10001.1000	GX100Mn13			ST + WQ								
ISO 13521:1999	GX120Mn13			ST + WQ								
JIS G 5131:1991	SCMnH 11			WT			390		740			
ASTM A 128/A 128M-93 (2003)	С		J91309	see standard								
AFNOR NF A 32-058:1984	Z120MC12-M											
ISO 13521:1999	GX120MnCr13-2			ST + WQ								
ASTM A 128/A 128M-93 (2003)	D		J91459	see standard								
AFNOR NF A 32-058:1984	Z100MN13 4-M											
ISO 13521:1999	GX120MnNi13-3			ST + WQ								
ASTM A 128/A 128M-93 (2003)	E-1		J91249	see standard								
AFNOR NF A 32-058:1984	Z110MD12 1M											
ISO 13521:1999	GX110MnMo13-1			ST + WQ								
ASTM A 128/A 128M-93 (2003)	E-2		J91339	see standard								
ISO 13521:1999	GX90MnMo14			AC	< 45 mm and C < 0.8							
				ST + WQ	≥ 45 mm							
ASTM A 128/A 128M-93 (2003)	F		J91340	see standard								
AFNOR NF A 32-058:1984	Z100MD8 1-M											
ISO 13521:1999	GX120MnMo7-1			ST + WQ								
AFNOR NF A 32-058:1984	Z120MC17 2-M											
ISO 13521:1999	GX120MnCr7-2			ST + WQ								

7.3.1A Chemical Composition of Cast Alloy Steels for General and Structural Purposes

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unles	s Otherwis	e Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
AFNOR NF A 32-053:1992	20 D5-M			0.23	1.20	0.60	0.025	0.020			0.45-0.65	
BS 3100:1991 AMD.1:1992	B1			0.20	0.40-1.00	0.20-0.60	0.040	0.040	0.30	0.40	0.45-0.65	Cu 0.30; Cr+Ni+Cu+V 0.80
AFNOR NF A 32-054:1994	G25CrMo4			0.22-0.28	1.00	0.60	0.030	0.020	0.80-1.20		0.15-0.35	
JIS G 5111:1991	SCCrM 1			0.20-0.30	0.50-0.80	0.30-0.60	0.040	0.040	0.80-1.20		0.15-0.35	
DIN 17205:1992	GS-25 CrMo 4	1.7218		0.22-0.29	0.50-0.80	0.60	0.020	0.015	0.80-1.20		0.20-0.30	
ASTM A 958-00	SC 4130			0.28-0.33	0.40-0.80	0.30-0.60	0.035	0.040	0.80-1.10		0.15-0.25	
DIN 17205:1992	GS-34 CrMo 4	1.7220		0.30-0.37	0.50-0.80	0.60	0.020	0.015	0.80-1.20		0.20-0.30	
JIS G 5111:1991	SCCrM 3			0.30-0.40	0.50-0.80	0.30-0.60	0.040	0.040	0.80-1.20		0.15-0.35	
AFNOR NF A 32-054:1994	G35CrMo4			0.30-0.38	1.00	0.60	0.030	0.020	0.80-1.20		0.15-0.35	
ASTM A 958-00	SC 4140			0.38-0.43	0.70-1.10	0.30-0.60	0.035	0.040	0.80-1.10		0.15-0.25	
DIN 17205:1992	GS-42 CrMo 4	1.7225		0.38-0.45	0.60-1.00	0.60	0.020	0.015	0.80-1.20		0.20-0.30	
AFNOR NF A 32-054:1994	G42CrMo4			0.39-0.45	1.00	0.60	0.030	0.020	0.80-1.20		0.15-0.35	
ASTM A 958-00	SC 4330			0.28-0.33	0.60-0.90	0.30-0.60	0.035	0.040	0.70-0.90	1.65-2.00	0.20-0.30	
JIS G 5111:1991	SCNCrM 2			0.25-0.35	0.90-1.50	0.30-0.60	0.040	0.040	0.30-0.90	1.60-2.00	0.15-0.35	
DIN 17205:1992	GS-33 CrNiMo 7 4 4	1.6740		0.30-0.36	0.50-0.80	0.60	0.015	0.007	0.90-1.20	1.50-1.80	0.35-0.50	
AFNOR NF A 32-054:1994	G30NiCrMo8			0.33	1.00	0.60	0.030	0.020	0.80-1.20	1.70-2.30	0.30-0.60	

7.3.1B Mechanical Properties of Cast Alloy Steels for General and Structural Purposes

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
AFNOR NF A 32-053:1992	20 D5-M			QT	≤ 100		245		440		22	27 J at -45°C
BS 3100:1991 AMD.1:1992	B1			NT or OQT or WQT			260		460		18	20 J at 20°C
					28 ≤ t < 50		380		580		18	22 J at RT
				N	50 ≤ t <100		300		580		16	20 J at RT
AFNOR NF A 32-054:1994				IN	100 ≤ t < 150		250		550		14	20 J at RT
	G25CrMo4				150 ≤ t < 250		250		550		14	20 J at RT
AI NOR NI A 32-034.1994	G25011VI04				28 ≤ t < 50		550		750		12	35 J at RT
				QT1	50 ≤ t <100		550		700		10	18 J at RT
				(TR1)	100 ≤ t < 150		520		650		10	10 J at RT
					150 ≤ t < 250		500		650		10	10 J at RT
JIS G 5111:1991	SCCrM 1A			NT			390		590		13	170 HB min
JIS G 5111.1991	SCCrM 1B			QT			490		690		13	201 HB min
	GS-25 CrMo 4	1.7218		NT	≤ 250		300		550-700		16	
	GS-25 CrMo 4, Class I	1.7218		QT	≤ 50		450		600-750		18	
DIN 17005:1000	GS-25 CrMo 4, Class II	1.7218		QT	≤ 50		600		750-900		10	see standard
IN 1/205:1992	GS-25 CrMo 4, Class I	1.7218		QT	50 < t ≤ 100		450		600-750		14	for impact data
	GS-25 CrMo 4, Class II	1.7218		QT	50 < t ≤ 100		550		700-850		10	
	GS-25 CrMo 4, Class I	1.7218		QT	100 < t ≤ 150		410		600-750		12	1

7.3.1B Mechanical Properties of Cast Alloy Steels for General and Structural Purposes (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	SC 4130 Class 65/35			NT			240	35	450	65	24	
	SC 4130 Class 70/36			NT			250	36	485	70	22	
	SC 4130 Class 80/40			NT			275	40	550	80	18	
	SC 4130 Class 80/50			NT			345	50	550	80	22	
ASTM A 958-00	SC 4130 Class 90/60			NT or QT			415	60	620	90	18	
ASTWI A 958-00	SC 4130 Class 105/85			QT			585	85	725	105	17	
	SC 4130 Class 115/95			QT			655	95	795	115	14	
	SC 4130 Class 130/115			QT			795	115	895	130	11	
	SC 4130 Class 135/125			QT			860	125	930	135	9	
	SC 4130 Class 150/135			QT			930	135	1035	150	7	
					≤ 150		380		650-800		10	
	GS-34 CrMo 4	1.7220		NT	150 < t ≤ 250		330		620-770		10	
					250 < t ≤ 400		300		620-770		10	
DIN 17205:1992	GS-34 CrMo 4, Class I	1.7220		QT	≤ 50		600		750-850		14	see standard
DIN 17205.1992	GS-34 CrMo 4, Class II	1.7220		QT	≤ 50		700		850-1000		10	for impact data
	GS-34 CrMo 4, Class I	1.7220		QT	50 < t ≤ 100		540		700-850		12	
	GS-34 CrMo 4, Class II	1.7220		QT	50 < t ≤ 100		650		830-980		10	
	GS-34 CrMo 4, Class I	1.7220		QT	100 < t ≤ 150		480		620-770		10	
JIS G 5111:1991	SCCrM 3A			NT			440		690		9	201 HB min
JIS G 5111:1991	SCCrM 3B			QT			540		740		9	217 HB min
					28 ≤ t < 50		520		750		12	20 J at RT
				NI	50 ≤ t <100		450		700		10	18 J at RT
				N	100 ≤ t < 150		380		650		10	15 J at RT
AFNOR NF A 32-054:1994	G35CrMo4				150 ≤ t < 250		330		620		10	15 J at RT
				OTO	28 ≤ t < 50		600		750		14	35 J at RT
				QT2 (TR2)	50 ≤ t <100		540		700		12	30 J at RT
				(104)	100 ≤ t < 150		480		620		10	25 J at RT

Chapter 7

7.3 Cast Alloy Steels

7.3.1B Mechanical Properties of Cast Alloy Steels for General and Structural Purposes (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thickr	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
	SC 4140 Class 65/35			NT			240	35	450	65	24	
	SC 4140 Class 70/36			NT			250	36	485	70	22	
	SC 4140 Class 80/40			NT			275	40	550	80	18	
	SC 4140 Class 80/50			NT			345	50	550	80	22	
	SC 4140 Class 90/60			NT			415	60	620	90	18	
ASTM A 958-00	SC 4140 Class 105/85			NT or QT			585	85	725	105	17	
ASTWIA 956-00	SC 4140 Class 115/95			QT			655	95	795	115	14	
	SC 4140 Class 130/115			QT			795	115	895	130	11	
	SC 4140 Class 135/125			QT			860	125	930	135	9	
	SC 4140 Class 150/135			QT			930	135	1035	150	7	
	SC 4140 Class 160/145			QT			1000	145	1105	160	6	
	SC 4140 Class 165/150			QT			1035	150	1140	165	5	
					≤ 150		400		700-850		10	
	GS-42 CrMo 4	1.7225		NT	150 < t ≤ 250		350		650-800		10	
					250 < t ≤ 400		320		650-800		10	-
DIN 17205:1992	GS-42 CrMo 4, Class I	1.7225		QT	≤ 50		650		780-930		14	see standard
DIN 17205.1992	GS-42 CrMo 4, Class II	1.7225		QT	≤ 50		800		900-1100		10	for impact data
	GS-42 CrMo 4, Class I	1.7225		QT	50 < t ≤ 100		600		800-950		12	
	GS-42 CrMo 4, Class II	1.7225		QT	50 < t ≤ 100		700		850-1000		10	
	GS-42 CrMo 4, Class I	1.7225		QT	100 < t ≤ 150		550		700-850		10	
					28 ≤ t < 50		580		780		10	12 J at RT
				N	50 ≤ t <100		460		740		10	12 J at RT
				N	100 ≤ t < 150		400		700		10	10 J at RT
AFNOR NF A 32-054:1994	G42CrMo4				150 ≤ t < 250		350		650		10	10 J at RT
				OTO	28 ≤ t < 50		650		800		14	27 J at RT
				QT2 (TR2)	50 ≤ t <100		600		780		12	27 J at RT
				(104)	100 ≤ t < 150		550		700		10	20 J at RT

7.3 Cast Alloy Steels

7.3.1B Mechanical Properties of Cast Alloy Steels for General and Structural Purposes (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thickr	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation	
Designation	Symbol or Name		Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	, min, %	Other
	SC 4330 Class 65/35			NT			240	35	450	65	24	
	SC 4330 Class 70/36			NT			250	36	485	70	22	
	SC 4330 Class 80/40			NT			275	40	550	80	18	
	SC 4330 Class 80/50			NT			345	50	550	80	22	
	SC 4330 Class 90/60			NT or QT			415	60	620	90	18	
	SC 4330 Class 105/85			QT			585	85	725	105	17	
ASTM A 958-00	SC 4330 Class 115/95			QT			655	95	795	115	14	
	SC 4330 Class 130/115			QT			795	115	895	130	11	
	SC 4330 Class 135/125			QT			860	125	930	135	9	
	SC 4330 Class 150/135			QT			930	135	1035	150	7	
	SC 4330 Class 160/145			QT			1000	145	1105	160	6	
	SC 4330 Class 165/150			QT			1035	150	1140	165	5	
	SC 4330 Class 210/180			QT			1240	180	1450	210	4	
110.0.5111.1001	SCNCrM 2A			NT			590		780		9	223 HB min
JIS G 5111:1991	SCNCrM 2B			QT			685		880		9	269 HB min
	00.00.0000000	4 0740		NIT	≤ 150		600		800-950		12	
	GS-33 CrNiMo 7 4 4	1.6740		NT	150 < t ≤ 400		550		750-900		12	
	GS-33 CrNiMo 7 4 4, Class I	1.6740		QT	≤ 100		700		850-1000		16	
DIN 17205:1992	GS-33 CrNiMo 7 4 4, Class II	1.6740		QT	≤ 100		950		1050-1250		10	see standard for impact data
	GS-33 CrNiMo 7 4 4, Class I	1.6740		QT	100 < t ≤ 250		700		850-1000		14	
	GS-33 CrNiMo 7 4 4, Class I	1.6740		QT	250 < t ≤ 400		650		800-950		10	
					28 ≤ t < 50		550		750		15	32 J at RT
				NI	50 ≤ t <100		550		750		12	32 J at RT
				N	100 ≤ t < 150		550		750		12	32 J at RT
AFNOR NF A 32-054:1994	G30NiCrMo8				150 ≤ t < 250		500		700		12	32 J at RT
AFNOR NF A 32-054:1994	G30INICTIVIO8				28 ≤ t < 50		700		850		15	50 J at RT
				QT2	50 ≤ t <100		700		850		14	50 J at RT
				(TR2)	100 ≤ t < 150		650		850		12	35 J at RT
					150 ≤ t < 250		650		820		10	27 J at RT

7.3.2A Chemical Composition of Cast Alloy Steels for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	, max, Unles	ss Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10213-2:1995	G20Mo5	1.5419		0.15-0.23	0.50-1.00	0.60	0.025	0.020		0.40-0.60		
JIS G 5151:1991	SCPH 11			0.25	0.50-0.80	0.60	0.040	0.040	0.35	0.45-0.65	0.50	W 0.1; Cu+Ni+Cr+W 1.00
ISO 4991:1994	C28H			0.15-0.23	0.50-1.00	0.30-0.60	0.035	0.030	0.30	0.40-0.60		
ASTM A 217/A 217M-02	WC1		J12524	0.25	0.50-0.80	0.60	0.04	0.045		0.45-0.65		Cu 0.50; Ni 0.50; Cr 0.35; W 0.10; Cu+Ni+Cr+W 1.00
JIS G 5151:1991	SCPH 21			0.20	0.50-0.80	0.60	0.040	0.040	1.00-1.50	0.50	0.45-0.65	W 0.10; Cu+Ni+W 1.00
ASTM A 217/A 217M-02	WC6		J12072	0.05-0.20	0.50-0.80	0.60	0.04	0.045	1.00-1.50		0.45-0.65	Cu 0.50; Ni 0.50; W 0.10; Cu+Ni+W 1.00
ISO 4991:1994	C32H			0.10-0.20	0.50-0.80	0.30-0.60	0.035	0.035	1.00-1.50		0.45-0.65	
EN 10213-2:1995	G17CrMo5-5	1.7357		0.15-0.20	0.50-1.00	0.60	0.020	0.020	1.00-1.50		0.45-0.65	
JIS G 5151:1991	SCPH 23			0.20	0.50-0.80	0.60	0.040	0.040	1.00-1.50	0.50	0.90-1.20	V 0.15-0.25; Cu 0.50; W 0.10; Cu+Ni+W 1.00
ASTM A 389/A 389M-03	C24		J12092	0.20	0.30-0.80	0.60	0.04	0.045	0.80-1.25		0.90-1.20	V 0.15-0.25
ISO 4991:1994	C35BH			0.13-0.20	0.50-0.80	0.30-0.60	0.035	0.035	1.20-1.60		0.90-1.20	V 0.15-0.35
EN 10213-2:1995	G17CrMoV5-10	1.7706		0.15-0.20	0.50-0.90	0.60	0.020	0.015	1.20-1.50		0.90-1.10	V 0.20-0.30; Sn 0.025
JIS G 5151:1991	SCPH 32			0.20	0.50-0.80	0.60	0.040	0.040	2.00-2.75	0.50	0.90-1.20	Cu 0.50; W 0.10; Cu+Ni+W 1.00
ASTM A 217/A 217M-02	WC9		J21890	0.05-0.18	0.40-0.70	0.60	0.04	0.045	2.00-2.75		0.90-1.20	Cu 0.50; Ni 0.50; W 0.10; Cu+Ni+W 1.00
ISO 4991:1994	C34AH			0.08-0.15	0.50-0.80	0.30-0.60	0.035	0.035	2.00250		0.90-1.20	
ASTM A 487/A 487M-93 (2003)	Grade 8, Class A, B, C		J22091	0.05-0.20	0.50-0.90	0.80	0.04	0.045	2.00-2.75		0.90-1.10	Cu 0.50; W 0.10; V 0.03; Cu+W+V 0.60
EN 10213-2:1995	G17CrMo9-10	1.7379		0.13-0.20	0.50-0.90	0.60	0.020	0.020	2.00-2.50		0.90-1.20	
ISO 4991:1994	C34BH			0.13-0.20	0.50-0.80	0.30-0.60	0.035	0.035	2.00250		0.90-1.20	
JIS G 5151:1991	SCPH 61			0.20	0.50-0.80	0.75	0.040	0.040	4.00-6.50	0.50	0.45-0.65	Cu 0.50; W 0.10; Cu+Ni+W 1.00
ASTM A 217/A 217M-02	C5		J42045	0.20	0.40-0.70	0.75	0.04	0.045	4.00-6.50		0.45-0.65	Cu 0.50; Ni 0.50; W 0.10; Cu+Ni+W 1.00
EN 10213-2:1995	GX15CrMo5	1.7365		0.12-0.19	0.50-0.80	0.80	0.025	0.025	4.00-6.00		0.45-0.65	
ISO 4991:1994	C37H			0.12-0.19	0.50-0.80	0.80	0.035	0.035	4.00-6.00		0.45-0.65	
EN 10295:2002	Gx30CrSi7	1.4710		0.20-0.35	0.50-1.00	1.00-2.50	0.035	0.030	6.00-8.00	0.50	0.15	
ISO 11973:1999	GX30CrSi7			0.20-0.35	0.5-1.0	1.0-2.5	0.04	0.04	6-8	0.5	0.5	
ASTM A 217/A 217M-02	C12		J82090	0.20	0.35-0.65	1.00	0.04	0.045	8.00-10.00		0.90-1.20	Cu 0.50; Ni 0.50; W 0.10; Cu+Ni+W 1.00
ISO 4991:1994	C38H			0.10-0.17	0.50-0.80	0.80	0.035	0.035	8.00-10.00		1.00-1.30	

7.3.2B Mechanical Properties of Cast Alloy Steels for Pressure Purposes at High Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number	00	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10213-2:1995	G20Mo5	1.5419		QT	≤ 100		245		440-590		22	27 J at RT
JIS G 5151:1991	SCPH 11			A, N, NT, or QT			245		450		22	
ISO 4991:1994	C28H			NT or QT			250		450-600		21	25 J at RT
ASTM A 217/A 217M-02	WC1		J12524	NT			240	35	450-620	65-90	24	
JIS G 5151:1991	SCPH 21			A, N, NT, or QT			275		480		17	
ASTM A 217/A 217M-02	WC6		J12072	NT			275	40	485-655	70-95	20	
ISO 4991:1994	C32H			NT or QT			290		490-640		18	27 J at RT
EN 10213-2:1995	G17CrMo5-5	1.7357		QT	≤ 100		315		490-690		20	27 J at RT
JIS G 5151:1991	SCPH 23			A, N, NT, or QT			345		550		13	
ASTM A 389/A 389M-03	C24		J12092	NT			345	50	552	80	15.0	
ISO 4991:1994	C35BH			N _{ac} T or QT			420		590-740		15	24 J at RT
EN 10213-2:1995	G17CrMoV5-10	1.7706		QT	≤ 150		440		590-780		15	27 J at RT
JIS G 5151:1991	SCPH 32			A, N, NT, or QT			275		480		17	
ASTM A 217/A 217M-02	WC9		J21890	NT			275	40	485-655	70-95	20	
ISO 4991:1994	C34AH			NT			280		510-660		18	25 J at RT
ASTM A 487/A 487M-93 (2003)	Grade 8, Class A		J22091	NT			380	55	585-760	85-110	20	
EN 10213-2:1995	G17CrMo9-10	1.7379		QT	≤ 150		400		590-740		18	40 J at RT
ISO 4991:1994	C34BH			(NT), N _{ac} T or QT			390		600-750		18	40 J at RT
ASTM A 487/A 487M-93 (2003)	Grade 8, Class C		J22091	QT			515	75	690	100	17	22 HRC max 235 HB max
ASTM A 487/A 487M-93 (2003)	Grade 8, Class B		J22091	QT			585	85	725	105	17	
JIS G 5151:1991	SCPH 61			A, N, NT, or QT			410		620		17	
ASTM A 217/A 217M-02	C5		J42045	NT			415	60	620-795	90-115	18	
EN 10213-2:1995	GX15CrMo5	1.7365		QT	≤ 150		420		630-760		16	27 J at RT
ISO 4991:1994	C37H			NT			420		630-780		16	25 J at RT
EN 10295:2002	GX30CrSi7	1.4710		Α								300 HB
ISO 11973:1999	GX30CrSi7			AC or A								
ASTM A 217/A 217M-02	C12		J82090	NT			415	60	620-795	90-115	18	
ISO 4991:1994	C38H			NT			420		630-780		16	20 J at RT

7.3.3A Chemical composition of Cast Alloy Steels for Pressure Purposes at Low Temperatures

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %,	max, Unles	s Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10213-3:1995	G18Mo5	1.5422		0.15-0.20	0.80-1.20	0.60	0.020	0.020			0.45-0.65	
JIS G 5152:1991	SCPL 11			0.25	0.50-0.80	0.60	0.040	0.040	0.35		0.45-0.65	Cu 0.50
ASTM A 352/A 352M-03	LC1		J12522	0.25	0.50-0.80	0.60	0.04	0.045			0.45-0.65	
JIS G 5152:1991	SCPL 21			0.25	0.50-0.80	0.60	0.040	0.040	0.35	2.00-3.00		Cu 0.50
EN 10213-3:1995	G9Ni10	1.5636		0.06-0.12	0.50-0.80	0.60	0.020	0.015		2.00-3.00		
ASTM A 757/A 757M-00	B2N, B2Q		J22501	0.25	0.50-0.80	0.60	0.025	0.025	0.40	2.0-3.0	0.25	Cu 0.50; V 0.03; P+S+Cu+V+Cr+Mo 1.00
ASTM A 352/A 352M-03	LC2		J22500	0.25	0.50-0.80	0.60	0.04	0.045		2.00-3.00		
ISO 4991:1994	C43L			0.14	0.50-0.80	0.30-0.60	0.030	0.030		3.00-4.00		
JIS G 5152:1991	SCPL 31			0.15	0.50-0.80	0.60	0.040	0.040	0.35	3.00-4.00		Cu 0.50
ASTM A 757/A 757M-00	B3N, B3Q		J31500	0.15	0.50-0.80	0.60	0.025	0.025	0.40	3.0-4.0	0.25	Cu 0.50; V 0.03; P+S+Cu+V+Cr+Mo 1.00
ASTM A 352/A 352M-03	LC3		J31550	0.15	0.50-0.80	0.60	0.04	0.045		3.00-4.00		
EN 10213-3:1995	G9Ni14	1.5638		0.06-0.12	0.50-0.80	0.60	0.020	0.015		3.00-4.00		
ISO 4991:1994	C43E2aL			0.22	0.40-0.80	0.30-0.60	0.030	0.030	1.35-2.00	2.50-3.50	0.35-0.60	
ASTM A 352/A 352M-03	LC2-1		J42215	0.22	0.55-0.75	0.50	0.04	0.045	1.351.85	2.50-3.50	0.30-0.60	
EN 10213-3:1995	G17NiCrMo13-6	1.6781		0.15-0.19	0.55-0.80	0.50	0.015	0.015	1.30-1.80	3.00-3.50	0.45-0.60	
ASTM A 757/A 757M-00	E2N1, E2Q1, E2N2, E2Q2, E2N3, E2Q3			0.20	0.40-0.70	0.60	0.020	0.020	1.50-2.00	2.75-3.90	0.40-0.60	Cu 0.50; V 0.03; W 0.10; P+S+V+Cu+W 0.70
ISO 4991:1994	C43E2bL			0.22	0.40-0.80	0.30-0.60	0.030	0.030	1.50-2.00	2.75-3.90	0.35-0.60	

7.3.3B Mechanical Properties of Cast Alloy Steels for Pressure Purposes at Low Temperatures

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10213-3:1995	G18Mo5	1.5422		QT	≤ 100		240		440-790		23	27 J at -45°C
JIS G 5152:1991	SCPL 11			A, N, NT, or QT			245		450		21	18 J at -60°C
ASTM A 352/A 352M-03	LC1		J12522	NT or QT			240	35.0	450-620	65.0-90.0	24	18 J at -59°C
JIS G 5152:1991	SCPL 21			A, N, NT, or QT			275		480		21	21 J at -75°C
EN 10213-3:1995	G9Ni10	1.5636		QT	≤ 35		280		480-630		24	27 J at -70°C
ASTM A 757/A 757M-00	B2N, B2Q		J22501	NT or QT	≤ 125	5	275	40	485	70	24	20 J at -73°C
ASTM A 352/A 352M-03	LC2		J22500	NT or QT			275	40.0	485-655	70.0-95.0	24	20 J at -73°C
ISO 4991:1994	C43L			QT			300		460-610		20	27 at -70°C
JIS G 5152:1991	SCPL 31			A, N, NT, or QT			275		480		21	21 J at-100°C
ASTM A 757/A 757M-00	B3N, B3Q		J31500	NT or QT	≤ 32	11/4	275	40	485	70	24	20 J at -101°C
ASTM A 352/A 352M-03	LC3		J31550	NT or QT			275	40.0	485-655	70.0-95.0	24	20 J at -101°C
EN 10213-3:1995	G9Ni14	1.5638		QT	≤ 35		360		500-650		20	27 J -90°C
ISO 4991:1994	C43E2aL			(NT), N _{ac} T or QT			450		620-800		16	27 J at -80°C
ASTM A 352/A 352M-03	LC2-1		J42215	NT or QT			550	80.0	725-895	105.0-130.0	18	41 J at -73°C
EN 10213-3:1995	G17NiCrMo13-6	1.6781		QT	≤ 200		600		750-900		15	27 J at -80°C
	E2N1			NT, QT			485	70	90-120	18	620-825	41 J at -73°C
	E2Q1			NT, QT			485	70	90-120	18	620-825	41 J at -73°C
ASTM A 757/A 757M-00	E2N2			NT, QT			585	85	105-135	15	725-930	27 J at -73°C
ASTIVI A 757/A 757/VI-UU	E2Q2			NT, QT			585	85	105-135	15	725-930	27 J at -73°C
	E2N3			NT, QT			690	100	115-145	13	795-1000	20 J at -73°C
	E2Q3			NT, QT			690	100	115-145	13	795-1000	20 J at -73°C
ISO 4991:1994	C43E2bL			(NT), N _{ac} T or QT			655		800-950		13	27 J at -60°C

Chapter 7

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.1A Chemical Composition of Martensitic and Ferritic Stainless Steels for General and Corrosion Resistant Applications

Standard	Grade, Class, Type,	Steel	UNS				٧	Veight, %	, max, Unles	s Otherwis	e Specifie	1
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5121:2003	SCS 1			0.15	1.00	1.50	0.040	0.040	11.50-14.00	1.00	0.50	
BS 3100:1991 AMD.1:1992	410C21			0.15	1.0	1.0	0.040	0.040	11.5-13.5	1.0		Cu 0.30
ASTM A 743/A 743M-03	CA15		J91150	0.15	1.00	1.50	0.04	0.04	11.5-14.0	1.00	0.50	
BS 3100:1991 AMD.1:1992	420C28			0.20	1.0	1.0	0.040	0.040	11.5-13.5	1.0		Cu 0.30
EN 10283:1998	GX12Cr12	1.4011		0.15	1.00	1.00	0.035	0.025	11.50-13.50	1.0	0.50	
ISO 11972:1998	GX 12 Cr 12			0.15	0.8	0.8	0.035	0.025	11.5-13.5	1.0	0.5	
BS 3100:1991 AMD.1:1992	420C29			0.20	1.0	1.0	0.040	0.040	11.5-13.5	1.0		Cu 0.30
JIS G 5121:2003	SCS 3			0.15	1.00	1.00	0.040	0.040	11.50-14.00	0.50-1.50	0.15-1.00	
EN 10283:1998	GX7CrNiMo12-1	1.4008		0.10	1.00	1.00	0.035	0.025	12.00-13.50	1.00-2.00	0.20-0.50	
ISO 11972:1998	GX 8 CrNiMo 12 1			0.10	0.8	0.8	0.035	0.025	11.5-13.0	0.8-1.8	0.2-0.5	
ASTM A 743/A 743M-03	CA15M		J91151	0.15	1.00	0.65	0.040	0.040	11.5-14.0	1.00	0.15-1.0	
JIS G 5121:2003	SCS 2			0.16-0.24	1.00	1.50	0.040	0.040	11.50-14.00	1.00	0.50	
013 G 5121.2003	SCS 2A			0.25-0.40	1.00	1.50	0.040	0.040	11.50-14.00	1.00	0.50	
ASTM A 743/A 743M-03	CA40		J91153	0.20-0.40	1.00	1.50	0.04	0.04	11.5-14.0	1.0	0.5	
AFNOR NF A 32-053:1992	Z 3CN13.4-M			0.05	1.00	1.00	0.035	0.015	12.0-13.5	3.5-5.0	0.70	
AFNOR NF A 32-054:1994	GX4CrNi13-4			0.06	1.00	0.80	0.035	0.020	12.00-13.50	3.50-4.50		
EN 10283:1998	GX4CrNi13-4	1.4317		0.06	1.00	1.00	0.035	0.025	12.00-13.50	3.50-5.00	0.70	
JIS G 5121:2003	SCS 5			0.06	1.00	1.00	0.040	0.040	11.50-14.00	3.50-4.50		
ISO 11972:1998	GX 4CrNi 12 4			0.06	1.5	1.0	0.035	0.025	11.5-13.0	3.5-5.0	1.0	
BS 3100:1991 AMD.1:1992	425C11			0.10	1.0	1.0	0.040	0.030	11.5-13.5	3.4-4.2	0.60	
JIS G 5121:2003	SCS 6			0.06	1.00	1.00	0.040	0.030	11.50-14.00	3.50-4.50	0.40-1.00	
BS 3100:1991 AMD.1:1992	425C12			0.06	1.0	1.0	0.040	0.030	11.5-14.0	3.5-4.5	0.40-1.0	
ASTM A 743/A 743M-03	CA6NM		J91540	0.06	1.00	1.00	0.04	0.03	11.5-14.0	3.5-4.5	0.4-1.0	
EN 10283:1998	GX4CrNiMo16-5-1	1.4405		0.06	1.00	0.80	0.035	0.025	15.00-17.00	4.00-6.00	0.70-1.50	
ISO 11972:1998	GX 4 CrNiMo 16 5 1			0.06	0.8	0.8	0.035	0.025	15.0-17.0	4.0-6.0	0.7-1.5	
AFNOR NF A 32-054:1994	GX4CrNi16-4			0.06	1.00	0.80	0.020	0.035	15.50-17.00	4.00-5.50		

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.1B Mechanical Properties of Martensitic and Ferritic Stainless Steels for General and Corrosion Resistant Applications

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elengation	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	Other
JIS G 5121:2003	SCS 1			T1			345		540		18	163-229 HB
BS 3100:1991 AMD.1:1992	410C21			AHT or OQT			370		540		15	
ASTM A 743/A 743M-03	CA15		J91150	A or NT			450	65	620	90	18	
JIS G 5121:2003	SCS 1			T2			450		620		16	179-241 HB
BS 3100:1991 AMD.1:1992	420C28			AHT or OQT			450		620		13	
EN 10283:1998	GX12Cr12	1.4011		QT	≤ 150		450		620		15	20 J at RT
ISO 11972:1998	GX 12 Cr 12			NT	≤ 150		450		620		14	20 J at RT
BS 3100:1991 AMD.1:1992	420C29			AHT or OQT			465		690		11	
JIS G 5121:2003	SCS 3			T			440		590		16	170-235 HB
EN 10283:1998	GX7CrNiMo12-1	1.4008		QT	≤ 300		440		590		15	27 J at RT
ISO 11972:1998	GX 8 CrNiMo 12 1			NT	≤ 300		440		590		15	27 J at RT
ASTM A 743/A 743M-03	CA15M		J91151	A or NT			450	65	620	90	18	
UO O 5404 0000	SCS 2			Т			390		590		16	170-235 HB
JIS G 5121:2003	SCS 2A			Т			485		690		15	269 HB max
ASTM A 743/A 743M-03	CA40		J91153	A or NT			485	70	690	100	15	
AFNOR NF A 32-053:1992	Z 3CN13.4-M			Q+T1+T2	≤ 300		500		700		20	27 J at -120°C
AFNOR NF A 32-054:1994	GX4CrNi13-4			OTO	28 ≤ t < 100		500		700		18	60 J at RT
AFNOR NF A 32-054: 1994	GX4CINI13-4			QT3	100 ≤ t < 200		500		700		16	60 J at RT
EN 10283:1998	GX4CrNi13-4	1.4317		QT3	≤ 300		500		700		16	50 J at RT
JIS G 5121:2003	SCS 5			QT			540		740		13	217-277 HB
AFNOR NF A 32-054:1994	GX4CrNi13-4			QT2	28 ≤ t < 200		550		750		15	50 J at RT
ISO 11972:1998	GX 4CrNi 12 4			QT1	≤ 300		550		750		15	45 J at RT
EN 10283:1998	GX4CrNi13-4	1.4317		QT1	≤ 300		550		760		15	50 J at RT
BS 3100:1991 AMD.1:1992	425C11			AHT or OQT			620		770		12	30 J at 20°C
AFNOR NF A 32-054:1994	GX4CrNi13-4			QT1	28 ≤ t < 200		800		900		12	35 J at RT
EN 10283:1998	GX4CrNi13-4	1.4317		QT2	≤ 300		830		900		12	35 J at RT
ISO 11972:1998	GX 4CrNi 12 4			QT2	≤ 300		830		900		12	35 J at RT
JIS G 5121:2003	SCS 6			Т			550		750		15	285 HB max
BS 3100:1991 AMD.1:1992	425C12			AHT or OQT			550		755		15	
ASTM A 743/A 743M-03	CA6NM		J91540	NT			550	80	755	110	15	
EN 10283:1998	GX4CrNiMo16-5-1	1.4405		QT	≤ 300		540		760		15	60 J at RT
ISO 11972:1998	GX 4 CrNiMo 16 5 1			NT	≤ 300		540		760		15	60 J at RT
AENOD NE A 00 0544004	OV40-NE40-4			QT2 (TR2)	28 ≤ t < 250		540		780		15	60 J at RT
AFNOR NF A 32-054:1994	GX4CrNi16-4			QT1 (TR1)	28 ≤ t < 250		830		1000		10	30 J at RT

Chapter 7

7.4 Cast Stainless Steels

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.2A Chemical Composition of Austenitic Stainless Steels for General and Corrosion Resistant Applications

Standard	Grade, Class, Type,	Steel	UNS					Weight, 9	%, max, Unle	ss Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5121:2003	SCS 12			0.20	2.00	2.00	0.040	0.040	18.00-21.00	8.00-11.00		
ASTM A 743/A 743M-03	CF20		J92602	0.20	1.50	2.00	0.04	0.04	18.0-21.0	8.0-11.0		
AFNOR NF A 32-053:1992	Z 5CN19.10-M			0.07	2.00	2.00	0.035	0.025	18.0-21.0	8.0-12.0	0.50	
EN 10283:1998	GX5CrNi19-10	1.4308		0.07	1.50	1.50	0.040	0.030	18.00-20.00	8.00-11.00		
ISO 11972:1998	GX 5 CrNi 19 9			0.07	1.5	1.5	0.040	0.030	18.0-21.0	8.0-11.0		
US C 5101:0000	SCS 13			0.08	2.00	2.00	0.040	0.040	18.00-21.00	8.00-11.00		
JIS G 5121:2003	SCS 13A			0.08	1.50	2.00	0.040	0.040	18.00-21.00	8.00-11.00		
DC 0400-4004 AMD 4-4000	304C15			0.08	2.0	1.5	0.040	0.040	18.0-21.0	8.0-11.0		
BS 3100:1991 AMD.1:1992	304C15LT196			0.08	2.0	1.5	0.040	0.040	18.0-21.0	8.0-11.0		
ASTM A 743/A 743M-03	CF8		J92600	0.08	1.50	2.00	0.04	0.04	18.0-21.0	8.0-11.0		
ASTM A 744/A 744M-00	CF8		J92600	0.08	1.50	2.0	0.04	0.04	18.0-21.0	8.0-11.0		
JIS G 5121:2003	SCS 19			0.03	2.00	2.00	0.040	0.040	17.00-21.00	8.00-12.00		
DO 0400 4004 AMD 4.4000	304C12			0.03	2.0	1.5	0.040	0.040	17.0-21.0	8.0-12.0		
BS 3100:1991 AMD.1:1992	304C12LT196			0.03	2.0	1.5	0.040	0.040	17.0-21.0	8.0-12.0		
EN 10283:1998	GX2CrNi19-11	1.4309		0.030	2.00	1.50	0.035	0.025	18.00-20.00	9.00-12.00		N 0.20
ISO 11972:1998	GX 2 CrNi 18 10			0.03	1.5	1.5	0.040	0.030	17.0-19.0	9.0-12.0		
JIS G 5121:2003	SCS 19A			0.03	1.50	2.00	0.040	0.040	17.00-21.00	8.00-12.00		
ASTM A 743/A 743M-03	CF3		J92500	0.03	1.50	2.00	0.04	0.04	17.0-21.0	8.0-12.0		
ASTM A 744/A 744M-00	CF3		J92500	0.03	1.50	2.0	0.04	0.04	17.0-21.0	8.0-12.0		
EN 10283:1998	GX5CrNiNb19-11	1.4552		0.07	1.50	1.50	0.040	0.030	18.00-20.00	9.00-12.00		Nb 8 x C to 1.00
ISO 11972:1998	GX 6 CrNiNb 19 10			0.08	1.5	1.5	0.040	0.030	18.0-21.0	9.0-12.0		Nb 8 x C to 1.00
JIS G 5121:2003	SCS 21			0.08	2.00	2.00	0.040	0.040	18.00-21.00	9.00-12.00		Nb 10 x C to 1.35
BS 3100:1991 AMD.1:1992	347C17			0.08	2.0	1.5	0.040	0.040	18.0-21.0	9.0-12.0		Nb 8 x C to 1.0
ASTM A 743/A 743M-03	CF8C		J92710	0.08	1.50	2.00	0.04	0.04	18.0-21.0	9.0-12.0		Cb 8 x C to 1.0
ASTM A 744/A 744M-00	CF8C		J92710	0.08	1.50	2.0	0.04	0.04	18.0-21.0	9.0-12.0		Cb 8 x C to 1.0
EN 10283:1998	GX5CrNiMo19-11-2	1.4408		0.07	1.50	1.50	0.040	0.030	18.00-20.00	9.00-12.00	2.00-2.50	
100 11070-1000	GX 5 CrNiMo 19 11 2			0.07	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	2.0-2.5	
ISO 11972:1998	GX 5 CrNiMo 19 11 3			0.07	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	3.0-3.5	
UC C 5404-0000	SCS 14			0.08	2.00	2.00	0.040	0.040	17.00-20.00	10.00-14.00	2.00-3.00	
JIS G 5121:2003	SCS 14A			0.08	1.50	1.50	0.040	0.040	18.00-21.00	9.00-12.00	2.00-3.00	
DO 0400 4004 AMD 4.4000	316C16			0.08	2.0	1.5	0.040	0.040	17.0-21.0	9.0 min	2.0-3.0	
BS 3100:1991 AMD.1:1992	316C16LT196			0.08	2.0	1.5	0.040	0.040	17.0-21.0	9.0 min	2.0-3.0	
ASTM A 743/A 743M-03	CF8M		J92900	0.08	1.50	2.00	0.04	0.04	18.0-21.0	9.0-12.0	2.0-3.0	
ASTM A 744/A 744M-00	CF8M		J92900	0.08	1.50	2.0	0.04	0.04	18.0-21.0	9.0-12.0	2.0-3.0	

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.2A Chemical Composition of Austenitic Stainless Steels for General and Corrosion Resistant Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weight	, %, max, Uni	ess Otherwis	se Specifie	d
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5121:2003	SCS 22			0.08	2.00	2.00	0.040	0.040	17.00-20.00	10.00-14.00	2.00-3.00	Nb 10 x C to 1.35
EN 10283:1998	GX5CrNiMoNb19-11-2	1.4581		0.07	1.50	1.50	0.040	0.030	18.00-20.00	9.00-12.00	2.00-2.50	Nb 8 x C to 1.00
ISO 11972:1998	GX 6 CrNiMoNb 19 11 2			0.08	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	2.0-2.5	Nb 8 x C to 1.00
BS 3100:1991 AMD.1:1992	318C17			0.08	2.0	1.5	0.040	0.040	17.0-21.0	9.0 min	2.0-3.0	Nb 8 x C to 1.0
BS 3100:1991 AMD.1:1992	316C12			0.03	2.0	1.5	0.040	0.040	17.0-21.0	9.0 min	2.0-3.0	
BS 3100:1991 AMD.1:1992	316C12LT196			0.03	2.0	1.5	0.040	0.040	17.0-21.0	9.0 min	2.0-3.0	
EN 10283:1998	GX2CrNiMo19-11-2	1.4409		0.030	2.00	1.50	0.035	0.025	18.00-20.00	9.00-12.00	2.00-2.50	N 0.20
ISO 11972:1998	GX 2 CrNiMo 19 11 2			0.03	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	2.0-2.5	
JIS G 5121:2003	SCS 16 A			0.03	1.50	1.50	0.040	0.040	17.00-21.00	9.00-13.00	2.00-3.00	
ASTM A 743/A 743M-03	CF3M			0.03	1.50	1.50	0.04	0.04	17.0-21.0	9.0-13.0	2.0-3.0	
ASTM A 744/A 744M-00	CF3M		J92800	0.03	1.50	1.50	0.04	0.04	17.0-21.0	9.0-13.0	2.0-3.0	
EN 10283:1998	GX2CrNiMoN17-13-4	1.4446		0.030	1.50	1.00	0.040	0.030	16.50-18.50	12.50-14.50	4.00-4.50	N 0.12-0.22
ISO 11972:1998	GX 2 CrNiMoN 19 11 2			0.03	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	2.0-2.5	N 0.10-0.20
130 11972.1990	GX 2 CrNiMoN 19 11 3			0.03	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	3.0-3.5	N 0.10-0.20
ASTM A 743/A 743M-03	CF3MN			0.03	1.50	1.50	0.040	0.040	17.0-22.0	9.0-13.0	2.0-3.0	N 0.10-0.20
EN 10283:1998	GX5CrNiMo19-11-3	1.4412		0.07	1.50	1.50	0.040	0.030	18.00-20.00	10.00-13.00	3.00-3.50	
BS 3100:1991 AMD.1:1992	317C16			0.08	2.0	1.5	0.040	0.040	17.0-21.0	9.0 min	3.0-4.0	
ASTM A 743/A 743M-03	CG8M		J93000	0.08	1.50	1.50	0.04	0.04	18.0-21.0	9.0-13.0	3.0-4.0	
ASTM A 744/A 744M-00	CG8M		J93000	0.08	1.50	1.50	0.04	0.04	18.0-21.0	9.0-13.0	3.0-4.0	
ISO 11972:1998	GX 2 CrNiMo 19 11 3			0.03	1.5	1.5	0.040	0.030	17.0-20.0	9.0-12.0	3.0-3.5	
ASTM A 743/A 743M-03	CG3M		J92999	0.03	1.50	1.50	0.04	0.04	18.0-21.0	9.0-13.0	3.0-4.0	
ASTM A 744/A 744M-00	CG3M		J92999	0.03	1.50	1.50	0.04	0.04	18.0-21.0	9.0-13.0	3.0-4.0	
JIS G 5121:2003	SCS 17			0.20	2.00	2.00	0.040	0.040	22.00-26.00	12.00-15.00		
ASTM A 743/A 743M-03	CH20		J93402	0.20	1.50	2.00	0.04	0.04	22.0-26.0	12.0-15.0		
JIS G 5121:2003	SCS 23			0.07	2.00	2.00	0.040	0.040	19.00-22.00	27.50-30.00	2.00-3.00	Cu 3.00-4.00
ASTM A 743/A 743M-03	CN7M			0.07	1.50	1.50	0.04	0.04	19.0-22.0	27.5-30.5	2.0-3.0	Cu 3.0-4.0
ASTM A 744/A 744M-00	CN7M		N08007	0.07	1.50	1.50	0.04	0.04	19.0-22.0	27.5-30.5	2.0-3.0	Cu 3.0-4.0
BS 3100:1991 AMD.1:1992	332C11			0.07	1.5	1.5	0.040	0.040	19.0-22.0	27.5-30.5	2.0-3.0	Cu 3.0-4.0
EN 10283:1998	GX2NiCrMo28-20-2	1.4458		0.030	2.00	1.00	0.035	0.025	19.00-22.00	26.00-30.00	2.00-2.50	Cu 2.00; N 0.20
EN 10203:1990	GX4NiCrCuMo30-20-4	1.4527		0.06	1.50	1.50	0.040	0.030	19.00-22.00	27.50-30.50	2.00-3.00	Cu 3.00-4.00
EN 10283:1998	GX2NiCrMoN25-20-5	1.4416		0.030	1.00	1.00	0.035	0.020	19.00-21.00	24.00-26.00	4.50-5.50	N 0.12-0.20
ASTM A 743/A 743M-03	CN3M		J94652	0.03	1.0	2.0	0.03	0.03	20.0-22.0	23.00-27.00	4.5-5.5	

343

7.4 Cast Stainless Steels

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.2A Chemical Composition of Austenitic Stainless Steels for General and Corrosion Resistant Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Weight, %, max, Unless Otherwise Specified									
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others	
EN 10283:1998	GX2NiCrMoCuN25-20-6	1.4588		0.025	2.00	1.00	0.035	0.020	19.00-21.00	24.00-26.00	6.00-7.00	Cu 0.50-1.50; N 0.10-0.25	
ASTM A 743/A 743M-03	CN3MN			0.03	2.00	1.00	0.040	0.010	20.0-22.0	23.50-25.50	6.00-7.00	Cu 0.75; N 0.18-0.26	
ASTM A 744/A 744M-00	CN3MN		J94651	0.03	2.00	1.00	0.040	0.010	20.0-22.0	23.5-25.5	6.00-7.00	Cu 0.75; N 0.18-0.26	
EN 10283:1998	GX2CrNiMoCuN20-18-6	1.4593		0.025	1.20	1.00	0.030	0.010	19.50-20.50	17.50-19.50	6.00-7.00	Cu 0.50-1.00; N 0.18-0.24	
ASTM A 743/A 743M-03	CK3MCuN			0.025	1.20	1.00	0.045	0.010	19.5-20.5	17.5-19.5	6.0-7.0	Cu 0.50-1.00; N 0.180-0.240	
ASTM A 744/A 744M-00	CK3MCuN		J93254	0.025	1.20	1.00	0.045	0.010	19.5-20.5	17.5-19.5	6.0-7.0	Cu 0.50-1.00; N 0.180-0.240	
ISO 11972:1998	GX 2 CrNiCuMoN 26 5 3 3			0.03	1.5	1.0	0.035	0.025	25.0-27.0	4.5-6.5	2.5-3.5	Cu 2.5-3.5; N 0.12-0.25	
BS 3100:1991 AMD.1:1992	332C13			0.04	1.0	1.0	0.040	0.040	24.5-26.5	4.75-6.0	1.75-2.25	Cu 2.75-3.25	
BS 3100:1991 AMD.1:1992	332C15			0.08	1.5	1.5	0.040	0.040	21.0-27.0	4.0-7.0	1.75-3.0	N 0.10-0.25	
ISO 11972:1998	GX 2 CrNiMoN 26 5 3			0.03	1.5	1.0	0.035	0.025	25.0-27.0	4.5-6.5	2.5-3.5	N 0.12-0.25	

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.2B Mechanical Properties of Austenitic Stainless Steels for General and Corrosion Resistant Applications

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 5121:2003	SCS 12			S			205		480		28	183 HB max
ASTM A 743/A 743M-03	CF20		J92602	S			205	30	485	70	30	
AFNOR NF A 32-053:1992	Z 5CN19.10-M			Q (HY)	≤ 300		200		440		30	60 J at -196°C
EN 10283:1998	GX5CrNi19-10	1.4308		AT	≤ 150		175		440		30	60 J at RT
ISO 11972:1998	GX 5 CrNi 19 9			ST/Q	≤ 150		180		440		30	60 J at RT
UC C 5101:0000	SCS 13			S			185		440		30	183 HB max
JIS G 5121:2003	SCS 13A			S			205		480		33	183 HB max
BS 3100:1991 AMD.1:1992	304C15			ST			215		480		26	
65 3100:1991 AMD.1:1992	304C15LT196			ST			215		480		26	41 J at -196°C
ASTM A 743/A 743M-03	CF8		J92600	S			205	30	485	70	35	
ASTM A 744/A 744M-00	CF8		J92600	S			205	30	485	70	35	
JIS G 5121:2003	SCS 19			S			185		390		33	183 HB max
BS 3100:1991 AMD.1:1992	304C12			ST			215		430		26	
BS 3100:1991 AMD.1:1992	304C12LT196			ST			215		430		26	41 J at -196°C
EN 10283:1998	GX2CrNi19-11	1.4309		AT	≤ 150		185		440		30	80 J at RT
ISO 11972:1998	GX 2 CrNi 18 10			ST/Q	≤ 150		180		440		30	80 J at RT
JIS G 5121:2003	SCS 19A			S			205		480		33	183 HB max
ASTM A 743/A 743M-03	CF3		J92500	S			205	30	485	70	35	
ASTM A 744/A 744M-00	CF3		J92500	S			205	30	485	70	35	
EN 10283:1998	GX5CrNiNb19-11	1.4552		AT	≤ 150		175		440		25	40 J at RT
ISO 11972:1998	GX 6 CrNiNb 19 10			ST/Q	≤ 150		180		440		25	40 J at RT
JIS G 5121:2003	SCS 21			S			205		480		28	183 HB max
BS 3100:1991 AMD.1:1992	347C17			ST			215		480		22	
ASTM A 743/A 743M-03	CF8C		J92710	S			205	30	485	70	30	
ASTM A 744/A 744M-00	CF8C		J92710	S			205	30	485	70	30	

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.2B Mechanical Properties of Austenitic Stainless Steels for General and Corrosion Resistant Applications (Continued)

Standard Designation	Grade, Class, Type,	Steel	UNS	Form/Heat	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation, min, %	
	Symbol or Name	Number	Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi		Other
EN 10283:1998	GX5CrNiMo19-11-2	1.4408		AT	≤ 150		185		440		30	60 J ar RT
ISO 11972:1998	GX 5 CrNiMo 19 11 2			ST/Q	≤ 150		180		440		30	60 J at RT
130 11972.1996	GX 5 CrNiMo 19 11 3			ST/Q	≤ 150		180		440		30	60 J at RT
JIS G 5121:2003	SCS 14			S			185		440		28	183 HB max
313 G 3121.2003	SCS 14A			S			205		480		33	183 HB max
BS 3100:1991 AMD.1:1992	316C16			ST			240		480		26	
BS 3100.1991 AMD.1.1992	316C16LT196			ST			240		480		26	41 J at -196°C
ASTM A 743/A 743M-03	CF8M		J92900	S			205	30	485	70	30	
ASTM A 744/A 744M-00	CF8M		J92900	S			205	30	485	70	30	
JIS G 5121:2003	SCS 22			S			205		440		28	183 HB max
EN 10283:1998	GX5CrNiMoNb19-11-2	1.4581		AT	≤ 150		185		440		25	40 J ar RT
ISO 11972:1998	GX 6 CrNiMoNb 19 11 2			ST/Q	≤ 150		180		440		25	40 J at RT
BS 3100:1991 AMD.1:1992	318C17			ST			240		480		18	
BS 3100:1991 AMD.1:1992	316C12			ST			215		430		26	
BS 3100:1991 AMD.1:1992	316C12LT196			ST				240	480	26		41 J at - 196°C
EN 10283:1998	GX2CrNiMo19-11-2	1.4409		AT	≤ 150		195		440		30	80 J at RT
ISO 11972:1998	GX 2 CrNiMo 19 11 2			ST/Q	≤ 150		180		440		30	80 J at RT
JIS G 5121:2003	SCS 16 A			S			205		480		33	183 HB max
ASTM A 743/A 743M-03	CF3M			S			205	30	485	70	30	
ASTM A 744/A 744M-00	CF3M		J92800	S			205	30	485	70	30	
EN 10283:1998	GX2CrNiMoN17-13-4	1.4446		AT	≤ 150		210		440		20	50 J at RT
100 11070:1000	GX 2 CrNiMoN 19 11 2			ST/Q	≤ 150		230		510		30	80 J at RT
ISO 11972:1998	GX 2 CrNiMoN 19 11 3			ST/Q	≤ 150		230		510		30	80 J at RT
ASTM A 743/A 743M-03	CF3MN			S			255	37	515	75	35	
EN 10283:1998	GX5CrNiMo19-11-3	1.4412		AT	≤ 150		205		440		30	60 J at RT
BS 3100:1991 AMD.1:1992	317C16			ST			240		480		22	
ASTM A 743/A 743M-03	CG8M		J93000	S			240	35	520	75	25	
ASTM A 744/A 744M-00	CG8M		J93000	S			240	35	520	75	25	

7.4.1 Cast Stainless Steels for General and Corrosion Resistant Applications

7.4.1.2B Mechanical Properties of Austenitic Stainless Steels for General and Corrosion Resistant Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS Number	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	
Designation		Number		Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
ISO 11972:1998	GX 2 CrNiMo 19 11 3			ST/Q	≤ 150		180		440		30	80 J at RT
ASTM A 743/A 743M-03	CG3M		J92999	S			240	35	515	75	25	
ASTM A 744/A 744M-00	CG3M		J92999	S			240	35	515	75	25	
JIS G 5121:2003	SCS 17			S			205		480		28	183 HB max
ASTM A 743/A 743M-03	CH20		J93402	S			205	30	485	70	30	
JIS G 5121:2003	SCS 23			S			165		390		30	183 HB max
ASTM A 743/A 743M-03	CN7M			S			170	25	425	62	35	
ASTM A 744/A 744M-00	CN7M		N08007	S			170	25	425	62	35	
BS 3100:1991 AMD.1:1992	332C11			ST			170		425		34	
EN 10000-1000	GX2NiCrMo28-20-2	1.4458		AT	≤ 150		165		430		30	60 J at RT
EN 10283:1998	GX4NiCrCuMo30-20-4	1.4572					170		430		35	60 J at RT
EN 10283:1998	GX2NiCrMoN25-20-5	1.4416		AT	≤ 150		185		450		30	60 J at RT
ASTM A 743/A 743M-03	CN3M		J94652	S			260	38	550	80	35	
EN 10283:1998	GX2NiCrMoCuN25-20-6	1.4588		AT	≤ 50		210		480		30	60 J at RT
ASTM A 743/A 743M-03	CN3MN			S			260	38	550	80	35	
ASTM A 744/A 744M-00	CN3MN		J94651	S			260	38	550	80	35	
EN 10283:1998	GX2CrNiMoCuN20-18-6	1.4593		AT	≤ 50		260		500		35	50 J at RT
ASTM A 743/A 743M-03	CK3MCuN			S			260	38	550	80	35	
ASTM A 744/A 744M-00	CK3MCuN		J93254	S			260	38	550	80	35	
ISO 11972:1998	GX 2 CrNiCuMoN 26 5 3 3			ST/Q	≤ 150		450		650		18	50 J at RT
BS 3100:1991 AMD.1:1992	332C13			ST			485		690		16	25 J at 20°C
BS 3100:1991 AMD.1:1992	332C15			ST			430		640		30	25 J at 20°C
ISO 11972:1998	GX 2 CrNiMoN 26 5 3			ST/Q	≤ 150		450		650		18	50 J at RT

7.4.2 Cast Stainless Steels for Pressure Purposes

7.4.2.1A Chemical Composition of Martensitic and Ferritic Stainless Steels for Pressure Purposes

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %,	max, Unles	s Otherwis	e Specified	I
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 217/A 217M-02	CA15		J91150	0.15	1.00	1.50	0.040	0.040	11.5-14.0	1.00	0.50	
ASTM A 487/A 487M-93 (2003)	CA15		J91171	0.15	1.00	1.50	0.040	0.040	11.5-14.0	1.00	0.50	Cu 0.50; W 0.10; V 0.05 Cu+W+V 0.50
EN 10213-2:1995	GX8CrNi12	1.4107		0.10	0.50-0.80	0.40	0.030	0.020	11.50-12.50	0.80-1.50	0.50	
ISO 4991:1994	C39CH			0.10-0.17	1.00	0.8	0.035	0.035	11.5-13.5	1.0	0.5	
150 4991.1994	C39CNiH			0.05-0.10	0.40-0.80	0.80	0.035	0.035	11.5-13.0	0.80-1.80	0.20-0.50	
EN 10213-2:1995	GX4CrNi13-4	1.4317		0.06	1.00	1.00	0.035	0.025	12.00-13.50	3.50-5.00	0.70	
EN 10213-3:1995	GX3CrNi13-4	1.6982		0.05	1.00	1.00	0.035	0.015	12.00-13.50	3.50-5.00	0.70	
ISO 4991:1994	C39NiH			0.08	1.50	1.00	0.035	0.035	11.5-13.5	3.50-5.00	1.00	
150 4991.1994	C39NiL			0.08	1.50	1.00	0.030	0.030	11.5-13.5	3.50-5.00	1.00	
ASTM A 352/A 352M-03	CA6NM		J91540	0.06	1.00	1.00	0.04	0.03	11.5-14.0	3.5-4.5	0.4-1.0	
ASTM A 487/A 487M-93 (2003)	CA6NM		J91540	0.06	1.00	1.00	0.04	0.03	11.5-14.0	3.5-4.5	0.4-1.0	Cu 0.50; W 0.10; V 0.05; Cu+W+V 0.50
ASTM A 757/A 757M-00	E3N		J91550	0.06	1.00	1.00	0.030	0.030	11.5-14.0	3.5-4.5	0.4-1.0	Cu 0.50; W 0.10; P+S+Cu+W 0.50
EN 10213-2:1995	GX23CrMoV12-1	1.4931		0.20-0.26	0.50-0.80	0.40	0.030	0.020	11.30-12.20	1.00	1.00-1.20	V 0.25-0.35; W 0.50
ISO 4991:1994	C40H			0.20-0.26	0.50-0.70	0.20-0.40	0.035	0.035	11.3-12.3	0.70-1.00	1.00-1.20	V 0.25-0.35

7.4.2 Cast Stainless Steels for Pressure Purposes

7.4.2.1B Mechanical Properties of Martensitic and Ferritic Stainless Steels for Pressure Purposes

Standard	Grade, Class, Type,	Steel	UNS	Product Form/Heat Treatment	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation, min, %	Other		
Designation	Symbol or Name	Number	Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi				
ASTM A 217/A 217M-02	CA15		J91150	NT			450	65	620-795	90-115	18			
	CA15, Class A		J91171	NT or QT			760-895	110-130	965-1170	140-170	10			
	CA15, Class B		J91171	NT or QT			450	65	620-795	90-115	18			
ASTM A 487/A 487M-93 (2003)	CA15, Class C		J91171	NT or QT			415	60	620	90	18	22 HRC max 235 HB max		
	CA15, Class D		J91171	NT or QT			515	75	690	100	17	22 HRC max 235 HB max		
EN 10213-2:1995	CV0CrNi10	CV0C*Ni10	GX8CrNi12	1.4107		QT1	≤ 300		355		540-690		18	45 J at RT
EN 10213-2.1995	GAOGINITZ	1.4107		QT2	≤ 300		500		600-800		16	40 J at RT		
ISO 4991:1994	C39CH			NT			450		620-770		14	20 J at RT		
130 4991.1994	C39CNiH			NT			360		540-690		18	35 J at RT		
EN 10213-2:1995	GX4CrNi13-4	1.4317		QT	≤ 300		550		760-960		15	50 J at RT		
EN 10213-3:1995	GX3CrNi13-4	1.6982		QT	≤ 300		500		700-900		15	27 J at -120°C		
ISO 4991:1994	C39NiH			NT			550		750-900		15	45 J at RT		
130 4991.1994	C39NiL			N _{ac} T or (NT)			550		750-900		15	27 J at -80°C		
ASTM A 352/A 352M-03	CA6NM		J91540	NT			550	80	760-930	110.0-135.0	15	27 J at -73°C		
	CA6NM, Class A		J91540	NT or QT			550	80	760-930	110-135	15			
ASTM A 487/A 487M-93 (2003)	CA6NM, Class B		J91540	NT or QT			515	75	690	100	17	23 HRC max 255 HB max		
ASTM A 757/A 757M-00	E3N		J91550	NT	≤ 32	11/4	550	80	760	110	15	27 J at -73°C		
EN 10213-2:1995	GX23CrMoV12-1	1.4931		QT	≤ 150		540		740-880		15	27 J at RT		
ISO 4991:1994	C40H			NT			540		740-880		15	21 J at RT		

7.4 Cast Stainless Steels

7.4.2 Cast Stainless Steels for Pressure Purposes

7.4.2.2A Chemical Composition of Austenitic Stainless Steels for Pressure Purposes

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %	6, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10213-4:1995	GX5CrNi19-10	1.4308		0.07	1.50	1.50	0.040	0.030	18.00-20.00	8.00-11.00		
ISO 4991:1994	C47			0.07	2.00	2.00	0.045	0.035	18.0-21.0	8.0-11.0		
130 4991.1994	C47L			0.07	2.00	2.00	0.045	0.035	17.0-20.0	9.0-12.0		
ASTM A 351/A 351M-03	CF-8, CF-8A		J92600	0.08	1.50	2.00	0.040	0.040	18.0-21.0	8.0-11.0	0.50	
EN 10213-4:1995	GX2CrNi19-11	1.4309		0.03	2.00	1.50	0.035	0.025	18.00-20.00	9.00-12.00		N 0.20
ISO 4991:1994	C46			0.03	2.00	2.00	0.045	0.035	17.0-19.0	9.0-12.0		
ASTM A 351/A 351M-03	CF-3, CF-3A		J92700	0.03	1.50	2.00	0.040	0.040	17.0-21.0	8.0-12.0	0.50	
EN 10213-4:1995	GX5CrNiNb19-11	1.4552		0.07	1.50	1.50	0.040	0.030	18.00-20.00	9.00-12.00		Nb 8 x C to 1.0
ISO 4991:1994	C50			0.08	2.00	2.00	0.045	0.035	18.0-21.0	9.0-12.0		Nb 8 x C to 1.0
ASTM A 351/A 351M-03	CF-8C		J92710	0.08	1.50	2.00	0.040	0.040	18.0-21.0	9.0-12.0	0.50	Cb 8 x C to 1.00
EN 10213-4:1995	GX5CrNiMo19-11-2	1.4408		0.07	1.50	1.50	0.040	0.030	18.00-20.00	9.00-12.00	2.00-2.50	
ISO 4991:1994	C60			0.07	2.00	2.00	0.045	0.035	17.0-21.0	9.0-13.0	2.0-2.5	
130 4991.1994	C61			0.07	2.00	2.00	0.045	0.035	17.0-21.0	9.0-13.0	2.5-3.0	
ASTM A 351/A 351M-03	CF-8M		J92900	0.08	1.50	1.50	0.040	0.040	18.0-21.0	9.0-12.0	2.0-3.0	
EN 10213-4:1995	GX5CrNiMoNb19-11-2	1.4581		0.07	1.50	1.50	0.040	0.030	18.00-20.00	9.00-12.00	2.00-2.50	Nb 8 x C to 1.0
ISO 4991:1994	C60Nb			0.08	2.00	2.00	0.045	0.035	17.0-21.0	9.0-13.0	2.0-2.5	Nb 8 x C to 1.0
ISO 4991:1994	C57			0.03	2.00	2.00	0.045	0.035	17.0-21.0	9.0-13.0	2.0-2.5	
130 4991.1994	C61LC			0.03	2.00	2.00	0.045	0.035	17.0-21.0	9.0-13.0	2.5-3.0	
EN 10213-4:1995	GX2CrNiMo19-11-2	1.4409		0.030	2.00	1.50	0.035	0.025	18.00-20.00	9.00-12.00	2.00-2.50	N 0.20
ASTM A 351/A 351M-03	CF-3M, CF-3MA		J92800	0.03	1.50	1.50	0.040	0.040	17.0-21.0	9.0-13.0	2.0-3.0	
ASTM A 351/A 351M-03	CN-7M		N08007	0.07	1.50	1.50	0.04	0.04	19.0-22.0	27.5-30.5	2.0-3.0	Cu 3.0-4.0
EN 10213-4:1995	GX2NiCrMo28-20-2	1.4458		0.030	2.00	1.00	0.035	0.025	19.00-22.00	26.00-30.00	2.00-2.50	Cu 2.00; N 0.20
EN 10213-4:1995	GX2CrNiMoCuN25-6-3-3	1.4517		0.030	1.50	1.00	0.035	0.025	24.50-26.50	5.00-7.00	2.50-3.50	Cu 2.75-3.50; N 0.12-0.22
ASTM A 351/A 351M-03	CD-4MCu		J93370	0.04	1.00	1.00	0.04	0.04	24.5-26.5	4.75-6.00	1.75-2.25	Cu 2.75-3.25

7.4 Cast Stainless Steels

7.4.2 Cast Stainless Steels for Pressure Purposes

7.4.2.2B Mechanical Properties of Austenitic Stainless Steels for Pressure Purposes

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Strei	ngth, min	Tensile St	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
EN 10213-4:1995	GX5CrNi19-10	1.4308		AT + QW	≤ 150		200		440-640		30	60 J at RT
ISO 4991:1994	C47			S			210		440-640		30	
150 4991:1994	C47L			S			210		440-640		30	45 J at -195°C
ASTM A 351/A 351M-03	CF-8		J92600	S			205	30	485	70	35.0	
AS I W A 35 I/A 35 I W - 03	CF-8A		J92600	S			240	35	530	77	35.0	
EN 10213-4:1995	GX2CrNi19-11	1.4309		AT + QW	≤ 150		210		440-640		30	80 J at RT
ISO 4991:1994	C46			S			210		440-640		30	
ASTM A 351/A 351M-03	CF-3		J92800	S			205	30	485	70	35.0	
AS TIVI A 35 T/A 35 TWI-03	CF-3A		J92800	S			240	35	530	77	35.0	
EN 10213-4:1995	GX5CrNiNb19-11	1.4552		AT + QW	≤ 150		200		440-640		25	40 J at RT
ISO 4991:1994	C50			S			210		440-640		25	
ASTM A 351/A 351M-03	CF-8C		J92710	S			205	30	485	70	30.0	
EN 10213-4:1995	GX5CrNiMo19-11-2	1.4408		AT + QW	≤ 150		210		440-640		30	60 J at RT
ISO 4991:1994	C60			S			210		440-640		30	
150 4991:1994	C61			S			210		440-640		30	
ASTM A 351/A 351M-03	CF-8M		J92900	S			205	30	485	70	30.0	
EN 10213-4:1995	GX5CrNiMoNb19-11-2	1.4581		AT + QW	≤ 150		210		440-640		25	40 J at RT
ISO 4991:1994	C60Nb			S			210		440-640		25	
ISO 4991:1994	C57			S			210		440-620		30	
150 4991:1994	C61LC			S			210		440-640		30	
EN 10213-4:1995	GX2CrNiMo19-11-2	1.4409		AT + QW	≤ 150		220		440-640		30	80 J at RT
ASTM A 351/A 351M-03	CF-3M		J92800	S			205	30	485	70	30.0	
ASTIVI A 351/A 351WI-03	CF-3MA		J92800	S			255	37	550	80	30.0	
ASTM A 351/A 351M-03	CN-7M		N08007	S			170	25	425	62	35.0	
EN 10213-4:1995	GX2NiCrMo28-20-2	1.4458		AT + QW	≤ 150		190		430-630		30	60 J at RT
EN 10213-4:1995	GX2CrNiMoCuN25-6-3-3	1.4517		AT + QW	≤ 150		480		650-850		22	50 J at RT
ASTM A 351/A 351M-03	CD-4MCu		J93370	S			485	70	690	100	16.0	

7.5A Chemical Composition of Cast Heat Resistant Steels

Standard	Grade, Class, Type,	Steel	UNS					Weight, %	6, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5122:2003	SCH 1			0.20-0.40	1.00	1.50-3.00	0.040	0.040	12.00-15.00	1.00	0.50	
JIS G 5122.2003	SCH 3			0.40	1.00	2.00	0.040	0.040	12.00-15.00	1.00	0.50	
BS 3100:1991 AMD.1:1992	420C24			0.25	1.0	2.0	0.050	0.050	12.0-16.0			
EN 10295:2002	GX40CrSi13	1.4729			1.00	1.00-2.50	0.040	0.030	12.00-14.00	1.00	0.50	
ISO 11973:1999	GX40CrSi13			0.3-0. 5	0.5-1.0	1.0-2.5	0.04	0.03	12-14	1	0.5	
EN 10295:2002	GX40CrSi17	1.4740		0.30-0.50	1.00	1.00-2.50	0.040	0.030	16.00-19.00	1.00	0.50	
ISO 11973:1999	GX40CrSi17			0.3-0.5	0.5-1.0	1.0-2.5	0.04	0.03	16-19	1	0.5	
EN 10295:2002	GX40CrSi24	1.4745		0.30-0.50	1.00	1.00-2.50	0.040	0.030	23.00-26.00	1.00	0.50	
ISO 11973:1999	GX40CrSi24			0.3-0.5	0.5-1.0	1.0-2.5	0.04	0.03	23-26	1	0.5	
EN 10295:2002	GX40CrSi28	1.4776		0.30-0.50	1.00	1.00-2.50	0.040	0.030	27.00-30.00	1.00	0.50	
ISO 11973:1999	GX40CrSi28			0.3-0.5	0.5-1.0	1.0-2.5	0.04	0.03	27-30	1	0.5	
EN 10295:2002	GX130CrSi29	1.4777		1.20-1.40	0.50-1.00	1.00-2.50	0.035	0.030	27.00-30.00	1.00	0.50	
ISO 11973:1999	GX130CrSi29			1.2-1.4	0.5-1.0	1.0-2.5	0.04	0.03	27-30	1	0.5	
JIS G 5122:2003	SCH 2			0.40	1.00	2.00	0.040	0.040	25.00-28.00	1.00	0.50	
ASTM A 297/A 297M-97 (2003)	HC		J92605	0.50	1.00	2.00	0.04	0.04	26.0-30.0	4.00	0.50	
ASTM A 608/A 608M-02	HC30		J92613	0.25-0.35	0.5-1.0	0.50-2.00	0.04	0.04	26-30	4.0	0.50	
BS 3100:1991 AMD.1:1992	452C11			1.0	1.0	2.0	0.050	0.050	25.0-30.0	4.0	1.5	
B3 3100.1991 AWD.1.1992	452C12			1.0-2.0	1.0	2.0	0.050	0.050	25.0-30.0	4.0	1.5	
ISO 11973:1999	GX40CrNiSi27-4			0.3-0.5	1.5	1.0-2.5	0.04	0.03	25-28	3-6	0.5	
ASTM A 297/A 297M-97 (2003)	HD		J93005	0.50	1.50	2.00	0.04	0.04	26.0-30.0	4.0-7.0	0.50	
JIS G 5122:2003	SCH 11			0.40	1.00	2.00	0.040	0.040	24.00-28.00	4.00-6.00	0.50	
ASTM A 608/A 608M-02	HD50		J93015	0.45-0.55	1.50	0.50-2.00	0.04	0.04	26-30	4-7	0.50	
EN 10295:2002	GX40CrNiSi27-4	1.4823		0.30-0.50	1.50	1.00-2.50	0.040	0.030	25.00-28.00	3.00-6.00	0.50	
JIS G 5122:2003	SCH 17			0.20-0.50	2.00	2.00	0.040	0.040	26.00-30.00	8.00-11.00	0.50	
ASTM A 297/A 297M-97 (2003)	HE		J93403	0.20-0.50	2.00	2.00	0.04	0.04	26.0-30.0	8.0-11.0	0.50	
ASTM A 608/A 608M-02	HE35		J93413	0.30-0.40	1.50	0.50-2.00	0.04	0.04	26-30	8-11	0.50	
BS 3100:1991 AMD.1:1992	309C40			0.5	2.0	2.0	0.050	0.050	25.0-30.0	8.0-12.0	1.5	
EN 10295:2002	GX25CrNiSi18-9	1.4825		0.15-0.35	2.00	0.50-2.50	0.040	0.030	17.00-19.00	8.00-10.00	0.50	
LN 10293.2002	GX40CrNiSi22-10	1.4826		0.30-0.50	2.00	1.00-2.50	0.040	0.030	21.00-23.00	9.00-11.00	0.50	
ISO 11973:1999	GX25CrNiSi18-9			0.15-0.35	2	1.0-2.5	0.04	0.03	17-19	8-10	0.5	
100 11970.1999	GX40CrNiSi22-10			0.3-0.5	2	1.0-2.5	0.04	0.03	21-23	9-11	0.5	
ASTM A 297/A 297M-97 (2003)	HF		J93603	0.20-0.40	2.00	2.00	0.04	0.04	18.0-23.0	8.0-12.0	0.50	
JIS G 5122:2003	SCH 12			0.20-0.40	2.00	2.00	0.040	0.040	18.00-23.00	8.00-12.00	0.50	
ASTM A 608/A 608M-02	HF30		J92803	0.25-0.35	1.50	0.50-2.00	0.04	0.04	19-23	9-12	0.50	
BS 3100:1991 AMD.1:1992	302C35			0.2-0.4	2.0	2.0	0.050	0.050	17.0-22.0	6.0-10.0	1.5	

7.5A Chemical Composition of Cast Heat Resistant Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weight, 9	%, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
EN 10295:2002	GX25CrNiSi20-14	1.4832		0.15-0.35	2.00	0.50-2.50	0.040	0.030	19.00-21.00	13.00-15.00	0.50	
ISO 11973:1999	GX25CrNiSi20-14			0.15-0.35	2	1.0-2.5	0.04	0.03	19-21	13-15	0.5	
EN 10295:2002	GX40CrNiSi25-12	1.4837		0.30-0.50	2.00	1.00-2.50	0.040	0.030	24.00-27.00	11.00-14.00	0.50	
ISO 11973:1999	GX40CrNiSi25-12			0.3-0.5	2	1.0-2.5	0.04	0.03	24-27	11-14	0.5	
JIS G 5122:2003	SCH 13			0.20-0.50	2.00	2.00	0.040	0.040	24.00-28.00	11.00-14.00	0.50	
313 G 3122.2003	SCH 13A			0.25-0.50	2.50	1.75	0.040	0.040	23.00-26.00	12.00-14.00	0.50	
BS 3100:1991 AMD.1:1992	309C35			0.20-0.50	2.0	1.5	0.040	0.040	24.0-28.0	11.0-14.0	1.5	
ASTM A 297/A 297M-97 (2003)	HH		J93503	0.20-0.50	2.00	2.00	0.04	0.04	24.0-28.0	11.0-14.0	0.50	
ASTM A 447/A 447M-93 (2003)	Type I		J93303	0.20-0.45	2.50	1.75	0.05	0.05	23.00-28.00	10.00-14.00		N 0.20
ASTM A 447/A 447M-93 (2003)	Type II		J93303	0.20-0.45	2.50	1.75	0.05	0.05	23.00-28.00	10.00-14.00		N 0.20
BS 3100:1991 AMD.1:1992	309C32			0.20-0.45	2.5	1.5	0.040	0.040	24.0-28.0	11.0-14.0	1.5	N 0.2
ASTM A 608/A 608M-02	HH30		J93513	0.25-0.35	1.50	0.50-2.00	0.04	0.04	24-28	11-14	0.50	
AS I W A 606/A 606W-02	HH33		J93633	0.28-0.38	1.50	0.50-2.00	0.04	0.04	24-26	12-14	0.50	
BS 3100:1991 AMD.1:1992	309C30			0.5	2.0	2.5	0.050	0.050	22.0-27.0	10.0-14.0	1.5	
ASTM A 297/A 297M-97 (2003)	HI		J94003	0.20-0.50	2.00	2.00	0.04	0.04	26.0-30.0	14.0-18.0	0.50	
ASTM A 608/A 608M-02	HI35		J94013	0.30-0.40	1.50	0.50-2.00	0.04	0.04	26-30	14-18	0.50	
JIS G 5122:2003	SCH 18			0.20-0.50	2.00	2.00	0.040	0.040	26.00-30.00	14.00-18.00	0.50	
JIS G 5122:12003	SCH 21			0.25-0.35	1.50	1.75	0.040	0.040	23.00-27.00	19.00-22.00	0.50	
ASTM A 297/A 297M-97 (2003)	HK		J94224	0.20-0.60	2.00	2.00	0.04	0.04	24.0-28.0	18.0-22.0	0.50	
ASTM A 351/A 351M-03	HK30		J94203	0.25-0.35	1.50	1.75	0.040	0.040	23.0-27.0	19.0-22.0	0.50	
ASTM A 608/A 608M-02	HK30		J94203	0.25-0.35	1.50	0.50-2.00	0.04	0.04	23-27	19-22	0.50	
ASTM A 351/A 351M-03	HK40		J94204	0.35-0.45	1.50	1.75	0.040	0.040	23.0-27.0	19.0-22.0	0.50	
EN 10295:2002	GX40CrNiSi25-20	1.4848		0.30-0.50	2.00	1.00-2.50	0.040	0.030	24.00-27.00	19.00-22.00	0.50	
JIS G 5122:2003	SCH 22			0.35-0.45	1.50	1.75	0.040	0.040	23.00-27.00	19.00-22.00	0.50	
BS 3100:1991 AMD.1:1992	310C40			0.30-0.5	2.0	1.5	0.040	0.040	24.0-27.0	19.0-22.0	1.5	
ISO 11973:1999	GX40CrNiSi25-20			0.3-0.5	2	1.0-2.5	0.04	0.03	24-27	19-22	0.5	
ASTM A 608/A 608M-02	HK40		J94204	0.35-0.45	1.50	0.50-2.00	0.04	0.04	23-27	19-22	0.50	
BS 3100:1991 AMD.1:1992	310C45			0.5	2.0	3.0	0.050	0.050	22.0-27.0	17.0-22.0	1.5	
ASTM A 297/A 297M-97 (2003)	HL		N08604	0.20-0.60	2.00	2.00	0.04	0.04	28.0-32.0	18.0-22.0	0.50	
ACTM A 600/A 600M 00	HL30		N08613	0.25-0.35	1.50	0.50-2.00	0.04	0.04	28-32	18-22	0.50	
ASTM A 608/A 608M-02	HL40		N08614	0.35-0.45	1.50	0.50-2.00	0.04	0.04	28-32	18-22	0.50	
JIS G 5122:2003	SCH 23			0.20-0.60	2.00	2.00	0.040	0.040	28.00-32.00	18.00-22.00	0.50	

7.5A Chemical Composition of Cast Heat Resistant Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weight, %	6, max, Unles	ss Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 5122:2003	SCH 19			0.20-0.50	2.00	2.00	0.040	0.040	19.00-23.00	23.00-27.00	0.50	
ASTM A 297/A 297M-97 (2003)	HN		J94213	0.20-0.50	2.00	2.00	0.04	0.04	19.0-23.0	23.0-27.0	0.50	
ASTM A 608/A 608M-02	HN40		J94214	0.35-0.45	1.50	0.50-2.00	0.04	0.04	19-23	23-27	0.50	
EN 10295:2002	GX35NiCrSi25-21	1.4805		0.20-0.50	2.00	1.00-2.00	0.040	0.030	19.00-23.00	23.00-27.00	0.50	
BS 3100:1991 AMD.1:1992	311C11			0.5	2.0	3.0	0.050	0.050	17.0-23.0	23.0-28.0	1.5	
EN 10295:2002	GX40CrNiSiNb24-24	1.4855		0.30-0.50	2.00	1.00-2.50	0.040	0.030	23.00-25.00	23.00-25.00	0.50	Nb 0.80-1.80
ISO 11973:1999	GX40CrNiSiNb24-24			0.25-0.50	2	1.0-2.5	0.04	0.03	23-25	23-25	0.5	Nb 1.2-1.8
EN 10295:2002	GX40NiCrSiNb35-26	1.4852		0.30-0.50	2.00	1.00-2.50	0.040	0.030	24.00-27.00	33.00-36.00	0.50	Nb 0.80-1.80
ASTM A 297/A 297M-97 (2003)	HP		N08705	0.35-0.75	2.00	2.50	0.04	0.04	24-28	33-37	0.50	
JIS G 5122:2003	SCH 24			0.35-0.75	2.00	2.00	0.040	0.040	24.00-28.00	33.00-37.00	0.50	
EN 10295:2002	GX40NiCrSi35-26	1.4857		0.30-0.50	2.00	1.00-2.50	0.040	0.030	24.00-27.00	33.00-36.00	0.50	
ISO 11973:1999	GX40NiCrSi35-26			0.3-0.5	2	1.0-2.5	0.04	0.03	24-27	33-36	0.5	
130 11973.1999	GX40NiCrSiNb35-26			0.3-0.5	2	1.0-2.5	0.04	0.03	24-27	33-36	0.5	Nb 0.8-1.8
EN 10295:2002	GX40NiCrSi35-17	1.4806		0.30-0.50	2.00	1.00-2.50	0.040	0.030	16.00-18.00	34.00-36.00	0.50	
ISO 11973:1999	GX40NiCrSi35-17			0.3-0.5	2	1.0-2.5	0.04	0.03	16-18	34-36	0.5	
JIS G 5122:2003	SCH 15			0.35-0.70	2.00	2.50	0.040	0.040	15.00-19.00	33.00-37.00	0.50	
ASTM A 297/A 297M-97 (2003)	HT		N08605	0.35-0.75	2.00	2.50	0.04	0.04	15.0-19.0	33.0-37.0	0.50	
ASTM A 608/A 608M-02	HT50		N08050	0.40-0.60	1.50	0.50-2.00	0.04	0.04	15-19	33-37	0.50	
BS 3100:1991 AMD.1:1992	330C12			0.75	2.0	3.0	0.050	0.050	13.0-20.0	30.0-40.0	1.5	
JIS G 5122:2003	SCH 16			0.20-0.35	2.00	2.50	0.040	0.040	13.00-17.00	33.00-37.00	0.50	
BS 3100:1991 AMD.1:1992	330C11			0.35-0.55	2.0	1.5	0.040	0.040	13.0-17.0	33.0-37.0	1.5	
ASTM A 351/A 351M-03	HT30		N08603	0.25-0.35	2.00	2.50	0.040	0.040	13.0-17.0	33.0-37.0	0.50	
JIS G 5122:2003	SCH 20			0.35-0.75	2.00	2.50	0.040	0.040	17.00-21.00	37.00-41.00	0.50	
	GX40NiCrSiNb35-18	1.4807		0.30-0.50	2.00	1.00-2.50	0.040	0.030	17.00-20.00	34.00-36.00	0.50	Nb 1.00-1.80
EN 10295:2002	GX40NiCrSiNb38-19	1.4849		0.30-0.50	2.00	1.00-2.50	0.040	0.030	18.00-21.00	36.00-39.00	0.50	Nb 1.20-1.80
	GX40NiCrSi38-19	1.4865		0.30-0.50	2.00	1.00-2.50	0.040	0.030	18.00-21.00	36.00-39.00	0.50	
ISO 11973:1999	GX40NiCrSi38-19			0.3-0.5	2	1.0-2.5	0.04	0.03	18-21	36	0.5	
130 11973.1999	GX40NiCrSiNb38-19			0.3-0.5	2	1.0-2.5	0.04	0.03	18-21	36	0.5	Nb 1.2-1.8
ASTM A 297/A 297M-97 (2003)	HU		N08004	0.35-0.75	2.00	2.50	0.04	0.04	17.0-21.0	37.0-41.0	0.50	
BS 3100:1991 AMD.1:1992	331C40			0.35-0.55	2.0	1.5	0.040	0.040	17.0-21.0	33.0-37.0	1.5	
ASTM A 608/A 608M-02	HU50		N08005	0.40-0.60	1.50	0.50-2.00	0.04	0.04	17-21	37-41	0.50	
BS 3100:1991 AMD.1:1992	331C60			0.75	2.0	3.0	0.050	0.050	15.0-25.0	36.0-46.0	1.5	
EN 10295:2002	G-NiCr50Nb	2.4680		0.10	0.50	1.00	0.020	0.020	48.00-52.00	bal	0.50	N 0.16; Nb 1.00-1.80; Fe 1.00
ISO 11973:1999	GX10NiCrNb50-50			0.1	0.5	0.5	0.02	0.02	47-52	bal	0.5	N 0.16; Nb 1.4-1.7; N+C 0.2

7.5A Chemical Composition of Cast Heat Resistant Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS					Weight, 9	%, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 297/ A297M-97 (2003)	HW			0.35-0.75	2.00	2.50	0.04	0.04	10.0-14.0	58.0-62.0	0.50	
ASTM A 608/A 608M-02	HW50			0.40-0.60	1.50	0.50-2.00	0.04	0.04	10-14	58-62	0.50	
EN 10295:2002	G-NiCr15	2.4815		0.35-0.65	2.00	1.00-2.50	0.040	0.030	12.00-18.00	58.00-66.00	1.00	Fe bal
ISO 11973:1999	GX50NiCr65-15			0.35-0.65	1.3	2	0.04	0.03	13-19	64-69		
ASTM A 297/A 297M-97 (2003)	HX		N06006	0.35-0.75	2.00	2.50	0.04	0.04	15.0-19.0	64.0-68.0	0.50	
ASTM A 608/A 608M-02	HX50		N08006	0.40-0.60	1.50	0.50-2.00	0.04	0.04	15.0-19.0	64-68	0.50	
BS 3100:1991 AMD.1:1992	334C11			0.75	2.0	3.0	0.050	0.050	10.0-20.0	55.0-65.0	1.5	
EN 10295:2002	G-CoCr28	2.4778		0.05-0.25	1.50	0.50-1.50	0.040	0.030	27.00-30.00	4.00	0.50	Nb 0.50; Co 48.0-52.0; Fe bal
ISO 11973:1999	GX30CoCr50-28			0.5	1	1	0.04	0.03	25-30	1	0.5	Co 48-52; Fe 20
EN 10295:2002	G-NiCr28W	2.4879		0.35-0.55	1.50	1.00-2.00	0.040	0.030	27.00-30.00	47.00-50.00	0.50	W 4.00-6.00; Fe bal
ISO 11973:1999	GX45NiCrWSi48-28-5			0.35-0.55	1.5	1.0-2.5	0.04	0.03	27-30	47-50		W 4-6
EN 10295:2002	GX50NiCrCo20-20-20	1.4874		0.35-0.65	2.00	1.00	0.040	0.030	19.00-22.00	18.00-22.00	2.50-3.00	Nb 0.75-1.25; Co 18.50-22.00; W 2.00-3.00
ISO 11973:1999	GX40NiCrCo20-20-20			0.35-0.60	2	1	0.04	0.03	19-22	18-22	2.5-3.0	Co 18-22; W 2-3

7.5B Mechanical Properties of Cast Heat Resistant Steels

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 5122:2003	SCH 1			Α					490			
313 G 5122.2003	SCH 3			Α					490			
BS 3100:1991 AMD.1:1992	420C24			AC								
EN 10295:2002	GX40CrSi13	1.4729		Α								300 HB
ISO 11973:1999	GX40CrSi13			Α								300 HB max
EN 10295:2002	GX40CrSi17	1.4740		Α								300 HB
ISO 11973:1999	GX40CrSi17			Α								300 HB max
EN 10295:2002	GX40CrSi24	1.4745										
ISO 11973:1999	GX40CrSi24			Α								300 HB max
EN 10295:2002	GX40CrSi28	1.4776										
ISO 11973:1999	GX40CrSi28			Α								320 HB max
EN 10295:2002	GX130CrSi29	1.4777										
ISO 11973:1999	GX130CrSi29			Α								400 HB max
JIS G 5122:2003	SCH 2			Α					340			
ASTM A 297/A 297M-97 (2003)	HC		J92605	AC					380	55		
ASTM A 608/A 608M-02	HC30		J92613	AC								
BS 3100:1991 AMD.1:1992	452C11			AC								
BS 3100.1991 AMD.1.1992	452C12			AC								
ISO 11973:1999	GX40CrNiSi27-4			AC			250		400		3	400 HB max
ASTM A 297/A 297M-97 (2003)	HD		J93005	AC			240	35	515	75	8	
JIS G 5122:2003	SCH 11			AC					590			
ASTM A 608/A 608M-02	HD50		J93015	AC								
EN 10295:2002	GX40CrNiSi27-4	1.4823					250		550		3	

7.5B Mechanical Properties of Cast Heat Resistant Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thic	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 5122:2003	SCH 17			AC			275		540		5	
ASTM A 297/A 297M-97 (2003)	HE		J93403	AC			275	40	585	85	9	
ASTM A 608/A 608M-02	HE35		J93413	AC								
BS 3100:1991 AMD.1:1992	309C40			AC								
EN 10295:2002	GX25CrNiSi18-9	1.4825					230		450		15	
EN 10295.2002	GX40CrNiSi22-10	1.4826					230		450		8	
ISO 11973:1999	GX25CrNiSi18-9			AC			230		450		15	
130 11973.1999	GX40CrNiSi22-10			AC			230		450		8	
ASTM A 297/A 297M-97 (2003)	HF		J93603	AC			240	35	485	70	25	
JIS G 5122:2003	SCH 12			AC			235		490		23	
ASTM A 608/A 608M-02	HF30		J92803	AC								
BS 3100:1991 AMD.1:1992	302C35			AC								
EN 10295:2002	GX25CrNiSi20-14	1.4832					230		450		10	
ISO 11973:1999	GX25CrNiSi20-14			AC			230		450		10	
EN 10295:2002	GX40CrNiSi25-12	1.4837					220		450		6	
ISO 11973:1999	GX40CrNiSi25-12			AC			220		450		6	
UC C 5100:0000	SCH 13			AC			235		490		8	
JIS G 5122:2003	SCH 13A			AC			235		490		8	
BS 3100:1991 AMD.1:1992	309C35			AC					510		7	
ASTM A 297/A 297M-97 (2003)	HH		J93503	AC			240	35	515	75	10	
ACTM A 447/A 447M AC (COCC)	Type I		J93303	AC					550	80	9	
ASTM A 447/A 447M-93 (2003)	Type II		J93303	AC					550	80	4	
BS 3100:1991 AMD.1:1992	309C32			HTC					550		3	
AOTIA A 000/A 000IA 00	HH30		J93513	AC								
ASTM A 608/A 608M-02	HH33		J93633	AC								
BS 3100:1991 AMD.1:1992	309C30			AC								
ASTM A 297/A 297M-97 (2003)	HI		J94003	AC			240	35	485	70	10	
ASTM A 608/A 608M-02	HI35		J94013	AC								
JIS G 5122:2003	SCH 18			AC			235		490		8	
JIS G 5122:2003	SCH 21			AC			235		440		8	
ASTM A 297/A 297M-97 (2003)	HK		J94224	AC			240	35	450	65	10	
ASTM A 351/A 351M-03	HK30		J94203	AC			240	35	450	65	10.0	
ASTM A 608/A 608M-02	HK30		J94203	AC								

7.5B Mechanical Properties of Cast Heat Resistant Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thicl	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	Other
ASTM A 351/A 351M-03	HK40		J94204	AC			240	35	425	62	10.0	
EN 10295:2002	GX40CrNiSi25-20	1.4848					220		450		8	
JIS G 5122:2003	SCH 22			AC			235		440		8	
BS 3100:1991 AMD.1:1992	310C40			AC					450		7	
ISO 11973:1999	GX40CrNiSi25-20			AC			220		450		6	
ASTM A 608/A 608M-02	HK40		J94204	AC								
BS 3100:1991 AMD.1:1992	310C45			AC								
ASTM A 297/A 297M-97 (2003)	HL		N08604	AC			240	35	450	65	10	
AOTIA A 000/A 000IA 00	HL30		N08613	AC								
ASTM A 608/A 608M-02	HL40		N08614	AC								
JIS G 5122:2003	SCH 23			AC			245		450		8	
JIS G 5122:2003	SCH 19			AC					390		5	
ASTM A 297/A 297M-97 (2003)	HN		J94213	AC					435	63	8	
ASTM A 608/A 608M-02	HN40		J94214	AC								
EN 10295:2002	GX35NiCrSi25-21	1.4805					220		430		8	
BS 3100:1991 AMD.1:1992	311C11			AC								
EN 10295:2002	GX40CrNiSiNb24-24	1.4855					220		450		4	
ISO 11973:1999	GX40CrNiSiNb24-24			AC			220		400		4	
EN 10295:2002	GX40NiCrSiNb35-26	1.4852					220		440		4	
ASTM A 297/A 297M-97 (2003)	HP		N08705	AC			235	34	430	62.5	4.5	
JIS G 5122:2003	SCH 24			AC			235		440		5	
EN 10295:2002	GX40NiCrSi35-26	1.4857					220		440		6	
100 44070 4000	GX40NiCrSi35-26			AC			220		440		6	
ISO 11973:1999	GX40NiCrSiNb35-26			AC			220		440		4	
ISO 11973:1999	GX40NiCrSi35-17			AC			220		420		6	
EN 10295:2002	GX40NiCrSi35-17	1.4806					220		420		6	
JIS G 5122:2003	SCH 15			AC					440		4	
ASTM A 297/A 297M-97 (2003)	HT		N08605	AC					450	65	4	
ASTM A 608/A 608M-02	HT50		N08050	AC								
BS 3100:1991 AMD.1:1992	330C12			AC								
JIS G 5122:2003	SCH 16			AC			195		440		13	
BS 3100:1991 AMD.1:1992	330C11			AC					450		3	
ASTM A 351/A 351M-03	HT30		N08603	AC			195	28	450	65	15.0	

7.5B Mechanical Properties of Cast Heat Resistant Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	
Designation	Symbol or Name	Number	Number	Form/Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	Other
JIS G 5122:2003	SCH 20			AC					390		4	
	GX40NiCrSiNb35-18	1.4807					220		420		4	
EN 10295:2002	GX40NiCrSiNb38-19	1.4849					220		420		4	
	GX40NiCrSi38-19	1.4865					220		420		6	
ISO 11973:1999	GX40NiCrSi38-19			AC			220		420		6	
150 11973:1999	GX40NiCrSiNb38-19			AC			220		420		4	
ASTM A 297/A 297M-97 (2003)	HU		N08004	AC					450	65	4	
BS 3100:1991 AMD.1:1992	331C40			AC					450		3	
ASTM A 608/A 608M-02	HU50		N08005	AC								
BS 3100:1991 AMD.1:1992	331C60			AC								
EN 10295:2002	G-NiCr50Nb	2.4680					230		540		8	
ISO 11973:1999	GX10NiCrNb50-50			AC			230		540		8	
ASTM A 297/ A297M-97 (2003)	HW			AC					60		415	
ASTM A 608/A 608M-02	HW50			AC								
EN 10295:2002	G-NiCr15	2.4815					200		400		3	
ISO 11973:1999	GX50NiCr65-15			AC			200		400		3	
ASTM A 297/A 297M-97 (2003)	HX		N06006	AC					415	60		
ASTM A 608/A 608M-02	HX50		N08006	AC								
BS 3100:1991 AMD.1:1992	334C11			AC								
EN 10295:2002	G-CoCr28	2.4778					235		490		6	
ISO 11973:1999	GX30CoCr50-28			AC								
EN 10295:2002	G-NiCr28W	2.4879					240		440		3	
ISO 11973:1999	GX45NiCrWSi48-28-5			AC			220		400		3	
EN 10295:2002	GX50NiCrCo20-20-20	1.4874					320		420		6	
ISO 11973:1999	GX40NiCrCo20-20-20			AC			320		400		6	

7.6 Non-Comparable Cast Carbon Steels

ASTM A 27/A 27M-	03 - Steel Cast	ing, Carbon, fo	r General Appl	ication								
Grade, Class, Type	N-1	N-2										
UNS Number												
ASTM A 148/A 148I	VI-03 - Steel Ca	stings, High S	trength, for Str	uctural Purpos	es							
Grade, Class, Type	115-95	130-115	135-125	150-135	160-145	165-150	165-150L	210-180	210-180L	260-210	260-210L	
UNS Number												
ASTM A 352/A 352I	VI-03 - Steel Ca	stings, Ferrition	and Martensit	c, for Pressure	-Containing Pa	arts, Suitable fo	r Low-Temper	ature Service				
Grade, Class, Type	LC4	LC9										
UNS Number	J41500	J31300										
ASTM A 757/A 757I	VI-00 - Steel Ca	stings, Ferrition	and Martensit	c, for Pressure	-Containing ar	nd Other Applic	ations, for Lov	v-Temperature	Service			
Grade, Class, Type	B4N	B4Q	C1Q	D1N1	D1N2	D1N3	D1Q1	D1Q2	D1Q3	E1Q	E3N	
UNS Number	J41501	J41501	J12582	J22092	J22092	J22092	J22092	J22092	J22092	J42220	J42065	
ASTM A 958-00 - St	teel Castings,	Carbon, and A	lloy, with Tensi	le Requirement	ts, Chemical R	equirements Si	milar to Standa	ard Wrought G	rades			
Grade, Class, Type	SC 4340	SC 8620	SC 8625	SC 8630								
UNS Number												
JIS G 5111:1991 - F	ligh Tensile St	rength Carbon	Steel Castings	and Low Alloy	Steel Casting	s for Structural	Purposes					
Symbol of Grade	SCMnCr 2	SCMnCr 3	SCMnCr 4	SCMnCrM 2	SCMnCrM 3	SCMnM 3						
JIS G 5151:1991 - S	Steel Castings	for High Temp	erature and Hig	h Pressure Se	rvice							
Class	SCPH 22											
BS 3100:1991 AMD	.1:1992 - Steel	Castings for C	eneral Engine	ering Purposes								
Steel	AL1	AL2	AL3	BL2	AM1	AM2	AW1	AW2	AW3	B3	B4	B5
Steel	B6	B7	BT1	BT2	ВТ3	BW2	BW3	BW4	302C25	B2		
AFNOR NF A 32-05	3:1992 - Cast 9	Steels for Low	Temperatures I	Purposes								
Designation	16 M5-M	10 N6-M	18 NCD12.6-M	10 N14-M	10 N19-M	20 NCD4-M						
AFNOR NF A 32-05	4:1994 - Cast S	Steels for Gene	eral Purpose in	Mechanical En	gineering							
Designation	G10MnMoV6	G15CrMoV6	G35NiCrMo6	G20NiCrMo12	G30NiCrMo14							
DIN 17205:1992 - Q	uenched and 1	Tempered Stee	l Castings for 0	General Applica	ations							
Steel Name	GS-30 C	rMoV 6 4	GS-35 Ci	MoV 10 4	GS-25	CrNiMo 4	GS-34 (CrNiMo 6	GS-30 C	rNiMo 8 5		· -
Steel Number	1.7	725	1.7	755	1.6	5515	1.6	5582	1.6	5570		-
EN 10213-2:1995 - 9	Steel Castings	for Pressure F	Purposes Part 2	: Steel Grades	for Use at Roo	m Temperature	and at Elevate	ed Temperature	•			
Steel Name	G12Mc	CrV5-2	GX4CrNi	Mo16-5-1								
Steel Number	1.7	720	1.4	405			-					
ISO 4991:1994 - Ste	eel Castings fo	r Pressure Pu	poses									
Steel Type	C31L	C33H	C34BL	C43C1L	C47H	C60H						

360

7.7 Non-Comparable Cast Manganese Steels

Class	SCMnH 21											
AFNOR NF A 32	2-058:1984 - Cast S	teels for Gene	ral Purpose in	Mechanical En	gineering							
Designation	45 S	7-M	18 CD	BB2-M	35 C	D 4-M	42 C	D 4-M	50 C	D 4-M	16 MC	DV 6-M
Designation	25 MCE	OV 6-M	30 MSC	B 6.4-M	35 CD\	/ 10 4-M	45 CS	SD 6-M	30 NSC	DV 86-M	20 NO	CD 8-M
Designation	32 NC	D 8-M	42 NC	D 16-M	50 NSC	CDV 5-M	85 CD	V 12-M	Z 100 C	CD 6 1-M	Z 160 C	DV 12-M
Designation	Z 200 C	C 12-M	Z 320 C	D 16 3-M	Z 280CI	D 16 3-M	Z 270	C 27-M	-		-	
SO 13521:1999	- Austenitic Mang	anese Steel Ca	stings				•		•		•	
Steel Type	GX120Mn17											

7.8 Non-Comparable Cast Alloy Steels

ASTM A 217/A 217N	/I-02 - Steel Ca	stings. Martens	sitic Stainless	and Allov. for F	ressure- Conta	aining Parts, Si	uitable for High	-Temperature	Service			
Grade, Class, Type	WC4	WC5	WC11	C12A								
UNS Number	J12082	J22000	J11872	J84090								
ASTM A 389/A 389N	STM A 389/A 389M-03 - Steel Castings, Alloy, Specially Heat-Treated, for Pressure-Containing Parts, Suitable for High-Temperature Service											
Grade, Class, Type	C23											
UNS Number	J12080											
ASTM A 487/A 487N	Л-93 (2003) - S	teel Castings S	uitable for Pre	ssure Service								
Grade, Class, Type	1	2	4	6	7	9	10	11	12	13	14	16
UNS Number	J13002	J13005	J13047	J13855	J12084	J13345	J23015	J12082	J22000	J13080	J15580	J31200
Grade, Class, Type	CA15M											
UNS Number	J91151											

7.9 Non-Comparable Cast Stainless Steels for General and Corrosion Resistant Applications

ASTM A 743/A 743I	VI-03 - Castings	s, Iron-Chromiu	ım, Iron-Chron	nium-Nickel, Co	rrosion Resist	ant, for Genera	al Application					
Grade, Class, Type	CG-12	CF16F	CF16Fa	CH-10	CE-30	CB-30	CC-50	CA-40F	CF10SMnN	CG6MMN	CN-7MS	CA6N
UNS Number	J93001	J92701			J93423	J91803	J92615	J91154	J92972			
Grade, Class, Type	CA-28MWV	CK-35MN	CB-6	CK20								
UNS Number	J91422		J91804	J94202								
ASTM A 744/A 744I	VI-00 - Castings	s, Iron-Chromiu	ım-Nickel, Cor	rosion Resistar	nt, for Severe S	ervice						
Grade, Class, Type	CN7MS											
UNS Number	J94650											
JIS G 5121:2003 - S	Stainless Steel	Castings										
Class	SCS 4	SCS 10	SCS 11	SCS 15	SCS 16	SCS 18	SCS 20	SCS 24				
EN 10283:1998 - Co	rrosion Resist	ant Steel Casti	ngs									
Steel Name	GX4CrNi	Mo16-5-2	GX5Crl	NiCu16-4	4 GX2NiCrMoCu25-20-5		GX2CrNiMoCuN29-25-5		GX6CrNiN26-7		GX2CrNiMoN22-5-3	
Steel Number	1.4	411	1.4	525	1.4	584	1.4587		1.4347		1.4470	
Steel Name	GX2CrNiN	1oN25-6-3	GX2CrNiMo	CuN25-6-3-3	GX2CrNiN	MoN25-7-3	GX2CrNi	MoN26-7-4				
Steel Number	1.4468		1.4517		1.4417		1.4469					
ISO 11972:1998 - C	orrosion-Resis	tant Cast Steel	s for General	Applications								
Steel Type	GX 2 CrN	liN 18 10										

7.10 Non-Comparable Cast Stainless Steels for Pressure Purposes

ASTM A 351/A 351I	VI-03 - Castings	, Austenitic, A	ustenitic-Ferrit	ic (Duplex), for	Pressure-Cont	taining Parts						•
Grade, Class, Type	CF10	CF10M	CH8	CH10	CF10MC	CN3MN	CE8MN	CG6MMN	CF10SMnN	CT15C	CK3MnCuN	CE20N
UNS Number	J92590	J92901	J93400	J93401	J92971	J94651				N08151	J93254	
Grade, Class, Type	CD3MWCuN	CF3-MN	CG-8M	CG-3M	CH-20	CK-20						
UNS Number			J93000	J92999	J93402	J94202						
EN 10213-4:1995 - 9	EN 10213-4:1995 - Steel Castings for Pressure Purposes Part 4: Austenitic and Austenitic-Ferritic Steel Grades											
Steel Name	GX2CrNiN	loN26-7-4	GX2CrNiN	1oN22-5-3	-		-					_
Steel Number	1.4469		1.4	470	-		-					

7.11 Non-Comparable Cast Heat Resistant Steels

EN 10295:2002 - Heat Resistant Steel Castings									
Steel Name	GX160CrSi18	GX10NiCrSiNb32-20	GX50NiCrCoW35-25-15-5	GX40NiC	Nb45-35	-		-	
Steel Number	1.4743	1.4859	1.4869	1.4889		889		-	
ISO 11973:1999 - Heat-Resistant Cast Steels and Alloys for General Applications									
Steel Type	GX10NiCrNb31-20	GX50NiCr52-19	GX45NiCrCoW35-25-15-5						

Chapter

8

WROUGHT STAINLESS STEELS

364 Wrought Stainless Steels – List of Standards Chapter 8

Plate, Sheet, Strip

ASTM Standards

ASTM A 167-99	Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
ASTM A 176-99	Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip
ASTM A 666-00	Annealed or Cold-Worked Austenitic Stainless Steel, Sheet, Strip, Plate, and Flat Bar
ASTM A 693-03	Precipitation-Hardening Stainless and Heat-Resisting Steel Plate, Sheet, and Strip
ASTM B 625-99	UNS N08904, UNS N08925, UNS N08031, UNS N08932, UNS N08926, and UNS R20033 Plate, Sheet, and Strip
ASTM B 688-96	Chromium-Nickel-Molybdenum-Iron (UNS N08366 and UNS N08367) Plate, Sheet, and Strip

JIS Standards

JIS G 4304:1999	Hot Rolled Stainless Steel Plates, Sheets and Strip
JIS G 4305:1999	Cold Rolled Stainless Steel Plates, Sheets and Strip
JIS G 4312:1991	Heat-Resisting Steel Plates and Sheets

CEN Standards

EN 10088-2:1995	Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purpose
EN 10095:1999	Heat Resisting Steels and Nickel Alloys

Bars

ASTM Standards

ASTM A 276-03	Stainless Steel Bars and Shapes
ASTM A 564/A 564M-02a	Hot-Rolled and Cold-Finished Age-Hardening Stainless Steel Bars and Shapes
ASTM A 565-03b	Martensitic Stainless Steel Bars for High-Temperature Service
ASTM A 582/A 582M-95b (2000)	Free-Machining Stainless Steel Bars
ASTM B 649-02	Ni-Fe-Cr-Mo-Cu Low-Carbon Alloy (UNS N08904), Ni-Fe-Cr-Mo-Cu-N Low-Carbon Alloys (UNS N08925, UNS N08031, and UNS N08926), and Cr-Ni-Fe-N Low-Carbon Alloy (UNS R20033) Bar and Wire
ASTM B 691-02	Iron-Nickel-Chromium-Molybdenum Alloys (UNS N08366 and UNS N08367) Rod, Bar, and Wire

JIS Standards

JIS G 4303:1998	Stainless Steel Bars
JIS G 4311:1991	Heat-Resisting Steel Bars
JIS G 4318:1998	Cold Finished Stainless Steel Bars

CEN Standards

1FIX 10088-3 1995	Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rod and Sections for General Purposes
EN 10095:1999	Heat Resisting Steels and Nickel Alloys

ISO Standard

ISO 4955:1994	Heat-Resisting Steels and Alloys

Heat Treatment Terms Applicable to this Chapter

Standard	Heat Treatment Terms
ASTM A 167-99	l
ASTM A 176-99	
ASTM A 276-03	HF or CF: hot-finished or cold-finished A: annealed; H: hardened and tempered at a relatively low temp.; T: hardened and tempered at a relatively
ASTIVI A 276-03	high temperature; S: strain hardened – relatively light cold work; B: relatively severe cold work; as hot-rolled
ASTM A 564/A 564M-02a	HR & CF: hot-rolled and cold-finished A: solution treated; HXXX: age hardening at specified temperature
ASTM A 582/A 582M-95b (2000)	HF or CF: hot-finished or cold-finished A: annealed; T: intermediate temper; H: hard temper
ASTM A 666-00	A: annealed; CW: cold-worked, 1/16 hard, 1/8 hard, 1/4 hard, 1/4 hard, 3/4 hard, full hard
ASTM A 693-03	S: solution treated condition; PHT: precipitation hardening treatment at specified temperature
ASTM B 625-99	HR or CR: hot rolled or cold-rolled. A: annealed
ASTM B 649-02	CF & HF: cold finished and hot finished
10711 D 222 22	S: solution-treated
ASTM B 688-96	HR or CR: hot-rolled or cold-rolled
ASTM B 691-02	HF & CF: hot-finished and cold-finished A: annealed
	HR or CR: hot rolled or cold rolled
EN 40000 0 4005	C: cold rolled strip; H: hot rolled strip; P: hot rolled plate and sheet
EN 10088-2:1995	A: annealed; QT: quenched and tempered; AT: solution annealed; P: precipitation hardened (with specified
	temperature); SR: strength relieved
	HF or CF: hot- or cold-formed
EN 10088-3:1995	A: annealed; QT: quenched and tempered; AT: solution annealed; PXXX: precipitation hardened at specified
	temperature
EN 10095:1999	PI, Sh, St/HR or CR: hot rolled or cold rolled; Bars/HF or CF: hot formed or cold formed
	A: annealed; AT: solution annealed
ISO 4955:1994	TA: annealed; TQ: quenched
	HF: hot-finished
JIS G 4303:1998	S: solution-treated; A: annealed; Q: quenched and tempered; HXXX: precipitation hardened at specified
	temperature
JIS G 4304:1999	HR: hot rolled; S: solution treated; A: annealed; QT: quenched and tempered; HXXX: precipitation hardening treatment at specified temperature
UC C 4205-4000	CR: cold rolled
JIS G 4305:1999	same as JIS G 4304, except SUS 301 and SUS 301L (TRR: thermal refining rolled)/ ¼ H, ½ H, ¾ H, H
JIS G 4311:1991	S: solution treatment, H: aging treatment after solution treatment
JIS G 4312:1991	S: solution treatment; H: aging treatment after solution treatment
JIS G 4318:1998	CF: cold finished

8.1.1A Chemical Composition of Martensitic Stainless Steels

Standard	Grade, Class,	Steel	UNS				W	eight, %, n	nax, Unless Ot	herwise S	pecified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 176-99	403		S40300	0.15	1.00	0.50	0.040	0.030	11.50-13.00	0.60		
JIS G 4304:1999	SUS403			0.15	1.00	0.05	0.040	0.030	11.50-13.00	0.60		
JIS G 4305:1999	SUS403			0.15	1.00	0.05	0.040	0.030	11.50-13.00	0.60		
JIS G 4312:1991	SUS403			0.15	1.00	0.05	0.040	0.030	11.50-13.00	0.60		
ASTM A 240/A 240M-03c	410		S41000	0.08-0.15	1.00	1.00	0.040	0.030	11.5-13.5	0.75		
JIS G 4304:1999	SUS410			0.15	1.00	1.00	0.040	0.030	11.5-13.0			
JIS G 4305:1999	SUS410			0.15	1.00	1.00	0.040	0.030	11.50-13.50			
EN 10088-2:1995	X12Cr13	1.4006		0.08-0.15	1.50	1.00	0.040	0.015	11.50-13.50	0.75		
ASTM A 240/A 240M-03c			S41003	0.030	1.5	1.00	0.040	0.030	10.5-12.5	1.5		
JIS G 4304:1999	SUS410L			0.030	1.00	1.00	0.040	0.030	11.00-13.50			
JIS G 4305:1999	SUS410L			0.030	1.00	1.00	0.040	0.030	11.00-13.50			
ASTM A 240/A 240M-03c	410S		S41008	0.08	1.00	1.00	0.040	0.030	11.5-13.5	0.60		
JIS G 4304:1999	SUS410S			0.08	1.00	1.00	0.040	0.030	11.50-13.50	0.60		
JIS G 4305:1999	SUS410S			0.08	1.00	1.00	0.040	0.030	11.50-13.50	0.60		
EN 10088-2:1995	X6Cr13	1.4000		0.08	1.00	1.00	0.040	0.015	12.00-14.00			
ISO 4955:1994	X6Cr13			0.08	1.0	1.0	0.040	0.030	12.0-14.0	1.0		
ASTM A 176-99	420		S42000	0.15 min	1.00	1.00	0.040	0.030	12.0-14.0	0.75	0.50	
JIS G 4304:1999	SUS420J1			0.16-0.25	1.00	1.00	0.040	0.030	12.00-14.00	0.60		
JIS G 4305:1999	SUS420J1			0.16-0.25	1.00	1.00	0.040	0.030	12.00-14.00	0.60		
EN 10088-2:1995	X20Cr13	1.4021		0.16-0.25	1.50	1.00	0.040	0.030	12.00-14.00			
JIS G 4304:1999	SUS420J2			0.26-0.40	1.00	1.00	0.040	0.030	12.00-14.00	0.60		
JIS G 4305:1999	SUS420J2			0.26-0.40	1.00	1.00	0.040	0.030	12.00-14.00	0.60		
EN 10088-2:1995	X30Cr13	1.4028		0.26-0.35	1.50	1.00	0.040	0.030	12.0-14.00			

8.1.1B Mechanical Properties of Martensitic Stainless Steels

Standard	Grade, Class,	Steel	UNS	Product Form/	Thic	kness	Yield Strer	ngth, min	Tensile Str	ength, min	Elongation,	Hardness,
Designation	Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 176-99	403		S40300	PI, Sh, St/			205	30	485	70	25.0	217/96/
JIS G 4304:1999	SUS403			Pl, Sh, St/HR, A			205		440		20	201/93/210
JIS G 4305:1999	SUS403			Pl, Sh, St/CR, A			205		440		20	201/93/210
JIS G 4312:1991	SUS403			PI, Sh, St/HR or CR, A			205		440		20	201/93/210
ASTM A 240/A 240M-03c	410		S41000	Pl, Sh, St			205	30	450	65	20	217/96/
JIS G 4304:1999	SUS410			PI, Sh, St/HR, A			205		440		20	201/93/210
JIS G 4305:1999	SUS410			PI, Sh, St/CR, A			205		440		20	201/93/210
				St/CR, A	≤ 6				600		00	000/00/000
EN 40000 0 4005	V400-40	4 4000		St/HR, A	≤ 12				600		20	200/90/200
EN 10088-2:1995	X12Cr13	1.4006		PI/HR, QT550	- 7F		400		550-750		15	/
				PI/HR, QT650	≤ 75		450		650-850		12	/
ASTM A 240/A 240M-03c			S41003	Pl, Sh, St			275	40	455	66	18	183/89/
JIS G 4304:1999	SUS410L			PI, Sh, St/HR, A			195		360		22	183/88/200
JIS G 4305:1999	SUS410L			Pl, Sh, St/CR, A			195		360		22	183/88/200
ASTM A 240/A 240M-03c	410S		S41008	Pl, Sh, St			205	30	415	60	22	183/89/
JIS G 4304:1999	SUS410S			PI, Sh, St/HR, A			205		410		20	183/88/200
JIS G 4305:1999	SUS410S			Pl, Sh, St/CR, A			205		410		20	183/88/200
				St/CR	≤ 6		240					
EN 10088-2:1995	X6Cr13	1.4000		St/HR	≤ 12		220		400-600		19	
				PI/HR	≤ 25		220					
ISO 4955:1994	X6Cr13			PI, Sh, St/TA			230		400-630		see standard	197//
ASTM A 176-99	420		S42000	PI, Sh, St/					485	70	15.0	217/96/
JIS G 4304:1999	SUS420J1			PI, Sh, St/HR, A			225		520		18	223/97/234
JIS G 4305:1999	SUS420J1			PI, Sh, St/CR, A			225		520		18	223/97/234
				St/CR, QT	≤ 3							//440-530
				St/CR, A	≤ 6						4.5	005/05/005
EN 10088-2:1995	X20Cr13	1.4021		HR St/A	≤ 12						15	225/95/225
				HR PI/QT65	. 75		450		650-850		12	/
				HR PI/QT750	≤ 75		550		750-950		10	/
JIS G 4304:1999	SUS420J2			PI, Sh, St/HR, A			225		540		18	235/99/247
JIS G 4305:1999	SUS420J2			Pl, Sh, St/CR, A			225		540		18	235/99/247
				St/CR, QT	≤ 3							//450-550
EN 40000 0 4005	V000 10	4 4000		St/CR, A	≤ 6				740			005/07/005
EN 10088-2:1995	X30Cr13	1.4028		St/HR, A	≤ 12				740 max		15	235/97/235
				PI/HR, QT800	≤ 75		600		800-1000		10	/

8.1.2A Chemical Composition of Ferritic Stainless Steels

Standard	Grade, Class,	Steel	UNS				W	eight, %, n	nax, Unless O	therwise S	pecified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	405		S40500	0.08	1.00	1.00	0.040	0.030	11.5-14.5	0.60		Al 0.10-0.30
JIS G 4304:1999	SUS405			0.08	1.00	1.00	0.040	0.030	11.50-14.50			Al 0.10-0.30
JIS G 4305:1999	SUS405			0.08	1.00	1.00	0.040	0.030	11.50-14.50			Al 0.10-0.30
JIS G 4312:1991	SUS405			0.08	1.00	1.00	0.040	0.030	11.50-14.50			Al 0.10-0.30
EN 10088-2:1995	X6CrAl13	1.4002		0.08	1.00	1.00	0.040	0.015	12.00-14.00			Al 0.10-0.30
ASTM A 240/A 240M-03c			S40977	0.030	1.5	1.00	0.040	0.015	10.5-12.5	0.30-1.00		N 0.030
ASTIVI A 240/A 240/VI-03C			S41050	0.030	1.00	1.00	0.040	0.030	12.0-13.0	0.50		N 0.030; Cb 9 x (C+N) to 0.60
EN 10088-2:1995	X2CrNi12	1.4003		0.030	1.50	1.00	0.040	0.015	10.50-12.50	0.30-1.00		N 0.030
JIS G 4312:1991	SUH409L			0.030	1.00	1.00	0.040	0.030	10.50-11.75			Ti 6 x C to 0.75
EN 10088-2:1995	X2CrTi12	1.4512		0.030	1.00	1.00	0.040	0.015	10.50-12.50			Ti 6 x (C+N) to 0.65
ASTM A 240/A 240M-03c	430		S43000	0.12	1.00	1.00	0.040	0.030	16.0-18.0	0.75		
JIS G 4304:1999	SUS430			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
JIS G 4305:1999	SUS430			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
JIS G 4312:1991	SUS430			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
EN 10088-2:1995	X6Cr17	1.4016		0.08	1.00	1.00	0.040	0.015	16.00-18.00			
JIS G 4304:1999	SUS430LX			0.030	1.00	0.75	0.040	0.030	16.00-19.00			Ti or Nb 0.10-1.00
JIS G 4305:1999	SUS430LX			0.030	1.00	0.75	0.040	0.030	16.00-19.00			Ti or Nb 0.10-1.00
	X2CrTi17	1.4520		0.025	0.50	0.50	0.040	0.015	16.00-18.00			N 0.015; Ti 0.30-0.60
EN 10088-2:1995	X3CrTi17	1.4510		0.05	1.00	1.00	0.040	0.015	16.00-18.00			Ti 4 x (C+N) + 0.15 to 0.80
	X3CrNb17	1.4511		0.05	1.00	1.00	0.040	0.015	16.00-18.00			Nb 12 x C to 1.00
ASTM A 240/A 240M-03c	434		S43400	0.12	1.00	1.00	0.040	0.030	16.0-18.0		0.75-1.25	
JIS G 4304:1999	SUS434			0.12	1.00	1.00	0.040	0.030	16.00-18.00		0.75-1.25	
JIS G 4305:1999	SUS434			0.12	1.00	1.00	0.040	0.030	16.00-18.00		0.75-1.25	
EN 10088-2:1995	X6CrMo17-1	1.4113		0.08	1.00	1.00	0.040	0.015	16.00-18.00		0.90-1.40	
	439		S43035	0.030	1.00	1.00	0.040	0.030	17.0-19.0	0.50		Ti [0.20 + 4 x (C+N)] to 1.10; N 0.030; Al 0.15
STM A 240/A 240M-03c			S43932	0.030	1.00	1.00	0.040	0.030	17.0-19.0	0.50		(Ti+Cb) [0.20 + 4 x (C+N)] to 0.75; N 0.030; Al 0.15
			S43940	0.030	1.00	1.00	0.040	0.015	17.5-18.5			Ti 0.10-0.60; Cb [0.30 + (3 x C)] min
EN 10088-2:1995	X2CrTiNb18	1.4509		0.030	1.00	1.00	0.040	0.015	17.50-18.50			Ti 0.10-0.60; Nb 3 x C+ 0.30 to 1.00

Standard	Grade, Class,	Steel	UNS				W	eight, %, n	nax, Unless Ot	herwise S	pecified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	444		S44400	0.025	1.00	1.000	0.040	0.030	17.5-19.5	1.00	1.75-2.50	(Ti+Cb) [0.20 + 4 x (C+N)] to 0.80; N 0.035
JIS G 4304:1999	SUS444			0.025	1.00	1.00	0.040	0.030	17.00-20.00		1.75-2.50	N 0.025; Ti, Nb, Zr or their combination 8 x (C+N) to 0.80
JIS G 4305:1999	SUS444			0.025	1.00	1.00	0.040	0.030	17.00-20.00		1.75-2.50	N 0.025; Ti+Nb or their combination 8 x (C+N) to 0.80
EN 10088-2:1995	X2CrMoTi18-2	1.4521		0.025	1.00	1.00	0.040	0.015	17.00-20.00		1.80-2.50	N 0.030; Ti 4 (C+N) + 0.15 to 0.80
ASTM A 176-99	446		S44600	0.20	1.50	1.00	0.040	0.030	23.00-27.00	0.75		N 0.25
JIS G 4312:1991	SUH446			0.20	1.50	1.00	0.040	0.030	23.00-27.00			N 0.25
ISO 4955:1994	X15CrN26			0.20	1.0	1.0	0.040	0.030	24.0-28.0	1.0		N 0.15-0.25
ASTM A 240/A 240M-03c			S44735	0.030	1.00	1.00	0.040	0.030	28.0-30.0	1.00	3.6-4.2	(Ti+Cb) 0.20-1.00; (Ti+Cb) 6 x (C+N) min; N 0.045
EN 10088-2:1995	X2CrMoTi29-4	1.4592		0.025	1.00	1.00	0.030	0.010	28.00-30.00		3.50-4.50	N 0.045; Ti 4X(C+N)+0.15-0.80

8.1.2B Mechanical Properties of Ferritic Stainless Steels

Standard	Grade, Class,	Charl	UNS	Product Form/	Thic	kness	Yield Strer	ngth, min	Tensile Str	ength, min	Flannstian	Hardness,
Designation	Type, Symbol or Name	Steel Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	405		S40500	Pl, Sh, St			170	25	415	60	20.0	179/88/
JIS G 4304:1999	SUS405			PI, Sh, St/HR, A			175		410		20	183/88/200
JIS G 4305:1999	SUS405			Pl, Sh, St/CR, A			175		410		20	183/88/200
JIS G 4312:1991	SUS405			PI, Sh/HR or CR, A			175		410		20	183/88/200
				St/CR, A	≤ 6		230					
EN 10088-2:1995	X6CrAl13	1.4002		St/HR, A	≤ 12		210		400-600		17	/
				PI/HR, A	≤ 25		210					
ACTM A 040/A 040M 00-			S40977	Pl, Sh, St			280	41	450	65	18	180/88/
ASTM A 240/A 240M-03c			S41050	Pl, Sh, St			205	30	415	60	22	183/89/
				St/CR, A	≤ 6		280				20	
EN 10088-2:1995	X2CrNi12	1.4003		St/HR, A	≤ 12		280		450-650		20	/
				PI/HR, A	≤ 25		250				18	
JIS G 4312:1991	SUH409L			PI, Sh/HR or CR, A			175		360		25	162/80/175
EN 10088-2:1995	X2CrTi12	1.4512		St/CR, A St/HR, A	≤ 6		210		380-560		25	/
ASTM A 240/A 240M-03c	400		S43000	· · · · · · · · · · · · · · · · · · ·	≤ 12		005	30	450	65	00	100/00/
	430 SUS430			PI, Sh, St			205 205		450 450		22	183/89/
JIS G 4304:1999				PI, Sh, St/HR, A								183/88/200
JIS G 4305:1999	SUS430			PI, Sh, St/CR, A			205		450		22	183/88/200
JIS G 4312:1991	SUS430			PI, Sh/HR or CR, A			205		450		22	183/88/200
				St/CR, A	≤ 6		260		450-600		20	
EN 10088-2:1995	X6Cr17	1.4016		St/HR, A	≤ 12		240				18	/
				PI/HR, A	≤ 25		240		430-630		20	
JIS G 4304:1999	SUS430LX			Pl, Sh, St/HR, A			175		360		22	183/88/200
JIS G 4305:1999	SUS430LX			Pl, Sh, St/CR, A			175		360		22	183/88/200
	X2CrTi17	1.4520		St/CR, A	≤ 6		180		380-530		24	/
EN 10088-2:1995	X3CrTi17	1.4510		St/CR, A	≤ 6		230		420-600		23	//
211 10000 2.1000	7,0011117	11.1010		St/HR, A	≤ 12		200		120 000			
	X3CrNb17	1.4511		St/CR, A	≤ 6		230		420-600		23	/
ASTM A 240/A 240M-03c	434		S43400	Pl, Sh, St			240	35	450	65	22	/89/
JIS G 4304:1999	SUS434			Pl, Sh, St/HR, A			205		450		22	183/88/200
JIS G 4305:1999	SUS434			Pl, Sh, St/CR, A			205		450		22	183/88/200
EN 10088-2:1995	X6CrMo17-1	1.4113		St/CR, A	≤ 6		260		450-630		18	/
LIV 10000-2.1990	AUGINIO 17-1	1.4113		St/HR, A	≤ 12		200		450-050		10	

Standard	Grade, Class,	Steel	UNS	Product Form/	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	Hardness,
Designation	Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
	439		S43035	PI, Sh, St			205	30	415	60	22.0	183/89/
ASTM A 240/A 240M-03c			S43932	Pl, Sh, St			205	30	415	60	22.0	183/89/
			S43940	Pl, Sh, St			250	36	430	62	18	180/88/
EN 10088-2:1995	X2CrTiNb18	1.4509		St/CR, A	≤ 6		230		430-630		18	/
ASTM A 240/A 240M-03c	444		S44400	Pl, Sh, St			275	40	415	60	20.0	217/96/
JIS G 4304:1999	SUS444			Pl, Sh, St/HR, A			245		410		20	217/96/230
JIS G 4305:1999	SUS444			Pl, Sh, St/CR, A			245		410		20	217/96/230
				St/CR, A	≤ 6		300		420-640			
EN 10088-2:1995	X2CrMoTi18-2	1.4521		St/HR, A	≤ 12		280		400-600		20	/
				PI/HR, A	≤ 12		280		420-620			
ASTM A 176-99	446		S44600	PI, Sh, St/A			275	40	515	65	20.0	217/96/
JIS G 4312:1991	SUH446			PI, Sh/HR or CR, A			275		510		20	201/95/210
ISO 4955:1994	X15CrN26			PI, Sh, St/TA			280		500-700		see standard	212//
ASTM A 240/A 240M-03c			S44735	Pl, Sh, St			415	60	550	80	18	255/25/
EN 10088-2:1995	X2CrMoTi29-4	1.4592		St/CR, A	≤ 6		430		550-700		20	/

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %,	max, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 666-03	201		S20100	0.15	5.5-7.5	0.75	0.060	0.030	16.0-18.0	3.5-5.5		N 0.25
ASTM A 240/A 240M-03c	201		S20100	0.15	5.5-7.5	1.00	0.060	0.030	16.0-18.0	3.5-5.5		N 0.25
EN 10088-2:1995	X12CrMnNiN17-7-5	1.4372		0.15	5.50-7.50	1.00	0.045	0.015	16.00-18.00	3.50-5.50		N 0.05-0.25
ASTM A 666-03	201L		S20103	0.03	5.5-7.5	0.75	0.045	0.030	16.0-18.0	3.5-5.5		N 0.25
ASTIVI A 000-03	201LN		S20153	0.03	6.4-7.5	0.75	0.045	0.015	16.0-17.5	4.0-5.0		N 0.10-0.25; Cu 1.00
ASTM A 240/A 240M-03c	201L		S20103	0.03	5.5-7.5	0.75	0.045	0.030	16.0-18.0	3.5-5.5		N 0.25
ASTIVI A 240/A 240IVI-030	201LN		S20153	0.03	6.4-7.5	0.75	0.045	0.015	16.0-17.5	4.0-5.0		N 0.10-0.25; Cu 1.00
EN 10088-2:1995	X2CrMnNiN17-7-5	1.4371		0.030	6.00-8.00	1.00	0.045	0.015	16.00-17.00	3.50-5.50		N 0.15-0.20
ASTM A 666-03	202		S20200	0.15	7.5-10.0	0.75	0.060	0.030	17.0-19.0	4.0-6.0		N 0.25
ASTM A 240/A 240M-03c	202		S20200	0.15	7.5-10.0	1.00	0.060	0.030	17.0-19.0	4.0-6.0		N 0.25
EN 10088-2:1995	X12CrMnNiN18-9-5	1.4373		0.15	7.50-10.50	1.00	0.045	0.015	17.00-19.00	4.00-6.00		N 0.05-0.25
ASTM A 666-03	301		S30100	0.15	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.10
ASTM A 240/A 240M-03c	301		S30100	0.15	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.10
IIC C 4004:4000	SUS301			0.15	2.00	1.00	0.045	0.030	16.00-18.00	6.00-8.00		
JIS G 4304:1999	SUS301J1			0.08-0.12	2.00	1.00	0.045	0.030	16.00-18.00	7.00-9.00		
JIS G 4305:1999	SUS301			0.15	2.00	1.00	0.045	0.030	16.00-18.00	6.00-8.00		
JIS G 4305:1999	SUS301J1			0.08-0.12	2.00	1.00	0.045	0.030	16.00-18.00	7.00-9.00		
EN 10088-2:1995	X10CrNi18-8	1.4310		0.05-0.15	2.00	2.00	0.045	0.015	16.00-19.00	6.00-9.50	0.80	N 0.11
ASTM A 240/A 240M-03c	301L		S30103	0.03	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.20
ASTM A 666-03	301L		S30103	0.03	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.20
JIS G 4304:1999	SUS301L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	6.00-8.00		N 0.20
JIS G 4305:1999	SUS301L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	6.00-8.00		N 0.20
ASTM A 240/A 240M-03c	301LN		S30153	0.03	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.07-0.20
ASTM A 666-03	301LN		S30153	0.03	2.00	1.00	0.045	0.030	16.0-18.0	6.0-8.0		N 0.07-0.20
EN 10088-2:1995	X2CrNiN18-7	1.4318		0.030	2.00	1.00	0.045	0.015	16.50-18.50	6.00-8.00		N 0.10-0.20
ASTM A 240/A 240M-03c	302		S30200	0.15	2.00	0.75	0.045	0.030	17.0-19.0	8.0-10.0		N 0.10
ASTM A 666-03	302		S30200	0.15	2.00	0.75	0.045	0.030	17.0-19.0	8.0-10.0		
JIS G 4304:1999	SUS302			0.15	2.00	1.00	0.045	0.030	17.00-19.00	8.00-10.00		
JIS G 4305:1999	SUS302			0.15	2.00	0.75	0.045	0.030	17.00-19.00	8.00-10.00		
ASTM A 167-99	302B		S30215	0.15	2.00	2.00-3.00	0.045	0.030	17.0-19.0	8.0-10.0		N 0.10
JIS G 4304:1999	SUS302B			0.15	2.00	2.00-3.00	0.045	0.030	17.00-19.00	8.00-10.00		
JIS G 4305:1999	SUS302B			0.15	2.00	2.00-3.00	0.045	0.030	17.00-19.00	8.00-10.00		
JIS G 4312:1991	SUS302B			0.15	2.00	2.00-3.00	0.045	0.030	17.00-19.00	8.00-10.00		

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %,	max, Unless	Otherwise Sp	ecified	
Designation	Symbol or Name	Number	Number	C	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	304		S30400	0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10
ASTM A 666-03	304		S30400	0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10
JIS G 4304:1999	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
JIS G 4305:1999	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
JIS G 4312:1991	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
EN 10088-2:1995	X5CrNi18-10	1.4301		0.07	2.00	1.00	0.045	0.015	17.00-19.50	8.00-10.50		N 0.11
ISO 4955:1994	X7CrNi18-9			0.10	2.0	1.0	0.045	0.030	17.0-19.0	8.0-11.0		
ASTM A 240/A 240M-03c	304L		S30403	0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10
ASTM A 666-03	304L		S30403	0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10
JIS G 4304:1999	SUS304L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	9.00-13.00		
JIS G 4305:1999	SUS304L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	9.00-13.00		
EN 10000 0:1005	X2CrNi19-11	1.4306		0.030	2.00	1.00	0.045	0.015	18.00-20.00	10.00-12.00		N 0.11
EN 10088-2:1995	X2CrNi18-9	1.4307		0.030	2.00	1.00	0.045	0.015	17.50-19.50	8.00-10.00		N 0.11
ASTM A 240/A 240M-03c	305		S30500	0.12	2.00	0.75	0.045	0.030	17.0-19.0	10.5-13.0		
JIS G 4304:1999	SUS305			0.12	2.00	1.00	0.045	0.030	17.00-19.00	10.50-13.00		
JIS G 4305:1999	SUS305			0.12	2.00	1.00	0.045	0.030	17.00-19.00	10.50-13.00		
EN 10088-2:1995	X4CrNi18-12	1.4303		0.06	2.00	1.00	0.045	0.015	17.00-19.00	11.00-13.00		N 0.11
ASTM A 240/A 240M-03c	304N		S30451	0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
ASTM A 666-03	304N		S30451	0.08	2.00	0.75	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10-0.16
JIS G 4304:1999	SUS304N1			0.08	2.50	1.00	0.045	0.030	18.00-20.00	7.00-10.50		N 0.15-0.25
JIS G 4305:1999	SUS304N1			0.08	2.50	1.00	0.045	0.030	18.00-20.00	7.00-10.50		N 0.10-0.25
ASTM A 240/A 240M-03c	304LN		S30453	0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10-0.16
ASTM A 666-03	304LN		S30453	0.030	2.00	0.75	0.045	0.030	18.0-20.0	8.0-12.0		N 0.10-0.16
JIS G 4304:1999	SUS304LN			0.030	2.00	1.00	0.045	0.030	17.00-19.00	8.50-11.50		N 0.12-0.22
JIS G 4305:1999	SUS304LN			0.030	2.00	1.00	0.045	0.030	17.00-19.00	8.50-11.50		N 0.12-0.22
EN 10088-2:1995	X2CrNiN18-10	1.4311		0.030	2.00	1.00	0.045	0.015	17.00-19.50	8.50-11.50		N 0.12-0.22
ASTM A 240/A 240M-03c			S30600	0.018	2.00	3.7-4.3	0.020	0.020	17.0-18.5	14.0-15.5	0.20	Cu 0.50
EN 10088-2:1995	X1CrNiSi18-15-4	1.4361		0.015	2.00	3.70-4.50	0.025	0.010	16.50-18.50	14.00-16.00	0.20	N 0.11
ASTM A 167-99	309		S30900	0.20	2.00	0.75	0.045	0.030	22.0-24.0	12.0-15.0		
JIS G 4312:1991	SUH309			0.20	2.00	1.00	0.040	0.030	22.00-24.00	12.00-15.00		

Standard	Grade, Class, Type,	Steel	UNS					Weight,	%, max, Unles	s Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	309S		S30908	0.08	2.00	0.75	0.045	0.030	22.0-24.0	12.0-15.0		
JIS G 4304:1999	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
JIS G 4305:1999	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
JIS G 4312:1991	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
EN 10095:1999	X12CrNi23-13	1.4833		0.15	2.00	1.00	0.045	0.015	22.00-24.00	12.00-14.00		N 0.11
ISO 4955:1994	X6CrNi23-14			0.08	2.0	1.0	0.045	0.030	22.0-24.0	12.0-15.0		
ASTM A 167-99	310		S31000	0.25	2.00	1.50	0.045	0.030	24.0-26.0	19.0-22.0		
JIS G 4312:1991	SUH310			0.25	2.00	1.50	0.040	0.030	24.00-26.00	19.00-22.00		
ASTM A 240/A 240M-03c	310S		S31008	0.08	2.00	1.50	0.045	0.030	24.0-26.0	19.0-22.0		
JIS G 4304:1999	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		
JIS G 4305:1999	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		
JIS G 4312:1991	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		
ISO 4955:1994	X6CrNi25-21			0.08	2.0	1.5	0.045	0.030	24.0-26.0	19.0-22.0		
ASTM A 240/A 240M-03c	310MoLN		S31050	0.20	2.00	0.50	0.030	0.010	24.0-26.0	20.5-23.5	1.60-2.60	N 0.09-0.15
EN 10088-2:1995	X1CrNiMoN25-22-2	1.4466		0.20	2.00	0.70	0.025	0.010	24.00-26.00	21.0-23.0	2.00-2.50	N 0.10-0.16
ASTM A 240/A 240M-03c			S31254	0.20	1.00	0.80	0.030	0.010	19.5-20.5	17.5-18.5	6.0-6.5	N 0.18-0.22; Cu 0.50-1.00
EN 10088-2:1995	X1CrNiMoCuN20-18-7	1.4547		0.20	1.00	0.70	0.030	0.010	19.50-20.50	17.50-18.50	6.00-7.00	N 0.18-0.25; Cu 0.50-1.00
ASTM A 240/A 240M-03c	316		S31600	0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
ASTM A 666-03	316		S31600	0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 4304:1999	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 4305:1999	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 4312:1991	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
EN 10088-2:1995	X5CrNiMo17-12-2	1.4401		0.07	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10066-2.1995	X3CrNiMo17-13-3	1.4436		0.05	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
ASTM A 240/A 240M-03c	316L		S31603	0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10
ASTM A 666-03	316L		S31603	0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 4304:1999	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
JIS G 4305:1999	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
	X2CrNiMo17-12-2	1.4404		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10088-2:1995	X2CrNiMo17-12-3	1.4432		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
	X2CrNiMo18-14-3	1.4435		0.030	2.00	1.00	0.045	0.015	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
ASTM A 240/A 240M-03c	316N		S31651	0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10-0.16
ASTM A 666-03	316N		S31651	0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10-0.16
JIS G 4304:1999	SUS316N			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	N 0.10-0.22
JIS G 4305:1999	SUS316N			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	N 0.10-0.22

Standard	Grade, Class, Type,	Steel	UNS				1	Weight, %	, max, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	316LN		S31653	0.030	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10-0.16
JIS G 4304:1999	SUS316LN			0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-14.50	2.00-3.00	N 0.12-0.22
JIS G 4305:1999	SUS316LN			0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-14.50	2.00-3.00	N 0.12-0.22
EN 10088-2:1995	X2CrNiMoN17-11-2	1.4406		0.030	2.00	1.00	0.045	0.015	16.50-18.50	10.00-12.00	2.00-2.50	N 0.12-0.22
EN 10000-2.1995	X2CrNiMoN17-13-3	1.4429		0.030	2.00	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22
ASTM A 240/A 240M-03c	316Cb		S31640	0.08	2.00	0.75	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	Cb 10xC min, 1.10 max; N 0.10
EN 10088-2:1995	X6CrNiMoNb17-12-2	1.4580		0.08	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.50	2.00-2.50	Nb 10xC to 1.00
ASTM A 240/A 240M-03c	316Ti		S31635	0.08	2.00	0.75	0.045	0.030	16.00-18.0	10.0-14.0	2.0-3.0	Ti 5 x (C+N) min, 0.70 max
JIS G 4304:1999	SUS316Ti			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	Ti ≥ 5 x C
JIS G 4305:1999	SUS316Ti			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	Ti ≥ 5 x C
JIS G 4312:1991	SUS316Ti			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	Ti ≥ 5 x C
EN 10088-2:1995	X6CrNiMoTi17-12-2	1.4571		0.08	2.00	1.00	0.045	0.015	16.50-18.50	10.50-13.50	2.00-2.50	Ti 5 x C to 0.70
ASTM A 240/A 240M-03c	317L		S31700	0.030	2.00	0.75	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	N 0.10
JIS G 4304:1999	SUS317L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 4305:1999	SUS317L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
EN 10088-2:1995	X2NiCrMo18-15-4	1.4438		0.030	2.00	1.00	0.045	0.015	17.50-19.50	13.00-16.00	3.00-4.00	N 0.11
ASTM A 240/A 240M-03c	317LN		S31753	0.030	2.00	0.75	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	N 0.10-0.22
JIS G 4304:1999	SUS317LN			0.03	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	N 0.10-0.22
JIS G 4305:1999	SUS317LN			0.03	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	N 0.10-0.22
EN 10088-2:1995	X2CrNiMoN18-12-4	1.4434		0.030	2.00	1.00	0.045	0.015	16.50-19.50	10.50-14.00	3.00-4.00	N 0.10-0.20
ASTM A 240/A 240M-03c	317LMN		S31726	0.030	2.00	0.75	0.045	0.030	17.0-20.0	13.5-17.5	4.0-5.0	N 0.10-0.20
JIS G 4304:1999	SUS317J1			0.040	2.50	1.00	0.045	0.030	16.00-19.00	15.00-17.00	4.00-6.00	
JIS G 4305:1999	SUS317J1			0.040	2.50	1.00	0.045	0.030	16.00-19.00	15.00-17.00	4.00-6.00	
EN 10088-2:1995	X2CrNiMoN17-13-5	1.4439		0.030	2.00	1.00	0.045	0.015	16.50-18.50	12.50-14.50	4.00-5.00	N 0.12-0.22
ASTM A 240/A 240M-03c			N08367	0.030	2.00	1.00	0.040	0.030	20.0-22.0	23.5-25.5	6.0-7.0	N 0.18-0.25
ASTM B 688-96			N08366	0.035	2.00	1.00	0.040	0.030	20.00-22.00	23.50-25.50	6.00-7.00	
A31W D 000-90			N08367	0.030	2.00	1.00	0.040	0.030	20.00-22.00	23.50-25.50	6.00-7.00	N 0.18-0.25; Cu 0.75
JIS G 4304:1999	SUS836L			0.030	2.00	1.00	0.045	0.030	19.00-24.00	24.00-26.00	5.00-7.00	N 0.25
JIS G 4305:1999	SUS836L			0.030	2.00	1.00	0.045	0.030	19.00-24.00	24.00-26.00	5.00-7.00	N 0.25
EN 10088-2:1995	X1NiCrMoCuN25-20-7	1.4529		0.020	1.00	0.50	0.030	0.010	19.00-21.00	24.00-26.00	6.00-7.00	N 0.15-0.25; Cu 0.50-1.50
ASTM A 240/A 240M-03c	904L		N08904	0.020	2.00	1.00	0.045	0.035	19.0-23.0	23.0-28.0	4.0-5.0	N 0.10; Cu 1.0-2.0
ASTM B 625-99			N08904	0.020	2.00	1.00	0.045	0.035	19.00-23.00	23.00-28.00	4.0-5.0	Cu 1.0-2.0; Fe bal
JIS G 4304:1999	SUS890L			0.020	2.00	1.00	0.045	0.030	19.00-23.00	23.00-28.00	4.00-5.00	Cu 1.00-2.00
JIS G 4305:1999	SUS890L			0.020	2.00	1.00	0.045	0.030	19.00-23.00	23.00-28.00	4.00-5.00	Cu 1.00-2.00
EN 10088-2:1995	X1NiCrMoCu25-20-5	1.4539		0.020	2.00	0.70	0.030	0.010	19.00-21.00	24.00-26.00	4.00-5.00	N 0.15; Cu 1.20-2.00

Standard	Grade, Class, Type,	Steel	UNS					Weight, %	, max, Unless	Otherwise S	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	321		S32100	0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x (C+N) min, 0.70 max
JIS G 4304:1999	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti ≥ 5 x C
JIS G 4305:1999	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti ≥ 5 x C
JIS G 4312:1991	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti ≥ 5 x C
EN 10088-2:1995	X6CrNiTi18-10	1.4541		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
ISO 4955:1994	X7CrNiTi18-10			0.040-0.10	2.0	1.0	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
ASTM A 240/A 240M-03c	347		S34700	0.08	2.00	0.75	0.045	0.030	17.0-19.0	9.0-13.0		Cb 10 x C min, 1.00 max
JIS G 4304:1999	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb ≥ 10 x C
JIS G 4305:1999	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb ≥ 10 x C
JIS G 4312:1991	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb ≥ 10 x C
EN 10088-2:1995	X6CrNiNb18-10	1.4550		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ISO 4955:1994	X7CrNiNb18-10			0.040-0.10	2.0	1.0	0.045	0.030	17.0-19.0	9.0-12.0		Nb 10 x C to 1.2

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Florestion	Hardness,
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm² or MPa	ksi	Elongation, min, %	max HB/HRB/HV
				PI, Sh, St/A			260	38	515	75	40	217/95/
				PI, Sh, St/CW, 1/16 Hard			310	45	655	95	40	/
				PI, Sh, St/CW, 1/8 Hard			380	55	690	100	45	//
				Pl, Sh, St/CW, 1/4 Hard			515	75	860	125	25	//
	004 014		000400			< 0.015					15	
ASTM A 666-03	201, Class 1		S20100	PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	18	/
						< 0.015					10	
				PI, Sh, St/CW, ¾ Hard		≥ 0.015	930	135	1205	175	12	/
						< 0.015					8	
				PI, Sh, St/CW, Full Hard		≥ 0.015	965	140	1275	185	9	/
	201, Class 2		S20100	PI, Sh, St/A			310	45	655	95	40	241/100/
AOTA A 040/A 040A 00	201-1		S20100	Pl, Sh, St			260	38	515	75	40	241/100/
ASTM A 240/A 240M-03c	201-2		S20100	Pl, Sh, St			310	45	655	95	40	241/100/
				St/CR, AT	≤ 6		350				4-	
EN 10088-2:1995	X12CrMnNiN17-7-5	1.4372		St/HR, AT	≤ 12		330		750-950		45	//
				PI/HR, AT	≤ 75		330				40	
				PI, Sh, St/A			260	38	655	95	40	217/95/
				PI, Sh, St/CW, 1/16 Hard			345	50	690	100	40	
				PI, Sh, St/CW, 1/8 Hard			380	55	725	105	35	
	201L		S20103	PI, Sh, St/CW, ¼ Hard			515	75	825	120	25	//
						≤ 0.030					22	
				PI, Sh, St/CW, ½ Hard		> 0.030	690	100	930	135	20	
ASTM A 666-03				Pl. Sh. St/A			310	45	655	95	45	241/100/
				PI, Sh, St/CW, 1/16 Hard			345	50	690	100	40	211,100,
				Pl, Sh, St/CW, 1/8 Hard			415	60	760	110	35	-
	201LN		S20153	Pl, Sh, St/CW, 1/4 Hard			515	75	825	120	25	/
				FI, SII, SI/CVV, 74 Haiu		≤ 0.030	313	7.5	023	120	22	
				PI, Sh, St/CW, ½ Hard		> 0.030	690	100	930	135	20	-
	201L		S20103	PI, Sh, St		> 0.030	260	38	655	95	40	217/95/
ASTM A 240/A 240M-03c	201LN		S20153	PI, Sh, St			310	45	655	95	45	241/100/
	ZOILIN		020100	St/CR, AT	≤ 6		300					241/100/
EN 10088-2:1995	X2CrMnNiN17-7-5	1.4371		St/HR, AT	<u>≤</u> 0		280		650-850		45	/
2.1 10000 2.1000	XLONIIII III 7 7 0	1		PI/HR, AT	<u> </u>		280		630-830		35	
				PI, Sh, St/A	≥ /3 		260	38	620	90	40	241//
ASTM A 666-03	202		S20200	Pl, Sh, St/CW, ¼ Hard		≤ 0.030	515		860	125	12	//
ASTM A 240/A 240M-03c	202		S20200	PI, SII, SI/CW, 1/4 Hard		≥ 0.030	260	38	620	90	40	241//
AUTIVI A 240/A 240/VI-030	202		020200	St/CR, AT	≤ 6		340			30	+0	241//
EN 10088-2:1995	X12CrMnNiN18-9-5	1.4373		St/HR, AT	≤0 ≤12		320		680-880		45	//
LIN 10000-2.1330	A 12 O I VIII II VIII VI 10-9-3	1.43/3		PI/HR, AT			320		600-800		35	,,
				PI/HK, A I	≤ 75		320		000-800		35	

Standard Designation	Crede Class Tune	Steel	UNS r Number	Product Form/ Heat Treatment	Thick	ness	Yield Strength, min		Tensile Strength, min		Elongation,	Hardness,
	Grade, Class, Type, Symbol or Name				t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	max HB/HRB/HV
				PI, Sh, St/A			205	30	515	75	40	217/95/
				PI, Sh, St/CW, 1/16 Hard			310	45	620	90	40	
				PI, Sh, St/CW, 1/8 Hard			380	55	690	100	40	
				PI, Sh, St/CW, 1/4 Hard			515	75	860	125	25	
ASTM A 666-03	301		S30100			< 0.015	700	110	1005	150	15	1
AS 1 W A 000-03	301		330100	PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	18	/
				DI Ob Ot/OW 3/ Hand		< 0.015	930	105	1005	175	10	
				PI, Sh, St/CW, ¾ Hard		≥ 0.015	930	135	1205	175	12	
				DI Ch Ct/CW Full Hard		< 0.015	965	140	1275	185	8	
				PI, Sh, St/CW, Full Hard		≥ 0.015	965	140		105	9	
ASTM A 240/A 240M-03c	301		S30100	Pl, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS301			PI, Sh, St/HR, S			205		520		40	207/95/218
	SUS301J1			PI, Sh, St/HR, S			205		570		45	187/90/200
				PI, Sh, St/CR, S			205		520		40	207/95/218
				PI, Sh, St/TRR, ¼ H	< 0.4		510				25	
					$0.4 \le t < 0.8$				860		25	/
					≥ 0.8						25	
					< 0.4				1030		9	/
				PI, Sh, St/TRR, ½ H	$0.4 \le t < 0.8$		755				10	
JIS G 4305:1999	SUS301				≥ 0.8						10	
010 0 4000.1000					< 0.4						3	
				PI, Sh, St/TRR, ¾ H	$0.4 \le t < 0.8$		930		1210		5	
					≥ 0.8						7	
				PI, Sh, St/TRR, H 0.4	< 0.4						3	
					0.4 ≤ t < 0.8		960		1270		4	
					≥ 0.8						5	
	SUS301J1			PI, Sh, St/CR, S			205		570		45	187/90/200
EN 10088-2:1995	X10CrNi18-8	1.4310		St/CR, AT	≤ 6		250		600-950		40	/

Standard	Grade, Class, Type,	Steel	UNS Number	Product Form/ Heat Treatment	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	Hardness,
Designation	Symbol or Name				t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	301L		S30103	PI, Sh, St			220	32	550	80	45	241/100/
				PI, Sh, St/A			220	32	550	80	45	241/100/
				PI, Sh, St/CW, 1/16 Hard			345	50	690	100	40	
ASTM A 666-03	301L		S30103	PI, Sh, St/CW, 1/8 Hard			415	60	760	110	35	//
				PI, Sh, St/CW, 1/4 Hard			515	75	825	120	25	
				PI, Sh, St/CW, 1/2 Hard			690	100	930	135	20	
JIS G 4304:1999	SUS301L			PI, Sh, St/HR, S			215		550		45	187/90/200
				PI, Sh, St/CR, S			215		550		45	207/95/218
				PI, Sh, St/TRR, 1/4 H			345		690		40	/
JIS G 4305:1999	SUS301L			PI, Sh, St/TRR, 1/2 H			410		760		35	/
				PI, Sh, St/TRR, ¾ H			480		820		25	//
				PI, Sh, St/TRR, H			685		930		20	/
ASTM A 240/A 240M-03c	301LN		S30153	PI, Sh, St			240	35	550	80	45	241/100/
			S30153	PI, Sh, St/A			240	35	550	80	45	241/100/
				PI, Sh, St/CW, 1/16 Hard			345	50	690	100	40	
ASTM A 666-03	301LN			PI, Sh, St/CW, 1/8 Hard			415	60	760	110	35	//
				PI, Sh, St/CW, 1/4 Hard			515	75	825	120	25	/
				PI, Sh, St/CW, 1/2 Hard			690	100	930	135	20	
	X2CrNiN18-7		3	St/CR, AT	≤ 6		350		650-850		35	
EN 10088-2:1995		1.4318		St/HR, AT	≤ 12		330		650-650		35	/
				PI/HR, AT	≤ 75		330		630-830		45	
ASTM A 240/A 240M-03c	302		S30200	PI, Sh, St			205	30	515	75	40	201/92/
				PI, Sh, St/A			205	30	515	75	40	201/92/
				PI, Sh, St/CW, 1/16 Hard			310	45	585	85	40	
				PI, Sh, St/CW, 1/8 Hard			380	55	690	100	35	
						≤ 0.030					10	_
				PI, Sh, St/CW, 1/4 Hard		> 0.030	515	75	860	125	12	
ASTM A 666-03	302		S30200			< 0.015					9	
AOTW A 000 00	302		000200	PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	10	/
											-	
				PI, Sh, St/CW, 3/4 Hard		< 0.015	930	135	1205	175	5	
						≥ 0.015					6	
				PI, Sh, St/CW, Full Hard		< 0.015	965	140	1275	185	3	
						≥ 0.015					4	
JIS G 4304:1999	SUS302			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS302			PI, Sh, St/CR, S			205		520		40	187/90/200

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thickn	ess	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	Hardness,
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 167-99	302B		S30215	PI, Sh, St/			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS302B			PI, Sh, St/HR, S			205		520		40	207/95/218
JIS G 4305:1999	SUS302B			Pl, Sh, St/CR, S			205		520		40	207/95/218
JIS G 4312:1991	SUS302B			PI, Sh/HR or CR, S			205		520		40	207/95/218
ASTM A 240/A 240M-03c	304		S30400	PI, Sh, St			205	30	515	75	40	201/92/
				PI, Sh, St/A			205	30	515	75	40	201/92/
				PI, Sh, St/CW, 1/16 Hard			310	45	550	80	35	
			'	PI, Sh, St/CW, 1/8 Hard			380	55	690	100	35	
ASTM A 666-03	304		S30400	DI OL 01/014/1/1/		≤ 0.030	515	75	000	105	10	1 , ,
				PI, Sh, St/CW, 1/4 Hard		> 0.030	515	75	860	125	12	/
				DI Ole ON/OWN 1/ Llevel		< 0.015	700	110	1005	150	6	_
				PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	7	
JIS G 4304:1999	SUS304			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS304			Pl, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS304			PI, Sh/HR or CR, S			205		520		40	187/90/200
				St/CR, AT	≤ 6		230		540-750			
EN 10088-2:1995	X5CrNi18-10	1.4301		St/HR, AT	≤ 12		210		500 700		45	/
			,	PI/HR, AT	≤ 75		210		520-720			
ISO 4955:1994	X7CrNi18-9			PI, Sh, St/TQ	0.5 ≤ a ≤ 75		195		500-700		see standard	192//
ASTM A 240/A 240M-03c	304L		S30403	Pl, Sh, St			170	25	485	70	40	201/92/
				PI, Sh, St/A			170	25	485	70	40	201/92/
				PI, Sh, St/CW, 1/16 Hard			310	45	550	80	40	
				PI, Sh, St/CW, 1/8 Hard			380	55	690	100	30	1
ASTM A 666-03	304L		S30403	DI OI: ONOM 1/ III-		≤ 0.030	515	75	860	125	8	/
				PI, Sh, St/CW, 1/4 Hard		> 0.030	515	75	860	125	10	
			'	DI Ch Ct/OW 1/ Hand		< 0.015	760	110	1035	150	5	
				PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	6	
JIS G 4304:1999	SUS304L			PI, Sh, St/HR, S			175		480		40	187/90/200
JIS G 4305:1999	SUS304L			Pl, Sh, St/CR, S			175		480		40	187/90/200
				St/CR, AT	≤ 6		220		E00 670			
	X2CrNi19-11	1.4306		St/HR, AT	≤ 12		200		520-670		45	/
EN 10000 0.1005			t	PI/HR, AT	≤ 75		200		500-650		45	
EN 10088-2:1995				St/CR, AT	≤ 6		220		520-670			/
	X2CrNi18-9	1.4307		St/HR, AT	≤ 12		200				45	
				PI/HR, AT	≤ 75		200		500-650			

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	Hardness,
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	305		S30500	Pl, Sh, St			170	25	485	70	40	183/88/
JIS G 4304:1999	SUS305			PI, Sh, St/HR, S			175		480		40	187/90/200
JIS G 4305:1999	SUS305			PI, Sh, St/CR, S			175		480		40	187/90/200
EN 10088-2:1995	X4CrNi18-12	1.4303		St/CR, A	≤ 6		220		500-650		45	/
ASTM A 240/A 240M-03c	304N		S30451	PI, Sh, St			240	35	550	80	30	217/95/
				PI, Sh, St/A			240	35	550	80	30	217/95/
				PI, Sh, St/CW, 1/16 Hard			310	45	620	90	40	
ACTM A CCC OO	304N		S30451	PI, Sh, St/CW, 1/8 Hard			380	55	690	100	37	1
ASTM A 666-03	304N		530451	PI, Sh, St/CW, 1/4 Hard			515	75	860	125	12	/
				DI OI 01/01/1/1/1		< 0.015	700	110	1005	150	6	-
				PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	8	
JIS G 4304:1999	SUS304N1			PI, Sh, St/HR, S			275		550		35	217/95/220
JIS G 4305:1999	SUS304N1			PI, Sh, St/CR, S			275		550		35	217/95/220
ASTM A 240/A 240M-03c	304LN		S30453	PI, Sh, St			205	30	515	75	40	217/95/
	304LN			PI, Sh, St/A			205	30	515	75	40	217/95/
			S30453	PI, Sh, St/CW, 1/16 Hard			310	45	620	90	40	
				PI, Sh, St/CW, 1/8 Hard			380	55	690	100	33	1
ASTM A 666-03				PI, Sh, St/CW, 1/4 Hard		≤ 0.030	515	75	000	105	10	/
						> 0.030			860	125	12	
				DI Ob OMOW 1/ Hand		< 0.015	760	110	1035	150	6	
				PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	7	
JIS G 4304:1999	SUS304LN			PI, Sh, St/HR, S			245		550		40	217/95/220
JIS G 4305:1999	SUS304LN			PI, Sh, St/CR, S			245		550		40	217/95/220
				St/CR, AT	≤ 6		290					
EN 10088-2:1995	X2CrNiN18-10	1.4311		St/HR, AT	≤ 12		270		550-750		40	/
				PI/HR, AT	≤ 75		270					
ASTM A 240/A 240M-03c			S30600	PI, Sh, St			240	35	540	48	40	/
EN 10088-2:1995	X1CrNiSi18-15-4	1.4361		PI/HR, AT	≤ 75		220		530-730		40	/
ASTM A 167-99	309		S30900	PI, Sh, St/			205	30	515	75	40	217/95/
JIS G 4312:1991	SUH309			PI, Sh/HR or CR, S			205		560		40	201/95/210

Standard	Grade, Class, Type,	Steel	UNS	Product Form/Heat Treatment	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	Hardness, max HB/HRB/HV
Designation	Symbol or Name	Number	Number		t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	
ASTM A 240/A 240M-03c	309S		S30908	PI, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS309S			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS309S			PI, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS309S			PI, Sh/HR or CR, A			205		520		40	187/90/200
EN 10095:1999	X12CrNi23-13	1.4833		PI, Sh, St/AT	≤ 75		210		500-700		see standard	192//
ISO 4955:1994	X6CrNi23-14			Pl, Sh, St/TQ			210		500-700		see standard	192//
ASTM A 167-99	310		S31000	Pl, Sh, St/			205	30	515	75	40	217/95/
JIS G 4312:1991	SUH310			PI, Sh/HR or CR, S			205		590		35	201/95/210
ASTM A 240/A 240M-03c	310S		S31008	Pl, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS310S			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS310S			Pl, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS310S			PI, Sh/HR or CR, A			205		520		40	187/90/200
ISO 4955:1994	X6CrNi25-21			PI, Sh, St/TQ	≤ 100		210		500-700		see standard	192//
ASTM A 240/A 240M-03c	310 MoLN		C010E0	DI Ch Ct		≤ 0.25	270	39	580	84	25	217/95/
ASTIVI A 240/A 240/VI-030	3 TO IVIOLIN		S31050	Pl, Sh, St		> 0.25	255	37	540	78	25	217/95/
EN 10088-2:1995	X1CrNiMoN25-22-2	1.4466		PI/HR, AT			250		540-740		40	/
ASTM A 240/A 240M-03c			S31254	Sh, St			310	35	690	100	35	223/96/
ASTIVI A 240/A 240/VI-030			331234	Pl			310	35	655	95	35	223/96/
				St/CR, AT	≤ 6		320				35	
EN 10088-2:1995	X1CrNiMoCuN20-18-7	1.4547		St/HR, AT	≤ 12		300		650-850		35	/
				PI/HR, AT	≤ 75		300				40	

Standard	Grade, Class, Type,	Steel	UNS Number	Product Form/Heat Treatment	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	Hardness,
Designation	Symbol or Name	Number			t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	316		S31600	Pl, Sh, St			205	30	515	75	40	217/95/
				PI, Sh, St/A			205	30	515	75	40	217/95/
				PI, Sh, St/CW, 1/16 Hard			310	45	585	85	35	
ASTM A 666-03	316		621600	PI, Sh, St/CW, 1/8 Hard			380	55	690	100	30	
ASTIVI A 000-03	310		S31600	PI, Sh, St/CW, 1/4 Hard			515	75	860	125	10	/
				Pl, Sh, St/CW, ½ Hard		< 0.015	760	110	1035	150	6	
				PI, SII, SI/GW, ½ naru		≥ 0.015	760	110	1035	150	7	
JIS G 4304:1999	SUS316			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS316			Pl, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS316			PI, Sh/HR or CR, A			205		520		40	187/90/200
				St/CR, AT	≤ 6		240		530-680		40	
	X5CrNiMo17-12-2	1.4401		St/HR, AT	≤ 12		220		530-660		40	/
EN 10088-2:1995				PI/HR, AT	≤ 75		220		520-670		45	
EN 10000-2.1995				St/CR, AT	≤ 6		240		FF0 700			
	X3CrNiMo17-13-3	1.4436		St/HR, AT	≤ 12		220		550-700		40	/
				PI/HR, AT	≤ 75		220		530-730			
ASTM A 240/A 240M-03c	316L		S31603	Pl, Sh, St			170	25	485	70	40	217/95/
	316L			PI, Sh, St/A			170	25	485	70	40	217/95/
			S31603	PI, Sh, St/CW, 1/16 Hard			310	45	585	85	35	/
				Flat Bar/CW, 1/16 Hard		>0.030	310	45	620	90	40	/
ASTM A 666-03				PI, Sh, St/CW, 1/8 Hard			380	55	690	100	25	/
				PI, Sh, St/CW, 1/4 Hard			515	75	860	125	8	/
				DI OI: OH/OM 1/ Hand		< 0.015	700	110	1005	150	5	
				PI, Sh, St/CW, ½ Hard		≥ 0.015	760	110	1035	150	6	/
JIS G 4304:1999	SUS316L			PI, Sh, St/HR, S			175		480		40	187/90/200
JIS G 4305:1999	SUS316L			Pl, Sh, St/CR, S			175		480		40	187/90/200
				St/CR, AT	≤ 6		240		530-680		40	
	X2CrNiMo17-12-2	1.4404		St/HR, AT	≤ 12		220		530-680		40	/
				PI/HR, AT	≤ 75		220		520-670		45	
				St/CR, AT	≤ 6		240		550 700			
EN 10088-2:1995	X2CrNiMo17-12-3	1.4432		St/HR, AT	≤ 12		220		550-700		40	/
		52		PI/HR, AT	≤ 75		220		520-670		45	
				St/CR, AT	≤ 6		240		FF0 700		40	
	X2CrNiMo18-14-3	1.4435		St/HR, AT	≤ 12		220		550-700		40	/
				PI/HR, AT	≤ 75		220		520-670		45	

Standard	Grade, Class, Type,	Steel	UNS	Product Form/Heat	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness,
Designation	Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	316N		S31651	PI, Sh, St			240	35	550	80	35	217/95/
				PI, Sh, St/A			240	35	550	80	35	217/95/
				PI, Sh, St/CW, 1/16 Hard			310	45	620	90	35	
ASTM A 666-03	316N		S31651	PI, Sh, St/CW, 1/8 Hard			380	55	690	100	32	
ASTIVI A 000-03	STOIN		331031	PI, Sh, St/CW, 1/4 Hard			515	75	860	125	12	/
				Pl, Sh, St/CW, ½ Hard		< 0.015	760	110	1035	150	6	
				PI, SII, SI/CVV, 1/2 maru		≥ 0.015	760	110	1035	150	8	
JIS G 4304:1999	SUS316N			PI, Sh, St/HR, S			275		550		35	217/95/220
JIS G 4305:1999	SUS316N			Pl, Sh, St/CR, S			275		550		35	217/95/220
ASTM A 240/A 240M-03c	316LN		S31653	Pl, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS316LN			PI, Sh, St/HR, S			245		550		40	217/95/220
JIS G 4305:1999	SUS316LN			PI, Sh, St/CR, S			245		550		40	217/95/220
				St/CR, AT	≤ 6		300					
	X2CrNiMoN17-11-2	1.4406		St/HR, AT	≤ 12		280		580-780		40	/
EN 10000 0:1005				PI/HR, AT	≤ 75		280					
EN 10088-2:1995	:: 1995			St/CR, AT	≤ 6		300				05	
	X2CrNiMoN17-13-3	1.4429		St/HR, AT	≤ 12		280		580-780		35	/
				PI/HR, AT	≤ 75		280		1		40	
ASTM A 240/A 240M-03c	316Cb		S31640	Pl, Sh, St			205	30	515	75	30	217/95/
EN 10088-2:1995	X6CrNiMoNb17-12-2	1.4580		PI/HR, AT	≤ 75		220		520-720		40	/
ASTM A 240/A 240M-03c	316Ti		S31635	Pl, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS316Ti			PI, Sh, St/HR, S			205		520		40	187/90//200
JIS G 4305:1999	SUS316Ti			Pl, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS316Ti			PI, Sh/HR or CR, A			205		520		40	187/90//200
				St/CR, AT	≤ 6		240		540-690			
EN 10088-2:1995	X6CrNiMoTi17-12-2	1.4571		St/HR, AT	≤ 12		220		540-690		40	/
				PI/HR, AT	≤ 75		220		520-670			
ASTM A 240/A 240M-03c	317L		S31700	Pl, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS317L			PI, Sh, St/HR, S			175		480		40	187/90/200
JIS G 4305:1999	SUS317L			Pl, Sh, St/CR, S			175		480		40	187/90/200
				St/CR, AT	≤ 6		240				25	
EN 10088-2:1995	X2NiCrMo18-15-4	1.4438		St/HR, AT	≤ 12		220		550-700		35	/
				PI/HR, AT	≤ 75		220		520-720		40	

Standard	Grade, Class, Type,	Steel	UNS	Product Form/Heat	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness,
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	317LN		S31753	PI, Sh, St			240	35	550	80	40	217/95/
JIS G 4304:1999	SUS317LN			PI, Sh, St/HR, S			245		550		40	217/95/220
JIS G 4305:1999	SUS317LN			PI, Sh, St/CR, S			245		550		40	217/95/220
				St/CR, AT	≤ 6		290		570-770		35	
EN 10088-2:1995	X2CrNiMoN18-12-4	1.4434		St/HR, AT	≤ 12		270		570-770		35	/
				PI/HR, AT	≤ 75		270		540-740		40	1
ASTM A 240/A 240M-03c	317LMN		S31726	Pl, Sh, St			240	35	550	80	40	223/96/
JIS G 4304:1999	SUS317J1			PI, Sh, St/HR, S			175		480		40	187/90/200
JIS G 4305:1999	SUS317J1			PI, Sh, St/CR, S			175		480		40	187/90/200
				St/CR, AT	≤ 6		290				35	
EN 10088-2:1995	X2CrNiMoN17-13-5	1.4439		St/HR, AT	≤ 12		270		580-780		35	/
				PI/HR, AT	≤ 75		270				40	1
ASTM A 240/A 240M-03c			N08367	Sh, St			310	45	690	100	30	/100/
ASTIVI A 240/A 240/VI-030			1106367	PI			310	45	655	95	30	241//
			N08366	PI, Sh, St/HR or CR	≤ 4.8	≤ 3/16	240	35	515	75	30	/95/
ASTM B 688-96			1100300	ri, Sii, Si/fin di Ch	> 4.8	> 3/16	240	33	515	75	30	212//
A21M D 000-90			N08367	PI, Sh, St/HR or CR	≤ 4.8	≤ 3/16	310	45	690	100	30	/100/
			1106367	PI, SII, SI/HR OF CR	> 4.8	> 3/16	310	45	655	95	30	240//
JIS G 4304:1999	SUS836L			Pl, Sh, St/HR, S			275		640		40	217/96/230
JIS G 4305:1999	SUS836L			PI, Sh, St/CR, S			275		640		40	217/96/230
EN 10088-2:1995	1XNiCrMoCuN25-20-7	1.4529		PI/HR, AT	≤ 75		300		650-850		40	/
ASTM A 240/A 240M-03c	904L		N08904	Pl, Sh, St			220	31	490	71	35	/90/
ASTM B 625-99			N08904	Pl, Sh, St/HR or CR, A			215	31	490	71	35	/70-90/
JIS G 4304:1999	SUS890L			PI, Sh, St/HR, S			215		490		35	187/90/200
JIS G 4305:1999	SUS890L			PI, Sh, St/CR, S			215		490		35	187/90/200
				St/CR, AT	≤ 6		240		500 700			
EN 10088-2:1995	X1NiCrMoCu25-20-5	1.4539		St/HR, AT	≤ 12		220		530-730		35	/
				PI/HR, AT	≤ 75		220		520-720		1	

Standard	Grade, Class, Type,	Steel	UNS	Product Form/Heat	Thick	ness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	Hardness,
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 240/A 240M-03c	321		S32100	Pl, Sh, St			205	30	515	75	40	217/95/
JIS G 4304:1999	SUS321			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS321			PI, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS321			PI, Sh/HR or CR, A			205		520		40	187/90/200
				St/CR, AT	≤ 6		220		520-720			
EN 10088-2:1995	X6CrNiTi18-10	1.4541		St/HR, AT	≤ 12		200		520-720		40	/
	7000 Z.1333			PI/HR, AT	≤ 75		200		500-700			
ISO 4955:1994	X7CrNiTi18-10			Pl, Sh, St/TQ			200		510-710		see standard	192//
ASTM A 240/A 240M-03c	347		S34700	Pl, Sh, St			205	30	515	75	40	201/92/
JIS G 4304:1999	SUS347			PI, Sh, St/HR, S			205		520		40	187/90/200
JIS G 4305:1999	SUS347			Pl, Sh, St/CR, S			205		520		40	187/90/200
JIS G 4312:1991	SUS347			PI, Sh/HR or CR, A			205		520		40	187/90/200
				St/CR, AT	≤ 6		220		500 700			
EN 10088-2:1995	X6CrNiNb18-10	1.4550	1	St/HR, AT	≤ 12		200		520-720		40	/
				PI/HR, AT	≤ 75		200		500-700			
ISO 4955:1994	X7CrNiNb18-10			PI, Sh, St/TQ			205		510-710		see standard	192//

8.1.4A Chemical Composition of Precipitation-Hardening Stainless Steels

Standard	Grade, Class, Type,	Steel	UNS				W	eight, %, r	nax, Unless C	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 693-03	630		S17400	0.07	1.00	1.00	0.040	0.030	15.0-17.5	3.0-5.0		Cu 3.0-5.0; Nb+Ta 0.15-0.45
JIS G 4304:1999	SUS630			0.07	1.00	1.00	0.040	0.030	15.50-17.50	3.00-5.00		Cu 3.00-5.00; Nb 0.15-0.45
JIS G 4305:1999	SUS630			0.07	1.00	1.00	0.040	0.030	15.00-17.50	3.00-5.00		Cu 3.00-5.00; Nb 0.15-0.45
JIS G 4312:1991	SUS630			0.07	1.00	1.00	0.040	0.030	15.50-17.50	3.00-5.00		Cu 3.00-5.00; Nb 0.15-0.45
EN 10088-2:1995	X5CrNiCuNb16-4	1.4542		0.07	1.50	0.70	0.040	0.015	15.00-17.00	3.00-5.00	0.60	Cu 3.00-5.00; Nb 5 x C to 0.45
ASTM A 693-03	631		S17700	0.09	1.00	1.00	0.040	1.00	16.00-18.00	6.5-7.7		AI 0.75-1.50
JIS G 4304:1999	SUS631			0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.50-7.75		AI 0.75-1.50
JIS G 4305:1999	SUS631			0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.50-7.75		AI 0.75-1.50
JIS G 4312:1991	SUS631			0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.50-7.75		AI 0.75-1.50
EN 10088-2:1995	X7CrNiAl17-7	1.4568		0.09	1.00	0.70	0.040	0.015	16.00-18.00	6.50-7.80		Al 0.70-1.50
ASTM A 693-03	632		S15700	0.09	1.00	1.00	0.040	0.030	14.00-16.00	6.5-7.7	2.00-3.00	Al 0.75-1.50
EN 10088-2:1995	X8CrNiMoAl15-7-2	1.4532		0.10	1.20	0.70	0.040	0.015	14.00-16.00	6.50-7.80	2.00-3.00	Al 0.70-1.50

8.1.4B Mechanical Properties of Precipitation-Hardening Stainless Steels

Standard G	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
	Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
				PI, Sh, St/ S	0.038 ≤ t < 102	0.0015≤ t < 4.0						363/38/
				DI OI: 01/	t < 4.765	t < 0.1875	1170	170	1310	190	5	/40-48/
				PI, Sh, St/ PHT: 900	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	1170	170	1310	190	8	388-477/40-48/
				F111. 900	15.90 ≤ t < 102	0.625 ≤ t < 4.0	1170	170	1310	190	10	388-477/40-48/
				DI Ch Ct/	t < 4.765	t < 0.1875	1070	155	1170	170	5	/38-46/
				PI, Sh, St/ PHT: 925	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	1070	155	1170	170	8	375-477/38-47/
				F111. 923	15.90 ≤ t < 102	0.625 ≤ t < 4.0	1070	155	1170	170	10	375-477/38-47/
				DI Ch Ct/	t < 4.765	t < 0.1875	1000	145	1070	155	5	/35-43/
				PI, Sh, St/ PHT: 1025	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	1000	145	1070	155	8	321-415/33-42/
				FH1. 1025	15.90 ≤ t < 102	0.625 ≤ t < 4.0	1000	145	1070	155	12	321-415/33-42/
ASTM A 693-03	630		S17400	DI 01 01/	t < 4.765	t < 0.1875	860	125	1000	145	5	/31-40/
				PI, Sh, St/ PHT: 1075	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	860	125	1000	145	9	293-375/29-38/
				PH1: 10/5	15.90 ≤ t < 102	0.625 ≤ t < 4.0	860	125	1000	145	13	293-375/29-38/
				D1 01 01/	t < 4.765	t < 0.1875	790	115	965	140	5	/31-40/
				PI, Sh, St/ PHT: 1100	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	790	115	965	140	10	293-375/29-38/
				PH1: 1100	15.90 ≤ t < 102	0.625 ≤ t < 4.0	790	115	965	140	14	93-375/29-38/
				D1 01 01/	t < 4.765	t < 0.1875	725	105	930	135	8	/28-38/
				PI, Sh, St/ PHT: 1150	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	725	105	930	135	10	269-352/ 26-36/
				PH1: 1150	15.90 ≤ t < 102	0.625 ≤ t < 4.0	725	105	930	135	16	269-352/ 26-36/
				DI 01 01/	t < 4.765	t < 0.1875	515	75	790	115	9	255-331/26-36/
				PI, Sh, St/ PHT: 1400+1150	4.762 ≤ t < 15.90	0.1875 ≤ t < 0.625	515	75	790	115	11	248-321/24-34/
				PH1: 1400+1150	15.90 ≤ t < 102	0.625 ≤ t < 4.0	515	75	790	115	18	248-321/24-34/
				PI, Sh, St/ HR, S								/38/
				PI, Sh, St/	≤ 5						5	
				HR, H900	5 < t ≤ 15		1175		1310		8	/40 min/
				1111, 11000	> 15						10	
				PI, Sh, St/	≤ 5						5	
IS G 4304:1999	SUS630			HR, H1025	5 < t ≤ 15		1000		1070		8	/35 min/
13 G 4304.1999	303030			1111, 111025	> 15						12	
				DI Ch Ct/	≤ 5						5	
				PI, Sh, St/ HR, H1075	5 < t ≤ 15		860		1000		9	/31 min/
				1111, 111073	> 15						13	
				DI Ch Ct/	≤ 5						8	
				PI, Sh, St/ HR, H1150	5 < t ≤ 15		725		930		10	/28 min/
				1111, 1111100	> 15						16	

NOTE: This section continued on next page.

8.1.4B Mechanical Properties of Precipitation-Hardening Stainless Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	Hardness, max
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
				PI, Sh, St/ CR, S								363/38/
				PI, Sh, St/	≤ 5		1175		1310		5	375 min/40 min/
				CR, H900	5 < t ≤ 15		1175		1310		8	373 11111/40 11111/
JIS G 4305:1999	SUS630			PI, Sh, St/	≤ 5		1000		1070		5	331 min/35 min/
JIS G 4305.1999	505630			CR, H1025	5 < t ≤ 15		1000		1070		8	331 11111/33 11111/
				PI, Sh, St/	≤ 5		860		1000		5	302 min/31 min/
				CR, H1075	5 < t ≤ 15		800		1000		9	302 11111/31 11111/
				PI, Sh, St/	≤ 5		725		930		8	277 min/28 min/
				CR, H1150	5 < t ≤ 15		725		930		10	277 11111/20 11111/
				PI, Sh/ HR or CR, S								363/38/
			PI, Sh/	≤ 5		1175		1310		5	375 min/40 min/	
				HR or CR, H900	5 < t ≤ 15		11/5		1310		8	3/3 11111/40 11111/
JIS G 4312:1991	CLICCOO			PI, Sh/	≤ 5		1000		1070		5	331 min/35 min/
JIS G 4312:1991	SUS630			HR or CR, H1025	5 < t ≤ 15		1000		1070		8	331 11111/33 11111/
				PI, Sh/	≤ 5		860		1000		5	302 min/31 min/
				HR or CR, H1075	5 < t ≤ 15		800		1000		9	302 11111/31 11111/
				PI, Sh/	≤ 5		725		930		8	277 min/28 min/
				HR or CR, H1150	5 < t ≤ 15		725		930		10	277 11111/20 11111/
				St/ CR, AT					≤ 1275		5	
				St/ CR, P1300	≤ 6		1150		≥ 1300		3	/
				St/ CR, P900			700		≥ 900		6	
EN 10088-2:1995	X5CrNiCuNb16-4	1.4542		Pl/ HR, P1070			1000		1070-1270		8	
				Pl/ HR, P950	< 50		800		950-1150		10	/
				Pl/ HR, P850	≤ 50		600		850-1050		12	/
				PI/ HR, SR630					≤ 1050			

8.1.4B Mechanical Properties of Precipitation-Hardening Stainless Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thic	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
				PI, Sh, St/	t < 0.25	t < 0.010	450	65	1035	150		
				S	$0.25 \le t < 102$	$0.010 \le t < 4.0$	380	55	1035	150	20	/92 HRB/
					$0.038 \le t < 0.127$	$0.0015 \le t < 0.0050$	1035	150	1240	180		/38/
				PI, Sh, St/	$0.127 \le t < 0.25$	$0.0050 \le t < 0.0010$	1035	150	1240	180		/38/
				PHT:	$0.25 \le t < 0.51$	0.010 ≤ t < 0.020	1035	150	1240	180		/38/
				1400+55+1050	$0.51 \le t < 4.762$	$0.020 \le t < 0.1875$	1035	150	1240	180		/38/
					$4.762 \le t < 15.88$	0.1875 ≤ t < 0.625	965	140	1170	170	20	/38/
ASTM A 693-03	631		S17700	_, _, _,	0.038 ≤ t < 0.127	0.0015 ≤ t < 0.0050	1310	190	1450	210		/44/
7.01W 7. 000 00	001		017700	PI, Sh, St/ PHT:	0.127 ≤ t < 0.25	0.0050 ≤ t < 0.0010	1310	190	1450	210		/44/
				1750+	0.25 ≤ t < 0.51	0.010 ≤ t < 0.020	1310	190	1450	210		/44/
				minus 100+950	0.51 ≤ t < 4.762	0.020 ≤ t < 0.1875	1310	190	1450	210		/44/
				11111100 1001000	4.762 ≤ t < 15.88	0.1875 ≤ t < 0.625	1240	180	1380	200	20	/43/
				PI, Sh, St/ CR	0.038 ≤ t < 0.13	0.0015 ≤ t < 0.0050	1205	175	1380	200		/41/
				PI, Sh, St/ CR + PHT: 900	0.038 ≤ t < 0.13	0.0015 ≤ t < 0.0050	1580	230	1655	240		/46/
				PI, Sh, St/ HR, S			380		1030		20	/92/200
110.0.4004.4000	0110004			Pl, Sh, St/	≤3		000		1110		3	/OF main /OAF main
JIS G 4304:1999	SUS631			HR, TH1050	> 3		960		1140		5	/35 min/345 min
				PI, Sh, St/	≤ 3		1030		1230			/40 min/392 min
				HR, RH950	> 3		1030		1230		4	/40 11111/392 111111
				PI, Sh, St/ CR, S			380 max		1030 max		20	192/92/200
JIS G 4305:1999	SUS631			Pl, Sh, St/	≤ 3		960		1140		3	/35 min/345 min
JIS G 4305.1999	303031			CR, TH1050	> 3		300		1140		5	/33 11111/343 111111
				Pl, Sh, St/	≤ 3		1030		1230			/40 min/392 min
				CR, RH950	> 3		1000		1200		4	740 11111/032 111111
				PI, Sh/ HR or CR, S			380 max		1030 max		20	192/92/200
				PI, Sh/	≤ 3						3	
JIS G 4312:1991	SUS631			HR or CR, TH1050	> 3		960		1140		5	/35 min/345 min
				PI, Sh/	≤ 3		1030		1230			/40 min/392 min
				HR or CR, RH950	> 3		1000		1200		4	/ 70 11111/032 111111
EN 10088-2:1995	X7CrNiAl17-7	1.4568		St/ CR, AT	- G				≤ 1030		19	/
	A/GINIAII/-/	1.4306		St/ CR, P1450	≤ 6		1310		≥ 1450		2	/

8.1.4B Mechanical Properties of Precipitation-Hardening Stainless Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thicl	rness	Yield Stre	ngth, min	Tensile Stre	ength, min	Elongation,	Hardness, max
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
				PI, Sh, St/ S	0.038 ≤ t < 102	0.0015≤ t < 4.0	450	65	1035	150	25	/100HRB/
					0.038 ≤ t < 0.127	0.0015 ≤ t < 0.0050	1170	170	1310	190		/40/
				PI, Sh, St/	0.127 ≤ t < 0.25	0.0050 ≤ t < 0.0010	1170	170	1310	190		/40/
				1400+55+1050	0.25 ≤ t < 0.51	0.010 ≤ t < 0.020	1170	170	1310	190		/40/
				1400+35+1050	0.51 ≤ t < 4.762	0.020 ≤ t < 0.1875	1170	170	1310	190		/40/
					4.762 ≤ t < 15.88	0.1875 ≤ t < 0.625	1170	170	1310	190	20	375/40/
ACTM A 602 02	632		015700		$0.038 \le t < 0.127$	0.0015 ≤ t < 0.0050	1380	200	1550	225		/46/
ASTM A 693-03	032		S15700	PI, Sh, St/	0.127 ≤ t < 0.25	0.0050 ≤ t < 0.0010	1380	200	1550	225		/46/
				1750+minus	0.25 ≤ t < 0.51	0.010 ≤ t < 0.020	1380	200	1550	225		/46/
				100+950	0.51 ≤ t < 4.762	0.020 ≤ t < 0.1875	1380	200	1550	225		/46/
					4.762 ≤ t < 15.88	0.1875 ≤ t < 0.625	1380	200	1550	225	20	429/45/
				PI, Sh, St/ CR	0.038 ≤ t < 0.13	0.0015 ≤ t < 0.0050	1205	175	1380	200		/41/
				PI, Sh, St/ CR+900	0.038 ≤ t < 0.13	0.0015 ≤ t < 0.0050	1585	230	1655	240		/46/
EN 10088-2:1995	X8CrNiMoAl15-7-2	1.4532		St/ CR, AT	≤ 6				1100 max		20	/
LIV 10000-2.1995	AGOTHINOATTS-7-2	1.4002		St/ CR, P1550	≤ 6		1380		1550		2	/

8.1.5A Chemical Composition of Duplex (Ferritic-Austenitic) Stainless Steels

Standard	Grade, Class, Type,	Steel	UNS				,	Weight, %,	max, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 240/A 240M-03c	2205		S32205	0.030	2.00	1.00	0.030	0.020	22.0-23.0	4.5-6.5	3.0-3.5	N 0.14-0.20
JIS G 4304:1999	SUS329J3L			0.030	2.00	1.00	0.040	0.030	21.00-24.00	4.50-6.50	2.50-3.50	N 0.08-0.20
JIS G 4305:1999	SUS329J3L			0.030	2.00	1.00	0.040	0.030	21.00-24.00	4.50-6.50	2.50-3.50	N 0.08-0.20
EN 10088-2:1995	X2CrNiMoN22-5-3	1.4462		0.030	2.00	1.00	0.035	0.015	21.00-23.00	4.50-6.50	2.50-3.50	N 0.10-0.22
ASTM A 240/A 240M-03c	2304		S32304	0.030	2.50	1.00	0.040	0.030	21.5-24.5	3.0-5.5	0.05-0.60	N 0.05-0.20; Cu 0.05-0.60
EN 10088-2:1995	X2CrNiN23-4	1.4362		0.030	2.00	1.00	0.035	0.015	22.00-24.00	3.50-5.50	0.10-0.60	N 0.05-0.20; Cu 0.10-0.60
ASTM A 240/A 240M-03c			S32520	0.030	1.50	0.80	0.035	0.020	24.0-26.0	5.5-8.0	3.0-4.0	N 0.20-0.35; Cu 0.50-2.00
EN 10088-2:1995	X2CrNiMoCuN25-6-3	1.4507		0.030	2.00	0.70	0.035	0.015	24.00-26.00	5.50-7.50	2.70-4.00	N 0.15-0.30; Cu 1.00-2.50
ASTM A 240/A 240M-03c	2507		S32750	0.030	1.20	0.80	0.035	0.020	24.0-26.0	6.0-8.0	3.0-5.0	N 0.24-0.32; Cu 0.50
EN 10088-2:1995	X2CrNiMoN25-7-4	1.4410		0.030	2.00	1.00	0.035	0.015	24.00-26.00	6.00-8.00	3.00-4.50	N 0.20-0.35
ASTM A 240/A 240M-03c			S32760	0.030	1.00	1.00	0.030	0.010	24.0-26.0	6.0-8.0	3.0-4.0	N 0.20-0.30; Cu 0.50-1.00; W 0.50-1.00
EN 10088-2:1995	X2CrNiMoCuWN25-7-4	1.4501		0.030	1.00	1.00	0.035	0.015	24.00-26.00	6.00-8.00	3.00-4.00	N 0.20-0.30; Cu 0.50-1.00; W 0.50-1.00

8.1.5B Mechanical Properties of Duplex (Ferritic-Austenitic) Stainless Steels

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thic	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRB/HV
ASTM A 240/A 240M-03c	2205		S32205	PI, Sh, St			450	65	655	95	25	293/31/
JIS G 4304:1999	SUS329J3L			PI, Sh, St/HR, S			450		620		18	302/32/320
JIS G 4305:1999	SUS329J3L			PI, Sh, St/CR, S			450		620		18	302/32/320
				St/CR, AT	≤ 6		480		660-950		20	
EN 10088-2:1995	X2CrNiMoN22-5-3	1.4462		St/HR, AT	≤ 12		460		000-930		20	/
				PI/HR, AT	≤ 75		460		640-840		25	
ASTM A 240/A 240M-03c	2304		S32304	Pl, Sh, St			400	58	600	87	25	290/32/
				St/CR, AT	≤ 6		420		600-850		20	
EN 10088-2:1995	X2CrNiN23-4	1.4362		St/HR, AT	≤ 12		400		600-850		20	
				PI/HR, AT	≤ 75		400		630-800		25	
ASTM A 240/A 240M-03c			S32520	Pl, Sh, St			550	80	770	112	25	310//
				St/CR, AT	≤ 6		510		690-940		17	
EN 10088-2:1995	X2CrNiMoCuN25-6-3	1.4507		St/HR, AT	≤ 12		490		690-940		17	
				PI/HR, AT	≤ 75		490		690-890		25	
ASTM A 240/A 240M-03c	2507		S32750	Pl, Sh, St			550	80	795	116	15	310/32/
				St/CR, AT	≤ 6		550		750-1000		15	
EN 10088-2:1995	X2CrNiMoN25-7-4	1.4410		St/HR, AT	≤ 12		530		750-1000		15	
				PI/HR, AT	≤ 75		530		730-930		20	
ASTM A 240/A 240M-03c			S32760	Pl, Sh, St			550	80	750	108	25	270//
EN 10088-2:1995	X2CrNiMoCuWN25-7-4	1.4501		PI/HR, AT	≤ 75		530		730-930		25	

8.2.1A Chemical Composition of Martensitic Stainless Steels

Standard	Grade, Class,	Steel	UNS				Wei	ght, %, max,	Unless Othe	rwise Speci	ified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 276-03	403		S40300	0.15	1.00	0.50	0.040	0.030	11.5013.0	0.60		
JIS G 4303:1998	SUS403			0.15	1.00	0.50	0.040	0.030	11.50-13.00			
JIS G 4311:1991	SUS403			0.15	1.00	0.50	0.040	0.030	11.50-13.00			
JIS G 4318:1998	SUS403			0.15	1.00	0.50	0.040	0.030	11.50-13.00			
ASTM A 276-03	410		S41000	0.08-0.15	1.00	1.00	0.040	0.030	11.5-13.5			
JIS G 4303:1998	SUS410			0.15	1.00	1.00	0.040	0.030	11.50-13.50			
JIS G 4311:1991	SUS410			0.15	1.00	1.00	0.040	0.030	11.50-13.50			
JIS G 4318:1998	SUS410			0.15	1.00	1.00	0.040	0.030	11.50-13.50			
EN 10088-3:1995	X12Cr13	1.4006		0.08-0.15	1.50	1.00	0.040	0.030	11.50-13.50	0.75		
ASTM A 582/A 582M-95b (2000)	416		S41600	0.15	1.25	1.00	0.06	0.15 min	12.00-14.00			
JIS G 4303:1998	SUS416			0.15	1.25	1.00	0.060	0.15 min	12.00-14.00		0.60	
JIS G 4318:1998	SUS416			0.15	1.25	1.00	0.060	0.15 min	12.00-14.00		0.60	
EN 10088-3:1995	X12CrS13	1.4005		0.08-0.15	1.50	1.00	0.040	0.15-0.35	12.00-14.00		0.60	
JIS G 4303:1998	SUS420J1			0.16-0.25	1.00	1.00	0.040	0.030	12.00-14.00			
JIS G 4318:1998	SUS420J1			0.16-0.25	1.00	1.00	0.040	0.030	12.00-14.00			
EN 10088-3:1995	X20Cr13	1.4021		0.16-0.25	1.50	1.00	0.040	0.030	12.00-14.00			
JIS G 4303:1998	SUS420J2			0.26-0.40	1.00	1.00	0.040	0.030	12.00-14.00			
JIS G 4318:1998	SUS420J2			0.26-0.40	1.00	1.00	0.040	0.030	12.00-14.00			
EN 10088-3:1995	X30Cr13	1.4028		0.26-0.35	1.50	1.00	0.040	0.030	12.00-14.00			
ASTM A 582/A 582M-95b (2000)	420F		S42020	0.30-0.40	1.25	1.00	0.06	0.15 min	12.00-14.00	0.50		
JIS G 4303:1998	SUS420F			0.26-0.40	1.25	1.00	0.060	0.15 min	12.00-14.00		0.60	
JIS G 4318:1998	SUS420F			0.26-0.40	1.25	1.00	0.060	0.15 min	12.00-14.00		0.60	
EN 10088-3:1995	X29CrS13	1.4029		0.25-0.32	1.50	1.00	0.040	0.15-0.25	12.00-13.50		0.60	
ASTM A 276-03	431		S43100	0.20	1.00	1.00	0.040	0.030	15.0-17.0	1.25-2.5		
JIS G 4303:1998	SUS431			0.20	1.00	1.00	0.040	0.030	15.00-17.00	1.25-2.50		
JIS G 4311:1991	SUS431			0.20	1.00	1.00	0.040	0.030	15.00-17.00	1.25-2.50		
EN 10088-3:1995	X17CrNi16-2	1.4057		0.12-0.22	1.50	1.00	0.040	0.030	15.00-17.00	1.50-2.50		
ASTM A 276-03	440A		S44002	0.60-0.75	1.00	1.00	0.040	0.030	16.0-18.0		0.75	
JIS G 4303:1998	SUS440A			0.60-0.75	1.00	1.00	0.040	0.030	16.00-18.00			
EN 10088-3:1995	X70CrMo15	1.4109		0.65-0.75	1.00	0.70	0.040	0.030	14.00-16.00		0.40-0.80	
ASTM A 276-03	440B		S44003	0.75-0.95	1.00	1.00	0.040	0.030	16.0-18.0		0.75	
JIS G 4303:1998	SUS440B			0.75-0.95	1.00	1.00	0.040	0.030	16.00-18.00			

8.2.1A Chemical Composition of Martensitic Stainless Steels (Continued)

Standard	Grade, Class,	Steel	UNS				Weig	ht, %, max	Unless Othe	rwise Spec	ified	
Designation	Type, Symbol or Name	Number	Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 276-03	440C		S44004	0.95-1.20	1.00	1.00	0.040	0.030	16.0-18.0		0.75	
JIS G 4303:1998	SUS440C			0.95-1.20	1.00	1.00	0.040	0.030	16.00-18.00			
JIS G 4318:1998	SUS440C			0.95-1.20	1.00	1.00	0.040	0.030	16.00-18.00		0.75	
EN 10088-3:1995	X105CrMo17	1.4125		0.95-1.20	1.00	1.00	0.040	0.030	16.00-18.00		0.40-0.80	

8.2 Stainless Steels: Bar

8.2.1B Mechanical Properties of Martensitic Stainless Steels

Standard	Grade, Class,	Steel	UNS	Product Form/	Thic	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
				Bar, Shape/HF, A			275	40	480	70	20	/
ASTM A 276-03	403		S40300	Bar, Shape/CF, A	all	all	275	40	480	70	16	/
A31W A 270-03	403		340300	Bar, Shape/HF, T	all	all	550	80	690	100	15	/
				Bar, Shape/CF, T			550	80	690	100	12	/
JIS G 4303:1998	SUS403			Bar/HF, Q	≤ 75		390		590		25	170 min//
JIS G 4311:1991	SUS403			Bar/HF, Q	≤ 75		390		590		25	170 min//
JIS G 4318:1998	SUS403			Bar/CF	med	chanical prop	erties of bars s	shall be agre	eed upon betv	veen the parti	es concerned wi	th delivery
				Bar, Shape/HF, A			275	40	480	70	20	/
ASTM A 276-03	410		S41000	Bar, Shape/CF, A	all	all	275	40	480	70	16	/
A31W A 270-03	410		341000	Bar, Shape/HF, T	all	all	550	80	690	100	15	/
				Bar, Shape/CF, T			550	80	690	100	12	/
JIS G 4303:1998	SUS410			Bar/HF, Q	≤ 75		345		540		25	159 min//
JIS G 4311:1991	SUS410			Bar/Q, HF	≤ 75		345		540		25	159 min//
JIS G 4318:1998	SUS410			Bar/CF	med	chanical prop	erties of bars s	shall be agre	eed upon betv	veen the parti	es concerned wi	th delivery
				Bar/HF or CF, A					730 max			220//
EN 10088-3:1995	X12Cr13	1.4006		Bar/ HF or CF, QT650	≤ 160		450		650-850		15	/
				Bar/HF or CF, A								262//
ASTM A 582/A 582M-95b (2000)	416		S41600	Bar/HF or CF, T								248-302//
				Bar/HF or CF, H								293-352//
JIS G 4303:1998	SUS416			Bar/HF, Q	≤ 75		345		540		17	159 min//
JIS G 4318:1998	SUS416			Bar/CF	med	chanical prop	erties of bars s	shall be agre	eed upon betv	veen the parti	es concerned wi	th delivery
				Bar/HF or CF, A					730 max			220//
EN 10088-3:1995	X12CrS13	1.4005		Bar/ HF or CF, QT650	≤ 160		450		650-850		12	/
JIS G 4303:1998	SUS420J1			Bar/HF, Q	≤ 75		440		640		20	192 min//
JIS G 4318:1998	SUS420J1			Bar/CF	med	chanical prop	erties of bars s	shall be agre	eed upon betv	veen the parti	es concerned wi	th delivery
				Bar/HF or CF, A					760 max			230//
EN 10088-3:1995	X20Cr13	1.4021		Bar/HF or CF, T700	≤ 160		500		700-850		13	/
				Bar/HF or CF, T800	≤ 160		600		800-950		12	/
JIS G 4303:1998	SUS420J2			Bar/HF, Q	≤ 75		540		740		12	217 min//
JIS G 4318:1998	SUS420J2			Bar/CF	med	chanical prop	erties of bars s	shall be agre	eed upon betv	veen the parti	es concerned wi	th delivery
EN 10000 2:1005	V200-40	1 4000		Bar/HF or CF, A					800 max			245//
EN 10088-3:1995	X30Cr13	1.4028		Bar/HF or CF, T850	≤ 160		650		850-1000		10	/

Standard	Grade, Class,	Steel	UNS	Product Form/	Thicl	kness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name	Number		Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
ASTM A 582/A 582M-95b (2000)	420F		S42020	Bar/HF or CF, A								262//
JIS G 4303:1998	SUS420F			Bar/HF, Q	≤ 75		540		740		8	217 min//
JIS G 4318:1998	SUS420F			Bar/CF	med	hanical prope	erties of bars s	shall be agre	eed upon betw	een the parti	es concerned wi	th delivery
EN 10088-3:1995	X29CrS13	1.4029		Bar/HF or CF, A					800 max			245//
EN 10066-3.1995	A2901313	1.4029		Bar/HF or CF, T850	≤ 160		650		850-1000		9	/
ASTM A 276-03	431		S43100	Bar, Shape/ HF or CF, A	all	all						285//
JIS G 4303:1998	SUS431			Bar/HF, Q	≤ 75		590		780		15	229 min//
JIS G 4311:1991	SUS431			Bar/HF, Q	≤ 75		590		780		15	229 min//
				Bar/HF or CF, A					950 max			295//
				Bar/HF or CF, T800	≤ 60		600		800-950		14	//
EN 10088-3:1995	X17CrNi16-2	crNi16-2 1.4057		bai/nr of Cr, 1600	60< d ≤ 160		600		800-950		12	/
				Bar/HF or CF. T900	≤ 60		700		900-1050		12	/
				bai/nr oi Cr, 1900	60< d ≤ 160		700		900-1050		10	/
ASTM A 276-03	440A		S44002	Bar, Shape/HF, A	all	all						269//
ASTIVI A 276-03	440A		344002	Bar, Shape/CF, A	all	all						285//
JIS G 4303:1998	SUS440A			Bar/HF, Q	≤ 75							/54 min/
EN 10088-3:1995	X70CrMo15	1.4109		Bar/HF or CF, A	≤ 100				900 max			280//
ASTM A 276-03	440B		S44003	Bar, Shape/HF, A	all	all						269//
ASTIVI A 276-03	4406		344003	Bar, Shape/CF, A	all	all						285//
JIS G 4303:1998	SUS440B			Bar/HF, Q	≤ 75							/56 min/
ASTM A 276-03	440C		S44004	Bar, Shape/HF, A	all	all						269//
ASTIVI A 2/0-03	4400		344004	Bar, Shape/CF, A	all	all						285//
JIS G 4303:1998	SUS440C			Bar/HF, Q	≤ 75							/58 min/
JIS G 4318:1998	SUS440C			Bar/CF	med	hanical prope	erties of bars s	shall be agre	eed upon betw	een the parti	es concerned wi	th delivery
EN 10088-3:1995	X105CrMo17	1.4125		Bar/HF or CF, A	≤ 100							285//

8.2 Stainless Steels: Bar

8.2.2A Chemical Composition of Ferritic Stainless Steels

Standard	Grade, Class,	Steel	UNS				Weig	ht, %, max,	Unless Other	wise Specif	ied	
Designation	Type, Symbol or Name		Number	С	Mn	Si	P	S	Cr	Ni	Мо	Others
ASTM A 276-03	405		S40500	0.08	1.00	1.00	0.040	0.030	11.5-14.5	0.50		Al 0.10-0.30
JIS G 4303:1998	SUS405			0.08	1.00	1.00	0.040	0.030	11.50-14.50			Al 0.10-0.30
JIS G 4311:1991	SUS405			0.08	1.00	1.00	0.040	0.030	11.50-14.50			Al 0.10-0.30
EN 10088-3:1995	X6Cr13	1.4000		0.08	1.00	1.00	0.040	0.030	12.00-14.00			
ISO 4955:1994	X6Cr13			0.08	1.0	1.0	0.040	0.030	12.0-14.0	1.0		
ASTM A 276-03	430		S43000	0.12	1.00	1.00	0.040	0.030	16.0-18.0			
JIS G 4303:1998	SUS430			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
JIS G 4311:1991	SUS430			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
JIS G 4318:1998	SUS430			0.12	1.00	0.75	0.040	0.030	16.00-18.00			
EN 10088-3:1995	X6Cr17	1.4016		0.08	1.00	1.00	0.040	0.030	16.00-18.00			
ASTM A 582/A 582M-95b (2000)	430F		S43020	0.12	1.25	1.00	0.060	0.15 min	16.00-18.00			
JIS G 4303:1998	SUS430F			0.12	1.25	1.00	0.060	0.15 min	16.00-18.00			
JIS G 4318:1998	SUS430F			0.12	1.25	1.00	0.060	0.15 min	16.00-18.00			
EN 10088-3:1995	X6CrMoS17	1.4105		0.08	1.50	1.50	0.040	0.15-0.35	16.00-18.00		0.20-0.60	
ISO 4955:1994	X6Cr17			0.08	1.0	1.0	0.040	0.030	16.0-18.0	1.0		
ASTM A 582/A 582M-95b (2000)			S18235	0.025	0.50	1.00	0.030	0.15-0.35	17.05-18.50	1.00	2.00-2.50	N 0.025; Ti 0.30-1.00; C+N 0.035
EN 10088-3:1995	X2CrMoTiS18-2	1.4523		0.030	0.50	1.00	0.040	0.15-0.35	17.50-19.00		2.00-2.50	C+N 0.040
JIS G 4303:1998	SUS434			0.12	1.00	1.00	0.040	0.030	16.00-18.00		0.75-1.25	
EN 10088-3:1995	X6CrMo17-1	1.4113		0.08	1.00	1.00	0.040	0.030	16.00-18.00		0.90-1.40	
ASTM A 276-03	447		S44700	0.010	0.30	0.20	0.025	0.020	28.0-30.0	0.15	3.5-4.2	N 0.020; Cu 0.15; C+N 0.025
JIS G 4303:1998	SUS447J1			0.010	0.40	0.40	0.030	0.020	28.50-32.00	0.50	1.50-2.50	N 0.015; Cu 0.20; Ni+Cu 0.50
ASTM A 276-03	XM-27		S44627	0.010	0.40	0.40	0.020	0.020	25.0-27.5	0.50	0.75-1.50	N 0.015; Cu 0.20; Cb 0.05-0.20
JIS G 4303:1998	SUSXM27			0.010	0.40	0.40	0.030	0.020	25.00-27.50	0.50	0.75-1.50	N 0.015; Cu 0.20; Ni+Cu 0.50
ASTM A 276-03	446		S44600	0.20	1.50	1.00	0.040	0.030	23.0-27.0	0.75		N 0.25
JIS G 4311:1991	SUH446			0.20	1.50	1.00	0.040	0.030	23.00-27.00			N 0.25
ISO 4955:1994	X15CrN26			0.20	1.0	1.0	0.040	0.030	24.0-28.0	1.0		N 0.15-0.25
EN 10095:1999	X18CrN28	1.4749		0.15-0.20	1.00	1.00	0.040	0.015	26.00-29.00			N 0.15-0.25

8.2 Stainless Steels: Bar

8.2.2B Mechanical Properties of Ferritic Stainless Steels

Standard	Grade, Class,	Steel	UNS	Product Form/	Thic	kness	Yield Stre	ngth, min	Tensile St	rength, min	Elongation,	Hardness,
Designation	Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	max HB/HRB/HV
ASTM A 276-03	405		S40500	Bar, Shape/HF, A	all	all						207//
AOTW A 270 00	403		040300	Bar, Shape/CF, A	all	all						217//
JIS G 4303:1998	SUS405			Bar/HF, A	≤ 75		175		410		20	183//
JIS G 4311:1991	SUS405			Bar/HF, A	≤ 75		175		410		20	183//
EN 10088-3:1995	X6Cr13	1.4000		Bar/HF or CF, A	≤ 25		230		400-630		20	200//
ISO 4955:1994	X6Cr13			Bar/TA			230		400-630		see standard	197//
ASTM A 276-03	430		S43000	Bar, Shape/ HF or CF, A	all	all	207	30	415	60	20	/
JIS G 4303:1998	SUS430			Bar/HF, A	≤ 75		205		450		22	183//
JIS G 4311:1991	SUS430			Bar/HF, A	≤ 75		205		450		22	183//
JIS G 4318:1998	SUS430			Bar/CF	med	hanical prope	rties of bars sh	all be agreed	upon between	the parties co	ncerned with de	livery
EN 10088-3:1995	X6Cr17	1.4016		Bar/HF or CF, A	≤ 100		240		400-630		20	200//
ASTM A 582/A 582M-95b (2000)	430F		S43020	Bar/HF or CF, A								262//
JIS G 4303:1998	SUS430F			Bar/HF, A	≤ 75		205		450		22	183//
JIS G 4318:1998	SUS430F			Bar/CF	med	hanical prope	erties of bars sh	all be agreed	upon between	the parties co	ncerned with de	livery
EN 10088-3:1995	X6CrMoS17	1.4105		Bar/HF or CF, A	≤ 100		250		430-630		20	200//
ISO 4955:1994	X6Cr17			Pl, Sh, St/TA	5 < t ≤ 15		250		430-630		see standard	197//
ASTM A 582/A 582M-95b (2000)			S18235	Bar/HF or CF, A								207//
EN 10088-3:1995	X2CrMoTiS18-2	1.4523		Bar/HF or CF, A	≤ 100		280		430-600		15	200//
JIS G 4303:1998	SUS434			Bar/HF, A	≤ 75		205		450		22	183//
EN 10088-3:1995	X6CrMo17-1	1.4113		Bar/HF or CF, A	≤ 100		280		440-660		18	200//
ACTM A 070 00	447		S44700	Bar, Shape/HF, A	all	all	380	55	480	70	20	/
ASTM A 276-03	447		544700	Bar, Shape/CF, A	all	all	415	60	520	75	15	/
JIS G 4303:1998	SUS447J1			Bar/HF, A	≤ 75		295		450		20	228//
ASTM A 276-03	XM-27		S44627	Bar, Shape/HF, A	all	all	275	40	450	65	20	219//
ASTM A 276-03	AIVI-27		544627	Bar, Shape/CF, A	all	all	275	40	450	65	16	219//
JIS G 4303:1998	SUSXM27			Bar/HF, A	≤ 75		245		410		20	219//
ASTM A 276-03	446		S44600	Bar, Shape/HF, A	all	all	275	40	450	65	20	219//
AS I WI A 2/0-03	440		344000	Bar, Shape/CF, A	all	all	275	40	450	65	16	219//
JIS G 4311:1991	SUH446			Bar/HF, A			275		510		20	201//
ISO 4955:1994	X15CrN26			Bar/TA			280		500-700		see standard	212//
EN 10095:1999	X18CrN28	1.4749		Rod, Section/ A	≤ 25		280		500-700		see standard	212//

8.2.3A Chemical Composition of Austenitic Stainless Steels

Standard	Grade, Class,	Steel	UNS				Weig	ıht, %, max,	Unless Other	wise Specifi	ied	
Designation	Type, Symbol or Name		Number	С	Mn	Si	P	s	Cr	Ni	Мо	Others
ASTM A 276-03	201		S20100	0.15	5.5-7.5	1.00	0.060	0.030	16.0-18.0	3.5-5.5		N 0.25
JIS G 4303:1998	SUS201			0.15	5.50-7.50	1.00	0.060	0.030	16.00-18.00	3.50-5.50		N 0.25
ASTM A 276-03	202		S20200	0.15	7.5-10.0	1.00	0.060	0.030	17.0-19.0	4.0-6.0		N 0.25
JIS G 4303:1998	SUS202			0.15	7.50-10.00	1.00	0.060	0.030	17.00-19.00	4.00-6.00		N 0.25
JIS G 4303:1998	SUS301			0.15	2.00	1.00	0.045	0.030	16.00-18.00	6.00-8.00		
EN 10088-3:1995	X10CrNi18-8	1.4310		0.05-0.15	2.00	2.00	0.045	0.015	16.00-19.00	6.00-9.50	0.80	N 0.11
ASTM A 276-03	302		S30200	0.15	2.00	1.00	0.045	0.030	17.0-19.0	8.0-10.0		N 0.10
JIS G 4303:1998	SUS302			0.15	2.00	0.75	0.045	0.030	17.00-19.00	8.00-10.00		
JIS G 4318:1998	SUS302			0.15	2.00	0.75	0.045	0.030	17.00-19.00	8.00-10.00		
ASTM A 582/A 582M-95b (2000)	303		S30300	0.15	2.00	1.00	0.20	0.15 min	17.00-19.00	8.00-10.00		
JIS G 4303:1998	SUS303			0.15	2.00	1.00	0.20	0.15 min	17.00-19.00	8.00-10.00	0.60	
JIS G 4318:1998	SUS303			0.15	2.00	1.00	0.20	0.15 min	17.00-19.00	8.00-10.00	0.60	
EN 10088-3:1995	X8CrNiS18-9	1.4305		0.10	2.00	1.00	0.045	0.15-0.35	17.00-19.00	8.00-10.00		N 0.11; Cu 1.00
ASTM A 582/A 582M-95b (2000)	303Se		S30323	0.15	2.00	1.00	0.20	0.06	17.00-19.00	8.00-10.00		Se 0.15 min
JIS G 4303:1998	SUS303Se			0.15	2.00	1.00	0.20	0.06	17.00-19.00	8.00-10.00	0.60	Se 0.15 min
JIS G 4318:1998	SUS303Se			0.15	2.00	1.00	0.20	0.06	17.00-19.00	8.00-10.00	0.60	Se 0.15 min
ASTM A 276-03	304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		
JIS G 4303:1998	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
JIS G 4311:1991	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
JIS G 4318:1998	SUS304			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
EN 10088-3:1995	X5CrNi18-10	1.4301		0.07	2.00	1.00	0.045	0.030	17.00-19.50	8.00-10.50		N 0.11
ASTM A 276-03	304L		S30403	0.030	2.00	1.00	0.045	0.030	18.0-20.0	8.0-12.0		
JIS G 4303:1998	SUS304L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	9.00-13.00		
JIS G 4318:1998	SUS304L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	9.00-13.00		
EN 10088-3:1995	X2CrNi18-9	1.4307		0.030	2.00	1.00	0.045	0.030	17.50-19.50	8.00-10.00		N 0.11
ASTM A 276-03	304N		S30451	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		N 0.10-0.16
JIS G 4303:1998	SUS304N1			0.08	2.50	1.00	0.045	0.030	18.00-20.00	7.00-10.50		N 0.10-0.25
ASTM A 276-03	304LN		S30453	0.030	2.00	1.00	0.045	0.030	18.0-20.0	8.0-11.0		N 0.10-0.16
JIS G 4303:1998	SUS304LN			0.030	2.00	1.00	0.045	0.030	17.00-19.00	8.50-11.50		N 0.12-0.22
EN 10088-3:1995	X2CrNiN18-10	1.4311		0.030	2.00	1.00	0.045	0.030	17.00-19.50	8.50-11.50		N 0.12-0.22
ASTM A 276-03	XM-21		S30452	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-10.0		N 0.16-0.30
JIS G 4303:1998	SUS304N2			0.08	2.50	1.00	0.045	0.030	18.00-20.00	7.50-10.50		N 0.15-0.30; Nb 0.15

8.2 Stainless Steels: Bar

8.2.3A Chemical Composition of Austenitic Stainless Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS				Weig	ht, %, max,	Unless Other	wise Specifi	ied	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 276-03	305		S30500	0.12	2.00	1.00	0.045	0.030	17.0-19.0	11.0-13.0		
JIS G 4303:1998	SUS305			0.12	2.00	1.00	0.045	0.030	17.00-19.00	10.50-13.00		
JIS G 4318:1998	SUS305			0.12	2.00	1.00	0.045	0.030	17.00-19.00	10.50-13.00		
EN 10088-3:1995	X4CrNi18-12	1.4303		0.06	2.00	1.00	0.045	0.030	17.00-19.00	11.00-13.00		N 0.11
ASTM A 276-03	309S		S30908	0.08	2.00	1.00	0.045	0.030	22.0-24.0	12.0-15.0		
JIS G 4303:1998	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
JIS G 4311:1991	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
JIS G 4318:1998	SUS309S			0.08	2.00	1.00	0.045	0.030	22.00-24.00	12.00-15.00		
ISO 4955:1994	X6CrNi23-14			0.08	2.0	1.0	0.045	0.030	22.0-24.0	12.0-15.0		
ASTM A 276-03	310S		S31008	0.08	2.00	1.50	0.045	0.30	24.0-26.0	19.0-22.0		
JIS G 4303:1998	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		
JIS G 4311:1991	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		
JIS G 4318:1998	SUS310S			0.08	2.00	1.50	0.045	0.030	24.00-26.00	19.00-22.00		
ISO 4955:1994	X6CrNi25-21			0.08	2.0	1.5	0.045	0.030	24.0-26.0	19.0-22.0		
ASTM A 276-03	316		S31600	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 4303:1998	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 4311:1991	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
JIS G 4318:1998	SUS316			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	
EN 10088-3:1995	X5CrNiMo17-12-2	1.4401		0.07	2.00	1.00	0.045	0.030	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10000-3.1995	X3CrNiMo17-13-3	1.4436		0.05	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
ASTM A 276-03	316L		S31603	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	
JIS G 4303:1998	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
JIS G 4318:1998	SUS316L			0.030	2.00	1.00	0.045	0.030	16.00-18.00	12.00-15.00	2.00-3.00	
	X2CrNiMo17-12-2	1.4404		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.00-13.00	2.00-2.50	N 0.11
EN 10088-3:1995	X2CrNiMo17-12-3	1.4432		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.00	2.50-3.00	N 0.11
	X2CrNiMo18-14-3	1.4435		0.030	2.00	1.00	0.045	0.030	17.00-19.00	12.50-15.00	2.50-3.00	N 0.11
ASTM A 276-03	316N		S31651	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10-0.16
JIS G 4303:1998	SUS316N			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	N 0.10-0.22
ASTM A 276-03	316LN		S31653	0.030	2.00	1.00	0.045	0.030	16.0-18.0	10.0-13.0	2.00-3.00	N 0.10-0.16
JIS G 4303:1998	SUS316LN			0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.50-14.50	2.00-3.00	N 0.12-0.22
EN 10088-3:1995	X2CrNiMoN17-11-2	1.4406		0.030	2.00	1.00	0.045	0.030	16.50-18.50	10.00-12.00	2.00-2.50	N 0.12-0.22
LIN 10000-3.1993	X2CrNiMoN17-13-3	1.4429		0.030	2.00	1.00	0.045	0.015	16.50-18.50	11.00-14.00	2.50-3.00	N 0.12-0.22

8.2 Stainless Steels: Bar

8.2.3A Chemical Composition of Austenitic Stainless Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS				Weig	ht, %, max,	Unless Other	rwise Specifi	ed	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 276-03	316Ti		S31635	0.08	2.00	1.00	0.045	0.030	16.0-18.0	10.0-14.0	2.00-3.00	N 0.10; Ti 5 x(C+N) to 0.70
JIS G 4303:1998	SUS316Ti			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	Ti 5 x C min
JIS G 4311:1991	SUS316Ti			0.08	2.00	1.00	0.045	0.030	16.00-18.00	10.00-14.00	2.00-3.00	Ti 5 x C min
EN 10088-3:1995	X6CrNiMoTi17-12-2	1.4571		0.08	2.00	1.00	0.045	0.030	16.50-18.50	10.50-13.50	2.0-2.50	Ti 5 x C to 0.70
ASTM A 276-03	317		S31700	0.08	2.00	1.00	0.045	0.030	18.0-20.0	11.0-15.0	3.0-4.0	N 0.10
JIS G 4303:1998	SUS317			0.08	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 4311:1991	SUS317			0.08	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
JIS G 4303:1998	SUS317L			0.030	2.00	1.00	0.045	0.030	18.00-20.00	11.00-15.00	3.00-4.00	
EN 10088-3:1995	X2CrNiMo18-15-4	1.4438		0.030	2.00	1.00	0.045	0.030	17.50-19.50	13.00-16.00	3.00-4.00	N 0.11
JIS G 4303:1998	SUS 317J1			0.040	2.50	1.00	0.045	0.030	16.00-19.00	15.00-17.00	4.00-6.00	
EN 10088-3:1995	X2CrNiMoN17-13-5	1.4439		0.030	2.00	1.00	0.045	0.015	16.50-18.50	12.50-14.50	4.00-5.00	N 0.12-0.22
ASTM B 691-02			N08367	0.030	2.00	1.00	0.040	0.030	20.00-22.00	23.50-25.50	6.00-7.00	N 0.18-0.25; Cu 0.75
JIS G 4303:1998	SUS836L			0.030	2.00	1.00	0.045	0.030	19.00-24.00	24.00-26.00	5.00-7.00	N 0.25
ASTM B 649-02			N08904	0.020	2.00	1.00	0.045	0.035	19.00-23.00	23.00-28.00	4.00-5.00	Cu 1.0-2.0
JIS G 4303:1998	SUS890L			0.020	2.00	1.00	0.045	0.030	19.00-23.00	23.00-28.00	4.00-5.00	Cu 1.00-2.00
EN 10088-3:1995	X1NiCrMoCu25-20-5	1.4539		0.020	2.00	0.70	0.030	0.010	19.00-21.00	24.00-26.00	4.00-5.00	N 0.15; Cu 1.20-2.00
ASTM A 276-03	321		S32100	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x (C+N) to 0.70
JIS G 4303:1998	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
JIS G 4318:1998	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
JIS G 4311:1991	SUS321			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Ti 5 x C min
EN 10088-3:1995	X6CrNiTi18-10	1.4541		0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-12.00		Ti 5 x C to 0.70
ISO 4955:1994	X7CrNiTi18-10			0.040-0.10	2.0	1.0	0.045	0.030	17.0-19.0	9.0-12.0		Ti 5 x C to 0.80
ASTM A 276-03	347		S34700	0.08	2.00	1.00	0.045	0.030	17.0-19.0	9.0-12.0		Cb 10 x C to 1.10
JIS G 4303:1998	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
JIS G 4311:1991	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
JIS G 4318:1998	SUS347			0.08	2.00	1.00	0.045	0.030	17.00-19.00	9.00-13.00		Nb 10 x C min
EN 10088-3:1995	X6CrNiNb18-10	1.4550		0.08	2.00	1.00	0.045	0.015	17.00-19.00	9.00-12.00		Nb 10 x C to 1.00
ISO 4955:1994	X7CrNiNb18-10			0.040-0.10	2.0	1.0	0.045	0.030	17.0-19.0	9.0-12.0		Nb 10 x C to 1.2
ASTM A 276-03	309		S30900	0.20	2.00	1.00	0.045	0.030	22.0-24.0	12.0-15.0		
JIS G 4311:1991	SUH309			0.20	2.00	1.00	0.040	0.030	22.00-24.00	12.00-15.00		
EN 10095:1999	X12CrNi23-13	1.4833		0.15	2.00	1.00	0.045	0.015	22.00-24.00	12.00-14.00		N 0.11
ASTM A 276-03	310		S31000	0.25	2.00	1.50	0.045	0.030	24.0-26.0	19.0-22.0		
JIS G 4311:1991	SUH310			0.25	2.00	1.50	0.040	0.030	24.00-26.00	19.00-22.00		
EN 10095:1999	X15CrNiSi25-21	1.4841		0.20	2.00	1.50-2.50	0.045	0.015	24.00-26.00	19.00-22.00		N 0.11
ISO 4955:1994	X15CrNiSi25-21			0.20	2.0	1.5-2.5	0.045	0.030	24.0-26.0	19.0-22.0		

Standard	Grade, Class,	Steel	UNS	Product Form/	Thickr	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRB/HV
ASTM A 276-03	201		S20100	Bar, Shape/ HF or CF, A	all	all	275	40	515	75	40	/
JIS G 4303:1998	SUS201			Bar/HF, S	≤ 180		275		520		40	241/100/253
				Bar, Shape/ HF or CF, A	all	all	275	40	515	75	40	/
					≤ 19.05	≤ 3/4	690	100	860	125	12	/
ASTM A 276-03	202		S20200	Day Chans/	19.05 < t ≤ 25.40	3⁄4 < t ≤ 1	550	80	795	115	15	/
				Bar, Shape/ CF, B	25.40 < t ≤ 31.75	1 < t ≤ 11⁄4	450	65	725	105	20	/
				CI, D	31.75 < t ≤ 38.10	1¼ < t ≤ 1½	345	50	690	100	24	/
					38.10 < t ≤ 44.45	1½ < t ≤ 1¾	310	45	655	95	28	/
JIS G 4303:1998	SUS202			Bar/HF, S	≤ 180		275		520		40	207/95/218
JIS G 4303:1998	SUS301			Bar/HF, S	≤ 180		205		520		40	207/95/218
EN 10088-3:1995	X10CrNi18-8	1.4310		Bar/HF or CF, AT	≤ 40		195		500-750		40	230//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
				Bar, Shape/CF, A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				bai, Silape/Ci , A	> 12.70	> ½	205	30	515	75	30	/
ASTM A 276-03	302		S30200		≤ 19.05	≤ 3/4	690	100	860	125	12	/
ASTIVI A 276-03	302		330200		19.05 < t ≤ 25.40	3⁄4 < t ≤ 1	550	80	795	115	15	/
				Bar, Shape/CF, B	25.40 < t ≤ 31.75	1 < t ≤ 11⁄4	450	65	725	105	20	/
					31.75 < t ≤ 38.10	1¼ < t ≤ 1½	345	50	690	100	24	/
					38.10 < t ≤ 44.45	1½ < t ≤ 1¾	310	45	655	95	28	/
JIS G 4303:1998	SUS302			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS302			Bar/CF	mechani	cal properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with o	delivery
ASTM A 582/A 582M-95b (2000)	303		S30300	Bar/HF or CF, A								262//
JIS G 4303:1998	SUS303			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS303			Bar/CF	mechani	cal properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with o	delivery
EN 10088-3:1995	X8CrNiS18-9	1.4305		Bar/HF or CF, AT	≤ 160		190		500-750		35	230//
ASTM A 582/A 582M-95b (2000)	303Se		S30323	Bar/HF or CF, A								262//
JIS G 4303:1998	SUS303Se			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS303Se			Bar/CF	mechani	cal properties of	bars shall be	agreed upo	n between th	ne parties co	ncerned with o	delivery

Standard	Grade, Class,	Steel	UNS	Product Form/	Thickr	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRB/HV
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
				Bar, Shape/CF, A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				bai, Shape/Oi , A	> 12.70	> ½	205	30	515	75	30	/
					≤ 19.05	≤ 3⁄4	690	100	860	125	12	/
					19.05 < t ≤ 25.40	$\frac{3}{4} < t \le 1$	550	80	795	115	15	/
ASTM A 276-03	304		S30400	Bar, Shape/CF, B	25.40 < t ≤ 31.75	1 < t ≤ 11⁄4	450	65	725	105	20	/
					31.75 < t ≤ 38.10	1¼ < t ≤ 1½	345	50	690	100	24	/
					38.10 < t ≤ 44.45	$1\frac{1}{2} < t \le 1\frac{3}{4}$	310	45	655	95	28	/
					≤ 50.8	≤ 2	515	75	650	95	25	/
				Bar, Shape/CF, S	50.8 < t ≤ 63.5	$2 < t \le 2\frac{1}{2}$	450	65	620	90	30	/
					63.5 < t ≤ 76.2	$2\frac{1}{2} < t \le 3$	380	55	550	80	30	/
JIS G 4303:1998	SUS304			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS304			Bar/HF, H	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS304			Bar/CF	mechani	cal properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with	delivery
EN 10088-3:1995	X5CrNi18-10	1.4301		Bar/HF or CF, AT	≤ 160		190		500-700		L: 45	215//
LN 10086-3.1993	ASCINITO-10	1.4301		Dai/Hi Ol Cl , Al	160 < t ≤ 250		190		300-700		T: 35	213//
				Bar, Shape/HF, A	all	all	170	25	485	70	40	/
ASTM A 276-03	304L		S30403	Bar, Shape/CF, A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
					> 12.70	> ½	170	25	485	70	30	/
JIS G 4303:1998	SUS304L			Bar/HF, S	≤ 180		175		480		40	187/90/200
JIS G 4318:1998	SUS304L			Bar/CF	mechani	cal properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with	delivery
EN 10088-3:1995	X2CrNi18-9	1.4307		Bar/HF or CF, AT	≤ 160		175		450-680		L: 45	215//
LN 10086-3.1993	AZCIIVI10-9	1.4307		Dai/Til Ol Cl , Al	160 < t ≤ 250		175		450-000		T: 35	213//
				Bar, Shape/ HF or CF, A	all	all	240	35	550	80	30	/
					≤ 19.05	≤ 3/4	690	100	860	125	12	/
					19.05 < t ≤ 25.40	$\frac{3}{4} < t \le 1$	550	80	795	115	15	/
A O TA A . 0 7 0 0 0	00.4N		000454	Bar, Shape/CF, B	25.40 < t ≤ 31.75	$1 < t \le 1\frac{1}{4}$	450	65	725	105	20	/
STM A 276-03 304N S304	304N		530451		31.75 < t ≤ 38.10	1¼ < t ≤ 1½	345	50	690	100	24	/
					38.10 < t ≤ 44.45	1½ < t ≤ 1¾	310	45	655	95	28	/
					≤ 50.8	≤ 2	515	75	650	95	25	/
				Bar, Shape/CF, S	50.8 < t ≤ 63.5	2 < t ≤ 2½	450	65	620	90	30	/
			63.5 < t ≤ 76.2	2½ < t ≤ 3	380	55	550	80	30	/		
JIS G 4303:1998	SUS304N1			Bar/HF, S	≤ 180		275		550		35	217/95/220

Standard	Grade, Class,	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRB/HV
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	304LN		S30453	Bar, Shape/CF, A	≤ 12.70	≤ ½	310	45	620	90	30	/
				bai, Shape/Oi , A	> 12.70	> ½	205	30	515	75	30	/
JIS G 4303:1998	SUS304LN			Bar/HF, S	≤ 180		245		550		40	217/95/220
EN 10088-3:1995	X2CrNiN18-10	1.4311		Bar/HF or CF, AT	≤ 160		270		550-760		L: 40	230//
	7.201110				160 < t ≤ 250						T: 30	
ASTM A 276-03	XM-21		S30452	Bar, Shape/ HF or CF, A	all	all	345	50	620	90	30	/
JIS G 4303:1998	SUS304N2			Bar/HF, S	≤ 180		345		690		35	250/100/260
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	305		S30500	Bar, Shape/CF, A	≤ 12.70	≤ ½	310	45	620	90	30	/
				bai, Shape/Oi, A	> 12.70	> ½	205	30	515	75	30	/
JIS G 4303:1998	SUS305			Bar/HF, S	≤ 180		175		480		40	187/90/200
JIS G 4318:1998	SUS305			Bar/CF	mechar	nical properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with o	delivery
EN 10088-3:1995	X4CrNi18-12	1.4303		Bar/HF or CF, AT	≤ 160		190		500-700		L: 45	215//
EN 10080-3.1993	X40111110-12	1.4303		Dai/Til Ol Ol , Al	$160 < t \le 250$		190		300-700		T: 35	213//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	309S		S30908	Bar, Shape/CF,A	≤ 12.70	≤ ½	310	45	620	90	30	/
				bai, Shape/Oi ,A	> 12.70	> ½	205	30	515	75	30	/
JIS G 4303:1998	SUS309S			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS309S			Bar/HF, H	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS309S			Bar/CF	mechar	nical properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with o	delivery
ISO 4955:1994	X6CrNi23-14			Bar/TQ			210		500-700		see standard	192//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	310S		S31008	Bar, Shape/CF, A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				bai, Shape/OF, A	> 12.70	> ½	205	30	515	75	30	//
JIS G 4303:1998	SUS310S			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS310S			Bar/HF, H	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS310S			Bar/CF	mechar	nical properties of	bars shall be	agreed upo	on between th	ne parties co	ncerned with o	delivery
ISO 4955:1994	X6CrNi25-21			PI, Sh, St/TQ	≤ 100		210		500-700		see standard	192//

Standard	Grade, Class,	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name		Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRB/HV
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
				Bar, Shape/CF, A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				bai, Shape/OF, A	> 12.70	> ½	205	30	515	75	30	/
					≤ 19.05	≤ 3/4	690	100	860	125	12	/
					19.05 < t ≤ 25.40	3⁄4 < t ≤ 1	550	80	795	115	15	/
ASTM A 276-03	316		S31600	Bar, Shape/CF, B	25.40 < t ≤ 31.75	1 < t ≤ 11⁄4	450	65	725	105	20	/
					31.75 < t ≤ 38.10	1¼ < t ≤ 1½	345	50	690	100	24	/
					38.10 < t ≤ 44.45	1½ < t ≤ 1¾	310	45	655	95	28	/
					≤ 50.8	≤ 2	515	75	650	95	25	/
				Bar, Shape/CF, S	50.8 < t ≤ 63.5	2 < t ≤ 2½	450	65	620	90	30	/
					63.5 < t ≤ 76.2	2½ < t ≤ 3	380	55	550	80	30	/
JIS G 4303:1998	SUS316			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS316			Bar/HF, H	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS316			Bar/CF	mechan	nical properties of	bars shall be	agreed upo	n between th	ne parties co	ncerned with o	delivery
	V50 NIM 47 40 0	1 1101		D #15 OF AT	≤ 160		000		500 700		L: 40	0.15/ /
EN 10000 0 1005	X5CrNiMo17-12-2	1.4401		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//
EN 10088-3:1995	V00 NIM 47 40 0	4 4400		D #15 OF AT	≤ 160		000		500 700		L: 40	045/ /
	X3CrNiMo17-13-3	1.4436		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//
				Bar, Shape/HF, A	all	all	170	25	485	70	40	/
ASTM A 276-03	316L		S31603	D 01 /05 A	≤ 12.70	≤ ½	310	45	620	90	30	/
				Bar, Shape/CF, A	> 12.70	> ½	170	25	485	70	30	/
JIS G 4303:1998	SUS316L			Bar/HF, S	≤ 180		175		480		40	187/90/200
JIS G 4318:1998	SUS316L			Bar/CF	mechan	nical properties of	bars shall be	agreed upo	n between th	ne parties co	ncerned with o	delivery
EN 10000 0.1005	V00-N:M-17 10 0	1 1101		Day/UE av OF AT	≤ 160						L: 40	
EN 10088-3:1995	X2CrNiMo17-12-2	1.4404		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//
EN 10000 0:1005	V00-NIM-17 10 0	1 1100		Day/UE av OF AT	≤ 160		000		F00 700		L: 40	045/ /
EN 10088-3:1995	X2CrNiMo17-12-3	1.4432		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//
EN 10000 0 1005	V00-NUM-40-44-0	4 4405		D//15 OF AT	≤ 160		000		500 700		L: 40	045/ /
EN 10088-3:1995	X2CrNiMo18-14-3	1.4435		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//

Standard	Grade, Class, Type,	Steel	UNS	Product Form/	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Elemention	Hardness, max
Designation	Symbol or Name	Number	Number	Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	HB/HRB/HV
				Bar, Shape/ HF or CF, A	all	all	240	35	550	80	30	/
			,		≤ 19.05	≤ 3⁄4	690	100	860	125	12	/
					19.05 < t ≤ 25.40	3⁄4 < t ≤ 1	550	80	795	115	15	/
	2.21			Bar, Shape/CF, B	25.40 < t ≤ 31.75	1 < t ≤ 1¼	450	65	725	105	20	/
ASTM A 276-03	316N		S31651		31.75 < t ≤ 38.10	1¼ < t ≤ 1½	345	50	690	100	24	/
					38.10 < t ≤ 44.45	1½ < t ≤ 1¾	310	45	655	95	28	//
			·		≤ 50.8	≤ 2	515	75	650	95	25	/
				Bar, Shape/CF, S	50.8 < t ≤ 63.5	2 < t ≤ 2½	450	65	620	90	30	/
					63.5 < t ≤ 76.2	2½ < t ≤ 3	380	55	550	80	30	/
JIS G 4303:1998	SUS316N			Bar/HF, S	≤ 180		275		550		35	217/95/220
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	316LN		S31653	Day Chana/OF A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	//
JIS G 4303:1998	SUS316LN			Bar/HF, S	≤ 180		245		550		40	217/95/220
	V00-NEM-N47-44-0	4 4400		D/!-IE OE AT	≤ 160		000		500,000		L: 40	050/ /
EN 40000 0 4005	X2CrNiMoN17-11-2	1.4406		Bar/HF or CF, AT	160 < t ≤ 250		280		580-800		T: 30	250//
EN 10088-3:1995	V00-N:M-N17-10-0	1 1100		Daw/UE aw OF AT	≤ 160		000		F00 000		L: 40	050/ /
	X2CrNiMoN17-13-3	1.4429		Bar/HF or CF, AT	160 < t ≤ 250		280		580-800		T: 30	250//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	316Ti		S31635	Dor Chana/CE A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	/
JIS G 4303:1998	SUS316Ti			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS316Ti			Bar/HF, H	≤ 180		205		520		40	187/90/200
EN 10000 0-1005	VCC-NIM-T:17 10 0	4 4574		Daw/UE aw OF AT	≤ 160		000		500 700		L: 40	045/ /
EN 10088-3:1995	X6CrNiMoTi17-12-2	1.4571		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	317		S31700	Day Chana/OF A	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	//
JIS G 4303:1998	SUS317			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS317			Bar/HF, H	≤ 180		205		520		40	187/90/200
JIS G 4303:1998	SUS317L			Bar/HF, S	≤ 180		175		480		40	187/90/200
					≤ 160						L: 40	
EN 10088-3:1995	X2CrNiMo18-15-4	1.4438		Bar/HF or CF, AT	160 < t ≤ 250		200		500-700		T: 30	215//
					160 < t ≤ 250		1				T: 30	1

Standard	Crede Class Turns	Steel	UNS	Duaduat Farm/	Thick	ness	Yield Stre	ngth, min	Tensile Str	rength, min	Florenstion	Hardness, max
Designation	Grade, Class, Type, Symbol or Name	Number		Product Form/ Heat Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	HB/HRB/HV
JIS G 4303:1998	SUS 317J1			Bar/HF, S	≤ 180		175		480		40	187/90/200
EN 10088-3:1995	X2CrNiMoN17-13-5	1.4439		Bar/HF or CF, AT	≤ 160 160 < t ≤ 250		280		580-800		L: 35 T: 30	250//
ASTM B 691-02			N08367	Bar/HF or CF, A	all	all	310	45	655	95	30	/
JIS G 4303:1998	SUS836L			Bar/HF, S	≤ 180		205		520		35	217/96/230
ASTM B 649-02			N08904	Bar/HF or CF, ST	all	all	220	31	490	71	35	/
JIS G 4303:1998	SUS890L			Bar/HF, S	≤ 180		215		490		35	187/90/200
EN 10088-3:1995	X1NiCrMoCu25-20-5	1.4539		Bar/HF or CF, AT	≤ 160 160 < t ≤ 250		230		530-730		L: 35 T: 30	230//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	/
ASTM A 276-03	321		S32100	·	≤ 12.70	≤ 1/2	310	45	620	90	30	/
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	/
JIS G 4303:1998	SUS321			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS321			Bar/CF		nical properties of	f bars shall be	agreed upo	on between th	ne parties co	ncerned with o	leliverv
JIS G 4311:1991	SUS321			Bar/HF, H	≤ 180		205		520		40	187/90/200
EN 10088-3:1995	X6CrNiTi18-10	1.4541		Bar/HF or CF, AT	≤ 160 160 < t ≤ 250		190		500-700		L: 40 T: 30	215//
ISO 4955:1994	X7CrNiTi18-10			Bar/TQ			200		510-710		see standard	192//
1000.1001	70 01141110 10			Bar, Shape/HF, A	all	all	205	30	515	75	40	//
ASTM A 276-03	347		S34700		≤ 12.70	≤ 1/2	310	45	620	90	30	/
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	/
JIS G 4303:1998	SUS347			Bar/HF, S	≤ 180		205		520		40	187/90/200
JIS G 4311:1991	SUS347			Bar/HF, H	≤ 180		205		520		40	187/90/200
JIS G 4318:1998	SUS347			Bar/CF		nical properties of		agreed upo		ne parties co		
EN 10088-3:1995	X6CrNiNb18-10	1.4550		Bar/HF or CF, AT	≤ 160 160 < t ≤ 250		205		510-740		L: 40 T: 30	230//
ISO 4955:1994	X7CrNiNb18-10			Bar/TQ			205		510-710		see standard	192//
	7.7 0.1 11.1 10 10			Bar, Shape/HF, A	all	all	205	30	515	75	40	//
ASTM A 276-03	309		S30900		≤ 12.70	≤ ½	310	45	620	90	30	//
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	//
JIS G 4311:1991	SUH309			Bar/HF, S	≤ 180		205		560		45	201//
EN 10095:1999	X12CrNi23-13	1.4833		Bar/HF or CF, AT			210		500-700		see standard	192//
				Bar, Shape/HF, A	all	all	205	30	515	75	40	//
ASTM A 276-03	310		S31000		≤ 12.70	≤ 1/2	310	45	620	90	30	//
				Bar, Shape/CF, A	> 12.70	> ½	205	30	515	75	30	//
JIS G 4311:1991	SUH310			Bar/HF, S	≤ 180		205		590		40	201//
EN 10095:1999	X15CrNiSi25-21	1.4841		Bar/HF or CF, AT			230		550-750		see standard	223//
ISO 4955:1994	X15CrNiSi25-21			Bar/TQ			230		550-750		see standard	223//

Wrought Stainless Steels

8.2.4A Chemical Composition of Precipitation-Hardening Stainless Steels

Standard	Grade, Class,	Steel	UNS				W	eight, %, r	nax, Unless C	Otherwise S _l	pecified	
Designation	Type, Symbol or Name		Number	С	Mn	Si	Р	s	Cr	Ni	Мо	Others
ASTM A 564/A 564M-02a	630		S17400	0.07	1.00	1.00	0.040	0.030	15.00-17.50	3.00-5.00		Cu 3.00-5.00; Cb+Ta 0.15-0.45
JIS G 4303:1998	SUS630			0.07	1.00	1.00	0.040	0.030	15.50-17.50	3.00-5.00		Cu 3.00-5.00; Nb 0.15-0.45
JIS G 4311:1991	SUS630			0.07	1.00	1.00	0.040	0.030	15.50-17.50	3.00-5.00		Cu 3.00-5.00; Nb 0.15-0.45
EN 10088-3:1995	X5CrNiCuNb16-4	1.4542		0.07	1.50	0.70	0.040	0.030	15.00-17.00	3.00-5.00	0.60	Cu 3.00-5.00; Nb 5 x C to 0.45
ASTM A 564/A 564M-02a	631		S17700	0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.50-7.75		AI 0.75-1.50
JIS G 4303:1998	SUS631			0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.5-7.75		AI 0.75-1.50
JIS G 4311:1991	SUS631			0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.5-7.75		AI 0.75-1.50
EN 10088-3:1995	X7CrNiAl17-7	1.4568		0.09	1.00	0.70	0.040	0.015	16.00-18.00	6.50-7.80		AI 0.70-1.50

8.2.4B Mechanical Properties of Precipitation-Hardening Stainless Steels

Standard	Grade, Class,	Steel	UNS	Product Form/Heat	Thick	ness	Yield Stre	ngth, min	Tensile Str	ength, min	Elongation,	Hardness, max
Designation	Type, Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	min, %	HB/HRC/HV
				Bar, Shape/ HR & CF, A								363/38/
				Bar, Shape/	≤ 75	≤ 3	1170	170	1310	190	10	388/40/
				HR & CF, H900	75 < t ≤ 200	3 < t ≤ 8	1170	170	1010	100	10	000/40/
				Bar, Shape/	≤ 75	≤ 3	1070	155	1170	170	10	375/38/
				HR & CF, H925	75 < t ≤ 200	$3 < t \le 8$	1070	155	1170	170	10	010/00/
				Bar, Shape/ HR & CF, H1025	≤ 200	≤ 8	1000	145	1070	155	12	331/35/
ASTM A 564/A 564M-02a	630		S17400	Bar, Shape/ HR & CF, H1075	≤ 200	≤ 8	860	125	1000	145	13	311/21/
				Bar, Shape/ HR & CF, H1100	≤ 200	≤ 8	795	115	965	140	14	302/31/
				Bar, Shape/ HR & CF, H1150	≤ 200	≤ 8	725	105	930	135	16	277/28/
				Bar, Shape/ HR & CF, H1150M	≤ 200	≤ 8	520	75	795	115	18	255/24/
				Bar, Shape/ HR & CF, H1150D	≤ 200	≤ 8	725	105	860	125	16	255/24/
				Bar/HF, S								/38/
				Bar/HF, H900			1175		1310		10	/40 min/
JIS G 4303:1998	SUS630			Bar/HF, H1025	≤ 75	75	1000		1070		12	/35 min/
				Bar/HF, H1075			860		1000		13	/31 min/
				Bar/HF, H1150			725		930		16	/28 min/
				Bar/HF, S								/38/
				Bar/HF, H900			1175		1310		10	/40 min/
JIS G 4311:1991	SUS630			Bar/HF, H1025	≤ 75		1000		1070		12	/35 min/
				Bar/HF, H1075			860		1000		13	/31 min/
				Bar/HF, H1150			725		930		16	/28 min/
				Bar/HF or CF, AT					1200 max			360//
				Bar/HF or CF, P800			520		800-950		18	/
EN 10088-3:1995	X5CrNiCuNb16-4	1.4542		Bar/HF or CF, P930	≤ 100		720		930-1100		16	/
				Bar/HF or CF, P960			790		960-1160		12	/
				Bar/HF or CF, P1070			1000		1070-1270		10	/

8.2.4B Mechanical Properties of Precipitation-Hardening Stainless Steels (Continued)

Standard	Grade, Class,	Steel	UNS	Product Form/Heat	Thick	ness	Yield Stre	ngth, min	Tensile Strength, min		Elongation,	Hardness, max
Designation	Type, Symbol or Name	Number		Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm² or MPa	ksi	min, %	HB/HRC/HV
				Bar, Shape/HR & CF, A								229/HRB98/
ASTM A 564/A 564M-02a	631		S17700	Bar, Shape/ HR & CF, RH950	≤ 100	≤ 4	1030	150	1280	185	6	388/41/
				Bar, Shape/ HR & CF, TH1050	≤ 150	≤ 6	965	140	1170	170	6	352/38/
				Bar/HF, S	≤ 75		380		1030		20	/
JIS G 4303:1998	SUS631			Bar/HF, RH950	≤ 75		1030		1230		4	/
				Bar/HF, TH1050	≤ 75		960		1140		5	/
				Bar/HF, S	≤ 75		380		1030		20	/
JIS G 4311:1991	SUS631			Bar/HF, RH950	≤ 75		1030		1230		4	/
				Bar/HF, TH1050	≤ 75		960		1140		5	/
EN 10088-3:1995	X7CrNiAl17-7	1.4568		Bar/HF or CF, AT	≤ 30				850 max			255//

8.2.5A Chemical Composition of Duplex Stainless Steels

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	max, Unless C	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 276-03			S31803	0.030	2.00	1.00	0.030	0.020	21.0-23.0	4.5-6.5	2.5-3.5	N 0.08-0.20
A3 1 W A 270-03			S32205	0.030	2.00	1.00	0.030	0.020	22.0-23.0	4.5-6.5	3.0-3.5	N 0.14-0.20
JIS G 4303:1998	SUS 329J3L			0.030	2.00	1.00	0.040	0.030	21.00-24.00	4.50-6.50	2.50-3.50	N 0.08-0.20
EN 10088-3:1995	X2CrNiMoN22-5-3	1.4462		0.030	2.00	1.00	0.035	0.015	21.00-23.00	4.50-6.50	2.50-3.50	N 0.10-0.22

8.2.5B Mechanical Properties of Duplex Stainless Steels

Standard	Grade, Class, Type,	Class, Type, Steel		UNS Product Form/Heat		Thickness		Yield Strength, min		Tensile Strength, min		Hardness, max
Designation	Symbol or Name	Number	Number	Treatment	t, mm	t, in.	N/mm ² or MPa	ksi	N/mm ² or MPa	ksi	Elongation, min, %	HB/HRC/HV
ASTM A 276-03			S31803	Bar, Shape/HF or CF, A	all	all	448	65	620	90	25	290//
A31W A 270-03			S32205	Bar, Shape/HF or CF, A	all	all	450	65	655	95	25	290//
JIS G 4303:1998	SUS 329J3L			Bar/HF, S	≤ 75		450		620		18	302/32/320
EN 10088-3:1995	X2CrNiMoN22-5-3	1.4462		Bar/HF or CF, AT	≤ 160		450		650-880		25	270//

8.3 Non-Comparable Stainless Steel Standards: Plate, Sheet and Strip

nless and He	at-Resisting Cl	hromium-Nicke	el Steel Plate, S	Sheet, and Strip	•						
308											
S30800											
nless and He	at-Resisting C	hromium Steel	Plate, Sheet, a	nd Strip							
422	431	442									
S42200	S43100	S44200									
03c - Chromi	um and Chrom	ium-Nickel Sta	inless Steel Pla	ate, Sheet, and	Strip for Press	ure Vessels ar	nd for General A	Applications			
	800	800H						XM-19	XM-31	XM-17	XM-18
N08020	N08800	N08810	N08811	N08926	S20161	S20162	S20400	S20910	S21400	S21600	S21603
	XM-29		304H		XM-21				309H	309Cb	309HCb
S21800	S24000	S28200	S30409	S30415	S30452	S30601	S30615	S30815	S30909	S30940	S30941
310H	310Cb	310HCb					316H	317	317LM		
S31009	S31040	S31041	S31200	S31260	S31266	S31277	S31609	S31700	S31725	S31803	S32001
			321H	255				329			
S32003	S32050	S32101	S32109	S32550	S32615	S32654	S32803	S32900	S32906	S32950	S33228
334		347H	348	348H				XM-15		409	
S33400	S34565	S34709	S34800	S34809	S35045	S35135	S35315	S38100	S38815	S40900	S40910
								429	436		XM-33
S40920	S40930	S40945	S40975	S41045	S41500	S42000	S42035	S42900	S43600	S44500	S44626
XM-27											
S44627	S44635	S44660	S44700	S44800	S46800						
ealed or Col	d-Worked Aust	enitic Stainless	Steel, Sheet,	Strip, Plate, an	d Flat Bar						
	205	XM-11	XM-14								
S20400	S20500	S21904	S21460								
cipitation-Ha	rdening Stainle	ss and Heat-Re	esisting Steel, I	Plate, Sheet an	d Strip						
633	634	635	XM-9	XM-12	XM-13	XM-16	XM-25				
S35000	S35500	S17600	S36200	S15500	S13800	S45500	S45000	S46500			
N08904, UN	S N08925, UNS	N08031, UNS	N08932, UNS N	l08926, and UN	S R20033 Plate	, Sheet, and S	trip				
N08925	N08932	N08031	N08926	R20033							
rolled stain	ess steel plate	s, sheets and s	trip								
SUS303	SUS304N2	SUS304J1	SUS304J2	SUS315J1	SUS315J2	SUS316J1	SUS316J1L	SUS317	SUS317J2	SUS317J3L	SUSXM7
USXM15J1	SUS429	SUS430J1L	SUS436L	SUS436J1L	SUS445J1	SUS445J2	SUS447J1	SUSXM27	SUS429J1	SUS440A	SUS329J1
00/11/1001											
	308 S30800 nless and He 422 S42200 03c - Chromi N08020 S21800 310H S31009 S32003 334 S33400 S40920 XM-27 S44627 ealed or Colo S20400 cipitation-Hai 633 S35000 S08904, UN N08925 rolled stainl	S30800	S308	S30800	Sans Sans	Sanson	Sant	308	Sample	Solon	Subsect Subs

8.3 Non-Comparable Stainless Steel Standards: Plate, Sheet and Strip (Continued)

JIS G 4305:1999 -	Cold rolled stai	inless steel plat	es, sheets and	strip								
Cumbal of Crade	SUS304N2	SUS304J1	SUS304J2	SUS315J1	SUS315J2	SUS316J1	SUS316J1L	SUS317	SUS317J2	SUS317J3L	SUSXM7	SUSXM15J1
Symbol of Grade	SUS329J1	SUS329J4L	SUS429	SUS430J1L	SUS436L	SUS436J1L	SUS445J1	SUS445J2	SUS447J1	SUSXM27	SUS429J1	SUS440A
JIS G 4312:1991 -	Heat-resisting	steel plates and	sheets									
Symbol of Grade	SUS317	SUSXM151J1	SUS410L	SUS430J1L	SUS436J1L	SUS410	SUH330	SUH660	SUH661	SUH21	SUH409	
EN 10088-2:1995 -	Stainless Stee	ls - Part 2: Tech	nical Delivery	Conditions for	Sheet/Plate an	d Strip for Gene	eral Purpose					
Steel Name	X6CrNiTi12	X2CrMoTi17-1	X6CrNi17-1	X2CrNbZr17	X2CrAlTi18-2	X39Cr13	X46Cr13	X50CrMoV15	X39CrMo17-1	X3CrNiMo13-4	X8CrNiS18-9	X1CrNi25-21
Steel Number	1.4516	1.4513	1.4017	1.4590	1.4605	1.4031	1.4034	1.4116	1.4122	1.4313	1.4305	1.4335
Steel Name	X1NiCrMc	Cu31-27-4	X1CrNiMo0	CuN25-25-5	X4CrNiMo16-5	-1 X6CrMc	Nb17-1					
Steel Number	1.4	563	1.4	537	1.4418	1.4	526					
EN 10095:1999 - H	eat Resisting S	teels and Nicke	el Alloys									
Steel Name	X10CrAlSi7	X10CrAlSi13	X10CrAlSi18	X10CrAlSi25	X3CrAlTi18-2	X8CrNiTi18-10	X15CrNiSi2	0-12 X12N	liCrSi35-16	X15CrNiSi25-4	NiCr15Fe	NiCr20Ti
Steel Number	1.4713	1.4724	1.4742	1.4762	1.4736	1.4878	1.4828	-	1.4864	1.4821	2.4816	2.4951
Steel Name	NiCr22	Mo9Nb	X6CrNiSil	NCe19-10	X6NiCrSi	NCe35-25	X10NiCı	rSiNb35-22	X9CrNis	SiNCe21-11-2	X10NiCr	AlTi32-21
Steel Number	2.4	856	1.4	1.4818		854	1.	4887	1	.4835	1.4	876
Steel Name	X6NiCrN	bCe32-27	X25CrMn	X25CrMnNiN25-9-7		NiCr23Fe		NiCr28FeSiCe		iCrSi35-19	X8Crl	Ni25-21
Steel Number	1.4	877	1.4	872	2.4	851	2.	4889	1	.4886	1.4	845

8.4 Non-Comparable Stainless Steel Standards: Bar

ASTM A 276-03 - S	tainless Steel E	Bars and Shape	es									
Grade, Class, Type			205	XM-19		XM-10	XM-11	XM-29	XM-28	302B		308
UNS Number	N08367	S20160	S20500	S20910	S21800	S21900	S21904	S24000	S24100	S30215	S30454	S30800
Grade, Class, Type		309Cb	310Cb		314	316Cb					-	348
UNS Number	S30815	S30940	S31040	S31254	S31400	S31640	S31654	S31725	S31726	S32654	S34565	S34800
Grade, Class, Type	XM-26					429	444		XM-30	414		
UNS Number	S31100	S32304	S32550	S32760	S40976	S42900	S44400	S44800	S41040	S41400	S41425	S41500
Grade, Class, Type												
UNS Number	S42010											
ASTM A 564/A 564	M-02a - Hot-Ro	lled and Cold-F	inished Age-H	ardening Stain	ess Steel Bars	and Shapes						
Grade, Class, Type	632	634	635	XM-12	XM-13	XM-16		XM-25				
UNS Number	S15700	S35500	S17600	S15500	S13800	S45500	S45503	S45000	S46500			
ASTM 582/A 582M-	95b (2000) - Fro	ee-Machining S	Stainless Steel	Bars								
Grade, Class, Type	XM-1	XM-5	XM-2	XM-6	416Se	420FSe	XM-34		430FSe	440F	440FSe	
UNS Number	S20300	S30310	S30345	S41610	S41623	S42023	S18200	S41603	S43023	S44020	S44023	
ASTM B 649-02 - N (UNS R20033) Bar a		Low-Carbon Al	loy (UNS N089	04), Ni-Fe-Cr-M	o-Cu-N Low-Ca	arbon Alloys (L	JNS N08925, UN	IS N08031, and	I UNS N08926),	and Cr-Ni-Fe-N	I Low-Carbon A	lloy
Grade, Class, Type												
UNS Number	N08925	N08031	N08926	R20033								
ASTM B 691-02 - Ir	on-Nickel-Chro	mium-Molybde	enum Alloys (U	NS N08366 and	UNS N08367)	Rod, Bar, and	Wire					
Grade, Class, Type												
UNS Number	N08366											
JIS G 4303:1998 - S	Stainless Steel	Bars										
Symbol of Grade	SUS303Cu	SUS304J3	SUS316J1	SUS316J1L	SUS316F	SUS317LN	SUSXM15J1	SUS329J1	SUS329J4L	SUS410L	SUS410J1	SUS410F2
Cymbol of Glade	SUS420F2	SUS440F	SUSXM7									
JIS G 4311:1991 - H	leat-Resisting	Steel Bars										
Symbol of Grade	SUSXM15J1	SUS410J1	SUH31	SUH35	SUH36	SUH37	SUH38	SUH330	SUH660	SUH661	SUH1	SUH3
Cymbol of Glade	SUH4	SUH11	SUH600	SUH616	SUS410L							
JIS G 4318:1998 - 0	Cold Finished S	Stainless Steel	Bars									
Symbol of Grade	SUS303Cu	SUS304J3	SUS305J1	SUS316F	SUS410F2	SUS420F2	SUS329J1					

8.4 Non-Comparable Stainless Steel Standards: Bar (Continued)

EN 10088-3:1995	- Stainless Steel	s – Part 3: Tec	hnical Delivery	Conditions for	Semi-Finishe	d Products, Ba	ars, Rod and Se	ctions for Gene	eral Purposes			
Steel Name	X2CrNi12	X39Cr13	X46Cr13	X50CrMoV15	X14CrMoS17	X39CrMo17-1	X3CrNiMo13-4	X90CrMoV18	X2CrNi19-11			
Steel Number	1.4003	1.4031	1.4034	1.4116	1.4104	1.4122	1.4313	1.4112	1.4306			
Steel Name	X3CrNiC	Cu18-9-4	X1NiCrMo	Cu25-20-5	X5CrNiMo	CuNb14-5	X6CrNiMo	Nb17-12-2	X2CrNiM	o18-14-3	X3CrNi	Cu19-9-2
Steel Number	1.4	567	1.4	1539	1.4	594	1.4580		1.44	135	1.4	1460
Steel Name	X6NiCrC	uS18-9-2	X3CrNiCul	X3CrNiCuMo17-11-3-2		X1NiCrMoCu31-27-4		X1CrNiMoCuN25-25-5		uN20-18-7	X1NiCrMc	CuN25-20-7
Steel Number	1.4	570	1.4578		1.4563		1.4537		1.4547		1.4	1529
Steel Name	X3CrNiM	oN27-5-2	X2CrN	NiN23-4	X2CrNiMo	CuN25-6-3	X2CrNiM	oN25-7-4	X2CrNiMoC	uWN25-7-4	X4CrNi	Mo16-5-1
Steel Number	1.4	460	1.4	362	1.4	507	1.4	410	1.4	501	1.4418	
Steel Name	X1CrNiSi18-15-4											
Steel Number	1.4361											
EN 10095:1999 - H	leat Resisting S	teels and Nick	el Alloys									
Steel Name	X10C	rAlSi7	X10C	rAlSi13	X10Ci	AlSi18	X10Cr	AISi25	X3CrA	Ti18-2	X8CrN	liTi18-10
Steel Number	1.4	713	1.4	724	1.4742		1.4742		1.4736		1.4	1878
Steel Name	X15CrN	iSi20-12	X12NiC	rSi35-16	X15CrN	NiSi25-4	NiCr	15Fe	NiCr	20Ti	NiCr22Mo9Nb	
Steel Number	1.4	328	1.4	864	1.4	821	2.4	816	2.49	951	2.4	1856
Steel Name	X6CrNiSiI	NCe19-10	X6NiCrS	NCe35-25	X10NiCr5	SiNb35-22	X9CrNiSiN	Ce21-11-2	X10NiCrA	AITi32-21	X6NiCrN	lbCe32-27
Steel Number	1.4	318	1.4	854	1.4	887	1.4	835	1.48	376	1.4	1877
Steel Name	X25CrMnl	X25CrMnNiN25-9-7 NiCr23Fe		NiCr28	FeSiCe	X10NiCi	rSi35-19	X8CrN	i25-21			
Steel Number	1.4	1.4872 2.4851		2.4889		1.4	886	1.48	345			
ISO 4955:1994 - H	eat-Resisting Steels and Alloys								-			
Ctool Tuno	X6Ci	Ti12	X10C	rAlSi13	X10Ci	AlSi18	X10Cr	AISi25	X6NiCr	Si36-19	X15Crl	NiSi20-12
Steel Type	X12NiCi	Si35-16	X8NiCr/	AITi32-21	X7CrNiSi	NCe21-11	NiCr1	5Fe8	NiCr	20Ti	NiCr2	2Mo9Nb

Chapter

9

STEELS FOR SPECIAL USE

418 Steels for Special Use - List of Standards Chapter 9

Free-Machining Steels

ASTM Standards

ASTM A 29/A 29M-03	General Requirements for Steel Bars, Carbon and Alloy, Hot-Wrought and Cold-Finished
ASTM A 576-90b (2000)	Standard Specification for Steel Bars, Carbon, Hot-Wrought, Special Quality
ASTM A 895-89 (2000)	Free-Machining Stainless Steel Plate, Sheet, and Strip

SAE Standard

SAE J403-NOV01	Chemical Compositions of SAE Carbon Steels

JIS Standard

JIS G 4804:1999	Free Cutting Carbon Steels

CEN Standards

EN 10087:1998	Free Cutting Steels - Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods
EN 10277-3:1999	Bright Steel Products - Technical Delivery Conditions - Part 3: Free-Cutting Steels

ISO Standard

ISO 683-9-1988	Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels - Part 9: Wrought Free-Cutting Steels	

Spring Steels

ASTM Standards

ASTM A 313/A 313M-03	Stainless Steel Spring Wire
ASTM A 682/A 682M-02	General Requirements For Steel, Strip, High-Carbon, Cold-Rolled
ASTM A 689-97 (2000)	Carbon and Alloy Steel Bars for Springs

JIS Standards

JIS G 4801:1984	Spring Steels
JIS G 4802:1999	Cold-Rolled Steel Strip for Springs
JIS G 4313:1996	Cold Rolled Stainless Steel Strip for Springs

CEN Standard

EN 10089:2002	Hot Rolled Steels for Quenched and Tempered Springs - Technical Delivery Conditions
EN 10132-4: 2000	Cold Rolled Narrow Steel Strip for Heat Treatment - Technical Delivery Conditions - Part 4: Spring Steels and Other Applications
EN 10151:2002	Stainless Steel Strip For Springs - Technical Delivery Conditions
EN 10270-3:2001	Steel Wire for Mechanical Springs

ISO Standard

ISO 683-14-1992	Heat-Treatable Steels, Alloy Steels and Free-Cutting Steels - Part 14: Hot-Rolled Steels for Quenched and
130 003-14-1992	Tempered Springs

Tool Steels

ASTM Standards

ASTM A 600-92a (1999)	Tool Steel High Speed
ASTM A 681-94 (1999)	Tool Steels Alloy
ASTM A 686-92 (1999)	Tool Steel, Carbon

SAE Standard

SAE J438 May 1970	Tool and Die Steels

JIS Standards

JIS G 4401: 2000	Carbon Tool Steels
JIS G 4403: 2000	High Speed Tool Steels
JIS G 4404: 2000	Alloy Tool Steels

ISO Standard

ISO 4957:1999	Tool Steels

Bearing Steels

ASTM Standards

ASTM A 295-98	High-Carbon Anti-Friction Bearing Steel
ASTM A 485-03	High Hardenability Antifriction Bearing Steel

JIS Standard

JIS G 4805:1999	High Carbon Chromium Bearing Steels	
IJIO G 4000. 1999	I liuli Calbon Chiomium Deamiu Steels	

ISO Standard

ISO 683-17:1999	Heat-Treated Steels, Alloy Steels and Free-Cutting Steels - Part 17: Ball and Roller Bearing Steels
-----------------	---

9.1 Free-Machining Steels

9.1.1 Chemical Composition of Resulfurized Carbon Steels for Free-Machining Applications

Standard Designation	Grade, Class, Type,	Steel Number	UNS Number	Weight, %, max, Unless Otherwise Specified								
	Symbol or Name			С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1109		G11090	0.08-0.13	0.60-0.90		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1109		G11090	0.08-0.13	0.60-0.90		0.040	0.08-0.13				
JIS G 4804:1999	SUM 12			0.08-0.13	0.60-0.90		0.040	0.08-0.13				
EN 10087:1998	10S20	1.0721		0.07-0.13	0.70-1.10	0.40	0.06	0.15-0.25				
EN 10277-3:1999	10S20	1.0721		0.07-0.13	0.70-1.10	0.40	0.06	0.15-0.25				
ISO 683-9:1988	10 S 20			0.07-0.13	0.70-1.10	0.15-0.40	0.06	0.15-0.25				
ASTM A 29/A 29M-03	1110		G11100	0.08-0.13	0.30-0.60		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1110		G11100	0.08-0.13	0.30-0.60		0.040	0.08-0.13				
JIS G 4804:1999	SUM 11			0.08-0.13	0.30-0.60		0.040	0.08-0.13				
ASTM A 29/A 29M-03	1117		G11700	0.14-0.20	1.00-1.30		0.040	0.08-0.13				
	1118		G11180	0.14-0.20	1.30-1.60		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1117		G11700	0.14-0.20	1.00-1.30		0.040	0.08-0.13				
	1118		G11180	0.14-0.20	1.30-1.60		0.040	0.08-0.13				
SAE J403-NOV01	1117		G11700	0.14-0.20	1.00-1.30		0.030	0.08-0.13				
	1118		G11180	0.14-0.20	1.30-1.60		0.030	0.08-0.13				
JIS G 4804:1999	SUM 31			0.14-0.20	1.00-1.30		0.040	0.08-0.13				
	SUM 32			0.12-0.20	0.60-1.10		0.040	0.10-0.20				
EN 10087:1998	15SMn13	1.0725		0.12-0.18	0.90-1.30	0.40	0.06	0.08-0.18				
EN 10277-3:1999	15SMn13	1.0725		0.12-0.18	0.90-1.30	0.40	0.06	0.08-0.18				
ISO 683-9:1988	17 SMn 20			0.14-0.20	1.20-1.60	0.15-0.40	0.06	0.15-0.25				
ASTM A 29/A 29M-03	1137		G11370	0.32-0.39	1.35-1.65		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1137		G11370	0.32-0.39	1.35-1.65		0.040	0.08-0.13				
SAE J403-NOV01	1137		G11370	0.32-0.39	1.35-1.65		0.030	0.08-0.13				
JIS G 4804:1999	SUM 41			0.32-0.39	1.35-1.65		0.040	0.08-0.13				
EN 10087:1998	35S20	1.0726		0.32-0.39	0.70-1.10	0.40	0.06	0.15-0.25				
	36SMn14	1.0764		0.32-0.39	1.30-1.70	0.40	0.06	0.10-0.18				
EN 10277-3:1999	35S20	1.0726		0.32-0.39	0.70-1.10	0.40	0.06	0.15-0.25				
	36SMn14	1.0764		0.32-0.39	1.30-1.70	0.40	0.06	0.10-0.18				
ISO 683-9:1988	35 S 20			0.32-0.39	0.70-1.10	0.15-0.40	0.06	0.15-0.25				
	35 SMn 20			0.32-0.39	0.90-1.40	0.15-0.40	0.06	0.15-0.25				
ASTM A 29/A 29M-03	1139		G11390	0.35-0.43	1.35-1.65		0.040	0.13-0.20				
ASTM A 576-90b (2000)	1139		G11390	0.35-0.43	1.35-1.65		0.040	0.13-0.20				
SAE J403-NOV01	1138		G11380	0.34-0.40	0.70-1.00		0.030	0.08-0.13				
EN 10087:1998	38SMn28	1.0760		0.35-0.40	1.20-1.50	0.40	0.06	0.24-0.33				
EN 10277-3:1999	38SMn28	1.0760		0.35-0.40	1.20-1.50	0.40	0.06	0.24-0.33				

9.1.1 Chemical Composition of Resulfurized Carbon Steels for Free-Machining Applications (Continued)

Standard	Grade, Class, Type,	Steel	UNS				\	Veight, %, ma	x, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1140		G11400	0.37-0.44	0.70-1.00		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1140		G11400	0.37-0.44	0.70-1.00		0.040	0.08-0.13				
SAE J403-NOV01	1140		G11400	0.37-0.44	0.70-1.00		0.030	0.08-0.13				
ASTM A 29/A 29M-03	1141		G11410	0.37-0.45	1.35-1.65		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1141		G11410	0.37-0.45	1.35-1.65		0.040	0.08-0.13				
SAE J403-NOV01	1141		G11410	0.37-0.45	1.35-1.65		0.030	0.08-0.13				
JIS G 4804:1999	SUM 42			0.37-0.45	1.35-1.65		0.040	0.08-0.13				
ASTM A 29/A 29M-03	1144		G11440	0.40-0.48	1.35-1.65		0.040	0.24-0.33				
ASTM A 576-90b (2000)	1144		G11440	0.40-0.48	1.35-1.65		0.040	0.24-0.33				
SAE J403-NOV01	1144		G11440	0.40-0.48	1.35-1.65		0.030	0.24-0.33				
JIS G 4804:1999	SUM 43			0.40-0.48	1.35-1.65		0.040	0.24-0.33				
EN 10087:1998	44SMn28	1.0762		0.40-0.48	1.30-1.70	0.40	0.06	0.24-0.33				
EN 10277-3:1999	44SMn28	1.0762		0.40-0.48	1.30-1.70	0.40	0.06	0.24-0.33				
ISO 683-9:1988	44 SMn 28			0.40-0.48	1.30-1.70	0.15-0.40	0.06	0.24-0.33				
ASTM A 29/A 29M-03	1146		G11460	0.42-0.49	0.70-1.00		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1146		G11460	0.42-0.49	0.70-1.00		0.040	0.08-0.13				
SAE J403-NOV01	1146		G11460	0.42-0.49	0.70-1.00		0.030	0.08-0.13				
EN 10087:1998	46S20	1.0727		0.42-0.50	0.70-1.10	0.40	0.06	0.15-0.25				
EN 10277-3:1999	46S20	1.0727		0.42-0.50	0.70-1.10	0.40	0.06	0.15-0.25				
ISO 683-9:1988	46 S 20			0.42-0.50	0.70-1.10	0.15-0.40	0.06	0.15-0.25				
ASTM A 29/A 29M-03	1151		G11510	0.48-0.55	0.70-1.00		0.040	0.08-0.13				
ASTM A 576-90b (2000)	1151		G11510	0.48-0.55	0.70-1.00		0.040	0.08-0.13				
SAE J403-NOV01	1151		G11510	0.48-0.55	0.70-1.00		0.030	0.08-0.13				

9.1.2 Chemical Composition of Rephosphorized and Resulfurized Carbon Steels for Free-Machining Applications

Standard	Grade, Class, Type,	Steel	UNS				V	/eight, %, m	ax, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	1212		G12120	0.13	0.70-1.00		0.07-0.12	0.16-0.23				
ASTM A 576-90b (2000)	1212		G12120	0.13	0.70-1.00		0.07-0.12	0.16-0.23				
SAE J403-NOV01	1212		G12120	0.13	0.70-1.00		0.07-0.12	0.16-0.23				
JIS G 4804:1999	SUM 21			0.13	0.70-1.00		0.07-0.12	0.16-0.23				
ISO 683-9:1988	9 S 20			0.13	0.60-1.20	0.05	0.11	0.15-0.25				
ASTM A 29/A 29M-03	1213		G12130	0.13	0.70-1.00		0.07-0.12	0.24-0.33				
ASTM A 576-90b (2000)	1213		G12130	0.13	0.70-1.00		0.07-0.12	0.24-0.33				
SAE J403-NOV01	1213		G12130	0.13	0.70-1.00		0.07-0.12	0.24-0.33				
JIS G 4804:1999	SUM 22			0.13	0.70-1.00		0.07-0.12	0.24-0.33				
EN 10087:1998	11SMn30	1.0715		0.14	0.90-1.30	0.05	0.11	0.27-0.33				
EN 10277-3:1999	11SMn30	1.0715		0.14	0.90-1.30	0.05	0.11	0.27-0.33				
ISO 683-9:1988	11 SMn 28			0.14	0.90-1.30	0.05	0.11	0.24-0.33				
ASTM A 29/A 29M-03	1215		G12150	0.09	0.75-1.05		0.04-0.09	0.26-0.35				
ASTM A 576-90b (2000)	1215		G12150	0.09	0.75-1.05		0.04-0.09	0.26-0.35				
SAE J403-NOV01	1215		G12150	0.09	0.75-1.05		0.04-0.09	0.26-0.35				
JIS G 4804:1999	SUM 23			0.09	0.75-1.05		0.04-0.09	0.26-0.35				
JIS G 4804:1999	SUM 25			0.15	0.90-1.40		0.07-0.12	0.30-0.40				
EN 10087:1998	11SMn37	1.0736		0.14	1.00-1.50	0.05	0.11	0.34-0.40				
EN 10277-3:1999	11SMn37	1.0736		0.14	1.00-1.50	0.05	0.11	0.34-0.40				
ISO 683-9:1988	12 SMn 35			0.15	1.00-1.50	0.05	0.11	0.30-0.40				

9.1.3 Chemical Composition of Resulfurized and Leaded Carbon Steels for Free-Machining Applications

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %, ma	ax, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	11 L 09		G11094	0.08-0.13	0.60-0.90		0.040	0.08-0.13				Pb 0.15-0.35
ASTM A 576-90b (2000)	11 L 09		G11094	0.08-0.13	0.60-0.90		0.040	0.08-0.13				Pb 0.15-0.35
EN 10087:1998	10SPb20	1.0722		0.07-0.13	0.70-1.10	0.40	0.06	0.15-0.25				Pb 0.20-0.35
EN 10277-3:1999	10SPb20	1.0722		0.07-0.13	0.70-1.10	0.40	0.06	0.15-0.25				Pb 0.20-0.35
ISO 683-9:1988	10 SPb 20			0.07-0.13	0.70-1.10	0.15-0.40	0.06	0.15-0.25				Pb 0.15-0.35
ASTM A 29/A 29M-03	11 L 17		G11174	0.14-0.20	1.00-1.30		0.040	0.08-0.13				Pb 0.15-0.35
ASTM A 576-90b (2000)	11 L 17		G11174	0.14-0.20	1.00-1.30		0.040	0.08-0.13				Pb 0.15-0.35
SAE J403-NOV01	11L17		G11174	0.14-0.20	1.00-1.30		0.030	0.08-0.13				Pb 0.15-0.35
JIS G 4804:1999	SUM 31 L			0.14-0.20	1.00-1.30		0.040	0.08-0.13				Pb 0.10-0.35
ASTM A 29/A 29M-03	11 L 37		G11374	0.32-0.39	1.35-1.65		0.040	0.08-0.13				Pb 0.15-0.35
ASTM A 576-90b (2000)	11 L 37		G11374	0.32-0.39	1.35-1.65		0.040	0.08-0.13				Pb 0.15-0.35
SAE J403-NOV01	11L37		G11374	0.32-0.39	1.35-1.65		0.030	0.08-0.13				Pb 0.15-0.35
EN 10087:1998	36SMnPb14	1.0765		0.32-0.39	1.30-1.70	0.40	0.06	0.10-0.18				Pb 0.15-0.35
EN 10277-3:1999	36SMnPb14	1.0765		0.32-0.39	1.30-1.70	0.40	0.06	0.10-0.18				Pb 0.15-0.35
ASTM A 29/A 29M-03	11 L 41		G11414	0.37-0.45	1.35-1.65		0.040	0.08-0.13				Pb 0.15-0.35
ASTM A 576-90b (2000)	11 L 41		G11414	0.37-0.45	1.35-1.65		0.040	0.08-0.13				Pb 0.15-0.35
SAE J403-NOV01	11L41		G11414	0.37-0.45	1.35-1.65		0.030	0.08-0.13				Pb 0.15-0.35
EN 10087:1998	38SMnPb28	1.0761		0.35-0.40	1.20-1.50	0.40	0.06	0.24-0.33				Pb 0.15-0.35
EN 10277-3:1999	38SMnPb28	1.0761		0.35-0.40	1.20-1.50	0.40	0.06	0.24-0.33				Pb 0.15-0.35
ASTM A 29/A 29M-03	11 L 44		G11444	0.40-0.48	1.35-1.65		0.040	0.24-0.33				Pb 0.15-0.35
ASTM A 576-90b (2000)	11 L 44		G11444	0.40-0.48	1.35-1.65		0.040	0.24-0.33				Pb 0.15-0.35
SAE J403-NOV01	11L44		G11444	0.40-0.48	1.35-1.65		0.030	0.24-0.33				Pb 0.15-0.35
EN 10087:1998	44SMnPb28	1.0763		0.40-0.48	1.30-1.70	0.40	0.06	0.24-0.33				Pb 0.15-0.35
EN 10277-3:1999	44SMnPb28	1.0763		0.40-0.48	1.30-1.70	0.40	0.06	0.24-0.33				Pb 0.15-0.35
ASTM A 29/A 29M-03	11 L 46		G11464	0.42-0.49	0.70-1.00		0.040	0.08-0.13				Pb 0.15-0.35
ASTM A 576-90b (2000)	11 L 46		G11464	0.42-0.49	0.70-1.00		0.040	0.08-0.13				Pb 0.15-0.35
SAE J403-NOV01	11L46		G11464	0.42-0.49	0.70-1.00		0.030	0.08-0.13				Pb 0.15-0.35
EN 10087:1998	46SPb20	1.0757		0.42-0.50	0.70-1.10	0.40	0.06	0.15-0.25				Pb 0.15-0.35
EN 10277-3:1999	46SPb20	1.0757		0.42-0.50	0.70-1.10	0.40	0.06	0.15-0.25				Pb 0.15-0.35

9.1.4 Chemical Composition of Rephosphorized, Resulfurized, and Leaded Carbon Steels for Free-Machining Applications

Standard	Grade, Class, Type,	Steel	UNS				W	eight, %, m	ax, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 29/A 29M-03	12 L 13		G12134	0.13	0.70-1.00		0.07-0.12	0.24-0.33				Pb 0.15-0.35
ASTM A 576-90b (2000)	12 L 13		G12134	0.13	0.70-1.00		0.07-0.12	0.24-0.33				Pb 0.15-0.35
SAE J403-NOV01	12L13		G12134	0.13	0.70-1.00		0.07-0.12	0.24-0.33				Pb 0.15-0.35
JIS G 4804:1999	SUM 22 L			0.13	0.70-1.00		0.07-0.12	0.24-0.33				Pb 0.10-0.35
EN 10087:1998	11SMnPb30	1.0718		0.14	0.90-1.30	0.05	0.11	0.27-0.33				Pb 0.20-0.35
EN 10277-3:1999	11SMnPb30	1.0718		0.14	0.90-1.30	0.05	0.11	0.27-0.33				Pb 0.20-0.35
ISO 683-9:1988	11 SMnPb 28			0.14	0.90-1.30	0.05	0.11	0.24-0.33				Pb 0.15-0.35
ASTM A 29/A 29M-03	12 L 14		G12144	0.15	0.85-1.15		0.04-0.09	0.26-0.35				Pb 0.15-0.35
ASTM A 576-90b (2000)	12 L 14			0.15	0.85-1.15		0.04-0.09	0.26-0.35				Pb 0.15-0.35
SAE J403-NOV01	12L14		G12144	0.15	0.85-1.15		0.04-0.09	0.26-0.35				Pb 0.15-0.35
JIS G 4804:1999	SUM 24 L			0.15	0.85-1.15		0.04-0.09	0.26-0.35				Pb 0.10-0.35
ASTM A 29/A 29M-03	12 L 15		G12154	0.09	0.75-1.05		0.04-0.09	0.26-0.35				Pb 0.15-0.35
ASTM A 576-90b (2000)	12 L 15		G12154	0.09	0.75-1.05		0.04-0.09	0.26-0.35				Pb 0.15-0.35
SAE J403-NOV01	12L15		G12154	0.09	0.75-1.05		0.04-0.09	0.26-0.35				Pb 0.15-0.35
JIS G 4804:1999	SUM 23 L			0.09	0.75-1.05		0.04-0.09	0.26-0.35				Pb 0.10-0.35
EN 10087:1998	11SMnPb37	1.0737		0.14	1.00-1.50	0.05	0.11	0.34-0.40				Pb 0.20-0.35
EN 10277-3:1999	11SMnPb37	1.0737		0.14	1.00-1.50	0.05	0.11	0.34-0.40				Pb 0.20-0.35
ISO 683-9:1988	12 SMnPb 35			0.15	1.00-1.50	0.05	0.11	0.30-0.40				Pb 0.15-0.35

9.1.5 Chemical Composition of Free-Machining Stainless Steels

Standard	Grade, Class, Type,	Steel	UNS				٧	/eight, %, m	nax, Unless C	therwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 895-89 (2000)	416		S41600	0.15	1.25	1.00	0.06	0.15 min	12.00-14.00			
EN 10088-3:1995	X12CrS13	1.4005		0.08-0.15	1.50	1.00	0.040	0.15-0.35	12.00-14.00		0.60	
ASTM A 895-89 (2000)	303		S30300	0.15	2.00	1.00	0.20	0.15 min	17.00-19.00	8.00-10.00		
EN 10088-3:1995	X8CrNiS18-9	1.4305		0.10	2.00	1.00	0.045	0.15-0.35	17.00-19.00	8.00-10.00		N 0.11; Cu 1.00

9.2.1 Chemical Composition of Cold Rolled Carbon Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, m	ax, Unless	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 682/A 682M-02	1040		G10400	0.37-0.44	0.60-0.90	0.15-0.30	0.035	0.040				
ASTM A 689-97 (2000)	1040		G10400	0.37-0.44	0.60-0.90	0.15-0.30	0.040	0.050				
EN 10089:2002	38Si7	1.5023		0.35-0.42	0.50-0.80	1.50-1.80	0.025	0.025				Cu+10Sn see standard
ASTM A 682/A 682M-02	1050		G10500	0.48-0.55	0.60-0.90	0.15-0.30	0.035	0.040				
ASTM A 689-97 (2000)	1050		G10500	0.48-0.55	0.60-0.90	0.15-0.30	0.040	0.050				
JIS G 4802:1999	S50C-CSP			0.47-0.53	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10089:2002	46Si7	1.5024		0.42-0.50	0.50-0.80	1.50-2.00	0.025	0.025				Cu+10Sn see standard
ASTM A 682/A 682M-02	1055		G10550	0.50-0.60	0.60-0.90	0.15-0.30	0.035	0.040				
ASTM A 689-97 (2000)	1055		G10550	0.50-0.60	0.60-0.90	0.15-0.30	0.040	0.050				
ASTM A 713-04	1055		G10550	0.50-0.60	0.60-0.90		0.040	0.050				
JIS G 4802:1999	S55C-CSP			0.52-0.58	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10089:2002	56Si7	1.5026		0.52-0.60	0.60-0.90	1.60-2.00	0.025	0.025				Cu+10Sn see standard
EN 10132-4:2000	C55S	1.1204		0.52-0.60	0.60-0.90	0.15-0.35	0.025	0.025	0.40	0.40	0.10	
ASTM A 682/A 682M-02	1060		G10600	0.55-0.65	0.60-0.90	0.15-0.30	0.035	0.040				
ASTM A 689-97 (2000)	1060		G10600	0.55-0.65	0.60-0.90	0.15-0.30	0.040	0.050				
ASTM A 713-04	1060		G10600	0.55-0.65	0.60-0.90		0.040	0.050				
JIS G 4802:1999	S60C-CSP			0.55-0.65	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10132-4:2000	C60S	1.1211		0.57-0.65	0.60-0.90	0.15-0.35	0.025	0.025	0.40	0.40	0.10	
ASTM A 682/A 682M-02	1064		G10640	0.60-0.70	0.50-0.80	0.15-0.30	0.035	0.040				
ASTIVI A 002/A 002IVI-UZ	1065		G10650	0.60-0.70	0.60-0.90	0.15-0.30	0.035	0.040				
ASTM A 713-04	1064		G10640	0.60-0.70	0.50-0.80		0.035	0.040				
ASTIVI A 713-04	1065		G10650	0.60-0.70	0.60-0.90		0.035	0.040				
JIS G 4802:1999	S65C-CSP			0.60-0.70	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
ASTM A 682/A 682M-02	1070		G10700	0.65-0.75	0.60-0.90	0.15-0.30	0.035	0.040				
ASTM A 689-97 (2000)	1070		G10700	0.65-0.75	0.60-0.90	0.15-0.30	0.040	0.050				
ASTM A 713-04	1070		G10700	0.65-0.75	0.60-0.90		0.040	0.050				
JIS G 4802:1999	S70C-CSP			0.65-0.75	0.60-0.90	0.15-0.35	0.030	0.035	0.20	0.20		Cu 0.30; Ni+Cr 0.35
EN 10132-4:2000	C67S	1.1231		0.65-0.73	0.60-0.90	0.15-0.35	0.025	0.025	0.40	0.40	0.10	
ASTM A 682/A 682M-02	1074		G10740	070-0.80	0.50-0.80	0.15-0.30	0.035	0.040				
ASTM A 713-04	1074		G10740	070-0.80	0.50-0.80		0.040	0.050				
EN 10132-4:2000	C75S	1.1248		0.70-0.80	0.60-0.90	0.15-0.35	0.025	0.025	0.40	0.40	0.10	
ASTM A 689-97 (2002)	1078		G10780	0.72-0.85	0.30-0.60		0.040	0.050				
ASTM A 713-04	1078		G10780	0.72-0.85	0.30-0.60		0.040	0.050				
JIS G 4801:1984	SUP 3			0.75-0.90	0.30-0.60	0.15-0.35	0.035	0.035				Cu 0.30

9.2.1 Chemical Composition of Cold Rolled Carbon Spring Steels (Continued)

Standard	Grade, Class, Type,	Steel	UNS				٧	Veight, %, m	ax, Unless	Otherwise S	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 682/A 682M-02	1085		G10850	0.80-0.95	0.70-1.00	0.15-0.30	0.035	0.040				
ASTM A 713-04	1084		G10840	0.80-0.93	0.60-0.90	0.15-0.30	0.040	0.050				
JIS G 4802:1999	SK5-CSP			0.80-0.90	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
EN 10132-4:2000	C85S	1.1269		0.80-0.90	0.40-0.70	0.15-0.35	0.025	0.025	0.40	0.40	0.10	
ASTM A 682/A 682M-02	1086		G10860	0.80-0.93	0.30-0.50	0.15-0.30	0.035	0.040				
ASTM A 713-04	1086		G10860	0.80-0.93	0.30-0.50		0.040	0.050				
EN 10132-4:2000	C90S	1.1217		0.85-0.95	0.40-0.70	0.15-0.35	0.025	0.025	0.40	0.40	0.10	
ASTM A 682/A 682M-02	1095		G10950	0.90-1.03	0.30-0.50	0.15-0.30	0.035	0.040				
ASTM A 689-97 (2000)	1095		G10950	0.90-1.03	0.30-0.50	0.15-0.30	0.040	0.050				
ASTM A 713-04	1095		G10950	0.90-1.03	0.30-0.50		0.040	0.050				
JIS G 4802:1999	SK4-CSP			0.90-1.00	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
EN 10132-4:2000	C100S	1.1274		0.95-1.05	0.30-0.60	0.15-0.35	0.025	0.025	0.40	0.40	0.10	

9.2.2 Chemical Composition of Hot Rolled Alloy Spring Steels

9.2.2.1 Chemical Composition of Hot Rolled Si Alloy Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	x, Unless Ot	therwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 4801:1984	SUP 6			0.56-0.64	0.70-1.00	1.50-1.80	0.035	0.035				Cu 0.30
ISO 683-14:1992	59 Si 7			0.55-0.63	0.60-1.00	1.60-2.00	0.030	0.030				
ASTM A 689-97 (2002)	9260		G92600	0.56-0.64	0.75-1.00	1.80-2.20	0.035	0.040				
JIS G 4801:1984	SUP 7			0.56-0.64	0.70-1.00	1.80-2.20	0.035	0.035				Cu 0.30

9.2.2.2 Chemical Composition of Hot Rolled Cr Alloy Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	x, Unless Ot	herwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 689-97 (2002)	5155		G51550	0.51-0.59	0.70-0.90	0.15-0.35	0.035	0.040	0.70-0.90			
JIS G 4801:1984	SUP 9			0.52-0.60	0.65-0.95	0.15-0.35	0.035	0.035	0.65-0.95			Cu 0.30
EN 10089:2002	55Cr3	1.7176		0.52-0.59	0.70-1.00	0.40	0.025	0.025	0.70-1.00			Cu+10Sn see standard
ISO 683-14:1992	55 Cr 3			0.52-0.59	0.70-1.00	0.15-0.40	0.030	0.030	0.70-1.00			
ASTM A 689-97 (2002)	5160		G51600	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.70-0.90			
JIS G 4801:1984	SUP 9 A			0.56-0.64	0.70-1.00	0.15-0.35	0.035	0.035	0.70-1.00			Cu 0.30
EN 10089:2002	60Cr3	1.7177		0.55-0.65	0.70-1.00	0.40	0.025	0.025	0.60-0.90			Cu+10Sn see standard

9.2.2.3 Chemical Composition of Hot Rolled Cr-Si Alloy Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	x, Unless Ot	herwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 4801:1984	SUP 12			0.51-0.59	0.60-0.90	1.20-1.60	0.035	0.035	0.60-0.90			
EN 10089:2002	54SiCr6	1.7102		0.51-0.59	0.50-0.80	1.20-1.60	0.025	0.025	0.50-0.80			Cu+10Sn see standard
ISO 683-14:1992	55 SiCr 6 3			0.51-0.59	0.50-0.80	1.20-1.60	0.030	0.030	0.55-0.85			

9.2.2.4 Chemical Composition of Hot Rolled Cr-Mo Alloy Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	ıx, Unless Ot	herwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 689-97 (2002)	4161		G41610	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.70-0.90		0.25-0.35	
JIS G 4801:1984	SUP 13			0.56-0.64	0.70-1.00	0.15-0.35	0.035	0.035	0.70-0.90		0.25-0.35	
	60CrMo3-1	1.7239		0.56-0.64	0.70-1.00	0.40	0.025	0.025	0.70-1.00		0.06-0.15	Cu+10Sn see standard
EN 10089:2002	60CrMo3-2	1.7240		0.56-0.64	0.70-1.00	0.40	0.025	0.025	0.70-1.00		0.15-0.25	Cu+10Sn see standard
	60CrMo3-3	1.7241		0.56-0.64	0.70-1.00	0.40	0.025	0.025	0.70-1.00		0.25-0.35	Cu+10Sn see standard
ISO 683-14:1992	60 CrMo 3 3			0.56-0.64	0.70-1.00	0.15-0.40	0.030	0.030	0.70-1.00		0.25-0.35	

9.2.2.5 Chemical Composition of Hot Rolled Cr-V Alloy Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	x, Unless Ot	herwise Sp	ecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 4801:1984	SUP 10			0.47-0.55	0.65-0.95	0.15-0.35	0.035	0.035	0.80-1.10			V 0.15-0.25; Cu 0.30
JIS G 4802:1999	SUP10-CSP			0.47-0.55	0.65-0.95	0.15-0.35	0.035	0.035	0.80-1.10			V 0.15-0.25
EN 10089:2002	51CrV4	1.8159		0.47-0.55	0.70-1.10	0.40	0.025	0.025	0.90-1.20			V 0.10-0.25; Cu+10Sn see standard
EN 10132-4:2002	51CrV4	1.8159		0.47-0.55	0.70-1.10	0.40	0.025	0.025	0.90-1.20	0.40	0.10	V 0.10-0.25
ISO 683-14:1992	51 CrV 4			0.47-0.55	0.60-1.00	0.100.40	0.030	0.030	0.80-1.10			V 0.10-0.25
ASTM A 689-97 (2002)	6150		G61500	0.48-0.53	0.70-0.90	0.15-0.35	0.035	0.040	0.80-1.10			V 0.15
EN 10089:2002	54SiCrV6	1.8152		0.51-0.59	0.50-0.80	1.20-1.60	0.025	0.025	0.50-0.80			V 0.10-0.20; Cu+10Sn see standard

9.2.2.6 Chemical Composition of Hot Rolled Cr-B Alloy Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	x, Unless Ot	herwise Sp	ecified		
Designation	Symbol or Name	Number	Number	The state of the s									
ASTM A 689-97 (2002)	51 B 60		G51601	0.56-0.64	0.75-1.00	0.15-0.35	0.035	0.040	0.70090			B 0.0005-0.003	
JIS G 4801:1984	SUP 11 A			0.56-0.64	0.70-1.00	0.15-0.35	0.035	0.035	0.70-1.00			B 0.0005; Cu 0.30	
ISO 683-14:1992	60 CrB 3			0.56-0.64	0.70-1.00	0.15-0.40	0.030	0.030	0.60-0.90			B 0.0008	

9.2.3 Chemical Composition of Stainless Spring Steels

Standard	Grade, Class, Type,	Steel	UNS				W	eight, %, n	nax, Unless C	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 4313:1996	SUS 420J2-CSP			0.26-0.40	1.00	1.00	0.040	0.030	12.00-14.00			
EN 10151:2002	X30Cr13	1.4028		0.26-0.35	1.50	1.00	0.040	0.015	12.0-14.0			
EN 10151.2002	X39Cr13	1.4031		0.36-0.42	1.00	1.00	0.040	0.015	12.5-14.5			
ASTM A 313/A 313M-03	302		S30200	0.12	2.00	1.00	0.045	0.030	17.0-19.0	8.0-10.0		N 0.10
EN 10151:2002	X10CrNi18-8	1.4310		0.05-0.15	2.00	2.00	0.045	0.015	16.0-19.0	6.0-9.5	0.80	N 0.11
EN 10270-3:2001	X10CrNi18-8	1.4310		0.05-0.15	2.00	2.00	0.045	0.015	16.00-19.00	6.00-9.50	0.80	N 0.11
JIS G 4313:1996	SUS 301-CSP			0.15	0.50-2.00	0.20-1.00	0.045	0.030	16.00-18.00	6.00-8.00		
ASTM A 313/A 313M-03	304		S30400	0.08	2.00	1.00	0.045	0.030	18.0-20.0	8.0-10.5		N 0.10
JIS G 4313:1996	SUS 304-CSP			0.08	2.00	1.00	0.045	0.030	18.00-20.00	8.00-10.50		
EN 10151:2002	X5CrNi18-10	1.4301		0.07	2.00	1.00	0.045	0.015	17.5-19.5	8.0-10.5		N 0.11
ASTM A 313/A 313M-03	316		S31600	0.07	2.00	1.00	0.045	0.030	16.5-18.0	10.5-13.5	2.00-2.50	N 0.10
EN 10151:2002	X5CrNiMo17-12-2	1.4401		0.07	2.00	1.00	0.045	0.015	16.5-18.5	10.0-13.0	2.00-2.50	N 0.11
ASTM A 313/A 313M-03	631		S17700	0.09	1.00	1.00	0.040	0.030	16.0-18.0	6.5-7.8		Al 0.75-1.50
EN 10151:2002	X7CrNiAl17-7	1.4568		0.09	1.00	0.70	0.040	0.015	16.0-18.0	6.5-7.8		Al 0.70-1.50
JIS G 4313:1996	SUS 631-CSP			0.09	1.00	1.00	0.040	0.030	16.00-18.00	6.5-7.75		Al 0.75-1.50

9.3 Tool Steels

9.3.1 Chemical Composition of Carbon Tool Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, ma	ax, Unless C	Otherwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
JIS G 4401:2000	SK65			0.60-0.70	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
ISO 4957:1999	C70U			0.65-0.75	0.10-0.40	0.10-0.30	0.030	0.030				
SAE J438-1970	W108		T72301	0.70-0.85								
JIS G 4401:2000	SK75			0.70-0.80	0.50	0.35	0.030	0.030	0.030	0.25		Cu 0.25
ISO 4957:1999	C80U			0.75-0.85	0.10-0.40	0.10-0.30	0.030	0.030				
ASTM A 686-92 (1999)	W1-A-8		T72301	0.80-0.90	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.10; W 0.15; Cu 0.20
JIS G 4401:2000	SK85			0.80-0.90	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
ASTM A 686-92 (1999)	W1-A-81/2		T72301	0.85-0.95	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.10; W 0.15; Cu 0.20
SAE J438-1970	W109		T72301	0.85-0.95								
ISO 4957:1999	C90U			0.85-0.95	0.10-0.40	0.10-0.30	0.030	0.030				
ASTM A 686-92 (1999)	W1-A-9		T72301	0.90-1.00	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.10; W 0.15; Cu 0.20
JIS G 4401:2000	SK95			0.90-1.00	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
ASTM A 686-92 (1999)	W1-A-10		T72301	1.00-1.10	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.10; W 0.15; Cu 0.20
SAE J438-1970	W110		T72301	0.95-1.10								
JIS G 4401:2000	SK105			1.00-1.10	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
ISO 4957:1999	C105U			1.00-1.10	0.10-0.40	0.10-0.30	0.030	0.030				
ASTM A 686-92 (1999)	W1-A-11½		T72301	1.15-1.25	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.10; W 0.15; Cu 0.20
SAE J438-1970	W112		T72301	1.10-1.30								
JIS G 4401:2000	SK120			1.10-1.30	0.50	0.35	0.030	0.030	0.30	0.25		Cu 0.25
ISO 4957:1999	C120U			1.15-1.25	0.10-0.40	0.10-0.30	0.030	0.030				
ASTM A 686-92 (1999)	W2-A-91/2			0.95-1.10	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.15-0.35; W 0.15; Cu 0.20
JIS G 4404:2000	SKS 43			1.00-1.10	0.30	0.25	0.030	0.030	0.20	0.25		V 0.10-0.25; Cu 0.25
ISO 4957:1999	105V			1.00-1.10	0.10-0.40	0.10-0.30						V 0.10-0.20
ASTM A 686-92 (1999)	W2-A-8½			0.85-0.95	0.10-0.40	0.10-0.40	0.030	0.030	0.15	0.20	0.10	V 0.15-0.35; W 0.15; Cu 0.20
JIS G 4404:2000	SKS 44			0.80-0.90	0.30	0.25	0.030	0.030	0.20	0.25		V 0.10-0.25; Cu 0.25

9.3 Tool Steels

Chemical Composition of High Speed Tool Steels 9.3.2

9.3.2.1 Chemical Composition of Tungsten Type High Speed Tool Steels

Standard	Grade, Class, Type,	Steel	UNS				We	eight, %, m	ax, Unless O	therwise S	pecified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 600-92a (1999)	T1		T12001	0.65-0.80	0.10-0.40	0.20-0.40	0.03	0.03	3.75-4.50			V 0.90-1.30; W 17.25-18.75; Ni+Cu 0.75
SAE J438-1970	T1		T12001	0.65-0.75	0.20-0.40	0.20-0.40			3.75-4.50			V 0.90-1.30; W 17.25-18.75
JIS G 4403:2000	SKH2			0.73-0.83	0.40	0.40	0.030	0.030	3.80-4.50	0.25		V 0.80-1.20; W 17.00-19.00; Cu 0.25
ISO 4957:1999	HS18-0-1			0.73-0.83	0.40	0.45	0.030	0.030	3.80-4.50			V 1.00-1.20; W 17.20-18.70
ASTM A 600-92a (1999)	T4		T12004	0.70-0.80	0.10-0.40	0.20-0.40	0.03	0.03	3.75-4.50		0.40-1.00	V 0.80-1.20; W 17.50-19.00; Co 4.25-5.75; Ni+Cu 0.75
SAE J438-1970	T4		T12004	0.70-0.80	0.20-0.40	0.20-0.40			3.75-4.50		0.70-1.00	V 0.80-1.20; W 17.25-18.75; Co 4.25-5.75
JIS G 4403:2000	SKH3			0.73-0.83	0.40	0.40	0.030	0.030	3.80-4.50	0.25		V 0.80-1.20; W 17.00-19.00; Co 4.50-5.50; Cu 0.25
ASTM A 600-92a (1999)	T5		T12005	0.75-0.85	0.20-0.40	0.20-0.40	0.03	0.03	3.75-5.00		0.50-1.25	V 1.80-2.40; W 17.50-19.00; Co 7.00-9.50; Ni+Cu 0.75
SAE J438-1970	T5		T12005	0.75-0.85	0.20-0.40	0.20-0.40			3.75-4.50		0.70-1.00	V 1.80-2.40; W 17.50-19.00; Co 7.00-9.00
JIS G 4403:2000	SKH4			0.73-0.83	0.40	0.40	0.030	0.030	3.80-4.50	0.25		V 1.00-1.50; W 17.00-19.00; Co 9.00-11.00; Cu 0.25
ASTM A 600-92a (1999)	T15		T12015	1.50-1.60	0.15-0.40	0.15-0.40	0.03	0.03	3.75-5.00		1.00	V 4.50-5.25; W 11.75-13.00; Co 4.75-5.25; Ni+Cu 0.75
JIS G 4403:2000	SKH10			1.45-1.60	0.40	0.40	0.030	0.030	3.80-4.50	0.25		V 4.20-5.20; W 11.50-13.50; Co 4.20-5.20; Cu 0.25

9.3.2 Chemical Composition of High Speed Tool Steels

9.3.2.2 Chemical Composition of Molybdenum Type High Speed Tool Steels

Standard	Grade, Class, Type,	Steel	UNS				V	Veight, %, r	max, Unless	Otherwis	e Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 600-92a (1999)	M2		T11301	0.78-0.88	0.15-0.40	0.20-0.45	0.03	0.03	3.754.50		4.50-5.50	V 1.75-2.20; W 5.50-6.75; Ni+Cu 0.75
SAE J438-1970	M2		T11301	0.78-0.88	0.20-0.40	0.20-0.40			3.754.50		4.50-5.50	V 1.60-2.20; W 5.50-6.75
JIS G 4403:2000	SKH51			0.80-0.90	0.40	0.40	0.030	0.030	3.80-4.50	0.25	4.50-5.50	V 1.60-2.20; W 5.50-6.70; Cu 0.25
ISO 4957:1999	HS6-5-2			0.80-0.88	0.40	0.45	0.030	0.030	3.80-4.50		4.70-5.20	V 1.70-2.10; W 5.90-6.70
ASTM A 600-92a (1999)	M3 Cl 1		T11313	1.00-1.10	0.15-0.40	0.20-0.45	0.03	0.03	3.75-4.50		4.75-6.50	V 2.25-2.75; W 5.00-6.75; Ni+Cu 0.75
SAE J438-1970	M3		T11313	1.00-1.25	0.20-0.40	0.20-0.40			3.75-4.50		4.75-6.25	V 2.25-3.25; W 5.50-6.75
JIS G 4403:2000	SKH52			1.00-1.10	0.40	0.40	0.030	0.030	3.80-4.50	0.25	4.80-6.20	V 2.30-2.80; W 5.50-6.70; Cu 0.25
ISO 4957:1999	HS6-6-2			1.00-1.10	0.40	0.45	0.030	0.030	3.80-4.50		5.50-6.50	V 2.30-2.60; W 5.90-6.70
ASTM A 600-92a (1999)	M3 Cl 2		T11323	1.15-1.25	0.15-0.40	0.20-0.45	0.03	0.03	3.75-4.50		4.75-6.50	V 2.75-3.25; W 5.00-6.75; Ni+Cu 0.75
JIS G 4403:2000	SKH53			1.10-1.25	0.40	0.40	0.030	0.030	3.80-4.50	0.25	4.60-5.30	V 2.80-3.30; W 5.70-6.70; Cu 0.25
ISO 4957:1999	HS6-5-3			1.15-1.25	0.40	0.45	0.030	0.030	3.80-4.50		4.70-5.20	V 2.70-3.20; W 5.90-6.70
ASTM A 600-92a (1999)	M4		T11304	1.25-1.40	0.15-0.40	0.20-0.45	0.03	0.03	3.75-4.75		4.25-5.50	V 3.75-4.50; W 5.25-6.50; Ni+Cu 0.75
SAE J438-1970	M4		T11304	1.25-1.40	0.20-0.40	0.20-0.40			4.004.75		4.50-5.50	V 3.90-4.50; W 5.25-6.50
JIS G 4403:2000	SKH54			1.25-1.40	0.40	0.40	0.030	0.030	3.80-4.50	0.25	4.50-5.50	V 3.90-4.50; W 5.30-6.50; Cu 0.25
ISO 4957:1999	HS6-5-4			1.25-1.40	0.40	0.45	0.030	0.030	3.80-4.50		4.20-5.00	V 3.70-4.20; W 5.20-6.00
ASTM A 600-92a (1999)	M7		T11307	0.97-1.05	0.15-0.40	0.20-0.55	0.03	0.03	3.50-4.00		8.20-9.20	V 1.75-2.25; W 1.40-2.10; Ni+Cu 0.75
JIS G 4403:2000	SKH58			0.95-1.05	0.40	0.50	0.030	0.030	3.50-4.50	0.25	8.20-9.20	V1.70-2.20; W 1.50-2.10; Cu 0.25
ISO 4957:1999	HS2-9-2			0.95-1.05	0.40	0.70	0.030	0.030	3.50-4.50		8.20-9.20	V 1.70-2.20; W 1.50-210
ASTM A 600-92a (1999)	M36		T11336	0.80-0.90	0.15-0.40	0.20-0.45	0.03	0.03	3.75-4.50		4.50-5.50	V 1.75-2.25; W 5.50-6.50; Co 7.75-8.75; Ni+Cu 0.75
JIS G 4403:2000	SKH56			0.85-0.95	0.40	0.40	0.030	0.030	3.80-4.50	0.25	4.60-5.30	V 1.70-2.20; W 5.70-6.70; Co 7.00-9.00; Cu 0.25
ASTM A 600-92a (1999)	M42		T11342	1.05-1.15	0.15-0.40	0.15-0.65	0.03	0.03	3.50-4.25		9.00-10.00	V 0.95-1.35; W 1.15-1.85; Co 7.75-8.75; Ni+Cu 0.75
JIS G 4403:2000	SKH59			1.00-1.15	0.40	0.25	0.030	0.030	3.50-4.50		9.00-10.00	V 0.90-1.40; W 1.20-1.90; Cu 0.25
ISO 4957:1999	HS2-9-1-8			1.05-1.15	0.70	0.45	0.030	0.030	3.50-4.50		9.00-10.0	V 0.90-1.30; W 1.20-1.90; Co 7.50-8.50
JIS G 4403:2000	SKH55			0.85-0.95	0.40	0.40	0.030	0.030	3.80-4.50	0.25	4.60-5.30	V 1.70-2.20; W 5.70-6.70; Co 4.50-5.50; Cu 0.25
ISO 4957:1999	HS6-5-2-5			0.87-0.95	0.40	0.45	0.030	0.030	3.80-4.50		4.70-5.20	V 1.70-2.10; W 5.90-6.70; Co 4.50-5.00
JIS G 4403:2000	SKH57			1.20-1.35	0.40	0.40	0.030	0.030	3.80-4.50	0.25	3.00-4.00	V 3.00-3.70; W 9.00-11.00; Co 9.00-11.00; Cu 0.25
ISO 4957:1999	HS10-4-3-10			1.20-1.35	0.40	0.45	0.030	0.030	3.80-4.50		3.20-3.90	V 3.00-3.50; W 9.00-10.00; Co 9.50-10.50

9.3 Tool Steels

9.3.3 Chemical Composition of Cold Work Tool Steels

Standard	Grade, Class, Type,	Steel	UNS				٧	/eight, %,	max, Unless C	therwise	Specified	·	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others	
ASTM A 681-94 (1999)	A2		T30102	0.95-1.05	0.40-1.00	0.10-0.50	0.030	0.030	4.75-5.50		0.90-1.40	V 0.15-0.50; Ni+Cu 0.75	
SAE J438-1970	A2		T30102	0.95-1.05	0.45-0.75	0.20-0.40			4.75-5.50		0.90-1.40	V 0.40	
JIS G 4404:2000	SKD 12			0.95-1.05	0.60-0.90	0.40	0.030	0.030	4.50-5.50	0.50	0.80-1.20	V 0.20-0.50; Cu 0.25	
ISO 4957:1999	X100CrMoV5			0.95-1.05	0.40-0.80	0.10-0.40	0.030	0.030	4.80-5.50		0.90-1.20	V 0.15-0.35	
ASTM A 681-94 (1999)	D2		T30402	1.40-1.60	0.10-0.60	0.10-0.60	0.030	0.030	11.00-13.00		0.70-1.20	V 0.50-1.10; Ni+Cu 0.75	
SAE J438-1970	D2		T30402	1.40-1.60	0.30-0.50	0.10-0.60			11.00-13.00		0.70-1.20	V 0.80; Co 0.60	
JIS G 4404:2000	SKD 11			1.40-1.60	0.60	0.40	0.030	0.030	11.00-13.00	0.50	0.80-1.20	V 0.20-0.50; Cu 0.25	
ASTM A 681-94 (1999)	D3		T30403	2.00-2.35	0.10-0.60	0.10-0.60	0.030	0.030	11.00-13.50			V 1.00; W 1.00; Ni+Cu 0.75	
SAE J438-1970	D3		T30403	2.00-2.35	0.24-0.45	0.25-0.45			11.00-13.00		0.80	V 0.80; W 0.75	
JIS G 4404:2000	SKD 1			1.80-2.40	0.60	0.40	0.030	0.030	12.00-15.00			Cu 0.25	
SO 4957:1999	X210Cr12			1.90-2.20	0.20-0.60	0.10-0.60	0.030	0.030	11.00-13.00				

9.3 Tool Steels

9.3.4 Chemical Composition of Hot Work Tool Steels

Standard	Grade, Class, Type,	Steel	UNS				V	/eight, %, r	max, Unless	Otherwise	Specified	
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others
ASTM A 681-94 (1999)	H10		T20810	0.35-0.45	0.20-0.70	0.80-1.25	0.030	0.030	3.00-3.75		2.00-3.00	V 0.25-0.75; Ni+Cu 0.75
JIS G 4404:2000	SKD 7			0.28-0.38	0.60	0.50	0.030	0.030	2.50-3.50	0.25	2.50-3.00	V 0.40-0.70; Cu 0.25
ISO 4957:1999	32CrMoV12-28			0.28-0.35	0.15-0.45	0.10-0.40	0.030	0.020	2.70-3.20		2.50-3.00	V 0.40-0.70
ASTM A 681-94 (1999)	H11		T20811	0.33-0.43	0.20-0.60	0.80-1.25	0.030	0.030	4.75-5.50		1.10-1.60	V 0.30-0.60; Ni+Cu 0.75
SAE J438-1970	H11		T20811	0.30-0.40	0.20-0.40	0.80-1.20			4.75-5.50		1.25-1.75	V 0.30-0.50
JIS G 4404:2000	SKD 6			0.32-0.42	0.50	0.80-1.20	0.030	0.030	4.50-5.50	0.25	1.00-1.50	V 0.30-0.50; Cu 0.25
ISO 4957:1999	X37CrMoV5-1			0.33-0.41	0.25-0.50	0.80-1.20	0.030	0.020	4.80-5.50		1.10-1.50	V 0.30-0.50
ASTM A 681-94 (1999)	H12		T20812	0.30-0.40	0.20-0.60	0.80-1.25	0.030	0.030	4.75-5.50		1.25-1.75	V 0.20-0.50; W 1.00-1.70; Ni+Cu 0.75
SAE J438-1970	H12		T20812	0.30-0.40	0.20-0.40	0.80-1.20			4.75-5.50		1.25-1.75	V 0.10-0.50; W 1.00-1.70
JIS G 4404:2000	SKD 62			0.32-0.42	0.50	0.80-1.20	0.030	0.030	4.50-5.50	0.25	1.00-1.50	V 0.20-0.60; W 1.00-1.50; Cu 0.25
ISO 4957:1999	X35CrWMoV5			0.32-0.40	0.20-0.50	0.80-1.20	0.030	0.020	4.75-5.50		1.25-1.60	V 0.20-0.50; W 1.10-1.60
ASTM A 681-94 (1999)	H13		T20813	0.32-0.45	0.20-0.60	0.80-1.25	0.030	0.030	4.755.50		1.10-1.75	V 0.80-1.20; Ni+Cu 0.75
SAE J438-1970	H13		T20813	0.30-0.40	0.20-0.40	0.80-1.20			4.755.50		1.25-1.75	V 0.80-1.20
JIS G 4404:2000	SKD 61			0.32-0.42	0.50	0.80-1.20	0.030	0.030	4.50-5.50	0.25	1.00-1.50	V 0.80-1.20; Cu 0.25
ISO 4957:1999	X40CrMoV5-1			0.35-0.42	0.25-0.50	0.80-1.20	0.030	0.020	4.80-5.50		1.20-1.50	V 0.85-1.15
ASTM A 681-94 (1999)	H19		T20819	0.32-0.45	0.20-0.50	0.15-0.50	0.030	0.030	4.00-4.75		0.30-0.55	V 1.75-2.20; W 3.75-4.50; Co 4.00-4.50; Ni+Cu 0.75
JIS G 4404:2000	SKD 8			0.35-0.45	0.60	0.50	0.030	0.030	4.00-4.70	0.25	0.30-0.50	V 1.70-2.20; W 3.80-4.50; Co 3.80-4.50; Cu 0.25
ISO 4957:1999	38CrCoWV18-17-17			0.35-0.45	0.25-0.50	0.15-0.50	0.030	0.020	4.00-4.70		0.30-0.50	V 1.70-2.10; W 3.80-4.50; Co 4.00-4.50
ASTM A 681-94 (1999)	H21		T20821	0.26-0.36	0.15-0.40	0.15-0.50	0.030	0.030	3.00-3.75			V 0.30-0.60; W 8.50-10.00; Ni+Cu 0.75
SAE J438-1970	H21		T20821	0.30-0.40	0.20-0.40	0.15-0.30			3.00-3.75			V 0.30-0.50; W 8.75-10.00
JIS G 4404:2000	SKD 5			0.25-0.35	0.60	0.40	0.030	0.030	2.00-3.00	0.25		V 0.30-0.50; W 9.00-10.00; Cu 0.25
ISO 4957:1999	X30WCrV9-3			0.25-0.35	0.15-0.45	0.10-0.40	0.030	0.020	2.50-3.20			V 0.30-0.50; W 8.50-9.50
JIS G 4404:2000	SKT 4			0.50-0.60	0.60-1.00	0.35	0.030	0.030	0.70-1.00	1.30-2.00	0.20-0.50	V 0.20; Cu 0.25
ISO 4957:1999	55NiCrMoV7			0.50-0.60	0.60-0.90	0.10-0.40	0.030	0.030	0.80-1.20	1.50-1.80	0.35-0.55	V 0.05-0.15

9.3.5 Chemical Composition of Special Purpose Tool Steels

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	nax, Unless	Otherwise	Specified		
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others	
ASTM A 681-94 (1999)	L6		T61206	0.65-0.75	0.25-0.80	5-0.80 0.10-0.50 0.030 0.030 0.60-1.20 1.25-2.00 0.50							
SAE J438-1970	L6		T61206	0.65-0.75	0.55-0.85	0.20-0.40			0.65-0.85	1.25-1.75	0.25	V 0.25	
JIS G 4404:2000	SKS 51			0.75-0.85	0.50	0.35	0.030	0.030	0.20-0.50	1.30-2.00		Cu 0.25	
ASTM A 681-94 (1999)	F2		T60602	1.20-1.40	0.10-0.50	0.10-0.50	0.030	0.030	0.20-0.40			W 3.00-4.50; Ni+Cu 0.75	
JIS G 4404:2000	SKS 11			1.20-1.30	0.50	0.35	0.030	0.030	0.20-0.50	0.25		W 3.00-4.00; V 0.10-0.30; Cu 0.25	

9.4 Bearing Steels

9.4.1 Chemical Composition of Bearing Steels

Standard	Grade, Class, Type,	Steel	UNS				W	/eight, %, r	nax, Unless	Otherwise	Specified		
Designation	Symbol or Name	Number	Number	С	Mn	Si	Р	S	Cr	Ni	Мо	Others	
ASTM A 295-98	52100			0.93-1.05	0.25-0.45	0.15-0.35	0.025	0.015	1.35-1.60	0.25	0.10	Cu 0.30; Al 0.050; O 0.0015	
JIS G 4805:1999	SUJ 2			0.95-1.10	0.50	0.15-0.35	0.025	0.025	1.30-1.60	0.25	0.08	Cu 0.25	
ISO 683-17:1999	B1, 100Cr6			0.93-1.05	0.25-0.45	0.15-0.35	0.025	0.015	1.35-1.60		0.10	Cu 0.30; Al 0.050; O 0.0015	
ASTM A 485-03	1		K19667	0.90-1.05	0.90-1.20	0.45-0.75	0.025	0.015	0.90-1.20	0.25	0.10	Cu 0.30; Al 0.050; O 0.0015; Ti 0.0050	
A3 1 W A 405-03	B2, 100CrMnSi4-4			0.93-1.05	0.90-1.20	0.45-0.75	0.025	0.015	0.90-1.20		0.10	Cu 0.30; Al 0.050; O 0.0015	
JIS G 4805:1999	SUJ 3			0.95-1.10	0.90-1.15	0.40-0.70	0.025	0.025	0.90-1.20	0.25	0.08	Cu 0.25	
ISO 683-17:1999	B2, 100CrMnSi4-4			0.93-1.05	0.90-1.20	0.45-0.75	0.025	0.015	0.90-1.20		0.10	Cu 0.30; Al 0.050; O 0.0015	
ASTM A 485-03	B3, 100CrMnSi6-4			0.93-1.05	1.00-1.20	0.45-0.75	0.025	0.015	1.40-1.65		0.10	Cu 0.30; Al 0.050; O 0.0015	
ISO 683-17:1999	B3, 100CrMnSi6-4			0.93-1.05	1.00-1.20	0.45-0.75	0.025	0.015	1.40-1.65		0.10	Cu 0.30; Al 0.050; O 0.0015	
ASTM A 485-03	B4, 100CrMnSi6-6			0.93-1.05	1.40-1.70	0.45-0.75	0.025	0.015	1.40-1.65		0.10	Cu 0.30; Al 0.050; O 0.0015	
ISO 683-17:1999	B4, 100CrMnSi6-6			0.93-1.05	1.40-1.70	0.45-0.75	0.025	0.015	1.40-1.65		0.10	Cu 0.30; Al 0.050; O 0.0015	
ASTM A 485-03	B5, 100CrMo7			0.93-1.05	0.25-0.45	0.15-0.35	0.025	0.015	1.65-1.95		0.15-0.30	Cu 0.30; Al 0.050; O 0.0015	
ISO 683-17:1999	B5, 100CrMo7			0.93-1.05	0.25-0.45	0.15-0.35	0.025	0.015	1.65-1.95		0.15-0.30	Cu 0.30; Al 0.050; O 0.0015	
ASTM A 485-03	B6, 100CrMo7-3			0.93-1.05	0.60-0.80	0.15-0.35	0.025	0.015	1.65-1.95		0.20-0.35	Cu 0.30; Al 0.050; O 0.0015	
ISO 683-17:1999	B6, 100CrMo7-3			0.93-1.05	0.60-0.80	0.15-0.35	0.025	0.015	1.65-1.95		0.20-0.35	Cu 0.30; Al 0.050; O 0.0015	
ASTM A 485-03	B7, 100CrMo7-4			0.93-1.05	0.60-0.80	0.15-0.35	0.025	0.015	1.65-1.95		0.40-0.50	Cu 0.30; Al 0.050; O 0.0015	
ISO 683-17:1999	B7, 100CrMo7-4			0.93-1.05	0.60-0.80	0.15-0.35	0.025	0.015	1.65-1.95		0.40-0.50	· · · · · ·	
ASTM A 485-03	B8, 100CrMnMoSi8-4-6			0.93-1.05	0.80-1.10	0.40-0.60	0.025	0.015	1.80-2.05		0.50-0.60	Cu 0.30; Al 0.050; O 0.0015	
ISO 683-17:1999	B8, 100CrMnMoSi8-4-6			0.93-1.05	0.80-1.10	0.40-0.60	0.025	0.015	1.80-2.05		0.50-0.60	Cu 0.30; Al 0.050; O 0.0015	

9.5 Non-Comparable Free-Machining Steels

ASTM A 29/A 29N	I-03 – General R	equirements fo	r Steel Bars, C	arbon and Allo	y, Hot-Wrough	t and Cold-Fini	shed			
Grade	1108	1116	1119	1132	1145	1211			 	
UNS Number	G11080	G11160	G11190	G11320	G11450	G12110			 	
ASTM A 576-90b	(2000) – Standar	d Specification	for Steel Bars	, Carbon, Hot-	Wrought, Speci	al Quality				
Grade	1116	1119	1132	1145	1211				 	
UNS Number	G11160	G11190	G11320	G11450	G12110				 	
ASTM A 895-89 (2	2000) – Free-Mad	hining Stainles	ss Steel Plate, S	Sheet, and Stri	р					
Grade									 	
UNS Number	S30323	S41623	S42020	S42023	S43020	S43023			 	
SAE J403-NOV01	- Chemical Cor	npositions of S	AE Carbon Ste	els						
SAE Number	1126	1132							 	
UNS Number	G11260	G11320							 	
EN 10087:1998 -	Free Cutting Ste	els - Technical	Delivery Cond	itions for Semi	i-Finished Prod	lucts, Hot-Rolle	d Bars and Ro	ds		
Steel Name	35SPb20								 	
Steel Number	1.0756								 	
EN 10277-3:1999	- Bright Steel Pr	roducts - Techi	nical Delivery C	onditions - Pa	rt 3: Free-Cuttir	ng Steels				
Steel Name	35SPb20								 	
Steel Number	1.0756								 	

9.6 Non-Comparable Spring Steels

·											
ASTM A 313/A 313N	1-03 Standard	Specification for	or Stainless Ste	el Spring V	Vire					 	
Grade	XM-28	305	321	347	XM-16					 	
UNS Number	S24100	S30500	S32100	S34700	S45500	S20430				 	
ASTM A 682/A 682N	1-02 – General	Requirements	For Steel, Strip	, High-Cark	on, Cold-Rolled						
Grade	1030	1035	1045	1080						 	
UNS Number	G10300	G10350	G10450	G1080						 	
JIS G 4313:1996 – C	old Rolled Sta	inless Steel St	rip for Springs								
Grade Designation	SUS 632	2J1-CSP								 	
EN 10089:2002 Hot	Rolled Steels f	or Quenched a	nd Tempered S	Springs – Te	echnical Delivery (Conditions					
Steel Name	56SiCr7	61SiCr7	45SiCrV6-2	60SiCrV7	46SiCrMo6	50SicrMo6	52SiCrNi5	52crMoV4		 	
Steel Number	1.7106	1.7108	1.8151	1.8153	1.8062	1.8063	1.7117	1.7701		 	
EN 10132-4:2000 – (Cold Rolled Na	rrow Steel Strip	o for Heat Trea	tment - Tec	hnical Delivery Co	nditions - Part	4: Spring Stee	Is and Other Ap	plications		
Steel Name	48Si7	56Si7	75Ni8	80CrV2	102Cr6	125Cr2	C125S			 	
Steel Number	1.5021	1.5026	1.5634	1.2235	1.2067	1.2002	1.1224			 	
EN 10151:2002 Stair	nless Steel Str	ip for Springs -	- Technical Del	ivery Cond	itions						
Steel Name	X6Cr17	X20Cr13	X11CrNiMnN	19-8-6 X	12CrMnNiN17-7-5					 	
Steel Number	1.4016	1.4021	1.4369		1.4372					 	
EN 10270-3:2001 St	eel Wire for Me	chanical Sprin	gs – Part 3: Sta	ainless Spri	ng Steel Wire						
Steel Name	X5CrNiMo17-	12-2 X70	rNiAl17-7							 	
Steel Number	1.4401		1.4568							 	
ISO 683-14:1992 – F	leat-Treatable	Steels, Alloy St	eels and Free-	Cutting Ste	els - Part 14: Hot-F	Rolled Steels fo	or Quenched ar	nd Tempered Sp	orings		
Steel Name	56 SiCr 7	61 SiCr 7	60 CrMo 3 1	52 CrMoV	4					 	
		1								-	

9.7 Non-Comparable Tool Steels

ASTM A 600-92a (1999) – Tool Ste	el High Speed										
Туре	T2	T6	T8	M1	M6	M10	M30	M33	M34	M41	M43	M44
UNS Number	T12002	T12006	T12008	T11301	T11306	T11310	T11330	T11333	T11334	T11341	T11343	T11344
Туре	M46	M47	M48	M62	M50	M52						
UNS Number	T11346	T11347			T11350	T11352						
ASTM A 681-94 (1	999) – Tool Stee	ls Alloy	1				'	'			'	'
Туре	H14	H22	H23	H24	H25	H26	H41	H42	H43	А3	A4	A5
UNS Number	T20814	T20822	T20823	T20824	T20825	T20826	T20841	T20842	T20843	T30103	T30104	T30105
Туре	A6	A7	A8	A9	A10	D4	D5	D7	01	O2	O6	07
UNS Number	T30106	T30107	T30108	T30109	T30110	T30404	T30405	T30407	T31501	T31502	T31506	T31507
Туре	S1	S2	S4	S5	S6	S7	L2	L3	F1	P2	P3	P4
UNS Number	T41901	T41902	T41904	T41905	T41906	T41907	T61202	T61203	T60601	T51602	T51603	T51604
Туре	P5	P6	P20	P21								
UNS Number	T51605	T51606	T51620	T51621								
ASTM A 686-92 (1	999) – Tool Stee	I, Carbon										
Туре	W1-C	W2-C	W5									
UNS Number	T72301	T72302	T72305									
SAE J438-1970 –	Tool and Die Ste	els										
SAE Designation	W209	W210	W310	S1	S2	S5	01	O2	O6	D5	D7	T2
UNS Number	T72302	T72302		T41901	T41902	T41905	T31501	T31502	T31506	T30405	T30407	T12002
SAE Designation	T8	M1	L7									
UNS Number	T12008	T11301										
JIS G 4401:2000 –	Carbon Tool St	eels						•				
Grade	SK140	SK90	SK80	SK70	SK60							
JIS G 4403:2000 –	High Speed Too	ol Steels										
Grade	SKH40	SKH50										
JIS G 4404:2000 –	Alloy Tool Stee	ls										
Grade	SKS 2	SKS 21	SKS 5	SKS 7	SKS 8	SKS 81	SKS 4	SKS 41	SKS 3	SKS 31	SKS 93	SKS 94
Grade	SKS 95	SKD 4	SKD 2	SKD 10	SKT 3	SKT 6						
ISO 4957:1999 – T	ool Steels											
Steel Name	50WCrV8	60WCrV8	102Cr6	21MnCr5	70MnMoCr8	90MnCrV8	95MnWCr5	X153CrMoV12	X210CrW12	35CrMo7	40CrMnl	NiMo8-6-4
Steel Name	45NiCrMo16	X40Cr14	X38CrMo16	X38CrMoV5-3	50CrMc	V13-15	HS0-4-1	HS1-4-2	HS1-8-1	HS3-3-2	HS6-5-2C	HS6-5-3C
Steel Name	HS6-5-3-8	C45U										

9.8 Non-Comparable Bearing Steels

ASTM A 295-98 -	- High-Carbon Ant	i-Friction Bea	aring Steel									
Grade	5195	1070M	5160									
UNS Number	G51950		G51600	K19526								
ASTM A 485-03 -	- High Hardenabili	ty Antifriction	n Bearing Steel				•					
Number	2	3	4									
Name	Grade 2	Grade 3	Grade 4									
UNS Number	K19195	K19965	K19990									
JIS G 4805:1999	– High Carbon Ch	romium Bear	ring Steels									
Grade	SUJ 1	SUJ 4	SUJ 5									
ISO 683-17:1999	- Heat-Treated St	eels, Alloy St	eels and Free-C	utting Steels -	Part 17: Ball an	d Roller Beari	ng Steels					
Number	B20	B21	B22	B23	B24	B25	B26	B27	B28	B29	B30	B31
Name	20Cr3	20Cr4	20MnCr4-2	17MnCr5	19MnCr5	15CrMo4	20CrMo4	20MnCrMo4-2	20NiCrMo2	20NiCrMo7	18CrNiMo7-6	18NiCrMo14-6
Number	B32	B40	B41	B42	B43	B50	B51	B52	В	53	В	60
Name	16NiCrMo16-5	C56E2	56Mn4	70Mn4	43CrMo4	X47Cr14	X65Cr14	X106CrMo17	X89CrN	ЛоV18-1	80MoC	rV42-16
Number	B6	1	В	62	В	3						
Name	13MoCrNi4	42-16-14	X82WMo	CrV6-5-4	X75WCr	V18-4-1						

Appendix

1

ASTM FERROUS METAL STANDARDS

Designation	Title
ASTM A 1-00	Standard Specification for Carbon Steel Tee Rails
ASTM A 2-02	Standard Specification for Carbon Steel Girder Rails of Plain, Grooved, and Guard Types
ASTM A 3-01	Standard Specification for Steel Joint Bars, Low, Medium, and High Carbon (Non-Heat-Treated)
ASTM A 6/A 6M-03c	Standard Specification for General Requirements for Rolled Structural Steel Bars, Plates, Shapes, and
	Sheet Piling
ASTM A 20/A 20M-02	Standard Specification for General Requirements for Steel Plates for Pressure Vessels
ASTM A 27/A 27M-03	Standard Specification for Steel Castings, Carbon, for General Application
ASTM A 29/A 29M-03	Standard Specification for Steel Bars, Carbon and Alloy, Hot-Wrought and Cold-Finished, General
ACTM A 21 00	Requirements for Standard Specification for Steel Rivets and Bars for Rivets, Pressure Vessels
ASTM A 31-00 ASTM A 34/A 34M-01	Standard Specification for Steel rivets and Bars for rivets, Pressure vessels Standard Practice for Sampling and Procurement Testing of Magnetic Materials
ASTM A 36/A 36M-03a	Standard Specification for Carbon Structural Steel
ASTM A 47/A 47M-99	Standard Specification for Ferritic Malleable Iron Castings
ASTM A 48/A 48M-03	Standard Specification for Gray Iron Castings
	Standard Specification for Heat-Treated Carbon Steel Joint Bars, Microalloyed Joint Bars, and Forged
ASTM A 49-01	Carbon Steel Compromise Joint Bars
ASTM A 53/A 53M-02	Standard Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless
ASTM A 65-01	Standard Specification for Steel Track Spikes
ASTM A 66-01	Standard Specification for Steel Screw Spikes
ASTM A 67-00	Standard Specification for Steel Tie Plates, Low-Carbon and High-Carbon Hot-Worked
ASTM A 74-03b	Standard Specification for Cast Iron Soil Pipe and Fittings
ASTM A 82-02	Standard Specification for Steel Wire, Plain, for Concrete Reinforcement
ASTM A 90/A 90M-01	Standard Test Method for Weight [Mass] of Coating on Iron and Steel Articles with Zinc or Zinc-Alloy
	Coatings
ASTM A 100.03 (2000)	Standard Specification for Ferromanganese Standard Specification for Ferrosilicon
ASTM A 100-93 (2000) ASTM A 101-93 (2000)	Standard Specification for Ferrochromium
ASTM A 101-93 (2000) ASTM A 102-93 (2000)	Standard Specification for Ferrovanadium
ASTM A 105/A 105M-03	Standard Specification for Carbon Steel Forgings for Piping Applications
ASTM A 106-02a	Standard Specification for Seamless Carbon Steel Pipe for High-Temperature Service
ASTM A 108-03	Standard Specification for Steel Bars, Carbon and Alloy, Cold-Finished
ASTM A 109/A 109M-03	Standard Specification for Steel, Strip, Carbon (0.25 Maximum Percent), Cold-Rolled
ASTM A 111-99a	Standard Specification for Zinc-Coated (Galvanized) Iron Telephone and Telegraph Line Wire
ASTM A 116-00	Standard Specification for Metallic-Coated, Steel Woven Wire Fence Fabric
ASTM A 121-99	Standard Specification for Zinc-Coated (Galvanized) Steel Barbed Wire
ASTM A 123/A 123M-02	Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products
ASTM A 125-96 (2001)	Standard Specification for Steel Springs, Helical, Heat-Treated
ASTM A 126-95 (2001) ASTM A 128/A 128M-93 (2003)	Standard Specification for Gray Iron Castings for Valves, Flanges, and Pipe Fittings Standard Specification for Steel Castings, Austenitic Manganese
ASTM A 131/A 131M-01	Standard Specification for Structural Steel for Ships
ASTM A 132-89 (2000)	Standard Specification for Ferromolybdenum
ASTM A 134-96 (2001)	Standard Specification for Pipe, Steel, Electric-Fusion (Arc)-Welded (Sizes NPS 16 and Over)
ASTM A 135-01	Standard Specification for Electric-Resistance-Welded Steel Pipe
ASTM A 139-00	Standard Specification for Electric-Fusion (Arc)-Welded Steel Pipe (NPS 4 and Over)
ASTM A 143/A 143M-03	Standard Practice for Safeguarding Against Embrittlement of Hot-Dip Galvanized Structural Steel
	Products and Procedure for Detecting Embrittlement
ASTM A 144-02	Specification for Ferrotungsten
ASTM A 148/A 148/A 02	Standard Specification for Molybdenum Oxide Products
ASTM A 148/A 148M-03 ASTM A 153/A 153M-03	Standard Specification for Steel Castings, High Strength, for Structural Purposes Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware
ASTM A 159-83 (2001)	Standard Specification for Automotive Gray Iron Castings
ASTM A 159-65 (2001) ASTM A 167-99	Standard Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
ASTM A 176-99	Standard Specification for Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip
	Standard Specification for Electric-Resistance-Welded Carbon Steel and Carbon-Manganese Steel
ASTM A 178/A 178M-02	Boiler and Superheater Tubes
ASTM	Standard Specification for Seamless Cold-Drawn Low-Carbon Steel Heat-Exchanger and Condenser
A 179/A 179M-90a (2001)	Tubes
ASTM A 181/A 181M-01	Standard Specification for Carbon Steel Forgings, for General-Purpose Piping
ASTM A 182/A 182M-02	Standard Specification for Forged or Rolled Alloy-Steel Pipe Flanges, Forged Fittings, and Valves and
	Parts for High-Temperature Service Standard Specification for Carbon Steel Track Bolts and Nuts
ASTM A 183-03 ASTM A 184/A 184M-01	Standard Specification for Carbon Steel Track Boits and Nuts Standard Specification for Fabricated Deformed Steel Bar Mats for Concrete Reinforcement
ASTM A 185-02	Standard Specification for Steel Welded Wire Reinforcement, Plain, for Concrete
7.0 1 W 7. 100 OL	1 Standard Specification for Stock Product Print Holliford Hollis, Flam, for Controls

Designation	Title
ASTM A 291-03	Standard Specification for Steel Forgings, Carbon and Alloy, for Pinions, Gears and Shafts for Reduction Gears
ASTM A 295-98	Standard Specification for High-Carbon Anti-Friction Bearing Steel
ASTM A 297/A 297M-97 (2003)	Standard Specification for Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat Resistant, for General Application
ASTM A 299/A 299M-02	Standard Specification for Pressure Vessel Plates, Carbon Steel, Manganese-Silicon
ASTM A 302/A 302M-03	Standard Specification for Pressure Vessel Plates, Alloy Steel, Manganese-Molybdenum and Manganese-Molybdenum-Nickel
ASTM A 304-02	Standard Specification for Carbon and Alloy Steel Bars Subject to End-Quench Hardenability Requirements
ASTM A 307-03	Standard Specification for Carbon Steel Bolts and Studs, 60 000 PSI Tensile Strength
ASTM A 308/A 308M-03	Standard Specification for Steel Sheet, Terne (Lead-Tin Alloy) Coated by the Hot-Dip Process
ASTM A 309-01	Standard Test Method for Weight and Composition of Coating on Terne Sheet by the Triple-Spot Test
ASTM A 311/A 311M-95 (2000)	Standard Specification for Cold-Drawn, Stress-Relieved Carbon Steel Bars Subject to Mechanical Property Requirements
ASTM A 312/A 312M-03	Standard Specification for Seamless and Welded Austenitic Stainless Steel Pipes
ASTM A 313/A 313M-03	Standard Specification for Stainless Steel Spring Wire
ASTM A 314-97 (2002)	Standard Specification for Stainless Steel Billets and Bars for Forging
ASTM A 319-71 (2001)	Standard Specification for Gray Iron Castings for Elevated Temperatures for Non-Pressure Containing Parts
ASTM A 320/A 320M-03	Standard Specification for Alloy/Steel Bolting Materials for Low-Temperature Service
ASTM A 321-90 (2001)	Standard Specification for Steel Bars, Carbon, Quenched and Tempered
ASTM A 322-91 (2001)	Standard Specification for Steel Bars, Alloy, Standard Grades
ASTM A 323-93 (2000)	Standard Specification for Ferroboron
ASTM A 324-73 (2000)	Standard Specification for Ferrotitanium
ASTM A 325M-00	Standard Specification for High-Strength Bolts for Structural Steel Joints [Metric]
ASTM A 325-02	Standard Specification for Structural Bolts, Steel, Heat Treated, 120/105 ksi Minimum Tensile Strength
ASTM A 327M-91 (1997)	Standard Test Methods for Impact Testing of Cast Irons (Metric)
ASTM A 327-91 (1997)	Standard Test Methods for Impact Testing of Cast Irons
ASTM A 328/A 328M-03	Standard Specification for Steel Sheet Piling
ASTM A 331-95 (2000)	Standard Specification for Steel Bars, Alloy, Cold-Finished
ASTM A 333/A 333M-99	Standard Specification for Seamless and Welded Steel Pipe for Low-Temperature Service
ASTM A 334/A 334M-99	Standard Specification for Seamless and Welded Carbon and Alloy-Steel Tubes for Low-Temperature Service
ASTM A 335/A 335M-03	Standard Specification for Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service
ASTM A 336/A 336M-03a	Standard Specification for Alloy Steel Forgings for Pressure and High-Temperature Parts
ASTM A 338-84 (1998)	Standard Specification for Malleable Iron Flanges, Pipe Fittings, and Valve Parts for Railroad, Marine, and Other Heavy Duty Service at Temperatures Up to 650°F (345°C)
ASTM A 340-03a	Standard Terminology of Symbols and Definitions Relating to Magnetic Testing
ASTM A 341/A 341M-00	Standard Test Method for Direct Current Magnetic Properties of Materials Using D-C Permeameters and the Ballistic Test Methods
ASTM A 342/A 342M-99	Standard Test Methods for Permeability of Feebly Magnetic Materials
ASTM A 343/ A 343M-03	Standard Test Method for Alternating-Current Magnetic Properties of Materials at Power Frequencies Using Wattmeter-Ammeter-Voltmeter Method and 25-cm Epstein Test Frame
ASTM A 345-98	Standard Specification for Flat-Rolled Electrical Steels for Magnetic Applications
ASTM A 348/A 348M-00	Standard Test Method for Alternating Current Magnetic Properties of Materials Using the Wattmeter- Ammeter-Voltmeter Method, 100 to 10 000 Hz and 25-cm Epstein Frame
ASTM A 350/A 350M-02b	Standard Specification for Carbon and Low-Alloy Steel Forgings, Requiring Notch Toughness Testing for Piping Components
ASTM A 351/A 351M-03	Standard Specification for Castings, Austenitic, Austenitic-Ferritic (Duplex), for Pressure-Containing Parts
ASTM A 352/A 352M-03	Standard Specification for Steel Castings, Ferritic and Martensitic, for Pressure-Containing Parts, Suitable for Low-Temperature Service
ASTM A 353/A 353M-93 (1999)	Standard Specification for Pressure Vessel Plates, Alloy Steel, 9 Percent Nickel, Double-Normalized and Tempered
ASTM A 354-03a	Standard Specification for Quenched and Tempered Alloy Steel Bolts, Studs, and Other Externally Threaded Fasteners
ASTM A 355-89 (2000)	Standard Specification for Steel Bars, Alloys, for Nitriding
ASTM A 356/A 356M-98 (2003)	Standard Specification for Steel Castings, Carbon, Low Alloy, and Stainless Steel, Heavy-Walled for Steam Turbines
ASTM A 358/A 358M-01	Standard Specification for Electric-Fusion-Welded Austenitic Chromium-Nickel Alloy Steel Pipe for High-Temperature Service
ASTM A 363-03	Standard Specification for Zinc-Coated (Galvanized) Steel Overhead Ground Wire Strand
ASTM A 367-60 (1999)	Standard Test Methods of Chill Testing of Cast Iron

Do alamatian	Tru.
Designation	Title Standard Specification for Zing Costed Flet Steel Armoring Tone
ASTM A 459-97 (2003) ASTM A 460-94 (1999)	Standard Specification for Zinc-Coated Flat Steel Armoring Tape Standard Specification for Copper-Clad Steel Wire Strand
ASTM A 460-94 (1999) ASTM A 463/A 463M-02a	Standard Specification for Steel Sheet, Aluminum-Coated, by the Hot-Dip Process
ASTM A 466/A 466M-01	Standard Specification for Weldless Chain
ASTM A 460/A 460M-01 ASTM A 467/A 467M-01	Standard Specification for Machine and Coil Chain
ASTM A 467/A 467/M-01 ASTM A 469-94a (1999)	Standard Specification for Vacuum-Treated Steel Forgings for Generator Rotors
	Standard Specification for Vacuum-Treated Carbon and Alloy Steel Forgings For Turbine Rotors and
ASTM A 470-03	Shafts
ASTM A 471-02	Standard Specification for Vacuum-Treated Alloy Steel Forgings for Turbine Rotor Disks and Wheels
ASTM A 472-98 (2003)	Standard Test Method for Heat Stability of Steam Turbine Shafts and Rotor Forgings
ASTM A 473-01	Standard Specification for Stainless Steel Forgings
ASTM A 474-03	Standard Specification for Aluminum-Coated Steel Wire Strand
ASTM A 475-03	Standard Specification for Zinc-Coated Steel Wire Strand
ASTM A 476/A 476M-00	Standard Specification for Ductile Iron Castings for Paper Mill Dryer Rolls
ASTM A 478-97 (2002)	Standard Specification for Chromium-Nickel Stainless Steel Weaving and Knitting Wire
ASTM A 479/A 479M-03	Standard Specification for Stainless Steel Bars and Shapes for Use in Boilers and Other Pressure Vessels
ASTM A 480/A 480M-03c	Standard Specification for General Requirements for Flat-Rolled Stainless and Heat-Resisting Steel Plate, Sheet, and Strip
ASTM A 481-94 (2000)	Standard Specification for Chromium Metal
ASTM A 482-93 (2000)	Standard Specification for Ferrochrome-Silicon
ASTM A 483-64 (2000)	Standard Specification for Silicomanganese
ASTM A 484/A 484M-03a	Standard Specification for General Requirements for Stainless Steel Bars, Billets, and Forgings
ASTM A 485-03	Standard Specification for High Hardenability Antifriction Bearing Steel
ASTM A 487/A 487M-93 (2003)	Standard Specification for Steel Castings Suitable for Pressure Service
ASTM A 488/A 488M-01	Standard Practice for Steel Castings, Welding, Qualifications of Procedures and Personnel
ASTM A 489-03	Standard Specification for Carbon Steel Lifting Eyes
ASTM A 490M-03	Standard Specification for High-Strength Steel Bolts, Classes 10.9 and 10.9.3, for Structural Steel Joints [Metric]
ASTM A 490-02	Standard Specification for Structural Bolts, Alloy Steel, Heat Treated, 150 ksi Minimum Tensile Strength
ASTM A 491-03	Standard Specification for Aluminum-Coated Steel Chain-Link Fence Fabric
ASTM A 492-95 (2000)	Standard Specification for Stainless Steel Rope Wire
ASTM A 493-95 (2000)	Standard Specification for Stainless Steel Wire and Wire Rods for Cold Heading and Cold Forging
ASTM A 494/A 494M-03a	Standard Specification for Castings, Nickel and Nickel Alloy
ASTM A 495-94 (2000)	Standard Specification for Calcium-Silicon Alloys
ASTM A 496-02	Standard Specification for Steel Wire, Deformed, for Concrete Reinforcement
ASTM A 497/A 497M-02	Standard Specification for Steel Welded Wire Fabric, Deformed, for Concrete
ASTM A 498-98	Standard Specification for Seamless and Welded Carbon, Ferritic, and Austenitic Alloy Steel Heat- Exchanger Tubes with Integral Fins
ASTM A 499-89 (2002)	Standard Specification for Steel Bars and Shapes, Carbon Rolled from "T" Rails
ASTM A 500-03a	Standard Specification for Cold-Formed Welded and Seamless Carbon Steel Structural Tubing in Rounds and Shapes
ASTM A 501-01	Standard Specification for Hot-Formed Welded and Seamless Carbon Steel Structural Tubing
ASTM A 502-03	Standard Specification for Rivets, Steel, Structural
ASTM A 503/A 503M-01(2001)	Standard Specification for Ultrasonic Examination of Large Forged Crankshafts
ASTM A 504-93 (1999)	Standard Specification for Wrought Carbon Steel Wheels
ASTM A 505-00	Standard Specification for Steel, Sheet and Strip, Alloy, Hot-Rolled and Cold-Rolled, General Requirements for
ASTM A 506-00	Standard Specification for Alloy and Structural Alloy Steel, Sheet and Strip, Hot-Rolled and Cold-Rolled
ASTM A 507-00	Standard Specification for Drawing Alloy Steel, Sheet and Strip, Hot-Rolled and Cold-Rolled
ASTM A 508/A 508M-03	Standard Specification for Quenched and Tempered Vacuum-Treated Carbon and Alloy Steel Forgings for Pressure Vessels
ASTM A 510M-03	Standard Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel [Metric]
ASTM A 510-03	Standard Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel
ASTM A 511-96	Standard Specification for Seamless Stainless Steel Mechanical Tubing
ASTM A 512-96 (2001)	Standard Specification for Cold-Drawn Buttweld Carbon Steel Mechanical Tubing
ASTM A 513-00	Standard Specification for Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing
ASTM A 514/A 514M-00a	Standard Specification for High-Yield-Strength, Quenched and Tempered Alloy Steel Plate, Suitable for Welding
ASTM A 515/A 515M-03	Standard Specification for Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher- Temperature Service
ASTM A 516/A 516M-03	Standard Specification for Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-
1	Temperature Service

Designation	Title
ASTM A 517/A 517M-93 (1999)	Standard Specification for Pressure Vessel Plates, Alloy Steel, High-Strength, Quenched and Tempered
ASTM A 518/A 518M-99 (2003)	Standard Specification for Corrosion-Resistant High-Silicon Iron Castings
ASTM A 519-03	Standard Specification for Seamless Carbon and Alloy Steel Mechanical Tubing
ASTM A 521-03	Standard Specification for Steel, Closed-Impression Die Forgings for General Industrial Use
ASTM A 522/A 522M-01	Standard Specification for Forged or Rolled 8 and 9% Nickel Alloy Steel Flanges, Fittings, Valves, and Parts for Low-Temperature Service
ASTM A 523-96 (2001)	Standard Specification for Plain End Seamless and Electric-Resistance-Welded Steel Pipe for High- Pressure Pipe-Type Cable Circuits
ASTM A 524-96 (2001)	Standard Specification for Seamless Carbon Steel Pipe for Atmospheric and Lower Temperatures
ASTM A 529/A 529M-03	Standard Specification for High-Strength Carbon-Manganese Steel of Structural Quality
ASTM A 530/A 530M-03	Standard Specification for General Requirements for Specialized Carbon and Alloy Steel Pipe
ASTM A 531/A 531M-91 (2001)	Standard Practice for Ultrasonic Examination of Turbine-Generator Steel Retaining Rings
ASTM A 532/A 532M-93a (2003)	Standard Specification for Abrasion-Resistant Cast Irons
ASTM A 533/A 533M-93 (1999)	Standard Specification for Pressure Vessel Plates, Alloy Steel, Quenched and Tempered, Manganese-Molybdenum and Manganese-Molybdenum-Nickel
ASTM A 534-01	Standard Specification for Carburizing Steels for Anti-Friction Bearings
ASTM A 536-84 (1999)	Standard Specification for Ductile Iron Castings
ASTM A 537/A 537M-95 (2000)	Standard Specification for Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel
ASTM A 540/A 540M-00	Standard Specification for Alloy-Steel Bolting Materials for Special Applications
ASTM A 541/A 541M-95 (1999)	Standard Specification for Quenched and Tempered Carbon and Alloy Steel Forgings for Pressure Vessel Components
ASTM A 542/A 542M-99	Standard Specification for Pressure Vessel Plates, Alloy Steel, Quenched-and-Tempered, Chromium-Molybdenum, and Chromium-Molybdenum-Vanadium
ASTM A 543/A 543M-93 (1999)	Standard Specification for Pressure Vessel Plates, Alloy Steel, Quenched and Tempered Nickel-Chromium-Molybdenum
ASTM A 550-78 (2000)	Standard Specification for Ferrocolumbium
ASTM A 551-94 (1999)	Standard Specification for Steel Tires
ASTM A 553/A 553M-95 (2000)	Standard Specification for Pressure Vessel Plates, Alloy Steel, Quenched and Tempered 8 and 9 Percent Nickel
ASTM A 554-03	Standard Specification for Welded Stainless Steel Mechanical Tubing
ASTM A 555/A 555M-97 (2002)	Standard Specification for General Requirements for Stainless Steel Wire and Wire Rods
ASTM A 556/A 556M-96 (2001)	Standard Specification for Seamless Cold-Drawn Carbon Steel Feedwater Heater Tubes
ASTM A 560/A 560M-93 (1998)	Standard Specification for Castings, Chromium-Nickel Alloy
ASTM A 561-71 (1999)	Standard Recommended Practice for Macrotech Testing of Tool Steel Bars
ASTM A 562/A 562M-90 (2001)	Standard Specification for Pressure Vessel Plates, Carbon Steel, Manganese-Titanium for Glass or Diffused Metallic Coatings
ASTM A 563M-03	Standard Specification for Carbon and Alloy Steel Nuts [Metric]
ASTM A 563-00	Standard Specification for Carbon and Alloy Steel Nuts
ASTM A 564/A 564M-02a	Standard Specification for Hot-Rolled and Cold-Finished Age-Hardening Stainless Steel Bars and Shapes
ASTM A 565-03b	Standard Specification for Martensitic Stainless Steel Bars, Forgings, and Forging Stock for High- Temperature Service
ASTM A 568/A 568M-03	Standard Specification for Steel, Sheet, Carbon, and High-Strength, Low-Alloy, Hot-Rolled and Cold-Rolled, General Requirements for
ASTM A 571/A 571M-01	Standard Specification for Austenitic Ductile Iron Castings for Pressure-Containing Parts Suitable for Low-Temperature Service
ASTM A 572/A 572M-03a	Standard Specification for High-Strength Low-Alloy Columbium-Vanadium Structural Steel
ASTM A 573/A 573M-00a	Standard Specification for Structural Carbon Steel Plates of Improved Toughness
ASTM A 574M-00	Standard Specification for Alloy Steel Socket-Head Cap Screws [Metric]
ASTM A 574-00	Standard Specification for Alloy Steel Socket-Head Cap Screws
ASTM A 575-96 (2002)	Standard Specification for Steel Bars, Carbon, Merchant Quality, M-Grades
ASTM A 576-90b (2000)	Standard Specification for Steel Bars, Carbon, Hot-Wrought, Special Quality
	Standard Specification for Ultrasonic Angle-Beam Examination of Steel Plates
ASTM A 577/A 577M-90 (2001)	Ctandard Openingation of Chaconic / High Doam Examination of Ctool / Iato
ASTM A 577/A 577M-90 (2001) ASTM A 578/A 578M-96 (2001)	Standard Specification for Straight-Beam Ultrasonic Examination of Plain and Clad Steel Plates for Special Applications
	Standard Specification for Straight-Beam Ultrasonic Examination of Plain and Clad Steel Plates for
ASTM A 578/A 578M-96 (2001)	Standard Specification for Straight-Beam Ultrasonic Examination of Plain and Clad Steel Plates for Special Applications
ASTM A 578/A 578M-96 (2001) ASTM A 579-01	Standard Specification for Straight-Beam Ultrasonic Examination of Plain and Clad Steel Plates for Special Applications Standard Specification for Superstrength Alloy Steel Forgings
ASTM A 578/A 578M-96 (2001) ASTM A 579-01 ASTM A 580/A 580M-98	Standard Specification for Straight-Beam Ultrasonic Examination of Plain and Clad Steel Plates for Special Applications Standard Specification for Superstrength Alloy Steel Forgings Standard Specification for Stainless Steel Wire Standard Specification for Free-Machining Stainless Steel Wire and Wire Rods Standard Specification for Free-Machining Stainless Steel Bars
ASTM A 578/A 578M-96 (2001) ASTM A 579-01 ASTM A 580/A 580M-98 ASTM A 581/A 581M-95b (2000)	Standard Specification for Straight-Beam Ultrasonic Examination of Plain and Clad Steel Plates for Special Applications Standard Specification for Superstrength Alloy Steel Forgings Standard Specification for Stainless Steel Wire Standard Specification for Free-Machining Stainless Steel Wire and Wire Rods

Designation	Title
ASTM A 588/A 588M-03	Standard Specification for High-Strength Low-Alloy Structural Steel with 50 ksi [345 MPa] Minimum Yield Point to 4-in. [100 mm] Thick
ASTM A 589-96 (2001)	Standard Specification for Seamless and Welded Carbon Steel Water-Well Pipe
ASTM A 591/A 591M-98	Standard Specification for Steel Sheet, Electrolytic Zinc-Coated, for Light Coating Weight [Mass] Applications
ASTM A 592/A 592M-89 (1999)	Standard Specification for High-Strength Quenched and Tempered Low-Alloy Steel Forged Fittings and Parts for Pressure Vessels
ASTM A 595-98 (2002)	Standard Specification for Steel Tubes, Low-Carbon, Tapered for Structural Use
ASTM A 596/A 596M-95 (1999)	Standard Test Method for Direct-Current Magnetic Properties of Materials Using the Ballistic Method and Ring Specimens
ASTM A 597-87 (1999)	Standard Specification for Cast Tool Steel
ASTM A 598/A 598M-02	Standard Test Method for Magnetic Properties Of Magnetic Amplifier Cores
ASTM A 599/A 599M-02	Standard Specification for Tin Mill Products, Electrolytic Tin-Coated, Cold-Rolled Sheet
ASTM A 600-92a (1999)	Standard Specification for Tool Steel High Speed
ASTM A 601-96 (2000)	Standard Specification for Electrolytic Manganese Metal
ASTM A 602-94 (1998)	Standard Specification for Automotive Malleable Iron Castings
ASTM A 603-98 (2003)	Standard Specification for Zinc-Coated Steel Structural Wire Rope
ASTM A 604-93 (2003)	Standard Test Method for Macroetch Testing of Consumable Electrode Remelted Steel Bars and Billets
ASTM A 606-01	Standard Specification for Steel, Sheet and Strip, High-Strength, Low-Alloy, Hot-Rolled and Cold-Rolled, with Improved Atmospheric Corrosion Resistance
ASTM A 608/A 608M-02	Standard Specification for Centrifugally Cast Iron-Chromium-Nickel High-Alloy Tubing for Pressure Application at High Temperatures
ASTM A 609/A 609M-91 (2002)	Standard Practice for Castings, Carbon, Low-Alloy, and Martensitic Stainless Steel, Ultrasonic Examination Thereof
ASTM A 610-79 (2000)	Standard Test Methods for Sampling and Testing Ferroalloys for Determination of Size
ASTM A 612/A 612M-03	Standard Specification for Pressure Vessel Plates, Carbon Steel, High Strength, for Moderate and Lower Temperature Service
ASTM A 615/A 615M-04	Standard Specification for Deformed and Plain Billet-Steel Bars for Concrete Reinforcement
ASTM A 618-01	Standard Specification for Hot-Formed Welded and Seamless High-Strength Low-Alloy Structural Tubing
ASTM A 623M-03	Standard Specification for Tin Mill Products, General Requirements [Metric]
ASTM A 623-03	Standard Specification for Tin Mill Products, General Requirements
ASTM A 624/A 624M-03	Standard Specification for Tin Mill Products, Electrolytic Tin Plate, Single Reduced
ASTM A 625/A 625M-03	Standard Specification for Tin Mill Products, Black Plate, Single Reduced
ASTM A 626/A 626M-03	Standard Specification for Tin Mill Products, Electrolytic Tin Plate, Double Reduced
ASTM A 627-03	Standard Test Methods for Tool-Resisting Steel Bars, Flats, and Shapes for Detention and Correctional Facilities
ASTM A 629-88 (1994) ASTM A 630-03	Standard Specification for Tool-Resisting Steel Flat Bars and Shapes for Security Applications Standard Test Methods for Determination of Tin Coating Weights for Electrolytic Tin Plate
ASTM A 632-02a	Standard Specification for Seamless and Welded Austenitic Stainless Steel Tubing (Small-Diameter) for General Service
ASTM A 633/A 633M-01	Standard Specification for Normalized High-Strength Low-Alloy Structural Steel Plates
	Standard Specification for Steel, Sheet and Strip, Heavy-Thickness Coils, Carbon, Commercial Steel,
ASTM A 635/A 635M-02	Drawing Steel, Structural, High-Strength Low-Alloy, and High-Strength Low-Alloy with Improved Formability, Hot-Rolled, General Requirements for
ASTM A 636-76 (2000)	Standard Specification for Nickel Oxide Sinter
ASTM A 638/A 638M-00	Standard Specification for Precipitation Hardening Iron Base Superalloy Bars, Forgings, and Forging Stock for High-Temperature Service
ASTM A 640-97 (2002)	Standard Specification for Zinc-Coated Steel Strand for Messenger Support of Figure 8 Cable
ASTM A 641/A 641M-03	Standard Specification for Zinc-Coated (Galvanized) Carbon Steel Wire
ASTM A 644-98 (2003)	Standard Terminology Relating to Iron Castings
ASTM A 645/A 645M-99a	Standard Specification for Pressure Vessel Plates, Five Percent Nickel Alloy Steel, Specially Heat Treated
ASTM A 646-95 (1999)	Standard Specification for Premium Quality Alloy Steel Blooms and Billets for Aircraft and Aerospace Forgings
ASTM A 648-95 (2000)	Standard Specification for Steel Wire, Hard Drawn for Prestressing Concrete Pipe
ASTM A 649/A 649M-99 (2003)	Standard Specification for Forged Steel Rolls Used for Corrugating Paper Machinery
ASTM A 650/A 650M-03	Standard Specification for Tin Mill Products, Black Plate, Double Reduced
ASTM A 653/A 653M-03	Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
ASTM A 656/A 656M-03	Standard Specification for Hot-Rolled Structural Steel, High-Strength Low-Alloy Plate with Improved Formability
ASTM A 657/A 657M-03	Standard Specification for Tin Mill Products, Black Plate Electrolytic Chromium-Coated, Single and Double Reduced
ASTM A 659/A 659M-97 (2001)	Standard Specification for Commercial Steel (CS), Sheet and Strip, Carbon (0.16 Maximum to 0.25 Maximum Percent), Hot-Rolled

Tempered, for Welded Layered Pressure Vessels

ASTM A 724/A 724M-99

Designation	Title
ASTM A 726-00	Standard Specification for Cold-Rolled Magnetic Lamination Quality Steel, Semiprocessed Types
ASTM A 727/A 727M-02	Standard Specification for Carbon Steel Forgings for Piping Components with Inherent Notch Toughness
ASTM A 729-93 (1999)	Standard Specification for Alloy Steel Axles, Heat-Treated, for Mass Transit and Electric Railway Service
ASTM A 730-93 (1999)	Standard Specification for Forgings, Carbon and Alloy Steel, for Railway Use
ASTM A 732/A 732M-02	Standard Specification for Castings, Investment, Carbon and Low Alloy Steel for General Application, and Cobalt Alloy for High Strength at Elevated Temperatures
ASTM A 733-03	Standard Specification for Welded and Seamless Carbon Steel and Austenitic Stainless Steel Pipe Nipples
ASTM A 734/A 734M-87a (2003)	Standard Specification for Pressure Vessel Plates, Alloy Steel and High-Strength Low-Alloy Steel, Quenched-and-Tempered
ASTM A 735/A 735M-03	Standard Specification for Pressure Vessel Plates, Low-Carbon Manganese-Molybdenum-Columbium Alloy Steel, for Moderate and Lower Temperature Service
ASTM A 736/A 736M-03	Standard Specification for Pressure Vessel Plates, Low-Carbon Age-Hardening Nickel-Copper-Chromium-Molybdenum-Columbium and Nickel-Copper-Manganese-Molybdenum-Columbium Alloy Steel
ASTM A 737/A 737M-99	Standard Specification for Pressure Vessel Plates, High-Strength, Low-Alloy Steel
ASTM A 738/A 738M-03a	Standard Specification for Pressure Vessel Plates, Heat-Treated, Carbon-Manganese-Silicon Steel, for Moderate and Lower Temperature Service
ASTM A 739-90a (2000)	Standard Specification for Steel Bars, Alloy, Hot-Wrought, for Elevated Temperature or Pressure- Containing Parts, or Both
ASTM A 740-98 (2003)	Standard Specification for Hardware Cloth (Woven or Welded Galvanized Steel Wire Fabric)
ASTM A 741-98 (2003)	Standard Specification for Zinc-Coated Steel Wire Rope and Fittings for Highway Guardrail
ASTM A 742/A 742M-03	Standard Specification for Steel Sheet, Metallic Coated and Polymer Precoated for Corrugated Steel Pipe
ASTM A 743/A 743M-03	Standard Specification for Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion Resistant, for General Application
ASTM A 744/A 744M-00	Standard Specification for Castings, Iron-Chromium-Nickel, Corrosion Resistant, for Severe Service
ASTM A 745/A 745M-94 (2003)	Standard Practice for Ultrasonic Examination of Austenitic Steel Forgings
ASTM A 746-03	Standard Specification for Ductile Iron Gravity Sewer Pipe
ASTM A 747/A 747M-99	Standard Specification for Steel Castings, Stainless, Precipitation Hardening
ASTM A 748/A 748M-87 (2003)	Standard Specification for Statically Cast Chilled White Iron-Gray Iron Dual Metal Rolls for Pressure Vessel Use
ASTM A 749/A 749M-97 (2002)	Standard Specification for Steel, Strip, Carbon and High-Strength, Low-Alloy, Hot-Rolled, General Requirements for
ASTM A 750-77 (1994)	Standard Specification for Steel Air Ventilating Grille Units for Detention Areas
ASTM A 751-01	Standard Test Methods, Practices, and Terminology for Chemical Analysis of Steel Products
ASTM A 752M-93 (2003)	Standard Specification for General Requirements for Wire Rods and Coarse Round Wire, Alloy Steel [Metric]
ASTM A 752-93 (2003)	Standard Specification for General Requirements for Wire Rods and Coarse Round Wire, Alloy Steel
ASTM A 753-02	Standard Specification for Wrought Nickel-Iron Soft Magnetic Alloys (UNS K94490, K94840, N14076, N14080)
ASTM A 754/A 754M-96 (2000)	Standard Test Method for Coating Weight (Mass) of Metallic Coatings on Steel by X-Ray Fluorescence
ASTM A 755/A 755M-03	Standard Specification for Steel Sheet, Metallic Coated by the Hot-Dip Process and Prepainted by the Coil-Coating Process for Exterior Exposed Building Products
ASTM A 756-94 (2001)	Standard Specification for Stainless Anti-Friction Bearing Steel
ASTM A 757/A 757M-00	Standard Specification for Steel Castings, Ferritic and Martensitic, for Pressure-Containing and Other Applications, for Low-Temperature Service
ASTM A 758/A 758M-00	Standard Specification for Wrought-Carbon Steel Butt-Welding Piping Fittings with Improved Notch Toughness
ASTM A 759-00	Standard Specification for Carbon Steel Crane Rails
ASTM A 760/A 760M-01a	Standard Specification for Corrugated Steel Pipe, Metallic-Coated for Sewers and Drains
ASTM A 761/A 761M-03	Standard Specification for Corrugated Steel Structural Plate, Zinc-Coated, for Field-Bolted Pipe, Pipe-Arches, and Arches
ASTM A 762/A 762M-00	Standard Specification for Corrugated Steel Pipe, Polymer Precoated for Sewers and Drains
ASTM A 763-93 (1999)e1	Standard Practices for Detecting Susceptibility to Intergranular Attack in Ferritic Stainless Steels
ASTM A 764-95 (2001)	Standard Specification for Metallic Coated Carbon Steel Wire, Coated at Size and Drawn to Size for Mechanical Springs
ASTM A 765/A 765M-01	Standard Specification for Carbon Steel and Low-Alloy Steel Pressure-Vessel-Component Forgings with Mandatory Toughness Requirements
ASTM A 767/A 767M-00b	Standard Specification for Zinc-Coated (Galvanized) Steel Bars for Concrete Reinforcement
ASTM A 768-95 (2001)	Standard Specification for Vacuum-Treated 12% Chromium Alloy Steel Forgings for Turbine Rotors and Shafts

Designation	Title
ASTM A 769/A 769M-00	Standard Specification for Carbon and High-Strength Electric Resistance Welded Steel Structural Shapes
ASTM A 770/A 770M-03	Standard Specification for Through-Thickness Tension Testing of Steel Plates for Special Applications
ASTM A 771/A 771M-95 (2001)	Standard Specification for Seamless Austenitic and Martensitic Stainless Steel Tubing for Liquid Metal-
ASTM A 772/A 772M-00	Cooled Reactor Core Components Standard Test Method for ac Magnetic Permeability of Materials Using Sinusoidal Current
ASTM A 773/A 773M-01	Standard Test Method for dc Magnetic Permeability of Materials Using Ring and Permeameter Procedures with dc Electronic Hysteresigraphs
ASTM A 774/A 774M-02	Standard Specification for As-Welded Wrought Austenitic Stainless Steel Fittings for General Corrosive Service at Low and Moderate Temperatures
ASTM A 775/A 775M-01	Standard Specification for Epoxy-Coated Reinforcing Steel Bars
ASTM A 778-01	Standard Specification for Welded, Unannealed Austenitic Stainless Steel Tubular Products
ASTM A 779/A 779M-00	Standard Specification for Steel Strand, Seven-Wire, Uncoated, Compacted, Stress-Relieved for Prestressed Concrete
ASTM A 780-01	Standard Practice for Repair of Damaged and Uncoated Areas of Hot-Dip Galvanized Coatings
	Standard Specification for Castings, Steel and Alloy, Common Requirements, for General Industrial
ASTM A 781/A 781M-03a	Use
ASTM A 782/A 782M-90 (2001)	Standard Specification for Pressure-Vessel Plates, Quenched-and-Tempered, Manganese-Chromium-Molybdenum-Silicon Zirconium Alloy Steel
ASTM A 786/A 786M-00b	Standard Specification for Hot-Rolled Carbon, Low-Alloy, High-Strength Low-Alloy, and Alloy Steel Floor Plates
ASTM A 787-01	Standard Specification for Electric-Resistance-Welded Metallic-Coated Carbon Steel Mechanical Tubing
ASTM A 788-03a	Standard Specification for Steel Forgings, General Requirements
ASTM A 789/A 789M-02a	Standard Specification for Seamless and Welded Ferritic/Austenitic Stainless Steel Tubing for General Service
ASTM A 790/A 790M-03	Standard Specification for Seamless and Welded Ferritic/Austenitic Stainless Steel Pipe
ASTM A 792/A 792M-03	Standard Specification for Steel Sheet, 55% Aluminum-Zinc Alloy-Coated by the Hot-Dip Process
ASTM A 793-96 (2001)	Standard Specification for Rolled Floor Plate, Stainless Steel
ASTM A 794-97 (2002)	Standard Specification for Commercial Steel (CS), Sheet, Carbon (0.16% Maximum to 0.25% Maximum), Cold-Rolled
ASTM A 795-00	Standard Specification for Black and Hot-Dipped Zinc-Coated (Galvanized) Welded and Seamless Steel Pipe for Fire Protection Use
ASTM A 796/A 796M-03	Standard Practice for Structural Design of Corrugated Steel Pipe, Pipe-Arches, and Arches for Storm and Sanitary Sewers and Other Buried Applications
ASTM A 798/A 798M-01	Standard Practice for Installing Factory-Made Corrugated Steel Pipe for Sewers and Other Applications
ASTM A 799/A 799M-92 (2002)	Standard Practice for Steel Castings, Stainless, Instrument Calibration, for Estimating Ferrite Content
ASTM A 800/A 800M-01	Standard Practice for Steel Casting, Austenitic Alloy, Estimating Ferrite Content Thereof
ASTM A 801/A 801M-99	Standard Specification for Wrought Iron-Cobalt High Magnetic Saturation Alloys UNS R30005 and K92650
ASTM A 802/A 802M-95 (2001)	Standard Practice for Steel Castings, Surface Acceptance Standards, Visual Examination
ASTM A 803/A 803M-03	Standard Specification for Welded Ferritic Stainless Steel Feedwater Heater Tubes
ASTM A 804/A 804M-99	Standard Test Methods for Alternating-Current Magnetic Properties of Materials at Power Frequencies Using Sheet-Type Test Specimens
ASTM A 805-93 (2002)	Standard Specification for Steel, Flat Wire, Carbon, Cold-Rolled
ASTM A 807/A 807M-02e1	Standard Practice for Installing Corrugated Steel Structural Plate Pipe for Sewers and Other Applications
ASTM A 808/A 808M-00a	Standard Specification for High-Strength, Low-Alloy Carbon, Manganese, Columbium, Vanadium Steel of Structural Quality with Improved Notch Toughness
ASTM A 809-03	Standard Specification for Aluminum-Coated (Aluminized) Carbon Steel Wire
ASTM A 810-01	Standard Specification for Zinc-Coated (Galvanized) Steel Pipe Winding Mesh
ASTM A 811-03	Standard Specification for Soft Magnetic Iron Parts Fabricated by Powder Metallurgy (P/M) Techniques
ASTM A 813/A 813M-01	Standard Specification for Single- or Double-Welded Austenitic Stainless Steel Pipe
ASTM A 814/A 814M-03	Standard Specification for Cold-Worked Welded Austenitic Stainless Steel Pipe
ASTM A 815/A 815M-01a	Standard Specification for Wrought Ferritic, Ferritic/Austenitic, and Martensitic Stainless Steel Piping Fittings
ASTM A 817-03	Standard Specification for Metallic-Coated Steel Wire for Chain-Link Fence Fabric and Marcelled Tension Wire
ASTM A 818-91 (2001)	Standard Specification for Coppered Carbon Steel Wire
ASTM A 820-01	Standard Specification for Steel Fibers for Fiber-Reinforced Concrete
ASTM A 821/A 821M-99	Standard Specification for Steel Wire, Hard Drawn for Prestressing Concrete Tanks
ASTM A 822-90 (2000)	Standard Specification for Seamless Cold-Drawn Carbon Steel Tubing for Hydraulic System Service
ASTM A 823-99 (2003)	Standard Specification for Statically Cast Permanent Mold Gray Iron Castings
ASTM A 824-01	Standard Specification for Metallic-Coated Steel Marcelled Tension Wire for Use With Chain Link Fence

Designation	Title
ASTM A 827/A 827M-02	Standard Specification for Plates, Carbon Steel, for Forging and Similar Applications
ASTM A 829/A 829M-00	Standard Specification for Alloy Structural Steel Plates
ASTM A 830/A 830M-02	Standard Specification for Plates, Carbon Steel, Structural Quality, Furnished to Chemical Composition Requirements
ASTM A 831/A 831M-95 (2000)	Standard Specification for Austenitic and Martensitic Stainless Steel Bars, Billets, and Forgings for Liquid Metal Cooled Reactor Core Components
ASTM A 832/A 832M-99e1	Standard Specification for Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Vanadium
ASTM A 833-84 (2001)	Standard Practice for Indentation Hardness of Metallic Materials by Comparison Hardness Testers
ASTM A 834-95 (2001)	Standard Specification for Common Requirements for Iron Castings for General Industrial Use
ASTM A 835-84 (2000)	Standard Specification for Sizes of Ferroalloys and Alloy Additives
ASTM A 836/A 836M-02	Standard Specification for Titanium-Stabilized Carbon Steel Forgings for Glass-Lined Piping and Pressure Vessel Service
ASTM A 837/A 837M-03	Standard Specification for Steel Forgings, Alloy, for Carburizing Applications
ASTM A 838-02	Standard Specification for Free-Machining Ferritic Stainless Soft Magnetic Alloys for Relay Applications
ASTM A 839-02	Standard Specification for Iron-Phosphorus Powder Metallurgy (P/M) Parts for Soft Magnetic Applications
ASTM A 840/A 840M-00	Standard Specification for Fully Processed Magnetic Lamination Steel
ASTM A 841/A 841M-03a	Standard Specification for Steel Plates for Pressure Vessels, Produced by Thermo-Mechanical Control Process (TMCP)
ASTM A 842-85 (1997)	Standard Specification for Compacted Graphite Iron Castings
ASTM A 844/A 844M-93 (1999)	Standard Specification for Steel Plates, 9% Nickel Alloy, for Pressure Vessels, Produced by the Direct-Quenching Process
ASTM A 845-85 (2000)	Standard Specification for Titanium Scrap for Use in Deoxidation and Alloying of Steel
ASTM A 846-85 (2000)	Standard Specification for Aluminum Scrap for Use in Deoxidation and Alloying of Steel
ASTM A 847-99a (2003)	Standard Specification for Cold-Formed Welded and Seamless High Strength, Low Alloy Structural Tubing with Improved Atmospheric Corrosion Resistance
ASTM A 848-01	Standard Specification for Low-Carbon Magnetic Iron
ASTM A 849-00	Standard Specification for Post-Applied Coatings, Pavings, and Linings for Corrugated Steel Sewer and Drainage Pipe
ASTM A 852/A 852M-03	Standard Specification for Quenched and Tempered Low-Alloy Structural Steel Plate with 70 ksi [485 MPa] Minimum Yield Strength to 4 in. [100 mm] Thick
ASTM A 853-93 (2003)	Standard Specification for Steel Wire, Carbon, for General Use
ASTM A 854/A 854M-98 (2003)	Standard Specification for Metallic-Coated Steel Smooth High-Tensile Fence and Trellis Wire
ASTM A 855/A 855M-03	Standard Specification for Zinc-5% Aluminum-Mischmetal Alloy-Coated Steel Wire Strand
ASTM A 856/A 856M-03	Standard Specification for Zinc-5% Aluminum-Mischmetal Alloy-Coated Carbon Steel Wire
ASTM A 857/A 857M-00a	Standard Specification for Steel Sheet Piling, Cold Formed, Light Gage
ASTM A 858/A 858M-00	Standard Specification for Heat-Treated Carbon Steel Fittings for Low-Temperature and Corrosive Service
ASTM A 859/A 859M-02	Standard Specification for Age-Hardening Alloy Steel Forgings for Pressure Vessel Components
ASTM A 860/A 860M-00	Standard Specification for Wrought High-Strength Low-Alloy Steel Butt-Welding Fittings
ASTM A 861-02	Standard Specification for High-Silicon Iron Pipe and Fittings
ASTM A 862/A 862M-98	Standard Practice for Application of Asphalt Coatings to Corrugated Steel Sewer and Drainage Pipe
ASTM A 865-03	Standard Specification for Threaded Couplings, Steel, Black or Zinc-Coated (Galvanized) Welded or Seamless, for Use in Steel Pipe Joints
ASTM A 866-01	Standard Specification for Medium Carbon Anti-Friction Bearing Steel
ASTM A 867-03	Standard Specification for Iron-Silicon Relay Steels
ASTM A 871/A 871M-03	Standard Specification for High-Strength Low-Alloy Structural Steel Plate With Atmospheric Corrosion Resistance
ASTM A 872/A 872M-02	Standard Specification for Centrifugally Cast Ferritic/Austenitic Stainless Steel Pipe for Corrosive Environments
ASTM A 874/A 874M-98	Standard Specification for Ferritic Ductile Iron Castings Suitable for Low-Temperature Service
ASTM A 875/A 875M-02a	Standard Specification for Steel Sheet, Zinc-5% Aluminum Alloy-Coated by the Hot-Dip Process
ASTM A 876-03	Standard Specification for Flat-Rolled, Grain-Oriented, Silicon-Iron, Electrical Steel, Fully Processed Types
ASTM A 877/A 877M-99	Standard Specification for Steel Wire, Chromium-Silicon Alloy Valve Spring Quality
ASTM A 878/A 878M-99	Standard Specification for Steel Wire, Modified Chromium Vanadium Valve Spring Quality

Process

Designation	Title
ASTM A 925-03	Standard Specification for Zinc-5% Aluminum-Mischmetal Alloy-Coated Steel Overhead Ground Wire
AOTNI A 323 00	Strand
ASTM A 926-03	Standard Test Method for Comparing the Abrasion Resistance of Coating Materials for Corrugated Metal Pipe
ASTM A 927/A 927M-99	Standard Test Method for Alternating-Current Magnetic Properties of Toroidal Core Specimens Using the Voltmeter-Ammeter-Wattmeter Method
ASTM A 928/A 928M-00	Standard Specification for Ferritic/Austenitic (Duplex) Stainless Steel Pipe Electric Fusion Welded with Addition of Filler Metal
ASTM A 929/A 929M-01	Standard Specification for Steel Sheet, Metallic-Coated by the Hot-Dip Process for Corrugated Steel Pipe
ASTM A 930-03	Standard Practice for Life-Cycle Cost Analysis of Corrugated Metal Pipe Used for Culverts, Storm Sewers, and Other Buried Conduits
ASTM A 931-96 (2002)	Standard Test Method for Tension Testing of Wire Ropes and Strand
ASTM A 932/A 932M-01	Standard Test Method for Alternating-Current Magnetic Properties of Amorphous Materials at Power Frequencies Using Wattmeter-Ammeter-Voltmeter Method with Sheet Specimens
ASTM A 933/A 933M-95 (2001)	Standard Specification for Vinyl (PVC) Coated Steel Wire and Welded Wire Fabric for Reinforcement
ASTM A 934/A 934M-03	Standard Specification for Epoxy-Coated Prefabricated Steel Reinforcing Bars
ASTM A 937/A 937M-01	Standard Test Method for Determining Interlaminar Resistance of Insulating Coatings Using Two Adjacent Test Surfaces
ASTM A 938-97 (2003)	Standard Test Method for Torsion Testing of Wire
ASTM A 939-96 (2001)	Standard Test Method for Ultrasonic Examination from Bored Surfaces of Cylindrical Forgings
ASTM A 940-96 (2001)	Standard Specification for Vacuum Treated Steel Forgings, Alloy, Differentially Heat Treated, for Turbine Rotors
ASTM A 941-03	Terminology Relating to Steel, Stainless Steel, Related Alloys, and Ferroalloys
ASTM A 942-95 (2001)	Standard Specification for Centrifugally Cast White Iron/Gray Iron Dual Metal Abrasion- Resistant Roll Shells
ASTM A 943/A 943M-01	Standard Specification for Spray-Formed Seamless Austenitic Stainless Steel Pipes
ASTM A 944-99	Standard Test Method for Comparing Bond Strength of Steel Reinforcing Bars to Concrete Using Beam-End Specimens
ASTM A 945/A 945M-00	Standard Specification for High-Strength Low-Alloy Structural Steel Plate with Low Carbon and Restricted Sulfur for Improved Weldability, Formability, and Toughness
ASTM A 946-95 (2000)	Standard Specification for Chromium, Chromium-Nickel and Silicon Alloy Steel Plate, Sheet, and Strip for Corrosion and Heat Resisting Service
ASTM A 947M-95 (2000)	Standard Specification for Textured Stainless Steel Sheet [Metric]
ASTM A 949/A 949M-01	Standard Specification for Spray-Formed Seamless Ferritic/Austenitic Stainless Steel Pipe
ASTM A 950/A 950M-99 (2003)	Standard Specification for Fusion Bonded Epoxy-Coated Structural Steel H-Piles and Sheet Piling
ASTM A 951-02	Standard Specification for Masonry Joint Reinforcement
ASTM A 952/A 952M-02	Standard Specification for Forged Grade 80 and Grade 100 Steel Lifting Components and Welded Attachment Links
ASTM A 953-02	Standard Specification for Austenitic Chromium-Nickel-Silicon Alloy Steel Seamless and Welded Tubing
ASTM A 954-02	Standard Specification for Austenitic Chromium-Nickel-Silicon Alloy Steel Seamless and Welded Pipe
ASTM A 955M/ A 955M-03b	Standard Specification for Deformed and Plain Stainless Steel Bars For Concrete Reinforcement
ASTM A 956-02	Standard Test Method for Leeb Hardness Testing of Steel Products
ASTM A 957-03	Standard Specification for Investment Castings, Steel and Alloy, Common Requirements, for General Industrial Use
ASTM A 958-00	Standard Specification for Steel Castings, Carbon, and Alloy, with Tensile Requirements, Chemical Requirements Similar to Standard Wrought Grades
ASTM A 959-03	Standard Guide for Specifying Harmonized Standard Grade Compositions for Wrought Stainless Steels
ASTM A 960-03	Standard Specification for Common Requirements for Wrought Steel Piping Fittings
ASTM A 961-02	Standard Specification for Common Requirements for Steel Flanges, Forged Fittings, Valves, and Parts for Piping Applications
ASTM A 962/A 962M-03	Standard Specification for Common Requirements for Steel Fasteners or Fastener Materials, or Both, Intended for Use at Any Temperature from Cryogenic to the Creep Range
ASTM A 964/A 964M-03	Standard Specification for Corrugated Steel Box Culverts
ASTM A 965/A 965M-02	Standard Specification for Steel Forgings, Austenitic, for Pressure and High Temperature Parts
ASTM A 966/A 966M-96 (2001)	Standard Test Method for Magnetic Particle Examination of Steel Forgings Using Alternating Current
ASTM A 967-01e1	Standard Specification for Chemical Passivation Treatments for Stainless Steel Parts Standard Specification for Chromium, Chromium-Nickel, and Silicon Alloy Steel Bars and Shapes for
ASTM A 968/A 968M-96 (2001) ASTM A 970/A 970M-98	Corrosion and Heat-Resisting Service Standard Specification for Welded or Forged Headed Bars for Concrete Reinforcement
49 LIVI A 9/U/A 9/UIVI-90	Standard Specification for welded of Forged Headed bars for Concrete Remiorcement

Alloy and High-Strength Low-Alloy with Improved Formability

Designation	Title	
ASTM A 1012-02	Standard Specification for Seamless and Welded Ferritic, Austenitic and Duplex Alloy Steel Condenser and Heat Exchanger Tubes With Integral Fins	
ASTM A 1013-00	Standard Test Method for High-Frequency (10 kHz-1 MHz) Core Loss of Soft Magnetic Core Components at Controlled Temperatures Using the Voltmeter-Ammeter-Wattmeter Method	
ASTM A 1014-03	Standard Specification for Precipitation-Hardening Bolting Material (UNS N07718) for High Temperature Service	
ASTM A 1015-01	Standard Guide for Videoborescoping of Tubular Products for Sanitary Applications	
ASTM A 1016/A 1016M-02a	Standard Specification for General Requirements for Ferritic Alloy Steel, Austenitic Alloy Steel, and Stainless Steel Tubes	
ASTM A 1017/A 1017M-01	Standard Specification for Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum-Tungsten	
ASTM A 1018/A 1018M-03a	Specification for Steel, Sheet and Strip, Heavy-Thickness Coils, Hot-Rolled, Carbon, Commercial, Drawing, Structural, High-Strength Low-Alloy, and High-Strength Low-Alloy with Improved Formability	
A1019/A1019M-01	Standard Specification for Closed Rib Steel Pipe with Diameter of 36 in. [900 mm] or Less, Polymer Precoated for Sewers and Drains	
A1020/A1020M-02	Standard Specification for Steel Tubes, Carbon and Carbon Manganese, Fusion Welded, for Boiler, Superheater, Heat Exchanger and Condenser Applications	
A1021-02	Standard Specification for Martensitic Stainless Steel Forgings and Forging Stock for High-Temperature Service	
A1022-01	Standard Specification for Deformed and Plain Stainless Steel Wire and Welded Wire for Concrete Reinforcement	
A1023/A1023M-02	Standard Specification for Stranded Carbon Steel Wire Ropes for General Purposes	
A1024/A1024M-02	Standard Specification for Steel Line Pipe, Black, Plain-End, Seamless	
A1025-02	Standard Specification for Ferroalloys, General Requirements	
A1026-03	Standard Specification for Alloy Steel Structural Shapes for Use in Building Framing	
A1028-03	Standard Specification for Stainless Steel Bars for Compressor and Turbine Airfoils	
A1030/A1030M-03	Standard Practice for Measuring Flatness Characteristics of Coated Sheet Products	
A1031-04	Standard Specification for Steel, Sheet and Strip, Heavy-Thickness Coils, Alloy, Drawing Steel and Structural Steel, Hot-Rolled	

Appendix

2

ASTM DISCONTINUED FERROUS METAL STANDARDS

Discontinued	Replaced By
A 4 (1965)	A 3 – Steel Joint Bars, Low, Medium and High Carbon (Non-Heat-Treated)
A 5 (1979)	A 3 – Steel Joint Bars, Low, Medium and High Carbon (Non-Heat-Treated)
A 7 (1967)	A 36 – Carbon Structural Steel (For Rolled Shapes) A 283 – Low and Intermediate Tensile Strength Carbon Steel Plates A 306 – Discontinued 1975; Replaced by A 663 – Steel Bars, Carbon, Merchant Quality, Mechanical Properties, and A 675 – Steel Bars, Carbon, Hot-Wrought, Special Quality, Mechanical Properties
A 8 (1963)	No Replacement
A 9 (1940)	No Replacement
A 10 (1970)	A 283 – Low and Intermediate Tensile Strength Carbon Steel Plates
A 11 (1930)	A 113 – Discontinued 1979; No Replacement
A 12 (1934)	A 131 – Structural Steel for Ships
A 13 (1934)	A 131 – Structural Steel for Ships
A 14 (1950)	A 68 – Discontinued 1975; Replaced by A 689 – Carbon and Alloy Steel Bars for Springs
A 15 (1969)	A 615 – Deformed and Plain Billet-Steel Bars for Concrete Reinforcement
A 16 (1969)	A 616 – Rail-Steel Deformed and Plain Bars for Concrete Reinforcement
A 17 (1945)	A 273 & A 274 – Discontinued 1975; Replaced by A 711 – Steel Forging Stock
A 18 (1940)	A 236 – Discontinued 1981; No Replacement
A 19 (1936)	A 236 – Discontinued 1981; No Replacement
A 21 (2003)	No Replacement
A 22 (1934)	A 57 – Discontinued 1966; Replaced by A 504 – Wrought Carbon Steel Wheels
A 23 (1917)	A 57 – Discontinued 1966; Replaced by A 504 – Wrought Carbon Steel Wheels
A 24 (1917)	A 57 – Discontinued 1966; Replaced by A 504 – Wrought Carbon Steel Wheels
A 25 (1993)	A 504 – Wrought Carbon Steel Wheels
A 26 (1966)	A 551 – Steel Tires
A 28 (1925)	A 83 – Discontinued 1967; Replaced by A 192 – Seamless Carbon Steel Boiler Tubes for High-Pressure Service
A 30 (1964)	No Replacement
A 32 (1927)	A 107 – Discontinued 1968; Replaced by A 575 – Steel Bars, Carbon, Merchant Quality, M-Grades, and A 576 – Steel Bars, Carbon, Hot-Wrought, Special Quality A 108 – Steel Bars, Carbon, Cold Finished, Standard Quality
A 33 (1937)	E 30 – Discontinued 1995; No Replacement
A 35 (1937)	No Replacement
A 37 (1936)	No Replacement
A 38 (1924)	A 83 – Discontinued 1967; Replaced by A 192 – Seamless Carbon Steel Boiler Tubes for High-Pressure Service
A 39 (1920)	A 84 – Discontinued 1972; No Replacement
A 40 (1920)	A 84 – Discontinued 1972; No Replacement
A 41 (1956)	No Replacement
A 42 (1972)	No Replacement
A 43 (1992)	No Replacement
A 44 (1955)	A 377 – Index of Specifications for Ductile-Iron Pressure Pipe
A 45 (1943)	No Replacement
A 46 (1943)	No Replacement
A 47M (1999)	A 47/A 47M – Specification for Ferritic Malleable Iron Castings
A 50 (1937)	A 183 - Carbon Steel Track Bolts and Nuts
A 51 (1937)	A 183 – Carbon Steel Track Bolts and Nuts
A 52 (1925)	A 83 – Discontinued 1967; Replaced by A 192 – Seamless Carbon Steel Boiler Tubes for High-Pressure Service
A 54 (1927)	A 107 – Discontinued 1968; Replaced by A 575 – Steel Bars, Carbon, Merchant Quality, M-Grades, and A 576 – Steel Bars, Carbon, Hot-Wrought, Special Quality A 108 – Steel Bars, Carbon, Cold Finished, Standard Quality
A 55 (1937)	E 30 – Discontinued 1995; No Replacement
A 56 (1972)	No Replacement
A 57 (1966)	A 504 – Wrought Carbon Steel Wheels
A 58 (1943)	A 689 – Carbon and Alloy Steel Bars for Springs
A 59 (1966)	A 689 – Carbon and Alloy Steel Bars for Springs
A 60 (1966)	A 552 – Discontinued 1974; Replaced by A 689 – Carbon and Alloy Steel Bars for Springs

A 129 (1969)

A 130 (1937)

No Replacement

E 30 - Discontinued 1995; No Replacement

Discontinued	Replaced By
A 133 (1941)	A 237 – Discontinued 1975; Replaced by A 668 – Steel Forgings, Carbon and Alloy, for General Industrial Use A 238 – Discontinued 1989; Replaced by A 730 – Forgings, Carbon and Alloy Steel, for Railway Use
A 136 (1945)	No Replacement
A 137 (1943)	No Replacement
A 138 (1945)	No Replacement
A 140 (1935)	No Replacement
A 141 (1967)	A 502 – Steel Structural Rivets
A 142 (1977)	A 716 – Ductile Iron Culvert Pipe
A 145 (1940)	A 132 – Ferromolybdenum
A 147 (1984)	No Replacement
A 149 (1940)	A 212 – Discontinued 1967; Replaced by A 515 – Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service, and A 516 – Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service
A 150 (1940)	A 212 – Discontinued 1967; Replaced by A 515 – Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service, and A 516 – Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service
A 151 (1938)	No Replacement
A 152 (1972)	No Replacement
A 154 (1936)	A 180 – Discontinued 1937; Replaced by A 27 – Steel Castings, Carbon, for General Application
A 155 (1978)	A 671 – Electric-Fusion-Welded Steel Pipe for Atmospheric and Lower Temperatures A 672 – Electric-Fusion-Welded Steel Pipe for High-Pressure Service at Moderate Temperatures A 691 – Carbon and Alloy Steel Pipe, Electric Fusion-Welded for High-Pressure Service at High Temperatures
A 156 (1936)	A 146 – Molybdenum Oxide Products
A 157 (1953)	A 217 – Steel Castings, Martensitic Stainless and Alloy, for Pressure-Containing Parts Suitable for High- Temperature Service A 351 – Castings, Austenitic, Austenitic-Ferritic (Duplex), for Pressure-Containing Parts
A 158 (1953)	A 335 – Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service
A 160 (1969)	A 617 – Axle-Steel Deformed and Plain Bars for Concrete Reinforcement
A 161 (1999)	A 192 – Seamless Carbon Steel Boiler Tubes for High Pressure Service A 209 – Seamless Carbon-Molybdenum Alloy-Steel Boiler and Superheater Tubes
A 162 (1973)	No Replacement
A 163 (1972)	No Replacement
A 164 (1981)	B 663 – Silver-Tungsten Carbide Electrical Contact Material
A 165 (1988)	B 766 – Electrodeposited Coatings of Cadmium
A 166 (1968)	B 456 – Electrodeposited Coatings of Copper Plus Nickel Plus Chromium and Nickel Plus Chromium
A 168 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 169 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 170 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 171 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 172 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 173 (1954)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application

Discontinued	Replaced By
A 174 (1940)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 175 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 177 (1989)	A 666 – Annealed or Cold-Worked Austenitic Stainless Steel, Sheet, Strip, Plate, and Flat Bar
A 180 (1937)	A 27 – Steel Castings, Carbon, for General Application
A 186 (1966)	A 504 – Wrought Carbon Steel Wheels
A 187 (1943)	No Replacement
A 188 (1943)	No Replacement
A 189 (1972)	No Replacement
A 190 (1962)	No Replacement
A 191 (1942)	A 239 – Test Method for Locating the Thinnest Spot in a Zinc (Galvanized) Coating on Iron or Steel Articles by the Preece Test (Copper Sulfate Dip)
A 195 (1966)	A 502 – Steel Structural Rivets
A 196 (1962)	No Replacement
A 197M (1998)	A 197/A 197M
A 198 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 199/A 199M (1995)	A 200 – Seamless Intermediate Alloy-Steel Still Tubes for Refinery Service
A 200 (1999)	A 213 – Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes
A 201 (1967)	A 515 – Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service A 516 – Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service
A 205 (1967)	A 233 – Discontinued 1970; No Replacement A 251 – Discontinued 1970; No Replacement
A 206 (1953)	A 335 – Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service
A 207 (1972)	No Replacement
A 208 (1941)	A 239 – Test Method for Locating the Thinnest Spot in a Zinc (Galvanized) Coating on Iron or Steel Articles by the Preece Test (Copper Sulfate Dip)
A 211 (1993)	No Replacement
A 212 (1967)	A 515 – Pressure Vessel Plates, Carbon Steel, for Intermediate- and Higher-Temperature Service A 516 – Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service
A 215 (1947)	A 27 – Steel Castings, Carbon, for General Application
A 218 (1963)	A 475 – Zinc-Coated Steel Wire Strand
A 219 (1972)	B 487 – Test Method for Measurement of Metal and Oxide Coating Thicknesses by Microscopical Examination of a Cross Section B 499 – Test Method for Measurement of Coating Thicknesses by the Magnetic Method: Nonmagnetic Coatings on Magnetic Basis Metals B 504 – Test Method for Measurement of Thickness of Metallic Coatings by the Coulometric Method B 529 – Discontinued 1979; Replaced by B 244 – Test Method for Measurement of Thickness of Anodic Coatings on Aluminum and of Other Nonconductive Coatings on Nonmagnetic Basis Metals with Eddy-Current Instruments B 530 – Test Method for Measurement of Coating Thicknesses by the Magnetic Method: Electrodeposited Nickel Coatings on Magnetic and Nonmagnetic Substrates
A 220M (1999)	A 220/A 220M
A 221 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 222 (1947)	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application

Discontinued	Replaced By
	A 296 – Discontinued 1980; Replaced by A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-
A 223 (1947)	Resistant, for General Application, and A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for
,	Severe Service A 297 – Steel Castings, Iron-Chromium and Iron-Chromium-Nickel, Heat-Resistant, for General Application
A 224 (1969)	G 4 – Guide for Conducting Corrosion Coupon Tests in Field Applications
A 226/A 226M (1997)	No Replacement
A 233 (1970)	No Replacement
A 235 (1975)	A 668 – Steel Forgings, Carbon and Alloy, for General Industrial Use
A 236 (1981)	No Replacement
A 237 (1975)	A 668 – Steel Forgings, Carbon and Alloy, for General Industrial Use
A 238 (1989)	A 730 – Forgings, Carbon and Alloy Steel, for Railway Use
A 241 (1979)	A 67 – Steel Tie Plates, Low-Carbon and High-Carbon Hot-Worked
A 243 (1975)	A 668 – Steel Forgings, Carbon and Alloy, for General Industrial Use
A 244 (1947)	A 504 – Wrought Carbon Steel Wheels
· ,	A 570 – Steel, Sheet and Strip, Carbon, Hot-Rolled, Structural Quality
A 245 (1972)	A 611 – Structural Steel (SS), Sheet, Carbon, Cold-Rolled
A 246 (1059)	A 245 – Discontinued 1972; Replaced by A 570 – Steel, Sheet and Strip, Carbon, Hot-Rolled, Structural Quality
A 246 (1958)	A 611 – Structural Steel (SS), Sheet, Carbon, Cold-Rolled
A 248 (1972)	A 273 & A 274 – Discontinued 1975; Replaced by A 711 – Steel Forging Stock
A 251 (1970)	No Replacement
A 253 (1962)	No Replacement
A 256 (1990)	No Replacement
A 257 (1945)	A 34 – Practice for Sampling and Procurement Testing of Magnetic Materials
A 258 (1945)	A 34 – Practice for Sampling and Procurement Testing of Magnetic Materials
A 259 (1945)	A 34 – Practice for Sampling and Procurement Testing of Magnetic Materials
A 260 (1966)	No Replacement
A 261 (1959)	No Replacement
A 267 (1954)	No Replacement
A 271 (1999)	A 213 – Seamless Ferritic and Austenitic Alloy-Steel Boiler, Superheater, and Heat-Exchanger Tubes
A 272 (1945)	E 109 – Discontinued 1981; Replaced by E 709 – Guide for Magnetic Particle Examination
A 273 (1975)	A 711 – Steel Forging Stock
A 274 (1975)	A 711 – Steel Forging Stock
A 277 (1952)	A 338 – Malleable Iron Flanges, Pipe Fittings, and Valve Parts for Railroad, Marine, and Other Heavy Duty Service at Temperatures up to 650°F (345°C)
A 279 (1945)	G 31 – Practice for Laboratory Immersion Corrosion Testing of Metals
A 280 (1953)	A 335 – Seamless Ferritic Alloy-Steel Pipe for High-Temperature Service
A 281 (1947)	A 27 – Steel Castings, Carbon, for General Application
A 282 (1945)	A 148 – Steel Castings, High Strength, for Structural Purposes
A 284/A 284M (1992)	A 283 – Low and Intermediate Tensile Strength Carbon Steel Plates
A 286 (1960)	A 434 – Steel Bars, Alloy, Hot-Wrought or Cold-Finished, Quenched and Tempered
A 287 (1955)	No Replacement
A 292 (1968)	A 469 – Vacuum-Treated Steel Forgings for Generator Rotors
A 293 (1984)	A 470 – Vacuum-Treated Carbon and Alloy Steel Forgings for Turbine Rotors and Shafts
' '	
A 296 (1980)	A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application
A 298 (1970)	
, ,	· ·
` '	
` '	
7. 000 (1070)	
A 305 (1968)	A 616 – Rail-Steel Deformed and Plain Bars for Concrete Reinforcement A 617 – Axle-Steel Deformed and Plain Bars for Concrete Reinforcement
A 306 (1975)	A 663 – Steel Bars, Carbon, Merchant Quality, Mechanical Properties A 675 – Steel Bars, Carbon, Hot-Wrought, Special Quality, Mechanical Properties
A 310 (1949)	Redesignated A 345 – Flat-Rolled Electrical Steels for Magnetic Applications
A 294 (1988) A 296 (1980) A 298 (1970) A 300 (1975) A 301 (1956) A 303 (1970) A 305 (1968) A 306 (1975)	A 471 – Vacuum-Treated Alloy Steel Forgings for Turbine Rotor Disks and Wheels A 743 – Castings, Iron-Chromium, Iron-Chromium-Nickel, Corrosion-Resistant, for General Application A 744 – Castings, Iron-Chromium-Nickel, Corrosion-Resistant, for Severe Service No Replacement No Replacement A 387 – Pressure Vessel Plates, Alloy Steel, Chromium-Molybdenum A 570 – Steel, Sheet and Strip, Carbon, Hot-Rolled, Structural Quality A 615 – Deformed and Plain Billet-Steel Bars for Concrete Reinforcement A 616 – Rail-Steel Deformed and Plain Bars for Concrete Reinforcement A 617 – Axle-Steel Deformed and Plain Bars for Concrete Reinforcement A 663 – Steel Bars, Carbon, Merchant Quality, Mechanical Properties A 675 – Steel Bars, Carbon, Hot-Wrought, Special Quality, Mechanical Properties

Discontinued	Replaced By
A 412 (1989)	No Replacement
A 415 (1970)	A 569 – Steel, Carbon (0.15 Maximum, Percent) Hot-Rolled Sheet and Strip Commercial Quality
A 417M (1989)	No Replacement
A 419 (1971)	No Replacement
A 422 (1994)	No Replacement
A 425 (1970)	A 569 – Steel, Carbon (0.15 Maximum, Percent) Hot-Rolled Sheet and Strip Commercial Quality
A 429 (1976)	A 276 – Stainless Steel Bars and Shapes
A 430/A 430M (1995)	A 312 – Seamless and Welded Austenitic Stainless Steel Pipes
A 431 (1968)	A 615 – Deformed and Plain Billet Steel Bars for Concrete Reinforcement
A 432 (1968)	A 615 – Deformed and Plain Billet-Steel Bars for Concrete Reinforcement
` '	No Replacement
A 433 (1972)	
A 438-80 (1997)	No Replacement
A 440 (1979)	No Replacement
A 441/A 441M (1989)	A 572/A 572M – High-Strength Low-Alloy Columbium-Vanadium Structural Steel
A 442/A 442M (1991)	No Replacement
A 443 (1966)	Combined with A 370 – Test Methods and Definitions for Mechanical Testing of Steel Products
A 444/A 444M (1995)	A 929/A 929M – Steel Sheet Metallic-Coated by the Hot-Dip Process for Corrugated Steel Pipe
A 445 (1974)	A 395 – Ferritic Ductile Iron Pressure-Retaining Castings for Use at Elevated Temperatures
A 446/A 446M (1004)	A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-
A 446/A 446M (1994)	Dip Process A 924/A 924M – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process
A 448 (1976)	No Replacement
A 452 (1995)	No Replacement
A 454 (1980)	No Replacement
A 457 (1990)	No Replacement
A 458 (1991)	No Replacement
A 461 (1971)	A 564 – Hot-Rolled and Cold-Finished Age-Hardening Stainless Steel Bars and Shapes A 637 – Discontinued; Redesignated B 637 – Precipitation-Hardening Nickel Alloy Bars, Forgings, and Forging Stock for High-Temperature Service A 638 – Precipitation Hardening Iron Base Superalloy Bars, Forgings, and Forging Stock for High-Temperature Service
	A 639 – Discontinued; Redesignated B 639 – Precipitation Hardening Cobalt-Containing Alloys (UNS R30155 and UNS R30816) Rod, Bar, Forgings, and Forging Stock for High-Temperature Service
A 462	E 165 – Test Method for Liquid Penetrant Examination
A 464 (1968)	A 376 – Seamless Austenitic Steel Pipe for High-Temperature Central-Station Service
A 465 (1975)	No Replacement
A 468 (1969)	A 6 – General Requirements for Rolled Structural Steel Bars, Plates, Shapes, and Sheet Piling A 341 – Test Method for Direct Current Magnetic Properties of Materials Using D-C Permeameters and the Ballistic Test Methods
A 476 (2000)	A 476/A 476M-00 – Ductile Iron Castings for Paper Mill Dryer Rolls
A 476M (2000)	A 476/A 476M-00 – Ductile Iron Castings for Paper Mill Dryer Rolls
A 477 (1991)	No Replacement
A 486/A 486M (1989)	No Replacement
A 502 (1999)	F 1470 – Guide for Fastener Sampling for Specified Mechanical Properties and Performance Inspection
A 509 (1983)	A 788 – General Requirements for Steel Forgings
A 518 M (1999)	A 518/A 518 M – Standard Specification for Corrosion-Resistant High-Silicon Iron Castings
A 520 (2000)	No Replacement
A 525/A 525M (1994)	A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot- Dip Process A 924/A 924M – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process
A 526/A 526M (1994)	A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot- Dip Process A 924/A 924M – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process
A 527/A 527M (1994)	A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot- Dip Process A 924/A 924M – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process
A 528/A 528M (1994)	A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot- Dip Process A 924/A 924M – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process

Discontinued	Replaced By
A 535 (1999)	No Replacement
A 538/A 538M (1989)	No Replacement
A 544 (1991)	No Replacement
A 545 (1991)	No Replacement
A 546 (1991)	No Replacement
A 547 (1991)	No Replacement
A 548 (1991)	No Replacement
A 549 (1991)	No Replacement
A 552 (1974)	A 689 – Carbon and Alloy Steel Bars for Springs
A 557/A 557M (1995)	A 178 – Electric-Resistance-Welded Carbon Steel and Carbon-Manganese Steel Boiler and Superheater Tubes
A 558 (1969)	No Replacement
A 559 (1969)	No Replacement
A 566 (1984)	No Replacement
A 567/A 567M (1987)	No Replacement
A 568M (1991)	A 568/A 568M – General Requirements for Steel, Sheet, Carbon, and High-Strength, Low-Alloy, Hot-Rolled
A 308W (1991)	and Cold-Rolled
A 569/A 569M (2000)	A 1011/A 1011M – Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-Strength Low-Alloy with Improved Formability
A 570/A 570M (2000)	A 1011/A 1011M – Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy and High- Strength Low-Alloy with Improved Formability
A 583	No Replacement
A 584 (2002)	No Replacement
A 585 (2002)	A 121 – Standard Specification for Zinc-Coated (Galvanized) Steel Barbed Wire
A 590 (1984)	No Replacement
A 593 (1976)	No Replacement
A 594 (1986)	No Replacement
A 599 (1992)	A 599/A 599M-99 – Tin Mill Products, Electrolytic Tin-Coated, Cold-Rolled Sheet
A 605/A 605M (1989)	No Replacement
A 607 (2000)	A 1011/A 1011M – Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-Strength Low-Alloy with Improved Formability
A 611 (2000)	A 1008 – Steel, Sheet, Cold-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-Strength Low-Alloy with Improved Formability
A 613 (1984)	No Replacement
A 614 (1987)	No Replacement
A 615M (1993)	A 615/A 615M – Deformed and Plain Billet-Steel Bars for Concrete Reinforcement
A 616/A 616M (1999)	A 996/A 996M – Rail-Steel and Axle-Steel Deformed Bars for Concrete Reinforcement
A 617/A 617M (1999)	A 996/A 996M – Rail-Steel and Axle-Steel Deformed Bars for Concrete Reinforcement
A 619/A 619M (1997)	No Replacement
A 620/A 620M (2000)	A 1008 – Steel, Sheet, Cold-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-Strength Low-Alloy with Improved Formability
A 621/A 621M (1997)	No Replacement
A 622/A 622M (2000)	A 1011/A 1011M – Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-
. ,	Strength Low-Alloy with Improved Formability
A 624M (1995)	A 624/A 624M – Tin Mill Products, Electrolytic Tin Plate, Single Reduced
A 625M (1992)	A 625/A 625M – Tin Mill Products, Black Plate, Single Reduced
A 626M (1995)	A 626/A 626M – Tin Mill Products, Electrolytic Tin Plate, Double Reduced
A 628 (1982)	No Replacement
A 631 (1993)	A 583 – Cast Steel Wheels for Railway Service
A 634 (1978)	No Replacement
A 635M (1991)	A 635/A 635M – Steel, Sheet and Strip, Heavy-Thickness Coils, Carbon, Hot-Rolled
A 637	Redesignated B 637 – Precipitation-Hardening Nickel Alloy Bars, Forgings, and Forging Stock for High- Temperature Service
A 639	Redesignated B 639 – Precipitation Hardening Cobalt-Containing Alloys (UNS R30155 and UNS R30816) Rod, Bar, Forgings, and Forging Stock for High-Temperature Service
A 641M (1997)	A 641/A 641M – Zinc-Coated (Galvanized) Carbon Steel Wire
A 0.40/A 0.40(* // 50 f)	A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-
A 642/A 642M (1994)	Dip Process A 924/A 924M – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process

Discontinued	Replaced By
A 643 (1982)	No Replacement
A 647 (1982)	No Replacement
A 650M-88 (1988)	A 650/A 650M – Tin Mill Products, Black Plate, Double Reduced
A 651 (1987)	No Replacement
A 652 (1984)	No Replacement
A 654 (1984)	No Replacement
A 655 (1984)	No Replacement
A 658/A 658M (1989)	No Replacement
A 661	Not Yet Assigned
A 665/A 665M (1998)	A 876/A 876M – Flat-Rolled, Grain-Oriented, Silicon-Iron, Electrical Steel, Fully Processed Types [Metric]
A 667M (1987)	A 667/A 667M – Centrifugally Cast Dual Metal (Gray and White Cast Iron) Cylinders
A 669 (1984)	A 789 – Seamless and Welded Ferritic/Austenitic Stainless Steel Tubing for General Service
A 670	Redesignated B 670 – Precipitation-Hardening Nickel Alloy (UNS N07718) Plate, Sheet, and Strip for High- Temperature Service
A 676 (1990)	No Replacement
A 677M (2000)	A 677/A 677M – Nonoriented Electrical Steel, Fully Processed Types
A 680/A 680M (1986)	A 684/A 684M – Steel, Strip, High-Carbon, Cold-Rolled
A 682M (1998)	A 682/A 682M – General Requirements for Steel, Strip, High-Carbon, Cold-Rolled, Spring Quality
A 683M (1999)	A 683/A 683M – Nonoriented Electrical Steel, Semiprocessed Types
A 685 (1986)	A 681 – Tool Steels Alloy
A 687 (1999)	No Replacement
A 695 (2002)	No Replacement
A 698 (1992)	A 698/A 698M – Test Method for Magnetic Shield Efficiency in Attenuating Alternating Magnetic Fields
A 692 (1995)	A 209 – Seamless Carbon-Molybdenum Alloy-Steel Boiler and Superheater Tubes
A 699 (1986)	No Replacement
A 708 (1989)	No Replacement
` ′	A 1011/A 1011M - Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-
A 715 (2000)	Strength Low-Alloy with Improved Formability
A 718 (1996)	No Replacement
A 722 (1995)	A 722/A 722M – Uncoated High-Strength Steel Bar for Prestressing Concrete
A 725/A 725M (1988)	A 876/A 876M – Flat-Rolled, Grain-Oriented, Silicon-Iron, Electrical Steel, Fully Processed Types [Metric]
A 726M (1998)	A 726 – Cold-Rolled Magnetic Lamination Quality Steel, Semiprocessed Types
A 728	Not Yet Assigned
A 731/A 731M (1995)	A 268 – Seamless and Welded Ferritic and Martensitic Stainless Steel Tubing for General Service
A 749M (1991)	A 749/A 749M – General Requirements for Steel, Strip, Carbon and High-Strength, Low-Alloy, Hot-Rolled
A 766/A 766M (1991)	No Replacement
A 776	Not Yet Assigned
A 777 (1995)	No Replacement
A 783 (1987)	No Replacement
A 784 (1988)	No Replacement
A 785 (1988)	No Replacement
A 791/A 791M (1995)	A 268 – Seamless and Welded Ferritic and Martensitic Stainless Steel Tubing for General Service
A 792M (1994)	A 792/A 792M – Steel Sheet, 55 Aluminum-Zinc Alloy-Coated by the Hot-Dip Process
A 797 (1990)	No Replacement A 000/A 000M Steel Sheet Metallic Costed by the Llet Dip Process for Corrugated Steel Dipe
A 806/A 806M (1995)	A 929/A 929M – Steel Sheet Metallic-Coated by the Hot-Dip Process for Corrugated Steel Pipe
A 812/A 812M (1997) A 816/A 816M (1994)	No Replacement A 653/A 653M – Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
A 040 (4005)	A 924/A 924Ma – General Requirements for Steel Sheet, Metallic-Coated by the Hot-Dip Process
A 819 (1995)	A 929/A 929M – Steel Sheet, Metallic-Coated by the Hot-Dip Process for Corrugated Steel Pipe
A 825 (1991)	No Replacement
A 828	Not Yet Assigned
A 829 (1992)	A 829/A 829M – Alloy Structural Steel Plates
A 830 (1992)	A 830/A 830M – Plates, Carbon Steel, Structural Quality, Furnished to Chemical Composition Requirements
A 831 (1994)	No Replacement
A 840 (2000)	A 840/A 840M – Fully Processed Magnetic Lamination Steel
A 843 (1988)	A 876/A 876M – Flat-Rolled, Grain-Oriented, Silicon-Iron, Electrical Steel, Fully Processed Types [Metric]

3

JIS STEEL AND RELATED STANDARDS

470 JIS Steel and Related Standards Appendix 3

Designation	Title
G 3101:2004	Rolled steels for general structure
G 3103:1987	Carbon steel and molybdenum alloy steel plates for boilers and other pressure vessels
G 3104:1987	Steel bars for rivet
G 3105:1987	Steel bars for chains
G 3106:2004	Rolled steels for welded structure
G 3108:1987	Rolled carbon steel for cold-finished steel bars
G 3109:1994	Steel bars for prestressed concrete
G 3111:1987	Rerolled carbon steel
G 3112:1987	Steel bars for concrete reinforcement
G 3113:1990	Hot-rolled steel plates, sheets and strip for automobile structural uses
G 3114:2004	Hot-rolled atmospheric corrosion resisting steels for welded structure
G 3115:2000	Steel plates for pressure vessels for intermediate temperature service
G 3116:2000	Steel sheets, plates and strip for gas cylinders
G 3117:1987	Rerolled steel bars for concrete reinforcement
G 3118:2000	Carbon steel plates for pressure vessels for intermediate and moderate temperature service
G 3119:1987	Manganese-molybdenum alloy and manganese-molybdenum-nickel alloy steel plates for boilers and other pressure vessels
G 3120:1987	Manganese-molybdenum and manganese-molybdenum-nickel alloy steel plates quenched and tempered for pressure vessels
G 3123:1987	Cold finished carbon and alloy steel bars
G 3124:2004	High strength steel plates for pressure vessel for intermediate and moderate temperature service
G 3125:2004	Superior atmospheric corrosion resisting rolled steels
G 3126:2004	Carbon steel plates for pressure vessels for low temperature service
G 3127:2000	Nickel steel plates for pressure vessels for low temperature service
G 3128:1999	High yield strength steel plates for welded structure
G 3129:1995	High tensile strength steel for tower structural purposes
G 3131:1996	Hot-rolled mild steel plates, sheets and strip
G 3132:1990	Hot-rolled carbon steel strip for pipes and tubes
G 3133:2004	Decarburized steel sheets and strip for porcelain enamelling
G 3134:1990	Hot rolled high strength steel sheets with improved formability for automobile structural uses
G 3135:1986	Cold rolled high strength steel sheets with improved formability for automobile structural uses
G 3136:1994	Rolled steels for building structure
G 3137:1994	Small size-deformed steel bars for prestressed concrete
G 3138:1996	Rolled bars for building structure
G 3141:1996	Cold-reduced carbon steel sheets and strip
G 3191:2002	Shape, dimensions, weight and tolerance for hot rolled steel bar and bar-in-coil
G 3192:2000	Dimensions, mass and permissible variations of hot rolled steel sections
G 3193:1990	Dimensions, mass and permissible variations of hot rolled steel plates, sheets and strip
G 3194:1998	Dimensions, mass and permissible variations of hot rolled flat steel
G 3199:1992	Specification for through-thickness characteristics of steel plate and wide flat
G 3201:1988	Carbon steel forgings for general use
G 3202:1988	Carbon steel forgings for pressure vessels
G 3203:1988	Alloy steel forgings for pressure vessels for high-temperature service
G 3204:1988	Quenched and tempered alloy steel forgings for pressure vessels
G 3205:1988	Carbon and alloy steel forgings for pressure vessels for low-temperature service
G 3205:1988 G 3206:1993	High strength chromium-molybdenum alloy steel forgings for pressure vessels under high-temperature service
G 3214:1991	Stainless steel forgings for pressure vessels
G 3214:1991 G 3221:1988	Chromium molybdenum steel forgings for general use
G 3221:1988 G 3222:1988	Nickel chromium molybdenum steel forgings for general use
	, , , , , , , , , , , , , , , , , , , ,
G 3223:1988	High tensile strength steel forgings for tower flanges
G 3251:1988	Carbon steel blooms and billets for forgings
G 3302:1998	Hot-dip zinc-coated steel sheets and coils
G 3303:2002	Tinplate and blackplate
G 3311:1998	Cold rolled special steel strip
G 3312:1994	Prepainted hot-dip zinc-coated steel sheets and coils
G 3313:1998	Electrolytic zinc-coated steel sheets and coils

Designation	Title
G 3314:1995	Hot-dip aluminium-coated steel sheets and coils
G 3315:2002	Chromium plated tin free steel
G 3316:1987	Shapes and dimensions of corrugated steel sheets
G 3317:1994	Hot-dip zinc-5% aluminium alloy-coated steel sheets and coils
G 3318:1994	Prepainted hot-dip zinc-5% aluminium alloy-coated steel sheets and coils
G 3320:1999	Coated stainless steel sheets
G 3321:1998	Hot-dip 55% aluminium-zinc alloy-coated steel sheets and coils
G 3322:1998	Prepainted hot-dip 55% aluminium-zinc alloy-coated steel sheets and coils
	Light gauge steels for general structure
G 3350:1987 G 3351:1987	
	Expanded metals
G 3352:2003	Steel decks
G 3353:1990	Welded light gauge H steels for general structures
G 3429:1988	Seamless steel tubes for high pressure gas cylinder
G 3441:1988	Alloy steel tubes for machine purposes
G 3442:2004	Galvanized steel pipes for ordinary piping
G 3443:2004	Coated steel pipes for water service
G 3444:1994	Carbon steel tubes for general structural purposes
G 3445:1988	Carbon steel tubes for machine structural purposes
G 3446:1994	Stainless steel pipes for machine and structural purposes
G 3447:2004	Stainless steel sanitary pipes
G 3448:2004	Light gauge stainless steel tubes for ordinary piping
G 3451:1987	Fittings of coated steel pipes for water service
G 3452:2004	Carbon steel pipes for ordinary piping
G 3454:1988	Carbon steel pipes for pressure service
G 3455:1988	Carbon steel pipes for high pressure service
G 3456:2004	Carbon steel pipes for high temperature service
G 3457:1988	Arc welded carbon steel pipes
G 3458:1988	Alloy steel pipes
G 3459:2004	Stainless steel pipes
G 3460:1988	Steel pipes for low temperature service
G 3461:1988	Carbon steel boiler and heat exchanger tubes
G 3462:2004	Alloy steel boiler and heat exchanger tubes
G 3463:1994	Stainless steel boiler and heat exchanger tubes
G 3464:1988	Steel heat exchanger tubes for low temperature service
G 3465:1988	Seamless steel tubes for drilling
G 3466:1988	Carbon steel square pipes for general structural purposes
G 3467:1988	Steel tubes for fired heaters
G 3468:2004	Large diameter welded stainless steel pipes
G 3469:2002	Polyethylene coated steel pipes
G 3471:1977	Corrugated steel pipes and sections
G 3472:1988	Electric resistance welded carbon steel tubes for automobile structural purposes
G 3473:1988	Carbon steel tubes for cylinder barrels
G 3474:1995	High tensile strength steel tubes for tower structural purposes
G 3475:1996	Carbon steel tubes for building structure
G 3491:1993	Asphalt protective coatings for steel water pipe
G 3492:1993	Coal-tar enamel protective coatings for steel water pipe
G 3502:2004	Piano wire rods
G 3503:1980	Wire rods for core wire of covered electrode
G 3505:2004	Low carbon steel wire rods
G 3506:2004	High carbon steel wire rods
G 3507:1991	Carbon steel wire rods for cold heading and cold forging
G 3508:1991	Boron steel wire rods for cold heading and cold forging
G 3509-1:2003	Low-alloyed steels for cold heading – Part 1: Wire rods
G 3509-2:2003	Low-alloyed steels for cold heading – Part 2: Wires
G 3510:1992	Testing methods for steel tire cords
5. 00 10.100Z	1 . 55

472 JIS Steel and Related Standards Appendix 3

Designation	Title
G 3521:1991	Hard drawn steel wires
G 3522:1991	Piano wires
G 3523:1980	Core wires for covered electrode
G 3525:1980	Wire ropes
G 3532:2000	Low carbon steel wires
G 3533:1993	Barbed wires
G 3535:1998	Wire ropes for aircraft control
G 3536:1999	Uncoated stress-relieved steel wires and strands for prestressed concrete
G 3537:1994	Zinc-coated steel wire strands
G 3538:1994	Hard drawn steel wire for prestressed concrete
G 3539:1991	Carbon steel wires for cold heading and cold forging
G 3540:1995	Wire ropes for mechanical control
G 3542:1993	Precoated color zinc-coated steel wires
G 3543:1999	Polyvinyl chloride coated color steel wires
G 3544:1993	Hot-dip aluminium-coated steel wires
G 3545:1991	Boron steel wires for cold heading and cold forging
G 3546:2000	Wire ropes with profile wires
G 3547:1993	Zinc-coated low carbon steel wires
G 3548:1994	Zinc-coated steel wires
G 3549:2000	Wire ropes for structure
G 3550:2003	Stainless steel wire ropes for structure
G 3551:2000	Welded steel wire and bar fabrics
G 3552:2002	Chain link wire netting
G 3553:2002	Crimped wire cloth
G 3554:2002	Hexagonal wire netting
G 3555:2004	Woven wire cloth
G 3556:2002	Industrial woven wire cloths
G 3560:1994	Oil tempered wire for mechanical springs
G 3561:1994	Oil tempered wire for valve springs
G 3601:2002	Stainless-clad steels
G 3602:2004	Nickel and nickel alloy clad steels
G 3603:1992	Titanium clad steels
G 3604:2004	Copper and copper alloy clad steels
G 4051:1979	Carbon steels for machine structural use
G 4052:2003	Structural steels with specified hardenability bands
G 4053:2003	Low-alloyed steels for machine structural use
G 4107:1994	Alloy steel bolting materials for high temperature service
G 4108:1994	Alloy steel bars for special application bolting materials
G 4109:2003	Chromium-molybdenum alloy steel plates for boilers and pressure vessels
G 4110:2004	High strength chromium-molybdenum and chromium-molybdenum-vanadium alloy steel plates for pressure vessels under high-temperature service
G 4202:1979	Aluminium chromium molybdenum steels
G 4303:1998	Stainless steel bars
G 4304:1999	Hot rolled stainless steel plates, sheets and strip
G 4305:1999	Cold rolled stainless steel plates, sheets and strip
G 4308:1998	Stainless steel wire rods
G 4309:1999	Stainless steel wires
G 4310:1999	Method of mass calculation for stainless steel plates and sheets, and heat-resisting steel plates and sheets
G 4311:1991	Heat-resisting steel bars
G 4312:1991	Heat-resisting steel plates and sheets
G 4313:1996	Cold rolled stainless steel strip for springs
G 4314:1994	Stainless steel wires for springs
G 4315:2000	Stainless steel wires for cold heading and cold forging
G 4316:1991	Stainless steel wire rods for welding
G 4317:1999	Hot rolled stainless steel equal leg angles
G 4318:1998	Cold finished stainless steel bars
G 7010.1000	Cota innorted diaminoso dicor baro

Designation	Title
G 4319:1991	Stainless steel blooms and billets for forgings
G 4320:2003	Cold formed stainless steel sections
G 4320:2003	Stainless steel for building structure
G 4321:2000 G 4401:2000	Carbon tool steels
G 4403:2000	High speed tool steels
G 4404:2000	Alloy tool steels
G 4410:1984	Hollow drill steels
G 4801:1984	Spring steels
G 4802:1999	Cold-rolled steel strips for springs
G 4804:1999	Free cutting carbon steel
G 4805:1999	High carbon chromium bearing steels
G 4901:1999	Corrosion-resisting and heat-resisting superalloy bars
G 4902:1991	Corrosion-resisting and heat-resisting superalloy plates and sheets
G 4903:1991	Seamless nickel-chromium-iron alloy pipes
G 4904:1991	Seamless nickel-chromium-iron alloy heat exchanger tubes
G 5101:1991	Carbon steel castings
G 5102:1991	Steel castings for welded structure
G 5111:1991	High tensile strength carbon steel castings and low alloy steel castings for structural purposes
G 5121:2003	Corrosion-resistant cast steels for general applications
G 5122:2003	Heat-resistant cast steels and alloys for general applications
G 5131:1991	High manganese steel castings
G 5151:1991	Steel castings for high temperature and high pressure service
G 5152:1991	Steel castings for low temperature and high pressure service
G 5201:1991	Centrifugally cast steel pipes for welded structure
G 5202:1991	Centrifugally cast steel pipes for high temperature and high pressure service
G 5501:1995	Grey iron castings
G 5502:2001	Spheroidal graphite iron castings
G 5503:1995	Austempered spheroidal graphite iron castings
G 5504:1992	Heavy-walled ferritic spheroidal graphite iron castings for low temperature service
G 5510:1999	Austenitic iron castings
G 5511:1991	Low thermal expansive fe-alloy castings
G 5525:2000	Cast-iron drainage pipes and fittings
G 5525:2000 G 5526:1998	Ductile iron pipes
G 5527:1998	Ductile iron fittings
G 5527.1996 G 5528:1984	Epoxy-powder coating for interior of ductile iron pipes and fittings
G 5528:1984 G 5705:2000	Malleable iron castings
	· ·
G 5901:1974	Molding silica sand
G 5902:1974	Molding natural sand
G 5903:1975	Cast shot and grit
G 5904:1966	Testing method of cast shot and grit grain size
G 7101:2000	Structural steels with improved atmospheric corrosion resistance
G 7102:2000	Continuously hot-rolled steel sheet of structural quality with improved atmospheric corrosion resistance
G 7103:2000	Steel for the reinforcement of concrete – Part 1: Plain bars
G 7104:2000	Steel for the reinforcement of concrete – Part 2: Ribbed bars
G 7105:2000	Heat-treatable steels, alloy steels and free-cutting steels – Part 18: Bright products of unalloyed and low alloy steels
G 7121:2000	Cold-reduced electrolytic tinplate
G 7122:2000	Cold-reduced electrolytic chromium/chromium oxide-coated steel
G 7123:2000	Cold-reduced blackplate in coil form for the production of tinplate or electrolytic chromium/chromium oxide-coated steel
G 7124:2000	Continuous hot-dip aluminium/silicon-coated cold-reduced carbon steel sheet of commercial and drawing qualities
G 7125:2003	Hollow steel bars for machining (ISO specifications)
G 7214:2000	Seamless nickel and nickel alloy tube
G 7215:2003	Plain end seamless steel tubes for mechanical application (ISO specifications)
G 7216:2003	Plain end seamless precision steel tubes – Technical conditions for delivery (ISO specifications)
G 7217:2003	Plain end welded precision steel tubes – Technical conditions for delivery (ISO specifications)
G 7218:2003	Plain end as-welded and sized precision steel tubes – Technical conditions for delivery (ISO specifications)
	,

474 JIS Steel and Related Standards Appendix 3

Designation	Title
G 7219:2003	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 1: Unalloyed steels with specified room temperature properties (ISO specifications)
G 7220:2003	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 2: Unalloyed and alloyed steels with specified elevated temperature properties (ISO specifications)
G 7221:2003	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 3: Unalloyed and alloyed steels with specified low temperature properties (ISO specifications)
G 7222:2003	Seamless steel tubes for pressure purposes – Technical delivery conditions – Part 4: Austenitic stainless steels (ISO specifications)
G 7223:2003	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 1: Unalloyed steel tubes with specified room temperature properties (ISO specifications)
G 7224:2003	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 2: Electric resistance and induction welded unalloyed and alloyed steel tubes with specified elevated temperature properties (ISO specifications)
G 7225:2003	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 3: Electric resistance and induction welded unalloyed and alloyed steel tubes with specified low temperature properties (ISO specifications)
G 7226:2003	Welded steel tubes for pressure purposes – Technical delivery conditions – Part 6: Longitudinally welded austenitic stainless steel tubes (ISO specifications)
G 7301:1998	Steel wire ropes for general purposes – Characteristics
G 7302:2000	Zinc coatings for steel wire
G 7303:2000	Zinc-coated steel wire for fencing
G 7304:2000	Steel wire for mechanical springs – Part 1: General requirements
G 7305:2000	Steel wire for mechanical springs – Part 2: Cold-drawn carbon steel wire
G 7306:2000	Steel wire for mechanical springs – Part 3: Oil-hardened and tempered wire
G 7307:2000	Steel for the prestressing of concrete – Part 1: General requirements
G 7308:2000	Steel for the prestressing of concrete – Part 2: Cold-drawn wire
G 7309:2000	Steel for the prestressing of concrete – Part 3: Quenched and tempered wire
G 7310:2000	Steel for the prestressing of concrete – Part 4: Strand
G 7311:2000	Steel for the prestressing of concrete – Part 5: Hot-rolled steel bars with or without subsequent processing
G 7401:2000	Steels for cold heading and cold extruding
G 7501:2000	Direct-hardening unalloyed and low-alloyed wrought steel in form of different black products
G 7502:2000	Wrought nitriding steels
G 7503:2000	Wrought case-hardening steels
G 7601:2000	Heat-resisting steels and alloys
G 7602:2000	Stainless steels for springs – Part 1: Wire
G 7603:2000	Valve steels for internal combustion engines
G 7604:2000	Nickel and nickel alloys bars
G 7605:2001	Nickel and nickel alloy plate, sheet and strip
G 7701:2000	Tool steels
G 7751:2000	Hot rolled steels for quenched and tempered springs
G 7821:2000	Cast carbon steels for general engineering purposes

4

JIS DISCONTINUED STEEL AND RELATED STANDARDS

476 JIS Discontinued Steel and Related Standards Appendix 4

Designation	Date Whitdrawn/Replaced by
JIS G 0301:1950	Withdrawn in: 1954-12-18
JIS G 0302:1956	Withdrawn in: 1966-11-01 Replaced by: G 1501;G 1511;G 1512;G1513
JIS G 0304:1951	Withdrawn in: 1957-10-30
JIS G 0305:1953	Withdrawn in: 1962-03-01
JIS G 0405:1950	Withdrawn in: 1959-12-01 Replaced by: G4801
JIS G 0406:1950	Withdrawn in: 1959-12-01 Replaced by: G4801
JIS G 0501:1952	Withdrawn in: 1955-02-12 Replaced by: G3421;G3422;G3423
JIS G 0502:1952	Withdrawn in: 1955-02-12 Replaced by: G3436;G3437;G3438
JIS G 0704:1977	Withdrawn in: 1980-03-01
JIS G 1202:1975	Withdrawn in: 1995-07-01 Replaced by: G1253
JIS G 1203:1977	Withdrawn in: 1986-06-01 Replaced by: Z2611
JIS G 1230:1969	Withdrawn in: 1982-09-01 Replaced by: G1257
JIS G 1231:1969	Withdrawn in: 1981-03-01 Replaced by: G1236;G1237
JIS G 1251:1976	
JIS G 1252:1975	Withdraws in 1000 00 04 Daylood by 01050
JIS G 1254:1976	Withdrawn in: 1986-06-01 Replaced by: G1256
JIS G 1255:1977 JIS G 1315:1974	Withdrawn in: 1986-06-01 Replaced by: G1256 Withdrawn in: 1983-11-01
	Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1511:1976 JIS G 1512:1976	Withdrawn in: 1986-02-01 Replaced by: G1601 Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1512.1976	Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1514:1976	Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1515:1976	Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1516:1976	Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1517:1975	Withdrawn in: 1985-03-01
JIS G 1518:1976	Withdrawn in: 1986-02-01 Replaced by: G1602
JIS G 1519:1975	Withdrawn in: 1986-02-01 Replaced by: G1602
JIS G 1520:1976	Withdrawn in: 1986-02-01 Replaced by: G1602
JIS G 1521:1975	Withdrawn in: 1986-02-01 Replaced by: G1602
JIS G 1522:1975	Withdrawn in: 1986-02-01 Replaced by: G1603
JIS G 1523:1975	Withdrawn in: 1986-02-01 Replaced by: G1603
JIS G 1524:1976	Withdrawn in: 1986-02-01 Replaced by: G1603
JIS G 1525:1975	Withdrawn in: 1986-02-01 Replaced by: G1603
JIS G 1526:1976	Withdrawn in: 1986-02-01 Replaced by: G1603
JIS G 1527:1976	Withdrawn in: 1986-02-01 Replaced by: G1601
JIS G 1528:1968	Withdrawn in: 1986-02-01 Replaced by: G1604
JIS G 1529:1975	Withdrawn in: 1985-03-01
JIS G 1530:1975	Withdrawn in: 1986-02-01 Replaced by: G1603
JIS G 1531:1975	Withdrawn in: 1986-02-01 Replaced by: G1602
JIS G 2201:1976	Withdrawn in: 2000-12-20
JIS G 2202:1976	Withdrawn in: 2000-12-20
JIS G 2203:1950 JIS G 2204:1950	Withdrawn in: 1953-11-07 Replaced by: G2201;G2202 Withdrawn in: 1953-11-07 Replaced by: G2201;G2202
JIS G 2205:1953	Withdrawn in: 1953-11-07 Replaced by: G2201;G2202 Withdrawn in: 1953-11-07 Replaced by: G2201;G2202
JIS G 2305:1969	Withdrawn in: 1978-12-01
JIS G 2317:1969	Withdrawn in: 1978-12-01
JIS G 3102:1964	Withdrawn in: 1965-07-01 Replaced by: G4051
JIS G 3107:1952	Withdrawn in: 1956-04-18 Replaced by: G3111
JIS G 3110:1953	Withdrawn in: 1965-03-01 Replaced by: G3112
JIS G 3115-1:1995 Part 1	Withdrawn in: 2000-06-20 Replaced by: JIS G 3115:2000
JIS G 3121:1951	Withdrawn in: 1955-02-12 Replaced by: G3123
JIS G 3122:1952	Withdrawn in: 1955-02-12 Replaced by: G3123
JIS G 3211:1977	Withdrawn in: 1982-07-01 Replaced by: G3202;G3203;G3204;G3205
JIS G 3212:1977	Withdrawn in: 1982-07-01 Replaced by: G3202;G3203;G3204;G3205
JIS G 3213:1977	Withdrawn in: 1982-07-01 Replaced by: G3202;G3203;G3204;G3205
JIS G 3301:1965	Withdrawn in: 1967-07-01 Replaced by: G3131
JIS G 3304:1950	Withdrawn in: 1956-07-17 Replaced by: G3301
JIS G 3305:1953	Withdrawn in: 1956-07-17 Replaced by: G3310
JIS G 3306:1954	Withdrawn in: 1956-07-17 Replaced by: G3310
JIS G 3307:1965	Withdrawn in: 1967-07-01 Replaced by: G3131
JIS G 3308:1957	Withdrawn in: 1969-08-06 Replaced by: G3141
JIS G 3309:1950	Withdrawn in: 1953-05-08
JIS G 3310:1965	Withdrawn in: 1969-08-06 Replaced by: G3141 Withdrawn in: 1988-10-01
JIS G 3391:1953	Williamit III. 1900-10-01

Designation	Date Whitdrawn/Replaced by
JIS G 3421:1951	Withdrawn in: 1955-02-12 Replaced by: G3432;G3433;G3434;G3435;G3436
JIS G 3422:1951	Withdrawn in: 1955-02-12 Replaced by: G3433
JIS G 3423:1951	Withdrawn in: 1955-02-12 Replaced by: G3435
JIS G 3424:1951	Withdrawn in: 1955-02-12 Replaced by: G3436
JIS G 3425:1951	Withdrawn in: 1955-02-12 Replaced by: G3437
JIS G 3426:1951	Withdrawn in: 1955-02-12 Replaced by: G3438
JIS G 3427:1951	Withdrawn in: 1955-02-12 Replaced by: G3432
JIS G 3428:1950	Withdrawn in: 1956-04-18 Replaced by: G3440
JIS G 3430:1952	Withdrawn in: 1957-10-30 Replaced by: G3443
JIS G 3431:1952	Withdrawn in: 1957-10-30 Replaced by: G3443
JIS G 3432:1958	Withdrawn in: 1962-03-01 Replaced by: G3452
JIS G 3433:1958	Withdrawn in: 1962-03-01 Replaced by: G3454;G3456
JIS G 3434:1958	Withdrawn in: 1962-03-01 Replaced by: G3455
JIS G 3435:1958	Withdrawn in: 1962-03-01 Replaced by: G3458;G3459
JIS G 3436:1958	Withdrawn in: 1962-03-01 Replaced by: G3461;G3462;G3463
JIS G 3437:1965	Withdrawn in: 1968-05-01
JIS G 3438:1958	Withdrawn in: 1962-03-01 Replaced by: G3459;G3461;G3462;G3463
JIS G 3439:1988	Withdrawn in: 1996-01-01
JIS G 3440:1956 JIS G 3501:1953	Withdrawn in: 1961-02-01 Replaced by: G3444;G3445 Withdrawn in: 1956-08-21 Replaced by: G3505;G3506
JIS G 3524:1953	Withdrawn in: 1956-08-21 Replaced by: G3505,G3506
JIS G 3524.1953 JIS G 3526:1962	Withdrawn in: 1980-03-01
JIS G 3520:1902 JIS G 3527:1951	Withdrawn in: 1980-03-01 Withdrawn in: 1954-01-30 Replaced by: G3532
JIS G 3528:1951	Withdrawn in: 1954-01-30 Replaced by: G3533
JIS G 3529:1951	Withdrawn in: 1954-01-30 Withdrawn in: 1954-01-30
JIS G 3530:1977	Withdrawn in: 1980-03-01
JIS G 3531:1977	Withdrawn in: 1980-03-01
JIS G 3534:1954	Withdrawn in: 1957-06-21 Replaced by: Z3201
JIS G 3534:1988	Withdrawn in: 1994-06-01
JIS G 3541:1988	Withdrawn in: 1992-02-01
JIS G 3565:1988	Withdrawn in: 1994-06-01
JIS G 3566:1988	Withdrawn in: 1994-06-01 Replaced by: G3561
JIS G 3567:1988	Withdrawn in: 1994-06-01 Replaced by: G3560
JIS G 3568:1989	Withdrawn in: 1994-06-01 Replaced by: G3560
JIS G 4102:1979	Withdrawn in: 2003-05-20 Replaced by: G 4053
JIS G 4103:1979	Withdrawn in: 2003-05-20 Replaced by: G 4053
JIS G 4104:1979	Withdrawn in: 2003-05-20 Replaced by: G 4053
JIS G 4105:1979	Withdrawn in: 2003-05-20 Replaced by: G 4053
JIS G 4106:1979	Withdrawn in: 2003-05-20 Replaced by: G 4053
JIS G 4201:1950	Withdrawn in: 1953-11-07 Replaced by: G3102;G4102;G4103;G4104;G4105
JIS G 4301:1955	Withdrawn in: 1959-12-01 Replaced by: G4303;G4304;G4305;G4306;G4307;G4308;G4309
JIS G 4302:1954	Withdrawn in: 1964-09-01 Replaced by: G4311;G4312
JIS G 4306:1988	Withdrawn in: 1991-11-01 Replaced by: G4304
JIS G 4307:1987	Withdrawn in: 1991-11-01 Replaced by: G4305
JIS G 4402:1953	Withdrawn in: 1956-04-18 Replaced by: G4404
JIS G 4405:1954	Withdrawn in: 1956-04-18
JIS G 4406:1954 JIS G 4407:1954	Withdrawn in: 1956-04-18
JIS G 4407:1954 JIS G 5521:1977	Withdrawn in: 1956-04-18 Replaced by: G4404 Withdrawn in: 1983-02-01
JIS G 5521:1977 JIS G 5522:1977	Withdrawn in: 1983-02-01 Withdrawn in: 1983-02-01
JIS G 5522:1977	Withdrawn in: 1983-02-01 Withdrawn in: 1983-02-01
JIS G 5523:1977	Withdrawn in: 1985-02-01 Withdrawn in: 1989-01-01
JIS G 5701:1952	Withdrawn in: 1969-01-01 Withdrawn in: 1960-03-01 Replaced by: G5702;G5703;G5704
JIS G 5702:1988	Withdrawn in: 1900-03-01 Neplaced by: d3702;d3703;d3704 Withdrawn in: 2000-02-20 Replaced by: JIS G 5705:2000
JIS G 5702:1988	Withdrawn in: 2000-02-20 Replaced by: JIS G 5705:2000
JIS G 5704:1988	Withdrawn in: 2000-02-20 Replaced by: JIS G 5705:2000
JIS G 9071:1976	Withdrawn in: 1992-02-01
JIS G 9072:1976	Withdrawn in: 1992-02-01

5

CEN CURRENT STEEL STANDARDS

480 CEN Current Steel Standards Appendix 5

Designation	Title	
EN ISO 683-17:1999	Heat-Treated Steels, Alloy Steels and Free-Cutting Steels – Ball and Roller Bearing Steels	
EN ISO 1127:1996	Stainless Steel Tubes – Dimensions, Tolerances and Conventional Masses per Unit Length	
EN ISO 4066:1999	Construction Drawings – Bar Scheduling	
EN ISO 4000:1999 EN ISO 4957:1999		
EN ISO 7153-1:2000	Tool Steels Surgical Instruments. Metallic Materials – Part 1: Stainless Steel	
EN ISO 11960:2001	Petroleum and Natural Gas Industries – Steel Pipes for Use as Casing or Tubing for Wells	
	1 0	
EN 502:1999	Roofing Products from Metal Sheet – Specification for Fully Supported Products of Stainless Steel Sheet	
EN 505:1999	Roofing Products from Metal Sheet – Specification for Fully Supported Roofing Products of Steel Sheet Roofing Products from Metal Sheet v Specification for Self-Supporting Products of Steel, Aluminum or Stainless Steel	
EN 508-1:2000	Sheet – Part 1: Steel	
EN 523:2003	Steel Strip Sheaths for Prestressing Tendons – Terminology, Requirements, Quality Control	
EN 524-1:1997	Steel Strip Sheaths for Prestressing Tendons – Test Methods – Part 1:Determination of Shape and Dimensions	
EN 524-2:1997	Steel Strip Sheaths for Prestressing Tendons – Test Methods – Part 2: Determination of Flexural Behaviour	
EN 524-3:1997	Steel Strip Sheaths for Prestressing Tendons – Test Methods – Part 2: To-and-Fro Bending Test	
EN 524-4:1997	Steel Strip Sheaths for Prestressing Tendons – Test Methods – Part 2: Determination of Lateral Load Resistance	
EN 524-5:1997	Steel Strip Sheaths for Prestressing Tendons – Test Methods – Part 2: Determination of Tensile Load Resistance	
EN 524-6:1997	Steel Strip Sheaths for Prestressing Tendons – Test Methods – Part 2: Determination of Leaktightness (Determination of Water Loss)	
EN 1123-1:1999	Pipes and Fittings of Longitudinally Welded Hot-Dip Galvanized Steel Pipes with Spigot and Socket for Waste Water Systems – Part 1: Requirements, Testing, Quality Control	
EN 1123-2:1999	Pipes and Fittings of Longitudinally Welded Hot-Dip Galvanized Steel Pipes with Spigot and Socket for Waste Water Systems – Part 2: Dimensions	
EN 1124-1:1999	Pipes and Fittings of Longitudinally Welded Stainless Steel Pipes with Spigot and Socket for Waste Water Systems – Part 1: Requirements, Testing, Quality Control	
EN 1124-2:1999	Pipes and Fittings of Longitudinally Welded Stainless Steel Pipes with Spigot and Socket for Waste Water Systems – Part 2: System S. Dimensions	
EN 1124-3:1999	Pipes and Fittings of Longitudinally Welded Stainless Steel Pipes with Spigot and Socket for Waste Water Systems – Part 3: System X; Dimensions	
EN 1370:1996	Founding. Surface Roughness Inspection by Visual Tactile Comparators	
EN 1503-1:2000	Valves. Materials for Bodies, Bonnets and Covers – Part 1: Steels Specified in European Standards	
EN 1503-2:2000	Valves. Materials for Bodies, Bonnets and Covers – Part 2: Steels Other Than Those Specified in European Standards	
EN 1559-2:2000	Founding. Technical Conditions of Delivery – Part 2: Additional Requirements for Steel Castings	
EN 1677-1:2000	Components for Slings – Safety – Part 1: Safety. Forged Steel Components, Grade 8	
EN 1677-2:2000	Components for Slings – Safety – Part 2: Forged Steel Lifting Hooks with Latch, Grade 8	
EN 10016-1:1994	Non-Alloy Steel Rods for Drawing and/or Cold Rolling – Part 1: General Requirements	
EN 10016-2:1994	Non-Alloy Steel Rods for Drawing and/or Cold Rolling – Part 2: Specific Requirements for General Purpose Rod	
LIN 10010-2.1994	Non-Alloy Steel Rods for Drawing and/or Cold Rolling – Part 2: Specific Requirements for Rimmed and Rimmed	
EN 10016-3:1994	Substitute Low Carbon Steel Rod	
EN 10016-4:1994	Non-Alloy Steel Rods for Drawing and/or Cold Rolling – Part 4: Specific Requirements for Rod for Special Applications	
EN 10024:1995	Hot Rolled Taper Flange I Sections – Tolerances On Shape and Dimensions	
EN 10025:1990	Iron and Steel Products, Structural Steels, Non Alloy Steel, Hot Rolled Products, Quality Classes, Designation, Specification, Chemical Composition, Mechanical Property, Mechanical Test, Inspection, Marking	
EN 10028-1:2000	Flat Products Made of Steels for Pressure Purposes – Part 1: General Requirements	
EN 10028-2:2003	Flat products Made of Steels for Pressure Purposes – Part 2: Non-Alloy and Alloy Steels with Specified Elevated Temperature Properties	
EN 10028-3:2003	Flat Products Made of Steels for Pressure Purposes – Part 3: Weldable Fine Grain Steels, Normalized	
EN 10028-4:2003	Flat Products Made of Steels for Pressure Purposes – Part 4: Nickel alloy Steels with Specified Low Temperature Properties	
EN 10028-5:2003	Flat Products Made of Steels for Pressure Purposes – Part 5: Weldable Fine Grain Steels, Thermomechanically Rolled	
EN 10028-6:2003	Flat Products Made of Steels for Pressure Purposes – Part 6: Weldable Fine Grain Steels, Quenched and Tempered	
EN 10028-7:2000	Flat Products Made of Steels for Pressure Purposes – Part 7: Stainless Steels	
EN 10029:1991	Hot Rolled Steel Plates 3 mm Thick or Above – Tolerances on Dimensions, Shape and Mass	
EN 10034:1993	Structural Steel I and H Sections – Tolerances On Shape and Dimensions	
EN 10034:1995 EN 10048:1996	Hot Rolled Narrow Steel Strip – Tolerances On Dimensions and Shape	
LIV 10070.1330		
EN 10051:1991	Continuously Hot-Rolled Uncoated Plate, Sheet and Strip of Non-Alloy and Alloy Steels – Tolerances On Dimensions and Shape	

Decimation	Title	
Designation	Title Ctrustural Ctast Faust and Unagual Lag Angles - Port 1: Dimensions	
EN 10056-1:1998	Structural Steel Equal and Unequal Leg Angles – Part 1: Dimensions	
EN 10056-2:1993	Structural Steel Equal and Unequal Leg Angles – Part 2: Tolerances on Shape and Dimensions Het Belled Bulb Elete - Dimensions and Tolerances On Shape - Dimensions and Mass	
EN 10067:1996	Hot Rolled Bulb Flats – Dimensions and Tolerances On Shape, Dimensions and Mass	
EN 10079:1992	Definition of Steel Products Overshad and Tempered Steels - Part 1: Technical Politicans Conditions for Special Steels	
EN 10083-1:1991	Quenched and Tempered Steels – Part 1: Technical Delivery Conditions for Special Steels	
EN 10083-2:1991	Quenched and Tempered Steels – Part 2: Technical Delivery Conditions for Unalloyed Quality Steels	
EN 10083-3:1995	Quenched and Tempered Steels – Part 3: Technical Delivery Conditions for Boron Steels	
EN 10084:1998	Case Hardening Steels – Technical Delivery Conditions	
EN 10085:2001	Nitriding Steel – Technical Delivery Conditions	
EN 10087:1998	Free Cutting Steels. Technical Delivery Conditions for Semi-Finished Products, Hot Rolled Bars and Rods	
EN 10088-1:1995	Stainless Steels – Part 1: List of Stainless Steels	
EN 10088-2:1995	Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purposes Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rods and Sections for	
EN 10088-3:1995	General Purposes	
EN 10090:1998	Valve Steels and Alloys for Internal Combustion Engines	
EN 10095:1999	Heat Resisting Steels and Nickel Alloys	
EN 10106:1995	Cold Rolled Non-Oriented Electrical Steel Sheet and Strip Delivered in the Fully Processed State	
EN 10107:1995	Grain-Oriented Electrical Steel Sheet and Strip Delivered in the Fully Processed State	
EN 10111:1998	Continuously Hot-Rolled Low Carbon Steel Sheet and Strip for Cold Forming – Technical Delivery Conditions	
EN 10113-1:1993	Hot-Rolled Products in Weldable Fine Grain Structural Steels – Part 1: General Delivery Conditions	
	Hot-Rolled Products in Weldable Fine Grain Structural Steels – Part 2: Delivery Conditions for Normalized/Normalized	
EN 10113-2:1993	Rolled Steels	
EN 10113-3:1993	Hot-Rolled Products in Weldable Fine Grain Structural Steels – Part 3: Delivery Conditions for Thermomechanical	
	Rolled Steels	
EN 10120:1996	Steel Sheet and Strip for Welded Gas Cylinders	
EN 10126:1995	Cold Rolled Electrical Non-Alloyed Steel Sheet and Strip Delivered in the Semi-Processed State	
EN 10130:1998	Cold-Rolled Low-Carbon Steel Flat Products for Cold Forming – Technical Delivery Conditions	
EN 10131:1991	Cold-Rolled Uncoated Low Carbon and High Yield Strength Steel Flat Products for Cold Forming – Tolerances On Dimensions and Shape	
EN 10132-1:2000	Cold Rolled Narrow Steel Strip for Heat Treatment. Technical Delivery Conditions – Part 1: General	
EN 10132-2:2000	Cold Rolled Narrow Steel Strip for Heat Treatment. Technical Delivery Conditions – Part 2: Case Hardening Steels	
EN 10132-3:2000	Cold Rolled Narrow Steel Strip for Heat Treatment. Technical Delivery Conditions – Part 3: Steels for Quenching and Tempering	
EN 10132-4:2000	Cold Rolled Narrow Steel Strip for Heat Treatment. Technical Delivery Conditions – Part 4: Spring Steels and Other Applications	
EN 10137-1:1995	Plates and Wide Flats Made of High Yield Strength Structural Steels in the Quenched and Tempered or Precipitation Hardened Conditions – Part 1: General Delivery Conditions	
EN 10137-2:1995	Plates and Wide Flats Made of High Yield Strength Structural Steels in the Quenched and Tempered or Precipitation Hardened Conditions – Part 2: Delivery Conditions for Quenched and Tempered Steels	
EN 10137-3:1995	Plates and Wide Flats Made of High Yield Strength Structural Steels in the Quenched and Tempered or Precipitation	
EN 10139:1997	Hardened Conditions – Part 3: Delivery Conditions for Precipitation Hardened Steels Cold Rolled Uncoated Mild Steel Narrow Strip for Cold Forming – Technical Delivery Conditions	
EN 10139.1997 EN 10140:1996	Cold Rolled Narrow Steel Strip – Tolerances On Dimensions and Shape	
	Continuously Hot-Dip Zinc Coated Low Carbon Steels Strip and Sheet for Cold Forming – Technical Delivery	
EN 10142:2000	Conditions	
EN 10143:1993	Continuously Hot-Dip Metal Coated Steel Sheet and Strip – Tolerances On Dimensions and Shape	
EN 10147:2000	Continuously Hot-Dip Zinc Coated Structural Steels Strip and Sheet – Technical Delivery Conditions	
EN 10149-1:1995	Specification for Hot-Rolled Flat Products Made of High Yield Strength Steels for Cold Forming – Part 1: General Delivery Conditions	
EN 10149-2:1995	Specification for Hot-Rolled Flat Products Made of High Yield Strength Steels for Cold Forming – Part 2: Delivery Conditions for Thermomechanically Rolled Steels	
EN 10149-3:1995	Specification for Hot-Rolled Flat Products Made of High Yield Strength Steels for Cold Forming – Part 3: Delivery Conditions for Normalized or Normalized Rolled Steels	
EN 10152:2003	Electrolytically Zinc Coated Cold Rolled Steel Flat Products for Cold Forming – Technical Delivery Conditions	
EN 10154:2002	Continuously Hot-Dip Aluminium-Silicon (AS) Coated Steel Strip and Sheet – Technical Delivery Conditions	
EN 10155:1993	Structural Steels with Improved Atmospheric Corrosion Resistance – Technical Delivery Conditions	
EN 10160:1999	Ultrasonic Testing of Steel Flat Product of Thickness Equal or Greater Than 6 Mm (Reflection Method)	
	Specification for Delivery Requirements for Surface Condition of Hot Rolled Steel Plates, Wide Flats and Sections –	
EN 10163-1:1991	Part 1: General Requirements	

482 CEN Current Steel Standards Appendix 5

Designation	Title	
EN 10163-2:1991	Specification for Delivery Requirements for Surface Condition of Hot Rolled Steel Plates, Wide Flats and Sections – Part 2: Plates and Wide Flats	
EN 10163-3:1991	Specification for Delivery Requirements for Surface Condition of Hot Rolled Steel Plates, Wide Flats and Sections – Part 3: Sections	
EN 10164:1993	Steel Products with Improved Deformation Properties Perpendicular To the Surface of the Product – Technical Delivery Conditions	
EN 10165:1995	Cold Rolled Electrical Alloyed Steel Sheet and Strip Delivered in the Semi-Processed State	
EN 10169-1:1997	Continuously Organic Coated (Coil Coated) Steel Flat Products – Part 1: General Information (Definitions, Materials, Tolerances, Test Methods)	
EN 10202:2001	Cold Reduced Tinmill Products – Electrolytic Tinplate and Electrolytic Chromium/Chromium Oxide Coated Steel	
EN 10204:1991	Metallic Products. Types of Inspection Documents	
EN 10205:1991	Cold Reduced Blackplate in Coil Form for the Production of Tinplate or Electrolytic Chromium/Chromium Oxide Coated Steel	
EN 10207:1992	Steels for Simple Pressure Vessels – Technical Delivery Requirements for Plates, Strips and Bars	
EN 10208-1:1997	Steel Pipes for Pipelines for Combustible Fluids – Technical Delivery Conditions – Part 1: Pipes of Requirement Class A	
EN 10208-2:1996	Steel Pipes for Pipelines for Combustible Fluids – Technical Delivery Conditions – Part 2: Pipes of Requirement Class B	
EN 10209:1996	Cold Rolled Low Carbon Steel Flat Products for Vitreous Enamelling – Technical Delivery Conditions	
EN 10210-1:1994	Hot Finished Structural Hollow Sections of Non-Alloy and Fine Grain Structural Steels – Part 1: Technical Delivery Requirements	
EN 10210-2:1997	Hot Finished Structural Hollow Sections of Non-Alloy and Fine Grain Structural Steels – Part 2: Tolerances, Dimensions and Sectional Properties	
EN 10213-1:1995	Technical Delivery Conditions for Steel Castings for Pressure Purposes – Part 1: General	
EN 10213-2:1995	Technical Delivery Conditions for Steel Castings for Pressure Purposes – Part 2: Steel Grades for Use at Room Temperature and at Elevated Temperature	
EN 10213-3:1995	Technical Delivery Conditions for Steel Castings for Pressure Purposes – Part 3: Steels for Use at Low Temperatures	
EN 10213-4:1995	Technical Delivery Conditions for Steel Castings for Pressure Purposes – Part 4: Austenitic and Austenitic-Ferritic Steel Grades	
EN 10214:1995	Continuously Hot-Dip Zinc-Aluminium (ZA) Coated Steel Strip and Sheet – Technical Delivery Conditions	
EN 10215:1995	Continuously Hot-Dip Zinc-Aluminium (AZ) Coated Steel Strip and Sheet – Technical Delivery Conditions	
EN 10218-1:1994	Steel Wire and Wire Products – General – Part 1: Test Methods	
EN 10218-2:1997	Steel Wire and Wire Products – General – Part 2: Wire Dimensions and Tolerances	
EN 10219-1:1997	Cold Formed Welded Structural Sections of Non-Alloy and Fine Grain Steels – Part 1: Technical Delivery Requirements	
EN 10219-2:1997	Cold Formed Welded Structural Sections of Non-Alloy and Fine Grain Steels – Part 2: Tolerances, Dimensions and Sectional Properties	
EN 10221:1995	Surface Quality Classes for Hot-Rolled Bars and Rods – Technical Delivery Conditions	
EN 10222-1:2002	Steel Forgings for Pressure Purposes – Part 1: General Requirements for Open Die Forgings	
EN 10222-2:1999	Steel Forgings for Pressure Purposes – Part 2: Ferritic and Martensitic Steels with Specified Elevated Temperature Properties	
EN 10222-3:1998	Steel Forgings for Pressure Purposes – Part 3: Nickel Steels with Specified Low-Temperature Properties	
EN 10222-4:1998	Steel Forgings for Pressure Purposes – Part 4: Weldable Fine-Grain Steels with High Proof Strength	
EN 10222-5:1999	Steel Forgings for Pressure Purposes – Part 5: Martensitic, Austenitic and Austenitic-Ferritic Stainless Steels	
EN 10223-1:1997	Steel Wire and Wire Products for Fences – Part 1: Zinc and Zinc Alloy Coated Steel Barbed Wire	
EN 10223-2:1997	Steel Wire and Wire Products for Fences – Part 2: Hexagonal Steel Wire Netting for Agricultural, Insulation and Fencing Purposes	
EN 10223-3:1997	Steel Wire and Wire Products for Fences – Part 3: Hexagonal Steel Wire Netting for Engineering Purposes	
EN 10223-4:1998	Steel Wire and Wire Products for Fences – Part 4: Steel Wire Welded Mesh Fencing	
EN 10223-5:1998	Steel Wire and Wire Products for Fences – Part 5: Steel Wire Woven Hinged Joint and Knotted Mesh Fencing	
EN 10223-6:1998	Steel Wire and Wire Products for Fences – Part 6: Steel Wire Chain Link Fencing	
EN 10228-1:1999	Non-Destructive Testing of Steel Forgings – Part 1: Magnetic Particle Inspection	
EN 10228-2:1998	Non-Destructive Testing of Steel Forgings – Part 2: Penetrant Testing	
EN 10228-3:1998	Non-Destructive Testing of Steel Forgings – Part 3: Ultrasonic Testing of Ferritic or Martensitic Steel Forgings	
EN 10228-4:1999	Non-Destructive Testing of Steel Forgings – Part 4: Ultrasonic Testing of Austenitic and Austenitic-Ferritic Stainless Steel Forgings	
EN 10238:1996	Automatically Blast Cleaned and Automatically Primed Structural Steel Products	
EN 10240:1997	Internal and/or External Protective Coatings for Steel Tubes – Specification for Hot Dip Galvanized Coatings Applied in Automatic Plants	
EN 10241:2000	Steel Threaded Pipe Fittings	
EN 10243-1:1999	Steel Die Forgings. Tolerances On Dimensions – Part 1: Drop and Vertical Press Forgings	

EN 10244-1:2001 S EN 10244-2:2001 S	Steel Die Forgings. Tolerances On Dimensions – Part 2: Upset Forgings Made On Horizontal Forging Machines Steel Wire and Wire Products – Non-Ferrous Metallic Coatings On Steel Wire – Part 1: General Principles	
EN 10244-1:2001 S EN 10244-2:2001 S		
EN 10244-2:2001 S	oteer while and while products - inon-perious inetailic Coathigs Off Steer while - Part 1. General Philophes	
	Steel Wire and Wire Products - Non-Ferrous Metallic Coatings On Steel Wire - Part 2: Zinc or Zinc Alloy Coatings	
EN 10244-3:2001 S	Steel Wire and Wire Products – Non-Ferrous Metallic Coatings On Steel Wire – Part 3: Aluminium Coatings	
	Steel Wire and Wire Products - Non-Ferrous Metallic Coatings On Steel Wire - Part 4: Tin Coatings	
	Steel Wire and Wire Products - Non-Ferrous Metallic Coatings On Steel Wire - Part 5: Nickel Coatings	
FN 10244-6:2001	Steel Wire and Wire Products – Non-Ferrous Metallic Coatings On Steel Wire – Part 6: Copper, Bronze or Brass Coatings	
	Steel Wire and Wire Products - Organic Coatings On Steel Wire - Part 1: General Rules	
	Steel Wire and Wire Products - Organic Coatings On Steel Wire - Part 1: PVC Finished Wire	
	Steel Wire and Wire Products - Organic Coatings On Steel Wire - Part 1: PE Coated Wire	
EN 10246-1:1006	Non-Destructive Testing of Steel Tubes – Part 1: Automatic Electromagnetic Testing of Seamless and Welded Except Submerged Arc Welded) Ferromagnetic Steel Tubes for Verification of Hydraulic Leak-Tightness	
	Non-Destructive Testing of Steel Tubes – Part 2: Automatic Eddy Current Testing of Seamless and Welded (Except Submerged Arc Welded) Austenitic and Austenitic-Ferritic Steel Tubes for Verification of Hydraulic Leak-Tightness	
EN 10246-3:1999 N	Non-Destructive Testing of Steel Tubes – Part 3: Automatic Eddy Current Testing of Seamless and Welded (Except Submerged Arc-Welded) Steel Tubes for the Detection of Imperfections	
EN 10246-4:1999 T	Non-Destructive Testing of Steel Tubes – Part 4: Automatic Full Peripheral Magnetic Transducer/Flux Leakage Festing of Seamless Ferromagnetic Steel Tubes for the Detection of Transverse Imperfections	
EN 10246-5:1999 To	Non-Destructive Testing of Steel Tubes – Part 5: Automatic Full Peripheral Magnetic Transducer/Flux Leakage Festing of Seamless and Welded (Except Submerged Arc-Welded) Ferromagnetic Steel Tubes for the Detection of Longitudinal Imperfections	
EN 10246-6:1999 T	Non-Destructive Testing of Steel Tubes – Part 6: Automatic Full Peripheral Ultrasonic Testing of Seamless Steel Fubes for the Detection of Transverse Imperfections	
EN 10246-7:1996	Non-Destructive Testing of Steel Tubes – Part 7: Automatic Full Peripheral Ultrasonic Testing of Seamless and Welded (Except Submerged Arc Welded) Steel Tubes for the Detection of Longitudinal Imperfections	
EN 10246-8.1999 S	Non-Destructive Testing of Steel Tubes – Part 8: Automatic Ultrasonic Testing of the Weld Seam of Electric Welded Steel Tubes for the Detection of Longitudinal Imperfections	
EN 10246-9:2000 N	Non-Destructive Testing of Steel Tubes – Part 9: Automatic Ultrasonic Testing of the Weld Seam of Submerged Arc Welded Steel Tubes for the Detection of Longitudinal and/or Transverse Imperfections	
EN 10246-10.2000 N	Non-Destructive Testing of Steel Tubes – Part 10: Radiographic Testing of the Weld Seam of Automatic Fusion Arc Nelded Steel Tubes for the Detection of Imperfections	
EN 10246-11:2000 th	Non-Destructive Testing of Steel Tubes – Part 11: Liquid Penetrant Testing of Seamless and Welded Steel Tubes for the Detection of Surface Imperfections	
EN 10246-12:2000 F	Non-Destructive Testing of Steel Tubes – Part 12: Magnetic Particle Inspection of Seamless and Welded Ferromagnetic Steel Tubes for the Detection of Surface Imperfections	
EN 10246-13.2000 S	Non-Destructive Testing of Steel Tubes – Part 13: Automatic Full Peripheral Ultrasonic Thickness Testing for Seamless and Welded (Except Submerged Arc Welded) Steel Tubes	
EN 10246-14:1999 S	Non-Destructive Testing of Steel Tubes – Part 14: Automatic Ultrasonic Testing of Seamless and Welded (Except Submerged Arc-Welded) Steel Tubes for the Detection of Laminar Imperfections	
EN 10246-15:2000 M	Non-Destructive Testing of Steel Tubes – Part 15: Automatic Ultrasonic Testing of Strip/Plate Used in the Manufacture of Welded Steel Tubes for the Detection of Laminar Imperfections	
EN 10246-16:2000 S	Non-Destructive Testing of Steel Tubes – Part 16: Automatic Ultrasonic Testing of the Area Adjacent To the Weld Seam of Welded Steel Tubes for the Detection of Laminar Imperfections	
EN 10246-17:2000 T	Non-Destructive Testing of Steel Tubes – Part 17: Ultrasonic Testing of Tube Ends of Seamless and Welded Steel Tubes for the Detection of Laminar Imperfections	
EN 10240-18:2000 W	Non-Destructive Testing of Steel Tubes – Part 18: Magnetic Particle Inspection of Tube Ends of Seamless and Nelded Ferromagnetic Steel Tubes for the Detection of Laminar Imperfections	
	Hot Rolled Sheet Piling of Non Alloy Steels – Part 1: Technical Delivery Conditions	
	Hot Rolled Sheet Piling of Non Alloy Steels – Part 2: Tolerances On Shape and Dimensions	
	Cold Formed Sheet Piling of Non Alloy Steels – Part 1: Technical Delivery Conditions	
	Cold Formed Sheet Piling of Non Alloy Steels – Part 2: Tolerances On Shape and Dimensions	
	Open Steel Die Forgings for General Engineering Purposes – Part 1: General Requirements	
	Open Steel Die Forgings for General Engineering Purposes – Part 2: Non-Alloy Quality and Special Steels	
	Open Steel Die Forgings for General Engineering Purposes – Part 3: Alloy Special Steels	
	Open Steel Die Forgings for General Engineering Purposes – Part 4: Stainless Steels	
	Magnetic Materials – Methods of Determination of the Geometrical Characteristics of Electrical Steel Sheet and Strip	
EN 10252:1997	Magnetic Materials – Methods of Measurement of Magnetic Properties of Magnetic Steel Sheet and Strip at Medium Frequencies	
EN 10255-1.1999 R	Butt-Welding Pipe Fittings – Part 1: Wrought Carbon Steel for General Use and Without Specific Inspection Requirements	
EN 10254:1999 S	Steel Closed Die Forgings – General Technical Delivery Conditions	

484 CEN Current Steel Standards Appendix 5

Designation	Title		
EN 10256:2000	Non-Destructive Testing On Steel Tubes – Qualification and Competence of Level 1 and Level 2 Non-Destructive Testing Personnel		
EN 10257-1:1998	Zinc or Zinc Alloy Coated Non-Alloy Steel Wire for Armouring Either Power Cables or Telecommunication Cables – Part 1: Land Cables		
EN 10257-2:1998	Zinc or Zinc Alloy Coated Non-Alloy Steel Wire for Armouring Either Power Cables or Telecommunication Cables – Part 2: Submarine Cables		
EN 10258:1997	Cold-Rolled Stainless Steel Narrow Strip and Cut Lengths – Part 1: Tolerances On Dimensions and Shape		
EN 10259:1997	Cold-Rolled Stainless and Heat Resisting Steel Wide Strip and Plate/Sheet – Tolerances On Dimensions and Shape		
EN 10267:1998	Ferritic-Pearlitic Steels for Precipitation Hardening from Hot-Working Temperatures		
EN 10268:1998	Cold-Rolled Flat Products Made of High Yield Strength Micro-Alloyed Steels for Cold Forming – General Delivery Conditions		
EN 10269:1999	Steels and Nickel Alloys for Fasteners with Specified Elevated and/or Low Temperature Properties		
EN 10270-1:2001	Steel Wire for Mechanical Springs - Part 1: Patented Cold Drawn Unalloyed Spring Steel Wire		
EN 10270-2:2001	Steel Wire for Mechanical Springs – Part 2: Oil Hardened and Tempered Spring Steel Wire		
EN 10270-3:2001	Steel Wire for Mechanical Springs – Part 3: Stainless Spring Steel Wire		
EN 10271:1998	Electrolytically Zinc-Nickel (ZN) Coated Steel Flat Products – Technical Delivery Conditions		
EN 10272:2000	Stainless Steel Bars for Pressure Purposes		
EN 10273:2000	Hot Rolled Weldable Steel Bars for Pressure Purposes with Specified Elevated Temperature Properties		
EN 10277-1:1999	Bright Steel Products – Part 1: Technical Delivery Conditions. General		
EN 10277-2:1999	Bright Steel Products – Part 2: Technical Delivery Conditions. Steels for General Engineering Purposes		
EN 10277-3:1999	Bright Steel Products – Part 3: Technical Delivery Conditions. Free Cutting Steels		
EN 10277-4:1999	Bright Steel Products – Part 4: Technical Delivery Conditions. Case-Hardening Steels		
EN 10277-5:1999	Bright Steel Products – Part 5: Technical Delivery Conditions. Steels for Quenching and Tempering		
EN 10278:1999	Dimensions and Tolerances of Bright Steel Products		
EN 10279:2000	Hot Rolled Steel Channels - Tolerances On Shape, Dimension and Mass		
EN 10283:1998	Corrosion Resistant Steel Castings		
EN 10292:2000	Continuously Hot-Dip Coated Strip and Sheet of Steels with Higher Yield Strength for Cold Forming – Technical Delivery Conditions		
EN 10303:2001	Thin Magnetic Steel Sheet and Strip for Use at Medium Frequencies		
EN 12007-3:2000	Gas Supply Systems – Pipelines for Maximum Operating Pressure Up To and Including 16 Bar – Part 3: Specific Functional Recommendations for Steel		
EN 12269-1:2000	Determination of the Bond Behaviour Between Reinforcing Steel and Autoclaved Aerated Concrete by the "Beam Test" – Part 1: Short Term Test		
EN 12454:1998	Founding – Visual Examination of Surface Discontinuities – Steel Sand Castings		
EN 10142:1990	Continuously Hot-Dip Zinc Coated Low Carbon Steel Sheet and Strip for Cold Forming – Technical Delivery Conditions		
EN 10147:1991	Continuously Hot-Dip Zinc Coated Structural Steel Sheet and Strip – Technical Delivery Conditions		
EN 10202:2001	Cold Reduced Tinmill Products – Electrolytic Tinplate and Electrolytic Chromium/Chromium Oxide Coated Steel		

6

CEN STANDARDS WITH SUPERSEDED FORMER NATIONAL STANDARDS

486 CEN Standards With Superseded Former National Standards Appendix 6

Chapter 2: Carbon and Alloy Steels for General Use		
Current CEN Standard	Former National Standards Superseded by CEN Standards	
EN 10083–1:1991+A1:1996 Quenched and Tempered Steels – Part 1: Technical Delivery Conditions for Special Steels	Supersedes: BSI BS 970-1:1983 Wrought Steels for Mechanical and Allied	
EN 10083–2:1991+A1:1996 Quenched and Tempered Steels – Part 2: Technical Delivery Conditions for Unalloyed Quality Steels	Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels	
EN 10084:1998 Case Hardening Steels – Technical Delivery Conditions	Supersedes: BSI BS 970-1:1996 Wrought Steels for Mechanical and Allied engineering Purposes – Part 1: General Inspection And Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels	
EN 10016-1:1995 Non-Alloy Steel Rod for Drawing or Cold Rolling – Part 1: General Requirements EN 10016-2:1995 Non-Alloy Steel Rod for Drawing or Cold Rolling; – Part 2: Specific Requirements for General Purpose Rod	Supersedes: DIN 17140-1:1983 Wire Rod for Cold Drawing – Technical Delivery Conditions for Basic Steel and Unalloyed Quality Steels	
EN 10016-2:1995 Non-Alloy Steel Rod for Drawing and/or Cold Rolling – Part 2: Specific Requirements for General Purposes Rod.	Supersedes: AFNOR NF A35-051:1982 Fil Machine en Acier Non Allié Destiné au Tréfilage et au Laminage à Froid – Nuances	
EN 10083-1:1991 Quenched And Tempered Steels – Part 1: Technical Delivery Conditions For Specials Steels.	Supersedes: AFNOR NF EN 10083-1:1991 Aciers pour Trempe et Revenu – Partie 1: Conditions Techniques de Livraison des Aciers Spéciaux	
EN 10083-2:1991 Quenched And Tempered Steels – Part 2: Technical Delivery Conditions For Unalloyed Quality Steels.	Supersedes: AFNOR NF EN 10083-2:1991 Aciers pour Trempe et Revenu – Partie 2: Conditions Techniques de Livraison des Aciers de Qualité Non Alliés AFNOR NF A33-101:1982 Aciers au Carbone de Qualité Aptes au Forgeage et aux Traitements Thermiques – Demi Produits, Barres et Fil Machine	
EN 10084:1998 Case Hardening Steels – Technical Delivery Conditions	Supersedes: AFNOR NF A35-551:1986 Aciers de Construction Non Alliés et Alliés Spéciaux pour Cémentation – Nuances - Demi-Produits, Barres et Fils Machine	

Chapter 3: Structural Steel Plates		
Current CEN Standards	Former National Standards Superseded by CEN Standards	
EN 10025:1993 Hot Rolled Products of Non-Alloy Structural Steels – Technical Delivery Conditions	Supersedes: BSI BS 4360:1986 Weldable Structural Steels (Withdrawn)	
EN 10113 Hot-Rolled Products in Weldable Fine Grain Structural Steels	Supersedes:	
EN 10113-1:1993 General Delivery Conditions	BSI BS 4360:1990 Weldable Structural Steels (Withdrawn)	
EN 10113-2:1993 Delivery Conditions for Normalized/Normalized Rolled Steels		
EN 10113-3:1993 Delivery Conditions for Thermomechanical Rolled Steels		
EN 10155:1993 Structural Steels with Improved Atmospheric Corrosion Resistance – Technical Delivery Conditions		
EN 10137 Plates and Wide Flats Made of High Yield Strength	Supersedes:	
Structural Steels in the Quenched and Tempered or Precipitation Hardened Conditions	BSI BS 7613:1994 Hot Rolled Quenched and Tempered Weldable Structural Steel Plates (Withdrawn)	
EN 10137-1:1996 General Delivery Conditions		
EN 10137-2:1996 Delivery Conditions for Quenched and Tempered Steels		
EN 10137-3:1996 Delivery Conditions for Precipitation Hardened Steels		
	Supersedes:	
EN 10025:1993 Hot Rolled Products of Non-Alloy Structural Steels - Technical Delivery Conditions	DIN 17100:1980 Steels for General Structural Purposes; Quality Standard (Withdrawn)	
EN 10113 Hot Rolled Products Made from Weldable, Fine Grain Structural Steel;	Supersedes:	
EN 10113-1:1993 General Technical Delivery Conditions	DIN 17102:1983 Weldable Normalized Fine Grain Structural Steels; Technical Delivery Conditions for Plate, Strip, Wide Flats, Sections and Bars (Withdrawn)	
EN 10113-2:1993 Delivery Conditions for Normalized/Normalized Rolled Steels		
EN 10028 Flat Products Made from Steel for Pressure Purposes		
EN 10028-1:2000 General Requirements		
EN 10028-3:2003 Weldable Fine Grain Steels, Normalized	Supercodes :	
EN 40440 II - B	Supersedes:	
EN 10113 Hot-Rolled Products in Weldable Fine Grain Structural Steels	AFNOR NF A 35-504:1984 Poutrelles et Profils en Aciers à Haute Limite d'Élasticité pour Constructions Soudées – Nuances et	
EN 10113-2:1993 Delivery Conditions for Normalized/Normalized	Qualités	
Rolled Steels.	AFNOR NF A 36-201:1984 Tôles en Aciers à Haute Limite d'Élasticité pour Constructions Soudées – Nuances et Qualités	

488 CEN Standards With Superseded Former National Standards Appendix 6

Chapter 3: Structural Steel Plates (Continued)		
Current CEN Standards	Former National Standards Superseded by CEN Standards	
EN 10137 Plates and Wide Flats Made of High Yield Strength	Supersedes:	
Structural Steels in the Quenched and Tempered or Precipitation		
Hardened Conditions	AFNOR NF A 36-204:1992 Produits Sidérurgiques – Tôles en Aciers	
	à Haute Limite d'Élasticité Livrées à l'État Traité pour Construction	
EN 10137-2:1996 Delivery Conditions for Quenched and Tempered	Soudée – Nuances et Qualité	
Steels		
EN 10137-3:1996 Delivery Conditions for Precipitation Hardened		
Steels		
	Supersedes:	
EN 10155 :1993 Structural Steels With Improved Atmospheric		
Corrosion Resistance – Technical Delivery Conditions	AFNOR NF A35-502 :1984 Aciers de Construction à Résistance	
Corrosion resistance – reclinical Delivery Conditions	Améliorée à la Corrosion Atmosphérique – Tôles Minces Moyennes	
	et Fortes, Larges Plats, Laminés Marchands et Poutrelles	

Chapter 4: Pressure Vessel Steel Plates	
Current CEN Standard	Former National Standards Superseded by CEN Standards
	Supersedes:
EN 10028 Flat Products Made of Steels for Pressure Purposes.	
EN 40000 0 0000 N AU LAU 01 L 11 0 16 L	BSI BS 1501 Steels for Pressure Purposes.
EN 10028-2 :2003 Non-Alloy and Alloy Steels with Specified Elevated Temperature Properties	PCLPS 1501 1 :1000 Carbon and Carbon Manganaga Stools :
Elevated Temperature Properties	BSI BS 1501-1 :1980 Carbon and Carbon Manganese Steels : Plates (Withdrawn)
EN 10028-3 :2003 Weldable Fine Grain Steels, Normalized	Fiales (Williamin)
EN 10020 0 .2000 Wordable I life Grain Globb, Normalized	BSI BS 1501-2 :1988 Alloy Steels : Plates (Withdrawn)
5N 40000 4 4005 5I + B + + + M + + + + + + + + + + + + + +	Supersedes:
EN 10028-4 :1995 Flat Products Made of Steels for Pressure	
Purposes – Part 4 : Nickel Alloy Steels with Specified Low Temperature Properties	BSI BS 1501-2 :1988 Steels for Pressure Purposes – Part 2 :
Temperature i Toperties	Specification for Alloy Steels : Plates (Withdrawn)
	Supersedes:
EN 10029 1 2000 Flat Producto Made of Stools for Processing	BSI BS 1501-1 :1980 Steels For Pressure Purposes – Part 1 :
EN 10028-1 :2000 Flat Products Made of Steels for Pressure Purposes – Part 1 : General Requirements	Specification for Carbon and Carbon Manganese Steels : Plates (Withdrawn)
ruiposes – rait i . General nequirements	(Williami)
	BSI BS 1501-2 :1988 Steels for Pressure Purposes – Part 2 :
	Specification for Alloy Steels : Plates (Withdrawn)
	Supersedes :
EN 10028-7 :2000 Flat Products Made of Steels for Pressure	
Purposes – Part 7 : Stainless Steels	BSI BS 1501-3 :1990 Amd 5 Steels for Pressure Purposes – Part 3 :
Tarposco Tart T. Starrioso Stools	Specification for Corrosion- and Heat-Resisting Steels : Plates,
EN 10000 FLUB LLL MILL (OLL L C B B	Sheet and Strip (Withdrawn)
EN 10028 Flat Products Made from Steel for Pressure Purposes;	Supersedes:
EN 10028-1 :2000 General requirements	DIN 17155 :1983 Weldable Normalized Fine Grain Structural Steels;
Elt 10020 1 .2000 donoral roquiromonic	Technical Delivery Conditions for Plate Strip, Wide Flats, Sections
EN 10028-2 :2003 Unalloyed and Alloy Steels with Elevated	and Bars
Temperature Properties	
EN 10028 :1993 Flat Products Made from Steel for Pressure	Supersedes:
Purposes	
	DIN 17102 :1983 Creep Resistant Steel Plate and Strip; Technical
EN 10028-1 : 2000 General requirements	Delivery Conditions
EN 10028-3 :2003 Weldable, Normalized, Fine Grain Steels	
LIN 10020-3 .2003 WEINADIE, MOITHAILZEN, FILIE GIAIH SIEEIS	
EN 10113 :1993 Hot Rolled Products Made from Weldable, Fine	
Grain Structural Steel	
EN 10113-1 :1993 General Technical Delivery Conditions	
EN 10113-2 :1993 Technical Delivery Conditions for Normalized	
Rolled Steel EN 10008 4 :0003 Flot Products Made of Steels for Procesure	Dawtially Cunavadae
EN 10028-4 :2003 Flat Products Made of Steels for Pressure	Partially Supersedes :
Purposes – Part 4 : Nickel-Alloy Steels with Specified Low Temperature Properties	DIN 17280 :1985 Steels With Low Temperature Toughness;
Tomporatoro i Toporado	Technical Delivery Conditions for Plate. Sheet, Strip, Wide
EN 10028-1 :2000 Flat Products Made of Steel for Pressure	Flats, Sections, Bars and Forgings
Purposes – Part 1 : General Requirements	

490 CEN Standards With Superseded Former National Standards Appendix 6

Chapter 4: Pressure Vessel Steel Plates (Continued)		
Current CEN Standard	Former National Standards Superseded by CEN Standards	
	Supersedes: DIN 17441:1997 Technical Delivery Conditions for Stainless Steel Cold-Rolled Strip, Slit Strip and Plate Cut Therefrom for Pressure Purposes	
EN 10028-7:2000 Flat Products Made of Steels for Pressure – Part	Partially Supersedes:	
7: Purposes Stainless Steels	DIN 17440:1996 Technical Delivery Conditions for Stainless Steel Plate, Hot Rolled Strip, and Bars for Pressure Purposes	
	DIN 17460:1992 High-Temperature Austenitic Steel Plate and Sheet, Cold and Hot Rolled Strip, Bars and Forgings; Technical Delivery Conditions	
EN 10028-2:2003 Flat Products Made of Steels for Pressure Purposes – Part 2: Non-Alloy and Alloy Steels with Specified Elevated Temperature Properties.	Supersedes: AFNOR NF A36-205:1982 Iron and steel products: steel plates for boilers and pressure vessels; carbon and carbon manganese steels, grades and qualities AFNOR NF A36-206:1983 Iron and steel products: steel plates for boilers and pressure vessels; Mo, Mn-Mo and Cr-Mo alloy steels, grades and qualities	
EN 10028-3:2003 Flat Products Made of Steels for Pressure Purposes – Part 3: Weldable Fine Grain Steels, Normalized.	Supersedes: AFNOR NF A36-207:1982 Iron and steel products: high yield strength steel plates for pressure vessels; grades and qualities (July)	
EN 10028-4:2003 Flat Products Made of Steels for Pressure Purposes – Part 4: Nickel Alloy Steels with Specified Low Temperature Properties.	Supersedes: AFNOR NF A36-208:1982 Tôles en Aciers au Nickel pour Appareils à Pression à Basse Température	
EN 10028-7:2000 Flat Products Made of Steels for Pressure Purposes – Part 7: Stainless Steels	Partially Supersedes: AFNOR NF A36-209:1990 Austenitic and Austenic-Ferritic Stainless Steels Plates for Boilers and Pressure Vessels	

Chapter 5: Steel Tubes and Pipes	
Current CEN Standard	Former National Standards Superseded by CEN Standards
	Supersedes:
EN 10208-1:1997 Steel Pipes for Pipe Lines for Combustible Fluids — Technical Delivery Conditions — Part 1: Pipes of Requirement Class A	DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to Special Requirements
	DIN 1629:1984 Seamless Circular Unalloyed Steel Tubes Subject to Special Requirements
	Supersedes:
EN 10216-1:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties	AFNOR NF A49-111:1978 Plain end seamless tubes of commercial quality for general purposes at mean pressure
	AFNOR NF A49-112:1987 Plain end seamless hot rolled tubes with specified room temperature properties and with special delivery conditions – Dimensions – Technical delivery conditions
	BSI BS 3059-1:1987 Steel Boiler and Superheater Tubes – Part 1: Specification for Low Tensile Carbon Steel Tubes Without Specified Elevated Temperature Properties
	BSI BS 3601:1987 Carbon Steel Pipes and Tubes with Specified Room Temperature Properties for Pressure Purposes
	DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to Special Requirements
	DIN 1629:1984 Seamless Circular Unalloyed Steel Tubes Subject to Special Requirements
	Supersedes:
EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties	AFNOR NF A 49-210:1985 Steel Tubes: Seamless Cold Drawn Tubes for Fluid Piping – Dimensions – Technical Delivery Conditions
	AFNOR NF A 49-211:1989 Steel Tubes; Seamless Plain-End Tubes in Unalloyed Steels for Fluid Piping at Elevated Temperatures – Dimensions – Technical Delivery Conditions
	AFNOR NF A 49-213:1990 Seamless Unalloyed and Mo and Cr-Mo Alloyed Steel Tubes for Use at High Temperatures – Dimensions (With Normal Tolerances) – Technical Delivery Conditions
	AFNOR NF A 49-215:1981 Seamless Tubes for Ferritic Non-Alloy and Alloy Steel Heat Exchangers – Dimensions – Technical Delivery Conditions
	AFNOR NF A 49-219:1990 Non-Alloy and Mo and Cr-Mo Alloy Steel Seamless Tubes for Furnaces – Dimensions – Technical Delivery Conditions
	BSI BS 3059-2:1990 Steel Boiler and Superheater Tubes Part 2: Carbon, Alloy and Austenitic Stainless Steel Tubes with Specified Elevated Temperature Properties
	BSI BS 3602-1:1987 Steel Pipes and Tubes for Pressure Purposes Carbon and Carbon Manganese Steel with Specified Elevated Temperature Properties: Seamless, Electric Resistance Welded and Induction Welded Tubes (Withdrawn)
	BSI BS 3606:1992 Steel Tubes for Heat Exchangers (Withdrawn)

Current CEN Standard	Former National Standards Superseded by CEN Standards
	Supersedes:
EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties	BSI BS 3604-1:1990 Steel Pipes and Tubes for Pressure Purposes: Ferritic Alloy Steel with Specified Elevated Temperature Properties - Part 1: Specification for Seamless and Electric Resistance Welded Tubes (Withdrawn) DIN 17175:1979 Seamless Tubes of Heat-resistant Steels
	Supersedes:
EN 10216-3:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 3: Alloy Fine Grain Steel Tubes	DIN 17179:1986 Seamless Circular Fine Grain Steel Tubes Subject to Special Requirements – Technical Delivery Conditions Supersedes:
EN 10216-4:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 4: Non-alloy and Alloy Steel Tubes with Specified Low Temperature Properties	AFNOR NF A 49-230:1985 Steel Tubes: Plain End Seamless Tubes for Pressure Vessels and Piping Systems Used at Low Temperatures – Dimensions – Technical Delivery Conditions BSI BS 3603:1991 Carbon and Alloy Steel Pipes and Tubes with Specified Low Temperature Properties for Pressure Purpose (Withdrawn) DIN 17173:1985 Seamless Circular Tubes Made from Steels with Low Temperature Toughness
EN 10217-1:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties	Supersedes: AFNOR NF A 49-142:1987 Longitudinally Pressure Welded Plain Ended and Hot Finished Tubes. Diameters from 13,5 to 168,3 mm With Specified Room Temperature Properties and with Special Delivery Conditions – Dimensions – Technical Delivery Conditions BSI BS 3059-1:1987 Steel Boiler and Superheater Tubes – Part 1: Specification for Low Tensile Carbon Steel Tubes Without Specified Elevated Temperature Properties BSI BS 3601:1987 Carbon Steel Pipes and Tubes with Specified Room Temperature Properties for Pressure Purposes DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to Special Requirements DIN 1628:1984 High Performance Welded Circular Unalloyed Steel Tubes – Technical Delivery Conditions DIN 1629:1984 Seamless Circular Unalloyed Steel Tubes Subject to Special Requirements
EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-Alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties	Supersedes: AFNOR NF A 49-241:1986 Steel Tubes - Longitudinally Pressure Welded Plain End Tubes in Non-Alloyed Steel Grades for Fluid Piping Up to 425°C – Diameters from 21.3 mm to 168.3 mm – Dimensions – Technical Delivery Conditions AFNOR NF A 49-242:1985 Longitudinally Pressure Welded Tubes D Inferior or Equal to 168.3 mm in Non-Alloyed and Low Alloyed Steels Used at Medium Elevated Temperatures – Dimensions – Technical

Chapter 5: Steel Tubes and Pipes (continued)	
Current CEN Standard	Former National Standards Superseded by CEN Standards
EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-Alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties	Supersedes: AFNOR NF A 49-243:1985 Longitudinally Ppressure Welded Tubes D Inferior or Equal to 168.3 mm in Non-Alloyed and Ferritic Alloyed
	Steels, Used at Elevated Temperatures – Dimensions – Technical Delivery Conditions AFNOR NF A 49-245:1986 Longitudinally Pressure Welded Tubes from Non-Alloy and Ferritic Alloy Steels for Heat Exchangers in
	Diameters from 15.9 mm and 76.1 mm Inclusive – Dimensions – Technical Delivery Conditions AFNOR NF A 49-252:1982 Welded Non-Alloy Steel Tubes of Diameters 168.3 mm to 1220 mm Used at Averagely Elevated
	Temperatures – Dimensions – Technical Delivery Conditions AFNOR NF A 49-253:1982 Longitudinally Fusion Welded Non-Alloy Steel and Ferritic Alloy Steel Tubes for Use at Elevated
	Temperatures – Dimensions – Technical Delivery Conditions BSI BS 3059-2:1990 Steel Boiler and Superheater Tubes Part 2:
	Carbon, Alloy and Austenitic Stainless Steel Tubes with Specified Elevated Temperature Properties
	BSI BS 3602-1:1987 Steel Pipes and Tubes for Pressure Purposes Carbon and Carbon Manganese Steel with Specified Elevated Temperature Properties – Part 1: Seamless, Electric Resistance Welded and Induction Welded Tubes (Withdrawn)
	BSI BS 3604-1:1990 Steel Pipes and Tubes for Pressure Purposes: Ferritic Alloy Steel with Specified Elevated Temperature Properties – Part 1: Specification for Seamless and Electric Resistance Welded Tubes (Withdrawn)
	BSI BS 3606:1992 Steel Tubes for Heat Exchangers (Withdrawn)
	DIN 17177:1979 Electric Pressure-Welded Steel Tubes for Elevated Temperatures
	Supersedes:
EN 10217-3:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 3: Alloy Fine Grain Steel Tubes	BSI BS 3602-2:1991 Steel Pipes and Tubes for Pressure Purposes: Carbon and Carbon Manganese Steel with Specified Elevated Temperature Properties – Part 2: Specification for Longitudinally Arc Welded Tubes (Withdrawn)
	DIN 17178:1986 Welded Circular Fine Grain Steel Tubes Subject to Special requirements – Technical Delivery Conditions
	Supersedes:
EN 10217-4:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 4: Electric Welded Non-Alloy Steel Tubes with Specified Low Temperature Properties	AFNOR NF A 49-240:1983 Steel Tubes: Plain Ended Steel Tubes Longitudinally Welded Without Fusion for Pressure Vessels and Piping Systems at Low Temperatures – Dimensions – Technical Delivery Conditions
	BSI BS 3603:1991 Carbon and Alloy Steel Pipes and Tubes with Specified Low Temperature Properties for Pressure Purpose (Withdrawn)
	DIN 17174:1985 Welded Circular Tubes of Heat-Resistant Steels

Chapter 5: Steel Tubes and Pipes (continued) Current CEN Standard	Former National Standards Superseded by CEN Standards
	Supersedes:
EN 10217-5:2002 Welded Steel Tubes for Pressure Purposes –	
Technical Delivery Conditions – Part 5: Submerged Arc Welded	AFNOR NF A 49-252:1982 Welded Non-Alloy Steel Tubes of
Non-Alloy and Alloy Steel Tubes with Specified Elevated	Diameters 168.3 mm to 1220 mm Used at Averagely Elevated
Temperatures Properties	Temperatures – Dimensions – Technical Delivery Conditions
	Supersedes:
	AFNOR NF A 49-253:1982 Longitudinally Fusion Welded Non-Aallo
EN 10217-5:2002 Welded Steel Tubes for Pressure Purposes –	Steel and Ferritic Alloy Steel Tubes for Use at Elevated
Technical Delivery Conditions – Part 5: Submerged Arc Welded	Temperatures – Dimensions – Technical Delivery Conditions
Non-Alloy and Alloy Steel Tubes with Specified Elevated	Temperatures Emilianolismo Teenmon Eemiling
Temperatures Properties	BSI BS 3602-2:1991 Steel Pipes and Tubes for Pressure Purposes:
Tomporataros Froportios	Carbon and Carbon Manganese Steel with Specified Elevated
	Temperature Properties – Part 2: Specification for Longitudinally Arc
	Welded Tubes (Withdrawn)
EN 10217-6:2002 Welded Steel Tubes for Pressure Purposes –	Supersedes:
Technical Delivery Conditions – Part 6: Submerged Arc Welded	Caps. 100 acc.
Non-Alloy Steel Tubes with Specified Low Temperature Properties	DIN 17174:1985 Welded Circular Tubes of Hear-Resistant Steels
Treat / tilley ereer rubee man epeemed Lem reimperature i reperties	Supersedes:
	Cuperocues.
	AFNOR NF A 49-150:1985 Steel Tubes. Welded Tubes Intended to
	be Coated or Protected for Use in Water Piping Systems –
	Dimensions – Technical Delivery Conditions.
	Billionolo Toolillioui Bollvory Collultiono.
EN 10224:2002 Non-Alloy Steel Tubes and Fittings for the	DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to
Conveyance of Aqueous Liquids Including Water for Human	Special Requirements
Consumption – Technical Delivery Conditions	oposiai rioquiromonio
	DIN 1628:1984 High Performance Welded Circular Unalloyed Steel
	Tubes – Technical Delivery Conditions
	Table Teelimon Dentelly Containent
	DIN 1629:1984 Seamless Circular Unalloyed Steel Tubes Subject to
	Special Requirements
	Supersedes:
	AFNOR NF A 49-341:1975 Precision Welded Tubes for Mechanical
	Application - Dimensions - Technical Delivery Conditions
	AFNOR NF A 49-343:1980 Longitudinally Welded D Inferior or Equa
	to 168.3 mm for Engineering Use – Dimensions – Technical Delivery
	Conditions
	BSI BS 6323-2:1982 Seamless and Welded Steel Tubes for
	Automobile, Mechanical and General Engineering Purposes –
EN 10296-1:2003 Welded Circular Steel Tubes for Mechanical and	Part 2: Specific Requirements for Hot Finished Welded Steel Tubes
	BSI BS 6323-5:1982 Seamless and Welded Steel Tubes for
General Engineering Purposes – Technical Delivery Conditions –	Automobile, Mechanical and General Engineering Purposes –
Part 1: Non-Alloy and Alloy Steel Tubes	Part 5: Specific Requirements for Electric Resistance Welded and
	Induction Welded Steel Tubes (Withdrawn)
	BSI BS 6323-7:1982 Seamless and Welded Steel Tubes for
	Automobile, Mechanical and General Engineering Purposes –
	Part 7: Specific Requirements for Submerged Arc Welded Steel
	Tubes
	DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to
	Special Requirements
	DIN 1628:1984 High Performance Welded Circular Unalloyed Steel
	Tubes – Technical Delivery Conditions

Chapter 5: Steel Tubes and Pipes (continued)	
Current CEN Standard	Former National Standards Superseded by CEN Standards
EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-Alloy and Alloy Steel Tubes	Supersedes:
	AFNOR NF A 49-311:1974 Seamless Tubes for Mechanical Application – Dimensions – Technical Delivery Conditions
EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-Alloy and Alloy Steel Tubes	Supersedes:
	BSI BS 6323-3:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 3: Specific Requirements for Hot Finished Seamless Steel Tubes (Withdrawn)
	DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to Special Requirements
	DIN 1629:1984 Seamless Circular Unalloyed Steel Tubes Subject to Special Requirements
	DIN 17204:1990 Seamless Circular Tubes Made from Steels for Quenching and Tempering – Technical Delivery Conditions Supersedes:
EN 10305-1:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 1: Seamless Cold Drawn Tubes	AFNOR NF A 49-310:1994 Seamless Precision Tubes for Mechanical Application – Dimensions – Technical Delivery Conditions
	AFNOR NF A 49-323:1978 Steel Tubes: Jacks for Hydraulic Transmissions; Cold Rolled or Drawn Seamless Tubes, Type – Ready for Use – Dimensions – Technical Delivery Conditions
	BSI BS 6323-4:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 4: Specific Requirements for Cold Finished Seamless Steel Tubes (Withdrawn)
	DIN 2391-2:1994 Seamless Precision Steel Tubes
	Supersedes:
EN 10305-2:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 2: Welded Cold Drawn Tubes	BSI BS 6323-6:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 6: Specific Requirements for Cold Finished Electric Resistance Welded and Induction Welded Steel Tubes (Withdrawn)
	DIN 2393-2:1994 Welded Precision Steel Tubes
	Supersedes:
EN 10305-3:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 3: Welded Cold Sized Tubes	BSI BS 6323-5:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 5: Specific Requirements for Electric Resistance Welded and Induction Welded Steel Tubes (Withdrawn)
	BSI BS 6323-6:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 6: Specific Requirements for Cold Finished Electric Resistance Welded and Induction Welded Steel Tubes (Withdrawn)
	DIN 2394-2:1994 Welded and Sized Precision Steel Tubes – Technical Delivery Conditions

496 CEN Standards With Superseded Former National Standards Appendix 6

Chapter 5: Steel Tubes and Pipes (continued)	
Current CEN Standard	Former National Standards Superseded by CEN Standards
EN 10305-4:2003 Steel Tubes for Precision Applications - Technical Delivery Conditions - Part 4: Seamless Cold Drawn Tubes for Hydraulic and Pneumatic Power Systems	BSI BS 6323-4:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 4: Specific Requirements for Cold Finished Seamless Steel Tubes (Withdrawn)
EN 10305-5:2003 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 5: Welded and Cold Sized Square and Rectangular Tubes	Supersedes: BSI BS 6323-5:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 5: Specific Requirements for Electric Resistance Welded and Induction Welded Steel Tubes (Withdrawn)
EN 10305-6:2003 Steel Tubes for Precision Applications - Technical Delivery Conditions - Part 6: Welded Cold Drawn Tubes for Hydraulic and Pneumatic Power Systems	Supersedes: BSI BS 6323-6:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 6: Specific Requirements for Cold Finished Electric Resistance Welded and Induction Welded Steel Tubes (Withdrawn)

Chapter 6: Steel Forgings	
Current CEN Standard	Former National Standards Superseded by CEN Standards
EN 10222 Steel Forgings for Pressure Purposes	Supersedes:
EN 10222-1:1998 General Requirements for Open Die Forgings	BSI BS 1503:1989 Amd 3 Steel Forgings for Pressure Purposes (Withdrawn)
EN 10222-3:1999 Nickel Steels with Specified Low-Temperature	,
EN 10222-4:1999 Weldable Fine-Grain Steels with High Proof Strength	
EN 10222-2:2000 Ferritic and Martensitic Steels with Specified Elevated Temperature Properties	
EN 10222-5:2000 Martensitic, Austenitic and Austenitic-Ferritic Stainless Steels	
EN 10250 Corr 1 Open Die Steel Forgings for General Eengineering Purposes	Supersedes:
·	BSI BS 29:1976 Carbon Steel Forgings Above 150 mm Ruling Section (Withdrawn)
EN 10250-2:2000 Non-Alloy Quality and Special Steels EN 10250 Open Die Steel Forgings for General Engineering	Supersedes:
Purposes	POLPO 4070 4074 Allers Oberl Franciscos (MCHedrover)
EN 10250-3:2000 Alloy Special Steels	BSI BS 4670:1971 Alloy Steel Forgings (Withdrawn)
	Partially Supersedes:
EN 10250: Open Die Steel Forgings for General Engineering Purposes	BSI BS 970-1:1996 Wrought Steels for Mechanical and Allied
EN 10250-4: 2000 Stainless Steels	engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels
	Supersedes:
	DIN 17103:1989 Weldable Fine Grain Structural Steel Forgings – Technical Delivery Conditions (Withdrawn)
	DIN 17243:1987 Weldable Heat Resisting Steel Forgings and Rolled or Forged Steel Bars – Technical Delivery Conditions (Withdrawn)
	Partially Supersedes:
EN 10222-1:1998 Steel Forgings for Pressure Purposes – Part 1: General Requirements for Open Die Forgings	DIN 17280:1985 Steels with Low Temperature Toughness – Technical Delivery Conditions for Plate, Sheet, Strip, Wide Flats, Sections, Bars and Forgings (Withdrawn)
	DIN 17440:1996 Stainless Steels – Technical Delivery Conditions for Plates, Hot Rolled Strip and Bars for Pressure Purposes, Drawn Wire and Forgings (Withdrawn)
	DIN 17100:1980 Steels for General Structural Purposes – Quality Standard (Withdrawn)
EN 10222 Steel Forgings for Pressure Purposes	Supersedes:
EN 10222-1:1998 General Requirements for Open Die Forgings	DIN 17243:1987 Weldable Heat Resisting Steel Forgings and Rolled or Forged Steel Bars – Technical Delivery Conditions (Withdrawn)
EN 10222-2:2000 Ferritic and Martensitic Steels with Specified Elevated Temperature Properties (Includes Corrigendum AC: 2000)	2 on the contract of the contr
EN 10273:2000 Hot Rolled Weldable Steel Bars for Pressure Purposes with Specified Elevated Temperature	

Chapter 6: Steel Forgings (Continued)	T
Current CEN Standard	Former National Standards Superseded by CEN Standards
	Supersedes:
EN 10250 Open Die Steel Forgings for General engineering Purposes	DIN 17100:1980 Steels for General Structural Purposes – Quality Standard (Withdrawn)
EN 10250-1:1999 General	Partially Supersedes:
EN 10250-2:2000 Non-Alloy Quality and Special Steels	DIN 17440:1996 Stainless Steels – Technical Delivery Conditions for Plates, Hot Rolled Strip and Bars for Pressure Purposes, Drawn Wire and Forgings (Withdrawn)
EN 10250 Open Die Steel Forgings for General engineering Purposes	Supersedes:
EN 10250-1:1999 General Requirements for Open Die Forgings	DIN 17100:1980 Steels for General Structural Purposes; Quality Standard (Withdrawn)
EN 10250-2:2000 Non-Alloy Quality and Special Steels	
EN 10250 Open Die Steel Forgings for General engineering Purposes	Partially Supersedes:
EN 10250-1:1999 General Requirements for Open Die Forgings	DIN 17440:1996 Stainless Steels – Technical Delivery Conditions for Plates, Hot Rolled Strip and Bars for Pressure Purposes, Drawn Wire and Forgings (Withdrawn)
EN 10250-4:2000 Stainless Steels	
EN 10222 Steel Forgings for Pressure Purposes	Supersedes:
EN 10222-1:1998 General Requirements for Open Die Forgings	AFNOR NF A36-601:1980 Pièces Forgées en Acier Soudable pour Chaudières et Appareils à Pression - Aciers au Carbone et Carbone-Manganèse – Nuances et Qualités (Withdrawn)
EN 10222-3:1999 Nickel Steels with Specified Low Temperature	, ,
Properties.	AFNOR NF A36-602:1988 Pièces Forgées en Acier Soudable pour
EN 10222-4:1999 Weldable Fine Grain Steels with High Proof Strength	Chaudières et Appareils à Pression – Aciers Alliés au Mo, au Mn-Mo et au Cr-Mo - Nuances et Qualités (Withdrawn)
EN 10222-2:2000 Ferritic and Martensitic Steels with Specified Elevated Temperature Properties	AFNOR NF A36-603:1988 Pièces Forgées en Acier Soudable pour Chaudières et Appareils à Pression - Aciers Alliés à Haute Limite d'Élasticité - Nuances et Qualités (Withdrawn)
EN 10222-5:2000 Martensitic, Austenitic and Austenitic-Ferritic Stainless Steels	AFNOR NF A36-607:1984 Pièces Obtenues par Forgeage Libre ou Estampage en Aciers Inoxydables Austénitiques pour Chaudières et Appareils à Pression – Nuances et Qualités (Withdrawn)
	Supersedes:
EN 10250 Open Die Steel Forgings for General engineering Purposes	AFNOR NF A36-612:1982 Pièces Forgées d'Usage Général – Aciers Non Alliés (Withdrawn)
EN 10250-1:1999 General Requirements	AFNOR NF A36-613:1986 Pièces Forgées d'Usage Général – Aciers Inoxydables (Withdrawn)
EN 10250 Open Die Steel Forgings for General engineering Purposes	Supersedes:
EN 10250-2:2000 Non-Alloy Quality and Special Steels	AFNOR NF A36-612:1982 Pièces Forgées d'Usage Général – Aciers Non Alliés (Withdrawn)
EN 10250 Open Die Steel Forging for General engineering Purposes	Supersedes:
EN 10250-4:2000 Stainless Steels	AFNOR NF A36-613:1986 Pièces Forgées d'Usage Général – Aciers Inoxydables (Withdrawn)

Chapter 7: Steel Castings	
Current CEN Standard	Former National Standards Superseded by CEN Standards
EN 10213 Steel Castings for Pressure Purposes	Supersedes:
EN 10213-1:1996 General	BSI BS 1504:1976 Steel Castings for Pressure Purposes (Withdrawn)
EN 10213-2:1996 Steel Grades for Use at Room Temperature and at Elevated Temperature	(Madamy
EN 10213-3:1996 Steels for Use at Low Temperatures	
EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades	
EN 10213: Steel Castings for Pressure Purposes	Supersedes:
EN 10213-1:1996 General	DIN 17245:1987 Ferritic Steel Castings with Elevated Temperature Properties – Technical Delivery Conditions (Withdrawn)
EN 10213-2:1996 Steel Grades for Use at Room Temperature and at Elevated Temperature	
EN 10213 Steel Castings for Pressure Purposes	Supersedes:
EN 10213-1:1996 General	DIN 17182:1992 General Purpose Steel Castings with enhanced Weldability and Higher Toughness – Technical Delivery Conditions
EN 10213-3:1996 Steels for Use at Low Temperatures	(Withdrawn)
EN 10213 Steel Castings for Pressure Purposes	Supersedes:
EN 10213-1:1996 General	DIN 17445:1984 Stainless Steel Castings – Technical Delivery Conditions (Withdrawn)
EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades	
	Supersedes:
EN 10283:1999 Corrosion resistant steel castings	DIN 17445:1984 Stainless Steel Castings – Technical Delivery Conditions
EN 10213 Steel Castings for Pressure Purposes	Supersedes:
EN 10213-1:1996 General	AFNOR NF A32-055:1985 Produits de Fonderie – Aciers Moulés Soudables pour Chaudières et Appareils à Pression (Withdrawn)
EN 10213-2:1996 Steel Grades for Use at Room Temperature and at Elevated Temperature	
EN 10213-3:1996 Steels for Use at Low Temperatures	
EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades	

500 CEN Standards With Superseded Former National Standards Appendix 6

Chapter 8: Wrought Stainless Steels and Heat-Resisting Steels	
Current CEN Standards	Former National Standards Superseded by CEN Standards
EN 10088-2:1995 Stainless Steels – Part 1: Technical Delivery Conditions for Sheet/Plate and Strip for General Purpose	Partially Supersedes:
EN 10088-3:1995 Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rods and Sections for General Purposes	BSI BS 970-1:1991 Wrought Steels for Mechanical and Allied engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels (Withdrawn)
EN 10095:1999 Heat Resisting Steels and Nickel Alloys	Supersedes: BSI BS 1449-2:1983 Amd 4 Steel Plate, Sheet and Strip – Part 2: Stainless and Heat-Resisting Steel Plate, Sheet and Strip AMD 9648 (Withdrawn) BSI BS 970-1:1996 Wrought Steels for Mechanical and Allied engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels
EN 10088-2:1995 Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purpose	Partially Supersedes: DIN 17440:1985 Stainless Steels – Technical Delivery Conditions for Plate and Sheet, Hot Rolled Strip, Wire Rod, Drawn Wire, Steel Bars, Forgings and Semi-Finished Products DIN 17441:1985 Stainless Steels – Technical Delivery Conditions for Cold Rolled Strip and Slit Strip and for Plate And Sheet Cut Therefrom
EN 10088-3:1995 Stainless Steels – Part 3: Technical Delivery Conditions for General Purpose Semi-Finished Products, Bars, Rod and Sections	Partially Supersedes: DIN 17440:1985 Stainless Steels – Technical Delivery Conditions for Plate and Sheet, Hot Rolled Strip, Wire Rod, Drawn Wire, Steel Bars, Forgings and Semi-Finished Products
EN 10088-2:1995 Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purposes	Supersedes: AFNOR NF A35-573:1990 Produits Sidérurgiques – Aciers Inoxydables d'Usage Général - Tôles, Larges Bandes et Feuillards
EN 10088-3:1995 Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rods, and Sections for General Purposes	Supersedes: AFNOR NF A35-574:1990 Produits Sidérurgiques – Aciers Inoxydables d'Usage Général - Demi-Produits, Barres et Fil Machine

Chapter 9: Steels for Special Use	
Current CEN Standard	Former National Standards Superseded by CEN Standards
	Partially Supersedes:
EN 10087:1999 Free Cutting Steels-Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods	BSI BS 970-1:1996 Wrought Steels for Mechanical and Allied Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels
	Supersedes:
	BSI BS 1449-2:1983 Steel Plate, Sheet and Strip – Part 2: Specification for Stainless and Heat-Resisting Steel Plate, Sheet and Strip (Withdrawn)
EN 10095:1999 Heat Resisting Steels and Nickel Alloys	Partially Supersedes:
	BSI BS 970-1:1991 Wrought Steels for Mechanical and Allied Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels
EN 10277 Bright Steel Products. Technical Delivery Conditions	Supersedes:
EN 10277-1:1999 General	BSI BS 970-3:1991 Wrought Steel for Mechanical and Allied Engineering Purposes – Part 3: Bright Bars for General Engineering
EN 10277-2:1999 Steels for General Engineering Purposes	Purposes;
EN 10277-3:1999 Free-Cutting Steels	
EN 10277-4:1999 Case-Hardening Steels	
EN 10277-5:1999 Steels for Quenching and Tempering	
EN 10278:1999 Dimensions and Tolerances of Bright Steel Products	
	Supersedes:
	BSI BS 5770:1981 Steel Strip Intended for the Manufacture of
EN 10132-4: 2000 Cold Rolled Narrow Steel Strip for Heat	Springs
Treatment-Technical Delivery Conditions – Part 4: Spring Steels and Other Applications	BSI BS 5770-1:1981 Hot Rolled Steel and Low Alloy Steel (Withdrawn)
EN 10132-1:2000 Cold Rolled Narrow Steel Strip for Heat Treatment. Technical Delivery Conditions – Part 1: General	BSI BS 5770-2:1981 Amd 1 Cold Rolled Carbon and Low Alloy Steel (Withdrawn)
	BSI BS 5770-3:1981 Pre-Hardened and Tempered Carbon Steel (Withdrawn)
EN ISO 4057:2000 Tool Stools	Supersedes:
EN ISO 4957:2000 Tool Steels	BSI BS 4659:1989 Tool and Die Steels
EN 1000 T 1000 F	Partially Supersedes:
EN 10087:1999 Free-Cutting Steels; Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods	DIN 1651:1988 Free-Cutting Steels – Part 2: Technical Delivery Conditions
EN 10132-4:2000 Cold-Rolled Narrow Steel Strip for Heat-Treatment	Supersedes:
- Technical Delivery Conditions – Part 4: Spring Steels and Other Applications	DIN 17222:1979 Cold Rolled Steel Strips for Springs – Technical Conditions of Delivery
EN 10132-1:2000 Cold-Rolled Narrow Steel Strip for Heat Treatment - Technical Delivery Conditions – Part 1: General	Salada Sa
EN ISO 4957:2000 Tool Steels	Supersedes:
	DIN 17350:1980 Tool Steel

502 CEN Standards With Superseded Former National Standards Appendix 6

Chapter 9: Steels for Special Use (Continued)	
Current CEN Standard	Former National Standards Superseded by CEN Standards
EN ISO 683-17:1999 Heat-Treated Steels, Alloy Steels and Free- Cutting Steels – Part 17: Ball and Roller Bearing Steels	Supersedes: DIN 17230:1980 Ball and Roller Bearing Steels – Technical Conditions of Delivery
EN 10087:1999 Free-Cutting Steels. Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods.	Supersedes: AFNOR NF A35-561:1992 Produits Sidérurgiques-Barres, Fil Machine en Acier de Décolletage d'Usage Général-Conditions Techniques de Livraison AFNOR NF A35-562:1986 Barres et Fils Machine en Aciers de Décolletage Spéciaux pour Traitement Thermique
EN 10277-3:1999 Bright Steel Products – Technical Delivery Conditions -Part 3: Free-Cutting Steels.	Supersedes: AFNOR NF A37-401:1993 Produits en Acier Transformés à Froid-Barres Étirées et Ronds Écroutés-Galètes-Caractéristiques Mécaniques
EN ISO 683-17:1999 Heat-Treated Steels, Alloy Steels and Free- Cutting Steels – Part 17: Ball and Roller Bearing Steels	Supersedes: AFNOR NF A 35-565: 1999 Aciers pour Traitement Thermique, Aciers Alliés et Aciers pour Décolletage. Partie 17:Aciers pour Roulements
EN ISO 4957:2000 Tool Steels	Supersedes: AFNOR NF A35-590:1992 Aciers Outils

Appendix

7

FORMER NATIONAL STANDARDS SUPERSEDED BY CEN STANDARDS

Chapter 2: Carbon and Alloy Steels for General Use	
Former National Standards Superseded by EN Standards	Current Standards
	Superseded by:
BSI BS 970-1:1983 Specification for Wrought Steels for Mechanical and Allied Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels	EN 10083-1:1991+A1:1996 Quenched and Tempered Steels – Part 1: Technical Delivery Conditions for Special Steels
	EN 10083-2:1991+A1:1996 Quenched and Tempered Steels - Part 2: Technical Delivery Conditions for Unalloyed Quality Steels
	Superseded by:
	BS 970-1:1996 Wrought Steels for Mechanical and Allied Engineering Purposes. General Inspection And Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels
BSI BS 970-1:1991 Specification for Wrought Steels for Mechanical and Allied Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon	EN 10083-3:1995 Quenched and Tempered Steels – Part 3: Technical Delivery Conditions for Boron Steels
Manganese, Alloy and Stainless Steels	EN 10088:1995 Stainless Steels
	EN 10088-1:1995 List of Stainless Steels
	EN 10088-3:1995 Technical Delivery Conditions for Semi-Finished Products, Bars, Rods and Sections for General Purposes
	Superseded by:
	EN 10084:1998 Case Hardening Steels – Technical Delivery Conditions
BSI BS 970-1:1996 Specification for Wrought Steels for Mechanical	EN 10085:2001 Nitriding Steel – Technical Delivery Conditions
and Allied Engineering Purposes – Part 1: General Inspection And Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels	EN 10087:1999 Free Cutting Steels – Technical Delivery Conditions for Semi-Finished Products, Hot Rolled Bars and Rods
	EN 10095:1999 Heat Resisting Steels and Nickel Alloys
	EN 10250-4:2000 Open Die Steel Forgings for General Stainless Steels Engineering Purposes – Part 4: Stainless Steels-Supersedes Table
	Superseded by:
DIN 17140-1:1983 Wire Rod for Cold Drawing – Technical Delivery Conditions for Basic Steel and Unalloyed Quality Steels	EN 10016-1:1995 Non-Alloy Steel Rod for Drawing or Cold Rolling Steels – Part 1: General Requirements
	EN 10016-2:1995 Non-Alloy Steel Rod for Drawing or Cold Rolling Steels – Part 2: Specific Requirements for General Purpose Rod
	Superseded by:
DIN 17211:1987 Nitriding Steels; Technical Delivery Conditions	EN 10085:2001 Nitriding Steels – Technical Delivery Conditions
	Superseded by:
AFNOR NF A35-051:1982 Fil Machine en Acier Non Allié Destiné au Tréfilage et au Laminage à Froid-Nuances	EN 10016-2:1995 Non-Alloy Steel Rod for Drawing and/or Cold Rolling - Part 2: Specific Requirements for General Purpose Rod
	Superseded by:
AFNOR NF EN 10083-1:1991 Aciers Pour Trempe et Revenu– Partie 1:Conditions Techniques de Livraison des Aciers Spéciaux	EN 10083-1:1991 Quenched and Tempered Steels – Part 1: Technical Delivery Conditions for Special Steels
AFNOR NF EN 10083-2:1991 Aciers pour Trempe et Revenu –	Superseded by:
Partie 2:Conditions Techniques de Livraison des Aciers de Qualité Non Alliés	EN 10083-2:1991 Quenched and Tempered Steels – Part 2:
AFNOR NF A33-101:1982 Aciers au Carbone de Qualité Aptes au Forgeage et aux Traitements Thermiques – Demi Produits, Barres et Fil Machine	Technical Delivery Conditions for Unalloyed Quality Steels

Chapter 2: Carbon and Alloy Steels for General Use (Continued)	
Former National Standards Superseded by EN Standards	Current Standards
AFNOR NF A35-551:1986 Aciers de Construction Non Alliés et Alliés Spéciaux pour Cémentation–Nuances-Demi-Produits, Barres et Fils Machine	Superseded by: EN 10084:1998 Case Hardening Steels – Technical Delivery Conditions

Chapter 3: Structural Steel Plates	
Former National Standards	Current Standards
BSI BS 4360:1986 Specification for Weldable Structural Steels (Withdrawn)	Partially Superseded by: EN 10025:1993 Hot Rolled Products of Non-Alloy Structural Steels –
(vviuiuiawii)	Technical Delivery Conditions Superseded by:
	BS 7613:1994 Hot Rolled Quenched and Tempered Weldable Structural Steel Plates (Withdrawn)
	BS 7668:1994 Weldable Structural Steels. Hot Finished Structural Hollow Sections in Weather Resistant Steels
	EN 10113 Hot-Rolled Products in Weldable Fine Grain Structural Steels
	EN 10113-1:1993 General Delivery Conditions
BSI BS 4360:1990 Weldable Structural Steels (Withdrawn)	EN 10113-2:1993 Delivery Conditions for Normalized/Normalized Rolled Steels
	EN 10113-3:1993 Delivery Conditions for Thermomechanical Rolled Steels
	EN 10155:1993 Structural Steels with Improved Atmospheric Corrosion Resistance – Technical Delivery Conditions
	EN 10029:1991 Tolerances on Dimensions, Shape and Mass for Hot Rolled Steel Plates 3 mm Thick or Above
	EN 10210-1:1994 Hot Finished Structural Hollow Sections of Non- Alloy and Fine Grain Structural Steels – Part 1: Technical Delivery Requirements
	Superseded by:
	EN 10137 Plates and Wide Flats Made of High Yield Strength Structural Steels in the Quenched and Tempered or Precipitation Hardened Conditions
BSI BS 7613:1994 Hot Rolled Quenched and Tempered Weldable Structural Steel Plates (Withdrawn)	EN 10137-1:1996 General Delivery Conditions
Ondectoral Otees (Withdrawn)	EN 10137-2:1996 Delivery Conditions for Quenched and Tempered Steels
	EN 10137-3:1996 Delivery Conditions for Precipitation Hardened Steels
DIN 17100:1000 Stools for Conseq Structural Burnasses Quality	Partially Superseded by:
DIN 17100:1980 Steels for General Structural Purposes; Quality Standard	EN 10025:1993 Hot Rolled Products of Non-Alloy Structural Steels— Technical Delivery Conditions Superseded by:
DIN 17102:1983 Weldable Normalized Fine Grain Structural Steels; Technical Delivery Conditions for Plate, Strip, Wide Flats, Sections And Bars (Withdrawn)	EN 10113 Hot Rolled Products Made from Weldable, Fine Grain Structural Steel;
	EN 10113-1:1993 General Technical Delivery Conditions
	EN 10113-2:1993 Delivery Conditions for Normalized/Normalized Rolled Steels
	EN 10028 Flat Products Made from Steel for Pressure Purposes
	EN 10028-1:2000 General Requirements
	EN 10028-3:2003 Weldable Fine Grain Steels, Normalized

Chapter 3: Structural Steel Plates (Continued)	
Former National Standards	Current Standards
	Superseded by:
AFNOR NF A 35-504:1984 Poutrelles et Profils en Aciers à Haute	
Limite d'Élasticité pour Constructions Soudées Nuances et Qualités	EN 10113 Hot-Rolled Products in Weldable Fine Grain Structural Steels
AFNOR NF A 36-201:1984 Tôles en Aciers à Haute Limite	
D'Élasticité pour Constructions Soudées-Nuances et Qualités	EN 10113-2:1993 Delivery Conditions for Normalized/Normalized Rolled Steels.
AFNOR NF A 36-204:1992 Produits Sidérurgiques – Tôles en Aciers à Haute Limite d'Élasticité Livrées à l'État Traité pour Construction Soudée – Nuances et Qualité	Superseded by: EN 10137 Plates and Wide Flats Made of High Yield Strength Structural Steels in the Quenched and Tempered or Precipitation Hardened Conditions EN 10137-2:1995 Delivery Conditions for Quenched and Tempered Steels EN 10137-3:1995 Delivery Conditions for Precipitation Hardened Steels
AFNOR NF A35-502:1984 Aciers de Construction à Résistance Améliorée à la Corrosion Atmosphérique – Tôles Minces Moyennes et Fortes, Larges Plats, Laminés Marchands et Poutrelles	Superseded by: EN 10155:1993 Structural Steels with Improved Atmospheric Corrosion Resistance – Technical Delivery Conditions

Chapter 4: Pressure Vessel Steel Plates Former National Standards Superseded by EN Standards	Current Standards
	Superseded by:
BSI BS 1501-1:1980 Specification for Carbon and Carbon Manganese Steels – Part 1: Plates (Withdrawn)	EN 10028 Flat Products Made of Steels for Pressure Purposes.
	EN 10028-2:2003 Non-Alloy and Alloy Steels with Specified Elevated Temperature Properties
	EN 10028-3:2003 Weldable Fine Grain Steels, Normalized
	EN 10029:1991 Tolerances on Dimensions, Shape and Mass for Hot Rolled Steel Plates 3 Mm Thick or Above
	Superseded by:
	EN 10028 Flat Products Made of Steels for Pressure Purposes.
DCI DC 1501 0:1000 Stools for Process Burnosco Dort 0:	EN 10028-2:2003 Non- Alloy and Alloy Steels with Specified Elevated Temperature Properties
BSI BS 1501-2:1988 Steels for Pressure Purposes – Part 2: Specification for Alloy Steels: Plates (Withdrawn)	EN 10028-3:2003 Weldable Fine Grain Steels, Normalized.
	EN 10028-4:2003 Nickel Alloy Steel with Specified Low Temperature Properties
	EN 10029:1991 Tolerances on Dimensions, Shape and Mass for Hot Rolled Steel Plates 3 Mm Thick or Above
BSI BS 1501-1:1980 Steels for Pressure Purposes – Part 1:	Superseded by:
Specification for Carbon and Carbon Manganese Steels: Plates (Withdrawn)	EN 10028-1:2000 Flat Products Made of Steels for Pressure Purposes – Part 1: General Requirements
BSI BS 1501-2:1988 Steels for Pressure Purposes – Part 2: Specification for Alloy Steels: Plates (Withdrawn)	
epointed in the state of the st	Superseded by:
	EN 10028-7:2000 Flat Products Made of Steels for Pressure Purposes – Part 7: Stainless Steels
	Partially Superseded by:
	EN 10029:1991 Tolerances on Dimensions, Shape And Mass for Hot Rolled Steel Plates 3 Mm Thick or Above
BSI BS 1501-3:1990 Amd 5 Steels for Pressure Purposes – Part 3: Specification for Corrosion- and Heat-Resisting Steels: Plates, Sheet and Strip (Withdrawn)	EN 10048:1997 Hot Rolled Narrow Steel Strip – Tolerances on Dimensions and Shape
	EN 10051:1992 Continuously Hot-Rolled Uncoated Plate, Sheet and Strip of Non-Alloy and Alloy Steels – Tolerances on Dimensions and Shape
	EN 10258:1997 Cold-Rolled Stainless Steel Narrow Strip and Cut Lengths – Tolerances on Dimensions and Shape
	EN 10259:1997 Cold-Rolled Stainless and Heat Resisting Steel Wide Strip and Plate/Sheet – Tolerances on Dimensions and Shape Partially Superseded by:
DIN 17280:1985 Steels With Low Temperature Toughness; Technical Delivery Conditions for Plate. Sheet, Strip, Wide Flats, Sections, Bars and Forgings	i amany Superseded by.
	EN 10028-1:2000 Flat Products Made of Steel for Pressure Purposes – Part 1: General Requirements
	EN 10028-4:2003 Flat Products Made of Steels for Pressure Purposes – Part 4: Nickel-Alloy Steels with Specified Low Temperature Properties
DIN 17441:1997 Technical Delivery Conditions for Stainless Steel	Superseded by:
Cold-Rolled Strip, Slit Strip and Plate Cut Therefrom for Pressure Purposes	EN 10028-7:2000 Flat Products Made of Steels for Pressure Purposes – Part 7: Stainless Steels

Chapter 4: Pressure Vessel Steel Plates (Continued)	
Former National Standards Superseded by EN Standards	Current Standards
DIN 17440:1996 Technical Delivery Conditions for Stainless Steel	Partially Superseded by:
Plate, Hot Rolled Strip, and Bars for Pressure Purposes	
	EN 10028-7:2000 Flat Products Made of Steels for Pressure
DIN 17460:1992 High-Temperature Austenitic Steel Plate and Sheet,	Purposes – Part 7: Stainless Steels
Cold and Hot Rolled Strip, Bars and Forgings; Technical Delivery	
Conditions	
AFNOR NF A36-205:1982 Iron and Steel Products: Steel Plates for	Superseded by:
Boilers and Pressure Vessels; Carbon and Carbon Manganese	
Steels, Grades and Qualities	EN 10028-2:2003 Flat Products Made of Steels for Pressure
45105 N5 400 000 1000 1	Purposes – Part 2: Non-Alloy and Alloy Steels with Specified
AFNOR NF A36-206:1983 Iron and Steel Products: Steel Plates for	Elevated Temperature Properties.
Boilers and Pressure Vessels; Mo, Mn-Mo and Cr-Mo Alloy Steels,	
Grades and Qualities	Consequented by
AENOD NE ASS 207:1000 Iron and Stool Braducto, Lligh Viold	Superseded by:
AFNOR NF A36-207:1982 Iron and Steel Products: High Yield Strength Steel Plates for Pressure Vessels; Grades and Qualities	EN 10028-3:2003 Flat Products Made of Steels for Pressure
Strength Steel Flates for Flessure vessels, Grades and Qualities	Purposes – Part 3: Weldable Fine Grain Steels, Normalized.
	Superseded by:
	Superseucu by.
AFNOR NF A36-208:1982 Tôles en Aciers au Nickel pour Appareils	EN 10028-4:2003 Flat Products Made of Steels for Pressure
à Pression à Basse Température	Purposes – Part 4: Nickel Alloy Steels with Specified Low
	Temperature Properties.
L	. eberenane ebernee.

Chapter 5: Steel Tubes and Pipes	
Former National Standards Superseded by EN Standards	Current EN Standards
Torrier National Standards Superseded by EN Standards	Superceded by:
BSI BS 3059-1:1987 Steel Boiler and Superheater Tubes – Part 1: Specification for Low Tensile Carbon Steel Tubes Without Specified Elevated Temperature Properties	EN 10216-1:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties
BSI BS 3601:1987 Carbon Steel Pipes and Tubes with Specified Room Temperature Properties for Pressure Purposes	EN 10217-1:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties
BSI BS 3059-2:1990 Steel Boiler and Superheater Tubes – Part 2: Carbon, Alloy and Austenitic Stainless Steel Tubes with Specified Elevated Temperature Properties BSI BS 3602-1:1987 Steel Pipes and Tubes for Pressure Purposes Carbon and Carbon Manganese Steel with Specified Elevated Temperature Properties: Seamless, Electric Resistance Welded and Induction Welded Tubes (Withdrawn) BSI BS 3604-1:1990 Steel Pipes and Tubes for Pressure Purposes: Ferritic Alloy Steel with Specified Elevated Temperature Properties – Part 1: Specification for Seamless and Electric Resistance Welded Tubes (Withdrawn)	Superceded by: EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
BSI BS 3606:1992 Steel Tubes for Heat Exchangers (Withdrawn)	Superceded by:
BSI BS 3602-2:1991 Steel Pipes and Tubes for Pressure Purposes: Carbon and Carbon Manganese Steel with Specified Elevated Temperature Properties – Part 2: Specification for Longitudinally Arc Welded Tubes (Withdrawn)	EN 10217-3:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 3: Alloy Fine Grain Steel Tubes EN 10217-5:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 5: Submerged Arc Welded Non- alloy and Alloy Steel Tubes with Specified Elevated Temperatures Properties
BSI BS 3603:1991 Carbon and Alloy Steel Pipes and Tubes with Specified Low Temperature Properties for Pressure Purpose (Withdrawn)	Superceded by: EN 10216-4:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 4: Non-alloy and Alloy Steel Tubes with Specified Low Temperature Properties EN 10217-4:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 4: Electric Welded Non-alloy Steel Tubes with Specified Low Temperature Properties
BSI BS 6323-2:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 2: Specific Requirements for Hot Finished Welded Steel Tubes BSI BS 6323-7:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 7: Specific Requirements for Submerged Arc Welded Steel Tubes	Superceded by: EN 10296-1:2003 Welded Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-alloy and Alloy Steel Tubes
BSI BS 6323-3:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 3: Specific Requirements for Hot Finished Seamless Steel Tubes (Withdrawn)	Superceded by: EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-alloy and Alloy Steel Tubes
BSI BS 6323-4:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 4: Specific Requirements for Cold Finished Seamless Steel Tubes (Withdrawn)	Superceded by: EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-alloy and Alloy Steel Tubes

Chapter 5: Steel Tubes and Pipes (Continued)		
Former National Standards Superseded by EN Standards	Current EN Standards	
	Superceded by:	
	EN 10296-1:2003 Welded Circular Steel Tubes for Mechanical and	
	General Engineering Purposes – Technical Delivery Conditions –	
BSI BS 6323-5:1982 Seamless and Welded Steel Tubes for	Part 1: Non-alloy and Alloy Steel Tubes	
Automobile, Mechanical and General Engineering Purposes –		
Part 5. Specific Requirements for Electric Resistance Welded and Induction Welded Steel Tubes (Withdrawn)	EN 10305-3:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 3: Welded Cold Sized Tubes	
middelion Weided Steel Tubes (Withdrawn)	recrifical Delivery Conditions – Fart 3. Welded Cold Sized Tubes	
	EN 10305-5:2003. Steel Tubes for Precision Applications –	
	Technical Delivery Conditions – Part 5: Welded and Cold Sized	
	Square and Rectangular Tubes Superceded by:	
	Superceded by.	
DCI DC C000 C:1000 Coordan and Welded Charl Tuber for	EN 10305-2:2002 Steel Tubes for Precision Applications –	
BSI BS 6323-6:1982 Seamless and Welded Steel Tubes for Automobile, Mechanical and General Engineering Purposes – Part 6:	Technical Delivery Conditions – Part 2: Welded Cold Drawn Tubes	
Specific Requirements for Cold Finished Electric Resistance Welded	EN 40005 0 0000 Otaal Tale on fan Brasisian Applications	
and Induction Welded Steel Tubes (Withdrawn)	EN 10305-3:2003 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 3: Welded Cold Sized Tubes	
	recrimed Benvery Conditions 1 are 6. Weided Cold Cized Tables	
	EN 10305-6:2003	
	Superceded by:	
	EN 10208-1:1997 Steel Pipes for Pipe Lines for Combustible Fluids –	
	Technical Delivery Conditions – Part 1: Pipes of Requirement	
	Class A	
	EN 10216-1:2002 Seamless Steel Tubes for Pressure Purposes –	
	Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with	
	Specified Room Temperature Properties	
	EN 10217-1:2002 Welded Steel Tubes for Pressure Purposes –	
DIN 1626:1984 Welded Circular Unalloyed Steel Tubes Subject to	Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties	
Special Requirements	oposiiou rissiii reimporuluis risponiis	
	EN 10224:2002 Non-Alloy Steel Tubes and Fittings for the	
	Conveyance of Aqueous Liquids Including Water for Human Consumption – Technical Delivery Conditions	
	Consumption – recrimical belivery conditions	
	EN 10296-1:2003 Welded Circular Steel Tubes for Mechanical and	
	General Engineering Purposes – Technical Delivery Conditions –	
	Part 1: Non-Alloy and Alloy Steel Tubes	
	EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and	
	General Engineering Purposes – Technical Delivery Conditions –	
	Part 1: Non-Alloy and Alloy Steel Tubes Superceded by:	
DIN 1628:1984 High Performance Welded Circular Unalloyed Steel Tubes – Technical Delivery Conditions	Superceded by.	
	EN 10296-1: 2003 Welded Circular Steel Tubes for Mechanical and	
	General Engineering Purposes – Technical Delivery Conditions –	
	Part 1: Non-Alloy and Alloy Steel Tubes	
	EN 10217-1:2002 Welded Steel Tubes for Pressure Purposes –	
	Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with	
	Specified Room Temperature Properties	
	EN 10224:2002 Non-Alloy Steel Tubes and Fittings for the	
	Conveyance of Aqueous Liquids Including Water for Human	
	Consumption – Technical Delivery Conditions	

Chapter 5: Steel Tubes and Pipes (Continued) Former National Standards Superseded by EN Standards	Current EN Standards
	Superceded by:
	EN 10208-1:1997 Steel Pipes for Pipe Lines for Combustible Fluids – Technical Delivery Conditions – Part 1: Pipes of Requirement Class A
	EN 10216-1:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties
DIN 1629:1984 Seamless Circular Unalloyed Steel Tubes Subject to Special Requirements	EN 10217-1:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with Specified Room Temperature Properties
	EN 10224:2002 Non-Alloy Steel Tubes and Fittings for the Conveyance of Aqueous Liquids Including Water for Human Consumption – Technical Delivery Conditions
	EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-Alloy and Alloy Steel Tubes
	Superceded by:
DIN 17173:1985 Seamless Circular Tubes Made from Steels with Low Temperature Toughness	EN 10216-4:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 4: Non-alloy and Alloy Steel Tubes with Specified Low Temperature Properties
	Superceded by:
DIN 17174:1985 Welded Circular Tubes of Hear-Resistant Steels	EN 10217-4:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 4: Electric Welded Non-alloy Steel Tubes with Specified Low Temperature Properties
	EN 10217-6:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 6: Submerged Arc Welded Non-Alloy Steel Tubes with Specified Low Temperature Properties
	Superceded by:
DIN 17175:1979 Seamless Tubes of Heat-resistant Steels	EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
	Superceded by:
DIN 17177:1979 Electric Pressure-welded Steel Tubes for Elevated Temperatures	EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
DIN 17179:1096 Wolded Circular Fine Crain Steel Tubes Subject to	Superceded by:
DIN 17178:1986 Welded Circular Fine Grain Steel Tubes Subject to Special requirements – Technical Delivery Conditions	EN 10217-3:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 3: Alloy Fine Grain Steel Tubes
DIN 17179:1986 Seamless Circular Fine Grain Steel Tubes Subject	Superceded by:
to Special Requirements – Technical Delivery Conditions	EN 10216-3:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 3: Alloy Fine Grain Steel Tubes Superceded by:
DIN 17204:1990 Seamless Circular Tubes Made from Steels for Quenching and Tempering – Technical Delivery Conditions	EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-alloy and Alloy Steel Tubes
	Superceded by:
DIN 2391-2:1994 Seamless Precision Steel Tubes	EN 10305-1:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 1: Seamless Cold Drawn Tubes

Chapter 5: Steel Tubes and Pipes (Continued)		
Former National Standards Superseded by EN Standards	Current EN Standards	
	Superceded by:	
DIN 2393-2:1994 Welded Precision Steel Tubes	EN 10305-2:2003 Steel Tubes for Precision Applications –	
	Technical Delivery Conditions – Part 2: Welded Cold Drawn Tubes	
	Superceded by:	
DIN 2394-2:1994 Welded and Sized Precision Steel Tubes -		
Technical Delivery Conditions	EN 10305-3:2003 Steel Tubes for Precision Applications –	
	Technical Delivery Conditions – Part 3: Welded Cold Sized Tubes	
	Superceded by:	
AFNOR NF A49-111:1978 Plain End Seamless Tubes of Commercial	EN 10216-1:2002 Seamless Steel Tubes for Pressure Purposes –	
Quality for General Purposes at Mean Pressure	Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with	
	Specified Room Temperature Properties	
	Superceded by:	
AFNOR NF A49-112:1987 Plain End Seamless Hot Rolled Tubes		
with Specified Room Temperature Properties and with Special	EN 10216-1:2002 Seamless Steel Tubes for Pressure Purposes –	
Delivery Conditions – Dimensions – Technical Delivery Conditions	Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with	
	Specified Room Temperature Properties	
AFNOR NF A 49-142:1987 Longitudinally Pressure Welded Plain	Superceded by:	
Ended and Hot Finished Tubes. Diameters from 13,5 to 168,3 mm	EN 10217-1:2002 Welded Steel Tubes for Pressure Purposes –	
with Specified Room Temperature Properties and with Special	Technical Delivery Conditions – Part 1: Non-Alloy Steel Tubes with	
Delivery Conditions - Dimensions - Technical Delivery Conditions	Specified Room Temperature Properties	
	Superceded by:	
AFNOR NF A 49-150:1985 Steel Tubes. Welded Tubes Intended to		
be Coated or Protected for use in Water Piping Systems –	EN 10224:2002 Non-Alloy Steel Tubes and Fittings for the	
Dimensions – Technical Delivery Conditions.	Conveyance of Aqueous Liquids Including Water for Human	
	Consumption – Technical Delivery Conditions	
	Superceded by:	
AFNOR NF A 49-210:1985 Steel Tubes: Seamless Cold Drawn	EN 10010 0:0000 Coordinate Charl Turbon for Discours Burnages	
Tubes for Fluid Piping – Dimensions – Technical Delivery Conditions	EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel	
	Tubes with Specified Elevated Temperature Properties	
	Superceded by:	
AFNOR NF A 49-211:1989 Steel Tubes; Seamless Plain-End Tubes		
in Unalloyed Steels for Fluid Piping at Elevated Temperatures –	EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes –	
Dimensions – Technical Delivery Conditions	Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel	
	Tubes with Specified Elevated Temperature Properties	
ACNOD NE A 40 010:1000 Coomless Unalloyed and Ma and Cr Ma	Superceded by:	
AFNOR NF A 49-213:1990 Seamless Unalloyed and Mo and Cr-Mo Alloyed Steel Tubes for Use at High Temperatures – Dimensions	EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes –	
(with Normal Tolerances) – Technical Delivery Conditions	Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel	
(minimum role and object to a model 20 months) Contained to	Tubes with Specified Elevated Temperature Properties	
	Superceded by:	
AFNOR NF A 49-215:1981 Seamless Tubes for Ferritic Non-Alloy		
and Alloy Steel Heat Exchangers – Dimensions – Technical Delivery	EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes –	
Conditions	Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel	
	Tubes with Specified Elevated Temperature Properties Superceded by:	
AFNOR NF A 49-219:1990 Non-Alloy and Mo and Cr-Mo Alloy Steel	- Superceueu by.	
Seamless Tubes for Furnaces – Dimensions – Technical Delivery	EN 10216-2:2002 Seamless Steel Tubes for Pressure Purposes –	
Conditions	Technical Delivery Conditions – Part 2: Non-Alloy and Alloy Steel	
	Tubes with Specified Elevated Temperature Properties	
	Superceded by:	
AFNOR NF A 49-230:1985 Steel Tubes: Plain end Seamless Tubes	FN 40040 4 0000 0	
for Pressure Vessels and Piping Systems Used at Low Temperatures	EN 10216-4:2002 Seamless Steel Tubes for Pressure Purposes –	
– Dimensions – Technical Delivery Conditions	Technical Delivery Conditions – Part 4: Non-alloy and Alloy Steel	
	Tubes with Specified Low Temperature Properties Superceded by:	
AFNOR NF A 49-240:1983 Steel Tubes: Plain Ended Steel Tubes	Capologada by.	
Longitudinally Welded Without Fusion for Pressure Vessels and	EN 10217-4:2002 Welded Steel Tubes for Pressure Purposes –	
Piping Systems at Low Temperatures – Dimensions – Technical	Technical Delivery Conditions – Part 4: Electric Welded Non-alloy	
Delivery Conditions	Steel Tubes with Specified Low Temperature Properties	

Chapter 5: Steel Tubes and Pipes (Continued)	
Former National Standards Superseded by EN Standards	Current EN Standards
AFNOR NF A 49-241:1986 Steel Tubes - Longitudinally Pressure Welded Plain End Tubes in Non-Alloyed Steel Grades for Fluid Piping up to 425°C – Diameters From 21.3 mm to 168.3 mm – Dimensions – Technical Delivery Conditions	Superceded by: EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
AFNOR NF A 49-242:1985 Longitudinally Pressure Welded Tubes D Inferior or Equal to 168.3 mm in Non-Alloyed and Low Alloyed Steels Used at Medium Elevated Temperatures – Dimensions – Technical Delivery Conditions	Superceded by: EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
AFNOR NF A 49-243:1985 Longitudinally Pressure Welded Tubes D Inferior or Equal to 168.3 mm in Non-Alloyed and Ferritic Alloyed Steels, Used at Elevated Temperatures – Dimensions – Technical Delivery Conditions	Superceded by: EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
AFNOR NF A 49-245:1986 Longitudinally Pressure Welded Tubes from Non-Alloy and Ferritic Alloy Steels for Heat Exchangers in Diameters From 15.9 mm and 76.1 mm Inclusive – Dimensions – Technical Delivery Conditions	Superceded by: EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties
AFNOR NF A 49-252:1982 Welded Non-Alloy Steel Tubes of Diameters 168.3 mm to 1220 mm Used at Averagely Elevated Temperatures – Dimensions – Technical Delivery Conditions	Superceded by: EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties EN 10217-5:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 5: Submerged Arc Welded Non- alloy and Alloy Steel Tubes with Specified Elevated Temperatures Properties
AFNOR NF A 49-253:1982 Longitudinally Fusion Welded Non-Alloy Steel and Ferritic Alloy Steel Tubes for Use at Elevated Temperatures – Dimensions – Technical Delivery Conditions	Superceded by: EN 10217-2:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 2: Electric Welded Non-alloy and Alloy Steel Tubes with Specified Elevated Temperature Properties EN 10217-5:2002 Welded Steel Tubes for Pressure Purposes – Technical Delivery Conditions – Part 5: Submerged Arc Welded Non- alloy and Alloy Steel Tubes with Specified Elevated Temperatures Properties
AFNOR NF A 49-310:1994 Seamless Precision Tubes for Mechanical Application – Dimensions – Technical Delivery Conditions	Superceded by: EN 10305-1:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 1: Seamless Cold Drawn Tubes Superceded by:
AFNOR NF A 49-311:1974 Seamless Tubes for Mechanical Application – Dimensions – Technical Delivery Conditions	EN 10297-1:2003 Seamless Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-alloy and Alloy Steel Tubes
AFNOR NF A 49-323:1978 Steel Tubes: Jacks for Hydraulic Transmissions; Cold Rolled or Drawn Seamless Tubes, Type – Ready for Use – Dimensions – Technical Delivery Conditions	Superceded by: EN 10305-1:2002 Steel Tubes for Precision Applications – Technical Delivery Conditions – Part 1: Seamless Cold Drawn Tubes Superceded by:
AFNOR NF A 49-341:1975 Precision Welded Tubes for Mechanical Application – Dimensions – Technical Delivery Conditions	EN 10296-1: 2003 Welded Circular Steel Tubes for Mechanical and General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-Alloy and Alloy Steel Tubes

Chapter 5: Steel Tubes and Pipes (Continued)	
Former National Standards Superseded by EN Standards	Current EN Standards
AFNOR NF A 49-343:1980 Longitudinally Welded D Inferior or Equal to 168.3 mm for Engineering Use – Dimensions – Technical Delivery	Superceded by: EN 10296-1: 2003 Welded Circular Steel Tubes for Mechanical and
Conditions	General Engineering Purposes – Technical Delivery Conditions – Part 1: Non-Alloy and Alloy Steel Tubes

516 Former National Standards Superseded by CEN Standards Appendix 7

Chapter 6: Steel Forgings	
Former National Standards Superseded by EN Standards	Current Standards
•	Superseded by:
BSI BS 29:1976 Carbon Steel Forgings Above 150 mm Ruling Section (Withdrawn)	EN 10250-2:2000 Corr 1 Open Die Steel Forgings for General Engineering Purposes – Part 2: Non-Alloy Quality and Special Steels CORR 11041
	Superseded by:
	EN 10222 Steel Forgings for Pressure Purposes
	EN 10222-1:1998 General Requirements for Open Die Forgings
BSI BS 1503:1989 Amd 3 Steel Forgings for Pressure Purposes (Withdrawn)	EN 10222-2:2000 Ferritic and Martensitic Steels with Specified Elevated Temperature Properties
(William)	EN 10222-3:1999 Nickel Steels with Specified Low-Temperature
	EN 10222-4:1999 Weldable Fine-Grain Steels with High Proof Strength
	EN 10222-5:2000 Martensitic, Austenitic and Austenitic-Ferritic Stainless Steels
	Superseded by:
BSI BS 4670:1971 Alloy Steel Forgings (Withdrawn)	EN 10250-3:2000 Open Die Steel Forgings for General Engineering Purposes – Part 3: Alloy Special Steels
DIN 17103:1989 Weldable Fine Grain Structural Steel Forgings; Technical Delivery Conditions (Withdrawn)	Superseded by:
DIN 17243:1987 Weldable Heat Resisting Steel Forgings and Rolled or Forged Steel Bars; Technical Delivery Conditions (Withdrawn)	EN 10222-1:1998 Steel Forgings for Pressure Purposes – Part 1: General Requirements for Open Die Forgings
DIN 17280:1985 Steels with Low Temperature Toughness; Technical Delivery Conditions for Plate, Sheet, Strip, Wide Flats, Sections, Bars	Partially Superseded by:
and Forgings (Withdrawn)	EN 10222-1:1998 Steel Forgings for Pressure Purposes – Part 1: General Requirements for Open Die Forgings
DIN 17440:1996 Stainless Steels- Technical Delivery Conditions for Plates, Hot Rolled Strip and Bars for Pressure Purposes, Drawn Wire and Forgings (Withdrawn)	
DIN 17100:1980 Steels for General Structural Purposes; Quality Standard (Withdrawn)	
,	Superseded by:
	EN 10222 Steel Forgings for Pressure Purposes
DIN 17243:1987 Weldable Heat Resisting Steel Forgings and Rolled	EN 10222-1:1998 General Requirements for Open Die Forgings
or Forged Steel Bars; Technical Delivery Conditions (Withdrawn)	EN 10222-2:2000 Ferritic and Martensitic Steels with Specified Elevated Temperature Properties (Includes Corrigendum AC: 2000)
	EN 10273:2000 Hot Rolled Weldable Steel Bars for Pressure Purposes with Specified Elevated Temperature
	Superseded by:
DIN 17100:1980 Steels for General Structural Purposes; Quality	EN 10250 Open Die Steel Forgings for General Engineering Purposes
Standard (Withdrawn)	EN 10250-1:1999 General
	EN 10250-2:2000 Non-Alloy Quality and Special Steels

Chapter 6: Steel Forgings (Continued)	
Former National Standards Superseded by EN Standards	Current Standards
•	Partially Superseded by:
	EN 10250 Open Die Steel Forgings for General Engineering
DIN 17440:1996 Stainless Steels-Technical Delivery Conditions for Plates, Hot Rolled Strip and Bars for Pressure Purposes, Drawn Wire	Purposes
and Forgings (Withdrawn)	EN 10250-1:1999 General
	EN 10250-4:2000 Open Die Steel Forgings for General Engineering Purposes
	Superseded by:
AFNOR NF A36-601:1980 Pièces Forgées en Acier Soudable pour Chaudières et Appareils à Pression- Aciers au Carbone et Carbone-Manganèse-Nuances et Qualités (Withdrawn)	EN 10222 Steel Forgings for Pressure Purposes
AFNOR NF A36-602:1988 Pièces Forgées en Acier Soudable pour	EN 10222-1:1998 General Requirements for Open Die Forgings
Chaudières et Appareils à Pression – Aciers Alliés au Mo, au Mn-Mo et au Cr-Mo Nuances et Qualités (Withdrawn)	EN 10222-3:1999 Nickel Steels with Specified Low Temperature Properties.
AFNOR NF A36-603:1988 Pièces Forgées en Acier Soudable pour Chaudières et Appareils à Pression-Aciers Alliés à Haute Limite d'Élasticité Nuances et Qualités (Withdrawn)	EN 10222-4:1999 Weldable Fine Grain Steels with High Proof Strength
AFNOR NF A36-607:1984 Pièces Obtenues par Forgeage Libre ou	EN 10222-2:2000 Ferritic and Martensitic Steels with Specified Elevated Temperature Properties
Estampage en Aciers Inoxydables Austénitiques pour Chaudières et Appareils à Pression – Nuances et Qualités (Withdrawn)	EN 10222-5:2000 Martensitic, Austenitic and Austenitic-Ferritic Stainless Steels
AFNOR NF A36-612:1982 Pièces Forgées d'Usage Général – Aciers Non Alliés (Withdrawn)	Superseded by:
AFNOR NF A36-613:1986 Pièces Forgées d'Usage Général – Aciers Inoxydables (Withdrawn)	EN 10250-1:1999 Open Die Steel Forgings for General Engineering Purposes – Part 1: General Requirements
AFNOR NF A36-612:1982 Pièces Forgées d'Usage Général – Aciers	Superseded by:
Non Alliés (Withdrawn)	EN 10250-2:2000 Open Die Steel Forgings for General Engineering Purposes – Part 2: Non-Alloy Quality and Special Steels
AFNOR NF A36-613:1986 Pièces Forgées d'Usage Général – Aciers	Superseded by:
Inoxydables (Withdrawn)	EN 10250-4:2000 Open Die Steel Forgings for General Engineering Purposes – Part 4: Stainless Steels

518 Former National Standards Superseded by CEN Standards Appendix 7

Chapter 7: Steel Castings	
Former National Standards Superseded by EN Standards	Current EN Standard
BSI BS 1504:1976 Steel Castings for Pressure Purposes (Withdrawn)	Superseded by:
	EN 10213 Steel Castings for Pressure Purposes
	EN 10213-1:1996 General
	EN 10213-2:1996 Steel Grades for Use at Room Temperature and at Elevated Temperature
	EN 10213-3:1996 Steels for Use at Low Temperatures
	EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades Partially Superseded by:
DIN 17182:1992 General Purpose Steel Castings with Enhanced	EN 10213 Steel Castings for Pressure Purposes
Weldability and Higher Toughness; Technical Delivery Conditions (Withdrawn)	EN 10213-1:1996 General
	EN 10213-3:1996 Steels for Use at Low Temperatures Superseded by:
	Superseded by:
DIN 17245:1987 Ferritic Steel Castings with Elevated Temperature	EN 10213: Steel Castings for Pressure Purposes
Properties; Technical Delivery Conditions (Withdrawn)	EN 10213-1:1996 General
	EN 10213-2:1996 Steel Grades for Use at Room Temperature and at Elevated Temperature
	Partially Superseded by:
DIN 17445:1984 Stainless Steel Castings; Technical Delivery	EN 10213 Steel Castings for Pressure Purposes
Conditions (Withdrawn)	EN 10213-1:1996 General
	EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades
	Superseded by:
	EN 10213 Steel Castings for Pressure Purposes
DIN 17445:1984 Stainless Steel Castings; Technical Delivery Conditions (Withdrawn)	EN 10213-1:1996 General
	EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades
	EN 10283:1999 Corrosion Resistant Steel Castings
DIN 17/65:1003 Heat Resisting Stool Castings	Superceded by:
DIN 17465:1993 Heat Resisting Steel Castings	EN 10295:2002 Heat Resistant Steel Castings.
AFNOR NF A 32-057:1981 Steel Grades and Related Alloys-	Superceded by:
Refractory Moulds	EN 10295:2002 Heat Resistant Steel Castings.
AFNOR NF A32-055:1985 Produits de Fonderie–Aciers Moulés Soudables pour Chaudières et Appareils à Pression (Withdrawn)	Superseded by:
	EN 10213 Steel Castings for Pressure Purposes
	EN 10213-1:1996 General
	EN 10213-2:1996 Steel Grades for Use at Room Temperature and at Elevated Temperature
	EN 10213-3:1996 Steels for Use at Low Temperatures
	EN 10213-4:1996 Austenitic and Austenitic-Ferritic Steel Grades

Chapter 8: Wrought Stainless Steels and Heat-Resisting Steels	
Former National Standards Superseded by EN Standards	Current EN Standards
	Partially Superseded by:
BSI BS 970-1:1991 Wrought Steels for Mechanical and Allied	BS 970-1:1996 Specification for Wrought Steels for Mechanical and Allied Engineering Purposes – Part 1: General Inspection And Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels
Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels (Withdrawn)	EN 10083-3:1996 Quenched and Tempered Steels – Part 3: Technical Delivery Conditions for Boron Steels
	EN 10088-2:1995 Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purposes
	EN 10088-3:1995 Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rods and Sections for General Purposes
	Superseded by:
	EN 10029:1991 Specification for Tolerances on Dimensions, Shape and Mass for Hot Rolled Steel Plates 3 Mm Thick or Above
	EN 10048:1997 Hot Rolled Narrow Steel Strip – Tolerances on Dimensions and Shape
BSI BS 1449-2:1983 Amd 4 Steel Plate, Sheet and Strip – Part 2: Specification for Stainless and Heat-Resisting Steel Plate, Sheet and Strip AMD 9648 (Withdrawn)	EN 10051:1992 Specification for Continuously Hot-Rolled Uncoated Plate, Sheet and Strip of Non-Alloy and Alloy Steels – Tolerances on Dimensions and Shape
	EN 10095:1999 Heat Resisting Steels and Nickel Alloys
	EN 10258:1997 Cold-Rolled Stainless Steel Narrow Strip and Cut Lengths – Tolerances on Dimensions and Shape
	EN 10259:1997 Cold-Rolled Stainless and Heat Resisting Steel Wide Strip and Plate/Sheet – Tolerances on Dimensions and Shape
	Partially Superseded by:
	EN 10084:1998 Case Hardening Steels – Technical Delivery Conditions
BSI BS 970-1:1991 Wrought Steels for Mechanical and Allied Engineering Purposes – Part 1: General Inspection and Testing	EN 10085:2001 Nitriding Steel – Technical Delivery Conditions
Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels	EN 10087:1999 Free Cutting Steels – Technical Delivery Conditions for Semi-Finished Products, Hot Rolled Bars and Rods
	EN 10095:1999 Heat Resisting Steels and Nickel Alloys
	EN 10250-4:2000 Open Die Steel Forgings for General Engineering Purposes – Part 4: Stainless Steels
DIN 17440:1985 Stainless Steels; Technical Delivery Conditions for	Superseded by:
Plate and Sheet, Hot Rolled Strip, Wire Rod, Drawn Wire, Steel Bars, Forgings and Semi-Finished Products	EN 10088-2:1995 Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purposes
DIN 17441:1985 Stainless Steels; Technical Delivery Conditions for Cold Rolled Strip and Slit Strip and for Plate and Sheet Cut Therefrom	
DIN 17440:1985 Stainless Steels; Technical Delivery Conditions for Plate and Sheet, Hot Rolled Strip, Wire Rod, Drawn Wire, Steel Bars, Forgings and Semi-Finished Products	Partially Superseded by:
	EN 10088-3:1995 Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rods and Sections for General Purposes
DIN 17440:1085 Stainless Stools: Tachnical Dalivani Conditions for	Partially Superseded by:
DIN 17440:1985 Stainless Steels; Technical Delivery Conditions for Plate and Sheet, Hot Rolled Strip, Wire Rod, Drawn Wire, Steel Bars, Forgings and Semi-Finished Products	EN 10250-4:2000 Open Die Steel Forgings for General Engineering Purposes – Part 4: Stainless Steels

520 Former National Standards Superseded by CEN Standards Appendix 7

Chapter 8: Wrought Stainless Steels and Heat-Resisting Steels (Continued)	
Former National Standards Superseded by EN Standards	Current EN Standards
	Superseded by:
AFNOR NF A35-573:1990 Produits Sidérurgiques- Aciers Inoxydables d'Usage Général-Tôles, Larges Bandes et Feuillards	EN 10088-2:1995 Stainless Steels – Part 2: Technical Delivery Conditions for Sheet/Plate and Strip for General Purposes
AFNOR NF A35-574:1990 Produits Sidérurgiques-Aciers Inoxydables d'Usage Général-Demi-Produits, Barres et Fil Machine	Superseded by: EN 10088-3:1995 Stainless Steels – Part 3: Technical Delivery Conditions for Semi-Finished Products, Bars, Rods and Sections for General Purposes

Chapter 9: Steels for Special Use		
Former National Standards Superseded by EN Standards	Current EN Standard	
BSI BS 970-1:1991 Wrought Steels for Mechanical and Allied	Superseded by:	
Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon Manganese, Alloy and Stainless Steels	EN 10095:1999 Heat Resisting Steels and Nickel Alloys	
BSI BS 970-1:1991 Wrought Steels for Mechanical and Allied	Partially Superseded by:	
	EN 10084:1998 Case Hardening Steels – Technical Delivery Conditions	
Engineering Purposes – Part 1: General Inspection and Testing Procedures and Specific Requirements for Carbon, Carbon	EN 10085:2001 Nitriding Steel – Technical Delivery Conditions	
Manganese, Alloy and Stainless Steels	EN 10087:1999 Free Cutting Steels-Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods	
	EN 10250-4:2000 Open Steel Die Forgings for General Engineering Purposes – Part 4: Stainless Steels	
BSI BS 970-2:1988 AMD 2:1992 Wrought Steels for Mechanical and	Superseded by:	
Allied Engineering Purposes – Part 2: Requirements for Steels for the Manufacture of Hot Formed Springs (Withdrawn)	EN 10089:2002 Hot Rolled Steels for Quenched and Tempered Springs – Technical Delivery Conditions.	
	Superseded by:	
	EN 10277 Bright Steel Products – Technical Delivery Conditions	
	EN 10277-1:1999 General	
BSI BS 970-3:1991 Wrought Steel for Mechanical and Allied Engineering Purposes – Part 3: Bright Bars for General Engineering	EN 10277-2:1999 Steels for General Engineering Purposes	
Purposes (Withdrawn)	EN 10277-3:1999 Free-Cutting Steels	
	EN 10277-4:1999 Case-Hardening Steels	
	EN 10277-5:1999 Steels for Quenching and Tempering	
	EN 10278:1999 Dimensions and Tolerances of Bright Steel Products	
	Superseded by:	
	EN 10095:1999 Heat Resisting Steels and Nickel Alloys	
	EN 10029:1991 Specification for Tolerances on Dimensions, Shape and Mass for Hot Rolled Steel Plates 3 Mm Thick or Above	
BSI BS 1449-2:1983 Steel Plate, Sheet and Strip – Part 2: Specification for Stainless and Heat-Resisting Steel Plate, Sheet and Strip (Withdrawn)	EN 10048:1997 Hot Rolled Narrow Steel Strip – Tolerances on Dimensions and Shape	
	EN 10051:1992 Specification for Continuously Hot-Rolled Uncoated Plate, Sheet and Strip of Non-Alloy and Alloy Steels – Tolerances on Dimensions and Shape	
	EN 10258:1997 Cold-Rolled Stainless Steel Narrow Strip and Cut Lengths – Tolerances on Dimensions and Shape	
	EN 10259:1997 Cold-Rolled Stainless and Heat Resisting Steel Wide Strip and Plate/Sheet – Tolerances on Dimensions and Shape	
PCLPC 46E0:1000 Tool and Dia Charle (Mithdraum)	Superseded by:	
BSI BS 4659:1989 Tool and Die Steels (Withdrawn)	EN ISO 4957:2000 Tool Steels	

Chapter 9: Steels for Special Use (Continued) Former National Standards Superseded by EN Standards	Current EN Standard
BSI BS 5770:1981 Steel Strip Intended for the Manufacture of	Current EN Standard
Springs (Withdrawn)	Superseded by:
BSI BS 5770-1:1981: Hot Rolled Steel and Low Alloy Steel (Withdrawn)	EN 10132-1:2000 Cold Rolled Narrow Steel Strip for Heat Treatment - Technical Delivery Conditions - Part 1: General
BSI BS 5770-2:1981 Amd 1 Cold Rolled Carbon and Low Alloy Steel (Withdrawn)	EN 10132-4:2000 Cold Rolled Narrow Steel Strip for Heat Treatment - Technical Delivery Conditions – Part 4: Spring Steels and Other Applications
BSI BS 5770-3:1981 Pre-Hardened and Tempered Carbon Steel (Withdrawn)	
BSI BS 5770-4:1981 Steel Strip Intended for the Manufacture of	Superseded by:
Springs – Part 4: Martensitic and Austenitic Stainless Steel (Withdrawn)	EN 10151:2002 Stainless Steel Strip for Springs – Technical Delivery Conditions
	Partially Superseded by:
DIN 1651:1988 Free-Cutting Steels – Technical Delivery Conditions	EN 10087:1999 Free-Cutting Steels – Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods
	Superceded by:
DIN 17221:1988 Hot Rolled Steels for Springs Suitable for Quenching and Tempering – Technical Delivery Conditions	EN 10151:2002 Stainless Steel Strip for Springs – Technical Delivery Conditions.
	Superseded by:
DIN 17222:1979 Cold Rolled Steel Strips for Springs – Technical Conditions of Delivery	EN 10132-4:2000 Cold-Rolled Narrow Steel Strip for Heat-Treatment – Technical Delivery Conditions – Part 4: Spring Steels and Other Applications
	EN 10132-1:2000 Cold-Rolled Narrow Steel Strip for Heat Treatment – Technical Delivery Conditions – Part 1: General
	Superseded by:
DIN 17224:1982 Stainless Steel Wire and Strip for Springs; Technical Delivery Conditions	EN 10151:2002 Stainless Steel Strip for Springs – Technical Delivery Conditions
	EN 10270-3:2001 Steel Wire for Mechanical Springs – Part 3: Stainless Spring Steel Wire
DIN 47000 4000 Ball and Ballon Bandon Otable. Tackwisel	Superseded by:
DIN 17230:1980 Ball and Roller Bearing Steels Technical Conditions of Delivery	EN ISO 683-17:1999 Heat-Treated Steels, Alloy Steels and Free- Cutting Steels – Part 17: Ball and Roller Bearing Steels
DIN 17350:1980 Tool Steel	Superseded by:
	EN ISO 4957:2000 Tool Steels
AFNOR NF A35-561:1992 Produits Sidérurgiques-Barres, Fil	Superseded by:
Machine en Acier de Décolletage d'Usage Général-Conditions Techniques de Livraison	EN 10087:1999 Free-Cutting Steels – Technical Delivery Conditions for Semi-Finished Products, Hot-Rolled Bars and Rods.
AFNOR NF A35-562:1986 Barres et Fils Machine en Aciers de Décolletage Spéciaux pour Traitement Thermique	
	Superseded by:
AFNOR NF A 35-565: 1999 Aciers pour Traitement Thermique, Aciers Alliés et Aciers pour Décolletage. Partie 17:Aciers pour Roulements	EN ISO 683-17:1999 Heat-Treated Steels, Alloy Steels and Free-
	Cutting Steels – Part 17: Ball and Roller Bearing Steels Superseded by:
AFNOR NF A35 571:1996 Special Structural Steels Suitable for the Manufacture of Suspension Components	EN 10089:2002 Hot Rolled Steels for Quenched and Tempered Springs – Technical Delivery Conditions.
	Superseded by:
AFNOR NF A35-590:1992 Aciers Outils	
	EN ISO 4957:2000 Tool Steels
AFNOR NF A37-401:1993 Produits en Acier Transformés à Froid-	Superseded by:
Barres Étirées et Ronds Écroutés-Galètes-Caractéristiques Mécaniques	EN 10277-3:1999 Bright Steel Products – Technical Delivery Conditions – Part 3: Free-Cutting Steels.

Appendix

8

ISO IRON AND STEEL PRODUCT STANDARDS

Designation	Title
ISO 404:1992	Steel and steel products General technical delivery requirements
ISO 630:1995	Structural steels Plates, wide flats, bars, sections and profiles
ISO 1052:1982	Steels for general engineering purposes
ISO 3755:1991	Cast carbon steels for general engineering purposes
ISO 4885:1996	Ferrous products Heat treatments Vocabulary
ISO 6929:1987	Steel products Definitions and classification
ISO 9477:1992	High strength cast steels for general engineering and structural purposes
ISO 10474:1991	Steel and steel products Inspection documents
ISO 683-1:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 1: Direct-hardening unalloyed and low-alloyed wrought steel in form of different black products
ISO 683-9:1988	Heat-treatable steels, alloy steels and free-cutting steels Part 9: Wrought free-cutting steels
ISO 683-10:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 10: Wrought nitriding steels
ISO 683-11:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 11: Wrought case-hardening steels
ISO 683-15:1992	Heat-treatable steels, alloy steels and free-cutting steels Part 15: Valve steels for internal combustion engines
ISO 683-17:1999	Heat-treated steels, alloy steels and free-cutting steels Part 17: Ball and roller bearing steels
ISO 683-18:1996	Heat-treatable steels, alloy steels and free- cutting steels Part 18: Bright products of unalloyed and low alloy steels
ISO 4954:1993	Steels for cold heading and cold extruding
ISO 4955:1994	Heat-resisting steels and alloys
ISO 5949:1983	Tool steels and bearing steels Micrographic method for assessing the distribution of carbides using reference
	photomicrographs
ISO 9443:1991	Heat-treatable and alloy steels Surface quality classes for hot-rolled round bars and wire rods Technical delivery conditions
ISO 9444:2002	Continuously hot-rolled stainless steel strip, plate/sheet and cut lengths Tolerances on dimensions and form
ISO 9445:2002	Continuously cold-rolled stainless steel narrow strip, wide strip, plate/sheet and cut lengths Tolerances on dimensions and form
ISO/TR 11637:1997	Boron treated engineering steels for quenching and tempering
ISO 6934-1:1991	Steel for the prestressing of concrete Part 1: General requirements
ISO 6934-2:1991	Steel for the prestressing of concrete Part 2: Cold-drawn wire
ISO 6934-3:1991	Steel for the prestressing of concrete Part 3: Quenched and tempered wire
ISO 6934-4:1991	Steel for the prestressing of concrete Part 4: Strand
ISO 6934-5:1991	Steel for the prestressing of concrete Part 5: Hot-rolled steel bars with or without subsequent processing
ISO 6935-1:1991	Steel for the reinforcement of concrete Part 1: Plain bars
ISO 6935-2:1991	Steel for the reinforcement of concrete Part 2: Ribbed bars
ISO 6935-3:1992	Steel for the reinforcement of concrete Part 3: Welded fabric
ISO 10144:1991	Certification scheme for steel bars and wires for the reinforcement of concrete structures
ISO 10544:1992	Cold-reduced steel wire for the reinforcement of concrete and the manufacture of welded fabric
ISO 11082:1992	Certification scheme for welded fabric for the reinforcement of concrete structures
ISO/TR 12662:1997	Certification scheme for prestressing steels
ISO 14654:1999	Epoxy-coated steel for the reinforcement of concrete
ISO 14655:1999	Epoxy-coated strand for the prestressing of concrete
ISO 14656:1999	Epoxy powder and sealing material for the coating of steel for the reinforcement of concrete
ISO 11692:1994	Ferritic-pearlitic engineering steels for precipitation hardening from hot-working temperatures
ISO 683-1:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 1: Direct-hardening unalloyed and low-alloyed wrought steel in form of different black products
ISO 683-9:1988	Heat-treatable steels, alloy steels and free-cutting steels Part 9: Wrought free-cutting steels
ISO 683-10:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 10: Wrought nitriding steels
ISO 683-11:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 11: Wrought case-hardening steels
ISO 683-15:1992	Heat-treatable steels, alloy steels and free-cutting steels Part 15: Valve steels for internal combustion engines
ISO 683-17:1999	Heat-treated steels, alloy steels and free-cutting steels Part 17: Ball and roller bearing steels
ISO 683-18:1996	Heat-treatable steels, alloy steels and free- cutting steels Part 18: Bright products of unalloyed and low alloy steels
ISO 4952:2003	Structural steels with improved atmospheric corrosion resistance
ISO 4954:1993	Steels for cold heading and cold extruding
ISO 4955:1994	Heat-resisting steels and alloys
ISO 5949:1983	Tool steels and bearing steels Micrographic method for assessing the distribution of carbides using reference photomicrographs
ISO 7153-1:1991	Surgical instruments Metallic materials Part 1: Stainless steel Amd 1:1999
ISO 9443:1991	Heat-treatable and alloy steels Surface quality classes for hot-rolled round bars and wire rods Technical delivery
.50 0 . 10.1001	conditions

Designation	Title
ISO 9444:2002	Continuously hot-rolled stainless steel strip, plate/sheet and cut lengths Tolerances on dimensions and form
ISO 9445:2002	Continuously cold-rolled stainless steel narrow strip, wide strip, plate/sheet and cut lengths Tolerances on dimensions and form
ISO 11972:1998	Corrosion-resistant cast steels for general applications
ISO 11973:1999	Heat-resistant cast steels and alloys for general applications
ISO/TR 15510:2003	Stainless steels Chemical composition
ISO 683-14:2004	Heat-treatable steels, alloy steels and free-cutting steels Part 14: Hot-rolled steels for quenched and tempered springs
ISO 6931-1:1994	Stainless steels for springs Part 1: Wire
ISO 6931-2:1989	Stainless steels for springs Part 2: Strip
ISO 8458-1:2002	Steel wire for mechanical springs Part 1: General requirements
ISO 8458-2:2002	Steel wire for mechanical springs Part 2: Patented cold-drawn non-alloy steel wire
ISO 8458-3:2002	Steel wire for mechanical springs Part 3: Oil-hardened and tempered wire
ISO 9442:1988	Steel Hot-rolled ribbed and grooved flats for spring leaves Tolerances and dimensions
ISO 2605-3:1985	Steel products for pressure purposes Derivation and verification of elevated temperature properties Part 3: An alternative procedure for deriving the elevated temperature yield or proof stress properties when data are limited
ISO 4978:1983	Flat rolled steel products for welded gas cylinders
ISO 4991:1994	Steel castings for pressure purposes
ISO 6303:1981	Pressure vessel steels not included in ISO 2604, Parts 1 to 6 Derivation of long-time stress rupture properties
ISO/TR 7468:1981	Summary of average stress rupture properties of wrought steels for boilers and pressure vessels
ISO 9327-1:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 1: General requirements
ISO 9327-2:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 2: Non-alloy and alloy (Mo, Cr and CrMo) steels with specified elevated temperature properties
ISO 9327-3:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 3: Nickel steels with specified low temperature properties
ISO 9327-4:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 4: Weldable fine grain steels with high proof strength
ISO 9327-5:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 5: Stainless steels
ISO 9328-1:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 1: General requirements
ISO 9328-2:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 2: Unalloyed and low-alloyed steels with specified room temperature and elevated temperature properties
ISO 9328-3:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 3: Nickel-alloyed steels with specified low temperature properties
ISO 9328-4:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 4: Weldable fine grain steels with high proof stress supplied in the normalized or quenched and tempered condition
ISO 9328-5:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 5: Austenitic steels
ISO 4957:1999	Tool steels
ISO 5949:1983	Tool steels and bearing steels Micrographic method for assessing the distribution of carbides using reference photomicrographs
ISO 11054:1993	Cutting tools Designation of high-speed steel groups
ISO 683-1:1987	Heat-treatable steels, alloy steels and free-cutting steels Part 1: Direct-hardening unalloyed and low-alloyed wrought steel in form of different black products
ISO 683-18:1996	Heat-treatable steels, alloy steels and free- cutting steels Part 18: Bright products of unalloyed and low alloy steels
ISO 3573:1999	Hot-rolled carbon steel sheet of commercial and drawing qualities
ISO 3574:1999	Cold-reduced carbon steel sheet of commercial and drawing qualities
ISO 3575:1996	Continuous hot-dip zinc-coated carbon steel sheet of commercial, lock-forming and drawing qualities
ISO 4950-1:1995	High yield strength flat steel products Part 1: General requirements
ISO 4950-2:1995	High yield strength flat steel products Part 2: Products supplied in the normalized or controlled rolled condition
ISO 4950-3:1995	High yield strength flat steel products Part 3: Products supplied in the heat-treated (quenched + tempered) condition
ISO 4960:1999	Cold-reduced carbon steel strip with a carbon content over 0,25 %
ISO 4995:2001	Hot-rolled steel sheet of structural quality
ISO 4996:1999	Hot-rolled steel sheet of high yield stress structural quality
ISO 4997:1999	Cold-reduced steel sheet of structural quality
ISO 4998:1996	Continuous hot-dip zinc-coated carbon steel sheet of structural quality
ISO 4999:1999	Continuous hot-dip terne (lead alloy) coated cold-reduced carbon steel sheet of commercial drawing and structural qualities
ISO 5000:1993	Continuous hot-dip aluminium/silicon-coated cold-reduced carbon steel sheet of commercial and drawing qualities

Designation	Title
ISO 5001:1999	Cold-reduced carbon steel sheet for vitreous enamelling
ISO 5002:1999	Hot-rolled and cold-reduced electrolytic zinc-coated carbon steel sheet of commercial and drawing qualities
ISO 5950:2000	Continuous electrolytic tin-coated cold-reduced carbon steel sheet of commercial and drawing qualities
ISO 5951:2001	Hot-rolled steel sheet of higher yield strength with improved formability
ISO 5952:1998	Continuously hot-rolled steel sheet of structural quality with improved atmospheric corrosion resistance
ISO 5954:1998	Cold-reduced carbon steel sheet according to hardness requirements
ISO 6316:2000	Hot-rolled steel strip of structural quality
ISO 6317:2000	Hot-rolled carbon steel strip of commercial and drawing qualities
ISO 6930-1:2001	High yield strength steel plates and wide flats for cold forming Part 1: Delivery conditions for thermomechanically-
	rolled steels
ISO 6932:2001	Cold-reduced carbon steel strip with a maximum carbon content of 0,25 %
ISO 7452:2002	Hot-rolled structural steel plates Tolerances on dimensions and shape
ISO 7778:1983	Steel plate with specified through-thickness characteristics
ISO 7788:1985	Steel Surface finish of hot-rolled plates and wide flats Delivery requirements
ISO 9034:1987	Hot-rolled structural steel wide flats Tolerances on dimensions and shape
ISO 9328-1:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 1: General requirements
ISO 9328-2:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 2: Unalloyed and low-alloyed
100 0000 0 1001	steels with specified room temperature and elevated temperature properties
ISO 9328-3:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 3: Nickel-alloyed steels with specified low temperature properties
ISO 9328-4:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 4: Weldable fine grain steels with
	high proof stress supplied in the normalized or quenched and tempered condition
ISO 9328-5:1991	Steel plates and strips for pressure purposes Technical delivery conditions Part 5: Austenitic steels
ISO 9364:2001	Continuous hot-dip aluminium/zinc-coated steel sheet of commercial, lock-forming and structural qualities
ISO 9444:2002	Continuously hot-rolled stainless steel strip, plate/sheet and cut lengths Tolerances on dimensions and form
ISO 9445:2002	Continuously cold-rolled stainless steel narrow strip, wide strip, plate/sheet and cut lengths Tolerances on dimensions and form
ISO 9473:1988	Textile machinery and accessories Strip steel for dents of reeds
ISO 10384:2001	Hot-rolled carbon steel sheet for machinery
ISO 11949:1995	Cold-reduced electrolytic tinplate
ISO 11950:1995	Cold-reduced electrolytic chromium/chromium oxide-coated steel
ISO 11951:1995	Cold-reduced blackplate in coil form for the production of tinplate or electrolytic chromium/chromium oxide-coated steel
ISO 13887:1995	Cold-reduced steel sheet of higher yield strength with improved formability
ISO 13976:1998	Hot-rolled steel sheet in coils of structural quality and heavy thickness
ISO 14590:1999	Cold-reduced steel sheet of high tensile strength and low yield point with improved formability
ISO 14788:1998	Continuous hot-dip zinc-5 %/aluminium alloy coated steel sheets and coils
ISO 16160:2000	Continuously hot-rolled steel sheet products Dimensional and shape tolerances
ISO 16162:2000	Continuously cold-rolled steel sheet products Dimensional and shape tolerances
ISO 16163:2000	Continuously hot-dipped coated steel sheet products Dimensional and shape tolerances
ISO 722:1991	Rock drilling equipment Hollow drill steels in bar form, hexagonal and round
ISO 1035-1:1980	Hot-rolled steel bars Part 1: Dimensions of round bars
ISO 1035-2:1980	Hot-rolled steel bars Part 2: Dimensions of square bars
ISO 1035-3:1980	Hot-rolled steel bars Part 3: Dimensions of flat bars
ISO 1035-4:1982	Hot-rolled steel bars Part 4: Tolerances
ISO 2938:1974	Hollow steel bars for machining
ISO 4951-1:2001	High yield strength steel bars and sections Part 1: General delivery requirements
ISO 4951-2:2001	High yield strength steel bars and sections Part 2: Delivery conditions for normalized, normalized rolled and as-
	rolled steels
ISO 4951-3:2001	High yield strength steel bars and sections Part 3: Delivery conditions for thermomechanically-rolled steels
ISO 9443:1991	Heat-treatable and alloy steels Surface quality classes for hot-rolled round bars and wire rods Technical delivery conditions
ISO 2232:1990	Round drawn wire for general purpose non-alloy steel wire ropes and for large diameter steel wire ropes Specifications
ISO 2408:2004	Steel wire ropes for general purposes Minimum requirements
ISO 2532:1974	Steel wire ropes Vocabulary
ISO 2701:1977	Drawn wire for general purpose non-alloy steel wire ropes Terms of acceptance
ISO 3108:1974	Steel wire ropes for general purposes Determination of actual breaking load
	-

Designation	Title
ISO 9305:1989	Seamless steel tubes for pressure purposes Full peripheral ultrasonic testing for the detection of transverse imperfections
ISO 9329-1:1989	Seamless steel tubes for pressure purposes Technical delivery conditions Part 1: Unalloyed steels with specified room temperature properties
ISO 9329-2:1997	Seamless steel tubes for pressure purposes Technical delivery conditions Part 2: Unalloyed and alloyed steels with specified elevated temperature properties
ISO 9329-3:1997	Seamless steel tubes for pressure purposes Technical delivery conditions Part 3: Unalloyed and alloyed steels with specified low temperature properties
ISO 9329-4:1997	Seamless steel tubes for pressure purposes Technical delivery conditions Part 4: Austenitic stainless steels
ISO 9330-1:1990	Welded steel tubes for pressure purposes Technical delivery conditions Part 1: Unalloyed steel tubes with specified room temperature properties
ISO 9330-2:1997	Welded steel tubes for pressure purposes Technical delivery conditions Part 2: Electric resistance and induction welded unalloyed and alloyed steel tubes with specified elevated temperature properties
ISO 9330-3:1997	Welded steel tubes for pressure purposes Technical delivery conditions Part 3: Electric resistance and induction welded unalloyed and alloyed steel tubes with specified low temperature properties
ISO 9330-4:2000	Welded steel tubes for pressure purposes Technical delivery conditions Part 4: Submerged arc-welded unalloyed and alloyed steel tubes with specified elevated temperature properties
ISO 9330-5:2000	Welded steel tubes for pressure purposes Technical delivery conditions Part 5: Submerged arc-welded unalloyed and alloyed steel tubes with specified low temperature properties
ISO 9330-6:1997	Welded steel tubes for pressure purposes Technical delivery conditions Part 6: Longitudinally welded austenitic stainless steel tubes
ISO 9402:1989	Seamless and welded (except submerged arc-welded) steel tubes for pressure purposes Full peripheral magnetic transducer/flux leakage testing of ferromagnetic steel tubes for the detection of longitudinal imperfections
ISO 9598:1989	Seamless steel tubes for pressure purposes Full peripheral magnetic transducer/flux leakage testing of ferromagnetic steel tubes for the detection of transverse imperfections
ISO 9764:1989	Electric resistance and induction welded steel tubes for pressure purposes Ultrasonic testing of the weld seam for the detection of longitudinal imperfections
ISO 9765:1990	Submerged arc-welded steel tubes for pressure purposes Ultrasonic testing of the weld seam for the detection of longitudinal and/or transverse imperfections
ISO 10124:1994	Seamless and welded (except submerged arc-welded) steel tubes for pressure purposes Ultrasonic testing for the detection of laminar imperfections
ISO 10332:1994	Seamless and welded (except submerged arc-welded) steel tubes for pressure purposes Ultrasonic testing for the verification of hydraulic leak-tightness
ISO 10543:1993	Seamless and hot-stretch-reduced welded steel tubes for pressure purposes Full peripheral ultrasonic thickness testing
ISO 10763:1994	Hydraulic fluid power Plain-end, seamless and welded precision steel tubes Dimensions and nominal working pressures
ISO 10799:2001	Structural steels Cold-formed, welded, structural hollow sections Technical delivery requirements
ISO 11484:1994	Steel tubes for pressure purposes Qualification and certification of non-destructive testing (NDT) personnel
ISO 11496:1993	Seamless and welded steel tubes for pressure purposes Ultrasonic testing of tube ends for the detection of laminar imperfections
ISO 11960:2001	Petroleum and natural gas industries Steel pipes for use as casing or tubing for wells
ISO 11961:1996	Petroleum and natural gas industries Steel pipes for use as drill pipe Specification
ISO 12094:1994	Welded steel tubes for pressure purposes Ultrasonic testing for the detection of laminar imperfections in strips/plates used in the manufacture of welded tubes
ISO 12095:1994	Seamless and welded steel tubes for pressure purposes Liquid penetrant testing
ISO 12096:1996	Submerged arc-welded steel tubes for pressure purposes Radiographic testing of the weld seam for the detection of imperfections
ISO 13663:1995	Welded steel tubes for pressure purposes Ultrasonic testing of the area adjacent to the weld seam for the detection of laminar imperfections
ISO 13664:1997	Seamless and welded steel tubes for pressure purposes Magnetic particle inspection of the tube ends for the detection of laminar imperfections
ISO 13665:1997	Seamless and welded steel tubes for pressure purposes Magnetic particle inspection of the tube body for the detection of surface imperfections
ISO 13680:2000	Petroleum and natural gas industries Corrosion-resistant alloy seamless tubes for use as casing, tubing and coupling stock Technical delivery conditions
ISO 13:1978	Grey iron pipes, special castings and grey iron parts for pressure main lines
ISO 65:1981	Carbon steel tubes suitable for screwing in accordance with ISO 7-1
ISO 1127:1992	Stainless steel tubes Dimensions, tolerances and conventional masses per unit length
ISO 2531:1998	Ductile iron pipes, fittings, accessories and their joints for water or gas applications
ISO 3304:1985	Plain end seamless precision steel tubes Technical conditions for delivery
ISO 3305:1985	Plain end welded precision steel tubes Technical conditions for delivery
ISO 3306:1985	Plain end as-welded and sized precision steel tubes Technical conditions for delivery

Designation	Title
ISO 12096:1996	Submerged arc-welded steel tubes for pressure purposes Radiographic testing of the weld seam for the detection
	of imperfections
ISO 13663:1995	Welded steel tubes for pressure purposes Ultrasonic testing of the area adjacent to the weld seam for the detection of laminar imperfections
ISO 13664:1997	Seamless and welded steel tubes for pressure purposes Magnetic particle inspection of the tube ends for the detection of laminar imperfections
ISO 13665:1997	Seamless and welded steel tubes for pressure purposes Magnetic particle inspection of the tube body for the detection of surface imperfections
ISO 4986:1992	Steel castings Magnetic particle inspection
ISO 4987:1992	Steel castings Penetrant inspection
ISO 4990:2003	Steel castings General technical delivery requirements
ISO 4991:1994	Steel castings for pressure purposes
ISO 4993:1987	Steel castings Radiographic inspection
ISO 7186:1996	Ductile iron products for sewage applications
ISO 11970:2001	Specification and approval of welding procedures for production welding of steel castings
ISO 11971:1997	Visual examination of surface quality of steel castings
ISO 11972:1998	Corrosion-resistant cast steels for general applications
ISO 11973:1999	Heat-resistant cast steels and alloys for general applications
ISO 13521:1999	Austenitic manganese steel castings
ISO 13583-1:2000	Centrifugally cast steel and alloy products Part 1: General testing and tolerances
ISO 9327-1:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 1: General requirements
ISO 9327-2:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 2: Non-alloy and alloy (Mo, Cr and CrMo) steels with specified elevated temperature properties
ISO 9327-3:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 3: Nickel steels with specified low temperature properties
ISO 9327-4:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 4: Weldable fine grain steels with high proof strength
ISO 9327-5:1999	Steel forgings and rolled or forged bars for pressure purposes Technical delivery conditions Part 5: Stainless steels
ISO/TR 15461:1997	Steel forgings Testing frequency, sampling conditions and test methods for mechanical tests
ISO 1834:1999	Short link chain for lifting purposes General conditions of acceptance
ISO 1835:1980	Short link chain for lifting purposes Grade M (4), non-calibrated, for chain slings etc.
ISO 1837:2003	Lifting hooks Nomenclature
ISO 2262:1984	General purpose thimbles for use with steel wire ropes Specification
ISO 2308:1972	Hooks for lifting freight containers of up to 30 tonnes capacity Basic requirements
ISO 2415:1987	Forged shackles for general lifting purposes Dee shackles and bow shackles
ISO 3056:1986	Non-calibrated round steel link lifting chain and chain slings Use and maintenance
ISO 3075:1980	Short link chain for lifting purposes Grade S (6) non calibrated, for chain slings etc.
ISO 3076:1984	Short link chain for lifting purposes Grade T (8), non-calibrated, for chain slings etc.
ISO 3077:2001	Short-link chain for lifting purposes Grade T, (types T, DAT and DT), fine-tolerance hoist chain
ISO 3266:1984	Eyebolts for general lifting purposes
ISO 4308-1:2003	Cranes and lifting appliances Selection of wire ropes Part 1: General
ISO 4308-2:1988	Cranes and lifting appliances Selection of wire ropes Part 2: Mobile cranes Coefficient of utilization
ISO 4309:1990	Cranes Wire ropes Code of practice for examination and discard
ISO 4778:1981	Chain slings of welded construction Grades M (4), S (6) and T (8)
ISO 4779:1986	Forged steel lifting hooks with point and eye for use with steel chains of grade M(4)
ISO 7592:1983	Calibrated round steel link lifting chains Guidelines to proper use and maintenance
ISO 7593:1986	Chain slings assembled by methods other than welding Grade T(8)
ISO 7597:1987	Forged steel lifting hooks with point and eye for use with steel chains of grade T(8)
	9 9 7
ISO 8539:1986	Forged steel lifting components for use with grade T(8) chain

Appendix

9

ASTM A 941-03 TERMINOLOGY RELATING TO STEEL, STAINLESS STEEL, RELATED ALLOYS, AND FERROALLOYS



Designation: A 941 - 03

Terminology Relating to Steel, Stainless Steel, Related Alloys, and Ferroalloys¹

This standard is issued under the fixed designation A 941; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

- 1.1 This standard is a compilation of definitions of terms related to steel, stainless steel, related alloys, and ferroalloys.
- 1.2 When a term is used in an ASTM document for which Committee A01 is responsible, it is included herein only when judged, after review by Subcommittee A01.92, to be a generally usable term.
- 1.3 Some definitions include a discussion section, which is a mandatory part of the definition and contains additional information that is relevant to the meaning of the defined term.
- 1.4 Definitions of terms specific to a particular standard will appear in that standard and will supersede any definitions of identical terms in this standard.

2. Referenced Documents

2.1 ASTM Standards:

E 112 Test Methods for Determining Average Grain Size²

3. Terminology

3.1 Definitions of General Terms:

alloy steel, *n*—a steel, other than a stainless steel, that conforms to a specification that requires one or more of the following elements, by mass percent, to have a minimum content equal to or greater than: 0.30 for aluminum; 0.0008 for boron; 0.30 for chromium; 0.30 for cobalt; 0.40 for copper; 0.40 for lead; 1.65 for manganese; 0.08 for molybdenum; 0.30 for nickel; 0.06 for niobium (columbium); 0.60 for silicon; 0.05 for titanium; 0.30 for tungsten (wolfram); 0.10 for vanadium; 0.05 for zirconium; or 0.10 for any other alloying element, except sulphur, phosphorus, carbon, and nitrogen.

capped steel, *n*—a **rimmed steel** in which, during ingot solidification, the rimming action was limited by mechanical or chemical means.

carbon steel, *n*—a **steel** that conforms to a specification that prescribes a maximum limit, by **heat analysis** in mass percent, of not more than: 2.00 for carbon and 1.65 for

manganese, but does not prescribe a minimum limit for chromium, cobalt, molybdenum, nickel, niobium (columbium), tungsten (wolfram), vanadium, or zirconium.

Discussion—Except as required above, it is permissible for carbon steel specifications to prescribe limits (minimum or maximum, or both) for each specified alloying element, subject to the following restrictions for the heat analysis limits in mass percent:

- (a) for wrought carbon steel products, the specified maximum limit is not to exceed: 0.10 for aluminum, 0.60 for silicon, and 0.050 for titanium:
- (b) for carbon steel castings, the specified maximum limit is not to exceed: 0.10 for aluminum, 1.00 for silicon, and 0.050 for titanium.
- (c) for **carbon steels** that are required to be rephosphorized, the specified minimum limit for phosphorus is not to be less than 0.040;
- (d) for **carbon steels** that are required to be resulfurized, the specified minimum limit for sulfur is not to be less than 0.060;
- (e) for **carbon steels** that are not required to be rephosphorized or resulfurized, the specified maximum limit is not to exceed: 0.60 for copper, 0.050 for phosphorus, and 0.060 for sulfur; and
- (f) for **carbon steels** that are required to contain boron, copper, or lead, the specified minimum limit is not to exceed: 0.0005 for boron, 0.35 for copper, and 0.25 for lead.

cast analysis—Deprecated term. Use the preferred term heat analysis.

certificate of compliance, n—in manufactured products, a document that states that the product was manufactured, sampled, tested, and inspected in accordance with the requirements of the specification (including year of issue) and any other requirements specified in the purchase order or contract, and has been found to meet such requirements.

Discussion—A single document, containing test report information and certificate of compliance information, may be used.

certifying organization, *n*—*in product specifications*, the entity responsible for the conformance and certification of the product to the specification requirements.

coarse grain practice, *n*—a steelmaking practice for other than **stainless steel** that is intended to produce a **killed steel** in which aluminum, niobium (columbium), titanium, and vanadium are **residual elements**.

cold working, *n*—mechanical deformation of a metal at temperatures below its **recrystallization temperature**.

defect, *n*—an imperfection of sufficient magnitude to warrant rejection based on the specified requirements.

¹ This terminology is under the jurisdiction of ASTM Committee A01 on Steel, Stainless Steel, and Related Alloys and is the direct responsibility of Subcommittee A01.92 on Terminology.

Current edition approved July 10, 2003. Published October 2003. Originally approved in 1995. Last previous edition approved in 2001 as A941-01.

² Annual Book of ASTM Standards, Vol 03.01.

direct quenching, *n*—*in thermomechanical processing*, **quenching** immediately following the final hot deformation. **electronic data interchange,** *n*—the computer to computer

exchange of business information in a standardized format.

ellipsis, *n*—*in a tabular entry*, three periods (...) that indicate that there is no requirement.

fine grain practice, *n*—a steelmaking practice for other than **stainless steel** that is intended to produce a **killed steel** that is capable of meeting the requirements specified for fine austenitic grain size.

DISCUSSION—It normally involves the addition of one or more austenitic grain refining elements in amounts that have been established by the steel producer as being sufficient. Austenitic grain refining elements include, but are not limited to, aluminum, niobium (columbium), titanium, and vanadium.

grain size, *n*—the dimensions of the grains or crystals in a polycrystalline metal, exclusive of twinned regions and subgrains when present.

Discussion—**Grain size** is usually estimated or measured on the cross section of an aggregate of grains, and designated by an ASTM grain size number. (See Test Methods E 112.)

heat, *n*—a generic term denoting a specific **lot** of **steel**, based upon steelmaking and casting considerations.

Discussion—Where it is necessary to be more definitive, the following more specific terms are used: **primary heat**, **multiple heat**, and **remelted heat**. In product specifications, the term **heat** generally is used, without qualification, to mean the **primary**, **multiple**, or **remelted heat**, whichever is applicable.

heat analysis, n—the chemical analysis determined by the steel producer as being representative of a specific heat of steel.

DISCUSSION—Where the analysis reported by the steel producer is not sufficiently complete for conformance with the heat analysis requirements of the applicable product specification to be fully assessed, the **manufacturer** may complete the assessment of conformance with such heat analysis requirements by using a product analysis for the **specified elements** that were not reported by the steel producer, provided that product analysis tolerances are not applied and the **heat analysis** is not altered

heat number, *n*—the alpha, numeric, or alphanumeric designator used to identify a specific **heat** of **steel**.

high-strength low-alloy steel, n—a steel, other than a carbon steel or an interstitial-free steel, that conforms to a specification that requires the minimum content for each specified alloying element to be lower than the applicable limit in the definition for alloy steel, and the yield point or yield strength of the product to be at least 36 ksi or 250 MPa.

hot-cold working, *n*—the mechanical deformation of austenitic and precipitation hardening steels at a temperature just below the **recrystallization temperature** to increase the yield strength and hardness by plastic deformation or precipitation hardening effects induced by plastic deformation, or both.

hot working, *n*—mechanical deformation of a metal at temperatures above its **recrystallization temperature**.

imperfection, *n*—a material discontinuity or irregularity that is

detectable by **inspection**.

inspection, *n*—the process of measuring, examining, testing, gaging, or otherwise comparing the unit of product with the applicable requirements.

interstitial-free steel, *n*—a **steel** that has essentially all of its carbon and nitrogen chemically combined with stabilization elements rather than being present interstitially.

Discussion—The heat analysis limits (minimum or maximum, or both) that are permitted to be prescribed in interstitial-free steel specifications are as given in the definition for **carbon steel**, except that the 0.050 % maximum limit for titanium does not apply.

killed steel, *n*—a **steel** deoxidized to such a level that essentially no reaction occurred between carbon and oxygen during solidification.

laser beam welding, n—a welding process that uses a laser beam as the heat source.

lot, *n*—a definite quantity of product manufactured under conditions that are considered uniform.

low-alloy steel, *n*—a **steel**, other than a **carbon steel** or an **interstitial-free steel**, that conforms to a specification that requires the minimum content for each specified alloying element to be lower than the applicable limit in the definition for **alloy steel**.

manufacturer, *n*—the organization responsible for the conversion of materials into products meeting the requirements of a product specification.

microalloyed steel, n—a low-alloy steel that conforms to a specification that requires the presence of one or more carbide-, nitride-, or carbonitride-forming elements, generally in individual concentrations less than 0.15 mass percent, to enhance strength.

Discussion—The most common microalloying elements are niobium (columbium), titanium, and vanadium.

multiple heat, *n*—two or more molten **primary heats**, in whole or in part, combined in a common ladle or in a common non-oscillating mold.

Discussion—A multiple heat is identified by a single heat number representative of the multiple heat, or by the individual heat numbers of the primary heats contained in the multiple heat. The heat analysis of a multiple heat identified by a single heat number is the weighted average analysis of the individual primary heats contained in the multiple heat. Two or more molten primary heats sequentially strand cast (poured into an oscillating mold) constitute a series of individual heats, not a multiple heat.

plate-as-rolled, *n*—the quantity of plate product rolled at one time, either from an individual slab or directly from an ingot.

DISCUSSION—This term does not refer to the surface condition or the heat-treatment state of the material; a **plate-as-rolled** may be in the as-rolled condition, or may have received one or more surface treatments or **heat treatments**, or both.

primary heat, *n*—the product of a single cycle of a batch melting process.

Discussion—In the investment casting industry, the term *master heat* is used.

remelted heat, *n*—the product of the remelting of a **primary heat**, in whole or in part.

Discussion—In the investment casting industry, the term *sub-heat* is used

residual element, *n*—*in steel*, a specified or unspecified element, not intentionally added, originating in the raw materials, refractories, or surrounding atmospheres used in steel making.

rimmed steel, *n*—a **steel** that contained sufficient oxygen to generate carbon monoxide at the boundary between the solid metal and the remaining molten metal during solidification, resulting in an outer layer low in carbon.

semikilled steel, *n*—an incompletely deoxidized **steel** that contained sufficient oxygen to form enough entrapped carbon monoxide during solidification to offset solidification shrinkage.

specified element, *n*—*in steel*, an element controlled to a specified minimum, maximum, or range, in accordance with the requirements of the applicable product specification.

stabilized stainless steel, *n*—a **stainless steel** that conforms to a specification that prescribes limits (minimum or range) for niobium (columbium), tantalum, titanium, or a combination thereof.

Discussion—Such limits are sometimes expressed as a function of the carbon and nitrogen contents. In an appropriately annealed condition, a **stabilized stainless steel** will resist sensitization to intergranular corrosion associated with the precipitation of chromium carbide at grain boundaries as a result of thermal exposure, such as **annealing, stress relieving**, welding, or high temperature service. Resistance to sensitization to intergranular corrosion is dependent upon the corrosivity of the environment. The condition of being stabilized with respect to sensitization is frequently demonstrated by passing one or more standard corrosion tests for sensitization.

stainless steel, *n*—a **steel** that conforms to a specification that requires, by mass percent, a minimum chromium content of 10.5 or more, and a maximum carbon content of less than 1.20.

steel, *n*—a material that conforms to a specification that requires, by mass percent, more iron than any other element and a maximum carbon content of generally less than 2.

Discussion—The iron content requirement is not normally stated in the specification and is not normally determined by chemical analysis, but is taken to be 100 % minus the sum of the mean values permitted by the specification for all other elements having a specified range or a specified maximum. For conformance purposes, this calculated value for iron is compared on an individual basis to the mean values permitted by the specification for each of the other elements having a specified range or a specified maximum. Some chromium-containing steels may contain more than 2 % carbon; however, 2 % carbon is generally considered to be the demarcation between **steel** and cast iron.

strain hardening, *n*—an increase in hardness and strength of a metal caused by plastic deformation at temperatures below its **recrystallization temperature**. (Syn. *work hardening*) **test record,** *n*—a document or electronic record that contains

the observations and derived data obtained by applying a given test method.

test report, *n*—a document that presents the applicable qualitative or quantitative results obtained by applying one or more given test methods.

Discussion—A single document, containing test report information and certificate of compliance information, may be used.

unspecified element, *n*—*in steel*, an element not controlled to a specified minimum, maximum, or range, in accordance with the requirements of the applicable product specification

3.2 Definitions of Terms Relating to Heat Treatment of Steels:

 Ac_{cm} , Ac_1 , Ac_3 , Ac_4 —See transformation temperature.

 Ae_{cm} , Ae_1 , Ae_3 , Ae_4 —See transformation temperature.

age hardening, *n*—hardening by **aging**, usually after rapid cooling or **cold working**.

aging, *n*—a change in the properties of certain **steels** that occurs at ambient or moderately elevated temperatures after hot working or a heat treatment (**quench aging, natural aging,** or **artificial aging**) or after a cold-working operation

(strain aging).

Discussion—The change in properties is often, but not always, due to **precipitation hardening**, but never involves a change in the chemical composition of the **steel**.

annealing, *n*—a generic term covering any of several **heat treatments**.

Discussion—This treatment is used for purposes such as reducing hardness, improving machinability, facilitating **cold working**, producing a desired microstructure, or obtaining desired mechanical, physical, or other properties. Where applicable, it is preferred that the following more specific terms be used: **black annealing, box annealing, bright annealing, flame annealing, full annealing, graphitization annealing, intermediate annealing, isothermal annealing, process annealing, quench annealing, recrystallization annealing, spheroidizing, and subcritical annealing**. The term "annealing," without qualification, implies **full annealing**. Any process of **annealing** will usually reduce stresses; however, if the treatment is applied for the sole purpose of stress reduction, it should be designated **stress relieving**.

 Ar_{cm} , Ar_1 , Ar_3 , Ar_4 —See transformation temperature. artificial aging, n—aging above room temperature.

austempering, n—heat treatment involving quenching a steel object from a temperature above the transformation range in a medium maintained at a temperature above the martensite range sufficiently fast to avoid the formation of high temperature transformation products, and then holding it at that temperature until transformation is complete.

austenitizing, n—forming austenite by heating a steel object above the **transformation range**.

baking, *n*—heating to a low temperature in order to remove gases.

batch furnace, n—a heating device within which steel objects

are held stationary or oscillated during the thermal processing cycle.

black annealing, *n*—**box annealing** steel sheet, strip, or wire. **blank carburizing,** *n*—simulating the **carburizing** operation without introducing carbon.

DISCUSSION—This is usually accomplished by using an inert material in place of the carburizing agent, or by applying a suitable protective coating on the object being heat treated.

blank nitriding, *n*—simulating the nitriding operation without introducing nitrogen.

DISCUSSION—This is usually accomplished by using an inert material in place of the nitriding agent, or by applying a suitable protective coating on the object being heat treated.

bluing, *n*—subjecting the scale-free surface of a steel object to the action of air, steam, or other agents at a suitable temperature, thereby forming a thin blue film of oxide and improving the object's appearance and corrosion resistance.

DISCUSSION—This term is ordinarily applied to sheet, strip, or finished parts. It is used also to denote the heating of springs after fabrication in order to improve their properties.

box annealing, *n*—**annealing** in a sealed container under conditions that minimize oxidation.

Discussion—The charge is usually heated slowly to a temperature below the **transformation range**, but sometimes above or within it, and is then cooled slowly.

- **bright annealing,** *n*—**annealing** in a protective medium to prevent discoloration of the bright surface.
- **carbon potential,** *n*—the carbon content at the surface of a specimen of pure iron in equilibrium with the carburizing medium considered, and under the conditions specified.
- **carbon restoration,** *n*—replacing the carbon lost from the surface layer in previous processing by carburizing this layer to substantially the original carbon level.
- **carbonitriding,** *n*—**case hardening** in which a suitable steel object is heated above Ac₁ in a gaseous atmosphere of such composition as to cause simultaneous absorption of carbon and nitrogen by the surface and, by diffusion, to create a concentration gradient.
- **carburizing,** *n*—a process in which an austenitized steel object is brought into contact with a carbonaceous environment of sufficient carbon potential to cause absorption of carbon at the surface and, by diffusion, to create a concentration gradient.
- case, n—in case hardening, the outer portion that has been made harder than the core as a result of altered composition or microstructure, or both, from treatments such as carburizing, nitriding, and induction hardening.
- **case hardening,** *n*—a generic term covering any of several processes applicable to **steel** that change the chemical composition or microstructure, or both, of the surface layer.

DISCUSSION—The processes commonly used are: **carburizing** and **quench hardening**; **cyaniding**; **nitriding**; and **carbonitriding**. It is preferred that the applicable specific process name be used.

cementation, *n*—the introduction of one or more elements into the outer portion of a steel object by means of diffusion at high temperature.

- **cold treatment,** *n*—exposing a steel object to temperatures below room temperature for the purpose of obtaining desired conditions or properties, such as dimensional or structural stability.
- **conditioning heat treatment,** *n*—a preliminary **heat treatment** used to prepare a steel object for a desired reaction to a subsequent **heat treatment**.
- **continuous-conveyance furnace**, *n*—a heating device through which steel objects are intentionally moved at a constant rate during the thermal processing cycle.
- **controlled cooling,** *n*—cooling a steel object from an elevated temperature in a predetermined manner to avoid hardening, cracking, or internal damage, or to produce a desired microstructure or mechanical properties.
- **core,** *n*—*in case hardening,* the interior portion of unaltered composition or microstructure, or both, of a case hardened steel object.
- **core,** *n*—*in clad products*, the central portion of a multilayer composite metallic material.
- **critical cooling rate,** n—the slowest rate of continuous cooling at which austenite can be cooled from above the **transformation range** to prevent its transformation above M_s .
- **cyaniding,** *n*—introducing carbon and nitrogen into a solid steel object by holding it above Ac₁ in contact with molten cyanide of suitable composition.
- **cycle annealing,** *n*—**annealing** employing a predetermined and closely controlled time-temperature cycle to produce specific properties or a specific microstructure.
- **decarburization,** *n*—the loss of carbon from the surface of a steel object as a result of its being heated in a medium that reacts with the carbon.
- **differential heating,** *n*—heating that intentionally produces a temperature gradient within a steel object such that, after cooling, a desired stress distribution or variation in properties is present within the object.
- **diffusion coating,** *n*—any process whereby a base metal is either coated with another metal and heated to a sufficient temperature in a suitable environment, or exposed to a gaseous or liquid medium containing the other metal, thereby causing diffusion of the coating or other metal into the base metal, with a resultant change in the composition and properties of its surface.
- **direct quenching,** *n*—*in thermochemical processing*, **quenching** immediately following the thermochemical treatment.
- **double aging,** *n*—employment of two different aging treatments, in sequence, to control the type of precipitate formed from a supersaturated alloy matrix in order to obtain the desired properties.

DISCUSSION—the first aging treatment, sometimes referred to as intermediate or stabilizing, is usually carried out at a higher temperature than the second.

double tempering, *n*—a treatment in which a quench-hardened steel object is given two complete tempering cycles at substantially the same temperature for the purpose of ensuring completion of the tempering reaction and promoting stability of the resultant microstructure.

- **ferritizing anneal,** *n*—a **heat treatment** that produces a predominantly ferritic matrix in a steel object.
- **flame annealing,** *n*—**annealing** in which the heat is applied directly by a flame.
- **flame hardening,** *n*—a process in which only the surface layer of a suitable steel object is heated by flame to above Ac₃ or Ac_{cm}, and then the object is **quenched**.
- **fog quenching,** *n*—**quenching** in a mist.
- **full annealing,** n—**annealing** a steel object by **austenitizing** it and then cooling it slowly through the **transformation** range.
 - Discussion—The austenitizing temperature is usually above Ac_3 for hypoeutectoid steels and between Ac_1 and $Ac_{\rm cm}$ for hypereutectoid steels.
- **grain growth**, *n*—an increase in the grain size of a steel object, usually as a result of exposure to elevated temperatures.
- **graphitization annealing,** *n*—**annealing** a steel object in such a way that some or all of the carbon is precipitated as graphite.
- **hardenability**, *n*—the property that determines the depth and distribution of hardness induced by **quenching** a steel object.
- **hardening,** *n*—increasing the hardness by suitable treatment, usually involving heating and cooling.
 - Discussion—Where applicable, it is preferred that the following more specific terms be used: **age hardening**, **case hardening**, **flame hardening**, **induction hardening**, **precipitation hardening**, and **quench hardening**.
- **heat treatment,** *n*—heating and cooling a steel object in such a way as to obtain desired conditions or properties.
 - Discussion—Heating for the sole purpose of hot working is excluded from the meaning of this definition.
- **homogeneous carburizing,** *n*—a process that converts a low-carbon steel to one of substantially uniform and higher carbon content throughout the section, so that a specific response to **hardening** may be obtained.
- **homogenizing,** *n*—holding a steel object at high temperature to eliminate or decrease chemical segregation by diffusion.
- **hot quenching,** *n*—an imprecise term used to cover a variety of quenching procedures in which the quenching medium is maintained at a prescribed temperature above 160°F or 70°C.
- **induction hardening,** n—in surface hardening, a process in which only the surface layer of a suitable steel object is heated by electrical induction to above Ac_3 or Ac_{cm} , and then the object is **quenched**.
- **induction hardening,** *n*—*in through hardening*, a process in which a suitable steel object is heated by electrical induction to above Ac₃ or Ac_{cm} throughout its section, and then the object is **quenched**.
- **induction heating,** *n*—heating by electrical induction.
- **intermediate annealing,** *n*—**annealing** wrought steel objects at one or more stages during manufacture prior to final thermal treatment.
- **interrupted aging,** *n*—**aging** at two or more temperatures, by steps, and cooling to room temperature after each step.
- interrupted quenching, n—quenching in which the object

- being quenched is removed from the quenching medium while the object is at a temperature substantially higher than that of the quenching medium.
- **isothermal annealing,** *n*—**austenitizing** a steel object and then cooling it to, and holding it at, a temperature at which austenite transforms to a ferrite-carbide aggregate.
- **isothermal transformation,** *n*—a change in phase at any constant temperature.
- M_f , M_s —See transformation temperature.
- **maraging,** *n*—a precipitation hardening treatment applied to a special group of **alloy steels** to precipitate one or more intermetallic compounds in a matrix of essentially carbon-free martensite.
- martempering, *n*—quenching an austenitized steel object in a medium at a temperature in the upper part of, or slightly above, the martensite range, holding it in the medium until its temperature is substantially uniform throughout, and then cooling it in air through the martensite range.
- martensite range, n—the temperature interval between M_s and M_f .
- **natural aging,** *n*—spontaneous aging of a super-saturated solid solution at room temperature.
- **nitriding,** *n*—introducing nitrogen into a solid steel object by holding it at a suitable temperature in contact with a nitrogenous environment.
- **normalizing,** *n*—heating a steel object to a suitable temperature above the **transformation range** and then cooling it in air to a temperature substantially below the **transformation range**.
- **overaging**, *n*—**aging** under conditions of time and temperature greater than those required to obtain maximum change in a certain property, so that the property is altered away from the maximum.
- **overheating**, *n*—heating a steel object to such a high temperature that excessive grain growth occurs.
 - Discussion—Unlike burning, it may be possible to restore the original properties/microstructure by further heat treatment or mechanical working, or a combination thereof.
- **patenting,** *n*—*in wire making,* heating a medium-carbon or high-carbon steel before wire drawing, or between drafts, to a temperature above the **transformation range**, and then cooling it in air, or a bath of molten lead or salt, to a temperature below Ae₁.
- **post-weld heat treatment,** *n*—heating weldments immediately after welding, to provide **tempering**, **stress relieving**, or a controlled rate of cooling to prevent formation of a hard or brittle microstructure.
- **precipitation hardening,** *n*—**hardening** caused by the precipitation of a constituent from a supersaturated solid solution
- **precipitation heat treatment,** *n*—**artificial aging** in which a constituent precipitates from a supersaturated solid solution.
- **preheating,** *n*—*for tool steels*, heating to an intermediate temperature immediately before final **austenitizing**.
- **preheating,** *n*—heating before welding, a mechanical treatment, or some further thermal treatment.

- **process annealing,** *n*—*in the sheet and wire industries*, heating a steel object to a temperature close to, but below, Ac₁ and then cooling it, in order to soften it for further cold working.
- **progressive aging,** n—**aging** by increasing the temperature in steps, or continuously, during the aging cycle.
- **quench aging,** *n*—**aging** associated with **quenching** after **solution heat treatment**.
- **quench annealing**, *n*—**annealing** an austenitic steel object by **solution heat treatment**.
- **quench hardening,** *n*—**hardening** a steel object by **austenitizing** it, and then cooling it rapidly enough that some or all of the austenite transforms to martensite.

Discussion—The austenitizing temperature is usually above ${\rm Ac_3}$ for hypoeutectoid steels and between ${\rm Ac_1}$ and ${\rm Ac_{cm}}$ for hypereutectoid steels.

quenching, *n*—rapid cooling.

Discussion—Where applicable, it is preferred that the following more specific terms be used: **fog quenching, hot quenching, interrupted quenching, selective quenching, spray quenching,** and **time quenching**.

recrystallization, *n*—the formation of a new grain structure through a nucleation and growth process.

Discussion—This is commonly produced by subjecting a steel object, which may be strained, to suitable conditions of time and temperature.

- **recrystallization annealing,** *n*—**annealing** a cold-worked steel object to produce a new grain structure without a change in phase.
- **recrystallization temperature,** *n*—the approximate minimum temperature at which recrystallization of a cold-worked steel object occurs within a specified time.
- **secondary hardening,** *n*—the hardening phenomenon that occurs during high-temperature **tempering** of certain **steels** containing one or more carbide-forming alloying elements.
- **selective heating,** *n*—intentionally heating only certain portions of a steel object.
- **selective quenching,** *n*—**quenching** only certain portions of a steel object.
- **semicontinuous-conveyance furnace,** *n*—a heating device through which steel objects are intentionally moved in accordance with a predetermined start-stop-start pattern during the thermal processing cycle.
- **shell hardening**, *n*—a surface hardening process in which a suitable steel object, when heated through and quench hardened, develops a martensitic layer or shell that closely follows the contour of the piece and surrounds a **core** of essentially pearlitic transformation product.

Discussion—This result is accomplished by a proper balance between section size, **hardenability**, and severity of quench.

slack quenching, *n*—the incomplete **hardening** of a steel object due to **quenching** from the austenitizing temperature at a rate slower than the **critical cooling rate** for the particular steel composition, resulting in the formation of one or more transformation products in addition to martensite.

- snap temper, n—a precautionary interim stress-relieving treatment applied to a high-hardenability steel immediately after quenching to prevent cracking because of delay in tempering it at the prescribed higher temperature.
- **soaking,** *n*—prolonged holding at a selected temperature.
- **solution heat treatment,** *n*—heating a steel object to a suitable temperature, holding it at that temperature long enough to cause one or more constituents to enter into solid solution, and then cooling it rapidly enough to hold such constituents in solution.
- **spheroidizing,** *n*—heating and cooling a steel object to produce a spheroidal or globular form of carbide in its microstructure.

Discussion—Spheroidizing methods commonly used are the following: (1) prolonged holding at a temperature just below Ae_1 ; (2) heating and cooling alternately between temperatures that are just above, and just below, Ae_1 ; (3) heating to a temperature above Ae_1 or Ae_3 and then cooling very slowly in the furnace or holding at a temperature just below Ae_1 ; (4) cooling, from the minimum temperature at which all carbide is dissolved, at a rate suitable to prevent the reformation of a carbide network, and then reheating in accordance with Method (1) or (2) above. (Applicable to hypereutectoid steels containing a carbide network.)

spray quenching, *n*—**quenching** in a spray of liquid.

stabilizing treatment, *n*—any treatment intended to stabilize the microstructure or dimensions of a steel object.

strain aging, *n*—**aging** induced by cold working.

- **stress relieving,** *n*—heating a steel object to a suitable temperature, holding it long enough to reduce residual stresses, and then cooling it slowly enough to minimize the development of new residual stresses.
- **subcritical annealing,** n—**annealing** at a temperature slightly below Ac_1 .
- **surface hardening**, *n*—a generic term covering any of several processes that, by **quench hardening** only, produce in a steel object a surface layer that is harder or more wear resistant than the **core**.

Discussion—There is no significant alteration of the chemical composition of the surface layer. Where applicable, it is preferred that the following more specific terms be used: **induction hardening, flame hardening**, and **shell hardening**.

- **temper brittleness,** *n*—brittleness that results when certain **steels** are held within, or are cooled slowly through, a certain range of temperature below the **transformation range**.
- **tempering,** *n*—reheating a quench hardened or normalized steel object to a temperature below Ac₁, and then cooling it at any desired rate.
- thermochemical treatment, *n*—a heat treatment carried out in a medium suitably chosen to produce a change in the chemical composition of the steel object by exchange with the medium.
- **time quenching,** *n*—interrupted **quenching** in which the duration of holding in the quenching medium is controlled.
- **transformation ranges,** *n*—those ranges of temperature within which austenite forms during heating and transforms during cooling.

Discussion—The two ranges are distinct, sometimes overlapping but never coinciding. The limiting temperatures of the ranges are dependent upon the steel composition and the rate of change of temperature, particularly during cooling.

transformation temperature, n—the temperature at which a change in phase occurs, with the limiting temperatures of the transformation ranges designated using the following symbols:

 Ac_{cm} —the temperature at which the solution of cementite in austenite is completed during heating.

 Ac_1 —the temperature at which austenite begins to form during heating.

Ac₃—the temperature at which transformation of ferrite to austenite is completed during heating.

Ac₄—the temperature at which austenite transforms to delta ferrite during heating.

Ae₁, Ae₃, Ae_{cm}, Ae₄—the temperatures of phase change at equilibrium.

 Ar_{cm} —the temperature at which precipitation of cementite starts during cooling.

Ar₁—the temperature at which transformation of austenite to ferrite or to ferrite plus cementite is completed during cooling.

Ar₃—the temperature at which austenite begins to transform to ferrite during cooling.

Ar₄—the temperature at which delta ferrite transforms to austenite during cooling.

M_f—the temperature at which transformation of austenite to martensite is substantially completed during cooling.

 $\rm M_s$ —the temperature at which transformation of austenite to martensite starts during cooling.

Discussion—All of the above changes, except the formation of martensite, occur at lower temperatures during cooling than during heating, and are dependent upon the rate of change of temperature.

SUMMARY OF CHANGES

Committee A01 has identified the location of selected changes to this standard since the last issue (A 941 - 01) that may impact the use of this standard.

- (1) Changed "columbium (niobium)" to "niobium (columbium)" in 3.1.
- (2) Added a definition for microalloyed steel in 3.1.
- (3) Revised the definition for heat analysis by adding a discussion section in 3.1.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every ve years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).

Appendix

10

ASTM E 527-83 (2003) STANDARD PRACTICE FOR NUMBERING METALS AND ALLOYS (UNS)



Designation: E 527 - 83 (Reapproved 2003)

Standard Practice for Numbering Metals and Alloys (UNS)¹

This standard is issued under the fixed designation E 527; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This practice (Note 1) covers a unified numbering system (UNS) for metals and alloys that have a "commercial standing" (see Note 2), and covers the procedure by which such numbers are assigned. Section 2 describes the system of alphanumeric designations or "numbers" established for each family of metals and alloys. Section 3 outlines the organization established for administering the system. Section 4 describes the procedure for requesting number assignment to metals and alloys for which UNS numbers have not previously been assigned.

Note 1—UNS designations shall not be used for metals and alloys that are not registered under the system described herein, or for any metal or alloy whose composition differs from those registered.

Note 2—The terms "commercial standing," "production usage," and others are intended to portray a material in active industrial use, although the actual amount of such use will depend, among other things, upon the type of materials. (Obviously gold will not be used in the same "tonnages" as hot-rolled steel.)

Different standardizing groups use different criteria to define the status that a material has to attain before a standard number will be assigned to it. For instance, the American Iron and Steel Institute requires for stainless steels "two or more producers with combined production of 200 tons per year for at least two years'"; the Copper Development Association requires that the material be "in commercial use (without tonnage limits)"; the Aluminum Association requires that the alloy be "offered for sale (not necessarily in commercial use)"; the SAE Aerospace Materials Division calls for "repetitive procurement by at least two users."

While it is apparent that no hard and fast usage definition can be set up for an all-encompassing system, the UNS numbers are intended to identify metals and alloys that are in more or less regular production and use. A UNS number will not ordinarily be issued for a material that has just been conceived or that is still in only experimental trial.

1.2 The UNS provides a means of correlating many nationally used numbering systems currently administered by societies, trade associations, and individual users and producers of metals and alloys, thereby avoiding confusion caused by use of

more than one identification number for the same material; and by the opposite situation of having the same number assigned to two or more entirely different materials. It also provides the uniformity necessary for efficient indexing, record keeping, data storage and retrieval, and cross referencing.

1.3 A UNS number is not in itself a specification, since it establishes no requirements for form, condition, quality, etc. It is a unified identification of metals and alloys for which controlling limits have been established in specifications published elsewhere.

Note 3—Organizations that issue specifications should report to appropriate UNS number-assigning offices (3.1.2) any specification changes that affect descriptions shown in published UNS listings.

2. Description of Numbers (or Codes) Established for Metals and Alloys

- 2.1 The unified numbering system (UNS) establishes 18 series of numbers for metals and alloys, as shown in Table 1. Each UNS number consists of a single letter-prefix followed by five digits. In most cases the letter is suggestive of the family of metals identified; for example, A for aluminum, P for precious metals, and S for stainless steels.
- 2.2 Whereas some of the digits in certain UNS number groups have special assigned meaning, each series is independent of the others in such significance; this practice permits greater flexibility and avoids complicated and lengthy UNS numbers.

Note 4—This arrangement of alphanumeric six-character numbers is a compromise between the thinking that identification numbers should indicate many characteristics of the material, and the belief that numbers should be short and uncomplicated to be widely accepted and used.

2.3 Wherever feasible, identification "numbers" from existing systems are incorporated into the UNS numbers. For example: carbon steel, presently identified by AISI 1020 (American Iron and Steel Institute), is covered by "UNS G 10200"; and free cutting brass, presently identified by CDA (Copper Development Association C 36000), is covered by "UNS C 36000." Table 2 shows the secondary division of some primary series of numbers.

¹ This practice is under the jurisdiction of ASTM Committee A01 on Steel, Stainless Steel and Related Alloys and is the direct responsibility of Subcommittee A01.91 on Editorial.

Current edition approved Apr. 10, 2003. Published May 2003. Originally approved in 1974. Last previous edition approved in 1997 as $\to 527-83 \ (1997)^{e1}$.

TABLE 1 Primary Series of Numbers

	•
Nonferrous Metals and Alloys	
A00001-A99999	aluminum and aluminum alloys
C00001-C99999	copper and copper alloys
E00001-E99999	rare earth and rare earth-like metals and alloys (18
	items; see Table 2)
L00001-L99999	low melting metals and alloys (15 items; see Table 2)
M00001-M99999	miscellaneous nonferrous metals and alloys (12 items; see Table 2)
N00001-N99999	nickel and nickel alloys
P00001-P99999	precious metals and alloys (8 items; see Table 2)
R00001-R99999	reactive and refractory metals and alloys (14 items; see
	Table 2)
Z00001–Z99999	zinc and zinc alloys
Ferrous Metals and Alloys	
D00001-D99999	speci ed mechanical properties steels
F00001-F99999	cast irons and cast steels
G00001-G99999	AISI and SAE carbon and alloy steels
H00001-H99999	AISI H-steels
J00001-J99999	cast steels (except tool steels)
K00001-K99999	miscellaneous steels and ferrous alloys
S00001-S99999	heat and corrosion resistant (stainless) steels
T00001-T99999	tool steels
Specialized Metals and Alloys	
W00001-W99999	welding ller metals, covered and tubular electrodes,
	classi ed by weld deposit composition (see Table 2)

TABLE 2 Secondary Division of Some Series of Numbers

E00001–E99999 Rare Earth and Rare Earth-Like Metals and Alloys		
E00000-E00999	actinium	
E01000-E20999	cerium	
E21000-E45999	mixed rare earths ^A	
E46000-E47999	dysprosium	
E48000-E49999	erbium	
E50000-E51999	europium	
E52000-E55999	gadolinium	
E56000-E57999	holmium	
E58000-E67999	lanthanum	
E68000–E68999	lutetium	
E69000–E68999 E69000–E73999		
	neodymium	
E74000–E77999	praseodymium	
E78000-E78999	promethium	
E79000-E82999	samarium 	
E83000-E84999	scandium	
E85000-E86999	terbium	
E87000-E87999	thulium	
E88000-E89999	ytterbium	
E90000-E99999	yttrium	
F00001–F9999 Cast Irons K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L99999 Low-Melting Metals and Alloys		
K00001–K99999 Miscellaneous Steels and Ferrous Alloys	h i o ma u th	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L99999 Low-Melting Metals and Alloys L00001–L00999	bismuth	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L99999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999	cadmium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L99999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999	cadmium cesium	
L00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L99999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999	cadmium cesium gallium	
L00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L99999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999	cadmium cesium gallium indium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L09999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999	cadmium cesium gallium indium lead	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L09999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L05999	cadmium cesium gallium indium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L09999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999	cadmium cesium gallium indium lead	
L00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L09999 Low-Melting Metals and Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L05999	cadmium cesium gallium indium lead lithium	
L00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L06999 L07001–L07999	cadmium cesium gallium indium lead lithium mercury	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L06999 L07001–L07999 L08001–L07999 L08001–L08999	cadmium cesium gallium indium lead lithium mercury potassium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L06999 L07001–L07999 L08001–L08999 L09001–L08999	cadmium cesium gallium indium lead lithium mercury potassium rubidium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L05999 L05001–L05999 L07001–L07999 L08001–L08999 L09001–L08999 L09001–L09999 L10001–L109999	cadmium cesium gallium indium lead lithium mercury potassium rubidium selenium	
C00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L06999 L07001–L07999 L08001–L08999 L09001–L08999 L09001–L09999 L10001–L109999 L11001–L119999	cadmium cesium gallium indium lead lithium mercury potassium rubidium selenium sodium	
L00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L06999 L07001–L07999 L08001–L08999 L10001–L10999 L11001–L11999 L11201–L12999 L13001–L12999	cadmium cesium gallium indium lead lithium mercury potassium rubidium selenium sodium thallium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L06001–L06999 L07001–L07999 L08001–L09999 L10001–L109999 L11001–L11999 L11001–L11999	cadmium cesium gallium indium lead lithium mercury potassium rubidium selenium sodium thallium	
L00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L01001–L01999 L02001–L02999 L03001–L03999 L05001–L05999 L05001–L06999 L07001–L07999 L08001–L08999 L09001–L09999 L10001–L10999 L11001–L11999 L12001–L12999 L13001–L13999 M00001–M99999 Miscellaneous Nonferrous Metals and Alloys	cadmium cesium gallium indium lead lithium mercury potassium rubidium selenium sodium thallium	
K00001–K99999 Miscellaneous Steels and Ferrous Alloys L00001–L00999 L01001–L01999 L01001–L01999 L02001–L02999 L03001–L03999 L04001–L04999 L05001–L05999 L07001–L07999 L07001–L07999 L08001–L08999 L09001–L09999 L11001–L11999 L11001–L11999 L12001–L12999 L13001–L13999 M00001–M99999 Miscellaneous Nonferrous Metals and Alloys M00001–M00999	cadmium cesium gallium indium lead lithium mercury potassium rubidium selenium sodium thallium tin	

TABLE 2 Continued

TABLE 2 Continued	
M04001-M04999	germanium
M05001-M05999	plutonium
M06001-M06999	strontium
M07001-M07999	tellurium
M08001-M08999	uranium
M10001-M19999	magnesium
M20001-M29999	manganese
M30001-M39999	silicon
P00001-P99999 Precious Metals and Alloys	
P00001-P00999	gold
P01001–P01999	iridium
P02001-P02999	osmium
P03001–P03999	palladium
P04001-P04999	platinum
P05001-P05999	rhodium
P06001-P06999	ruthenium
P07001-P07999	silver
R00001–R99999 Reactive and Refractory Metals and Alloys	
R01001–R01999	boron
R02001-R02999	hafnium
R03001-R03999	molybdenum
R04001-R04999	niubium (columbium)
R05001–R05999	tantalum
R06001-R06999	thorium
R07001–R07999	tungsten
R08001-R08999	vanadium
R10001–R19999	beryllium
R20001-R29999	chromium
R30001–R39999	cobalt
R40001–R49999	rhenium
R50001–R59999	titanium
R60001–R69999	zirconium
W00001-W99999 Welding Filler Metals Classi ed by Weld Deposit	
Composition	
W00001-W09999	carbon steel with no signi cant alloying elements
W10000-W19999	manganese-molybdenum low alloy steels
W20000-W29999	nickel low alloy steels
W30000-W39999	austenitic stainless steels
W40000–W49999	ferritic stainless steels
W50000-W59999	chromiun low alloy steels
W60000-W69999	copper base alloys
W70000-W79999	surfacing alloys
W80000–W89999	nickel base alloys

A Alloys in which the rare earths are used in the ratio of their natural occurrence (that is, unseparated rare earths). In this mixture, cerium is the most abundant of the rare earth elements.

2.4 Welding filler metals fall into two general categories: those whose compositions are determined by the filler metal analysis (e.g. solid bare wire or rods and cast rods) and those whose composition is determined by the weld deposit analysis (e.g. covered electrodes, flux-cored and other composite wire electrodes). The latter are assigned to a new primary series with the letter W as shown in Table 1. The solid bare wire and rods continue to be assigned in the established number series according to their composition.

Z00001-Z99999 Zinc and Zinc Alloys

Note 5—Readers are cautioned *not* to make their own assignments of numbers from such listings, as this can result in unintended and unexpected duplication and conflict.

2.5 ASTM and SAE periodically publish up-to-date listings of all UNS numbers assigned to specific metals and alloys, with appropriate reference information on each.² Many trade

associations also publish similar listings related to materials of primary interest to their organizations.

3. Organization for Administering the UNS for Metals and Alloys

- 3.1 The organization for administering the UNS consists of the following:
- 3.1.1 Advisory Board—The Advisory Board has approximately 20 volunteer members who are affiliated with major producing and using industries, trade associations, government agencies, and standards societies, and who have extensive experience with identification, classification, and specification of materials. The Board is the administrative arm of SAE and ASTM on all matters pertaining to the UNS. It coordinates thinking on the format of each series of numbers and the administration of each by selected experts. It sets up ground rules for determining eligibility of any material for a UNS number, for requesting such numbers, and for appealing unfavorable rulings. It is the final referee on matters of disagreement between requesters and assigners.

² Request ASTM DS 56A and SAE Handbook Supplement HS 1086a, *Unified Numbering System for Metals and Alloys*, (a joint ASTM–SAE publication), PCN 05-056001-01.

- 3.1.2 Several Number-Assigning Offices— UNS number assigners for certain materials are set up at trade associations which have successfully administered their own numbering systems; for other materials, assigners are located at offices of SAE and ASTM. Each of these assigners has the responsibility for administering a specific series of numbers, as shown in Table 3. Each considers requests for assignment of new UNS numbers, and informs applicants of the action taken. Trade association UNS number assigners report immediately to both SAE and ASTM details of each number assignment. ASTM and SAE assigners collaborate with designated consultants when considering requests for assignment of new numbers.
- 3.1.3 Corps of Volunteer Consultants— Consultants are selected by the Advisory Board to provide expert knowledge of a specific field of materials. Since they are utilized primarily by the Board and the SAE and ASTM number assigners, they are not listed in this recommended practice. At the request of the

ASTM (or SAE) number assigner, a consultant considers a request for a new number in the light of the ground rules established for the material involved, decides whether a new number is justified, and informs the ASTM or the SAE number assigner accordingly. This utilization of experts (consultants and number assigners) is intended to ensure prompt and fair consideration of all requests. It permits each decision to be based on current knowledge of the needs of a specific industry of producers and users.

- 3.1.4 *Staffs at ASTM and SAE*—Staff members at SAE and ASTM maintain duplicate master listings of all UNS numbers assigned.
- 3.1.5 In addition, established SAE and ASTM committees which normally deal with standards and specifications for the materials covered by the UNS, and other knowledgeable persons, are called upon by the Advisory Board for advice

TABLE 3 Number Assigners and Areas of Responsibility

The Aluminum Association 818 Connecticut Ave. N.W. Washington, D.C. 20006

Attention: Office for Uni ed Numbering System for Metals

Telephone: (202)862-5100

American Iron and Steel Institute 1000 16th St., N.W. Washington, D.C. 20036 Attention: Office for United Numbering

Attention: Office for Uni ed Numbering System for Metals

Telephone: (202)452-7236

American Welding Society 550 N. W. LeJeune Road P.O. Box 351040 Miami, FL 33135

Attention: Office for Uni ed Numbering System for Metals

Telephone: (305)642-7090

Copper Development Association 405 Lexington Ave. New York, N. Y. 10017

Attention: Office for Uni ed Numbering System for Metals

Telephone: (212)953-7321

ASTM

100 Barr Harbor Drive West Conshohocken, Pa. 19428

Attention: Office for Uni ed Numbering System for Metals

Telephone: (610)832-9652

Aluminum and Aluminum Alloys UNS Number Series: A 00001-A 99999

Carbon and Alloy Steels
UNS Number Series: G 00001–G 99999

H-Steels

UNS Number Series: H 00001-H 99999

Tool Steels

UNS Number Series: T 00001-T 99999

Welding Filler Metals

UNS Number Series: W 00001-W 99999

Copper and Copper Alloys

UNS Number Series: C 00001-C 99999

Rare Earth and Rare Earth-Like Metals and Alloys

UNS Number Series: E 00001–E 99999

Low Melting Metals and Alloys

UNS Number Series: L 00001-L 99999 Miscellaneous Steels and Ferrous Alloys

UNS Number Series: K 00001-K 99999 Miscellaneous Nonferrous Metals and Alloys

UNS Number Series: M 00001–M 99999

Cast Steels

UNS Number Series: J 00001–J 99999 Heat and Corrosion Resistant (Stainless) Steels UNS Number Series: S 00001–S 99999

Zinc and Zinc Alloys

UNS Number Series: Z 00001-Z 99999

Precious Metals and Allovs

UNS Number Series: P 00001-P 99999

Cast Irons and Cast Steels

UNS Number Series: F 00001-F 99999

Nickel and Nickel Alloys

UNS Number Series: N 00001–N 99999 Steels Speci ed by Mechanical Properties UNS Number Series: D 00001–D 99999 Reactive and Refractory Metals and Alloys

UNS Number Series: R 00001-R 99999

Society of Automotive Engineers 400 Commonwealth Drive Warrendale, Pa. 15096

Attention: Office for Uni ed Numbering System for Metals

Telephone: (412)776-4841

when considering appeals from unfavorable rulings in the matter of UNS number assignments.

4. Procedure for Requesting Number Assignment to Metals and Alloys Not Already Covered by UNS Numbers (or Codes)

- 4.1 UNS numbers are assigned only to metals and alloys that have a commercial standing (as defined in Note 2).
- 4.2 The need for a new number should always be verified by determining from the latest complete listing of already assigned UNS numbers that a usable number is or is not available.

Note 6—In assigning UNS numbers, and consequently in searching complete listings of numbers, the predominant element of the metal or alloy usually determines the prefix letter of the series to which it is assigned. In certain instances where no one element predominates, arbitrary decisions are made as to what prefix letter to use, depending on the producing industry and other factors.

- 4.3 For a new UNS number to be assigned, the composition (or other properties, as applicable) must be significantly different from that of any metal or alloy which has already been assigned a UNS number.
- 4.3.1 In the case of metals or alloys that are normally identified or specified by chemical composition, the chemical composition limits must be reported.
- 4.3.2 In the case of metals or alloys that are normally identified or specified by mechanical (or other) properties, such properties and limits thereof must be reported. Only those chemical elements and limits, if any, which are significant in defining such materials need be reported.
- 4.4 Requests for new numbers shall be submitted on "Application for UNS Number Assignment" forms (see Fig. 1 and Fig. 2). Copies of these are available from any UNS number-assigning office (see Table 3) or facsimiles may be made of the one herein.

- 4.5 All instructions on the printed application form should be read carefully and all information provided as indicated.
- Note 7—The application form is designed to serve also as a data input sheet to facilitate processing each request through to final print-out of the data on electronic data-processing equipment and to minimize transcription errors at number-assigning offices and data-processing centers.
- 4.6 To further assist in assigning UNS numbers, the requester is encouraged to suggest a possible UNS number in each request, giving appropriate consideration to any existing number presently used by a trade association, standards society, producer, or user.
- 4.7 Each completed application form shall be sent to the UNS number-assigning office having responsibility for the series of numbers that appears to most closely relate to the material described on the form (see Table 3).

5. Keywords

5.1 aluminum alloy numbering system; aluminum alloy UNS numbering; cast iron numbering system; cast iron UNS numbering; copper alloy numbering system; copper alloy UNS numbering; ferrous alloys numbering system; ferrous alloys UNS numbering; nickel alloy numbering system; nickel alloy UNS numbering; reactive metals and alloys numbering system; reactive metals and alloys UNS numbering; refractory metals and alloys numbering system; refractory metals and alloys numbering; steel alloy numbering system; steel alloy UNS numbering; steel alloy numbering system; stainless steel alloy UNS numbering; unified numbering system; UNS metal and alloy numbering; unified numbering system; UNS metal and alloy numbering system; weld filler metal numbering; welding electrode numbering system; welding electrode UNS numbering

APPLICATION FOR UNS NUMBER ASSIGNMENT

and

Data Input Sheet for Entering a Specific Material in the SAE-ASTM Unified Numbering System for Metals and Alloys (See Reverse Side for Instructions for Completing This Form)

Material Descr	iption					
				1 I I I I I I I I I I I I I I I I I I I		
* UNS Assigne	d Description		Sugg	gested UNS No		
			* UN	NS Assigned No		
* Chemical Con	mposition					
Aluminum	Âl	Indium	In		Selenium	Se
Antimony	Sb	Iridium	Ir		Silicon	Si
Arsenic	As		Fe		Silver	Ag
Beryllium	Be	Lead	Pb		Sulfur	S
Bismuth	Bi	Lithium	Li		Tantalum	
Boron	В		Mg		Tellurium	Te
Cadmium	Cd	Manganese	Mn		Thorium	Th
Carbon	C	Mercury	Hg		Tin	Sn
Chromium	Cr	Molybdenum	Mo		Titanium	Ti
Cobalt	Co	Nickel	Ni		Tungsten	W
Columbium	Cb	Nitrogen	N		Uranium	U
Copper	Cu		0		Vanadium	V
Germanium	Ge		Р		Zinc	Zn
Gold	Au		Pt		Zirconium	Zr
Hafnium	Hf		Re		Other	
Hydrogen	Н		Rh			
* C D . C						
* Cross Referen	nces					
ACI						
-						
AISI						
ANSI						
AMS						
ASME						
ASTM						
AWS						
CDA _						
FED						
MIL SPEC						
SAE						
OTHERS _						
Requesting Per	rson and Organizati	on (full address)				
			ate of Rec			
* Assigning Or		*	Date of U	NS Assignment		
Assigner's Nan	ne and Office					

Applicant do not write in shaded areas.

* These items for Computer Operator.

Note—Reverse side of Fig. 1 is located on the next page.

FIG. 1 Sample Application Form.

General:

Before attempting to complete this form, the applicant should be thoroughly familiar with the objectives of the UNS and the "ground rules" for assigning numbers, as stated in SAE J 1086 and ASTM E 527, Section 4.

Material Description:

Identify the base element; the single alloying element that constitutes 50 % or more of the total alloy content; other distinguishing predominant characteristics (such as "casting"); and common or generic names if any (such as "ounce metal" or "Waspalloy"). When no single element makes up 50 % or more of the total alloy content, list in decreasing order of abundance the two alloying elements that together constitute the largest portion of the total alloy contents; except that if no two elements make up at least 50 % of the total alloy content, list the three most abundant, and so on. Instead of "iron," use "steel" to identify the base element of those iron-low-carbon alloys commonly known as steels.

When mechanical properties or physical characteristics are the primary defining criteria and chemical composition is secondary or nonsignificant, enter such properties and characteristics with the appropriate values or limits for each.

Suggested UNS No.:

While applicant's suggestion may or may not be the one finally assigned, it will assist proper identification of the material by the UNS Number Assigner.

Chemical Composition:

Enter limits such as 0.13-0.18 (not .13-.18, or 0.13 to 0.18), 1.5 max, 0.040 min, and balance. In space designated "other" enter information such as "Each 0.05 max, Total 0.15 max" and "Sn plus Pb 2.0 min."

Cross References:

Letter-symbols listed indicate widely known trade associations and standards-issuing organizations. Enter after appropriate symbols any known specification numbers or identification numbers issued by such groups to cover material equivalent to, similar to, or closely resembling the subject material.

Examples: SAE J 404 (50B44), AISI 415, ASTM A 638 (660)

In space designated "other" enter any pertinent numbers issued by groups not listed above. In these instances, the full name and address of the issuing group shall be included.

SUBMIT COMPLETED FORM TO APPROPRIATE UNS NUMBER ASSIGNER, AS LISTED IN SAE J 1086 AND ASTM E 527.

FIG. 2 Sample Application Form (Reverse Side).

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every ve years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).

Appendix

11

SI QUICK REFERENCE GUIDE

SI QUICK REFERENCE GUIDE: International System of Units (SI) The Modernized Metric System*

UNITS

The International System of Units (SI) is based on seven fundamental (base) units:

Base Units

Quantity	Name	Symbol	
length	metre	m	
mass	kilogram	kg	
time	second	s	
electric current	ampere	Α	
thermodynamic temperature	kelvin	K	
amount of substance	mole	mol	
luminous intensity	candela	cd	

and a number of derived units which are combinations of base units and which may have special names and symbols:

Examples of Derived Units

Quantity	Expression	Name	Symbol
acceleration			
angular	rad/s ²		
linear	m/s ²		
angle			
plane	dimensionless	radian	rad
solid	dimensionless	steradian	sr
area	m ²		
Celsius temperature	K	degree Celsius	°C
density		3	
heat flux	W/m ²		
mass	kg/m³		
current	A/m²		
energy, enthalpy			
work, heat	N∙m	joule	J
specific	J/kg	,	-
entropy	e,g		
heat capacity	J/K		
specific	J/(kg·K)		
flow, mass	kg/s		
flow, volume	m³/s		
force	kg⋅m/s²	newton	N
frequency	g		••
periodic	1/s	hertz	Hz
rotating	rev/s	110112	
inductance	Wb/A	henry	Н
magnetic flux	V·s	weber	Wb
mass flow	kg/s	Webei	***
moment of a force	N∙m		
potential, electric	W/A	volt	V
power, radiant flux	J/s	watt	w
pressure, stress	N/m ²	pascal	Pa
resistance, electric	V/A	ohm	Ω
thermal conductivity	W/(m⋅K)	Ollili	22
velocity	VV/ (111-1X)		
angular	rad/s		
linear	m/s		
viscosity	111/3		
	Pa⋅s		
dynamic (absolute)(μ)	m²/s		
kinematic (v) volume	m²/s m³		

volume, specific	m³/kg		

^{*}For complete information see IEEE/ASTM SI-10.

SI QUICK REFERENCE GUIDE

SYMBOLS

Symbol	Name	Quantity	Formula
A	ampere	electric current	base unit
Bq	becquerel	activity (of a radio nuclide)	1/s
C .	coulomb	electric charge	A∙s
°C	degree Celsius	temperature interval	°C = K
cd	candela	luminous intensity	base unit
F	farad	electric capacitance	C/V
Gy	gray	absorbed dose	J/kg
g	gram	mass	kg/1000
g H	henry	inductance	Wb/A
Hz	hertz	frequency	1/s
ha	hectare*	area	10 000 m ²
J	joule	energy, work, heat	N∙m
K	kelvin	temperature	base unit
kg	kilogram	mass	base unit
L	litre	volume	m ³ /1000
lm	lumen	luminous flux	cd·sr
lx	lux	illuminance	lm/m ²
m	metre	length	base unit
mol	mole	amount of substance	base unit
N	newton	force	kg·m/s ²
Ω	ohm	electric resistance	V/A
Pa	pascal	pressure, stress	N/m ²
rad	radian	plane angle	m/m (dimensionless)
S	siemens	electric conductance	A/V
Sv	sievert	dose equivalent	J/kg
S	second	time	base unit
sr	steradian	solid angle	m ² /m ² (dimensionless)
Т	tesla	magnetic flux density	Wb/m²
t	tonne, metric ton	mass	1000 kg; Mg
V	volt	electric potential	W/A
W	watt	power, radiant flux	J/s
Wb	weber	magnetic flux	V·s

^{*}allowed with SI

Use of Symbols

The correct use of symbols is important because an incorrect symbol may change the meaning of a quantity. Some SI symbols are listed in the Symbol table.

SI has no abbreviations—only symbols. Therefore, no periods follow a symbol except at the end of a sentence.

Examples: A, not amp; s, not sec; SI, not S.I.

Symbols appear in lower case unless the unit name has been taken from a proper name. In this case the first letter of the symbol is capitalized.

Examples: m, metre; Pa, pascal; W, watt

Exception: L, litre

Symbols and prefixes are printed in upright (roman) type regardless of the type style in surrounding text.

Example: ... a distance of 73 km between ...

Unit symbols are the same whether singular or plural.

Examples: 1 mm, 100 mm; 1 kg, 65 kg

Leave a space between the value and the symbol.

Examples: 115 W, not 115W; 0.75 L, not 0.75L

88 °C, not 88°C or 88° C

Exception: No space is left between the numerical value

and symbol for degree of plane angle.

Examples: 73°, not 73°

Note: Symbol for for coulomb is C; for degree Celsius it is °C

Do not mix symbols and names in the same expression.

Examples: radians per second or rad/s

not radians/second; not radians/s m/s or metres per second, not metres/second; not metres/s J/kg or joules per kilogram, not joules/kilogram; not joules/kg

Symbol for product—use the raised dot (•)

Examples: N·m; mPa·s; W/(m²·K)

Symbol for quotient—use one of the following forms:

Examples: m/s or $\frac{m}{s}$ or use negative exponent

Note: Use only one solidus (/) per expression and parentheses to avoid any ambiguity.

Do not use modifying terms such as electrical, alternating current, etc.

Examples: kPa (gage); MW (e); V (ac)

PREFIXES

Most prefixes indicate orders of magnitude in steps of 1000 and provide a convenient way to express large and small numbers and to eliminate nonsignificant digits and leading zeros in decimal fractions.

Examples: 64 000 watts is the same as 64 kilowatts*

0.057 metre is the same as 57 millimetres

16 000 metres is the same as 16 kilometres*

*except for intended accuracy

Prefix	Symbol	Represents	
yotta	Υ	1024	
zetta	Z	10 ²¹	
exa	E	10 ¹⁸	
peta	Р	10 ¹⁵	
tera	T	10 ¹²	
giga	G	10 ⁹	
mega	M	10 ⁶	
kilo	k	10 ³	
hecto	h*	10 ²	
deka	da*	10 ¹	
deci	d*	10 ⁻¹	
centi	C*	10 ⁻²	
milli	m	10 ⁻³	
micro	μ	10 ⁻⁶	
nano	n	10 ⁻⁹	
pico	p f	10 ⁻¹²	
femto	f	10 ⁻¹⁵	
atto	а	10 ⁻¹⁸	
zepto	Z	10 ⁻²¹	
yocto	у	10 ⁻²⁴	

To realize the full benefit of the prefixes when expressing a quantity by numerical value, choose a prefix so that the number lies between 0.1 and 1000. For simplicity, give preference to prefixes representing 1000 raised to an integral power (i.e., µm, mm, km).

*Exceptions:

In expressing area and volume, the prefixes hecto, deka, deci, and centi may by required; for example, cubic decimetre (L), square hectometre (hectare), cubic centimetre.

Tables of values of the same quantity.

Comparison of values.

For certain quantities in particular applications. For example, the millimetre is used for linear dimensions in architectural and engineering drawings even when the values lie far outside the range of 0.1 mm to 1000 mm; the centimetre is usually used for anatomical measurements and clothing sizes.

Compound units. A compound unit is a derived unit expressed with two or more units. The prefix is attached to a unit in the numerator.

Examples: V/m not mV/mm MJ/kg not kJ/g

Compound prefixes formed by a combination of two or more prefixes are not used. Use only one prefix.

Examples: 2 nm not 2 mµm

6 m³ not 6 kL 6 MPa not 6 kkPa **Exponential Powers.** An exponent attached to a symbol containing a prefix indicates that the multiple (of the unit with its prefix) is raised to the power of 10 expressed by the exponent.

Examples:
$$1 \text{ mm}^3 = (10^{-3} \text{ m})^3 = 10^{-9} \text{ m}^3$$

 $1 \text{ ns}^{-1} = (10^{-9} \text{ s})^{-1} = 10^9 \text{ s}^{-1}$
 $1 \text{ mm}^2/\text{s} = (10^{-3} \text{ m})^2/\text{s} = 10^{-6} \text{ m}^2/\text{s}$

NUMBERS

International practice separates the digits of large numbers into groups of three, counting from the decimal to the left and to the right, and inserts a space to separate the groups. In numbers of four digits, the space is not necessary except for uniformity in tables.

Examples: 6.358 568; 85 365; 51 845 953; 88 000;

 $0.246\ 113\ 562; 7\ 258$

Small Numbers. When writing numbers less than one, always put a zero before the decimal marker.

Example: 0.046

Decimal Marker. The recommended decimal marker is a dot on the line (period). (In some countries, a comma is used as the decimal marker.)

Because **billion** means a million million in most countries but a thousand million in the United States, avoid using billion in technical writing.

DO'S AND DON'TS

The units in the international system of units are called SI units not Metric Units and not SI Metric Units.

Non-SI units in the US are called Inch-Pound units (I-P units)—*not* conventional units, *not* U.S. customary units, *not* English units, and *not* Imperial units.)

Treat all spelled out names as nouns. Therefore, do not capitalize the first letter of a unit except at the beginning of a sentence or in capitalized material such as a title.

Examples: watt, pascal; ampere; volt, newton; kelvin *Exception*: Always capitalize the first letter of Celsius.

Do not begin a sentence with a unit symbol—either rearrange the words or write the unit name in full.

Use plurals for spelled out words when required by the rules of grammar.

Examples: metre—metres; henry—henries;

kilogram—kilograms; kelvin—kelvins

Irregular: hertz—hertz; lux—lux; siemens—siemens

Do not put a space or hyphen between the prefix and unit name.

Examples: kilometre not kilo metre or kilo-metre;

milliwatt not milli watt or milli-watt

SI QUICK REFERENCE GUIDE

When a prefix ends with a vowel and the unit name begins with a vowel, retain and pronounce both vowels.

Example: kiloampere

Exceptions: hectare; kilohm; megohm

When compound units are formed by multiplication, leave a space between units that are multiplied.

Examples: newton metre, not newton-metre;

volt ampere, not volt-ampere

Use the modifier squared or cubed after the unit name.

Example: metre per second squared

Exception: For area or volume the modifier may be placed

before the units.

Example: square millimetre; cubic metre

When compound units are formed by division, use the word *per*, not a solidus (/).

Examples: metre per second, not metre/second; watt per

square metre, not watt/square meter

Do not use modifying terms such as electrical, alternating current, etc. after the symbol.

Examples: kPa (gage); MW (e); V (ac)

SELECTED CONVERSION FACTORS

CAUTION: These conversion values are rounded to three or four significant figures, which is sufficiently accurate for most applications. When making conversions, remember that a converted value is no more precise than the original value. Round off the final value to the same number of significant figures as those in the original value. See ANSI SI 10 for additional conversions with more significant figures.

Multiply	Ву	To Obtain
acre	0.4047	ha
atmosphere, standard	*101.325	kPa
bar	*100	kPa
barrel (42 US gal, petroleum)	159	L
Btu, (International Table)	1.055	kJ
Btu / lb \cdot °F (specific heat, c^p)	4.184	kJ/(kg⋅K)
bushel	0.03524	m³
calorie, kilogram (kilocalorie)	4.187	kJ
candle, candlepower	*1.0	cd
centipoise, dynamic vicosity, µ	*1.00	mPa⋅s
centistokes, kinematic viscosity, v	*1.00	mm²/s
ft	*0.3048	m
ft	*304.8	mm
ft/min, fpm	*0.00508	m/s
ft/s, fps	*0.3048	m/s
ft of water	2.99	kPa
ft ²	0.09290	m^2
ft ² /s, kinematic viscosity, ν	92 900	mm²/s
ft ³	28.32	L
ft ³	0.02832	m^3
ft ³ /h, cfh	7.866	mL/s
ft ³ /min, cfm	0.4719	L/s
ft ³ /s, cfs	28.32	L/s
footcandle	10.76	lx
ft·lb _f (torque or moment)	1.36	N⋅m

Multiply	Ву	To Obtain
ft·lb _f (work)	1.36	J
ft·lb _f /lb (specific energy)	2.99	J/kg
ft·lb _f /min (power)	0.0226	W
gallon, US (*231 in ³)	3.785	L
gph	1.05	mL/s
gpm	0.0631	L/s
gpm/ft²	0.6791	L/(s·m²)
gr/gal	17.1	g/m³
horsepower (550 ft·lb _f /s)	0.746	kW
inch	*25.4	mm
in of mercury (60°F)	3.377	kPa
in of water (60°F)	248.8	Pa mN.m
in·lb _f (torque or moment) in ²	113 645	mN∙m mm²
in ³ (volume)	16.4	mL
in³ (section modulus)	16 400	mm ³
in (section modulus)	416 200	mm ⁴
km/h	0.278	m/s
kWh	*3.60	MJ
kip/in² (ksi)	6.895	MPa
litre	*0.001	m ³
micron (μm) of mercury (60°F)	133	mPa
mil (0.001 in.)	*25.4	μm
mile	1.61	km
mile, nautical	1.85	km
mph	1.61	km/h
mph	0.447	m/s
millibar	*0.100	kPa
mm of mercury (60°F)	0.133	kPa
mm of water (60°F)	9.80	Pa
ounce (mass, avoirdupois)	28.35	g
ounce (force of thrust)	0.278	N .
ounce (liquid, US)	29.6	mL
ounce (avoirdupois) per gallon	7.49	kg/m³
pint (liquid, US)	473	mL
pound	0.4526	ka
lb _m (mass) lb _m (mass)	0.4536 453.6	kg
lb_{f} (force or thrust)	4.45	g N
lb _m /ft (uniform load)	1.49	kg/m
$lb_{m}/(tt \cdot h)$ (dynamic viscosity, μ)	0.413	mPa⋅s
$lb_{m}/(ft \cdot s)$ (dynamic viscosity, μ)	1490	mPa·s
$lb_{f} \cdot s / ft^{2}$ (dynamic viscosity, μ)	47 880	mPa·s
lb _m /min	0.00756	kg/s
lb _m '''/h	0.126	g/s
lb _f / ft²	47.9	Pa
lb _m /ft ²	4.88	kg/m²
lb_{m}^{m}/ft^{3} (density, ρ)	16.0	kg/m³
lb _m /gallon	120	kg/m³
ppm (by mass)	*1.00	mg/kg
psi	6.895	kPa
quad (10 ¹⁵ Btu)	1.06	EJ
quart (liquid, US)	0.946	L .,
rpm	0.105	rad/s
tablespoon (approx.)	15	mL
teaspoon (approx.)	5	mL
therm (100,000 Btu)	105.5	MJ
ton, short (2000 lb) yd	0.907 *0.9144	Mg; t (tonne) m
yd²	0.836	m²
,~	5.70-0	
yd ³	0.7646	m ³

^{*}Conversion factor is exact.

Note: In this list the kelvin (K) expresses temperature intervals. The degree Celsius symbol ($^{\circ}$ C) may be used for this purpose as well.

STEEL GRADE/NAME INDEX

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
1	ASTM A 266/A 266M-03a	272, 275	1010 (continued)	ASTM A 513-03a	165, 166,
	ASTM A 333/A 333M-99	196, 198			167, 168, 169, 176,
	ASTM A 334/A 334M-99	196, 198			177, 178,
	ASTM A 485-03	435			179
	ASTM	360		ASTM A 576-90b (2000)	23
	A 487/A 487M-93 (2003)	070 075		SAE J403 NOV01	23
	ASTM A 508/A 508M-03a ASTM	273, 275	1011	ASTM A 29/A 29M-03	43
	A 537/A 537M-95 (2000)	105, 111		ASTM A 512-96 (2001)	170, 180
	ASTM	273, 275	1012	ASTM A 29/A 29M-03	23
	A 541/A 541M-95 (1999) ASTM A 735/A 735M-03	154		ASTM A 512-96 (2001)	166, 176, 177
10	ASTM A 333/A 333M-99	260		ASTM A 576-90b (2000)	23
10	ASTM	360		SAE J403 NOV01	23
	A 487/A 487M-93 (2003)	000	1013	ASTM A 29/A 29M-03	43
10 N14-M	AFNOR NF A 32-053:1992	359		SAE J403 NOV01	44
10 N19-M	AFNOR NF A 32-053:1992	359	1015	ASTM A 108-03	24
10 N6-M	AFNOR NF A 32-053:1992	359		ASTM A 29/A 29M-03	24
10 S 20	ISO 683-9:1988	420		ASTM A 512-96 (2001)	166, 177
10 SPb 20	ISO 683-9:1988	423		ASTM A 513-03a	166, 168,
100 [690]	ASTM A 709/A 709M-03a	82		7.01710.00	169, 170,
100 [690], Type A	ASTM A 709/A 709M-03a	86			177, 178,
100 [690], Type B	ASTM A 709/A 709M-03a	86			179
100 [690], Type C	ASTM A 709/A 709M-03a	86		ASTM A 576-90b (2000)	24
100 [690], Type E	ASTM A 709/A 709M-03a	87		SAE J403 NOV01	24
100 [690], Type F	ASTM A 709/A 709M-03a	87	1016	ASTM A 108-03	24
100 [690], Type H	ASTM A 709/A 709M-03a	87		ASTM A 29/A 29M-03	24
100 [690], Type J	ASTM A 709/A 709M-03a	87		ASTM A 512-96 (2001)	171, 181
100 [690], Type M	ASTM A 709/A 709M-03a	87		ASTM A 576-90b (2000)	24
100 [690], Type P	ASTM A 709/A 709M-03a	87		SAE J403 NOV01	24
100 [690], Type Q	ASTM A 709/A 709M-03a	87	1017	ASTM A 29/A 29M-03	24
1005	ASTM A 29/A 29M-03	23		ASTM A 576-90b (2000)	24
	SAE J403 NOV01	23		SAE J403 NOV01	24
1006	ASTM A 29/A 29M-03	23	1018	ASTM A 108-03	24
1000	SAE J403 NOV01	23		ASTM A 29/A 29M-03	24
1008	ASTM A 108-03	23		ASTM A 512-96 (2001)	171, 181
1000	ASTM A 100-03 ASTM A 29/A 29M-03	23		ASTM A 576-90b (2000)	24
	ASTM A 513-03a	165, 166,		SAE J403 NOV01	24
	A3 TW A 3 13-03a	168, 169,	1019	ASTM A 29/A 29M-03	24
		176, 177,		ASTM A 576-90b (2000)	24
		178, 179 [°]		SAE J403 NOV01	44
	ASTM A 576-90b (2000)	23	1020	ASTM A 108-03	25
	SAE J403 NOV01	23		ASTM A 29/A 29M-03	25
1009	SAE J403 NOV01	44		ASTM A 513-03a	167, 169,
100W [690W]	ASTM A 709/A 709M-03a	82			170, 171,
100W [690W], Type A	ASTM A 709/A 709M-03a	86			177, 179,
100W [690W], Type B	ASTM A 709/A 709M-03a	86		ACTM A 510 00	181
100W [690W], Type C	ASTM A 709/A 709M-03a	86		ASTM A 519-03	166, 167, 170, 171,
100W [690W], Type E	ASTM A 709/A 709M-03a	87			170, 171,
100W [690W], Type F	ASTM A 709/A 709M-03a	87			180, 181
100W [690W], Type H	ASTM A 709/A 709M-03a	87		ASTM A 576-90b (2000)	25
100W [690W], Type J	ASTM A 709/A 709M-03a	87		SAE J403 NOV01	25
100W [690W], Type M	ASTM A 709/A 709M-03a	87	1021	ASTM A 29/A 29M-03	25
100W [690W], Type P	ASTM A 709/A 709M-03a	87		ASTM A 513-03a	167, 169,
100W [690W], Type Q	ASTM A 709/A 709M-03a	87			171, 172,
1010	ASTM A 108-03	23			177, 178,
	ASTM A 29/A 29M-03	23			180, 181,
	ASTM A 512-96 (2001)	176		ASTM A 576-90b (2000)	182 25
	(/			SAE J403 NOV01	25 25
				OAL 0700 INO VUI	20

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
1022	ASTM A 108-03	25	1038	ASTM A 29/A 29M-03	27
	ASTM A 29/A 29M-03	25		ASTM A 576-90b (2000)	27
	ASTM A 576-90b (2000)	25		SAE J403 NOV01	27
	SAE J403 NOV01	25	1039	ASTM A 29/A 29M-03	28
1023	ASTM A 29/A 29M-03	25		ASTM A 576-90b (2000)	28
	ASTM A 576-90b (2000)	25		SAE J403 NOV01	28
	SAE J403 NOV01	25	1040	ASTM A 108-03	28
1025	ASTM A 108-03	26		ASTM A 29/A 29M-03	28
	ASTM A 29/A 29M-03	26		ASTM A 513-03a	170, 171,
	ASTM A 512-96 (2001)	172, 182			174, 180,
	ASTM A 513-03a	168, 170,			181, 183, 184
		171, 173, 178, 180,		ASTM A 576-90b (2000)	28
		181, 182		ASTM A 682/A 682M-02	425
	ASTM A 519-03	167, 168,		ASTM A 689-97 (2000)	425
		171, 173,		SAE J403 NOV01	28
		178, 181,	1042	ASTM A 29/A 29M-03	28
	A OTA A 570 00b (0000)	182		ASTM A 576-90b (2000)	28
	ASTM A 576-90b (2000)	26		SAE J403 NOV01	28
	SAE J403 NOV01	26	1043	ASTM A 29/A 29M-03	28
1026	ASTM A 29/A 29M-03	26		ASTM A 576-90b (2000)	28
	ASTM A 513-03a	169, 171,		SAE J403 NOV01	28
		173, 179, 181, 182,	1044	ASTM A 29/A 29M-03	29
		183		ASTM A 576-90b (2000)	29
	ASTM A 576-90b (2000)	26		SAE J403 NOV01	29
	SAE J403 NOV01	26	1045	ASTM A 108-03	29
1029	ASTM A 29/A 29M-03	26	1010	ASTM A 29/A 29M-03	29
	ASTM A 576-90b (2000)	26		ASTM A 519-03	170, 172,
	SAE J403 NOV01	26		7.6.17.0.00	174, 180,
102Cr6	EN 10132-4:2000	437			182, 183,
	ISO 4957:1999	438			184
1030	ASTM A 108-03	26		ASTM A 576-90b (2000)	29
	ASTM A 29/A 29M-03	26		ASTM A 682/A 682M-02	437
	ASTM A 512-96 (2001)	173, 183		SAE J403 NOV01	29
	ASTM A 513-03a	169, 171,	1046	ASTM A 29/A 29M-03	29
		173, 174,		ASTM A 576-90b (2000)	29
		179, 181,		SAE J403 NOV01	29
	ACTM A E76 00b (2000)	183	1049	ASTM A 29/A 29M-03	30
	ASTM A 576-90b (2000) ASTM A 682/A 682M-02	26 437		ASTM A 576-90b (2000)	30
		43 <i>7</i> 26		SAE J403 NOV01	30
1000	SAE J403 NOV01		1050	ASTM A 108-03	30
1033	SAE J403 NOV01	44		ASTM A 29/A 29M-03	30
1034 1035	ASTM A 100 03	27 27		ASTM A 519-03	171, 173,
1033	ASTM A 20/A 20M 02				174, 181, 182, 183
	ASTM A 29/A 29M-03	27		ASTM A 576-90b (2000)	30
	ASTM A 513-03a	170, 171, 173, 174,		ASTM A 682/A 682M-02	425
		180, 181,		ASTM A 689-97 (2000)	425
		183, 184		SAE J403 NOV01	30
	ASTM A 519-03	169, 170,	1053	ASTM A 29/A 29M-03	30
		173, 174,		ASTM A 576-90b (2000)	30
		179, 180,		SAE J403 NOV01	30
	ASTM A 576-90b (2000)	182, 183 27	1055	ASTM A 29/A 29M-03	31
	ASTM A 682/A 682M-02	437		ASTM A 576-90b (2000)	31
	SAE J403 NOV01	43 <i>7</i> 27		ASTM A 682/A 682M-02	425
1027				ASTM A 689-97 (2000)	425
1037	ASTM A 29/A 29M-03	27		ASTM A 713-04	425 425
	ASTM A 576-90b (2000)	27		SAE J403 NOV01	31
	SAE J403 NOV01	44	105-85	ASTM A 148/A 148M-03	322, 325
			100-00	AO I WI A 140/A 140/VI-US	JZZ, JZJ

556 Steel Grade/Name Index

Steel Grade/Name 1059	Specification Designation	Page 31	Steel Grade/Name	Specification Designation	Page 33
	ASTM A 29/A 29M-03	_	1095 (continued)	SAE J403 NOV01	
105V	ISO 4957:1999	430	10CrMo5-5	EN 10216-2:2002	219
1060	ASTM A 29/A 29M-03	31	10CrMo9-10	EN 10028-2:2003	124, 125
	ASTM A 576-90b (2000)	31	4001000 4		220
	ASTM A 682/A 682M-02	425	10NiCr5-4		44
	ASTM A 689-97 (2000)	425	10S10	, ,	257
	ASTM A 713-04	425	10S20		420
1004	SAE J403 NOV01	31	400Pk00		420
1064	ASTM A 29/A 29M-03 ASTM A 682/A 682M-02	32 425	10SPb20		423
		425 425	4.4		423
1065	ASTM A 713-04	425 32	11		260
1005	ASTM A 29/A 29M-03 ASTM A 682/A 682M-02	32 425			260
		425 425			360
ASTM A 713-04 SAE J403 NOV01	425 32	11 L 09	` ,	423	
1069	ASTM A 29/A 29M-03	32			423
1070	ASTM A 29/A 29M-03 ASTM A 29/A 29M-03	32	11 L 17		423
1070	ASTM A 29/A 29/N-03 ASTM A 576-90b (2000)	32			423
	ASTM A 682/A 682M-02	425	11 L 37		423
AS	ASTM A 689-97 (2000)	425			423
	ASTM A 713-04	425	11 L 41	ASTM A 29/A 29M-03	423
	SAE J403 NOV01	32		ASTM A 576-90b (2000)	423
1070M	ASTM A 295-98	439	11 L 44	ASTM A 29/A 29M-03	423
1071	ASTM A 29/A 29M-03	32		ASTM A 576-90b (2000)	423
1074	ASTM A 29/A 29M-03	32	11 L 46	ASTM A 29/A 29M-03	423
1074	ASTM A 682/A 682M-02	425		ASTM A 576-90b (2000)	423
	ASTM A 713-04	425	11 MnNi 5 3	ISO 9328-3:1991	129
	SAE J403 NOV01	44		ASTM A 29/A 29M-03 ASTM A 576-90b (2000)	199, 20
1075	ASTM A 29/A 29M-03	32		ISO 9330-3:1997	199, 20
1075	SAE J403 NOV01	44		ISO 9330-5:2000	199, 20
1078	ASTM A 29/A 29M-03	32	11 SMn 28	ISO 683-9:1988	422
1070	ASTM A 576-90b (2000)	32	11 SMnPb 28		424
	ASTM A 689-97 (2002)	425	11, Class 1	ASTM A 387/A 387M-03	123
	ASTM A 713-04	425	11, Class 2	ASTM A 387/A 387M-03	123
	SAE J403 NOV01	32	11, Class 4	ASTM	312
1080	ASTM A 29/A 29M-03	33	,	A 541/A 541M-95 (1999)	
1000	ASTM A 576-90b (2000)	33	1108	ASTM A 29/A 29M-03	436
	ASTM A 682/A 682M-02	437	1109	ASTM A 29/A 29M-03	420
	SAE J403 NOV01	33		ASTM A 576-90b (2000)	43, 420
1084	ASTM A 29/A 29M-03	33	1110	ASTM A 29/A 29M-03	420
1004	ASTM A 576-90b (2000)	33		ASTM A 512-96 (2001)	170, 18
	ASTM A 713-04	426		EN 10216-2:2002 EN 10084:1998 ASTM A 512-96 (2001) EN 10087:1998 EN 10277-3:1999 EN 10087:1998 EN 10277-3:1999 ASTM A 333/A 333M-99 ASTM A 334/A 334M-99 ASTM A 334/A 334M-99 ASTM A 29/A 29M-03 ASTM A 576-90b (2000) ISO 9328-3:1991 ISO 9329-3:1997 ISO 9330-3:1997 ISO 9330-5:2000 ISO 683-9:1988 ISO 683-9:1988 ASTM A 387/A 387M-03 ASTM A 541/A 541M-95 (1999) ASTM A 29/A 29M-03 ASTM A 29/A 29M-03 ASTM A 387/A 387M-03 ASTM A 387/A 387M-03 ASTM A 387/A 387M-03 ASTM A 29/A 29M-03	43, 420
	SAE J403 NOV01	44	1115	ASTM A 512-96 (2001)	257
1085	ASTM A 682/A 682M-02	426	1116	ASTM A 29/A 29M-03	436
	SAE J403 NOV01	44		, ,	43, 436
1086	ASTM A 29/A 29M-03	33	1117		420
.000	ASTM A 682/A 682M-02	426		` '	257
	ASTM A 713-04	426		, ,	43, 420
	SAE J403 NOV01	33			420
1090	ASTM A 29/A 29M-03	33	1118		420
	ASTM A 576-90b (2000)	33		` '	43, 420
	SAE J403 NOV01	33			420
1095	ASTM A 108-03	33	1119	ASTM A 29/A 29M-03	436
	ASTM A 29/A 29M-03	33		, ,	43, 436
	ASTM A 29/A 29M-03 ASTM A 576-90b (2000)	33	1126	SAE J403 NOV01	436
	ASTM A 576-900 (2000) ASTM A 682/A 682M-02	33 426	1132	ASTM A 29/A 29M-03	436
AS				ASTM A 576-90b (2000)	43, 436
	ASTM A 689-97 (2000)	426		` '	,

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
1137	ASTM A 29/A 29M-03	420	12, Class 2	ASTM A 387/A 387M-03	122
	ASTM A 576-90b (2000)	43, 420	1211	ASTM A 29/A 29M-03	436
	SAE J403 NOV01	420		ASTM A 576-90b (2000)	43, 436
138	SAE J403 NOV01	420	1212	ASTM A 29/A 29M-03	422
139	ASTM A 29/A 29M-03	420		ASTM A 576-90b (2000)	43, 422
	ASTM A 576-90b (2000)	43, 420		SAE J403 NOV01	422
140	ASTM A 29/A 29M-03	421	1213	ASTM A 29/A 29M-03	422
	ASTM A 576-90b (2000)	43, 421		ASTM A 576-90b (2000)	43, 422
	SAE J403 NOV01	421		SAE J403 NOV01	422
141	ASTM A 29/A 29M-03	421	1215	ASTM A 29/A 29M-03	422
	ASTM A 576-90b (2000)	43, 421		ASTM A 576-90b (2000)	43, 422
	SAE J403 NOV01	421		SAE J403 NOV01	422
144	ASTM A 29/A 29M-03	421	125Cr2	EN 10132-4:2000	437
	ASTM A 576-90b (2000)	43, 421	12CrMoV12-10	EN 10028-2:2003	155
	SAE J403 NOV01	421	12L13	SAE J403 NOV01	424
145	ASTM A 29/A 29M-03	436	12L14	ASTM A 576-90b (2000)	43
	ASTM A 576-90b (2000)	43, 421		SAE J403 NOV01	424
146	ASTM A 29/A 29M-03	421	12L15	SAE J403 NOV01	424
	ASTM A 576-90b (2000)	43, 421	12Ni14	EN 10028-4:2003	132, 133
	SAE J403 NOV01	421		EN 10216-4:2002	199, 200
151	ASTM A 29/A 29M-03	421		EN 10222-3:1998	289, 290
	ASTM A 576-90b (2000)	43, 421	12Ni14G1	ISO 9327-3:1999	289, 290
	SAE J403 NOV01	421	12Ni14G2	ISO 9327-3:1999	289, 290
15-95	ASTM A 148/A 148M-03	359	12Ni19	ISO 9327-3:1999	289, 290
1CrMo9-10	EN 10216-2:2002	220	13	ASTM	360
	EN 10222-2:1999	283, 284		A 487/A 487M-93 (2003)	
1L17	SAE J403 NOV01	423	13 CrMo 4 4	DIN 28180:1985	217, 218
1L37	SAE J403 NOV01	423	13 CrMo 9 10 T1	ISO 9328-2:1991	124, 125
1L41	SAE J403 NOV01	423	13 CrMo 9 10 T2	ISO 9328-2:1991	124, 125
1L44	SAE J403 NOV01	423	13 MnNi 6-3	ISO 9328-3:1991	129
1L46	SAE J403 NOV01	423		ISO 9329-3:1997	199, 200
1MnNi5-3	EN 10028-4:2003	129		ISO 9330-3:1997	199, 200
	EN 10216-4:2002	199, 200		ISO 9330-5:2000	199, 200
	ISO 9327-3:1999	291	130-115	ASTM A 148/A 148M-03	359
1SMn30	EN 10087:1998	422	1330	ASTM A 29/A 29M-03	43
	EN 10277-3:1999	422		ASTM A 322-91 (2001)	43
1SMn37	EN 10087:1998	422		ASTM A 519-03	257
	EN 10277-3:1999	422		SAE J404 JUN00	44
1SMnPb30	EN 10087:1998	424	1335	ASTM A 29/A 29M-03	43
	EN 10277-3:1999	424		ASTM A 322-91 (2001)	43
1SMnPb37	EN 10087:1998	424		ASTM A 519-03	257
	EN 10277-3:1999	424		SAE J404 JUN00	44
2	ASTM	360	1340	ASTM A 29/A 29M-03	43
	A 487/A 487M-93 (2003)			ASTM A 322-91 (2001)	43
2 L 13	ASTM A 29/A 29M-03	424		ASTM A 519-03	257
	ASTM A 576-90b (2000)	424		EN 10305-1:2002	258
2 L 14	ASTM A 29/A 29M-03	424		SAE J404 JUN00	44
	ASTM A 576-90b (2000)	424	1345	ASTM A 29/A 29M-03	43
2 L 15	ASTM A 29/A 29M-03	424		ASTM A 322-91 (2001)	43
	ASTM A 576-90b (2000)	424		ASTM A 519-03	257
2 Ni 14	ISO 9329-3:1997	199, 200		SAE J404 JUN00	44
	ISO 9330-3:1997	199, 200	135-125	ASTM A 148/A 148M-03	359
	ISO 9330-5:2000	199, 200	13CrMo4-5	EN 10028-2:2003	122
2 Ni 14 G1	ISO 9328-3:1991	132, 133		EN 10216-2:2002	217, 218
2 Ni 14 G2	ISO 9328-3:1991	132, 133		EN 10222-2:1999	281
2 SMn 35	ISO 683-9:1988	422	13CrMo9-10	ISO 9327-2:1999	283, 284
2 SMnPb 35	ISO 683-9:1988	424	13CrMoSi5-5	EN 10028-2:2003	123
2 3 WILLE D 33					

558 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
13MnNi6-3	EN 10028-4:2003	129	1572	ASTM A 29/A 29M-03	43
	EN 10216-4:2002	199, 200		ASTM A 576-90b (2000)	43
	EN 10222-3:1998	291	15MnCrMoNiV5-3	EN 10222-2:1999	312
	ISO 9327-3:1999	291	15MnMoV4-5	EN 10222-2:1999	312
14	ASTM	360	15NiCr13	EN 10084:1998	38
14 CrMo 4 E	A 487/A 487M-93 (2003)	100	15NiCuMoNb5-6-4	EN 10028-2:2003	139, 140
14 CrMo 4 5	ISO 9328-2:1c991	122		EN 10216-2:2002	261
14CrMo4-5	ISO 9327-2:1999	281	15NiMn6	EN 10028-4:2003	130
14MoV6-3	EN 10216-2:2002	216		EN 10222-3:1998	289, 290
440004404	EN 10222-2:1999	312		ISO 9327-3:1999	289, 290
14NiCrMo13-4	EN 10084:1998	39	15S10	ASTM A 512-96 (2001)	257
15 Mo 3	DIN 28180:1985	213	15SMn13	EN 10087:1998	420
15 NiCr 13	ISO 683-11:1987	38		EN 10277-3:1999	420
15 NiMn 6	ISO 9328-3:1991	130	16	ASTM	360
150-135	ASTM A 148/A 148M-03	359		A 487/A 487M-93 (2003)	
1513	ASTM A 29/A 29M-03	43	16 M5-M	AFNOR NF A 32-053:1992	359
	ASTM A 576-90b (2000)	43	16 MCDV 6-M	AFNOR NF A 32-058:1984	360
1518	ASTM A 29/A 29M-03	43	16 MnCr 5	ISO 683-11:1987	45
	ASTM A 576-90b (2000)	43	16 MnCrS 5	ISO 683-11:1987	45
	ASTM A 29/A 29M-03	34	16 Mo 3	ISO 9328-2:1991	117, 119
522	ASTM A 576-90b (2000)	34	160-145	ASTM A 148/A 148M-03	359
	SAE J403 NOV01	34	165-150	ASTM A 148/A 148M-03	359
1524	ASTM A 29/A 29M-03	43	165-150L	ASTM A 148/A 148M-03	359
3 <u>-</u> 1	ASTM A 513-03a	171, 174,	16-8-2H	ASTM A 376/A 376M-02a	262
		181, 183,	16MnCr5	EN 10084:1998	44
		184		EN 10297-1:2003	258
	ASTM A 576-90b (2000)	43	16MnCrB5		44
	SAE J403 NOV01	44	16MnCrS5		44
1525	ASTM A 29/A 29M-03	43			258
	ASTM A 576-90b (2000)	43	16Mo3		117, 119
1526	ASTM A 29/A 29M-03	43	1011100		213
	ASTM A 576-90b (2000)	43			213
	SAE J403 NOV01	44			213
1527	ASTM A 29/A 29M-03	43			279
	ASTM A 576-90b (2000)	43			279
	SAE J403 NOV01	44	16NiCr4		279 44
1536	ASTM A 29/A 29M-03	34			
	ASTM A 576-90b (2000)	34	16NiCrS4		44
	SAE J403 NOV01	44	17 NiCrMo 6		39
1541	ASTM A 29/A 29M-03	34	17 SMn 20		420
	ASTM A 576-90b (2000)	34	17Cr3		35
	SAE J403 NOV01	34	17CrNi6-6		44
1547	ASTM A 29/A 29M-03	43	17CrS3		35
	ASTM A 576-90b (2000)	43	17NiCrMo6-4		44
	SAE J403 NOV01	44	17NiCrMoS6-4	ISO 9327-3:1999 ASTM A 512-96 (2001) EN 10087:1998 EN 10277-3:1999 ASTM A 487/A 487M-93 (2003) AFNOR NF A 32-053:1992 AFNOR NF A 32-058:1984 ISO 683-11:1987 ISO 683-11:1987 ISO 9328-2:1991 ASTM A 148/A 148M-03 ASTM A 148/A 148M-03 ASTM A 148/A 148M-03 ASTM A 376/A 376M-02a EN 10084:1998 EN 10297-1:2003 EN 10084:1998 EN 10297-1:2003 EN 10028-2:2003 EN 10028-2:2003 EN 10217-2:2002 EN 10217-2:2002 EN 10217-2:2002 EN 1022-2:1999 ISO 9327-2:1999 EN 10084:1998	44
1548	ASTM A 29/A 29M-03	43	18 CDBB2-M		360
10-10	ASTM A 576-90b (2000)	43	18 CrMo 4	ISO 683-11:1987	37
	SAE J403 NOV01	44	18 CrMoS 4	ISO 683-11:1987	37
1551	ASTM A 29/A 29M-03	43	18 CrNiMo 7	ISO 683-11:1987	45
1551	ASTM A 576-90b (2000)		18 NCD12.6-M	AFNOR NF A 32-053:1992	359
1552	ASTM A 576-900 (2000) ASTM A 29/A 29M-03	43 43	18-2	ASTM A 803/A 803M-03	262
1002			18Cr-2Mo	ASTM A 268/A 268M-03	259
	ASTM A 576-90b (2000)	43	18CrMo4	EN 10084:1998	37
4504	SAE J403 NOV01	44		EN 10250-3:1999	311
1561	ASTM A 29/A 29M-03	43	18CrMoS4	EN 10084:1998	37
	ASTM A 576-90b (2000)	43	18CrNiMo7-6	EN 10084:1998	44
1566	ASTM A 29/A 29M-03	43	18MnMo4-5	EN 10028-2:2003	117, 119
	ASTM A 576-90b (2000)	43 44	18MnMoNi5-5	EN 10222-2:1999	312

ASTM A 508IA 508M-03a	Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
C A STM A STM A STM	18S10					
C A 541/A 541M-95 (1999) C A ASTM A 266/A 266/H-03a 312 20NiCindo2-2 EN 10084-1998 39 A 541/A 541M-95 (1999) C EN 10082-1995 375, 385 20NiCindo5-2 EN 10084-1998 39 A 541/A 541M-3 (2003) 273, 275 385 20NiCindo5-2 EN 10084-1998 39 A 541/A 541M-3 (2003) ASTM A 266/A 266/H-03a 273, 275 385 20NiCindo5-2 EN 10084-1998 39 ASTM A 487/A 487/M-93 (2003) ASTM A 487/A 487/M-93 (2003) ASTM A 487/A 487/M-93 (2003) ASTM A 57/A 537/M-95 (2000) ASTM A 738/A 738/M-03 154 210-180 ASTM A 387/A 387/A 387/M-03 126 ASTM A 738/A 738/M-03 154 210-180 ASTM A 148/A 148/M-03 359 ASTM A 387/A 387/M-03 126 ASTM A 387/A 387/A 387/M-03 126 ASTM A 387/A 387/A 387/M-03 126 ASTM A 387/A 387/M-03 127 210-180 ASTM A 148/A 148/M-03 359 ASTM A 387/A 387/M-03 121 210-180 ASTM A 148/A 148/M-03 359 ASTM A 387/A 387/M-03 121 210-180 ASTM A 148/A 148/M-03 359 ASTM A 387/A 387/M-03 121 21 210-180 ASTM A 387/A 387/M-03 124 12 210-180 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 21 Class 1 ASTM A 387/A 387/M-03 124 12 ASTM A 387/	1A		•			
C ASTM A 541/A 541M-95 (1999) XNIC/MoCUNZ5-0-7 EN 10088-2:1995 EN 10088-2:1995 EN 1008-2:1996 BN 1008-2:1996 ASTM A 266/A 266M-03a ASTM A 367/A 487/M-93 (2003) ASTM A 367/A 537/M-93 (2004) ASTM A 735/A 735/M-93 (2004) ASTM A 506/A 506M-03a 292 215/S15 BS 3005-11991 ASTM A 186/A 148/M-93 (2004) ASTM A 186/A 148/M-93 (200			273, 275			
XNIC/MoCuN25-20-7 EN 10088-2:1995 375, 385 20NIC/MoS2-2 EN 10084-1998 39 39 39 39 39 39 39 39 39 39 39 39 39	10	` ,	010			
XNIC/MoCuN25-20-7 EN 10088-2:1995 375, 385 2	10		312	20NiCrMo2-2	EN 10084:1998	39
ASTM A 266/A 266M-03a	1XNiCrMoCuN25-20-7		375, 385		EN 10297-1:2003	
ASTM A 4877A 4877h-93 (2003) ASTM A 4877A 4877h-93 (2003) ASTM A 5377A 5377h-95 (2000) ASTM A 735/A 735M-95 (2000) ASTM A 735/A 735M-93 121 210-1800 ASTM A 143/A 148M-03 359 ASTM A 508/A 508M-03a 292 215515 BS 3605-11991 AMD 2:1997 262 ASTM A 508/A 508M-03a 292 215515 BS 3605-11991 AMD 2:1997 262 ASTM A 508/A 508M-03a 292 215515 BS 3605-11991 AMD 2:1997 262 ASTM A 508/A 508M-03a 292 215MC/5 ISO 683-11991 AMD 2:1997 262 ASTM A 508/A 508M-03a 292 21MC/5 ISO 683-11991 AMD 2:1997 262 ASTM A 508/A 508M-03a 292 22 LC Class 1 ASTM A 508/A 508M-03a 292 22 LC Class 1 ASTM A 508/A 508M-03a 292 22 LC Class 1 ASTM A 508/A 508M-03a 292 22 LC Class 1 ASTM A 508/A 508M-03a 292 22 LC Class 2 ASTM A 508/A 508M-03a 292 22 LC Class 2 ASTM A 508/A 508M-03a 292 22 LC Class 2 ASTM A 508/A 508M-03a 292 22 LC Class 2 ASTM A 508/A 508M-03a 292 22 LC Class 2 ASTM A 508/A 508M-03a 292 22 LC Class 2 DO CO C 4 ISO 683-11:1987 35 22, Class 2 ASTM A 508/A 508M-03a 283, 284 DO MAC 5 ISO 683-11:1987 35 22, Class 2 DO MAC 5 ISO 683-11:1987 45 22, Class 3 DO MAC 5 ISO 683-11:1987 45 22, Class 4 DO MAC 5 ISO 683-11:1987 39 22 CM 5 ASTM A 508/A 508M-03a 283, 284 DO MAC 5 ISO 683-11:1987 39 22 CM 5 ASTM A 508/A 508M-03a 283, 284 DO MCD 4 AFNOR NF A 32-053:1992 309, 301 ASTM A 240/A 240M-03c 151, 12 DO MCOMO ISO 3755:1991 319, 323 2V ASTM A 508/A 520M-03C 151, 12 DO MCOMO ISO 3755:1991 319, 323 2V ASTM A 240/A 240M-03c 151, 12 DO MCOMO ISO 3755:1991 319, 323 2V ASTM A 240/A 240M-03c 151, 12 DO LCIASS 2 ASTM A 240/A 240M-03c 156, 372, 277 240-M03-3 C 241 - Category II CSA 2245 - 2002 250, 22 ASTM A 240/A 240M-03c 156, 372, 277 240-M03-3 C 255 ASTM A 240/A 240M-03c 151, 12 DO LCIASS 2 ASTM A 240/A 240M-03c 156, 372, 277 240-M03-3 C 255 ASTM A 240/A 240M-03c 156, 372, 277 240-M03-3 C 255 ASTM A 240/A 240M-03c 156, 372, 277 240-M03-3 C 255 ASTM A 240/A 240M-03c 156, 372, 277 240-M03-3 C 255 ASTM A 240/A 240M-03c 156, 372, 277 240-M03	2		•	20NiCrMoS2-2	EN 10084:1998	39
A 4877A 4877M-99 (2003) A 537M 537M-99 (2000) A 537M A 537M-99 (2000) A 537M A 736/A 735M-95 (2000) A 537M A 736/A 735M-93 126 A 537M A 387M-95 (2000) A 537M A 736/A 735M-93 154 21 (-1882 2 A57M A 387M-387M-03 126 A57M A 587M-387M-03 126 A57M A 587M-387M-03 121 210-180L A57M A 148/A 148M-03 359 A57M A 580/A 508M-038 292 215MnCr5 ISO 64957:1999 A541/A 541M-95 (1999) A541/A	-		•	20NiCrMoS6-4	EN 10084:1998	39
ASTM A 537/A 537M-95 (2000) ASTM A 736/A 735M-95 (2000) ASTM A 736/A 735M-03 126 ASTM A 387/A 387M-03 126 ASTM A 387/A 387M-03 126 ASTM A 387/A 387M-03 126 ASTM A 587/A 547M-03 121 10-180L ASTM A 180/A 148/A 148M-03 359 ASTM A 508/A 508M-03a ASTM A 608-03 ASTM A 508/A 508M-03a ASTM A 608-03 ASTM A 508/A 508M-03a ASTM A 508/A 508			000	21 L, Class 1	ASTM A 387/A 387M-03	126
A 537/A 537M-95 (2000) ASTM A 736/A 537M-96 (2000) ASTM A 736/A 736M-93 ASTM A 736/A 736M-93 ASTM A 736/A 736M-93 ASTM A 508/A 508M-03a ASTM A 608-03 ASTM A 608-03 ASTM A 608-03 ASTM A 240/A 240M-03a ASTM A 240/A 240M-03		` ,	108, 112	21, Class 1	ASTM A 387/A 387M-03	126
2. Class 1 ASTM A 3877A 387M-03 121 210-180L ASTM A 148/A 148M-03 389 ASTM A 508/A 508M-03a 292 215515 BS 3605.1:1991 AMD 2:1997 262 21MnCr5 150 4857A 387M-03 124, 12 22 L, Class 1 SC 4857A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 387A 387M-03 124, 12 22 L, Class 1 ASTM A 508/A 508M-03 263, 23 L, Class 1 ASTM A 508/A 508M-03 263, 23 L, Class 1		A 537/A 537M-95 (2000)		21, Class 2	ASTM A 387/A 387M-03	126
ASTM A 500k 508h-03a 292 215S15 BS 3605-1:1991 AMD 2:1997 262 21fMnCr5 ISO 4957:1999 438 ASTM A 541/A 541h/95 (1999) 438 ASTM A 541/A 541h/95 (1999) 438 ASTM A 5367/A 387h/03 124, 121 22 L, Class 1 ASTM A 387/A 387h/03 124, 12 22 L, Class 1 ASTM A 387/A 387h/03 124, 12 22 L, Class 1 ASTM A 387/A 387h/03 124, 12 22 L, Class 1 ASTM A 387/A 387h/03 124, 12 22 L, Class 1 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 22 L, Class 2 ASTM A 387/A 387h/03 124, 12 20 D, Cr6 4 ISO 683-11:1987 35 22, Class 2 ASTM A 508/A 508h/03 283, 26 20 Ms-M AFNOR NF A 32-053:1992 320, 324 22 L, Class 4 ASTM A 508/A 508h/03 283, 26 20 Ms-M AFNOR NF A 32-053:1992 320, 324 22 L, Class 4 ASTM A 508/A 508h/03 283, 26 20 Ms-M AFNOR NF A 32-053:1992 320, 324 22 L, Class 4 ASTM A 508/A 508h/03 283, 26 20 Ms-M AFNOR NF A 32-053:1992 359 220 L, Class 5 ASTM A 541/A 541h/95 (1999) 310 NCDDs-M AFNOR NF A 32-053:1992 359 220 S ASTM A 240/A 240/M-030 151, 12 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1998 37 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1999 319, 323 20 NGCMoS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1999 319, 323 20 NGCMOS 2 ISO 683-11:1987 39 22C/MoS3-5 EN 10084:1999 319, 323 20 NGCMOS 2 ISO 683-11:1997 39 22C/MoS3-5 EN 10084:1999 319, 323 32 NGCMOS 2 ISO 683-11:1997 39 22C/MOS3-5 EN 10084:1999 319, 323 32 NGCMOS 2 ISO 683-11:1991 319, 323 32 NGCMOS 2 ISO 683-11:1991 319, 323 32 NGCMOS 2 ISO 683-11:1991 319, 323 32 NGCMOS 2 ISO 683-11		ASTM A 735/A 735M-03	154	210-180	ASTM A 148/A 148M-03	359
ASTM A 541/A 541M-95 (1999) 2, Class 2 ASTM A 387/A 387M-03	2, Class 1	ASTM A 387/A 387M-03	121	210-180L	ASTM A 148/A 148M-03	359
A 541/A 541/M-95 (1999) C, Class 2 ASTM A 387/A 387/M-03 ASTM A 541/A 541/M-95 (1999) A 541/A 541/M-95 (1999) B 52 C Class 1 ASTM A 387/A 387/M-03 ASTM A 541/A 541/M-95 (1999) B 52 C Class 2 ASTM A 387/A 387/M-03 ASTM A 541/A 541/M-95 (1999) B 52 C Class 2 ASTM A 387/A 387/M-03 ASTM A 587/A 587/M-05 ASTM A 587/A 587/A ASTM A 587/A 587/M-05 ASTM A 587/A 587/A ASTM A 587/A 587/ASTM A 587/A 587/A ASTM		ASTM A 508/A 508M-03a	292	215\$15	BS 3605-1:1991 AMD 2:199	7 262
2. Class 2 ASTM A 387/A 387M-03 121 22 L. Class 1 ASTM A 387/A 387M-03 124, 12 ASTM A 581/A 581/M-95 (1999) 34 ASTM A 581/A 581/M-95 (1999) 35 22, Class 1 ASTM A 387/A 387M-03 124, 12 Clos 64 ISO 683-11:1987 35 22, Class 2 ASTM A 387/A 387M-03 124, 12 Clos 64 ISO 683-11:1987 35 22, Class 3 ASTM A 581/A 581/M-03 124, 12 Clos 654 ISO 683-11:1987 35 22, Class 3 ASTM A 581/A 581/M-03 124, 12 Clos 654 ISO 683-11:1987 35 22, Class 3 ASTM A 581/A 581/M-03 124, 12 Clos 654 ISO 683-11:1987 35 22, Class 3 ASTM A 581/A 581/M-95 (1999) ASTM A FNOR NF A 32-053:1992 320, 324 ASTM A 581/A 581/M-95 (1999) ASTM A 240/A 240/M-03 151, 15 Clos NICMO-0 ISO 3755:1991 319, 323 ASTM A 581/A 581/M-95 (1999) ASTM A 581/A 581/M-9			292	21MnCr5	ISO 4957:1999	438
ASTM A 589/A 38/M-03 121, 22 L. Class 1 ASTM A 387/A 387M-03 124, 12 ASTM A 580/A 508M-03a 292 22 Mn 6 ISO 683-11:987 34 ASTM A 541/A 541M-95 (1999) 120 Cr 4 ISO 683-11:1987 35 22, Class 3 ASTM A 587/A 387M-03 124, 12 ASTM A 580/A 580M-03a 283, 25 Clos 4 ISO 683-11:1987 35 22, Class 3 ASTM A 580/A 580M-03a 283, 25 Clos 5 ASTM A 240/A 240M-03a 151, 15 Clos 683-11:987 39 20 Clos 683-11:987				21V	ASTM A 832/A 832M-99	154
ASTM A 500/A 5009M-03a ASTM A 541/A 541M-95 (1999) A 541/A 541/A 541M-95 (1999) B 522 C 1 Class 1 ASTM A 387/A 387M-03 C 124, 12 C 12 Class 2 ASTM A 387/A 387M-03 C 124, 12 C 12 Class 3 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 4 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 3 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 4 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 5 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 C 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 Class 6 ASTM A 508/A 508M-03a C 124, 12 Class 6 ASTM A 240/A 240M-03c C 150, 12 Class 6 ASTM A 240/A 240M-03c C 150, 12 Class 6 ASTM A 240/A 240M-03c C 150, 12 Class 7 ASTM A 240/A 240M-03c C 150, 12 Class 1 ASTM A 240/A 240M-03c C 150, 12 Class 1 ASTM A 240/A 240M-03c C 150, 12 Class 1 ASTM A 240/A 240M-03c C 150, 12 Class 1 ASTM A 240/A 240M-03c C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156, 372, 230-450W C 150, 12 Class 2 ASTM A 240/A 240M-03c C 156,	2, Class 2			22 L. Class 1		124, 125
ASTM A 541M-95 (1999) A 541/A 541M-95 (1999) B 541/A 541M-95 (1999) A 541/A 541M-95 (1999) B 60 Cr 54				•		-
20 CC 4			292			124, 125
20 CrS 4	20 Cr 4	` ,	25	·		124, 125
20 D5-M				•		•
AFNOR NF A 32-053:1992 320, 324 22, Class 4 ASTM ASTM A 541/A 541M-95 (1999) 312 320 MnCr5 5 ISO 683-1:1987 45 22, Class 5 ASTM ASTM 312 320 MnCr5 5 ISO 683-1:1987 45 22, Class 5 ASTM ASTM ASTM ASTM ASTM ASZ-053:1992 359 2205 ASTM ASTM ASTM ASTM ASZ-053:1992 359 2205 ASTM ASTM ASTM ASZ-053:1992 360 ASTM ASZ-053:1992 360 ASTM ASZ-053:1992 360 ASZ-053:1992 360 ASZ-053:1993 360 ASZ-053:1993 360 ASZ-053:1991 319, 323 ASZ-053:1991 319, 323 ASZ-053:1991 ASZ-053:1991 319, 323 ASZ-053:1991 ASZ-053:1993 ASZ				££, 01033 0		-
20,00 MinCr 5 ISO 683-1:1987 45 22, Class 4 ASTM 312 20, MinCr 5 ISO 683-1:1987 45 45 22, Class 5 ASTM A 541/A 541M-95 (1999) 20, MinCr 5 ISO 683-1:1987 45 22, Class 5 ASTM A 541/A 541M-95 (1999) 20, MinCr 5 ISO 683-1:1987 39 2205 ASTM A 240/A 240M-03c 151, 15 20, NICrMO 2 ISO 683-1:11987 39 22CrMoS3-5 EN 10084:1998 37 22V ASTM A 240/A 240M-03c 151, 15 20, NICrMO 2 ISO 683-1:11987 39 22V ASTM A 232/A 832M-99 154 20, NICrMO 2 ISO 683-1:1991 319, 323 A 541/A 541M-95 (1999) ASTM A 232/A 832M-99 154 20, NICrMO 2 ISO 683-1:1987 39 22V ASTM A 232/A 832M-99 154 20, NICrMO 2 ISO 683-1:1987 37 230 ASTM A 240/A 240M-03c 151, 15 20, NICrMO 2 ISO 683-1:1987 37 230 ASTM A 240/A 240M-03c 151, 15 20, NICrMO 2 ISO 683-1:1987 39 22V ASTM A 240/A 240M-03c 151, 15 20, NICrMO 2 ISO 683-1:1987 37 23V ASTM A 240/A 240M-03c 156, 372, 23V ASTM A 240/A 240M-03c 156, 372, 23V ASTM A 240/A 240M-03c 156, 372, 241 Category ISO 3755:1991 319, 32 32 32 32 32 32 32 32			•			200, 204
20 MnCr5 ISO 683-11:1987 45 22, Class 5 ASTM A 240/A 240M-03c 151, 15 20 NnCD8-M AFNOR NF A 32-058:1984 360 2205 ASTM A 240/A 240M-03c 151, 15 392, 20 NnCM8 2 ISO 683-11:1987 39 22CfMoS3-5 EN 10084:1998 37 37 22 NnCM8 2 ISO 683-11:1987 39 22 CfMoS3-5 EN 10084:1998 37 37 38 38 38 38 38 3			•	22. Class 4	, ,	312
20 NCD8-M AFNOR NF A 32-058:1984 360				,		
20 NCD4-M AFNOR NF A 32-053:1992 359 2205 ASTM A 240/A 240M-03c 151, 15 20 NiCrMo2 2 ISO 683-11:1987 39 22V ASTM A 260-0400 ISO 3755:1991 319, 323 ASTM A 260-03 372, 377 ASTM A 260-03 372, 377 230-450 ISO 3755:1991 319, 32 32-201-1 ASTM A 260-03 372, 377 230-450 ISO 3755:1991 319, 32 30-450 ISO 3755:1991 310, 32 30-450 ISO				22, Class 5	ASTM	312
10 NiCrMo 2 ISO 683-11:1987 39 22 CrMoS3-5 EN 10084:1998 37 37 220 NiCrMoS 2 ISO 683-11:1987 39 22 CrMoS3-5 EN 10084:1998 37 37 39 32 32 32 32 32 32 32	20 NCD8-M	AFNOR NF A 32-058:1984	360		` ,	
20 NIC/MoS 2 ISO 683-11:1987 39 22CrMoS3-5 EN 10084:1998 37 ASTM	20 NCD4-M	AFNOR NF A 32-053:1992	359	2205	ASTM A 240/A 240M-03c	151, 152,
200-400 ISO 355-11:1987 39 22V ASTM A 541/A 541M-95 (1999) 154 200-400 ISO 3755:1991 319, 323 ASTM A 832/A 832M-99 154 201 ASTM A 276-03 400, 403 2304 ASTM A 240/A 240M-03c 151, 15 392, 35 201, Class 2 ASTM A 666-03 372, 377 230-450 ISO 3755:1991 319, 32 377 241 - Category I CSA 2245.1-2002 246, 24 377 241 - Category I CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 25 CrMo 4 ISO 683-1:1987 37 25 CrMo 4 ISO 683-1:1991	20 NiCrMo 2	ISO 683-11:1987	39	22CrMoS3 5	EN 10084:1008	
1900-400W ISO 3755:1991 319, 323 A 541/A 541M-95 (1999) ASTM A 832/A 832M-99 154 201 (20 NiCrMoS 2	ISO 683-11:1987	39			
1900-400W 1900-3755:1991 319, 323 ASTM A 832/A 832M-99 154	200-400	ISO 3755:1991	319, 323	22 V		200, 204
201 ASTM A 276-03 400, 403 2304 ASTM A 240/A 240M-03c 151, 15 392, 38 201, Class 1 ASTM A 666-03 372, 377 230-450 ISO 3755:1991 319, 32 201-11 ASTM A 240/A 240M-03c 156, 372, 230-450W ISO 3755:1991 319, 32 201-11 ASTM A 240/A 240M-03c 156, 372, 230-450W ISO 3755:1991 319, 32 201-12 ASTM A 240/A 240M-03c 156, 372, 241 - Category I CSA Z245.1-2002 246, 24 24 1 - Category II CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 1 - Category III CSA Z245.1-2002 250, 25 24 24 240M-03c 156, 372, 25 CrMoS 4 ISO 683-1:1987 37 25 C	200-400W	ISO 3755:1991	319, 323		` ,	154
201, Class 1 ASTM A 666-03 372, 377 230-450 ISO 3755:1991 319, 32 30-10, Class 2 ASTM A 240/A 240M-03c 156, 372, 377 23V ASTM A 832/A 832M-99 154 201-2 ASTM A 240/A 240M-03c 156, 372, 241 - Category I CSA 2245.1-2002 246, 24 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category II CSA 2245.1-2002 250, 25 377 241 - Category III CSA 2245.1-2002 250, 25 377 240 - Category III CSA 2245.1-2002 250, 25 377 240 - Category III CSA 2245.1-2002 250, 25 377 240 - Category III CSA 2245.1-2002 250, 25 377 240 - Category III CSA 2245.1-2002 250, 25 377 250 - Category III CSA 2245.1-2002 2	201	ASTM A 276-03	400, 403	2304		151, 152,
ASTM A 240/A 240M-03c	201, Class 1	ASTM A 666-03	372, 377			392, 393
377 23V ASTM A 832/A 832M-99 154 201-2 ASTM A 240/A 240M-03c 156, 372, 241 - Category I CSA Z245.1-2002 246, 24 201L ASTM A 240/A 240M-03c 156, 372, 241 - Category II CSA Z245.1-2002 250, 25 201L ASTM A 666-03 372, 377 241 - Category III CSA Z245.1-2002 250, 25 201LN ASTM A 240/A 240M-03c 156, 372, 241 - Category III CSA Z245.1-2002 250, 25 201LN ASTM A 240/A 240M-03c 156, 372, 25 CrMo 4 ISO 683-1:1987 37 27 25 CrMo 4 ISO 683-1:1987 37 2802 ASTM A 240/A 240M-03c 156, 372, 25 CrMo 4 ISO 683-1:1987 37 2902 ASTM A 240/A 240M-03c 156, 372, 25 Or ASTM A 240/A 240M-03c 151, 15 377 25 MCDV 6-M AFNOR NF A 32-058:1984 360 202 ASTM A 260-03 400, 403 25-4-4 ASTM A 240/A 240M-03c 151, 15 377 ASTM A 266-03 372, 377 ASTM A 803/A 803M-03 259 205 ASTM A 276-03 415 255 ASTM A 240/A 240M-03c 156, 41 20 ASTM A 666-03 413 25 CrMo4 EN 10083-1:1991 37 20 ASTM A 666-03 413 25 CrMo4 EN 10083-1:1991 37 20 ASTM A 260-2:1999 311 EN 10250-3:1999 277, 27 20 ASTM A 250-2:1999 311 EN 10250-3:1999 277, 27 20 ASTM A 250-2:1999 311 25 CrMoS4 EN 10083-1:1991 37 20 ASTM A 250-2:1999 311 260-2:10 ASTM A 148/A 148M-03 359 20 ASTM A 148/A 148M-03 359	201, Class 2	ASTM A 666-03	372, 377	230-450	ISO 3755:1991	319, 323
ASTM A 240/A 240M-03c	201-1	ASTM A 240/A 240M-03c	156, 372,	230-450W	ISO 3755:1991	319, 323
377 241 - Category II CSA Z245.1-2002 250, 25 25 25 25 25 25 25 25 25 25 25 25 25				23V	ASTM A 832/A 832M-99	154
ASTM A 240/A 240M-03c 156, 372, 377 241 - Category III CSA Z245.1-2002 250, 250, 250, 250, 250, 250, 250, 250,	201-2	ASTM A 240/A 240M-03c		241 - Category I	CSA Z245.1-2002	246, 247
ASTM A 240/A 240M-03c 377 241 - Category III CSA Z245.1-2002 250, 250 250	2041	A C.T.M. A. 0.40/A. 0.40M. 00-			CSA Z245.1-2002	250, 253
ASTM A 666-03 372, 377 24CrMo13-6 EN 10085:2001 44 201LN ASTM A 240/A 240M-03c 156, 372, 377 25 CrMo 4 ISO 683-1:1987 37 ASTM A 666-03 372, 377 25 MCDV 6-M AFNOR NF A 32-058:1984 360 202 ASTM A 240/A 240M-03c 156, 372, 377 ASTM A 276-03 400, 403 25-4-4 ASTM A 268/A 268M-03 259 ASTM A 276-03 415 255 ASTM A 240/A 240M-03c 156, 41 ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 20CrMoV13-5-5 EN 10216-2:2002 261 EN 10250-3:1999 311 EN 10250-3:1999 311 EN 10250-3:1998 44 EN 10084:1998 44 EN 10084:1998 44 EN 10083-1:1991 37 EN 10250-3:1999 311 EN 10250-3:1999 312 EN 10250-210L ASTM A 148/A 148M-03 SEMINANNIS	201L	ASTM A 240/A 240M-03C			CSA Z245.1-2002	250, 253
201LN ASTM A 240/A 240M-03c 156, 372, 25 CrMo 4 ISO 683-1:1987 37 ASTM A 666-03 372, 377 25 MCDV 6-M AFNOR NF A 32-058:1984 360 202 ASTM A 240/A 240M-03c 156, 372, 377 ASTM A 276-03 400, 403 25-4-4 ASTM A 268/A 268M-03 259 ASTM A 276-03 415 255 ASTM A 240/A 240M-03c 156, 41 ASTM A 666-03 372, 377 ASTM A 268/A 268M-03 259 ASTM A 666-03 372, 377 ASTM A 268/A 268M-03 259 ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 20CrMoV13-5-5 EN 10216-2:2002 261 EN 10250-2:1999 311 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20MnB5 EN 10083-3:1995 44 EN 10083-1:1991 37 EN 10250-3:1998 44 EN 10083-1:1991 37 EN 10250-3:1999 311 BN 10250-3:1991 37 EN 10250-3:1999 37 EN 10250-3:1999 311 BN 10250-3:1997 199, 20 EN 10250-3:1999 311 BN 10250-3:1999 311 BN 10250-3:1997 199, 20 EN 10250-3:1999 311 BN 10250-3:1999 312 BN 10250-210L ASTM A 148/A 148M-03 359		ASTM A 666-03		24CrMo13-6	EN 10085:2001	44
377 25 CrMoS 4 ISO 683-1:1987 37 ASTM A 666-03 372, 377 25 MCDV 6-M AFNOR NF A 32-058:1984 360 202 ASTM A 240/A 240M-03c 156, 372, 377 ASTM A 276-03 400, 403 25-4-4 ASTM A 268/A 268M-03 259 ASTM A 666-03 372, 377 ASTM A 803/A 803M-03 262 205 ASTM A 276-03 415 255 ASTM A 240/A 240M-03c 156, 41 ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 20CrMoV13-5-5 EN 10216-2:2002 261 20Mnn5 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20Mnn65 EN 10084:1998 44 20MnCr5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 EN 10250-3:1999 37 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 EN 10250-3:1999 311 260-210 ASTM A 148/A 148M-03 359 ENMINONIONIONIONIONIONIONIONIONIONIONIONION	2011 N					
ASTM A 666-03 372, 377 25 MCDV 6-M AFNOR NF A 32-058:1984 360 ASTM A 240/A 240M-03c 156, 372, 377 2507 ASTM A 240/A 240M-03c 151, 15 377 392, 38 ASTM A 276-03 400, 403 25-4-4 ASTM A 268/A 268M-03 259 ASTM A 666-03 372, 377 ASTM A 803/A 803M-03 262 ASTM A 276-03 415 255 ASTM A 240/A 240M-03c 156, 41 ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 ASTM A 666-03 413 25CrMo4 EN 10216-2:2002 261 BN 10250-2:1999 311 EN 10250-3:1999 277, 27 BOMNB5 EN 10083-3:1995 44 EN 10083-1:2002 185, 18 BOMNCr5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 BOMNMONi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 BOMNMONi5 ISO 9327-2:1999 312 260-210 ASTM A 148/A 148M-03 359 BOMNMONI5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359	LOTEIV	7.6 TW 7. 246/7. 246W 666	, ,			
ASTM A 240/A 240M-03c		ASTM A 666-03				
377 ASTM A 276-03 ASTM A 666-03 372, 377 ASTM A 803/A 803M-03 262 205 ASTM A 276-03 ASTM A 240/A 240M-03c 156, 41 ASTM A 666-03 ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 20CrMoV13-5-5 EN 10216-2:2002 261 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20MnB5 EN 10084:1998 44 25CrMoS4 EN 10305-1:2002 185, 18 20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 20MnMoNi5 ISO 9327-2:1999 312 260-210 ASTM A 148/A 148M-03 359	202	ASTM A 240/A 240M-03c				
ASTM A 276-03				2007	7.0 TW 7. 240/7. 240W 000	392, 393
ASTM A 276-03 415 255 ASTM A 240/A 240M-03c 156, 41 ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 COCMOV13-5-5 EN 10216-2:2002 261 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 COMNB5 EN 10083-3:1995 44 EN 10297-1:2003 185, 18 COMNCr5 EN 10084:1998 44 25CrMoS4 EN 10305-1:2002 185, 18 COMNCS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 COMNMONI4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 EN 10250-3:1999 311 260-210 ASTM A 148/A 148M-03 359 COMMONI5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359		ASTM A 276-03	400, 403	25-4-4	ASTM A 268/A 268M-03	
ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 20CrMoV13-5-5 EN 10216-2:2002 261 EN 10216-2:2002 261 20Mn5 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20MnB5 EN 10083-3:1995 44 EN 10297-1:2003 185, 18 20MnCr5 EN 10084:1998 44 EN 10305-1:2002 185, 18 20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 20MnMoNi5 ISO 9327-2:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359		ASTM A 666-03	372, 377		ASTM A 803/A 803M-03	262
ASTM A 666-03 413 25CrMo4 EN 10083-1:1991 37 20CrMoV13-5-5 EN 10216-2:2002 261 EN 10216-2:2002 261 20Mn5 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20MnB5 EN 10083-3:1995 44 EN 10297-1:2003 185, 18 20MnCr5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10084:22003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 20MnMoNi5 ISO 9327-2:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359	205	ASTM A 276-03	415	255	ASTM A 240/A 240M-03c	156, 413
20CrMoV13-5-5 EN 10216-2:2002 261 EN 10216-2:2002 261 20Mn5 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20MnB5 EN 10083-3:1995 44 EN 10297-1:2003 185, 18 20MnCr5 EN 10084:1998 44 EN 10305-1:2002 185, 18 20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 20MnMoNi5 ISO 9327-2:1999 311 260-210 ASTM A 148/A 148M-03 359		ASTM A 666-03	413	25CrMo4	EN 10083-1:1991	
20Mn5 EN 10250-2:1999 311 EN 10250-3:1999 277, 27 20MnB5 EN 10083-3:1995 44 EN 10297-1:2003 185, 18 20MnCr5 EN 10084:1998 44 EN 10305-1:2002 185, 18 20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 20MnMoNi5 ISO 9327-2:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359	20CrMoV13-5-5	EN 10216-2:2002	261			261
20MnB5 EN 10083-3:1995 44 EN 10297-1:2003 185, 18 20MnCr5 EN 10084:1998 44 EN 10305-1:2002 185, 18 20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 EN 10250-3:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359	20Mn5	EN 10250-2:1999	311			277, 278
20MnCr5 EN 10084:1998 44 EN 10305-1:2002 185, 18 20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 EN 10250-3:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359	20MnB5	EN 10083-3:1995	44			185, 186
20MnCrS5 EN 10084:1998 44 25CrMoS4 EN 10083-1:1991 37 20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 EN 10250-3:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359	20MnCr5					
20MnMoNi4-5 EN 10028-2:2003 137, 138 26 CrMo 4 ISO 9329-3:1997 199, 20 20MnMoNi5 ISO 9327-2:1999 311 260-210 ASTM A 148/A 148M-03 359				25CrMoS4		
EN 10250-3:1999 311 260-210 ASTM A 148/A 148M-03 359 20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359						
20MnMoNi5 ISO 9327-2:1999 312 260-210L ASTM A 148/A 148M-03 359						
THE COLOR OF THE C	20MnMoNi5					
260W (38W) CSA G40.21-04 /2, /5						
	_0771111100	LIV 10210 2.2002	201	20UVV (38VV)	CSA G40.21-04	12, 15

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
260WT (38WT)	CSA G40.21-04	72, 75	302C25	BS 3100:1991 AMD.1:1992	359
26-3-3	ASTM A 268/A 268M-03	259	302C35	BS 3100:1991 AMD.1:1992	351, 356
	ASTM A 803/A 803M-03	262	303	ASTM	400, 403
26CrMo4-2	EN 10216-4:2002	199, 201		A 582/A 582M-95b (2000)	40.4
26Mn5	EN 10305-1:2002	175, 184	2222	ASTM A 895-89 (2000)	424
26Mo2	EN 10305-1:2002	185, 186	303Se	ASTM	400, 403
270-480	ISO 3755:1991	320, 323	304	A 582/A 582M-95b (2000) ASTM A 240/A 240M-03c	143, 146,
270-480W	ISO 3755:1991	320, 323	304	A31W A 240/A 240W-030	373, 380
27MnCrB5-2	EN 10083-3:1995	41		ASTM A 276-03	400, 404
28 Mn 6	ISO 683-1:1987	34		ASTM A 313/A 313M-03	429
28Cr4	EN 10084:1998	35		ASTM A 358/A 358M-01	225, 234
28CrS4	EN 10084:1998	35		ASTM A 473-01	298, 302
28Mn6	EN 10083-1:1991	34		ASTM A 666-03	373, 380
	EN 10250-2:1999	311	304C12	BS 3100:1991 AMD.1:1992	341, 344
28NiCrMoV8-5	EN 10250-3:1999	311	304C12LT196	BS 3100:1991 AMD.1:1992	341, 344
290 - Category I	CSA Z245.1-2002	246, 247	304C15	BS 3100:1991 AMD.1:1992	341, 344
290 - Category II	CSA Z245.1-2002	250, 253	304C15LT196	BS 3100:1991 AMD.1:1992	341, 344
290 - Category III	CSA Z245.1-2002	250, 253	304H	ASTM A 240/A 240M-03c	143, 146,
29-4	ASTM A 268/A 268M-03	259	30411	A31W A 240/A 240W-030	413
23-4	ASTM A 200/A 200W-03	259		ASTM A 358/A 358M-01	227, 236
	ASTM A 511-96 ASTM A 803/A 803M-03	262	304L	ASTM A 240/A 240M-03c	143. 146.
29-4-2	ASTM A 268/A 268M-03	259			373, 380
29-4-2				ASTM A 276-03	400, 404
	ASTM A 511-96	259		ASTM A 358/A 358M-01	226, 235
00.40	ASTM A 803/A 803M-03	262		ASTM A 473-01	298, 302
29-4C	ASTM A 803/A 803M-03	262		ASTM A 666-03	373, 380
3	ASTM A 266/A 266M-03a	311	304LN	ASTM A 240/A 240M-03c	143, 146,
	ASTM A 333/A 333M-99	197, 198			373, 381
	ASTM A 333/A 333M-99	199, 200		ASTM A 276-03	400, 405
	ASTM A 334/A 334M-99	199, 200		ASTM A 358/A 358M-01	262
	ASTM	108, 112		ASTM A 666-03	373, 381
	A 537/A 537M-95 (2000) ASTM A 735/A 735M-03	154	304N	ASTM A 240/A 240M-03c	143, 146,
3, Class 1	ASTM A 508/A 508M-03a	293		ACTM A 070 00	373, 381
o, olass i	ASTM A 300/A 300M-03a	293		ASTM A 276-03	400, 404
	A 541/A 541M-95 (1999)	290		ASTM A 358/A 358M-01	262
3, Class 2	ASTM A 508/A 508M-03a	293	224244	ASTM A 666-03	373, 381
-,	ASTM	293	304S11	BS 3605-1:1991 AMD 2:199	•
	A 541/A 541M-95 (1999)			BS 3605-2:1992 AMD 1:199	
30 [205]	ASTM A 1011/A 1011M-03	50, 66	304S31	BS 3605-1:1991 AMD 2:199	
30 CrNiMo 8	EN 10083-1:1991	44		BS 3605-2:1992 AMD 1:199	
30 MSCB 6.4-M	AFNOR NF A 32-058:1984	360	304S51	BS 3605-1:1991 AMD 2:199	
30 NSCDV 86-M	AFNOR NF A 32-058:1984	360	305	ASTM A 240/A 240M-03c	156, 373,
300W (44W)	CSA G40.21-04	72, 76		ACTM A 276 02	381
300WT (44WT)	CSA G40.21-04	72, 76		ASTM A 276-03	401, 405
301	ASTM A 240/A 240M-03c	156, 372,	200	ASTM A 313/A 313M-03	437
		378	308	ASTM A 167-99	413
	ASTM A 666-03	372, 378	000	ASTM A 276-03	415
301L	ASTM A 240/A 240M-03c	156, 372,	309	ASTM A 167-99	373, 381
	40TM 4 000 00	379	00000	ASTM A 276-03	402, 408
00/11/11	ASTM A 666-03	372, 379	309C30	BS 3100:1991 AMD.1:1992	
301LN	ASTM A 240/A 240M-03c	143, 146,	309C32	BS 3100:1991 AMD.1:1992	*
	ASTM A 666-03	372, 379 372, 379	309C35	BS 3100:1991 AMD.1:1992	•
302	ASTM A 240/A 240M-03c		309C40	BS 3100:1991 AMD.1:1992	
JU2	A3 I WI A 240/A 240WI-U3C	156, 372, 379	309Cb	ASTM A 240/A 240M-03c	156, 413
	ASTM A 276-03	400, 403		ASTM A 276-03	415
	ASTM A 313/A 313M-03	429		ASTM A 358/A 358M-01	262
	AGTIVI A GTG/A GTGIVI-UG				
			309H	ASTM A 240/A 240M-03c	143, 147,
302B	ASTM A 666-03 ASTM A 167-99	372, 379 372, 380	309H 309HCb	ASTM A 240/A 240M-03c ASTM A 240/A 240M-03c	143, 147, 413 156, 413

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
309S	ASTM A 240/A 240M-03c	156, 374,	316N (continued)	ASTM A 358/A 358M-01	262
	ACTM A 276 02	382		ASTM A 666-03	374, 384
	ASTM A 256/A 256M 01	401, 405	316S11	BS 3605-1:1991 AMD 2:1997	7 229, 239
000-14-4	ASTM A 358/A 358M-01	227, 236		BS 3605-2:1992 AMD 1:1997	7 229, 239
30CrMo4	EN 10297-1:2003	185, 186	316S13	BS 3605-1:1991 AMD 2:1997	7 229, 239
30CrMoV9	EN 10250-3:1999	311		BS 3605-2:1992 AMD 1:1997	7 229, 239
30CrNiMo8	EN 10250-3:1999	311	316S31	BS 3605-1:1991 AMD 2:1997	7 228, 238
	EN 10297-1:2003	258		BS 3605-2:1992 AMD 1:1997	7 228, 238
30MnB5	EN 10083-3:1995	44	316S33	BS 3605-1:1991 AMD 2:1997	7 228, 238
31 CrMo 12	ISO 683-10:1987	45		BS 3605-2:1992 AMD 1:1997	7 228, 238
31 CrNiMo 8	ISO 683-1:1987	45	316S51	BS 3605-1:1991 AMD 2:1997	7 230, 240
310	ASTM A 167-99	374, 382	316S52	BS 3605-1:1991 AMD 2:1997	7 230, 240
	ASTM A 276-03	402, 408	316Ti	ASTM A 240/A 240M-03c	144, 148,
	ASTM A 473-01	299, 303			375, 384
310C40	BS 3100:1991 AMD.1:1992	352, 357		ASTM A 276-03	402, 407
310C45	BS 3100:1991 AMD.1:1992	352, 357	317	ASTM A 240/A 240M-03c	156, 375
310Cb	ASTM A 240/A 240M-03c	156, 413		ASTM A 276-03	402, 407
	ASTM A 276-03	415		ASTM A 473-01	300, 305
	ASTM A 358/A 358M-01	262	317 - Category I	CSA Z245.1-2002	246, 248
310H	ASTM A 240/A 240M-03c	143, 147,	317 - Category II	CSA Z245.1-2002	250, 253
		413	317 - Category III	CSA Z245.1-2002	250, 253
310HCb	ASTM A 240/A 240M-03c	156, 413	317C16	BS 3100:1991 AMD.1:1992	342, 345
310MoLN	ASTM A 240/A 240M-03c	156, 374,	317L	ASTM A 240/A 240M-03c	144, 148,
		382			384, 413
310S	ASTM A 240/A 240M-03c	156, 374,	317LM	ASTM A 240/A 240M-03c	156, 413
	A O.T.A A O.Z.O O.O.	382	317LMN	ASTM A 240/A 240M-03c	145, 148,
	ASTM A 276-03	401, 405			375, 385
	ASTM A 358/A 358M-01	227, 237	317LN	ASTM A 240/A 240M-03c	144, 148,
311C11	BS 3100:1991 AMD.1:1992	353, 357	040047	DO 0100-1001 AMD 1-1000	375, 385
314	ASTM A 276-03	415	318C17	BS 3100:1991 AMD.1:1992	342, 345
3140	ASTM A 519-03	258	31CrMo12	EN 10085:2001	44
316	ASTM A 240/A 240M-03c	143, 147,	31CrMoV9	EN 10085:2001	44
	ACTM A 076 00	374, 383	32 NCD 8-M	AFNOR NF A 32-058:1984	360
	ASTM A 276-03	401, 406	321	ASTM A 240/A 240M-03c	145, 149,
	ASTM A 313/A 313M-03	429		ASTM A 276-03	376, 386 402, 408
	ASTM A 358/A 358M-01	228, 238		ASTM A 276-03 ASTM A 358/A 358M-01	-
	ASTM A 473-01	299, 303			231, 242
0.100.10	ASTM A 666-03	374, 383		ASTM A 473-01	300, 306
316C12	BS 3100:1991 AMD.1:1992	,	00411	ASTM A 313/A 313M-03	437
316C12LT196	BS 3100:1991 AMD.1:1992	•	321H	ASTM A 240/A 240M-03c	145, 149, 413
316C16	BS 3100:1991 AMD.1:1992	341, 345	321S31	BS 3605-1:1991 AMD 2:1997	
316C16LT196	BS 3100:1991 AMD.1:1992	341, 345	021001	BS 3605-2:1992 AMD 1:1997	
316Cb	ASTM A 240/A 240M-03c	144, 148,	321S51	BS 3605-1:1991 AMD 2:1997	-
	ACTNA A 07C 00	375, 384	329	ASTM A 240/A 240M-03c	
04011	ASTM A 276-03	415			156, 413
316H	ASTM A 240/A 240M-03c	144, 147,	32CrAlMo7-10	EN 10085:2001	40
	ASTM A 358/A 358M-01	413 230, 240	32CrMo12	EN 10250-3:1999	311
316L	ASTM A 240/A 240M-03c		32CrMoV12-28	ISO 4957:1999	434
310L	A31W A 240/A 240W-03C	144, 147, 374, 383	33 [230]	ASTM A 1011/A 1011M-03	52, 67
	ASTM A 276-03	401, 406	33 CrAlMo 5 4	ISO 683-10:1987	45
	ASTM A 358/A 358M-01	229, 239	330C11	BS 3100:1991 AMD.1:1992	•
	ASTM A 473-01	299, 304	330C12	BS 3100:1991 AMD.1:1992	-
	ASTM A 666-03	374, 383	331C40	BS 3100:1991 AMD.1:1992	
	. 10 1 111 / 1 000 00		331C60	BS 3100:1991 AMD.1:1992	353, 358
316l N	ASTM A 240/A 240M-036	144 14X			
316LN	ASTM A 240/A 240M-03c	144, 148, 375. 384	332C11	BS 3100:1991 AMD.1:1992	342, 346
316LN	ASTM A 240/A 240M-03c ASTM A 276-03	375, 384	332C11 332C13	BS 3100:1991 AMD.1:1992 BS 3100:1991 AMD.1:1992	•
316LN	ASTM A 276-03	375, 384 401, 407			343, 346
	ASTM A 276-03 ASTM A 358/A 358M-01	375, 384 401, 407 262	332C13	BS 3100:1991 AMD.1:1992	343, 346
316LN 316N	ASTM A 276-03	375, 384 401, 407	332C13 332C15	BS 3100:1991 AMD.1:1992 BS 3100:1991 AMD.1:1992	343, 346 343, 346

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
33MnCrB5-2	EN 10083-3:1995	41	36 Mn 6	ISO 683-1:1987	34
33NiCrMoV14-5	EN 10250-3:1999	311	36 NiCrMo 16	EN 10083-1:1991	44
34 Cr 4	ISO 683-1:1987	35	36 [250], Type 1	ASTM A 1011/A 1011M-03	53, 67
34 CrMo 4	ISO 683-1:1987	38	36 [250], Type 2	ASTM A 1011/A 1011M-03	54, 68
34 CrMoS 4	ISO 683-1:1987	38	36CrNiMo4	EN 10250-3:1999	311
34 CrNiMo 6	EN 10083-1:1991	44		EN 10297-1:2003	258
34 CrS 4	ISO 683-11:1987	35	36NiCrMo16	EN 10250-3:1999	311
340-550	ISO 3755:1991	321, 324	36SMn14	EN 10087:1998	420
340-550W	ISO 3755:1991	321, 324		EN 10277-3:1999	420
347	ASTM A 240/A 240M-03c	145, 149,	36SMnPb14	EN 10087:1998	423
		376, 386		EN 10277-3:1999	423
	ASTM A 276-03	402, 408	37 Cr 4	ISO 683-1:1987	35
	ASTM A 358/A 358M-01	232, 243	37 CrS 4	ISO 683-11:1987	35
	ASTM A 473-01	301, 306	37Cr4	EN 10083-1:1991	35
	ASTM A 313/A 313M-03	437		EN 10250-3:1999	311
347C17	BS 3100:1991 AMD.1:1992	341, 344	37CrS4	EN 10083-1:1991	35
347H	ASTM A 240/A 240M-03c	145, 149,	37S10	ASTM A 512-96 (2001)	257
		413	380W (55W)	CSA G40.21-04	73, 77
347S31	BS 3605-1:1991 AMD 2:199	•	386 - Category I	CSA Z245.1-2002	246, 248
	BS 3605-2:1992 AMD 1:199		386 - Category II	CSA Z245.1-2002	251, 254
347S51	BS 3605-1:1991 AMD 2:199	•	386 - Category III	CSA Z245.1-2002	251, 254
348	ASTM A 240/A 240M-03c	156, 413	38Cr2	EN 10083-1:1991	44
	ASTM A 276-03	415	333.2	EN 10250-3:1999	311
	ASTM A 358/A 358M-01	262	38CrCoWV18-17-17	ISO 4957:1999	434
348H	ASTM A 240/A 240M-03c	156, 413	38CrS2	EN 10083-1:1991	44
34Cr4	EN 10083-1:1991	35	38Mn6	EN 10297-1:2003	175, 184
	EN 10250-3:1999	311		EN 10083-3:1995	44
34CrAlMo5-10	EN 10085:2001	40	38MnB5		
34CrAlNi7-10	EN 10085:2001	40	38Si7	EN 10089:2002	425
34CrMo4	EN 10083-1:1991	38	38SMn28	EN 10087:1998	420
	EN 10250-3:1999	277, 278	000M-Ph-00	EN 10277-3:1999	420
	EN 10297-1:2003	185, 187	38SMnPb28	EN 10087:1998	423
34CrMoS4	EN 10083-1:1991	38	00140	EN 10277-3:1999	423
34CrNiMo6	EN 10250-3:1999	311	39MnCrB5-2	EN 10083-3:1995	41
34CrS4	EN 10083-1:1991	35	3V	ASTM A 508/A 508M-03a	285
35	ASTM A 1005/A 1005M-00	250, 253		ASTM	285
	ASTM A 984/A 984M-03	250, 253	3VCb	A 541/A 541M-95 (1999) ASTM A 508/A 508M-03a	312
35 CD 4-M	AFNOR NF A 32-058:1984	360	3705	ASTM A 300/A 300M-03a	312
35 CDV 10 4-M	AFNOR NF A 32-058:1984	360		A 541/A 541M-95 (1999)	012
35 S 20	ISO 683-9:1988	420	4	ASTM A 266/A 266M-03a	273, 275
35 SMn 20	ISO 683-9:1988	420		ASTM A 333/A 333M-99	260
350A (50A)	CSA G40.21-04	90, 95		ASTM	360
350AT (50AT)	CSA G40.21-04	90, 95		A 487/A 487M-93 (2003)	
350R (50R)	CSA G40.21-04	90, 95		ASTM A 735/A 735M-03	154
350W (50W)	CSA G40.21-04	73, 77	40 [275]	ASTM A 1011/A 1011M-03	54, 68
350WT (50WT)	CSA G40.21-04	73, 77	400A (60A)	CSA G40.21-04	93, 96
359 - Category I	CSA Z245.1-2002	246, 248	400AT (60AT)	CSA G40.21-04	93, 96
359 - Category II	CSA Z245.1-2002	251, 254	400W (60W)	CSA G40.21-04	74, 78
359 - Category III	CSA Z245.1-2002	251, 254	400WT (60WT)	CSA G40.21-04	74, 78
35CrMo7	ISO 4957:1999	438	4012	ASTM A 29/A 29M-03	43
35S20	EN 10087:1998	420		ASTM A 519-03	258
	EN 10277-3:1999	420	4023	ASTM A 29/A 29M-03	43
35SPb20	EN 10087:1998	436		ASTM A 322-91 (2001)	43
-	EN 10277-3:1999	436		ASTM A 519-03	258
36 [250]	ASTM A 709/A 709M-03a	54, 68		SAE J404 JUN00	44
36 CrNiMo 4	EN 10083-1:1991	44	4024	ASTM A 29/A 29M-03	43
55 OII 111110 T	ISO 683-1:1987	45		ASTM A 322-91 (2001)	43
36 CrNiMo 6	ISO 683-1:1987	45		ASTM A 519-03	258
33 311 11110 0	.50 000 111007				

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
4027	ASTM A 29/A 29M-03	43	4137 (continued)	SAE J404 JUN00	38
	ASTM A 322-91 (2001)	43	414	ASTM A 276-03	415
4007	ASTM A 519-03	258	414 - Category I	CSA Z245.1-2002	246, 248
4027	SAE J404 JUN00	44	414 - Category II	CSA Z245.1-2002	251, 255
4028	ASTM A 29/A 29M-03	43	414 - Category III	CSA Z245.1-2002	251, 255
	ASTM A 510 00	43	4140	ASTM A 29/A 29M-03	38
400	ASTM A 519-03	185, 186		ASTM A 322-91 (2001)	38
403	ASTM A 176-99	366, 367		ASTM A 513-03a	185, 187
4000	ASTM A 22/4-22/4-22	394, 396		ASTM A 519-03	185, 187
4032	ASTM A 29/A 29M-03	43	44.40	SAE J404 JUN00	38
4037	ASTM A 29/A 29M-03	43	4142	ASTM A 29/A 29M-03	43
	ASTM A 322-91 (2001)	43		ASTM A 322-91 (2001)	43
	ASTM A 519-03	258		ASTM A 519-03	185, 187
40.40	SAE J404 JUN00	44		SAE J404 JUN00	44
4042	ASTM A 29/A 29M-03	43	4145	ASTM A 29/A 29M-03	38
	ASTM A 519-03	258		ASTM A 322-91 (2001)	38
4047	ASTM A 29/A 29M-03	43		ASTM A 519-03	257
	ASTM A 322-91 (2001)	43		SAE J404 JUN00	38
	ASTM A 519-03	258	4147	ASTM A 29/A 29M-03	43
	SAE J404 JUN00	44		ASTM A 322-91 (2001)	43
405	ASTM A 240/A 240M-03c	141, 142,		ASTM A 519-03	258
	A C.T.M. A. 0.7.C. 0.0	368, 370	4150	ASTM A 29/A 29M-03	38
4000	ASTM A 276-03	398, 399		ASTM A 322-91 (2001)	38
4063	ASTM A 519-03	258		ASTM A 519-03	258
409	ASTM A 240/A 240M-03c	413		SAE J404 JUN00	38
40CrMnNiMo8-6-4	ISO 4957:1999	438	416	ASTM	394, 396
40CrMoV13-9	EN 10085:2001	44		A 582/A 582M-95b (2000)	
	EN 10250-3:1999	311		ASTM A 895-89 (2000)	424
41 Cr 4	ISO 683-1:1987	36	4161	ASTM A 29/A 29M-03	43
41 CrAlMo 7 4	ISO 683-10:1987	40		ASTM A 322-91 (2001)	43
41 CrNiMo 2	ISO 683-1:1987	39		ASTM A 689-97 (2002)	428
41 CrNiMoS 2	ISO 683-1:1987	39	416Se	ASTM	415
41 CrS 4	ISO 683-11:1987	36	41Cr4	A 582/A 582M-95b (2000)	26
410	ASTM A 240/A 240M-03c	156, 366,	41014	EN 10083-1:1991 EN 10250-3:1999	36 311
	A C.T.M. A. 0.7.C. 0.0	367			
	ASTM A 276-03	394, 396	410-4114-7-10	EN 10297-1:2003	258
440004	ASTM A 473-01	295, 296	41CrAlMo7-10	EN 10085:2001	40
410C21	BS 3100:1991 AMD.1:1992	339, 340	41CrS4	EN 10083-1:1991	36
410S	ASTM A 240/A 240M-03c	156, 366,	41NiCrMo7-3-2	EN 10297-1:2003	258
4118	ASTM A 29/A 29M-03	367 37	42 [290], Type 1	ASTM A 572/A 572M-03a	72, 75
4110	ASTM A 322-91 (2001)	37	42 [290], Type 2	ASTM A 572/A 572M-03a	72, 75
	ASTM A 513-03a	258	42 [290], Type 3	ASTM A 572/A 572M-03a	72, 75
	ASTM A 519-03	258	42 [290], Type 4	ASTM A 572/A 572M-03a	72, 75
	SAE J404 JUN00	37	42 [290], Type 5	ASTM A 572/A 572M-03a	72, 75
4120	ASTM A 29/A 29M-03	37	42 CD 4-M	AFNOR NF A 32-058:1984	360
4120	SAE J404 JUN00	37	42 CrMo 4	ISO 683-1:1987	38
4121			42 CrMoS 4	ISO 683-1:1987	38
	ASTM A 29/A 29M-03	37	42 Mn 6	ISO 683-1:1987	34
4130	ASTM A 29/A 29M-03	37	42 NCD 16-M	AFNOR NF A 32-058:1984	360
	ASTM A 322-91 (2001)	37	420	ASTM A 176-99	366, 367
	ASTM A 513-03a	185, 186	420C24	BS 3100:1991 AMD.1:1992	351, 355
	ASTM A 519-03	185, 186	420C28	BS 3100:1991 AMD.1:1992	339, 340
44.05	SAE J404 JUN00	37	420C29	BS 3100:1991 AMD.1:1992	339, 340
4135	ASTM A 29/A 29M-03	43	420F	ASTM	394, 397
	ASTM A 519-03	185, 187	10050	A 582/A 582M-95b (2000)	446
	SAE J404 JUN00	44	420FSe	ASTM	415
4137	ASTM A 29/A 29M-03	38	422	A 582/A 582M-95b (2000) ASTM A 176-99	413
	ASTM A 322-91 (2001)	38	425C11	BS 3100:1991 AMD.1:1992	339, 340
	ASTM A 519-03	185, 187	420011	DO 0100.1991 AMD.1.1992	555, 540

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
425C12	BS 3100:1991 AMD.1:1992	,	45 [310]	ASTM A 1011/A 1011M-03	56, 69
429	ASTM A 240/A 240M-03c	156, 413	45 [310], Class 1	ASTM A 1011/A 1011M-03	72
	ASTM A 276-03	415	45 CSD 6-M	AFNOR NF A 32-058:1984	360
42CrMo4	EN 10083-1:1991	38	45 S7-M	AFNOR NF A 32-058:1984	360
	EN 10250-3:1999	277, 278	45 [310] Class 2	ASTM A 1011/A 1011M-03	97
	EN 10297-1:2003	185, 187	4520	ASTM A 519-03	258
	EN 10305-1:2002	185, 187	452C11	BS 3100:1991 AMD.1:1992	351, 355
42CrMoS4	EN 10083-1:1991	38	452C12	BS 3100:1991 AMD.1:1992	351, 355
430	ASTM A 182/A 182M-02	297	45NiCrMo16	ISO 4957:1999	438
	ASTM A 240/A 240M-03c	156, 368,	45SiCrV6-2	EN 10089:2002	437
		370	46 S 20	ISO 683-9:1988	421
	ASTM A 276-03	398, 399	4615	ASTM A 29/A 29M-03	43
	ASTM A 473-01	297		ASTM A 322-91 (2001)	43
430F	ASTM	398, 399		ASTM A 519-03	258
40050-	A 582/A 582M-95b (2000)	445		SAE J404 JUN00	44
430FSe	ASTM A 582/A 582M-95b (2000)	415	4617	ASTM A 519-03	258
431	ASTM A 176-99	413		SAE J404 JUN00	44
101	ASTM A 276-03	394, 397	4620	ASTM A 29/A 29M-03	43
4320	ASTM A 29/A 29M-03	39	.0_0	ASTM A 322-91 (2001)	43
4320	ASTM A 29/A 29M-03 ASTM A 322-91 (2001)	39		ASTM A 519-03	258
	ASTM A 522-91 (2001) ASTM A 519-03	258		SAE J404 JUN00	44
	SAE J404 JUN00	39	4621	ASTM A 29/A 29M-03	43
4337	ASTM A 519-03	258	4021	ASTM A 322-91 (2001)	43
434	ASTM A 319-03 ASTM A 240/A 240M-03c			ASTM A 519-03	258
434	ASTIVI A 240/A 240/VI-030	156, 368, 370	4626	ASTM A 29/A 29M-03	43
4340	ASTM A 29/A 29M-03	39	4020	ASTM A 322-91 (2001)	43
	ASTM A 322-91 (2001)	39	46Cr2	EN 10250-3:1999	311
	ASTM A 519-03	258	46Cr4	EN 10230-3.1999 EN 10083-1:1991	44
	SAE J404 JUN00	39	46CrS4	EN 10083-1:1991	44
436	ASTM A 240/A 240M-03c	156, 413			
439	ASTM A 240/A 240M-03c	141, 142,	46S20	EN 10087:1998	421
100	7.6 1.11 7.12 16,7 12 16111 666	368, 371	400:7	EN 10277-3:1999	421
44 SMn 28	ISO 683-9:1988	421	46Si7	EN 10089:2002	425
440A	ASTM A 276-03	394, 397	46SiCrMo6	EN 10089:2002	437
440B	ASTM A 276-03	394, 397	46SPb20	EN 10087:1998	423
440C	ASTM A 276-03	395, 397		EN 10277-3:1999	423
440F	ASTM	415	4715	ASTM A 29/A 29M-03	43
	A 582/A 582M-95b (2000)		4718	ASTM A 29/A 29M-03	43
440FSe	ASTM	415		ASTM A 519-03	258
	A 582/A 582M-95b (2000)		4720	ASTM A 29/A 29M-03	43
4419	ASTM A 29/A 29M-03	43		ASTM A 322-91 (2001)	43
442	ASTM A 176-99	413		ASTM A 519-03	258
4422	ASTM A 29/A 29M-03	43	480A (70A)	CSA G40.21-04	93, 96
	ASTM A 519-03	258	480AT (70AT)	CSA G40.21-04	93, 96
4427	ASTM A 29/A 29M-03	43	480W (70W)	CSA G40.21-04	98
	ASTM A 519-03	258	480WT (70WT)	CSA G40.21-04	80, 84
444	ASTM A 240/A 240M-03c	141, 142,	4815	ASTM A 29/A 29M-03	43
	ACTM A 076 00	369, 371		ASTM A 322-91 (2001)	43
440	ASTM A 276-03	415		ASTM A 519-03	258
446	ASTM A 176-99	369, 371	4817	ASTM A 29/A 29M-03	43
4.47	ASTM A 276-03	398, 399		ASTM A 322-91 (2001)	43
447	ASTM A 276-03	398, 399		ASTM A 519-03	258
448 - Category I	CSA Z245.1-2002	246, 248	4820	ASTM A 29/A 29M-03	43
448 - Category II	CSA Z245.1-2002	252, 255		ASTM A 322-91 (2001)	43
448 - Category III	CSA Z245.1-2002	252, 255		ASTM A 519-03 `	258
44SMn28	EN 10087:1998	421		SAE J404 JUN00	44
	EN 10277-3:1999	421	483 - Category I	CSA Z245.1-2002	246, 249
44SMnPb28	EN 10087:1998	423		CSA Z245.1-2002	252, 256
440WIII 020	EN 10277-3:1999	423	483 - Category II	USA Z243. 1-2002	202. 200

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
48Si7	EN 10132-4:2000	437	50CrMoV13-15	ISO 4957:1999	438
4N, Class 1	ASTM A 508/A 508M-03a	312	50S [345S]	ASTM A 709/A 709M-03a	97
	ASTM	312	50SiCrMo6	EN 10089:2002	437
4N. Class 0	A 541/A 541M-95 (1999)	010	50W [345W], Type A	ASTM A 709/A 709M-03a	79, 84
4N, Class 2	ASTM A 508/A 508M-03a	312	50W [345W], Type B	ASTM A 709/A 709M-03a	79, 84
	ASTM A 541/A 541M-95 (1999)	312	50W [345W], Type C	ASTM A 709/A 709M-03a	79, 84
4N, Class 3	ASTM A 508/A 508M-03a	294	50WCrV8	ISO 4957:1999	438
,	ASTM	294	51 B 60	ASTM A 689-97 (2002)	428
	A 541/A 541M-95 (1999)		51 CrV 4	ISO 683-1:1987	42
5, Class 1	ASTM A 508/A 508M-03a	312		ISO 683-14:1992	428
	ASTM	312	5115	ASTM A 29/A 29M-03	43
	A 541/A 541M-95 (1999)			ASTM A 519-03	258
	ASTM A 387/A 387M-03	127		SAE J404 JUN00	44
5, Class 2	ASTM A 508/A 508M-03a	312	5117	ASTM A 322-91 (2001)	43
	ASTM	312	5120	ASTM A 29/A 29M-03	35
	A 541/A 541M-95 (1999)	107		ASTM A 322-91 (2001)	35
50	ASTM A 1005/A 1005M 00	127		ASTM A 519-03	258
50	ASTM A 1005/A 1005M-00	263		SAE J404 JUN00	35
EO [240]	ASTM A 984/A 984M-03	251, 254	5130	ASTM A 29/A 29M-03	35
50 [340]	ASTM A 1011/A 1011M-03	58, 69		ASTM A 322-91 (2001)	35
50 [340], Class 1	ASTM A 1011/A 1011M-03	72		ASTM A 513-03a	258
50 [340], Class 2	ASTM A 1011/A 1011M-03	72 50. 70		ASTM A 519-03	258
50 [345]	ASTM A 529/A 529M-03	59, 70		SAE J404 JUN00	35
50 [345], Type 1	ASTM A 572/A 572M-03a	72, 76	5132	ASTM A 29/A 29M-03	35
50 [045] Tues 0	ASTM A 709/A 709M-03a	72, 75		ASTM A 322-91 (2001)	35
50 [345], Type 2	ASTM A 572/A 572M-03a	72, 76		ASTM A 519-03	258
50 [0.45]. T 0	ASTM A 709/A 709M-03a	72, 75		SAE J404 JUN00	35
50 [345], Type 3	ASTM A 572/A 572M-03a	72, 76	5135	ASTM A 29/A 29M-03	35
	ASTM A 656/A 656M-03	72, 75		ASTM A 519-03 SAE J404 JUN00 ASTM A 29/A 29M-03 ASTM A 322-91 (2001) ASTM A 519-03 SAE J404 JUN00 ASTM A 29/A 29M-03 ASTM A 322-91 (2001) ASTM A 519-03 ASTM A 29/A 29M-03 ASTM A 322-91 (2001) ASTM A 322-91 (2001) ASTM A 519-03 SAE J404 JUN00	35
E0 [0.45]. T 4	ASTM A 709/A 709M-03a	72, 75		ASTM A 519-03	258
50 [345], Type 4	ASTM A 572/A 572M-03a	72, 76	5140		36
50 (0.45). To 5	ASTM A 709/A 709M-03a	72, 75		ASTM A 322-91 (2001)	36
50 [345], Type 5	ASTM A 572/A 572M-03a	72, 76		ASTM A 519-03	258
50 (0.45) T 7	ASTM A 709/A 709M-03a	72, 75			36
50 [345], Type 7	ASTM A 656/A 656M-03	72, 75	5145	ASTM A 29/A 29M-03	36
50 CD 4-M	AFNOR NF A 32-058:1984	360		ASTM A 519-03	258
50 CrMo 4	ISO 683-1:1987	38	5147	ASTM A 29/A 29M-03	43
50 NSCDV 5-M	AFNOR NF A 32-058:1984	360		ASTM A 519-03	258
5015	ASTM A 29/A 29M-03	43	5150	ASTM A 29/A 29M-03	43
	ASTM A 519-03	258		ASTM A 322-91 (2001)	43
5046	ASTM A 29/A 29M-03	43		ASTM A 519-03	258
	ASTM A 519-03	258		SAE J404 JUN00	44
50B40	ASTM A 519-03	258	5155	ASTM A 29/A 29M-03	43
50B44	ASTM A 29/A 29M-03	41		ASTM A 322-91 (2001)	43
	ASTM A 322-91 (2001)	41		ASTM A 519-03	258
	ASTM A 519-03	258		ASTM A 689-97 (2002)	427
50B46	ASTM A 29/A 29M-03	41	5160	ASTM A 29/A 29M-03	43
	ASTM A 322-91 (2001)	41	0.00	ASTM A 295-98	439
	ASTM A 519-03	258		ASTM A 322-91 (2001)	43
	SAE J404 JUN00	41		ASTM A 519-03	258
50B50	ASTM A 29/A 29M-03	41		ASTM A 689-97 (2002)	427
	ASTM A 322-91 (2001)	41		SAE J404 JUN00	44
	ASTM A 519-03	258	5195	ASTM A 295-98	439
50B60	ASTM A 29/A 29M-03	41	51B60	ASTM A 29/A 29M-03	439
	ASTM A 322-91 (2001)	41	31000	ASTM A 322-91 (2001)	41
	ASTM A 519-03	258			
50CrMo4	EN 10083-1:1991	38	51R61	SAE J404 JUN00 ASTM A 510-03	41 258
	EN 10250-3:1999	277, 278	51B61	ASTM A 519-03	258

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
51CrV4	EN 10083-1:1991	42	60 [415], Type IV	ASTM A 871/A 871M-03	93, 96
	EN 10089:2002	428	60 CrB 3	ISO 683-14:1992	428
	EN 10132-4:2002	428	60 CrMo 3 1	ISO 683-14:1992	437
	EN 10250-3:1999	311	60 CrMo 3 3	ISO 683-14:1992	428
52 CrMoV 4	ISO 683-14:1992	437	60-30	ASTM A 27/A 27M-03	319, 323
52100	ASTM A 295-98	435	60Cr3	EN 10089:2002	427
52CrMoV4	EN 10089:2002	437	60CrMo3-1	EN 10089:2002	428
52SiCrNi5	EN 10089:2002	437	60CrMo3-2	EN 10089:2002	428
54SiCr6	EN 10089:2002	427	60CrMo3-3	EN 10089:2002	428
54SiCrV6	EN 10089:2002	428	60SiCrV7	EN 10089:2002	437
55 [380]	ASTM A 1011/A 1011M-03	59, 70	60WCrV8	ISO 4957:1999	438
	ASTM A 516/A 516M-03	153	61 SiCr 7	ISO 683-14:1992	437
	ASTM A 529/A 529M-03	59, 70	6118	ASTM A 29/A 29M-03	43
55 [380], Class 1	ASTM A 1011/A 1011M-03	73		ASTM A 322-91 (2001)	43
55 [380], Class 2	ASTM A 1011/A 1011M-03	72		ASTM A 519-03	258
55 [380], Type 1	ASTM A 572/A 572M-03a	73, 77	6120	ASTM A 519-03	258
55 [380], Type 2	ASTM A 572/A 572M-03a	73, 77	6150	ASTM A 29/A 29M-03	42
55 [380], Type 3	ASTM A 572/A 572M-03a	73, 77		ASTM A 322-91 (2001)	42
55 [380], Type 4	ASTM A 572/A 572M-03a	73, 77		ASTM A 519-03	258
55 [380], Type 5	ASTM A 572/A 572M-03a	73, 77		ASTM A 689-97 (2002)	428
55 Cr 3	ISO 683-14:1992	427		SAE J404 JUN00	42
55 SiCr 6 3	ISO 683-14:1992	427	61SiCr7	EN 10089:2002	437
550 - Category I	CSA Z245.1-2002	246, 249	620	BS 3604-2:1991	217, 218
550 - Category II	CSA Z245.1-2002	252, 256	620 Category I	CSA Z245.1-2002	263
550 - Category III	CSA Z245.1-2002	252, 256	620 Category II	CSA Z245.1-2002	263
550A (80A)	CSA G40.21-04	93, 96	620 Category III	CSA Z245.1-2002	263
550AT (80AT)	CSA G40.21-04	93, 96	621	BS 3604-2:1991	219
550W (80W)	CSA G40.21-04	98	622	BS 3604-2:1991	220
550WT (80WT)	CSA G40.21-04	81, 85	630	ASTM A 564/A 564M-02a	409, 410
55Cr3	EN 10089:2002	427		ASTM A 693-03	387, 388
55NiCrMoV7	ISO 4957:1999	434		ASTM	307, 308
56 SiCr 7	ISO 683-14:1992	437		A 705/A 705M-95(2000)	
56Si7	EN 10089:2002	425	631	ASTM A 313/A 313M-03	429
	EN 10132-4:2000	437		ASTM A 564/A 564M-02a	409, 411
56SiCr7	EN 10089:2002	437		ASTM A 693-03	387, 390
58 [400]	ASTM A 573/A 573M-00a	54, 68	632	ASTM A 564/A 564M-02a	415
59 Si 7	ISO 683-14:1992	427		ASTM A 693-03	387, 391
6	ASTM A 333/A 333M-99	197, 198	633	ASTM A 693-03	413
	ASTM A 334/A 334M-99	197, 198	634	ASTM A 564/A 564M-02a	415
	ASTM	360		ASTM A 693-03	413
	A 487/A 487M-93 (2003)		635	ASTM A 564/A 564M-02a	415
60	ASTM A 1005/A 1005M-00	251, 255		ASTM A 693-03	413
	ASTM A 181/A 181M-01	272, 275	65 [450]	ASTM A 515/A 515M-03	105, 110
	ASTM A 984/A 984M-03	252, 255		ASTM A 516/A 516M-03	105, 110
60 [410], Class 1	ASTM A 1011/A 1011M-03	74		ASTM A 573/A 573M-00a	58, 69
60 [410], Class 2	ASTM A 1011/A 1011M-03	73	65 [450], Class 1	ASTM A 1011/A 1011M-03	74
60 [415]	ASTM A 515/A 515M-03	104, 109	65 [450], Class 2	ASTM A 1011/A 1011M-03	74
	ASTM A 516/A 516M-03	104, 109	65 [450], Type 1	ASTM A 572/A 572M-03a	74, 78
60 [415], Type 1	ASTM A 572/A 572M-03a	74, 78	65 [450], Type 2	ASTM A 572/A 572M-03a	74, 78
60 [415], Type 2	ASTM A 572/A 572M-03a	74, 78	65 [450], Type 3	ASTM A 572/A 572M-03a	74, 78
60 [415], Type 3	ASTM A 572/A 572M-03a	74, 78	65 [450], Type 4	ASTM A 572/A 572M-03a	74, 78
	ASTM A 656/A 656M-03	73, 77	65 [450], Type 5	ASTM A 572/A 572M-03a	74, 78
60 [415], Type 4	ASTM A 572/A 572M-03a	74, 78	65 [450], Type I	ASTM A 871/A 871M-03	93, 96
60 [415], Type 5	ASTM A 572/A 572M-03a	74, 78	65 [450], Type II	ASTM A 871/A 871M-03	93, 96
60 [415], Type 7	ASTM A 656/A 656M-03	73, 77	65 [450], Type III	ASTM A 871/A 871M-03	93, 96
60 [415], Type I	ASTM A 871/A 871M-03	93, 96	65 [450], Type IV	ASTM A 871/A 871M-03	93, 96
60 [415], Type II	ASTM A 871/A 871M-03	93, 96	65-35	ASTM A 27/A 27M-03	319, 323
60 [415], Type III	ASTM A 871/A 871M-03	93, 96	690 Category I	CSA Z245.1-2002	263

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
690 Category II	CSA Z245.1-2002	263	8620 (continued)	ASTM A 519-03	258
690 Category III	CSA Z245.1-2002	263		SAE J404 JUN00	39
7	ASTM A 333/A 333M-99	260	8622	ASTM A 29/A 29M-03	43
	ASTM A 334/A 334M-99	260		ASTM A 322-91 (2001)	43
	ASTM	360		ASTM A 519-03	258
70	A 487/A 487M-93 (2003)	050 056		SAE J404 JUN00	44
70	ASTM A 1005/A 1005M-00	252, 256	8625	ASTM A 29/A 29M-03	43
	ASTM A 181/A 181M-01	273, 275		ASTM A 322-91 (2001)	43
70 [400] 0 0	ASTM A 984/A 984M-03	263		ASTM A 519-03	258
70 [480], Class 2	ASTM A 1011/A 1011M-03	74		SAE J404 JUN00	44
70 [485]	ASTM A 515/A 515M-03	105, 111	8627	ASTM A 29/A 29M-03	43
	ASTM A 516/A 516M-03	105, 111		ASTM A 322-91 (2001)	43
	ASTM A 573/A 573M-00a	59, 70		ASTM A 519-03	258
70 [485], Type 3	ASTM A 656/A 656M-03	74, 78		SAE J404 JUN00	44
70 [485], Type 7	ASTM A 656/A 656M-03	74, 78	8630	ASTM A 29/A 29M-03	43
70 [480], Class 1	ASTM A 1011/A 1011M-03	97		ASTM A 322-91 (2001)	43
700Q (100Q)	CSA G40.21-04	83, 87		ASTM A 513-03a	258
700QT (100QT)	CSA G40.21-04	83, 87		ASTM A 519-03	258
70-36	ASTM A 27/A 27M-03	320, 323		SAE J404 JUN00	44
70-40	ASTM A 27/A 27M-03	320, 323	8637	ASTM A 29/A 29M-03	43
70MnMoCr8	ISO 4957:1999	438	0007	ASTM A 322-91 (2001)	43
75Ni8	EN 10132-4:2000	437		ASTM A 519-03	258
3	ASTM A 333/A 333M-99	197, 198		SAE J404 JUN00	44
	ASTM A 333/A 333M-99	199, 201	8640		
	ASTM A 334/A 334M-99	199, 201	8640	ASTM A 29/A 29M-03	39
B, Class A	ASTM	335, 336		ASTM A 322-91 (2001)	39
, 0.0007.	A 487/A 487M-93 (2003)	333, 333		ASTM A 519-03	258
B, Class B	ASTM	335, 336		SAE J404 JUN00	39
	A 487/A 487M-93 (2003)		8642	ASTM A 29/A 29M-03	43
B, Class C	ASTM	335, 336		ASTM A 322-91 (2001)	43
20	A 487/A 487M-93 (2003)	050 050		ASTM A 519-03	258
30	ASTM A 055/A 055M-00	252, 256	8645	ASTM A 29/A 29M-03	43
	ASTM A 656/A 656M-03	98		ASTM A 322-91 (2001)	43
200	ASTM A 984/A 984M-03	252, 256		ASTM A 519-03	258
300	ASTM A 240/A 240M-03c	145, 149,		SAE J404 JUN00	44
		233, 245, 413	8650	ASTM A 29/A 29M-03	43
300H	ASTM A 240/A 240M-03c	145, 150,		ASTM A 519-03	258
50011	7.6 TM 7.7 240/7.7 240M 666	233, 245,	8655	ASTM A 29/A 29M-03	43
		413		ASTM A 322-91 (2001)	43
30-40	ASTM A 148/A 148M-03	321, 324		ASTM A 519-03	258
30-50	ASTM A 148/A 148M-03	321, 324		SAE J404 JUN00	44
30CrV2	EN 10132-4:2000	437	8660	ASTM A 29/A 29M-03	43
3115	ASTM A 29/A 29M-03	43		ASTM A 519-03	258
	ASTM A 519-03	258	86B45	ASTM A 519-03	258
31B45	ASTM A 29/A 29M-03	43	8720	ASTM A 29/A 29M-03	43
	ASTM A 322-91 (2001)	43	0.20	ASTM A 322-91 (2001)	43
	ASTM A 519-03	258		ASTM A 519-03	258
35 CDV 12-M	AFNOR NF A 32-058:1984	360		SAE J404 JUN00	44
3615	ASTM A 29/A 29M-03	43	8735	ASTM A 519-03	258
,010	ASTM A 322-91 (2001)	43			
	ASTM A 519-03	258	8740	ASTM A 29/A 29M-03	43
	SAE J404 JUN00	44		ASTM A 510 03	43
2617				ASTM A 519-03	258
3617	ASTM A 29/A 29M-03	43	0746	SAE J404 JUN00	44
	ASTM A 322-91 (2001)	43	8742	ASTM A 519-03	258
	ASTM A 519-03	258	8822	ASTM A 29/A 29M-03	43
2000	SAE J404 JUN00	44		ASTM A 322-91 (2001)	43
3620	ASTM A 29/A 29M-03	39		ASTM A 519-03	258
	ASTM A 322-91 (2001)	39		SAE J404 JUN00	44
	ASTM A 513-03a	258	8MoB5-4	EN 10216-2:2002	214, 21

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
9	ASTM A 333/A 333M-99	260	A (continued)	ASTM A 668/A 668M-03	268, 271
	ASTM A 334/A 334M-99	260		ASTM A 678/A 678M-00a	59, 70
	ASTM	360		ASTM A 724/A 724M-99	154
2.0.00	A 487/A 487M-93 (2003)	400		ASTM	154
9 S 20	ISO 683-9:1988	422	. 50	A 734/A 734M-87a (2003)	
9, Class 1	ASTM A 387/A 387M-03	153	A - PSL 1	API 5L-2004	246, 247
9, Class 2	ASTM A 387/A 387M-03	153	A, Class 1	ASTM A 1021-02	295, 296
904L	ASTM A 240/A 240M-03c	145, 149,		ASTM A 710/A 710M-02	81, 85
	ACTM A 140/A 140M 00	375, 385		ASTM A 736/A 736M-03	154
90-60	ASTM A 148/A 148M-03	321, 324		ASTM A 841/A 841M-03a	114, 116
90MnCrV8	ISO 4957:1999	438	A, Class 2	ASTM A 1021-02	295, 296
91, Class 2	ASTM A 387/A 387M-03	128		ASTM A 710/A 710M-02	79, 84
911, Class 2	ASTM A 387/A 387M-03	128		ASTM A 736/A 736M-03	154
9254	ASTM A 29/A 29M-03	43		ASTM A 841/A 841M-03a	114, 116
	SAE J404 JUN00	44	A, Class 3	ASTM A 710/A 710M-02	80, 84
9255	ASTM A 29/A 29M-03	43		ASTM A 736/A 736M-03	154
	ASTM A 519-03	258	A1	BS 3100:1991 AMD.1:1992	319, 323
9259	ASTM A 29/A 29M-03	43	A-1	ASTM A 210/A 210M-02	208, 211
	ASTM A 322-91 (2001)	43	A10	ASTM A 681-94 (1999)	438
	SAE J404 JUN00	44	A1Q	ASTM A 757/A 757M-00	327
9260	ASTM A 29/A 29M-03	43	A2		
	ASTM A 322-91 (2001)	43	MC	ASTM A 556/A 556M-96 (2001)	206, 210
	ASTM A 519-03	258		ASTM A 681-94 (1999)	433
	ASTM A 689-97 (2002)	427		BS 3100:1991 AMD.1:1992	320, 323
	, ,	44		SAE J438-1970	433
0000	SAE J404 JUN00		A25 Class I - PSL 1		
9262	ASTM A 519-03	258		API 5L-2004	246, 247
94B15	ASTM A 519-03	258	A25 Class II - PSL 1	API 5L-2004	246, 247
94B17	ASTM A 29/A 29M-03	43	A2Q	ASTM A 757/A 757M-00	327
	ASTM A 322-91 (2001)	43	A3	ASTM A 681-94 (1999)	438
	ASTM A 519-03	258		BS 3100:1991 AMD.1:1992	320, 324
94B30	ASTM A 29/A 29M-03	43	A4	ASTM A 681-94 (1999)	438
	ASTM A 322-91 (2001)	43		BS 3100:1991 AMD.1:1992	320, 324
	ASTM A 519-03	258	A5	ASTM A 681-94 (1999)	438
94B40	ASTM A 519-03	258		BS 3100:1991 AMD.1:1992	321, 324
5MnWCr5	ISO 4957:1999	438	A6	ASTM A 681-94 (1999)	438
9840	ASTM A 519-03	258		BS 3100:1991 AMD.1:1992	322, 325
9850	ASTM A 519-03	258	A7	ASTM A 681-94 (1999)	438
A	ASTM A 106-02a	206, 210	A8	ASTM A 681-94 (1999)	438
	ASTM	328, 329	A9	ASTM A 681-94 (1999)	438
	A 128/A 128M-93 (2003)	020, 020	AL1	BS 3100:1991 AMD.1:1992	359
	ASTM A 135-01	202, 204	AL2	BS 3100:1991 AMD.1:1992	359
	ASTM A 139-00	202, 204	AL3	BS 3100:1991 AMD.1:1992	
	ASTM A 178/A 178M-02	206, 210	AM1	BS 3100:1991 AMD.1:1992	
	ASTM A 202/A 202M-03	153	AM2	BS 3100:1991 AMD.1:1992	359
	ASTM	131			
	A 203/A 203M-97 (2003)		AW1	BS 3100:1991 AMD.1:1992	359
	ASTM A 204/A 204M-03	117, 119	AW2	BS 3100:1991 AMD.1:1992	359
	ASTM A 283/A 283M-03	50, 66	AW3	BS 3100:1991 AMD.1:1992	359
	ASTM A 285/A 285M-03	153	В	ASTM A 106-02a	208, 211
	ASTM A 302/A 302M-03	117, 119		ASTM A 135-01	203, 205
	ASTM A 355-89 (2000)	40		ASTM A 139-00	203, 205
	ASTM A 500-03	166, 177		ASTM A 202/A 202M-03	153
		•		ASTM	131
	ASTM A 514/A 514M-00a	82, 86		A 203/A 203M-97 (2003)	
	ASTM A 517/A 517M 02 (1000)	153		ASTM A 204/A 204M-03	117, 119
	A 517/A 517M-93 (1999)	73, 77		ASTM A 283/A 283M-03	51, 66
	ASTM A 588/A 588M-03a			ASTM A 285/A 285M-03	153
	ASTM A 595-98 (2002)	171, 181		ASTM A 302/A 302M-03	118, 120
	A C T N A C C C / A C C C N A C 4				
	ASTM A 633/A 633M-01 ASTM A 662/A 662M-03	72, 75 113, 115		ASTM A 355-89 (2000)	43

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
B (continued)	ASTM A 514/A 514M-00a	82, 86	B43, 43CrMo4	ISO 683-17:1999	439
	ASTM	153	B4N	ASTM A 757/A 757M-00	359
	A 517/A 517M-93 (1999)	70 77	B4Q	ASTM A 757/A 757M-00	359
	ASTM A 588/A 588M-03a	73, 77	B5	BS 3100:1991 AMD.1:1992	359
	ASTM A 595-98 (2002)	171, 181	B5, 100CrMo7	ASTM A 485-03	435
	ASTM A 662/A 662M-03	114, 116		ISO 683-17:1999	435
	ASTM A 668/A 668M-03	268, 271	B50, X47Cr14	ISO 683-17:1999	439
	ASTM A 678/A 678M-00a	64, 71	B51, X65Cr14	ISO 683-17:1999	439
	ASTM A 710/A 710M-02	98	B52, X106CrMo17	ISO 683-17:1999	439
	ASTM A 724/A 724M-99	154	B53, X89CrMoV18-1	ISO 683-17:1999	439
	ASTM A 734/A 734M-87a (2003)	154	B6	BS 3100:1991 AMD.1:1992	359
	ASTM A 737/A 737M-99	105, 111	B6, 100CrMo7-3	ASTM A 485-03	435
	ASTM A 738/A 738M-03a	108, 112		ISO 683-17:1999	435
B - PSL 1	API 5L-2004	246, 247	B60, 80MoCrV42-16	ISO 683-17:1999	439
B - PSL 2	API 5L-2004	250, 253	B61, 13MoCrNi42-16-14	ISO 683-17:1999	439
B, Class 1	ASTM A 1021-02	295, 296	B62, X82WMoCrV6-5-4	ISO 683-17:1999	439
_, _, _,	ASTM A 841/A 841M-03a	114, 116	B63, X75WCrV18-4-1	ISO 683-17:1999	439
B, Class 2	ASTM A 841/A 841M-03a	114, 116	B7	BS 3100:1991 AMD.1:1992	359
B1	BS 3100:1991 AMD.1:1992	330, 331	B7, 100CrMo7-4	ASTM A 485-03	435
B-1	ASTM	328, 329		ISO 683-17:1999	435
	A 128/A 128M-93 (2003)	020, 020	B8, 100CrMnMoSi8-4-6	ASTM A 485-03	435
B1, 100Cr6	ISO 683-17:1999	435		ISO 683-17:1999	435
B2	ASTM	208, 211	BL2	BS 3100:1991 AMD.1:1992	359
	A 556/A 556M-96 (2001)		BT1	BS 3100:1991 AMD.1:1992	359
	BS 3100:1991 AMD.1:1992	359	BT2	BS 3100:1991 AMD.1:1992	359
B-2	ASTM	328, 329	ВТ3	BS 3100:1991 AMD.1:1992	359
DO 4000-M-014-4	A 128/A 128M-93 (2003)	405	BW10	BS 3100:1991 AMD.1:1992	328, 329
B2, 100CrMnSi4-4	ASTM A 485-03	435	BW2	BS 3100:1991 AMD.1:1992	359
Doc 200 0	ISO 683-17:1999	435	BW3	BS 3100:1991 AMD.1:1992	359
B20, 20Cr3	ISO 683-17:1999	439	BW4	BS 3100:1991 AMD.1:1992	359
B21, 20Cr4	ISO 683-17:1999	439	С	ASTM A 106-02a	209, 212
B22, 20MnCr4-2	ISO 683-17:1999	439		ASTM	328, 329
B23, 17MnCr5	ISO 683-17:1999	439		A 128/A 128M-93 (2003)	,
B24, 19MnCr5	ISO 683-17:1999	439		ASTM A 139-00	203, 205
B25, 15CrMo4	ISO 683-17:1999	439		ASTM A 178/A 178M-02	208, 211
B26, 20CrMo4	ISO 683-17:1999	439		ASTM A 204/A 204M-03	117, 119
B27, 20MnCrMo4-2	ISO 683-17:1999	439		ASTM A 210/A 210M-02	209, 212
B28, 20NiCrMo2	ISO 683-17:1999	439		ASTM A 225/A 225M-03	153
B29, 20NiCrMo7	ISO 683-17:1999	439		ASTM A 283/A 283M-03	54, 68
B2N	ASTM A 757/A 757M-00	337, 338		ASTM A 285/A 285M-03	153
B2Q	ASTM A 757/A 757M-00	337, 338		ASTM A 302/A 302M-03	137, 138
B3	BS 3100:1991 AMD.1:1992	359		ASTM A 355-89 (2000)	43
B-3	ASTM	328, 329		ASTM A 500-03	169, 180
B3, 100CrMnSi6-4	A 128/A 128M-93 (2003) ASTM A 485-03	435		ASTM A 514/A 514M-00a	82, 86
D3, 10001WI1310-4	ISO 683-17:1999	435		ASTM	153
B30, 18CrNiMo7-6	ISO 683-17:1999	439		A 517/A 517M-93 (1999)	70 77
•				ASTM A 588/A 588M-03a	73, 77
B31, 18NiCrMo14-6 B32, 16NiCrMo16-5	ISO 683-17:1999	439 430		ASTM A 595-98 (2002)	257
•	ISO 683-17:1999	439		ASTM A 633/A 633M-01	74, 77
B3N	ASTM A 757/A 757M-00	337, 338		ASTM A 662/A 662M-03	114, 116
B3Q	ASTM A 757/A 757M-00	337, 338		ASTM A 668/A 668M-03	268, 271
B4	BS 3100:1991 AMD.1:1992	359		ASTM A 678/A 678M-00a	65, 71
B-4	ASTM A 128/A 128M-93 (2003)	328, 329		ASTM A 724/A 724M-99	154
B4, 100CrMnSi6-6	ASTM A 485-03	435		ASTM A 737/A 737M-99	108, 112
, roommoio o	ISO 683-17:1999	435	0.40	ASTM A 738/A 738M-03a	108, 112
B40, C56E2	ISO 683-17:1999	439	C 10	ISO 683-11:1987	23
B41, 56Mn4	ISO 683-17:1999	439	C 15 E4	ISO 683-11:1987	24
B42, 70Mn4	ISO 683-17:1999	439	C 15 M2	ISO 683-11:1987	24
D-TC, I DIVILIT	100 000-17.1333	-100			

570 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
C 16 E4	ISO 683-11:1987	24	C20D2	EN 10016-4:1995	25
C 16 M2	ISO 683-11:1987	24	C22	EN 10083-2:1991	25
C 25	ISO 683-1:1987	26		EN 10250-2:1999	268, 271
C 25 E 4	ISO 683-1:1987	26	C22E	EN 10083-1:1991	25
C 25 M 2	ISO 683-1:1987	26		EN 10297-1:2003	169, 172,
C 30	ISO 683-1:1987	26	COOR	EN 10000 1:1001	180, 182
C 30 E 4	ISO 683-1:1987	26	C22R	EN 10083-1:1991	25
C 30 M 2	ISO 683-1:1987	26	C23	ASTM A 389/A 389M-03	360
C 35	ISO 2937:1974	173, 182	C23-45A	ISO 4991:1994	326
	ISO 683-1:1987	27	C23-45AH	ISO 4991:1994	326
C 35 E 4	ISO 683-1:1987	27	C23-45B	ISO 4991:1994	326
C 35 M 2	ISO 683-1:1987	27	C23-45BH	ISO 4991:1994	326
C 40	ISO 683-1:1987	28	C23-45BL	ISO 4991:1994	327
C 40 E 4	ISO 683-1:1987	28	C24	ASTM A 389/A 389M-03	335, 336
C 40 M 2	ISO 683-1:1987	28	C25	EN 10083-2:1991	26
C 45	ISO 683-1:1987	29	0	EN 10250-2:1999	268, 271
C 45 E4	ISO 683-1:1987	29	C25E	EN 10083-1:1991	26
C 45 M2	ISO 683-1:1987	29		EN 10250-2:1999	268, 271
C 50	ISO 683-1:1987	30	C25R	EN 10083-1:1991	26
C 50 E4	ISO 683-1:1987	30	C26-52	ISO 4991:1994	326
C 50 M2	ISO 683-1:1987	30	C26-52H	ISO 4991:1994	326
C 55	ISO 683-1:1987	31	C26-52L	ISO 4991:1994	327
C 55 E4	ISO 683-1:1987	31	C26D	EN 10016-2:1995	26
C 55 M2	ISO 683-1:1987	31	C26D2	EN 10016-4:1995	26
C 60	ISO 683-1:1987	31	C28H	ISO 4991:1994	335, 336
C 60 E 4	ISO 683-1:1987	31	C30	EN 10083-2:1991	26
C 60 M 2	ISO 683-1:1987	31		EN 10250-2:1999	269, 271
C, Class 1	ASTM A 736/A 736M-03	154	C30E	EN 10083-1:1991	26
o, olaco 1	ASTM A 841/A 841M-03a	114, 116	C30R	EN 10083-1:1991	26
C, Class 2	ASTM A 841/A 841M-03a	114, 116	C31L	ISO 4991:1994	359
C, Class 3	ASTM A 736/A 736M-03	154	C32D	EN 10016-2:1995	27
C100S	EN 10132-4:2000	426	C32D2	EN 10016-4:1995	26
C105U	ISO 4957:1999	430	C32H	ISO 4991:1994	335, 336
C10D	EN 10016-2:1995	23	C33H	ISO 4991:1994	359
C10D2	EN 10016-4:1995	23	C34AH	ISO 4991:1994	335, 336
C10E	EN 10084:1998	23	C34BH	ISO 4991:1994	335, 336
0.02	EN 10297-1:2003	257	C34BL	ISO 4991:1994	359
C10R	EN 10084:1998	23	C35	EN 10083-2:1991	27
C12	ASTM A 217/A 217M-02	335, 336		EN 10250-2:1999	269, 271
C120U	ISO 4957:1999	430	C35BH	ISO 4991:1994	335, 336
C125S	EN 10132-4:2000	437	C35E	EN 10083-1:1991	27
C12A	ASTM A 217/A 217M-02	360		EN 10250-2:1999	269, 271
C12D	EN 10016-2:1995	23		EN 10297-1:2003	173, 175,
C12D2	EN 10016-4:1995	23		EN 40005 4,0000	183, 184
C15D	EN 10016-2:1995	24		EN 10305-1:2002	170, 171, 173, 174,
C15D2	EN 10016-4:1995	24			180, 181,
C15E	EN 10084:1998	24			182, 183
0.02	EN 10297-1:2003	257	C35R	EN 10083-1:1991	27
C15R	EN 10084:1998	24	C36D2	EN 10016-4:1995	27
	EN 10297-1:2003	257	C37H	ISO 4991:1994	335, 336
C16E	EN 10084:1998	24	C38D	EN 10016-2:1995	27
C16R	EN 10084:1998	24	C38D2	EN 10016-4:1995	27
C18D	EN 10004:1995	24	C38H	ISO 4991:1994	335, 336
C18D2	EN 10016-4:1995	24	C39CH	ISO 4991:1994	347, 348
C1Q	ASTM A 757/A 757M-00	359	C39CNiH	ISO 4991:1994	347, 348
C2	ASTM	209, 212	C39NiH	ISO 4991:1994	347, 348
- -					
	A 556/A 556M-96 (2001)		C39NiL	ISO 4991:1994	347, 348

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
C40	EN 10083-2:1991	28	C60E	EN 10083-1:1991	31
	EN 10250-2:1999	269, 271		EN 10250-2:1999	311
C40D2	EN 10016-4:1995	28		EN 10297-1:2003	257
C40E	EN 10083-1:1991	28	C60H	ISO 4991:1994	359
C40H	ISO 4991:1994	347, 348	C60Nb	ISO 4991:1994	349, 350
C40R	EN 10083-1:1991	28	C60R	EN 10083-1:1991	31
C42D	EN 10016-2:1995	28	C60S	EN 10132-4:2000	425
C42D2	EN 10016-4:1995	28	C61	ISO 4991:1994	349, 350
C43C1L	ISO 4991:1994	359	C61LC	ISO 4991:1994	349, 350
C43E2aL	ISO 4991:1994	337, 338	C62D	EN 10016-2:1995	32
C43E2bL	ISO 4991:1994	337, 338	C62D2	EN 10016-4:1995	32
C43L	ISO 4991:1994	337, 338	C66D	EN 10016-2:1995	32
C45	EN 10083-2:1991	29	C66D2	EN 10016-4:1995	32
	EN 10250-2:1999	270, 271	C67S	EN 10132-4:2000	425
C45E	EN 10083-1:1991	29	C68D	EN 10016-2:1995	32
	EN 10250-2:1999	270, 271	C68D2	EN 10016-4:1995	32
	EN 10297-1:2003	174, 175,	C70D	EN 10016-2:1995	32
	- 11	184	C70D2	EN 10016-4:1995	32
	EN 10305-1:2002	172, 173,	C70U	ISO 4957:1999	430
		175, 182, 184	C72D	EN 10016-2:1995	32
C45R	EN 10083-1:1991	29	C72D2	EN 10016-4:1995	32
C45U	ISO 4957:1999	438	C75S	EN 10132-4:2000	425
C46	ISO 4991:1994	349, 350	C76D	EN 10016-2:1995	32
C46D2	EN 10016-4:1995	29	C76D2	EN 10016-4:1995	32
C47	ISO 4991:1994	349, 350	C78D	EN 10016-2:1995	32
C47H	ISO 4991:1994	359	C78D2	EN 10016-4:1995	32
C47L	ISO 4991:1994	349, 350	C7D	EN 10016-2:1995	23
C48D	EN 10016-2:1995	29	C80D	EN 10016-2:1995	32
C48D2	EN 10016-4:1995	29	C80D2	EN 10016-4:1995	32
C4D	EN 10016-2:1995	23	C80U	ISO 4957:1999	430
C5	ASTM A 217/A 217M-02	335, 336	C82D	EN 10016-2:1995	32
C50	EN 10083-2:1991	30	C82D2	EN 10016-4:1995	32
000	EN 10250-2:1999	270, 271	C85S	EN 10132-4:2000	426
	ISO 4991:1994	349, 350	C86D	EN 10016-2:1995	33
C50D	EN 10016-2:1995	30	C86D2	EN 10016-4:1995	33
C50D2	EN 10016-4:1995	30	C88D	EN 10016-2:1995	33
C50E	EN 10083-1:1991	30	C88D2	EN 10016-4:1995	33
C50R	EN 10083-1:1991	30	C8D2	EN 10016-4:1995	23
C52D	EN 10016-2:1995	30	C90S	EN 10132-4:2000	426
C52D2	EN 10016-4:1995	30	C90U	ISO 4957:1999	430
C55	EN 10083-2:1991	31	C92D	EN 10016-2:1995	33
	EN 10250-2:1999	270, 271	C92D2	EN 10016-4:1995	33
C55E	EN 10083-1:1991	31	C98D2	EN 10016-4:1995	33
	EN 10250-2:1999	270, 271	C9D	EN 10016-2:1995	23
C55R	EN 10083-1:1991	31	CA15	ASTM A 217/A 217M-02	347, 348
C55S	EN 10132-4:2000	425		ASTM	347
C56D	EN 10016-2:1995	31		A 487/A 487M-93 (2003)	
C56D2	EN 10016-4:1995	31		ASTM A 743/A 743M-03	339, 340
C57	ISO 4991:1994	349, 350	CA15, Class A	ASTM	348
C58D	EN 10016-2:1995	31	CA15, Class B	A 487/A 487M-93 (2003) ASTM	348
C58D2	EN 10016-4:1995	31	57110, Olass D	A 487/A 487M-93 (2003)	0-70
C5D2	EN 10016-4:1995	23	CA15, Class C	ASTM	348
C60	EN 10010-4:1993 EN 10083-2:1991	31	•	A 487/A 487M-93 (2003)	
J00	EN 10083-2.1991 EN 10250-2:1999	311	CA15, Class D	ASTM	348
			044514	A 487/A 487M-93 (2003)	000
COD	ISO 4991:1994	349, 350	CA15M	ASTM A 497/A 497M 02 (2002)	360
C60D	EN 10016-2:1995	31		A 487/A 487M-93 (2003)	
C60D2	EN 10016-4:1995	31		ASTM A 743/A 743M-03	339, 340

572 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
CA40	ASTM A 743/A 743M-03	339, 340	CH-20	ASTM A 351/A 351M-03	361
CA-40F	ASTM A 743/A 743M-03	361	CH8	ASTM A 351/A 351M-03	361
CA6N	ASTM A 743/A 743M-03	361	CK20	ASTM A 743/A 743M-03	361
CA6NM	ASTM A 352/A 352M-03	347, 348	CK-20	ASTM A 351/A 351M-03	361
	ASTM	347	CK-35MN	ASTM A 743/A 743M-03	361
	A 487/A 487M-93 (2003)		CK3MCuN	ASTM A 743/A 743M-03	343, 346
	ASTM A 743/A 743M-03	339, 340		ASTM A 744/A 744M-00	343, 346
CA6NM, Class A	ASTM	348	CK3MnCuN	ASTM A 351/A 351M-03	361
0400114 01 D	A 487/A 487M-93 (2003)	0.10	Class 1	ASTM	154
CA6NM, Class B	ASTM A 487/A 487M-93 (2003)	348		A 782/A 782M-90 (2001)	
CB-30	ASTM A 743/A 743M-03	361	Class 2	ASTM	154
CB-6	ASTM A 743/A 743M-03	361	01 0	A 782/A 782M-90 (2001)	454
CC-50	ASTM A 743/A 743M-03	361	Class 3	ASTM A 782/A 782M 00 (2001)	154
CD3MWCuN	ASTM A 351/A 351M-03	361	CN3M	A 782/A 782M-90 (2001) ASTM A 743/A 743M-03	342, 346
CD-4MCu	ASTM A 351/A 351M-03	349, 350	CN3MN	ASTM A 351/A 351M-03	361
CE20N	ASTM A 351/A 351M-03	361	CINGIVIIN	ASTM A 743/A 743M-03	343, 346
CE-30	ASTM A 743/A 743M-03	361		ASTM A 743/A 743M-00	343, 346
CE8MN	ASTM A 743/A 743M-03 ASTM A 351/A 351M-03	361	CN7M	ASTM A 744/A 744M-00 ASTM A 743/A 743M-03	343, 346
CF10		361	CINTIVI	ASTM A 743/A 743M-03 ASTM A 744/A 744M-00	•
CF10M	ASTM A 351/A 351M-03		CNI 7M		342, 346
-	ASTM A 351/A 351M-03	361	CN-7M	ASTM A 351/A 351M-03	349, 350
CF10MC	ASTM A 351/A 351M-03	361	CN7MS	ASTM A 744/A 744M-98	361
CF10SMnN	ASTM A 351/A 351M-03	361	CN-7MS	ASTM A 743/A 743M-03	361
05405	ASTM A 743/A 743M-03	361	CS Type A	ASTM A 1011/A 1011M-03	97
CF16F	ASTM A 743/A 743M-03	361	CS Type B	ASTM A 1011/A 1011M-03	97
CF16Fa	ASTM A 743/A 743M-03	361	CS Type C	ASTM A 1011/A 1011M-03	97
CF20	ASTM A 743/A 743M-03	341, 344	CT15C	ASTM A 351/A 351M-03	361
CF3	ASTM A 743/A 743M-03	341, 344	D	ASTM	328, 329
	ASTM A 744/A 744M-00	341, 344		A 128/A 128M-93 (2003) ASTM A 139-00	203, 205
CF-3	ASTM A 351/A 351M-03	349, 350			
CF-3A	ASTM A 351/A 351M-03	349, 350		ASTM A 178/A 178M-02 ASTM	209, 212 132, 133
CF3M	ASTM A 743/A 743M-03	342, 345		A 203/A 203M-97 (2003)	132, 133
	ASTM A 744/A 744M-00	342, 345		ASTM A 225/A 225M-03	153
CF-3M	ASTM A 351/A 351M-03	349, 350		ASTM A 283/A 283M-03	56, 69
CF-3MA	ASTM A 351/A 351M-03	349, 350		ASTM A 302/A 302M-03	139, 140
CF3MN	ASTM A 743/A 743M-03	342, 345		ASTM A 355-89 (2000)	43
CF3-MN	ASTM A 351/A 351M-03	361		ASTM A 500-03	168, 179
CF8	ASTM A 743/A 743M-03	341, 344		ASTM A 633/A 633M-01	74, 77
	ASTM A 744/A 744M-00	341, 344		ASTM A 668/A 668M-03	269, 271
CF-8	ASTM A 351/A 351M-03	349, 350		ASTM A 678/A 678M-00a	97
CF-8A	ASTM A 351/A 351M-03	349, 350		ASTM A 738/A 738M-03a	154
CF8C	ASTM A 743/A 743M-03	341, 344	D, Class 3	ASTM A 841/A 841M-03a	154
	ASTM A 744/A 744M-00	341, 344	D1N1	ASTM A 757/A 757M-00	359
CF-8C	ASTM A 351/A 351M-03	349, 350	D1N2	ASTM A 757/A 757M-00	359
CF8M	ASTM A 743/A 743M-03	341, 345	D1N3	ASTM A 757/A 757M-00	359
	ASTM A 744/A 744M-00	341, 345	D1Q1	ASTM A 757/A 757M-00	359
CF-8M	ASTM A 351/A 351M-03	349, 350	D1Q2	ASTM A 757/A 757M-00	359
CG-12	ASTM A 743/A 743M-03	361	D1Q2	ASTM A 757/A 757M-00 ASTM A 757/A 757M-00	359
CG3M	ASTM A 743/A 743M-03	342, 346	D1Q3		
	ASTM A 744/A 744M-00	342, 346	DZ	ASTM A 681-94 (1999)	433
CG-3M	ASTM A 351/A 351M-03	361	Do	SAE J438-1970	433
CG6MMN	ASTM A 351/A 351M-03	361	D3	ASTM A 681-94 (1999)	433
	ASTM A 743/A 743M-03	361	D4	SAE J438-1970	433
CG8M	ASTM A 743/A 743M-03	342, 345	D4	ASTM A 681-94 (1999)	438
	ASTM A 744/A 744M-00	342, 345	D5	ASTM A 681-94 (1999)	438
CG-8M	ASTM A 351/A 351M-03	361		SAE J438-1970	438
CH10	ASTM A 351/A 351M-03	361	D7	ASTM A 681-94 (1999)	438
CH-10	ASTM A 743/A 743M-03	361		SAE J438-1970	438
CH20	ASTM A 743/A 743M-03	342, 346	DS Type A	ASTM A 1011/A 1011M-03	97
JU	. 13 1 11 / 1 / 10// 1 7 500 00	5, 5-0			

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
DS Type B	ASTM A 1011/A 1011M-03	97	E220	EN 10296-1:2003	166, 177
E	ASTM A 139-00	203, 205		EN 10305-3:2002	166, 177
	ASTM	132, 133	E235	EN 10296-1:2003	166, 168,
	A 203/A 203M-97 (2003)				177, 178
	ASTM A 514/A 514M-00a	82, 86		EN 10297-1:2003	167, 178
	ASTM	153		EN 10305-1:2002	166, 169,
	A 517/A 517M-93 (1999)	74 70			171, 177,
	ASTM A 633/A 633M-01	74, 78		EN 10205 0:2000	179, 181
	ASTM A 668/A 668M-03	270, 271		EN 10305-2:2002	166, 170, 172, 177,
	ASTM A 738/A 738M-03a	154			180, 182
E 185	ISO 630:1995	50, 66		EN 10305-3:2002	166, 167,
E 235 A	ISO 630:1995	51, 66			168, 177,
E 235 B	ISO 630:1995	51, 66			178
E 235 B NF	ISO 630:1995	51, 66	E255	EN 10305-1:2002	168, 170,
E 235 C	ISO 630:1995	51, 66			173, 174,
E 235 D	ISO 630:1995	51, 66			178, 180, 182, 183
E 275 A	ISO 630:1995	56, 69	E260	EN 10296-1:2003	167, 177
E 275 B	ISO 630:1995	56, 69		EN 10305-3:2002	167, 177
E 275 C	ISO 630:1995	56, 69	E275	EN 10296-1:2003	168, 170,
E 275 D	ISO 630:1995	56, 69	•		178, 179
E 295	EN 10025:1993	60, 70		EN 10297-1:2003	168, 179
E 335	EN 10025:1993	65, 71		EN 10305-2:2002	168, 169,
E 355 C	ISO 630:1995	60, 70			172, 174,
E 355 D	ISO 630:1995	61, 70			178, 179,
E 355 DD	ISO 4950-2:1995	79, 84		EN 10005 0.0000	182, 183
E 355 E	ISO 4950-2:1995	79, 84		EN 10305-3:2002	168, 169, 170, 178,
E 360	EN 10025:1993	65, 71			170, 170,
E 460 CC	ISO 4950-2:1995	97	E275K2	EN 10296-1:2003	167, 178
E 460 DD	ISO 4950-2:1995	97		EN 10297-1:2003	169, 179
00	ISO 4950-3:1995	80, 84	E275M	EN 10296-1:2003	257
E 460 E	ISO 4950-2:1995	97	E2N1	ASTM A 757/A 757M-00	337, 338
2 100 2	ISO 4950-3:1995	80, 84	E2N2	ASTM A 757/A 757M-00	337, 338
E 550 DD	ISO 4950-3:1995	97	E2N3	ASTM A 757/A 757M-00	337, 338
E 550 E	ISO 4950-3:1995	97	E2Q1	ASTM A 757/A 757M-00	337, 338
E 690 DD	ISO 4950-3:1995	97	E2Q2	ASTM A 757/A 757M-00	337, 338
E 690 E	ISO 4950-3:1995	97	E2Q3	ASTM A 757/A 757M-00	337, 338
E, Class 4	ASTM A 841/A 841M-03a	154	E315	EN 10297-1:2003	170, 180
E, Class 5	ASTM A 841/A 841M-03a	154	E320	EN 10296-1:2003	169, 179
E-1	ASTM A 041/A 041M-03a	328, 329		EN 10305-3:2002	169, 179
L-1	A 128/A 128M-93 (2003)	320, 329	E3310	ASTM A 519-03	258
E155	EN 10296-1:2003	165, 176	E355	EN 10296-1:2003	171, 172,
	EN 10305-2:2002	165, 167,			173, 181,
		168, 176,			183
		177, 179		EN 10297-1:2003	171, 181
	EN 10305-3:2002	165, 176		EN 10305-1:2002	170, 172,
E190	EN 10305-3:2002	165, 176			174, 175,
	ISO 3306:1985	165, 176			180, 183,
E195	EN 10296-1:2003	166		EN 10305-2:2002	184 170, 172,
	EN 10305-2:2002	165, 166,		214 10000 2.2002	174, 175,
		167, 169,			180, 183,
		176, 178,			184
	EN 1000E 0:0000	180		EN 10305-3:2002	170, 172,
	EN 10305-3:2002	165, 166,			173, 180,
E1Q	ASTM A 757/A 757M-00	176 359	E355K2	EN 10296-1:2003	182 257
E-2	ASTM	328, 329	LUUUINA	EN 10296-1:2003 EN 10297-1:2003	257 258
	A 128/A 128M-93 (2003)	3_0, 3_0	ESEM		256 257
E215	EN 10305-1:2002	165, 168,	E355M	EN 10296-1:2003	
		169, 176,	E370	EN 10296-1:2003 EN 10305-3:2002	171, 181 171, 180
		178, 180		LIN 10303-3.2002	171, 180

574 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
E3N	ASTM A 757/A 757M-00	359	F 304N	ASTM A 182/A 182M-02	298, 302
	ASTM A 757/A 757M-00	347, 348		ASTM A 965/A 965M-02	298, 302
E410	EN 10305-1:2002	173, 174,	F 309H	ASTM A 182/A 182M-02	313
		175, 182,	F 310	ASTM A 182/A 182M-02	299, 303
		183, 184,		ASTM A 965/A 965M-02	299, 303
E420	EN 10305-3:2002	172, 182	F 310MoLN	ASTM A 182/A 182M-02	313
E420J2	EN 10297-1:2003	174, 184	F 316	ASTM A 182/A 182M-02	299, 303
E420M	EN 10296-1:2003	257		ASTM A 965/A 965M-02	299, 303
E4337	ASTM A 519-03	258	F 316H	ASTM A 182/A 182M-02	300, 305
E4340	ASTM A 29/A 29M-03	39		ASTM A 965/A 965M-02	300, 305
	ASTM A 322-91 (2001)	39	F 316L	ASTM A 182/A 182M-02	299, 304
	ASTM A 519-03	258	. 0.02	ASTM A 965/A 965M-02	299, 304
	SAE J404 JUN00	39	F 316LN	ASTM A 182/A 182M-02	300, 305
E460K2	EN 10296-1:2003	257	1 010214	ASTM A 965/A 965M-02	300, 305
	EN 10297-1:2003	258	F 316N	ASTM A 182/A 182M-02	299, 304
E460M	EN 10296-1:2003	257	1 31011	ASTM A 162/A 162M-02 ASTM A 965/A 965M-02	299, 304
E470	EN 10297-1:2003	175, 184	F 317		
E50100	ASTM A 519-03	258	F 317L	ASTM A 182/A 182M-02	300, 305
E51100	ASTM A 519-03	258		ASTM A 182/A 182M-02	300, 305
E52100	ASTM A 519-03	258	F 321	ASTM A 182/A 182M-02	300, 306
	SAE J404 JUN00	44	E 00411	ASTM A 965/A 965M-02	300, 306
E590K2	EN 10297-1:2003	175, 184	F 321H	ASTM A 182/A 182M-02	300, 306
E7140	ASTM A 519-03	258	E 0.47	ASTM A 965/A 965M-02	300, 306
E730K2	EN 10297-1:2003	258	F 347	ASTM A 182/A 182M-02	301, 306
E9310	ASTM A 29/A 29M-03	39		ASTM A 965/A 965M-02	301, 306
E9310	ASTM A 519-03	258	F 347H	ASTM A 182/A 182M-02	301, 306
_			F 348	ASTM A 182/A 182M-02	313
F	ASTM A 128/A 128M-93 (2003)	328, 329	F 348H	ASTM A 182/A 182M-02	313
	ASTM	132, 133	F 3V	ASTM A 182/A 182M-02	285
	A 203/A 203M-97 (2003)	102, 100	F 3VCb	ASTM A 182/A 182M-02	312
	ASTM A 514/A 514M-00a	82, 86	F 429	ASTM A 182/A 182M-02	313
	ASTM	153	F 44	ASTM A 182/A 182M-02	313
	A 517/A 517M-93 (1999)		F 45	ASTM A 182/A 182M-02	313
	ASTM A 668/A 668M-03	270, 271	F 46	ASTM A 182/A 182M-02	313
F 1	ASTM A 182/A 182M-02	279	F 47	ASTM A 182/A 182M-02	313
F 10	ASTM A 182/A 182M-02	313	F 48	ASTM A 182/A 182M-02	313
F 11, Class 1	ASTM A 182/A 182M-02	312	F 49	ASTM A 182/A 182M-02	313
F 11, Class 2	ASTM A 182/A 182M-02	282	F 5	ASTM A 182/A 182M-02	286
F 11, Class 3	ASTM A 182/A 182M-02	282	F 50	ASTM A 182/A 182M-02	309, 310
F 12, Class 1	ASTM A 182/A 182M-02	312	F 51	ASTM A 182/A 182M-02	309, 310
F 12, Class 2	ASTM A 182/A 182M-02	281	F 52	ASTM A 182/A 182M-02	313
F 122	ASTM A 182/A 182M-02	313	F 53	ASTM A 182/A 182M-02	309, 310
F 2	ASTM A 182/A 182M-02	280	F 54	ASTM A 182/A 182M-02	313
F 20	ASTM A 182/A 182M-02	313	F 55	ASTM A 182/A 182M-02	309, 310
F 21	ASTM A 182/A 182M-02	285	F 56	ASTM A 182/A 182M-02	313
F 22, Class 1	ASTM A 182/A 182M-02	283, 284	F 57	ASTM A 182/A 182M-02	313
F 22, Class 3	ASTM A 182/A 182M-02	283, 284	F 58	ASTM A 182/A 182M-02	313
F 22V	ASTM A 182/A 182M-02	283, 284	F 59	ASTM A 182/A 182M-02	309, 310
F 23	ASTM A 182/A 182M-02	312	F 5a	ASTM A 182/A 182M-02	286
F 24	ASTM A 182/A 182M-02	312	F 60	ASTM A 182/A 182M-02	309, 310
F 304	ASTM A 182/A 182M-02	298, 302	F 61	ASTM A 182/A 182M-02	313
	ASTM A 965/A 965M-02	298, 302	F 62	ASTM A 182/A 182M-02	313
F 304H	ASTM A 182/A 182M-02	298, 302	F 6a, Class 1	ASTM A 182/A 182M-02	295, 296
	ASTM A 965/A 965M-02	298, 302	F 6a, Class 2	ASTM A 182/A 182M-02	295, 296
F 304L	ASTM A 182/A 182M-02	298, 302	F 6a, Class 3	ASTM A 182/A 182M-02	295, 296
	ASTM A 965/A 965M-02	298, 302	F 6a, Class 4	ASTM A 182/A 182M-02	295, 296
F 304LN	ASTM A 182/A 182M-02	298, 303	F 6b		
. 501211	ASTM A 965/A 965M-02	298, 303	F 6NM	ASTM A 182/A 182M-02	295, 296
	, to , t 000// t 000/vi 02	200, 000	F 9	ASTM A 182/A 182M-02	295, 296
			1 9	ASTM A 182/A 182M-02	287

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
F 91	ASTM A 182/A 182M-02	312	G30NiCrMo14	AFNOR NF A 32-054:1994	359
F 911	ASTM A 182/A 182M-02	312	G30NiCrMo8	AFNOR NF A 32-054:1994	330, 334
F 92	ASTM A 182/A 182M-02	312	G35CrMo4	AFNOR NF A 32-054:1994	330, 332
F XM-11	ASTM A 182/A 182M-02	313	G35NiCrMo6	AFNOR NF A 32-054:1994	359
F XM-19	ASTM A 182/A 182M-02	313	G42CrMo4	AFNOR NF A 32-054:1994	330, 333
F XM-27Cb	ASTM A 182/A 182M-02	313	G9Ni10	EN 10213-3:1995	337, 338
F, Class 6	ASTM A 841/A 841M-03a	154	G9Ni14	EN 10213-3:1995	337, 338
F, Class 7	ASTM A 841/A 841M-03a	154	G-CoCr28	EN 10295:2002	354, 358
F, Class 8	ASTM A 841/A 841M-03a	154	GE230	AFNOR NF A 32-054:1994	319, 323
F1	ASTM A 336/A 336M-03a	279	GE280	AFNOR NF A 32-054:1994	320, 323
	ASTM A 681-94 (1999)	438	GE320	AFNOR NF A 32-054:1994	321, 324
F11, Class 1	ASTM A 336/A 336M-03a	312	GE370	AFNOR NF A 32-054:1994	322, 325
F11, Class 2	ASTM A 336/A 336M-03a	282	G-NiCr15	EN 10295:2002	354, 358
F11, Class 3	ASTM A 336/A 336M-03a	282	G-NiCr28W	EN 10295:2002	354, 358
F12	ASTM A 336/A 336M-03a	281	G-NiCr50Nb	EN 10295:2002	353, 358
F2	ASTM A 681-94 (1999)	434	GP240GH	EN 10213-2:1995	326
F21, Class 1	ASTM A 336/A 336M-03a	285	GP240GR	EN 10213-2:1995	326
F21, Class 3	ASTM A 336/A 336M-03a	285	GP280GH	EN 10213-2:1995	326
F22, Class 1	ASTM A 336/A 336M-03a	283, 284	Grade 2	ASTM A 485-03	439
F22, Class 3	ASTM A 336/A 336M-03a	283, 284	Grade 3	ASTM A 485-03	439
F22V	ASTM A 336/A 336M-03a	283, 284	Grade 4	ASTM A 485-03	439
F310H	ASTM A 182/A 182M-02	299, 303	GS-25 CrMo 4	DIN 17205:1992	330, 331
	ASTM A 965/A 965M-02	299, 303	GS-25 CrMo 4, Class I	DIN 17205:1992	330, 331
F3V	ASTM A 336/A 336M-03a	285	GS-25 CrMo 4, Class II	DIN 17205:1992	330, 331
F3VCb	ASTM A 336/A 336M-03a	312	GS-25 CrNiMo 4	DIN 17205:1992	359
F5	ASTM A 336/A 336M-03a	286	GS-30 CrMoV 6 4	DIN 17205:1992	359
F5A	ASTM A 336/A 336M-03a	286	GS-30 CrNiMo 8 5	DIN 17205:1992	359
F6	ASTM A 336/A 336M-03a	312	GS-30 Mn 5	DIN 17205:1992	320, 324
F9	ASTM A 336/A 336M-03a	287	GS-33 CrNiMo 7 4 4	DIN 17205:1992	330, 334
F91	ASTM A 336/A 336M-03a	312	GS-33 CrNiMo 7 4 4,	DIN 17205:1992	330, 334
F911	ASTM A 336/A 336M-03a	312	Class I	DIN 17203.1332	000, 004
Fe 235W, Quality B	ISO 4952:2003	88, 94	GS-33 CrNiMo 7 4 4,	DIN 17205:1992	330, 334
Fe 235W, Quality C	ISO 4952:2003	88, 94	Class II		
Fe 235W, Quality D	ISO 4952:2003	88, 94	GS-34 CrMo 4	DIN 17205:1992	330, 332
Fe 355W, Quality 1A	ISO 4952:2003	90, 95	GS-34 CrMo 4, Class I	DIN 17205:1992	330, 332
Fe 355W, Quality 1D	ISO 4952:2003	90, 95	GS-34 CrMo 4, Class II	DIN 17205:1992	330, 332
Fe 355W, Quality 2B	ISO 4952:2003	90, 95	GS-34 CrNiMo 6	DIN 17205:1992	359
Fe 355W, Quality 2C	ISO 4952:2003	90, 95	GS-35 CrMoV 10 4	DIN 17205:1992	359
Fe 355W, Quality 2D	ISO 4952:2003	90, 95	GS-38	DIN 1681:1985	319, 323
FR	ASTM A 182/A 182M-02	312	GS-42 CrMo 4	DIN 17205:1992	330, 333
G (GH)	ASTM A 668/A 668M-03	311	GS-42 CrMo 4, Class I	DIN 17205:1992	330, 333
G10MnMoV6	AFNOR NF A 32-054:1994	359	GS-42 CrMo 4, Class II	DIN 17205:1992	330, 333
G12MoCrV5-2	EN 10213-2:1995	359	GS-45	DIN 1681:1985	319, 323
G15CrMoV6	AFNOR NF A 32-054:1994	359	GS-52	DIN 1681:1985	320, 324
G16Mn5	AFNOR NF A 32-054:1994	319, 323	GS-60	DIN 1681:1985	321, 324
G17CrMo5-5	EN 10213-2:1995	335, 336	GX 12 Cr 12	ISO 11972:1998	339, 340
G17CrMo9-10	EN 10213-2:1995	335, 336	GX 2 CrNi 18 10	ISO 11972:1998	341, 344
G17CrMoV5-10	EN 10213-2:1995	335, 336	GX 2 CrNiCuMoN 26 5 3	3 ISO 11972:1998	343, 346
G17Mn5	EN 10213-3:1995	327	GX 2 CrNiMo 19 11 2	ISO 11972:1998	342, 345
G17NiiCrMo13-6	EN 10213-3:1995	337, 338	GX 2 CrNiMo 19 11 3	ISO 11972:1998	342, 346
G18Mo5	EN 10213-3:1995	337, 338	GX 2 CrNiMoN 19 11 2	ISO 11972:1998	342, 345
G20Mn5	EN 10213-3:1995	327	GX 2 CrNiMoN 19 11 3	ISO 11972:1998	342, 345
			GX 2 CrNiMoN 26 5 3	ISO 11972:1998	343, 346
G20Mn6 G20Mo5	AFNOR NF A 32-054:1994 EN 10213-2:1995	320, 324 335, 336	GX 2 CrNiN 18 10	ISO 11972:1998	361
	AFNOR NF A 32-054:1994	359, 356	GX 4 CrNiMo 16 5 1	ISO 11972:1998	339, 340
G20NiCrMo12 G25CrMo4			GX 4CrNi 12 4	ISO 11972:1998	339, 340
G30Mn6	AFNOR NF A 32-054:1994 AFNOR NF A 32-054:1994	330, 331 321, 322,	GX 5 CrNi 19 9	ISO 11972:1998	341, 344
GOOIVIIIO	ALINOTENI A 32-034.1994	324, 325	GX 5 CrNiMo 19 11 2	ISO 11972:1998	341, 345
		5_ 1, 5_5			

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
GX 5 CrNiMo 19 11 3	ISO 11972:1998	341, 345	GX40CrNiSi27-4	EN 10295:2002	351, 355
GX 6 CrNiMoNb 19 11 2	ISO 11972:1998	342, 345		ISO 11973:1999	351, 355
GX 6 CrNiNb 19 10	ISO 11972:1998	341, 344	GX40CrNiSiNb24-24	EN 10295:2002	353, 357
GX 8 CrNiMo 12 1	ISO 11972:1998	339, 340		ISO 11973:1999	353, 357
GX100Mn13	ISO 13521:1999	328, 329	GX40CrSi13	EN 10295:2002	351, 355
GX10NiCrNb31-20	ISO 11973:1999	362		ISO 11973:1999	351, 355
GX10NiCrNb50-50	ISO 11973:1999	353, 358	GX40CrSi17	EN 10295:2002	351, 355
GX10NiCrSiNb32-20	EN 10295:2002	362		ISO 11973:1999	351, 355
GX110MnMo13-1	ISO 13521:1999	328, 329	GX40CrSi24	EN 10295:2002	351, 355
GX120Mn13	ISO 13521:1999	328, 329		ISO 11973:1999	351, 355
GX120Mn17	ISO 13521:1999	360	GX40CrSi28	EN 10295:2002	351, 355
GX120MnCr13-2	ISO 13521:1999	328, 329		ISO 11973:1999	351, 355
GX120MnCr7-2	ISO 13521:1999	328, 329	GX40NiCrCo20-20-20	ISO 11973:1999	354, 358
GX120MnMo7-1	ISO 13521:1999	328, 329	GX40NiCrNb45-35	EN 10295:2002	362
GX120MnNi13-3	ISO 13521:1999	328, 329	GX40NiCrSi35-17	EN 10295:2002	353, 357
GX12Cr12	EN 10283:1998	339, 340		ISO 11973:1999	353, 357
GX130CrSi29	EN 10295:2002	351, 355	GX40NiCrSi35-26	EN 10295:2002	353, 357
	ISO 11973:1999	351, 355		ISO 11973:1999	353, 357
GX15CrMo5	EN 10213-2:1995	335, 336	GX40NiCrSi38-19	EN 10295:2002	353, 358
GX160CrSi18	EN 10295:2002	362		ISO 11973:1999	353, 358
GX23CrMoV12-1	EN 10213-2:1995	347, 348	GX40NiCrSiNb35-18	EN 10295:2002	353, 358
GX25CrNiSi18-9	EN 10295:2002	351, 356	GX40NiCrSiNb35-26	EN 10295:2002	353, 357
	ISO 11973:1999	351, 356		ISO 11973:1999	353, 357
GX25CrNiSi20-14	EN 10295:2002	352, 356	GX40NiCrSiNb38-19	EN 10295:2002	353, 358
	ISO 11973:1999	352, 356		ISO 11973:1999	353, 358
GX2CrNi19-11	EN 10213-4:1995	349, 350	GX45NiCrCoW35-25-15-5	ISO 11973:1999	362
	EN 10283:1998	341, 344	GX45NiCrWSi48-28-5	ISO 11973:1999	354, 358
GX2CrNiMo19-11-2	EN 10213-4:1995	349, 350	GX4CrNi13-4	AFNOR NF A 32-054:1994	339, 340
	EN 10283:1998	342, 345		EN 10213-2:1995	347, 348
GX2CrNiMoCuN20-18-6	EN 10283:1998	343, 346		EN 10283:1998	339, 340
GX2CrNiMoCuN25-6-3-3	EN 10213-4:1995	349, 350	GX4CrNi16-4	AFNOR NF A 32-054:1994	339, 340
	EN 10283:1998	361	GX4CrNiMo16-5-1	EN 10213-2:1995	359
GX2CrNiMoCuN29-25-5	EN 10283:1998	361		EN 10283:1998	339, 340
GX2CrNiMoN17-13-4	EN 10283:1998	342, 345	GX4CrNiMo16-5-2	EN 10283:1998	361
GX2CrNiMoN22-5-3	EN 10213-4:1995	361	GX4NiCrCuMo30-20-4	EN 10283:1998	342, 346
	EN 10283:1998	361	GX50NiCr52-19	ISO 11973:1999	362
GX2CrNiMoN25-6-3	EN 10283:1998	361	GX50NiCr65-15	ISO 11973:1999	354, 358
GX2CrNiMoN25-7-3	EN 10283:1998	361	GX50NiCrCo20-20-20	EN 10295:2002	354, 358
GX2CrNiMoN26-7-4	EN 10213-4:1995	361	GX50NiCrCoW35-25-15-5	EN 10295:2002	362
	EN 10283:1998	361	GX5CrNi19-10	EN 10213-4:1995	349, 350
GX2NiCrMo28-20-2	EN 10213-4:1995	349, 350		EN 10283:1998	341, 344
	EN 10283:1998	342, 346	GX5CrNiCu16-4	EN 10283:1998	361
GX2NiCrMoCu25-20-5	EN 10283:1998	361	GX5CrNiMo19-11-2	EN 10213-4:1995	349, 350
GX2NiCrMoCuN25-20-6	EN 10283:1998	343, 346		EN 10283:1998	341, 345
GX2NiCrMoN25-20-5	EN 10283:1998	342, 346	GX5CrNiMo19-11-3	EN 10283:1998	342, 345
GX30CoCr50-28	ISO 11973:1999	354, 358	GX5CrNiMoNb19-11-2	EN 10213-4:1995	349, 350
GX30CrSi7	EN 10295:2002	335, 336		EN 10283:1998	342, 345
	ISO 11973:1999	335, 336	GX5CrNiNb19-11	EN 10213-4:1995	349, 350
GX35NiCrSi25-21	EN 10295:2002	353, 357		EN 10283:1998	341, 344
GX3CrNi13-4	EN 10213-3:1995	347, 348	GX6CrNiN26-7	EN 10283:1998	361
GX40CrNiSi22-10	EN 10295:2002	351, 356	GX7CrNiMo12-1	EN 10283:1998	339, 340
	ISO 11973:1999	351, 356	GX8CrNi12	EN 10213-2:1995	347, 348
GX40CrNiSi25-12	EN 10295:2002	352, 356	GX90MnMo14	ISO 13521:1999	328, 329
	ISO 11973:1999	352, 356	Н	ASTM A 514/A 514M-00a	82, 86
GX40CrNiSi25-20	EN 10295:2002	352, 357		ASTM	153
	ISO 11973:1999	352, 357	ц /ЦЦ\	A 517/A 517M-93 (1999)	211
			H (HH)	ASTM A 668/A 668M-03	311

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
H10	ASTM A 681-94 (1999)	434	HS2-9-2	ISO 4957:1999	432
H11	ASTM A 681-94 (1999)	434	HS3-3-2	ISO 4957:1999	438
	SAE J438-1970	434	HS6-5-2	ISO 4957:1999	432
H12	ASTM A 681-94 (1999)	434	HS6-5-2-5	ISO 4957:1999	432
	SAE J438-1970	434	HS6-5-2C	ISO 4957:1999	438
H13	ASTM A 681-94 (1999)	434	HS6-5-3	ISO 4957:1999	432
	SAE J438-1970	434	HS6-5-3-8	ISO 4957:1999	438
H14	ASTM A 681-94 (1999)	438	HS6-5-3C	ISO 4957:1999	438
H19	ASTM A 681-94 (1999)	434	HS6-5-4	ISO 4957:1999	432
H21	ASTM A 681-94 (1999)	434	HS6-6-2	ISO 4957:1999	432
	SAE J438-1970	434	HSA 235W, Class B	ISO 5952:1998	88, 94
H22	ASTM A 681-94 (1999)	438	HSA 235W, Class D	ISO 5952:1998	88, 94
H23	ASTM A 681-94 (1999)	438	HSA 245W, Class B	ISO 5952:1998	89, 94
H24	ASTM A 681-94 (1999)	438	HSA 245W, Class D	ISO 5952:1998	89, 94
H25	ASTM A 681-94 (1999)	438	HSA 365W, Class B	ISO 5952:1998	91, 95
H26	ASTM A 681-94 (1999)	438	HSA 365W, Class D	ISO 5952:1998	91, 95
H41	ASTM A 681-94 (1999)	438	HSA355W1, Class A	ISO 5952:1998	93, 96
H42	ASTM A 681-94 (1999)	438	HSA355W1, Class D	ISO 5952:1998	93, 96
H43	ASTM A 681-94 (1999)	438	HSA355W2, Class C	ISO 5952:1998	93, 96
HC	ASTM	351, 355	•	ISO 5952:1998	93, 96
	A 297/A 297M-97 (2003)	,	HSA355W2, Class D	ASTM	•
HC30	ASTM A 608/A 608M-02	351, 355	HT	A 297/A 297M-97 (2003)	353, 357
HD	ASTM	351, 355	HT30	ASTM A 351/A 351M-03	353, 357
LIDEO	A 297/A 297M-97 (2003)	054 055	HT50	ASTM A 608/A 608M-02	353, 357
HD50	ASTM A 608/A 608M-02	351, 355	HU	ASTM	353, 358
HE	ASTM	351, 356		A 297/A 297M-97 (2003)	,
HE35	A 297/A 297M-97 (2003) ASTM A 608/A 608M-02	351, 356	HU50	ASTM A 608/A 608M-02	353, 358
HF	ASTM	351, 356	HW	ASTM	354, 358
111	A 297/A 297M-97 (2003)	001, 000		A 297/A297M-97 (2003)	
HF30	ASTM A 608/A 608M-02	351, 356	HW50	ASTM A 608/A 608M-02	354, 358
HH	ASTM	352, 356	HX	ASTM	354, 358
	A 297/A 297M-97 (2003)		HX50	A 297/A 297M-97 (2003) ASTM A 608/A 608M-02	354, 358
HH30	ASTM A 608/A 608M-02	352, 356	J	ASTM A 514/A 514M-00a	82, 86
HH33	ASTM A 608/A 608M-02	352, 356	· ·	ASTM	153
HI	ASTM	352, 356		A 517/A 517M-93 (1999)	100
HI35	A 297/A 297M-97 (2003)	252 256	J (JH)	ASTM A 668/A 668M-03	311
HK	ASTM A 608/A 608M-02 ASTM	352, 356	K	ASTM A 514/A 514M-00a	82, 86
ПК	A 297/A 297M-97 (2003)	352, 356		ASTM	153
HK30	ASTM A 351/A 351M-03	352, 356		A 517/A 517M-93 (1999)	
	ASTM A 608/A 608M-02	352, 356		ASTM A 588/A 588M-03a	73, 77
HK40	ASTM A 351/A 351M-03	352, 357	K (KH)	ASTM A 668/A 668M-03	311
	ASTM A 608/A 608M-02	352, 357	L (LH)	ASTM A 668/A 668M-03	311
HL	ASTM	352, 357	L175, Class I	ISO 3183-1:1996	246, 247
	A 297/A 297M-97 (2003)	•	L175, Class II	ISO 3183-1:1996	246, 247
HL30	ASTM A 608/A 608M-02	352, 357	L2	ASTM A 681-94 (1999)	438
HL40	ASTM A 608/A 608M-02	352, 357	L210	ISO 3183-1:1996	246, 247
HN	ASTM	353, 357	L210GA	EN 10208-1:1997	246, 247
111140	A 297/A 297M-97 (2003)		L235GA	EN 10208-1:1997	263
HN40	ASTM A 608/A 608M-02	353, 357	L245	ISO 3183-1:1996	246, 247
HP	ASTM	353, 357	L245GA	EN 10208-1:1997	246, 247
HPS 50W [HPS 345W]	A 297/A 297M-97 (2003) ASTM A 709/A 709M-03a	97	L245MB	EN 10208-2:1996	250, 253
HPS 70W [HPS 485W]	ASTM A 709/A 709M-03a	80, 84		ISO 3183-2:1996	250, 253
HS0-4-1	ISO 4957:1999	438	L245NB	EN 10208-2:1996	250, 253
HS10-4-3-10	ISO 4957:1999	432		ISO 3183-2:1996	250, 253
HS1-4-2	ISO 4957:1999	438	L290	ISO 3183-1:1996	246, 247
HS18-0-1	ISO 4957:1999	431	L290GA	EN 10208-1:1997	246, 247
HS1-8-1	ISO 4957:1999	438	L290MB	EN 10208-2:1996	250, 253
HS2-9-1-8	ISO 4957:1999	432		ISO 3183-2:1996	250, 253
1102-0-1-0	100 4007.1000	402			

578 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
L290NB	EN 10208-2:1996	250, 253	LW 19	BS 6323-8:1982 AMD 2:198	
	ISO 3183-2:1996	250, 253	LW 20	BS 6323-8:1982 AMD 2:198	-
L3	ASTM A 681-94 (1999)	438	LW 21	BS 6323-8:1982 AMD 2:198	-
L320	ISO 3183-1:1996	246, 248	LW 22	BS 6323-8:1982 AMD 2:198	-
L360	ISO 3183-1:1996	246, 248	LW 23	BS 6323-8:1982 AMD 2:198	
L360GA	EN 10208-1:1997	246, 248	LW 24	BS 6323-8:1982 AMD 2:198	
L360MB	EN 10208-2:1996	251, 254	LWCF 20	BS 6323-8:1982 AMD 2:198	-
	ISO 3183-2:1996	251, 254	LWCF 21	BS 6323-8:1982 AMD 2:198	
L360NB	EN 10208-2:1996	251, 254	LWCF 22	BS 6323-8:1982 AMD 2:198	•
	ISO 3183-2:1996	251, 254	LWCF 23	BS 6323-8:1982 AMD 2:198	•
L360QB	EN 10208-2:1996	251, 254	LWCF 24	BS 6323-8:1982 AMD 2:198	,
	ISO 3183-2:1996	251, 254	M	ASTM A 514/A 514M-00a	82, 86
L390	ISO 3183-1:1996	246, 248		ASTM	153
L415	ISO 3183-1:1996	246, 248	NA (NALI)	A 517/A 517M-93 (1999)	011
L415MB	EN 10208-2:1996	251, 255	M (MH)	ASTM A 668/A 668M-03	311
	ISO 3183-2:1996	251, 255	M1	ASTM A 600-92a (1999)	438
L415NB	EN 10208-2:1996	251, 255	M40	SAE J438-1970	438
	ISO 3183-2:1996	251, 255	M10	ASTM A 600-92a (1999)	438
L415QB	EN 10208-2:1996	251, 255	M2	ASTM A 600-92a (1999)	432
	ISO 3183-2:1996	251, 255	140	SAE J438-1970	432
L450	ISO 3183-1:1996	246, 248	M3	SAE J438-1970	432
L450MB	EN 10208-2:1996	252, 255	M3, Class 1	ASTM A 600-92a (1999)	432
	ISO 3183-2:1996	252, 255	M3, Class 2	ASTM A 600-92a (1999)	432
L450QB	EN 10208-2:1996	252, 255	M30	ASTM A 600-92a (1999)	438
L-100QD	ISO 3183-2:1996	252, 255	M33	ASTM A 600-92a (1999)	438
L485	ISO 3183-1:1996	246, 249	M34	ASTM A 600-92a (1999)	438
L485MB	EN 10208-2:1996	252, 256	M36	ASTM A 600-92a (1999)	432
L403IVID	ISO 3183-2:1996	252, 256	M4	ASTM A 600-92a (1999)	432
L485QB	EN 10208-2:1996	252, 256 252, 256		SAE J438-1970	432
L400QD		•	M41	ASTM A 600-92a (1999)	438
1.555	ISO 3183-2:1996	252, 256	M42	ASTM A 600-92a (1999)	432
L555	ISO 3183-1:1996	246, 249	M43	ASTM A 600-92a (1999)	438
L555MB	EN 10208-2:1996	252, 256	M44	ASTM A 600-92a (1999)	438
	ISO 3183-2:1996	252, 256	M46	ASTM A 600-92a (1999)	438
L555QB	EN 10208-2:1996	252, 256	M47	ASTM A 600-92a (1999)	438
	ISO 3183-2:1996	252, 256	M48	ASTM A 600-92a (1999)	438
L6	ASTM A 681-94 (1999)	434	M50	ASTM A 600-92a (1999)	438
	SAE J438-1970	434	M52	ASTM A 600-92a (1999)	438
L7	SAE J438-1970	438	M6	ASTM A 600-92a (1999)	438
LC1	ASTM A 352/A 352M-03	337, 338	M62	ASTM A 600-92a (1999)	438
LC2	ASTM A 352/A 352M-03	337, 338	M7	ASTM A 600-92a (1999)	432
LC2-1	ASTM A 352/A 352M-03	337, 338	MT 1010	ASTM A 512-96 (2001)	165, 169,
LC3	ASTM A 352/A 352M-03	337, 338	MT 4045	ACTM A 510 00 (0001)	176, 180
LC4	ASTM A 352/A 352M-03	359	MT 1015	ASTM A 512-96 (2001)	165, 171, 176, 181
LC9	ASTM A 352/A 352M-03	359	MT 1017	ASTM A 512-96 (2001)	170, 181
LCA	ASTM A 352/A 352M-03	327	MT 1020	ASTM A 512-96 (2001)	167, 172,
LCB	ASTM A 352/A 352M-03	327	1111 1020	7.01.11.71.012.00 (2001)	177, 182
LCC	ASTM A 352/A 352M-03	327	MT 1025	ASTM A 512-96 (2001)	167, 178
LF1, Class 1	ASTM A 350/A 350M-02b	272, 275	MT 1030	ASTM A 512-96 (2001)	170, 180
LF2, Class 1	ASTM A 350/A 350M-02b	273, 275	MT 302	ASTM A 511-96	259
LF2, Class 2	ASTM A 350/A 350M-02b	273, 275	MT 303Se	ASTM A 511-96	259
LF3, Class 1	ASTM A 350/A 350M-02b	289, 290	MT 304	ASTM A 511-96	190, 193
LF3, Class 2	ASTM A 350/A 350M-02b	289, 290	MT 304L	ASTM A 511-96	190, 193
LF5	ASTM A 350/A 350M-02b	312	MT 305	ASTM A 511-96	259
LF6	ASTM A 350/A 350M-02b	312	MT 309S	ASTM A 511-96	259
	ACTM A OFO/A OFOM OOK	212			
LF787	ASTM A 350/A 350M-02b	312	MT 310S	ASTM A 511-96	259
LF787 LF9	ASTM A 350/A 350M-02b	312	MT 310S MT 316	ASTM A 511-96 ASTM A 511-96	259 191, 194

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
MT 317	ASTM A 511-96	259	P 28	ISO 9327-4:1999	272, 275
MT 321	ASTM A 511-96	192, 195	P 285 TN	ISO 9328-4:1991	113, 115
MT 347	ASTM A 511-96	192, 195	P 290	ISO 9328-2:1991	105, 110
MT 403	ASTM A 511-96	259	P 315	ISO 9328-2:1991	106, 111
MT 405	ASTM A 511-96	188, 189	P 315 TN	ISO 9328-4:1991	104, 109
MT 410	ASTM A 511-96	188, 189	P 35	ISO 9327-4:1999	273, 275
MT 414	ASTM A 511-96	259	P 355	ISO 9328-2:1991	107, 112
MT 416Se	ASTM A 511-96	259	P 355 TN	ISO 9328-4:1991	114, 116
MT 429	ASTM A 511-96	259	P 390 TN	ISO 9328-4:1991	155
MT 430	ASTM A 511-96	188, 189	P 42	ISO 9327-4:1999	274, 276
MT 431	ASTM A 511-96	259	P 420 TN	ISO 9328-4:1991	155
MT 440A	ASTM A 511-96	259	P 46	ISO 9327-4:1999	311
MT 443	ASTM A 511-96	259	P 460 TN	ISO 9328-4:1991	155
MT 446-1	ASTM A 511-96	259	P 460 TQ	ISO 9328-4:1991	155
MT 446-2	ASTM A 511-96	259	P 500 TQ	ISO 9328-4:1991	155
MT-301	ASTM A 554-03	259	P 550 TQ	ISO 9328-4:1991	155
MT-302	ASTM A 554-03	259	P 620 TQ	ISO 9328-4:1991	155
MT-304	ASTM A 554-03	190, 193	P 690 TQ	ISO 9328-4:1991	155
MT-304L	ASTM A 554-03	190, 193	P1		
MT-305	ASTM A 554-03	259		ASTM A 335/A 335M-03	214, 215
MT-309S	ASTM A 554-03	259	P11 P12	ASTM A 335/A 335M-03	219
MT-309S-Cb	ASTM A 554-03	259		ASTM A 335/A 335M-03	217, 218
MT-310S	ASTM A 554-03	259	P122	ASTM A 333/A 333M-99	260
MT-316	ASTM A 554-03	191, 194	P15	ASTM A 335/A 335M-03	261
MT-316L	ASTM A 554-03	191, 194	P195GH	EN 10216-2:2002	206, 210
MT-317	ASTM A 554-03	259	D	EN 10217-2:2002	206, 210
MT-321	ASTM A 554-03	192, 195	P195TR1	EN 10216-1:2002	202, 204
MT-330	ASTM A 554-03	259		EN 10217-1:2002	202, 204
MT-347	ASTM A 554-03	192, 195	P195TR2	EN 10216-1:2002	202, 204
MT-429	ASTM A 554-03	259		EN 10217-1:2002	202, 204
MT-430	ASTM A 554-03	188, 189	P2	ASTM A 335/A 335M-03	216
MT-430-Ti	ASTM A 554-03	259		ASTM A 681-94 (1999)	438
N (NH)	ASTM A 668/A 668M-03	311	P20	ASTM A 681-94 (1999)	438
N-1	ASTM A 27/A 27M-03	359	P21	ASTM A 335/A 335M-03	261
N-2	ASTM A 27/A 27M-03	359		ASTM A 681-94 (1999)	438
NCF 800 TF	JIS G 3467:1988	233, 245	P215NL	EN 10216-4:2002	196, 198
NCF 800H TF	JIS G 3467:1988	233, 245		EN 10217-4:2002	196, 198
NiCr15Fe	EN 10095:1999	414, 416		EN 10217-6:2002	196, 198
NiCr15Fe8	ISO 4955:1994	416	P22	ASTM A 335/A 335M-03	220
NiCr20Ti	EN 10095:1999	414, 416	P23	ASTM A 333/A 333M-99	260
141012011	ISO 4955:1994	416	P235GH	EN 10028-2:2003	103, 109
NiCr22Mo9Nb	EN 10095:1999	414, 416		EN 10216-2:2002	207, 210
TVIOIZZIVIOSIVO	ISO 4955:1994	416		EN 10217-2:2002	207, 210
NiCr23Fe	EN 10095:1999	414, 416		EN 10217-5:2002	207, 210
NiCr28FeSiCe	EN 10095:1999		P235TR1	EN 10216-1:2002	202, 204
	ASTM A 681-94 (1999)	414, 416		EN 10217-1:2002	202, 204
01	` '	438	P235TR2	EN 10216-1:2002	202, 204
00	SAE J438-1970	438		EN 10217-1:2002	202, 204
O2	ASTM A 681-94 (1999)	438	P245GH	EN 10222-2:1999	272, 275
00	SAE J438-1970	438	P255QL	EN 10216-4:2002	196, 198
O6	ASTM A 681-94 (1999)	438	P265GH	EN 10028-2:2003	104, 109
07	SAE J438-1970	438		EN 10216-2:2002	208, 211
07	ASTM A 681-94 (1999)	438		EN 10217-2:2002	208, 211
Р	ASTM A 514/A 514M-00a	82, 86		EN 10217-5:2002	208, 211
	ASTM A 517/A 517M 02 (1000)	153	P265NL	EN 10216-4:2002	197, 198
P 235	A 517/A 517M-93 (1999) ISO 9328-2:1991	103, 109		EN 10217-4:2002	197, 198
P 255 TN	ISO 9328-4:1991	113, 115		EN 10217-6:2002	197, 198
P 265	ISO 9328-2:1991	104, 109			*
1 400	130 3320-2.1331	104, 109			

580 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
P265TR1	EN 10216-1:2002	203, 205	P460NL2	EN 10028-3:2003	155
	EN 10217-1:2002	203, 205		EN 10216-3:2002	259
P265TR2	EN 10216-1:2002	203, 205		EN 10217-3:2002	261
	EN 10217-1:2002	203, 205	P460Q	EN 10028-6:2003	155
P275NH	EN 10028-3:2003	104, 109	P460QH	EN 10028-6:2003	155
P275NL1	EN 10028-3:2003	113, 115	P460QL1	EN 10028-6:2003	155
	EN 10216-3:2002	259	P460QL2	EN 10028-6:2003	155
	EN 10217-3:2002	261	P5	ASTM A 335/A 335M-03	221
P275NL2	EN 10028-3:2003	113, 115		ASTM A 681-94 (1999)	438
	EN 10216-3:2002	196, 198	P500Q	EN 10028-6:2003	155
	EN 10217-3:2002	261	P500QH	EN 10028-6:2003	155
P280GH	EN 10222-2:1999	273, 275	P500QL1	EN 10028-6:2003	155
P285NH	EN 10222-4:1998 A1:2001	272, 275	P500QL2	EN 10028-6:2003	155
P285QH	EN 10222-4:1998 A1:2001	272, 275	P5b	ASTM A 335/A 335M-03	261
P295GH	EN 10028-2:2003	105, 110	P5c	ASTM A 335/A 335M-03	261
P3	ASTM A 681-94 (1999)	438	P6	ASTM A 681-94 (1999)	438
P305GH	EN 10222-2:1999	273, 275	P620Q	EN 10216-3:2002	259
P355GH	EN 10028-2:2003	107, 112	P620QH	EN 10216-3:2002	259
P355M	EN 10028-5:2003	155	P620QL	EN 10216-3:2002	259
P355M1	EN 10028-5:2003	155	P690Q	EN 10028-6:2003	155
P355M2	EN 10028-5:2003	155		EN 10216-3:2002	259
P355N	EN 10028-3:2003	106, 111,	P690QH	EN 10028-6:2003	155
		114, 116		EN 10216-3:2002	259
	EN 10216-3:2002	259	P690QL1	EN 10028-6:2003	155
	EN 10217-3:2002	261		EN 10216-3:2002	259
P355NH	EN 10028-3:2003	106, 111,	P690QL2	EN 10028-6:2003	155
	EN 10010 0 0000	114, 116		EN 10216-3:2002	259
	EN 10216-3:2002	259	P9	ASTM A 335/A 335M-03	222
	EN 10217-3:2002	261	P91	ASTM A 335/A 335M-03	261
D0==1# /	EN 10222-4:1998 A1:2001	273, 275	P911	ASTM A 333/A 333M-99	260
P355NL1	EN 10028-3:2003	114, 116	P92	ASTM A 333/A 333M-99	260
	EN 10216-3:2002	259	PH 235	ISO 9328-2:1991	103, 109
	EN 10217-3:2002	261	PH 255 TN	ISO 9328-4:1991	113, 115
P355NL2	EN 10028-3:2003	114, 116	PH 26	ISO 9327-2:1999	268, 271
	EN 10216-3:2002	259	PH 265	ISO 9328-2:1991	104, 109
	EN 10217-3:2002	261	PH 28	ISO 9327-4:1999	272, 275
P355Q	EN 10028-6:2003	155	PH 285 TN	ISO 9328-4:1991	113, 115
P355QH	EN 10028-6:2003	155	PH 29	ISO 9327-2:1999	268, 271
P355QH1	EN 10222-4:1998 A1:2001	273, 275	PH 290	ISO 9328-2:1991	105, 110
P355QL1	EN 10028-6:2003	155	PH 31	ISO 9327-2:1999	269, 271
P355QL2	EN 10028-6:2003	155	PH 315	ISO 9328-2:1991	106, 111
P4	ASTM A 681-94 (1999)	438	PH 315 TN	ISO 9328-4:1991	104, 109
P420M	EN 10028-5:2003	155	PH 35	ISO 9327-4:1999	273, 275
P420M1	EN 10028-5:2003	155	PH 355	ISO 9328-2:1991	107, 112
P420M2	EN 10028-5:2003	155	PH 355 TN		•
P420NH	EN 10222-4:1998 A1:2001	274, 276		ISO 9328-4:1991	114, 116
P420QH	EN 10222-4:1998 A1:2001	274, 276	PH 390 TN	ISO 9328-4:1991	155
P460M	EN 10028-5:2003	155	PH 42	ISO 9327-4:1999	274, 276
P460M1	EN 10028-5:2003	155	PH 420 TN	ISO 9328-4:1991	155
P460M2	EN 10028-5:2003	155	PH 46	ISO 9327-4:1999	311
P460N	EN 10216-3:2002	259	PH 460 TN	ISO 9328-4:1991	155
	EN 10217-3:2002	261	PH 460 TQ	ISO 9328-4:1991	155
P460NH	EN 10028-3:2003	155	PH 500 TQ	ISO 9328-4:1991	155
	EN 10216-3:2002	259	PH 550 TQ	ISO 9328-4:1991	155
	EN 10217-3:2002	261	PH 620 TQ	ISO 9328-4:1991	155
P460NL1	EN 10028-3:2003	155	PH 690 TQ	ISO 9328-4:1991	155
	EN 10216-3:2002	259	PL 21	ISO 9329-3:1997	196, 198
	EN 10217-3:2002	261		ISO 9330-3:1997	196, 198

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
PL 21 (continued(ISO 9330-5:2000	196, 198	R37	ISO 3304:1985	166, 167,
PL 23	ISO 9329-3:1997	197, 198			168, 170,
	ISO 9330-3:1997	197, 198			177, 178,
	ISO 9330-5:2000	197, 198		ISO 3305:1985	179, 180 166, 167,
PL 25	ISO 9329-3:1997	196, 198		130 3303.1903	168, 170,
	ISO 9330-3:1997	196, 198			177, 178,
	ISO 9330-5:2000	196, 198			179, 180
PL 255 TN	ISO 9328-4:1991	113, 115		ISO 3306:1985	166, 167,
PL 26	ISO 9329-3:1997	260			168, 177,
	ISO 9330-3:1997	260	R44	ISO 3304:1985	178, 179 168, 169,
	ISO 9330-5:2000	260	1144	130 3304.1903	170, 173,
PL 28	ISO 9327-4:1999	272, 275			179, 180,
PL 285 TN	ISO 9328-4:1991	113, 115			182
PL 315 TN	ISO 9328-4:1991	104, 109		ISO 3305:1985	168, 169,
PL 35	ISO 9327-4:1999	273, 275			170, 173,
PL 355 TN	ISO 9328-4:1991	114, 116			179, 180,
PL 390 TN	ISO 9328-4:1991	155		ISO 3306:1985	182 168, 169,
PL 42	ISO 9327-4:1999			130 3300.1903	179
	ISO 9328-4:1991	274, 276	R50	ISO 3304:1985	171, 173,
PL 420 TN		155			174, 181,
PL 46	ISO 9327-4:1999	311			183, 184
PL 460 TN	ISO 9328-4:1991	155		ISO 3305:1985	171, 172,
PL 460 TQ	ISO 9328-4:1991	155			173, 174,
PL 500 TQ	ISO 9328-4:1991	155			181, 183, 184
PL 550 TQ	ISO 9328-4:1991	155		ISO 3306:1985	171, 172,
PL 620 TQ	ISO 9328-4:1991	155		100 0000.1000	173, 181,
PL 690 TQ	ISO 9328-4:1991	155			182
PLH 35	ISO 9327-4:1999	273, 275	S	ASTM A 514/A 514M-00a	82, 86
PLH 355 TN	ISO 9328-4:1991	114, 116		ASTM	153
PLH 390 TN	ISO 9328-4:1991	155		A 517/A 517M-93 (1999)	
PLH 42	ISO 9327-4:1999	274, 276	S 09 CK	JIS G 4051:1979	23
PLH 420 TN	ISO 9328-4:1991	155	S 10 C	JIS G 4051:1979	23
PLH 46	ISO 9327-4:1999	311	S 12 C	JIS G 4051:1979	23
PLH 460 TN	ISO 9328-4:1991	155	S 15 C	JIS G 4051:1979	24
PLH 460 TQ	ISO 9328-4:1991	155	S 15 CK	JIS G 4051:1979	24
PLH 500 TQ	ISO 9328-4:1991	155	S 17 C	JIS G 4051:1979	24
PLH 550 TQ	ISO 9328-4:1991	155	S 20 C	JIS G 4051:1979	25
PLH 620 TQ	ISO 9328-4:1991	155	S 20 CK	JIS G 4051:1979	25
PLH 690 TQ	ISO 9328-4:1991	155	S 22 C	JIS G 4051:1979	25
Q	ASTM A 514/A 514M-00a	82, 86	S 25 C	JIS G 4051:1979	26
Q	ASTM A ST4/A ST4W 00a	153	S 28 C	JIS G 4051:1979	26
	A 517/A 517M-93 (1999)	100	S 30 C	JIS G 4051:1979	26
R	ASTM A 514/A 514M-00a	82, 86	S 33 C	JIS G 4051:1979	27
R28	ISO 3304:1985	165, 167,	S 35 C	JIS G 4051:1979	27
		168, 176,	S 38 C	JIS G 4051:1979	27
		177, 179	S 40 C	JIS G 4051:1979	28
	ISO 3305:1985	165, 167,	S 43 C	JIS G 4051:1979	28
		168, 176,	S 45 C	JIS G 4051:1979	29
	ISO 3306:1985	177, 179 165, 166,	S 48 C	JIS G 4051:1979	29
	130 3300.1983	176, 177			
R33	ISO 3304:1985	166, 167,	S 50 C	JIS G 4051:1979	30
-		169, 177,	S 53 C	JIS G 4051:1979	30
		178, 179	S 55 C	JIS G 4051:1979	31
	ISO 3305:1985	166, 167,	S 58 C	JIS G 4051:1979	31
		169, 177,	S CM 415 TK	JIS G 3441:1988	258
	ISO 2206:1005	178, 179	S Cr 420 TK	JIS G 3441:1988	258
	ISO 3306:1985	166, 177	S1	ASTM A 681-94 (1999)	438
				SAE J438-1970	438
			S185	EN 10025:1993	50, 66

582 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
S2	ASTM A 681-94 (1999)	438	S50C-CSP	JIS G 4802:1999	425
	SAE J438-1970	438	S550A	EN 10137-3:1996	81, 85
S235J0	EN 10025:1993	52, 67	S550AL	EN 10137-3:1996	81, 85
S235J0W	EN 10155:1993	88, 94	S550Q	EN 10137-2:1996	81, 85
S235J2G3	EN 10025:1993	53, 67	S550QL	EN 10137-2:1996	81, 85
	EN 10250-2:1999	268, 271	S550QL1	EN 10137-2:1996	81, 85
S235J2G4	EN 10025:1993	53, 67	S55C-CSP	JIS G 4802:1999	425
S235J2W	EN 10155:1993	88, 94	S6	ASTM A 681-94 (1999)	438
S235JR	EN 10025:1993	52, 67	S60C-CSP	JIS G 4802:1999	425
S235JRG1	EN 10025:1993	52, 67	S620A	EN 10137-3:1996	82, 86
S235JRG2	EN 10025:1993	52, 67	S620AL	EN 10137-3:1996	82, 86
	EN 10250-2:1999	268, 271	S620Q	EN 10137-2:1996	82, 86
S275J0	EN 10025:1993	57, 69	S620QL	EN 10137-2:1996	82, 86
S275J2G3	EN 10025:1993	57, 69	S620QL1	EN 10137-2:1996	82, 86
S275J2G4	EN 10025:1993	58, 69	S65C-CSP	JIS G 4802:1999	425
S275JR	EN 10025:1993	57, 69	S690A	EN 10137-3:1996	82, 87
S275M	EN 10113-3:1993	98	S690AL	EN 10137-3:1996	82, 87
S275ML	EN 10113-3:1993	98	S690Q	EN 10137-2:1996	82, 87
S275N	EN 10113-2:1998	98	S690QL	EN 10137-2:1996	82, 87
S275NL	EN 10113-2:1998	98	S690QL1	EN 10137-2:1996	82, 87
S355J0	EN 10025:1993	62, 71	S7	ASTM A 681-94 (1999)	438
S355J0W	EN 10155:1993	92, 96	S70C-CSP	JIS G 4802:1999	425
S355J0WP	EN 10155:1993	92, 96	S890Q	EN 10137-2:1996	98
S355J2G1W	EN 10155:1993	92, 96	S890QL	EN 10137-2:1996	98
S355J2G2W	EN 10155:1993	92, 96	S890QL1	EN 10137-2:1996	98
S355J2G3	EN 10025:1993	62, 71	S960Q	EN 10137-2:1996	98
	EN 10250-2:1999	311	S960QL	EN 10137-2:1996	98
S355J2G4	EN 10025:1993	63, 71	SACM 645	JIS G 4202:1979	40
S355J2WP	EN 10155:1993	92, 96	SB 410	JIS G 3103:1987	104, 109
S355JR	EN 10025:1993	62, 71	SB 42	JIS G 3120:1987	155
S355K2G1W	EN 10155:1993	92, 96	SB 450	JIS G 3103:1987	105, 110
S355K2G2W	EN 10155:1993	93, 96	SB 450 M	JIS G 3103:1987	117, 119
S355K2G3	EN 10025:1993	63, 71	SB 46	JIS G 3120:1987	155
S355K2G4	EN 10025:1993	63, 71	SB 46 M	JIS G 3120:1987	155
S355M	EN 10113-3:1993	72, 76	SB 480	JIS G 3103:1987	105, 110
S355ML	EN 10113-3:1993	72, 76	SB 480 M	JIS G 3103:1987	117, 119
S355N	EN 10113-2:1998	73, 77	SB 49	JIS G 3120:1987	155
S355NL	EN 10113-2:1998	73, 77	SB 49 M	JIS G 3120:1987	155
S4	ASTM A 681-94 (1999)	438	SBV 1 A	JIS G 3119:1987	117, 119
S420M	EN 10113-3:1993	74, 77	SBV 1 B	JIS G 3119:1987	118, 120
S420ML	EN 10113-3:1993	74, 77	SBV 2	JIS G 3119:1987	137, 138
S420N	EN 10113-2:1998	98	SBV 3	JIS G 3119:1987	139, 140
S420NL	EN 10113-2:1998	98	SC 360	JIS G 5101:1991	319, 323
S460M	EN 10113-3:1993	98			
S460ML	EN 10113-3:1993	98	SC 410	JIS G 5101:1991 ASTM A 958-00	319, 323 330, 332
S460N	EN 10113-2:1998	98	SC 4130 Class 105/85		· · · · · · · · · · · · · · · · · · ·
S460NL	EN 10113-2:1998	98	SC 4130 Class 115/95	ASTM A 958-00	330, 332
S460Q	EN 10137-2:1996	80, 84	SC 4130 Class 130/115	ASTM A 958-00 ASTM A 958-00	330, 332
S460QL	EN 10137-2:1996	80, 84	SC 4130 Class 135/125		330, 332
S460QL1	EN 10137-2:1996	80, 84	SC 4130 Class 150/135	ASTM A 958-00	330, 332
S5	ASTM A 681-94 (1999)	438	SC 4130 Class 65/35	ASTM A 958-00	330, 332
00	SAE J438-1970	438	SC 4130 Class 70/36	ASTM A 958-00	330, 332
\$500A			SC 4130 Class 80/40	ASTM A 958-00	330, 332
S500A	EN 10137-3:1996	81, 85 81 85	SC 4130 Class 80/50	ASTM A 958-00	330, 332
S500AL	EN 10137-3:1996	81, 85	SC 4130 Class 90/60	ASTM A 958-00	330, 332
S500Q	EN 10137-2:1996	80, 84	SC 4140 Class 105/85	ASTM A 958-00	330, 333
S500QL	EN 10137-2:1996	80, 84	SC 4140 Class 115/95	ASTM A 958-00	330, 333
S500QL1	EN 10137-2:1996	80, 84	SC 4140 Class 130/115	ASTM A 958-00	330, 333

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SC 4140 Class 135/125	ASTM A 958-00	330, 333	SCH 13A	JIS G 5122:2003	352, 356
SC 4140 Class 150/135	ASTM A 958-00	330, 333	SCH 15	JIS G 5122:2003	353, 357
SC 4140 Class 160/145	ASTM A 958-00	330, 333	SCH 16	JIS G 5122:2003	353, 357
SC 4140 Class 165/150	ASTM A 958-00	330, 333	SCH 17	JIS G 5122:2003	351, 356
SC 4140 Class 65/35	ASTM A 958-00	330, 333	SCH 18	JIS G 5122:2003	352, 356
SC 4140 Class 70/36	ASTM A 958-00	330, 333	SCH 19	JIS G 5122:2003	353, 357
SC 4140 Class 80/40	ASTM A 958-00	330, 333	SCH 2	JIS G 5122:2003	351, 355
SC 4140 Class 80/50	ASTM A 958-00	330, 333	SCH 20	JIS G 5122:2003	353, 358
SC 4140 Class 90/60	ASTM A 958-00	330, 333	SCH 21	JIS G 5122:2003	352, 356
SC 4330 Class 105/85	ASTM A 958-00	330, 334	SCH 22	JIS G 5122:2003	352, 357
SC 4330 Class 115/95	ASTM A 958-00	330, 334	SCH 23	JIS G 5122:2003	352, 357
SC 4330 Class 130/115	ASTM A 958-00	330, 334	SCH 24	JIS G 5122:2003	353, 357
SC 4330 Class 135/125	ASTM A 958-00	330, 334	SCH 3	JIS G 5122:2003	351, 355
SC 4330 Class 150/135	ASTM A 958-00	330, 334	SCM 415	JIS G 4053:2003	44
SC 4330 Class 160/145	ASTM A 958-00	330, 334	30W 413	JIS G 4105:1979	44
SC 4330 Class 165/150	ASTM A 958-00	330, 334	SCM 418	JIS G 4053:2003	37
SC 4330 Class 210/180	ASTM A 958-00	330, 334	SCM 418 TK	JIS G 3441:1988	185, 186
SC 4330 Class 65/35	ASTM A 958-00	330, 334	SCM 420	JIS G 4053:2003	37
SC 4330 Class 70/36	ASTM A 958-00	330, 334			
SC 4330 Class 80/40	ASTM A 958-00	330, 334	SCM 420 TK	JIS G 3441:1988	185, 186
SC 4330 Class 80/50	ASTM A 958-00	330, 334	SCM 421	JIS G 4053:2003	37
SC 4330 Class 90/60	ASTM A 958-00	330, 334	SCM 425	JIS G 4053:2003	37
SC 4340	ASTM A 958-00	359	SCM 430	JIS G 4053:2003	37
SC 450	JIS G 5101:1991	319, 323	SCM 430 TK	JIS G 3441:1988	185, 186
SC 480	JIS G 5101:1991	320, 323	SCM 432	JIS G 4053:2003	37
SC 8620	ASTM A 958-00	359	SCM 435	JIS G 4053:2003	38
SC 8625	ASTM A 958-00	359	SCM 435 TK	JIS G 3441:1988	185, 187
SC 8630	ASTM A 958-00	359	SCM 440	JIS G 4053:2003	38
SC 1020, Class 65/35	ASTM A 958-00	319, 323	SCM 440 TK	JIS G 3441:1988	185, 187
SC 1020, Class 70/36	ASTM A 958-00	320, 323	SCM 445	JIS G 4053:2003	38
SC 1025, Class 65/35	ASTM A 958-00	319, 323	SCM 822	JIS G 4053:2003	37
SC 1025, Class 70/36	ASTM A 958-00	320, 323	SCMn 1	JIS G 5111:1991	320, 321
SC 1030, Class 65/35	ASTM A 958-00	319, 323	SCMn 1A	JIS G 5111:1991	324
SC 1030, Class 70/36	ASTM A 958-00	320, 323	SCMn 1B	JIS G 5111:1991	324
SC 1030, Class 80/40	ASTM A 958-00	321, 324	SCMn 2	JIS G 5111:1991	321, 321
SC 1030, Class 80/50	ASTM A 958-00	321, 324	SCMn 2A	JIS G 5111:1991	324
SC 1040 Class 90/60	ASTM A 958-00	321, 324	SCMn 2B	JIS G 5111:1991	324
SC 1040, Class 70/36	ASTM A 958-00	320, 323	SCMn 3	JIS G 5111:1991	321, 322
SC 1040, Class 80/40	ASTM A 958-00	321, 324	SCMn 3A	JIS G 5111:1991	324
SC 1040, Class 80/50	ASTM A 958-00	321, 324	SCMn 3B	JIS G 5111:1991	325
SC 1045 Class 105/85	ASTM A 958-00	322, 325	SCMn 5	JIS G 5111:1991	322, 322
SC 1045 Class 90/60	ASTM A 958-00	321, 324	SCMn 5A	JIS G 5111:1991	325
SC 1045, Class 80/40	ASTM A 958-00	321, 324	SCMn 5B	JIS G 5111:1991	325
SC 1045, Class 80/50	ASTM A 958-00	321, 324	SCMnCr 2	JIS G 5111:1991	359
SCC 3	JIS G 5111:1991	320, 321	SCMnCr 3	JIS G 5111:1991	359
SCC 3A	JIS G 5111:1991	324	SCMnCr 4	JIS G 5111:1991	359
SCC 3B	JIS G 5111:1991	324	SCMnCrM 2	JIS G 5111:1991	359
SCC 5	JIS G 5111:1991	321, 322	SCMnCrM 3	JIS G 5111:1991	359
SCC 5A	JIS G 5111:1991	324	SCMnH 1	JIS G 5131:1991	328, 329
SCC 5B	JIS G 5111:1991	325	SCMnH 11	JIS G 5131:1991	328, 329
SCCrM 1A	JIS G 5111:1991	330, 331	SCMnH 2	JIS G 5131:1991	328, 329
SCCrM 1B	JIS G 5111:1991	330, 331	SCMnH 21	JIS G 5131:1991	360
SCCrM 3A	JIS G 5111:1991	330, 332	SCMnH 3	JIS G 5131:1991	328, 329
SCCrM 3B	JIS G 5111:1991	330, 332	SCMnM 3	JIS G 5111:1991	359
SCH 1	JIS G 5122:2003	351, 355	SCMQ4E	JIS G 4110:1993	124, 125
SCH 11	JIS G 5122:2003	351, 355	SCMQ4V	JIS G 4110:1993	155
SCH 12	JIS G 5122:2003	351, 356	SCMQ5V	JIS G 4110:1993	155
SCH 13	JIS G 5122:2003	352, 356	SCMV 1 Div 1	JIS G 4109:1987	121

584 Steel Grade/Name Index

	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SCMV 1 Div 2	JIS G 4109:1987	121	SCSiMn 2	JIS G 5111:1991	321
SCMV 2 Div 1	JIS G 4109:1987	122	SCSiMn 2A	JIS G 5111:1991	324
SCMV 2 Div 2	JIS G 4109:1987	122	SCSiMn 2B	JIS G 5111:1991	324
SCMV 3 Div 1	JIS G 4109:1987	123	SCW 410	JIS G 5102:1991	319, 323
SCMV 3 Div 2	JIS G 4109:1987	123	SCW 450	JIS G 5102:1991	319, 323
SCMV 4 Div 1	JIS G 4109:1987	124, 125	SCW 480	JIS G 5102:1991	320, 323
SCMV 4 Div 2	JIS G 4109:1987	124, 125	SCW 550	JIS G 5102:1991	321, 324
SCMV 5 Div 1	JIS G 4109:1987	126	SCW 620	JIS G 5102:1991	321, 324
SCMV 5 Div 2	JIS G 4109:1987	126	SEV 245	JIS G 3124:1987	107, 112
SCMV 6 Div 1	JIS G 4109:1987	127	SEV 25	JIS G 3124:1987	155
SCMV 6 Div 2	JIS G 4109:1987	127	SEV 295	JIS G 3124:1987	117, 119
SCNCrM 2A	JIS G 5111:1991	330, 334	SEV 30	JIS G 3124:1987	155
SCNCrM 2B	JIS G 5111:1991	330, 334	SEV 345	JIS G 3124:1987	118, 120
SCPH 1	JIS G 5151:1991	326	SEV 35	JIS G 3124:1987	155
SCPH 11	JIS G 5151:1991	335, 336	SF 340 A	JIS G 3201:1988	268, 271
SCPH 2	JIS G 5151:1991	326	SF 390 A	JIS G 3201:1988	268, 271
SCPH 21	JIS G 5151:1991	335, 336	SF 440 A	JIS G 3201:1988	268, 271
SCPH 22	JIS G 5151:1991	359	SF 490 A	JIS G 3201:1988	269, 271
SCPH 23	JIS G 5151:1991	335, 336	SF 540 A	JIS G 3201:1988	269, 271
SCPH 32	JIS G 5151:1991	335, 336	SF 540 B	JIS G 3201:1988	269, 271
SCPH 61	JIS G 5151:1991	335, 336	SF 590 A	JIS G 3201:1988	270, 271
SCPL 1	JIS G 5152:1991	327	SF 590 B	JIS G 3201:1988	270, 271
SCPL 11	JIS G 5152:1991	337, 338	SF 640 B	JIS G 3201:1988	270, 271
SCPL 21	JIS G 5152:1991	337, 338	SFCM 590 D	JIS G 3221:1988	311
SCPL 31	JIS G 5152:1991	337, 338	SFCM 590 R	JIS G 3221:1988	311
SCr 415	JIS G 4053:2003	35	SFCM 590 N	JIS G 3221:1988	311
SCr 420	JIS G 4053:2003	35	SFCM 640 D	JIS G 3221:1988	311
SCr 430	JIS G 4053:2003	35	SFCM 640 R	JIS G 3221:1988	311
SCr 435	JIS G 4053:2003	35			
SCr 440	JIS G 4053:2003	36	SFCM 640 S	JIS G 3221:1988	311
SCr 445	JIS G 4053:2003	36	SFCM 690 D	JIS G 3221:1988	311
SCS 1	JIS G 5121:2003	339, 340	SFCM 690 R	JIS G 3221:1988	311
SCS 10	JIS G 5121:2003	361	SFCM 690 S	JIS G 3221:1988	277, 278
SCS 11	JIS G 5121:2003	361	SFCM 740 D	JIS G 3221:1988	311
			SFCM 740 R	JIS G 3221:1988	311
SCS 12	JIS G 5121:2003	341, 344	SFCM 740 S	JIS G 3221:1988	277, 278
SCS 13	JIS G 5121:2003	341, 344	SFCM 780 D	JIS G 3221:1988	311
SCS 13A	JIS G 5121:2003	341, 344	SFCM 780 R	JIS G 3221:1988	311
SCS 14	JIS G 5121:2003	341, 345	SFCM 780 S	JIS G 3221:1988	277, 278
SCS 14A	JIS G 5121:2003	341, 345	SFCM 830 D	JIS G 3221:1988	311
SCS 15	JIS G 5121:2003	361	SFCM 830 R	JIS G 3221:1988	311
SCS 16	JIS G 5121:2003	361	SFCM 830 S	JIS G 3221:1988	311
SCS 16 A	JIS G 5121:2003	342, 345	SFCM 880 D	JIS G 3221:1988	311
SCS 17	JIS G 5121:2003	342, 346	SFCM 880 R	JIS G 3221:1988	311
SCS 18	JIS G 5121:2003	361	SFCM 880 S	JIS G 3221:1988	311
SCS 19	JIS G 5121:2003	341, 344	SFCM 930 D	JIS G 3221:1988	311
SCS 19A	JIS G 5121:2003	341, 344	SFCM 930 R	JIS G 3221:1988	311
SCS 2	JIS G 5121:2003	339, 340	SFCM 930 S	JIS G 3221:1988	311
SCS 20	JIS G 5121:2003	361	SFCM 980 D	JIS G 3221:1988	311
SCS 21	JIS G 5121:2003	341, 344	SFCM 980 R	JIS G 3221:1988	311
SCS 22	JIS G 5121:2003	342, 345	SFCM 980 S	JIS G 3221:1988	311
SCS 23	JIS G 5121:2003	342, 346	SFL 1	JIS G 3205:1988	272, 275
SCS 24	JIS G 5121:2003	361	SFL 2	JIS G 3205:1988	273, 275
SCS 2A	JIS G 5121:2003	339, 340	SFL 3	JIS G 3205:1988	289, 290
SCS 3	JIS G 5121:2003	339, 340	SFVA F 1	JIS G 3203:1988	279
SCS 4	JIS G 5121:2003	361	SFVA F 11 A	JIS G 3203:1988	282
	JIS G 5121:2003 JIS G 5121:2003	361 339, 340	SFVA F 11 A SFVA F 11 B	JIS G 3203:1988 JIS G 3203:1988	282 282

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SFVA F 2	JIS G 3203:1988	280	SKH40	JIS G 4403:2000	438
SFVA F 21 A	JIS G 3203:1988	285	SKH50	JIS G 4403:2000	438
SFVA F 21 B	JIS G 3203:1988	285	SKH51	JIS G 4403:2000	432
SFVA F 22 A	JIS G 3203:1988	283, 284	SKH52	JIS G 4403:2000	432
SFVA F 22 B	JIS G 3203:1988	283, 284	SKH53	JIS G 4403:2000	432
SFVA F 5 A	JIS G 3203:1988	286	SKH54	JIS G 4403:2000	432
SFVA F 5 B	JIS G 3203:1988	286	SKH55	JIS G 4403:2000	432
SFVA F 5 C	JIS G 3203:1988	286	SKH56	JIS G 4403:2000	432
SFVA F 5 D	JIS G 3203:1988	286	SKH57	JIS G 4403:2000	432
SFVA F 9	JIS G 3203:1988	287	SKH58	JIS G 4403:2000	432
SFVC 1	JIS G 3202:1988	272, 275	SKH59	JIS G 4403:2000	432
SFVC 2 A	JIS G 3202:1988	273, 275	SKS 11	JIS G 4404:2000	434
SFVC 2 B	JIS G 3202:1988	273, 275	SKS 2	JIS G 4404:2000	438
SFVCM F22B	JIS G 3206:1993	283, 284	SKS 21	JIS G 4404:2000	438
SFVCM F22V	JIS G 3206:1993	283, 284	SKS 3	JIS G 4404:2000	438
SFVCM F3V	JIS G 3206:1993	285	SKS 31	JIS G 4404:2000	438
SFVQ 1 A	JIS G 3204:1988	293	SKS 4	JIS G 4404:2000	438
SFVQ 1 B	JIS G 3204:1988	293	SKS 41	JIS G 4404:2000	438
SFVQ 2A	JIS G 3204:1988	292	SKS 43	JIS G 4404:2000	430
SFVQ 2B	JIS G 3204:1988	292	SKS 44	JIS G 4404:2000	430
SFVQ 3	JIS G 3204:1988	294	SKS 5	JIS G 4404:2000	438
SGP	JIS G 3452:1997	165, 176	SKS 51	JIS G 4404:2000	434
SGV410	JIS G 3118:2000	104, 109	SKS 7	JIS G 4404:2000	438
SGV450	JIS G 3118:2000	105, 110	SKS 8	JIS G 4404:2000	438
SGV480	JIS G 3118:2000	105, 110	SKS 81	JIS G 4404:2000	438
SHY 685	JIS G 3128:1999	83, 87	SKS 93	JIS G 4404:2000	438
SHY 685 N	JIS G 3128:1999	83, 87	SKS 94	JIS G 4404:2000	438
SHY 685 NS	JIS G 3128:1999	83, 87	SKS 95	JIS G 4404:2000	438
SK105	JIS G 4401:2000	430	SKT 3	JIS G 4404:2000	438
SK120	JIS G 4401:2000	430	SKT 4	JIS G 4404:2000	434
SK140	JIS G 4401:2000	438	SKT 6	JIS G 4404:2000	438
SK4-CSP	JIS G 4802:1999	426	SL2N255	JIS G 3127:2000	131
SK5-CSP	JIS G 4802:1999	426	SL3N255	JIS G 3127:2000	132, 133
SK60	JIS G 4401:2000	438	SL3N275	JIS G 3127:2000	132, 133
SK65	JIS G 4401:2000	430	SL3N440	JIS G 3127:2000	132, 133
SK70	JIS G 4401:2000	438	SL5N590	JIS G 3127:2000	134
SK75	JIS G 4401:2000	430	SL9N520	JIS G 3127:2000	135, 136
SK80	JIS G 4401:2000	438	SL9N590	JIS G 3127:2000	135, 136
SK85	JIS G 4401:2000	430	SLA 325 A	JIS G 3126:2000	113, 115
SK90	JIS G 4401:2000	438	SLA 325 B	JIS G 3126:2000	113, 115
SK95	JIS G 4401:2000	430	SLA 365	JIS G 3126:2000	114, 116
SKD 1	JIS G 4404:2000	433	SLA 410	JIS G 3126:2000	114, 116
SKD 10	JIS G 4404:2000	438	SM400A	JIS G 3106:1999	54, 68
SKD 10	JIS G 4404:2000	433	SM400A SM400B	JIS G 3106:1999	54, 68
SKD 12					
SKD 12	JIS G 4404:2000 JIS G 4404:2000	433	SM400C	JIS G 3106:1999 JIS G 3106:1999	55, 68
		438	SM490A		59, 70
SKD 4	JIS G 4404:2000	438	SM490B	JIS G 3106:1999	59, 70
SKD 5	JIS G 4404:2000	434	SM490C	JIS G 3106:1999	59, 70
SKD 6	JIS G 4404:2000	434	SM490YA	JIS G 3106:1999	60, 70
SKD 61	JIS G 4404:2000	434	SM490YB	JIS G 3106:1999	60, 70
SKD 62	JIS G 4404:2000	434	SM520B	JIS G 3106:1999	64, 71
SKD 7	JIS G 4404:2000	434	SM520C	JIS G 3106:1999	64, 71
SKD 8	JIS G 4404:2000	434	SM570	JIS G 3106:1999	65, 71
SKH10	JIS G 4403:2000	431	SMA400AP	JIS G 3114:1998	89, 94
SKH2	JIS G 4403:2000	431	SMA400AW	JIS G 3114:1998	89, 94
SKH3	JIS G 4403:2000	431	SMA400BP	JIS G 3114:1998	89, 94
SKH4	JIS G 4403:2000	431	SMA400BW	JIS G 3114:1998	89, 94

586 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SMA400CP	JIS G 3114:1998	89, 94	SS400	JIS G 3101:1995	54, 68
SMA400CW	JIS G 3114:1998	89, 94	SS490	JIS G 3101:1995	59, 70
SMA490AP	JIS G 3114:1998	91, 95	SS540	JIS G 3101:1995	64, 71
SMA490AW	JIS G 3114:1998	90, 95	St 33	DIN 1615:1984	165, 176
SMA490BP	JIS G 3114:1998	91, 95	St 35.8	DIN 28180:1985	207, 210
SMA490BW	JIS G 3114:1998	91, 95	St 37.0	DIN 28180:1985	207, 210
SMA490CP	JIS G 3114:1998	91, 95	St 37.0	DIN 28181:1985	207, 210
SMA490CW	JIS G 3114:1998	91, 95	St 37.4	DIN 1630:1984	207, 210
SMA570P	JIS G 3114:1998	93, 96	St 37.8	DIN 28181:1985	207, 210
SMA570W	JIS G 3114:1998	93, 96	St 44.4	DIN 1630:1984	208, 211
SMn 420	JIS G 4053:2003	34	St 52.4	DIN 1630:1984	209, 212
SMn 433	JIS G 4053:2003	34	STAM 290 GA	JIS G 3472:1988	165, 176
SMn 438	JIS G 4053:2003	34	STAM 290 GB	JIS G 3472:1988	165, 176
SMn 443	JIS G 4053:2003	34	STAM 340 G	JIS G 3472:1988	166, 177
SMnC 420	JIS G 4053:2003	34	STAM 390 G	JIS G 3472:1988	168, 178
SMnC 443	JIS G 4053:2003	34	STAM 440 G	JIS G 3472:1988	170, 180
SN400A	JIS G 3136:1994	55, 68	STAM 440 H	JIS G 3472:1988	170, 180
SN400B	JIS G 3136:1994	55, 68	STAM 470 G	JIS G 3472:1988	171, 181
SN400C	JIS G 3136:1994	55, 68	STAM 470 H	JIS G 3472:1988	171, 181
SN490B	JIS G 3136:1994	60, 70	STAM 500 G	JIS G 3472:1988	172, 182
SN490C	JIS G 3136:1994	60, 70	STAM 500 H	JIS G 3472:1988	172, 182
SNC 236	JIS G 4053:2003	•	STAM 540 H	JIS G 3472:1988	173, 183
		44	STB 340	JIS G 3461:1988	206, 210
SNC 415	JIS G 4053:2003	44	STB 410	JIS G 3461:1988	208, 211
SNC 631	JIS G 4053:2003	44	STB 510	JIS G 3461:1988	200, 211
SNC 815	JIS G 4053:2003	38	STBA 12	JIS G 3462:1988	214, 215
SNC 836	JIS G 4053:2003	44			-
SNCM 220	JIS G 4053:2003	39	STBA 13	JIS G 3462:1988	214, 215
SNCM 240	JIS G 4053:2003	39	STBA 20	JIS G 3462:1988	216
SNCM 415	JIS G 4053:2003	39	STBA 22	JIS G 3462:1988	217, 218
SNCM 420	JIS G 4053:2003	39	STBA 23	JIS G 3462:1988	219
SNCM 431	JIS G 4053:2003	44	STBA 24	JIS G 3462:1988	220
	JIS G 4103:1979	44	STBA 25	JIS G 3462:1988	221
SNCM 439	JIS G 4053:2003	39	STBA 26	JIS G 3462:1988	222
SNCM 447	JIS G 4053:2003	44	STBL 380	JIS G 3464:1988	196, 198
	JIS G 4103:1979	44	STBL 450	JIS G 3464:1988	199, 200
SNCM 616	JIS G 4053:2003	44	STBL 690	JIS G 3464:1988	199, 201
	JIS G 4103:1979	44	STC 370	JIS G 3473:1988	167, 178
SNCM 625	JIS G 4053:2003	44	STC 440	JIS G 3473:1988	170, 180
	JIS G 4103:1979	44	STC 510A	JIS G 3473:1988	172, 182
SNCM 630	JIS G 4053:2003	44	STC 510B	JIS G 3473:1988	172, 182
	JIS G 4103:1979	44	STC 540	JIS G 3473:1988	173, 182
SNCM 815	JIS G 4053:2003	44	STC 590A	JIS G 3473:1988	174, 183
	JIS G 4103:1979	44	STC 590B	JIS G 3473:1988	174, 183
SPA-C	JIS G 3125:1987	90, 95	STF 410	JIS G 3467:1988	208, 211
SPA-H	JIS G 3125:1987	90, 95	STFA 12	JIS G 3467:1988	214, 215
SPV235	JIS G 3115:2000	104, 109	STFA 22	JIS G 3467:1988	217, 218
SPV315	JIS G 3115:2000	106, 111	STFA 23	JIS G 3467:1988	219
SPV410	JIS G 3115:2000	108, 112	STFA 24	JIS G 3467:1988	220
SPV450	JIS G 3115:2000	108, 112	STFA 25	JIS G 3467:1988	221
SPV490	JIS G 3115:2000	155	STFA 26	JIS G 3467:1988	222
SQV 1 A	JIS G 3120:1987	118, 120	STK290	JIS G 3444:1994	165, 176
SQV 1 B	JIS G 3120:1987	118, 120	STK400	JIS G 3444:1994	168, 179
SQV 2 A	JIS G 3120:1987	137, 138	STK490	JIS G 3444:1994	172, 181
SQV 2 B	JIS G 3120:1987	137, 138	STK500	JIS G 3444:1994	172, 182
SQV 3 A	JIS G 3120:1987	139, 140	STK540	JIS G 3444:1994	173, 182
SQV 3 B	JIS G 3120:1987	139, 140	STKM 11 A	JIS G 3445:1988	165, 176
			STKM 12 A	JIS G 3445:1988	166, 177
SS330	JIS G 3101:1995	50, 66	CITAM IZ /	0.0 0 0440.1000	.50, 177

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
STKM 12 B	JIS G 3445:1988	168, 178	SUH4	JIS G 4311:1991	415
STKM 12 C	JIS G 3445:1988	171, 181	SUH409	JIS G 4312:1991	414
STKM 13 A	JIS G 3445:1988	167, 178	SUH409L	JIS G 4312:1991	368, 370
STKM 13 B	JIS G 3445:1988	170, 180	SUH446	JIS G 4311:1991	398, 399
STKM 13 C	JIS G 3445:1988	172, 182		JIS G 4312:1991	369, 371
STKM 14 A	JIS G 3445:1988	169, 179	SUH600	JIS G 4311:1991	415
STKM 14 B	JIS G 3445:1988	172, 182	SUH616	JIS G 4311:1991	415
STKM 14 C	JIS G 3445:1988	173, 183	SUH660	JIS G 4311:1991	415
STKM 15 A	JIS G 3445:1988	171, 181		JIS G 4312:1991	414
STKM 15 C	JIS G 3445:1988	174, 183	SUH661	JIS G 4311:1991	415
STKM 16 A	JIS G 3445:1988	172, 182		JIS G 4312:1991	414
STKM 16 C	JIS G 3445:1988	174, 184	SUJ 1	JIS G 4805:1999	439
STKM 17 A	JIS G 3445:1988	173, 183	SUJ 2	JIS G 4805:1999	435
STKM 17 C	JIS G 3445:1988	175, 184	SUJ 3	JIS G 4805:1999	435
STKM 18 A	JIS G 3445:1988	170, 180	SUJ 4	JIS G 4805:1999	439
STKM 18 B	JIS G 3445:1988	172, 181	SUJ 5	JIS G 4805:1999	439
STKM 18 C	JIS G 3445:1988	172, 182	SUM 11	JIS G 4804:1999	420
STKM 19 A	JIS G 3445:1988	172, 181	SUM 12	JIS G 4804:1999	420
STKM 19 C	JIS G 3445:1988	173, 183	SUM 21	JIS G 4804:1999	422
STKM 20 A	JIS G 3445:1988	173, 182	SUM 22	JIS G 4804:1999	422
STKT 540	JIS G 3474:1995	173, 183	SUM 22 L	JIS G 4804:1999	424
STKT 590	JIS G 3474:1995	174, 183	SUM 23	JIS G 4804:1999	422
STPA 12	JIS G 3458:1988	214, 215	SUM 23 L	JIS G 4804:1999	424
STPA 20	JIS G 3458:1988	216	SUM 24 L	JIS G 4804:1999	424
STPA 22	JIS G 3458:1988	217, 218	SUM 25	JIS G 4804:1999	422
STPA 23	JIS G 3458:1988	219	SUM 31	JIS G 4804:1999	420
STPA 24	JIS G 3458:1988	220	SUM 31 L	JIS G 4804:1999	423
STPA 25	JIS G 3458:1988	221	SUM 32	JIS G 4804:1999	420
STPA 26	JIS G 3458:1988	222	SUM 41	JIS G 4804:1999	420
STPG 370	JIS G 3454:1988	202, 204	SUM 42	JIS G 4804:1999	421
STPG 410	JIS G 3454:1988	203, 205	SUM 43	JIS G 4804:1999	421
STPL 380	JIS G 3460:1988	196, 198	SUP 10	JIS G 4801:1984	428
STPL 450	JIS G 3460:1988	197, 198,	SUP 11 A	JIS G 4801:1984	428
		199, 200	SUP 12	JIS G 4801:1984	427
STPL 690	JIS G 3460:1988	197, 198,	SUP 13	JIS G 4801:1984	428
OTDT 070	WO O 0450 4000	199, 201	SUP 3	JIS G 4801:1984	425
STPT 370	JIS G 3456:1988	207, 210	SUP 6	JIS G 4801:1984	427
STPT 410	JIS G 3456:1988	208, 211	SUP 7	JIS G 4801:1984	427
STPT 480	JIS G 3456:1988	209, 212	SUP 9	JIS G 4801:1984	427
STPY 400	JIS G 3457:1988	203, 205	SUP 9 A	JIS G 4801:1984	427
STS 370	JIS G 3455:1988	207, 210	SUP10-CSP	JIS G 4802:1999	428
STS 410	JIS G 3455:1988	208, 211	SUS 301-CSP	JIS G 4313:1996	429
STS 480	JIS G 3455:1988	209, 212	SUS 304 TF	JIS G 3467:1988	225, 234
SUH1	JIS G 4311:1991	415	SUS 304-CSP	JIS G 4313:1996	429
SUH11	JIS G 4311:1991	415	SUS 304H TF	JIS G 3467:1988	227, 236
SUH21	JIS G 4312:1991	414			260
SUH3	JIS G 4311:1991	415	SUS 309 TF	JIS G 3467:1988 JIS G 3214:1991	299, 303
SUH309	JIS G 4311:1991	402, 408	SUS 316		299, 303
	JIS G 4312:1991	373, 381	SUS 316 TF	JIS G 3467:1988	-
SUH31	JIS G 4311:1991	415	SUS 316H	JIS G 3214:1991	300, 305
SUH310	JIS G 4311:1991	402, 408	SUS 316H TF	JIS G 3467:1988	230, 240
	JIS G 4312:1991	374, 382	SUS 317	JIS G 3214:1991	300, 305
SUH330	JIS G 4311:1991	415	SUS 317J1	JIS G 4303:1998	402, 408
	JIS G 4312:1991	414	SUS 321 TF	JIS G 3467:1988	231, 242
SUH35	JIS G 4311:1991	415	SUS 321H TF	JIS G 3467:1988	232, 243
SUH36	JIS G 4311:1991	415	SUS 329J3L	JIS G 4303:1998	412
SUH37	JIS G 4311:1991	415	SUS 347 TF	JIS G 3467:1988	232, 243
SUH38	JIS G 4311:1991	415	SUS 347H TF	JIS G 3467:1988	233, 244

588 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SUS 420J2-CSP	JIS G 4313:1996	429	SUS304J1	JIS G 4304:1999	413
SUS 631-CSP	JIS G 4313:1996	429		JIS G 4305:1999	414
SUS 632J1-CSP	JIS G 4313:1996	437	SUS304J2	JIS G 4304:1999	413
SUS F 304	JIS G 3214:1991	298, 302		JIS G 4305:1999	414
SUS F 304H	JIS G 3214:1991	298, 302	SUS304J3	JIS G 4303:1998	415
SUS F 304L	JIS G 3214:1991	298, 302		JIS G 4318:1998	415
SUS F 304LN	JIS G 3214:1991	298, 303	SUS304L	JIS G 3468:1994	226, 235
SUS F 304N	JIS G 3214:1991	298, 302		JIS G 4303:1998	400, 404
SUS F 310	JIS G 3214:1991	299, 303		JIS G 4304:1999	373, 380
SUS F 316L	JIS G 3214:1991	299, 304		JIS G 4305:1999	373, 380
SUS F 316LN	JIS G 3214:1991	300, 305		JIS G 4318:1998	400, 404
SUS F 316N	JIS G 3214:1991	299, 304	SUS304LN	JIS G 4303:1998	400, 405
SUS F 317L	JIS G 3214:1991	300, 305		JIS G 4304:1999	373, 381
SUS F 321	JIS G 3214:1991	300, 306		JIS G 4305:1999	373, 381
SUS F 321H	JIS G 3214:1991	300, 306	SUS304LTB	JIS G 3463:1994	226, 235
SUS F 347	JIS G 3214:1991	301, 306	SUS304LTP	JIS G 3459:1997	226, 235
SUS F 347H	JIS G 3214:1991	301, 306	SUS304N1	JIS G 4303:1998	400, 404
SUS F 410-A	JIS G 3214:1991	295, 296		JIS G 4304:1999	373, 381
SUS F 410-B	JIS G 3214:1991	295, 296		JIS G 4305:1999	373, 381
SUS F 410-C	JIS G 3214:1991	295, 296	SUS304N2	JIS G 4303:1998	400, 405
SUS F 410-D	JIS G 3214:1991	295, 296		JIS G 4304:1999	413
SUS F 630	JIS G 3214:1991	307, 308		JIS G 4305:1999	414
SUS F 6B	JIS G 3214:1991	295, 296	SUS304TB	JIS G 3463:1994	225, 234
SUS F 6NM	JIS G 3214:1991	295, 296	SUS304TKA	JIS G 3446:1994	190, 193
SUS201	JIS G 4303:1998	400, 403	SUS304TKC	JIS G 3446:1994	190, 193
SUS202	JIS G 4303:1998	400, 403	SUS304TP	JIS G 3459:1997	225, 234
SUS301	JIS G 4303:1998	400, 403	SUS305	JIS G 4303:1998	401, 405
	JIS G 4304:1999	372, 378		JIS G 4304:1999	373, 381
	JIS G 4305:1999	372, 378		JIS G 4305:1999	373, 381
SUS301J1	JIS G 4304:1999	372, 378		JIS G 4318:1998	401, 405
	JIS G 4305:1999	372, 378	SUS305J1	JIS G 4318:1998	415
SUS301L	JIS G 4304:1999	372, 379	SUS309S	JIS G 3468:1994	227, 236
	JIS G 4305:1999	372, 379		JIS G 4303:1998	401, 405
SUS302	JIS G 4303:1998	400, 403		JIS G 4304:1999	374, 382
	JIS G 4304:1999	372, 379		JIS G 4305:1999	374, 382
	JIS G 4305:1999	372, 379		JIS G 4311:1991	401, 405
	JIS G 4318:1998	400, 403		JIS G 4312:1991	374, 382
SUS302B	JIS G 4304:1999	372, 380		JIS G 4318:1998	401, 405
	JIS G 4305:1999	372, 380	SUS309STB	JIS G 3463:1994	227, 236
	JIS G 4312:1991	372, 380	SUS309STP	JIS G 3459:1997	227, 236
SUS303	JIS G 4303:1998	400, 403	SUS309TB	JIS G 3463:1994	227, 237
	JIS G 4304:1999	413	SUS309TP	JIS G 3459:1997	227, 237
	JIS G 4318:1998	400, 403	SUS310S	JIS G 3468:1994	227, 237
SUS303Cu	JIS G 4303:1998	415		JIS G 4303:1998	401, 405
	JIS G 4318:1998	415		JIS G 4304:1999	374, 382
SUS303Se	JIS G 4303:1998	400, 403		JIS G 4305:1999	374, 382
	JIS G 4318:1998	400, 403		JIS G 4311:1991	401, 405
SUS304	JIS G 3468:1994	225, 234		JIS G 4312:1991	374, 382
	JIS G 4303:1998	400, 404		JIS G 4318:1998	401, 405
	JIS G 4304:1999	373, 380	SUS310STB	JIS G 3463:1994	227, 237
	JIS G 4305:1999	373, 380	SUS310STP	JIS G 3459:1997	227, 237
	JIS G 4311:1991	400, 404	SUS310TB	JIS G 3463:1994	228, 237
	JIS G 4312:1991	373, 380	SUS310TF	JIS G 3467:1988	228, 237
	JIS G 4318:1998	400, 404	SUS310TP	JIS G 3459:1997	263
SUS304HTB	JIS G 3463:1994	227, 236	SUS315J1	JIS G 4304:1999	413
SUS304HTP	JIS G 3459:1997	227, 236		JIS G 4305:1999	414
	·	, ====			•

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SUS315J2	JIS G 4304:1999	413	SUS317L (continued)	JIS G 4304:1999	375, 384
	JIS G 4305:1999	414		JIS G 4305:1999	375, 384
SUS316	JIS G 3468:1994	228, 238	SUS317LN	JIS G 4303:1998	415
	JIS G 4303:1998	401, 406		JIS G 4304:1999	375, 385
	JIS G 4304:1999	374, 383		JIS G 4305:1999	375, 385
	JIS G 4305:1999	374, 383	SUS317LTB	JIS G 3463:1994	231, 241
	JIS G 4311:1991	401, 406	SUS317LTP	JIS G 3459:1997	231, 241
	JIS G 4312:1991	374, 383	SUS317TB	JIS G 3463:1994	231, 241
	JIS G 4318:1998	401, 406	SUS317TP	JIS G 3459:1997	231, 241
SUS316F	JIS G 4303:1998	415	SUS321	JIS G 3468:1994	231, 242
	JIS G 4318:1998	415		JIS G 4303:1998	402, 408
SUS316HTB	JIS G 3463:1994	230, 240		JIS G 4304:1999	376, 386
SUS316HTP	JIS G 3459:1997	230, 240		JIS G 4305:1999	376, 386
SUS316J1	JIS G 4303:1998	415		JIS G 4311:1991	402, 408
	JIS G 4304:1999	413		JIS G 4312:1991	376, 386
	JIS G 4305:1999	414		JIS G 4318:1998	402, 408
SUS316J1L	JIS G 4303:1998	415	SUS321HTB	JIS G 3463:1994	232, 243
	JIS G 4304:1999	413	SUS321HTP	JIS G 3459:1997	232, 243
	JIS G 4305:1999	414	SUS321J1TP	JIS G 3459:1997	263
SUS316L	JIS G 3468:1994	229, 239	SUS321J3LTP	JIS G 3459:1997	263
	JIS G 4303:1998	401, 406	SUS321J4LTP	JIS G 3459:1997	263
	JIS G 4304:1999	374, 383	SUS321TB	JIS G 3463:1994	231, 242
	JIS G 4305:1999	374, 383	SUS321TKA	JIS G 3446:1994	192, 195
	JIS G 4318:1998	401, 406	SUS321TP	JIS G 3459:1997	231, 242
SUS316LN	JIS G 4303:1998	401, 407	SUS329J1	JIS G 3468:1994	263
	JIS G 4304:1999	375, 384		JIS G 4303:1998	415
	JIS G 4305:1999	375, 384		JIS G 4304:1999	413
SUS316LTB	JIS G 3463:1994	229, 239		JIS G 4305:1999	414
SUS316LTP	JIS G 3459:1997	229, 239		JIS G 4318:1998	415
SUS316N	JIS G 4303:1998	401, 407	SUS329J1TB	JIS G 3463:1994	263
	JIS G 4304:1999	374, 384	SUS329J3L	JIS G 4304:1999	392, 393
	JIS G 4305:1999	374, 384		JIS G 4305:1999	392, 393
SUS316TB	JIS G 3463:1994	228, 238	SUS329J3LTB	JIS G 3463:1994	232, 243
SUS316Ti	JIS G 4303:1998	402, 407	SUS329J4L	JIS G 4303:1998	415
	JIS G 4304:1999	375, 384		JIS G 4304:1999	413
	JIS G 4305:1999	375, 384		JIS G 4305:1999	414
	JIS G 4311:1991	402, 407	SUS329J4LTB	JIS G 3463:1994	232, 243
	JIS G 4312:1991	375, 384	SUS347	JIS G 3468:1994	232, 243
SUS316TiTB	JIS G 3463:1994	230, 241		JIS G 4303:1998	402, 408
SUS316TiTP	JIS G 3459:1997	230, 241		JIS G 4304:1999	376, 386
SUS316TKA	JIS G 3446:1994	191, 194		JIS G 4305:1999	376, 386
SUS316TKC	JIS G 3446:1994	191, 194		JIS G 4311:1991	402, 408
SUS316TP	JIS G 3459:1997	228, 238		JIS G 4312:1991	376, 386
SUS317	JIS G 3468:1994	231, 241		JIS G 4318:1998	402, 408
	JIS G 4303:1998	402, 407	SUS347HTB	JIS G 3463:1994	233, 244
	JIS G 4304:1999	413	SUS347HTP	JIS G 3459:1997	233, 244
	JIS G 4305:1999	414	SUS347TB	JIS G 3463:1994	232, 243
	JIS G 4311:1991	402, 407	SUS347TKA	JIS G 3446:1994	192, 195
	JIS G 4312:1991	414	SUS347TP	JIS G 3459:1997	232, 243
SUS317J1	JIS G 4304:1999	375, 385	SUS403	JIS G 4303:1998	394, 396
	JIS G 4305:1999	375, 385		JIS G 4304:1999	366, 367
SUS317J2	JIS G 4304:1999	413		JIS G 4305:1999	366, 367
	JIS G 4305:1999	414		JIS G 4311:1991	394, 396
SUS317J3L	JIS G 4304:1999	413		JIS G 4312:1991	366, 367
	JIS G 4305:1999	414		JIS G 4318:1998	394, 396
SUS317L	JIS G 3468:1994	231, 241	SUS405	JIS G 4303:1998	398, 399
	JIS G 4303:1998	402, 408	-	JIS G 4304:1999	368, 370
	2.0 0.000.1000	.52, .56		3.3 G +00+.1000	000, 070

590 Steel Grade/Name Index

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SUS405 (continued)	JIS G 4305:1999	368, 370	SUS430J1L	JIS G 4304:1999	413
	JIS G 4311:1991	398, 399		JIS G 4305:1999	414
	JIS G 4312:1991	368, 370		JIS G 4312:1991	414
SUS405TB	JIS G 3463:1994	263	SUS430J1LTB	JIS G 3463:1994	263
SUS405TP	JIS G 3459:1997	263	SUS430J1LTP	JIS G 3459:1997	263
SUS409LTB	JIS G 3463:1994	263	SUS430LX	JIS G 4304:1999	368, 370
SUS409LTP	JIS G 3459:1997	263		JIS G 4305:1999	368, 370
SUS409TB	JIS G 3463:1994	223, 224	SUS430LXTB	JIS G 3463:1994	223, 224
SUS410	JIS G 4303:1998	394, 396	SUS430LXTP	JIS G 3459:1997	263
	JIS G 4304:1999	366, 367	SUS430TB	JIS G 3463:1994	223, 224
	JIS G 4305:1999	366, 367	SUS430TKA	JIS G 3446:1994	188, 189
	JIS G 4311:1991	394, 396	SUS430TKC	JIS G 3446:1994	188, 189
	JIS G 4312:1991	414	SUS430TP	JIS G 3459:1997	263
	JIS G 4318:1998	394, 396	SUS431	JIS G 4303:1998	394, 397
SUS410F2	JIS G 4303:1998	415		JIS G 4311:1991	394, 397
	JIS G 4318:1998	415	SUS434	JIS G 4303:1998	398, 399
SUS410J1	JIS G 4303:1998	415		JIS G 4304:1999	368, 370
	JIS G 4311:1991	415		JIS G 4305:1999	368, 370
SUS410L	JIS G 4303:1998	415	SUS436J1L	JIS G 4304:1999	413
	JIS G 4304:1999	366, 367		JIS G 4305:1999	414
	JIS G 4305:1999	366, 367		JIS G 4312:1991	414
	JIS G 4311:1991	415	SUS436L	JIS G 4304:1999	413
	JIS G 4312:1991	414		JIS G 4305:1999	414
SUS410S	JIS G 4304:1999	366, 367	SUS436LTB	JIS G 3463:1994	263
	JIS G 4305:1999	366, 367	SUS436LTP	JIS G 3459:1997	263
SUS410TB	JIS G 3463:1994	223, 224	SUS440A	JIS G 4303:1998	394, 397
SUS410TiTB	JIS G 3463:1994	263		JIS G 4304:1999	413
SUS410TKA	JIS G 3446:1994	188, 189		JIS G 4305:1999	414
SUS410TKC	JIS G 3446:1994	188, 189	SUS440B	JIS G 4303:1998	394, 397
SUS416	JIS G 4303:1998	394, 396	SUS440C	JIS G 4303:1998	395, 397
	JIS G 4318:1998	394, 396		JIS G 4318:1998	395, 397
SUS420F	JIS G 4303:1998	394, 397	SUS440F	JIS G 4303:1998	415
	JIS G 4318:1998	394, 397	SUS444	JIS G 4304:1999	369, 371
SUS420F2	JIS G 4303:1998	415		JIS G 4305:1999	369, 371
	JIS G 4318:1998	415	SUS444TB	JIS G 3463:1994	263
SUS420J1	JIS G 4303:1998	394, 396	SUS444TP	JIS G 3459:1997	263
	JIS G 4304:1999	366, 367	SUS445J1	JIS G 4304:1999	413
	JIS G 4305:1999	366, 367		JIS G 4305:1999	414
	JIS G 4318:1998	394, 396	SUS445J2	JIS G 4304:1999	413
SUS420J1TKA	JIS G 3446:1994	259		JIS G 4305:1999	414
SUS420J2	JIS G 4303:1998	394, 396	SUS447J1	JIS G 4303:1998	398, 399
	JIS G 4304:1999	366, 367		JIS G 4304:1999	413
	JIS G 4305:1999	366, 367		JIS G 4305:1999	414
	JIS G 4318:1998	394, 396	SUS630	JIS G 4303:1998	409, 410
SUS420J2TKA	JIS G 3446:1994	259		JIS G 4304:1999	387, 388
SUS429	JIS G 4304:1999	413		JIS G 4305:1999	387, 389
000 120	JIS G 4305:1999	414		JIS G 4311:1991	409, 410
SUS429J1	JIS G 4304:1999	413		JIS G 4312:1991	387, 389
000-12001	JIS G 4305:1999	414	SUS631	JIS G 4303:1998	409, 411
SUS430	JIS G 4303:1998	398, 399	000001	JIS G 4304:1999	387, 390
000400	JIS G 4304:1999			JIS G 4305:1999	387, 390
	JIS G 4305:1999	368, 370 368, 370		JIS G 4311:1991	409, 411
	JIS G 4305:1999 JIS G 4311:1991			JIS G 4311:1991 JIS G 4312:1991	
		398, 399 368, 370	21120361		387, 390
	JIS G 4312:1991	368, 370	SUS836L	JIS G 4303:1998	402, 408
CLIC420E	JIS G 4318:1998	398, 399		JIS G 4304:1999	375, 385
SUS430F	JIS G 4303:1998	398, 399	CLICOCCI TD	JIS G 4305:1999	375, 385
	JIS G 4318:1998	398, 399	SUS836LTB	JIS G 3463:1994	233, 245

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
SUS836LTP	JIS G 3459:1997	263	T5c	ASTM A 213/A 213M-03a	261
SUS890L	JIS G 4303:1998	402, 408	Т6	ASTM A 600-92a (1999)	438
	JIS G 4304:1999	375, 385	Т8	ASTM A 600-92a (1999)	438
	JIS G 4305:1999	375, 385		SAE J438-1970	438
SUS890LTB	JIS G 3463:1994	233, 245	Т9	ASTM A 213/A 213M-03a	222
SUS890LTP	JIS G 3459:1997	233, 245	T91	ASTM A 213/A 213M-03a	222
SUSXM151J1	JIS G 4312:1991	414	T911	ASTM A 213/A 213M-03a	261
SUSXM15J1	JIS G 4303:1998	415	T92	ASTM A 213/A 213M-03a	261
000/(W1001	JIS G 4304:1999	413	TP 304	ASTM A 632-02a	190, 193
	JIS G 4305:1999	414	TP 304L	ASTM A 632-02a	190, 193
	JIS G 4311:1991	415	55.2	ASTM A 778-01	190, 193
CHCVM15 I1TD			TP 310	ASTM A 632-02a	259
SUSXM15J1TB	JIS G 3463:1994	263	TP 316	ASTM A 632-02a	191, 194
SUSXM27	JIS G 4303:1998	398, 399	TP 316L	ASTM A 632-02a	191, 194
	JIS G 4304:1999	413	11 0102	ASTM A 778-01	191, 194
	JIS G 4305:1999	414	TP 316N	ASTM A 688/A 688M-03	262
SUSXM27TB	JIS G 3463:1994	223, 224	TP 317	ASTM A 632-02a	259
SUSXM7	JIS G 4303:1998	415			
	JIS G 4304:1999	413	TP 317L	ASTM A 778-01	259
	JIS G 4305:1999	414	TP 321	ASTM A 632-02a	192, 195
SUSXM8TB	JIS G 3463:1994	263		ASTM A 778-01	192, 195
T	ASTM A 514/A 514M-00a	82, 86	TP 347	ASTM A 632-02a	192, 195
	ASTM	153		ASTM A 778-01	192, 195
	A 517/A 517M-93 (1999)		TP 348	ASTM A 632-02a	259
T1	ASTM A 209/A 209M-03	214, 215	TP XM-27	ASTM A 803/A 803M-03	223, 224
	ASTM	214, 215	TP XM-29	ASTM A 688/A 688M-03	262
	A 250/A 250M-95 (2001)		TP XM-33	ASTM A 803/A 803M-03	262
	ASTM A 600-92a (1999)	431	TP201	ASTM A 213/A 213M-03a	261
	SAE J438-1970	431		ASTM A 249/A 249M-03	262
T11	ASTM A 213/A 213M-03a	219	TP202	ASTM A 213/A 213M-03a	261
	ASTM	219		ASTM A 249/A 249M-03	262
T10	A 250/A 250M-95 (2001)	017 010	TP304	ASTM A 213/A 213M-03a	225, 234
T12	ASTM A 213/A 213M-03a	217, 218		ASTM A 249/A 249M-03	225, 234
	ASTM A 250/A 250M-95 (2001)	217, 218		ASTM A 269-02a	190, 193
T122	ASTM A 213/A 213M-03a	261		ASTM A 312/A 312M-03	225, 234
T15	ASTM A 600-92a (1999)	431		ASTM A 376/A 376M-02a	225, 234
T17	ASTM A 213/A 213M-03a	261		ASTM A 409/A 409M-01	225, 234
T1a	ASTM A 209/A 209M-03	214, 215		ASTM A 688/A 688M-03	225, 234
Πα	ASTM A 200/A 200M 00	214, 215	TP304H	ASTM A 213/A 213M-03a	227, 236
	A 250/A 250M-95 (2001)	214, 213		ASTM A 249/A 249M-03	227, 236
T1b	ASTM A 209/A 209M-03	214, 215		ASTM A 312/A 312M-03	227, 236
	ASTM	214, 215		ASTM A 376/A 376M-02a	227, 236
	A 250/A 250M-95 (2001)	, -	TP304L	ASTM A 213/A 213M-03a	226, 235
T2	ASTM A 213/A 213M-03a	216	11 00 12	ASTM A 249/A 249M-03	226, 235
	ASTM	216		ASTM A 269-02a	190, 193
	A 250/A 250M-95 (2001)			ASTM A 312/A 312M-03	226, 235
	ASTM A 600-92a (1999)	438		ASTM A 409/A 409M-01	226, 235
	SAE J438-1970	438		ASTM A 409/A 409M-01 ASTM A 688/A 688M-03	226, 235
T21	ASTM A 213/A 213M-03a	261	TP304LN		
T22	ASTM A 213/A 213M-03a	220	1F304LN	ASTM A 213/A 213M-03a	226, 235
	ASTM	220		ASTM A 249/A 249M-03	226, 235
T 00	A 250/A 250M-95 (2001)			ASTM A 269-02a	190, 193
T23	ASTM A 213/A 213M-03a	261		ASTM A 312/A 312M-03	262
T24	ASTM A 213/A 213M-03a	261		ASTM A 376/A 376M-02a	226, 235
T4	ASTM A 600-92a (1999)	431	TD00 444	ASTM A 688/A 688M-03	226, 235
	SAE J438-1970	431	TP304N	ASTM A 213/A 213M-03a	261
T5	ASTM A 213/A 213M-03a	221		ASTM A 312/A 312M-03	262
	ASTM A 600-92a (1999)	431	TP305	ASTM A 249/A 249M-03	262
	SAE J438-1970	431	TP309Cb	ASTM A 213/A 213M-03a	261
T5b	ASTM A 213/A 213M-03a	221		ASTM A 249/A 249M-03	262

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
TP309Cb (continued)	ASTM A 312/A 312M-03	262	TP317 (continued)	ASTM A 409/A 409M-01	231, 241
	ASTM A 409/A 409M-01	262	TP317L	ASTM A 213/A 213M-03a	231, 241
TP309H	ASTM A 213/A 213M-03a	227, 237		ASTM A 249/A 249M-03	231, 241
	ASTM A 249/A 249M-03	227, 237		ASTM A 312/A 312M-03	231, 241
	ASTM A 312/A 312M-03	262	TP321	ASTM A 213/A 213M-03a	231, 242
TP309HCb	ASTM A 213/A 213M-03a	261		ASTM A 249/A 249M-03	231, 242
	ASTM A 249/A 249M-03	262		ASTM A 269-02a	192, 195
	ASTM A 312/A 312M-03	262		ASTM A 312/A 312M-03	231, 242
TP309S	ASTM A 213/A 213M-03a	227, 236		ASTM A 376/A 376M-02a	231, 242
	ASTM A 249/A 249M-03	227, 236		ASTM A 409/A 409M-01	231, 242
	ASTM A 312/A 312M-03	227, 236	TP321H	ASTM A 213/A 213M-03a	232, 243
	ASTM A 409/A 409M-01	262		ASTM A 249/A 249M-03	232, 243
TP310Cb	ASTM A 213/A 213M-03a	261		ASTM A 312/A 312M-03	232, 243
	ASTM A 249/A 249M-03	262		ASTM A 376/A 376M-02a	232, 243
	ASTM A 312/A 312M-03	262	TP347	ASTM A 213/A 213M-03a	232, 243
	ASTM A 409/A 409M-01	262		ASTM A 249/A 249M-03	232, 243
TP310H	ASTM A 213/A 213M-03a	228, 237		ASTM A 269-02a	192, 195
	ASTM A 249/A 249M-03	262		ASTM A 312/A 312M-03	232, 243
	ASTM A 312/A 312M-03	262		ASTM A 376/A 376M-02a	232, 243
TP310HCb	ASTM A 213/A 213M-03a	261		ASTM A 409/A 409M-01	232, 243
	ASTM A 249/A 249M-03	262	TP347H	ASTM A 213/A 213M-03a	233, 244
	ASTM A 312/A 312M-03	262		ASTM A 249/A 249M-03	233, 244
TP310HCbN	ASTM A 213/A 213M-03a	261		ASTM A 312/A 312M-03	233, 244
TP310S	ASTM A 213/A 213M-03a	227, 237		ASTM A 376/A 376M-02a	233, 244
11 3103	ASTM A 249/A 249M-03	227, 237	TP347HFG	ASTM A 213/A 213M-03a	261
	ASTM A 312/A 312M-03	227, 237	TP347LN	ASTM A 213/A 213M-03a	261
		262 262	1F34/LN		
TD016	ASTM A 409/A 409M-01		TD240	ASTM A 312/A 312M-03	262
TP316	ASTM A 213/A 213M-03a	228, 238	TP348	ASTM A 213/A 213M-03a	261
	ASTM A 249/A 249M-03	228, 238		ASTM A 249/A 249M-03	262
	ASTM A 269-02a	191, 194		ASTM A 269-02a	259
	ASTM A 312/A 312M-03	228, 238		ASTM A 312/A 312M-03	262
	ASTM A 376/A 376M-02a	228, 238		ASTM A 376/A 376M-02a	262
	ASTM A 409/A 409M-01	228, 238	TD0.401.1	ASTM A 409/A 409M-01	262
TDO4011	ASTM A 688/A 688M-03	228, 238	TP348H	ASTM A 213/A 213M-03a	261
TP316H	ASTM A 213/A 213M-03a	230, 240		ASTM A 249/A 249M-03	262
	ASTM A 249/A 249M-03	230, 240		ASTM A 312/A 312M-03	262
	ASTM A 312/A 312M-03	230, 240	TP403Ti	ASTM A 268/A 268M-03	259
	ASTM A 376/A 376M-02a	230, 240	TP405	ASTM A 268/A 268M-03	188, 189
TP316L	ASTM A 213/A 213M-03a	229, 239	TP409	ASTM A 268/A 268M-03	188, 189,
	ASTM A 249/A 249M-03	229, 239		ACTM A 902/A 902M 02	223, 224
	ASTM A 269-02a	191, 194	TD410	ASTM A 803/A 803M-03	223, 224
	ASTM A 312/A 312M-03	229, 239	TP410	ASTM A 268/A 268M-03	188, 189, 223, 224
	ASTM A 409/A 409M-01	229, 239	TP429	ASTM A 268/A 268M-03	259
	ASTM A 688/A 688M-03	229, 239	TP430	ASTM A 268/A 268M-03	188, 189,
TP316LN	ASTM A 213/A 213M-03a	230, 240	11 100	7.0 TM 7.1 200/7.1 200M 00	223, 224
	ASTM A 249/A 249M-03	230, 240	TP439	ASTM A 268/A 268M-03	188, 189
	ASTM A 269-02a	191, 194		ASTM A 803/A 803M-03	262
	ASTM A 312/A 312M-03	262	TP443	ASTM A 268/A 268M-03	259
	ASTM A 376/A 376M-02a	230, 240	TP446-1	ASTM A 268/A 268M-03	259
	ASTM A 688/A 688M-03	230, 240	TP446-2	ASTM A 268/A 268M-03	259
TP316N	ASTM A 213/A 213M-03a	261	TP468	ASTM A 268/A 268M-03	259
	ASTM A 249/A 249M-03	262	TPXM-10	ASTM A 269-02a	259
	ASTM A 312/A 312M-03	262		ASTM A 312/A 312M-03	262
	ASTM A 376/A 376M-02a	262	TPXM-11	ASTM A 312/A 312W-03	259
TP317	ASTM A 213/A 213M-03a	231, 241	II VIAL II	ASTM A 312/A 312M-03	262
* : :	ASTM A 249/A 249M-03	231, 241	TPXM-15	ASTM A 312/A 312M-03 ASTM A 249/A 249M-03	262
	ASTM A 269-02a	259	II VINI-19		
	ASTM A 312/A 312M-03	231, 241		ASTM A 269-02a	259
	7.0 TW A 012/A 012W-00	201, 241		ASTM A 312/A 312M-03	262

TPXM-19	Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
ASTM A 512/A 312M-03	TPXM-19	ASTM A 249/A 249M-03	262	TS Z 2 CND 17-12	AFNOR NF A 49-247:1981	229, 239
ASTM A 512/A 312M-03 262 TS Z 6 CN 18-09 AFNOR IN F A 49-247:1981 252, 234 TPXM-29 ASTM A 2680-20a 599 TS Z 6 CN D 17-11 AFNOR IN F A 49-247:1981 282, 238 ASTM A 2680-20a 262 TS Z 6 CN D 17-11 AFNOR IN F A 49-247:1981 191.194		ASTM A 269-02a	259	TS Z 2 CND 19-15	AFNOR NF A 49-247:1981	
TPXM-27		ASTM A 312/A 312M-03		TS Z 6 CN 18-09	AFNOR NF A 49-247:1981	225, 234
ASTM A 269 02a	TPXM-27	ASTM A 268/A 268M-03	259		AFNOR NF A 49-647:1979	
ASTM A 312/A 312/A0 312/A0 32	TPXM-29	ASTM A 269-02a	259	TS Z 6 CND 17-11	AFNOR NF A 49-247:1981	228, 238
ASTM A 312A 312BA03		ASTM A 249/A 249M-03	262		AFNOR NF A 49-647:1979	191, 194
TS 1		ASTM A 312/A 312M-03	262	TS Z 6 CNT 18-10	AFNOR NF A 49-247:1981	
TS 1 ISO 2804-II:1975 206, 210 TTS:1 SN DIN 28180:1985 206, 207 TS 10 ISO 2804-II:1975 208, 211 TU 10 CD 5-05 AFNOR NF A 49-220:1990 212 TS 13 ISO 2804-II:1975 209, 212 TU 10 CD 5-05 AFNOR NF A 49-220:1990 220 TS 14 ISO 2804-II:1975 209, 212 TU 10 CD 5-05 AFNOR NF A 49-220:1990 217, 218 TS 15 IB ISO 2804-II:1975 209, 212 TU 15 CD 2-05 AFNOR NF A 49-220:1990 212 TS 26 ISO 2804-II:1975 209, 212 TU 15 CD 2-05 AFNOR NF A 49-220:1990 212 TS 26 ISO 2804-II:1975 206, 210 TU 37 C AFNOR NF A 49-220:1990 207, 210 TS 28 ISO 2804-II:1975 213 TU 42 C AFNOR NF A 49-220:1990 209, 212 TS 34 ISO 2804-II:1975 216 TU 21 CND 25 22 AZ AFNOR NF A 49-220:1990 209, 212 TS 34 ISO 2804-II:1975 216 TU 21 CND 25 22 AZ AFNOR NF A 49-217:1987 228, 237 TS 37-R ISO 2804-II:1975 216 T	TPXM-33	ASTM A 268/A 268M-03	259	TS Z 8 C 17	AFNOR NF A 49-647:1979	188, 189
TS 10	TS 1	ISO 2604-II:1975	206, 210	TTSt 35 N	DIN 28180:1985	
TS 13 SO 2804-11:1975 209, 212		ISO 2937:1974	166, 177			210
TS 13	TS 10	ISO 2604-II:1975	208, 211			
TS 15 SO 2604 11975 209, 212 TU 13 CD 4-04 AFNOR NF A 49-220-1990 216 TS 18 SO 2604 11975 209, 212 TU 15 CD 2-05 AFNOR NF A 49-220-1990 216 SO 2393-1974 72, 181 TU 15 D 3 AFNOR NF A 49-220-1990 209, 212 TU 15 D 3 AFNOR NF A 49-217-1987 228, 237 TU 15 D 200 AFNOR NF A 49-217-1987 229, 239 TU 200	TS 13	ISO 2604-II:1975				
TS 15	TS 14	ISO 2604-II:1975	209, 212			
TS 18 ISO 2804-II:1975 209, 212 TU 15 D 2-05 AFNORN NF A 49-220:1990 218 TS 2 ISO 2937:1974 172, 181 TU 15 D 3 AFNORN NF A 49-220:1990 207, 210 TS 2 ISO 2604-II:1975 206, 210 TU 42 C AFNORN NF A 49-220:1990 209, 212 TS 28 ISO 2604-II:1975 213 TU 48 C AFNORN NF A 49-220:1990 209, 212 TS 33 ISO 2604-II:1975 216 TU 52 C AFNORN NF A 49-220:1990 209, 212 TS 34 ISO 2604-II:1975 216 TU Z 1 CND 25 22 AZ AFNORN NF A 49-221:1997 228, 237 TS 37 ISO 2604-II:1975 221 TU Z 1 CND 18 10.5 AFNORN NF A 49-217:1987 228, 237 TS 37-a (NE) AFNOR NF A 49-141:1978 167 TU Z 1 NCDU 25 20 04 AFNOR NF A 49-217:1987 228, 237 TS 38 ISO 2604-II:1975 222 TU Z 1 NCDU 31 27 03 AFNOR NF A 49-217:1987 263 TS 39-a (NE) ISO 2604-II:1975 227, 236 TU Z 2 CN 18 10 AZ AFNOR NF A 49-217:1987 223, 224 TS 49 ISO 2604-II:1975	TS 15	ISO 2604-II:1975				
ISO 2837:1974 172, 181 TU 15 D 3	TS 18	ISO 2604-II:1975				
TS 2		ISO 2937:1974				
TS 26	TS 2					
TS 32 ISO 2604-II:1975 217, 218 TU 52 C AFNOR N F A 49-22:1990 209, 212 TS 33 ISO 2604-II:1975 220 TU 21 CND 25:22 AZ AFNOR N F A 49-217:1987 228, 237 TS 37 ISO 2604-II:1975 220 TU 21 CND 25:22 AZ AFNOR N F A 49-217:1987 228, 237 TS 37-a AFNOR N F A 49-141:1978 167 TU 21 CND 25:20 AZ AFNOR N F A 49-217:1987 228, 237 TS 37-a (NE) AFNOR N F A 49-141:1978 167 TU 21 NCDU 25:20 AZ AFNOR N F A 49-217:1987 228, 237 TS 38 ISO 2604-II:1975 222 TU 21 NCDU 31:27 O3 AFNOR N F A 49-217:1987 263 TS 39 ISO 2604-II:1975 223, 224 TU 21 C 13 AFNOR N F A 49-217:1987 263 TS 40 ISO 2604-II:1975 260 TU 2 C N 18 10 AZ AFNOR N F A 49-217:1987 262, 235 TS 43 ISO 2604-II:1975 260 TU 2 C N 18 10 AZ AFNOR N F A 49-217:1987 262, 235 TS 45 ISO 2604-II:1975 260 TU 2 C N 18 10 AZ AFNOR N F A 49-217:1987 262, 235 TS 43 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td></t<>						
RS 33 ISO 2604-II:1975 216 IU 2 1 CND 25 22 AZ AFNOR NF A 49-217:1987 229, 237 TS 34 ISO 2604-II:1975 220 TU Z 1 CNDU 20 18 06 AZ AFNOR NF A 49-217:1987 228, 237 TS 37-3 ISO 2604-II:1975 221 TU Z 1 CND 18 15 AFNOR NF A 49-217:1987 228, 237 TS 37-a (NE) AFNOR NF A 49-141:1978 179 TU Z 1 NCDU 35 20 04 AFNOR NF A 49-217:1987 228, 237 TS 38 ISO 2604-II:1975 222 TU Z 1 NCDU 31 27 03 AFNOR NF A 49-217:1987 263 TS 39 ISO 2604-II:1975 223, 224 TU Z 10 C1 18 10 AZ AFNOR NF A 49-217:1987 223, 224 TS 40 ISO 2604-II:1975 260 TU Z 2 CN 18 10 AFNOR NF A 49-217:1987 226, 235 TS 43 ISO 2604-II:1975 260 TU Z 2 CN 18 10 AFNOR NF A 49-217:1987 263 TS 43 ISO 2604-II:1975 260 TU Z 2 CN 18 10 AFNOR NF A 49-217:1987 263 TS 43 ISO 2604-II:1975 260 TU Z 2 CN 18 10 AFNOR NF A 49-217:1987 263 TS 44 ISO 2604-II:1			217. 218			
TS 34						
TS 37						
TS 37-a (NE) AFNOR NF A 49-141:1978 179 TU Z 1 (NDU) 25 20 AFNOR NF A 49-147:1987 263 178 37-a (NE) AFNOR NF A 49-141:1978 179 TU Z 1 (NDU) 25 20 AFNOR NF A 49-147:1987 263 183 81 SO 2604-II:1975 223, 224 TU Z 1 OCT 17 AFNOR NF A 49-217:1987 223, 224 TU Z 1 OCT 17 AFNOR NF A 49-217:1987 223, 224 AFNOR NF A 49-217:1987 224, 225 AFNOR NF A 49-217:1987 226, 235 AFNOR NF A 49-217:198						
TS 37-a (NE) AFNOR NF A 49-141:1978 170 I U Z 1 NCDU 31 27 03 AFNOR NF A 49-217:1987 283 TS 38 ISO 2604-II:1975 222 TU Z 1 NCDU 31 27 03 AFNOR NF A 49-217:1987 223, 224 TS 39 ISO 2604-II:1975 223, 224 TU Z 1 O C 17 AFNOR NF A 49-217:1987 223, 224 TS 4 ISO 2604-II:1975 207, 210 TU Z 2 CN 18 10 AFNOR NF A 49-217:1987 226, 235 TS 40 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 226, 235 TS 40 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 266 TS 43 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 263 TS 45 ISO 2604-II:1975 260 TU Z 2 CND 17:12 AFNOR NF A 49-217:1987 293 TS 46 ISO 2604-II:1975 226, 235 TU Z 2 CND 17:12 AFNOR NF A 49-217:1987 293 TS 47 ISO 2604-II:1975 225, 234 TU Z 2 CND 17:12 AFNOR NF A 49-217:1987 293 TS 48 ISO 2604-II:1975						
TS 38 ISO 2604-II:1975 222 TU Z 10 C 17 AFNOR NF A 49-217:1967 223, 224 TS 39 ISO 2604-II:1975 223, 224 TU Z 10 C 17 AFNOR NF A 49-217:1967 223, 224 TS 40 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 226, 235 TS 40 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 226, 235 TS 42-a AFNOR NF A 49-341:1975 171 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 260 TS 43 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 229, 293 TS 45 ISO 2604-II:1975 260 TU Z 2 CND 17-12 AFNOR NF A 49-217:1987 229, 293 TS 45 ISO 2604-II:1975 260 TU Z 2 CND 17-12 AFNOR NF A 49-217:1987 220, 293 TS 45 ISO 2604-II:1975 226, 235 TU Z 2 CND 17-12 AFNOR NF A 49-217:1987 220, 293 TS 47 ISO 2604-II:1975 227, 236 TU Z 2 CND 18-10 AFNOR NF A 49-217:1987 223, 243 TS 48 ISO 2604-II:1975						
TS 39						
TS 4 ISO 2604-II:1975 207, 210 TU Z 12 CN 18 10 AFNOR NF A 49-217:1987 223, 224 TS 40 ISO 2937:1974 167, 177 TU Z 2 CN 18 10 AFNOR NF A 49-217:1987 226, 235 TS 40 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 226, 235 TS 43 ISO 2604-II:1975 260 TU Z 2 CN 18-10 AFNOR NF A 49-217:1987 223 TS 45 ISO 2604-II:1975 260 TU Z 2 CN D 17 12 AFNOR NF A 49-217:1987 229, 239 TS 46 ISO 2604-II:1975 260 TU Z 2 CN D 17 12 AFNOR NF A 49-217:1987 229, 239 TS 46 ISO 2604-II:1975 226, 235 TU Z 2 CND 17 12 AFNOR NF A 49-217:1987 230, 240 TS 47 ISO 2604-II:1975 225, 234 TU Z 2 CND 18 05 03 AFNOR NF A 49-217:1987 263 TS 48 ISO 2604-II:1975 227, 236 TU Z 2 CND 18 05 03 AFNOR NF A 49-217:1987 263 TS 50 ISO 2604-II:1975 231, 242 TU Z 2 CND 18 05 03 AFNOR NF A 49-217:1987 232, 243 TS 53 ISO 2604-II						
ISO 2937:1974 167, 177 TU Z 2 CN 18 10 AZ AFNOR NF A 49-217:1987 226, 235 235 242 236						
TS 40						
TS 42-a AFNOR NF A 49-341:1975	TS 40					
TS 43						
TS 45						
TS 46						
TS 47 ISO 2604-II:1975 225, 234 TU Z 2 CND 18 05 03 AFNOR NF A 49-217:1987 263 TS 48 ISO 2604-II:1975 207, 210 TU Z 2 CND 18 14 AFNOR NF A 49-244:1993 229, 239 TS 5 ISO 2604-II:1975 207, 210 TU Z 2 CND 22 05 03 AFNOR NF A 49-247:1987 232, 243 TS 50 ISO 2604-II:1975 231, 242 TU Z 2 CND 25 07 03 AFNOR NF A 49-217:1987 232, 243 TS 53 ISO 2604-II:1975 231, 242 TU Z 2 CND 25 07 03 AFNOR NF A 49-217:1987 232, 243 TS 54 ISO 2604-II:1975 232, 244 TU Z 2 CND 21 08 02 AFNOR NF A 49-217:1987 263 TS 56 ISO 2604-II:1975 233, 244 TU Z 5 CND 21 08 02 AFNOR NF A 49-217:1987 263 TS 57 ISO 2604-II:1975 229, 239 TU Z 6 CND 17 11 AFNOR NF A 49-217:1987 225, 234 TS 58 ISO 2604-II:1975 229, 239 TU Z 6 CND 17 11 AFNOR NF A 49-217:1987 225, 234 TS 58 ISO 2604-II:1975 207, 210 TW 1 ISO 2604-III:1975 206, 210 TS 60 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 206, 210 TS 61 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 208, 211 TS 63 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 66 ISO 2604-II:1975 200, 240 TW 14 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 208, 211 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 TS 9 ISO 2604-II:1975 208, 211 TW 46 ISO 2604-III:1975 207, 210 TS E 24-a AFNOR NF A 49-250:1979 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 2 12 CN 17-07 AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235						
TS 48			·			
TS 5						
TS 50 ISO 2604-II:1975 232, 244 TU Z 2 CND 25 07 03 AFNOR NF A 49-217:1987 232, 243 TS 53 ISO 2604-II:1975 231, 242 TU Z 2 CNDU 17 16 AFNOR NF A 49-217:1987 263 TS 54 ISO 2604-II:1975 232, 243 TU Z 5 CNDU 21 08 02 AFNOR NF A 49-217:1987 263 TS 56 ISO 2604-II:1975 229, 239 TU Z 6 CN 18 09 AFNOR NF A 49-217:1987 225, 234 TS 57 ISO 2604-II:1975 229, 239 TU Z 6 CN 18 10 AFNOR NF A 49-217:1987 228, 238 TS 58 ISO 2604-II:1975 229, 239 TU Z 6 CN 18 10 AFNOR NF A 49-217:1987 228, 238 TS 60 ISO 2604-II:1975 229, 239 TU Z 6 CN 18 10 AFNOR NF A 49-217:1987 228, 238 TS 60 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 206, 210 TS 60 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 209, 212 TS 61 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 260 TW 14 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-III:1975 207, 210 TS E 24-a AFNOR NF A 49-250:1979 169, 179 TW 4 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-V:1978 225, 234 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 232, 244						
TS 53						
TS 54 ISO 2604-II:1975 232, 243 TU Z 5 CNDU 21 08 02 AFNOR NF A 49-217:1987 263 TS 56 ISO 2604-II:1975 233, 244 TU Z 6 CN 18 09 AFNOR NF A 49-217:1987 225, 234 TS 57 ISO 2604-II:1975 229, 239 TU Z 6 CND 17 11 AFNOR NF A 49-217:1987 228, 238 TS 58 ISO 2604-II:1975 229, 239 TU Z 6 CND 17 11 AFNOR NF A 49-217:1987 228, 238 TS 6 ISO 2604-II:1975 207, 210 TW 1 ISO 2604-III:1975 206, 210 TS 60 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 208, 211 TS 61 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 230, 240 TW 14 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 213 TS 69 ISO 2604-II:1975 208, 211 TS 69 ISO 2604-II:1975 208, 211 TS 9H ISO 2604-II:1975 208, 211 TW 32 ISO 2604-II:1975 207, 210 TS 2 2 CN 18-10 AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-II:1975 207, 210 TS 2 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 5 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 5 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235						
TS 56 ISO 2604-II:1975 233, 244 TU Z 6 CN 18 09 AFNOR NF A 49-217:1987 225, 234 TS 57 ISO 2604-II:1975 229, 239 TU Z 6 CND 17 11 AFNOR NF A 49-217:1987 228, 238 TS 58 ISO 2604-II:1975 229, 239 TU Z 6 CNT 18 10 AFNOR NF A 49-217:1987 228, 238 TS 58 ISO 2604-II:1975 229, 239 TU Z 6 CNT 18 10 AFNOR NF A 49-217:1987 231, 242 TS 6 ISO 2604-II:1975 207, 210 TW 1 ISO 2604-III:1975 206, 210 TS 60 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 208, 211 TS 61 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 230, 240 TW 14 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 206, 210 TS 69 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS 57			·			
TS 58						
TS 6 ISO 2604-II:1975 207, 210 TW 1 ISO 2604-III:1975 206, 210 TS 60 ISO 2604-II:1975 229, 238 TW 10 ISO 2604-III:1975 208, 211 TS 61 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 230, 240 TW 14 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 206, 210 TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-III:1975 207, 210 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS 60						
TS 61 ISO 2604-II:1975 229, 238 TW 13 ISO 2604-III:1975 209, 212 TS 63 ISO 2604-II:1975 230, 240 TW 14 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 206, 210 TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 232, 244						
TS 63 ISO 2604-II:1975 230, 240 TW 14 ISO 2604-III:1975 209, 212 TS 67 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 206, 210 TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS 67 ISO 2604-II:1975 260 TW 15 ISO 2604-III:1975 209, 212 TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 206, 210 TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS 68 ISO 2604-II:1975 228, 237 TW 2 ISO 2604-III:1975 206, 210 TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-247:1981 226, 235 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 50 ISO 2604-V:1978 231, 242						
TS 69 ISO 2604-II:1975 260 TW 26 ISO 2604-III:1975 213 TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS 9 ISO 2604-II:1975 208, 211 TW 32 ISO 2604-III:1975 217, 218 ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						,
ISO 2937:1974 169, 179 TW 4 ISO 2604-III:1975 207, 210 TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS 9H ISO 2604-II:1975 208, 211 TW 46 ISO 2604-V:1978 226, 235 TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242	198					
TS E 24-a AFNOR NF A 49-250:1979 167, 178 TW 47 ISO 2604-V:1978 225, 234 TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242	TO 011					
TS E 26-b AFNOR NF A 49-250:1979 169, 179 TW 5 ISO 2604-III:1975 207, 210 TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242						
TS Z 12 CN 17-07 AFNOR NF A 49-647:1979 259 TW 50 ISO 2604-V:1978 232, 244 TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242			•			
TS Z 2 CN 18-10 AFNOR NF A 49-247:1981 226, 235 TW 53 ISO 2604-V:1978 231, 242					ISO 2604-III:1975	
AFNOD NE A 40 047 4070 400 400				TW 50	ISO 2604-V:1978	
AFNOR NF A 49-64/:19/9 190, 193 TW 57 ISO 2604-V:1978 229, 239	15 Z 2 CN 18-10					231, 242
		AFNOR NF A 49-647:1979	190, 193	TW 57	ISO 2604-V:1978	229, 239

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
TW 58	ISO 2604-V:1978	229, 239	Type F, Grade A	ASTM A 53/A 53M-02	202, 204
TW 6	ISO 2604-III:1975	207, 210	Type I	ASTM	352, 356
TW 60	ISO 2604-V:1978	229, 238	Typo I	A 447/A 447M-93 (2003)	135, 136
TW 61	ISO 2604-V:1978	229, 238	Туре I	ASTM A 553/A 553M-95 (2000)	133, 130
TW 69	ISO 2604-V:1975	263	Type II	ASTM	352, 356
TW 9	ISO 2604-III:1975	208, 211	. , , ,	A 447/A 447M-93 (2003)	302, 333
TW 9H	ISO 2604-III:1975	208, 211	Type II	ASTM `´	135, 136
Type 1	ASTM A 242/A 242M-03a	73, 77		A 553/A 553M-95 (2000)	
Type 2	ASTM A 606-01	90, 95	Type S, Grade A	ASTM A 53/A 53M-02	202, 204
Type 4	ASTM A 606-01	90, 95	Type S, Grade B	ASTM A 53/A 53M-02	203, 205
Type A, Class 1	ASTM	118, 120	Type B, Class 1	ASTM	137, 138
	A 533/A 533M-93 (1999)		Type P. Class 2	A 533/A 533M-93 (1999) ASTM	107 100
	ASTM A 542/A 542M-99	153	Type B, Class 2	A 533/A 533M-93 (1999)	137, 138
Type A, Class 2	ASTM	118, 120	Type B, Class 3	ASTM	137, 138
	A 533/A 533M-93 (1999)	150	. , po 2, e.aee e	A 533/A 533M-93 (1999)	,
T 4 01 0	ASTM A 542/A 542M-99	153	Type C, Class 1	ASTM `´	139, 140
Type A, Class 3	ASTM A 533/A 533M-93 (1999)	118, 120		A 533/A 533M-93 (1999)	
	ASTM A 542/A 542M-99	153	U-60-30	ASTM A 27/A 27M-03	319, 323
Type A, Class 4	ASTM A 542/A 542M-99	153	W108	SAE J438-1970	430
Type A, Class 4a	ASTM A 542/A 542M-99	153	W109	SAE J438-1970	430
Type B, Class 1	ASTM A 542/A 542M-99	153	W110	SAE J438-1970	430
Type D, Class T	ASTM A 542/A 542/N-99 ASTM	153	W112	SAE J438-1970	430
	A 543/A 543M-93 (1999)	100	W1-A-10	ASTM A 686-92 (1999)	430
Type B, Class 2	ASTM A 542/A 542M-99	153	W1-A-11½	ASTM A 686-92 (1999)	430
,, , , , , , , , , , , , , , , , , , , ,	ASTM	153	W1-A-8	ASTM A 686-92 (1999)	430
	A 543/A 543M-93 (1999)		W1-A-8½	ASTM A 686-92 (1999)	430
Type B, Class 3	ASTM A 542/A 542M-99	153	W1-A-9	ASTM A 686-92 (1999)	430
	ASTM	153	W1-C	ASTM A 686-92 (1999)	438
	A 543/A 543M-93 (1999)		W209	SAE J438-1970	438
Type B, Class 4	ASTM A 542/A 542M-99	153	W210	SAE J438-1970	438
Type B, Class 4a	ASTM A 542/A 542M-99	153	W2-A-81/2	ASTM A 686-92 (1999)	430
Type C, Class 1	ASTM A 542/A 542M-99	153	W2-A-9½	ASTM A 686-92 (1999)	430
	ASTM	153	W2-C	ASTM A 686-92 (1999)	438
Type C, Class 2	A 543/A 543M-93 (1999)	120 140	W310	SAE J438-1970 `	438
Type C, Class 2	ASTM A 533/A 533M-93 (1999)	139, 140	W5	ASTM A 686-92 (1999)	438
	ASTM A 542/A 542M-99	153	WC1	ASTM A 217/A 217M-02	335, 336
	ASTM	153	WC11	ASTM A 217/A 217M-02	360
	A 543/A 543M-93 (1999)		WC4	ASTM A 217/A 217M-02	360
Type C, Class 3	ASTM	139, 140	WC5	ASTM A 217/A 217M-02	360
	A 533/A 533M-93 (1999)	450	WC6	ASTM A 217/A 217M-02	335, 336
	ASTM A 542/A 542M-99	153	WC9	ASTM A 217/A 217M-02	335, 336
	ASTM	153	WCA	ASTM	326
Type C, Class 4	A 543/A 543M-93 (1999) ASTM A 542/A 542M-99	153		A 216/A 216M-93 (2003)	020
Type C, Class 4 Type C, Class 4a	ASTM A 542/A 542M-99	153	WCB	ASTM	326
Type D, Class 1	ASTM A 542/A 542/N-99 ASTM	153		A 216/A 216M-93 (2003)	
Type D, Class T	A 533/A 533M-93 (1999)	100	WCC	ASTM	326
	ASTM A 542/A 542M-99	153	V 10 Ni 0	A 216/A 216M-93 (2003)	100 001
Type D, Class 2	ASTM	153	X 10 Ni 9	ISO 9329-3:1997	199, 201
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	A 533/A 533M-93 (1999)		V 40 NE 5	ISO 9330-5:2000	199, 201
	ASTM A 542/A 542M-99	153	X 12 Ni 5	ISO 9329-3:1997	199, 201
Type D, Class 3	ASTM	153		ISO 9330-3:1997	199, 201
	A 533/A 533M-93 (1999)			ISO 9330-5:2000	199, 201
	ASTM A 542/A 542M-99	153	X 2 CrNi 18 10	ISO 9328-5:1991	143, 146
Type D, Class 4	ASTM A 542/A 542M-99	153	X 2 CrNi 19 11	DIN 17457:1985	226, 235
Type D, Class 4a	ASTM A 542/A 542M-99	153		DIN 17458:1985	226, 235
Type E, Class 4	ASTM A 542/A 542M-99	153	X 2 CrNiMo 17 12	ISO 9328-5:1991	144, 147
	ASTM A 542/A 542M-99	153	X 2 CrNiMo 17 13	ISO 9328-5:1991	144, 147
* *	ASTIVI A 342/A 342/VI-99				
Type E, Class 4a Type E, Grade A Type E, Grade B	ASTM A 53/A 53M-02 ASTM A 53/A 53M-02	202, 204 203, 205	X 2 CrNiMo 17 13 2	DIN 17457:1985	229, 239 229, 239

X 2 CMMON 18 1-43 DIN 17467-1995 229, 239 X 8 CMMT 18 10 DIN 17469-1992 230 155, 196	Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
X 2 C/MIMON 17 12 ISO 93828-51991 144, 148	X 2 CrNiMo 18 14 3	DIN 17457:1985	229, 239	X 8 CrNiTi 18 10	DIN 17459:1992	263
X 2 C/MIMON 17 13 SIO 9328-5-1991		DIN 17458:1985	229, 239	X 8 Ni 9	ISO 9328-3:1991	135, 136
X 2 CrNIMON 17 13 3 DIN 17457-1985 230, 240	X 2 CrNiMoN 17 12	ISO 9328-5:1991	144, 148	X 8 NiCrAlTi 32 21	DIN 17459:1992	233, 245
No. 1745-1895 20, 240 X100C/MOV5 SC 4957.1999 43, 23 24 X105C/MOV5 SC 4957.1999 414, 416 165, 425, 425	X 2 CrNiMoN 17 13	ISO 9328-5:1991	144, 148	X 8 NiCrAlTi 32 21 TQ1	ISO 9328-5:1991	145, 150
X 2 CrNIMON 17 13 5	X 2 CrNiMoN 17 13 3	DIN 17457:1985	230, 240	X 8 NiCrAlTi 32 21 TQ2	ISO 9328-5:1991	145, 150
DIN 17488-1985		DIN 17458:1985	230, 240	X100CrMoV5	ISO 4957:1999	433
DIN 17488-1985 233, 244 X10C/AISH3 EN 10085-1999 414, 416 16082-1991 145, 148 EN 10085-1994 416	X 2 CrNiMoN 17 13 5	DIN 17457:1985	233, 244	X105CrMo17	EN 10088-3:1995	395, 397
SC 9328-51991		DIN 17458:1985	233, 244	X10CrAlSi13	EN 10095:1999	414, 416
X 2 Cr\times Din 17457-1985 226, 255 X10Cr\times EN 1008-1999 414, 416 X2 NICM\times S0 9328-5-1991 143, 146 X10Cr\times X1 NICCr\times		ISO 9328-5:1991	145, 148		ISO 4955:1994	416
DIN 17458:1985 226, 235 ISO 4955:1994 416, 416 A2 NICAMOCU 25 20 5 ISO 9328-5:1991 143, 146 X10CrAISI25 EN 10095:1999 414, 416 X2 NICAMOCU 25 20 5 ISO 9328-5:1991 145, 149 X10CrAISI25 EN 10095:1999 414, 416 X3 CrAINIA 18 ISO 9328-5:1991 144, 148 X10CrAISI25 EN 10095:1999 414, 416 X3 CrAINIA 18 ISO 9328-5:1991 200, 240 X10CrMoVNB9-1 EN 10026-2:2002 222 222 223 X10CrMoVNB9-1 EN 10026-2:2002 222 223 X3 CrAINIA 18 ISO 9328-5:1991 225, 234 X10CrAISI25 EN 10028-2:1999 287	X 2 CrNiN 18 10	DIN 17457:1985		X10CrAlSi18	EN 10095:1999	414, 416
143, 146		DIN 17458:1985	226, 235		ISO 4955:1994	416
X 2 NICMMOL 25 20 5		ISO 9328-5:1991	143, 146	X10CrAlSi25	EN 10095:1999	414, 416
X 3 CriMiNo 18 16 4 X 3 CriMiNo 17 13 X 3 CriMiNo 18 11 X 3 CriMiNo 17 13 X 5 CriMino 17 13 X 5 CriMino 17 12 X 5 CriMino 18 11 X 5 CriMino 17 12 X 5 CriMino 17 13 X 6 CriMino 17 12 X 7 CriMino 17 12 X 7 CriMino 17 12 X 7 CriMino 17 12 X 8 CriMino 17 13 X 8 CriMino 17 12 X 9 CriMino 17 13 X 8 CriMino 17 13 X 9 CriMin	X 2 NiCrMoCu 25 20 5	ISO 9328-5:1991	145, 149		ISO 4955:1994	-
X 3 C/NIM N 17 13 DIN 17459:1992 283 X10C/MoVNB-1 EN 10262-22003 128 X 3 C/NIN 18 11 DIN 17459:1995 225, 234 X 5 C/NI 18 10 DIN 17459:1995 225, 234 DIN 28181:1985 225, 234 EN 10088-2:1995 372, 378 DIN 28181:1985 225, 234 DIN 28181:1985 228, 238 DIN 28181:1985 228, 238 DIN 17459:1995 228, 238 DIN 17459:1995 228, 238 DIN 28181:1985 230, 240 DIN 28181:1985 230, 241 DIN 28181:1985 230,	X 3 CrNiMo 18 16 4	ISO 9328-5:1991	144, 148	X10CrAlSi7		
X 3 C/NIN 18 11 DIN 17459:1992 25, 234 FIN 10216-2:2002 222 25, 234 DIN 17459:1985 225, 234 EN 10088-2:1995 372, 378 DIN 26190:1985 225, 234 EN 10088-2:1995 372, 378 DIN 26190:1985 225, 234 EN 10088-2:1995 400, 403 DIN 26190:1985 225, 234 EN 10088-3:1995 414, 416 DIN 270-3:2001 429 DIN 27457:1985 228, 238 X10NIC/SI35-19 EN 10095:1999 414, 416 DIN 2710-2009 220 DIN 17457:1985 228, 238 X10NIC/SI35-19 EN 10095:1999 414, 416 DIN 26190:1985 228, 238 X10NIC/SI35-19 EN 10095:1999 414, 416 DIN 26190:1985 228, 238 X110-M0541 EN 10216-2:2002 221 DIN 26191:1985 228, 238 X110-M054NT1 EN 10216-2:2002 221 DIN 26191:1985 228, 238 X110-M054NT2 EN 10216-2:2002 222 DIN 26191 DIN 261999 225 DIN 261995 225 DIN 261995 225 DIN 261991 225 DIN 261995 225 DIN 2619	X 3 CrNiMoN 17 13	DIN 17459:1992				-
X 5 CrNi 18 10	X 3 CrNiN 18 11	DIN 17459:1992	263			
DIN 17458:1985 225, 234	X 5 CrNi 18 10	DIN 17457:1985	225, 234			
No. 28181-1985 225, 234		DIN 17458:1985	225, 234	X10CrNi18-8		
X 5 C/Ni 18 19		DIN 28180:1985	225, 234	7.1.00		-
X 5 CNIN 18 9 ISO 9328-5:1991 143, 146 X 10 ChN18-8 EN 10270-3:2001 429 X 5 CNIMO 17 12 ISO 9328-5:1991 143, 147 X 10NIG EN 10216-4:2002 199, 201 X 5 CNIMO 17 12 2 DIN 1745:1985 228, 238 X 10NIC/GRIS3-19 EN 10095:1999 414, 416 N 10 28180:1985 228, 238 X 10NIC/GRIS3-19 EN 10095:1999 414, 416 X 5 CNIMO 17 13 ISO 9328-5:1991 143, 147 X 11C/MO5+H EN 10216-2:2002 221 X 5 CNIMO 17 13 ISO 9328-5:1991 143, 147 X 11C/MO5+NT1 EN 10216-2:2002 221 X 5 CNIMO 17 13 ISO 9328-5:1991 143, 147 X 11C/MO6+NT2 EN 10216-2:2002 221 X 5 CNIMO 17 13 ISO 9328-5:1991 228, 238 X 11C/MO6+NT2 EN 10216-2:2002 222 X 5 CNIMO 17 13 ISO 9328-5:1991 228, 238 X 11C/MO6+NT2 EN 10216-2:2002 222 X 5 NIC/ATTI 31 20 IN 17459-1992 235 X 11C/MO6-HT2 EN 10216-2:2002 222 X 5 NIC/ATTI 31 20 IN 17459-1992 230, 240 X		DIN 28181:1985	225, 234			-
X 5 CrNIMo 17 12 ISO 9328-5:1991 143, 147 X 10NI9 EN 10216-4:2002 199, 201 X 5 CrNIMo 17 12 2 DIN 17457:1985 228, 238 X 10NIC/GRITI-32-21 EN 10095:1999 414, 416 DIN 28181:1985 228, 238 X 10NIC/GRITI-32-21 EN 10095:1999 414, 416 DIN 28181:1985 228, 238 X 10NIC/GRISI-5-19 EN 100216-2:2002 221 X 5 CrNIMO 17 13 ISO 9328-5:1991 143, 147 X 11C/Mo54-NT1 EN 10216-2:2002 221 X 5 CrNIMO 17 13 DIN 17457:1985 228, 238 X 11C/Mo54-NT1 EN 10216-2:2002 221 X 5 NIC/ATT 31 20 DIN 17457:1985 228, 238 X 11C/Mo54-NT1 EN 10216-2:2002 222 X 5 NIC/ATT 31 20 DIN 17459:1992 233, 245 X 11C/Mo91-HT EN 10216-2:2002 222 X 5 NIC/ATT 31 20 DIN 17459:1992 245 X 11C/Mo91-HT EN 10216-2:2002 222 X 5 NIC/ATT 31 20 DIN 17459:1992 230, 240 X 12C/min Min M19-8-6 EN 10151:2002 437 X 6 CrNIMO 17 13 DIN 17459:1995 230, 241 X 12	X 5 CrNi 18 9	ISO 9328-5:1991	143, 146	X10CrNi18-8		
X 5 CrNiMo 17 12 2 DIN 17457:1985 228, 238	X 5 CrNiMo 17 12	ISO 9328-5:1991	143, 147			
DIN 17458:1985 228, 238	X 5 CrNiMo 17 12 2	DIN 17457:1985	228, 238			-
DIN 28180:1985 228, 238		DIN 17458:1985	228, 238			-
DIN 28181-1985 228, 238		DIN 28180:1985	228, 238			
X 5 CrNIMO 17 13 ISO 9328-5:1991 143, 147 X 11 CrMo5+NT2 EN 10216-2:2002 221 X 5 CrNIMO17 13 3 DIN 17457:1985 228, 238 X11 CrMo5+NT2 EN 10216-2:2002 221 X 5 NICrAITI 31 20 DIN 17459:1992 233, 245 X11 CrMo9-1+NT EN 10216-2:2002 222 X 5 NICrAITI 31 20 RK DIN 17459:1992 245 X11 CrMo9-1+NT EN 10151:2002 437 X 6 CrNIM 18 11 DIN 17459:1992 227, 236 X12Cr13 DIN 17456:1999 188, 189 X 6 CrNIMON 17 12 DIN 17459:1992 230, 240 EN 10088-2:1995 366, 367 X 6 CrNIMOND 17 12 DIN 17459:1995 262 EN 10088-2:1995 372, 377 X 6 CrNIMOND 17 12 2 DIN 17459:1985 262 EN 10088-2:1995 372, 377 X 6 CrNIMOND 17 12 2 DIN 17459:1985 230, 241 X12CrMnNIN17-7-5 EN 10088-2:1995 372, 377 X 6 CrNIMOND 17 12 2 DIN 17459:1985 230, 241 X12CrMnO5-1 ISO 9327-2:1999 286 X 6 CrNIMOND 17 12 2 DIN 28180:1985 230, 241 X12CrMnO5-1 ISO		DIN 28181:1985	228, 238			•
X 5 CrNiMo17 13 3	X 5 CrNiMo 17 13	ISO 9328-5:1991	143, 147			
DIN 17458:1985 228, 238	X 5 CrNiMo17 13 3	DIN 17457:1985	228, 238			
X 5 NICrAITI 31 20 DIN 17459:1992 233, 245 X11CrMo9-1+NT EN 10216-2:2002 222 X 5 NICrAITI 31 20 RK 6 CrN 18 11 DIN 17459:1992 245 X11CrNIMnN19-8-6 EN 10151:2002 437 X 6 CrN 18 11 DIN 17459:1992 230, 240 X12Cr13 DIN 17456:1999 188, 189 X 6 CrN 18 11 DIN 17459:1992 230, 240 EN 10088-2:1995 366, 367 X 6 CrN 18 11 ISO 9328-5:1991 144, 148 X12CrMnNIN17-7-5 EN 10088-2:1995 394, 396 X 6 CrN 18 17 12 ISO 9328-5:1991 144, 148 X12CrMnNIN17-7-5 EN 10088-2:1995 372, 377 X 6 CrN 18 17 12 2 DIN 17457:1985 230, 241 X12CrMnNIN18-9-5 EN 10088-2:1995 372, 377 X 6 CrN 18 10 11 DIN 17457:1985 230, 241 X12CrMo5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X12CrMo5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X12CrMo5-1 ISO 9327-2:1999 286 X 6 CrN 17 18 19 DIN 17458:1985 232, 242 X12CrMo5-1 EN 10028		DIN 17458:1985	228, 238			
X 5 NiCrAITI 31 20 RK X 6 CrNi 18 11 DIN 17459:1992 227, 236 X11CrNiiMnN19-8-6 EN 10151:2002 437 X 6 CrNi 18 11 DIN 17459:1992 230, 240 EN 10088-2:1995 366, 367 X 6 CrNiMo 17 12 ISO 9328-5:1991 144, 148 EN 10088-3:1995 394, 396 X 6 CrNiiMoNb 17 12 DIN 17458:1985 262 X 6 CrNiiMoNb 17 12 DIN 17458:1985 230, 241 X 12CrMnNiN17-7-5 EN 10088-2:1995 372, 377 DIN 28180:1985 230, 241 X 12CrMnNiN18-9-5 DIN 17458:1985 230, 241 X 12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28180:1985 230, 241 X 12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X 12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X 12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X 12CrMnO5-1 ISO 9327-2:1999 286 X 6 CrNiiNb 18 10 DIN 17457:1985 232, 244 X 12CrMo5-1 ISO 9328-5:1991 145, 149 X 6 CrNiiTi 18 10 DIN 17458:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 374, 382, 492 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X 12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 EN 1028-2:2003 155 EN 1028-2:2003 156 EN 1028-2:2003 156 EN 1028-2:2003 157 EN 10088-3:1999 414, 416 X 7 CrNii 18 9 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 7 CrNii 18 10 ISO 9328-5:1991 145, 149 X 15CrNii 12-18 ISO 9328-5:1991 1	X 5 NiCrAlTi 31 20	DIN 17459:1992	233, 245			
X 6 CrNi I8 11 DIN 17459:1992 227, 236 X12Cr13 DIN 17456:1999 188, 189 X 6 CrNiMon 17 13 DIN 17459:1992 230, 240 EN 10088-2:1995 366, 367 X 6 CrNiMon 17 12 ISO 3928-5:1991 144, 148 EN 10088-2:1995 394, 396 X 6 CrNiMo 17 12 2 DIN 17458:1985 262 EN 10250-4:1999 295, 296 X 6 CrNiMo 17 17 12 2 DIN 17457:1985 230, 241 X12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 X 6 CrNiMo 17 17 12 2 DIN 17458:1985 230, 241 X12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28180:1985 230, 241 X12CrMnO5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X12CrMo5-1 ISO 9327-2:1999 286 X 6 CrNiNb 18 10 DIN 17457:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 X 6 CrNiTi 18 10 DIN 17457:1985 231, 242 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 2	X 5 NiCrAlTi 31 20 RK	DIN 17459:1992	245			
X 6 CrNiMoNb 17 12 ISO 9328-5:1991 144, 148 EN 10088-2:1995 366, 367 X 6 CrNiMoNb 17 12 ISO 9328-5:1991 144, 148 EN 10088-3:1995 394, 396 EN 10088-2:1995 394, 396 EN 10088-2:1995 394, 396 EN 10088-2:1995 372, 377 EN 1015 17 12 ISO 9328-5:1991 144, 148 X12CrMnNiN17-7-5 EN 10088-2:1995 372, 377 EN 1015 1:2002 437 EN 1	X 6 CrNi 18 11	DIN 17459:1992	227, 236			
X 6 CrNiMoNb 17 12 ISO 9328-5:1991 144, 148 EN 10088-3:1995 394, 396 X 6 CrNiMoNb 17 12 2 DIN 17458:1985 262 EN 10250-4:1999 295, 296 X 6 CrNiMoTi 17 12 1 ISO 9328-5:1991 144, 148 X12CrMnNiN17-7-5 EN 10088-2:1995 372, 377 X 6 CrNiMoTi 17 12 2 DIN 17457:1985 230, 241 X12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X12CrMo5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X12CrMo5 EN 10028-2:2003 127 DIN 28181:1985 230, 241 X12CrMo5 EN 10028-2:2003 127 DIN 28181:1985 232, 244 X12CrMo5-1 ISO 9327-2:1999 286 X 6 CrNiNb 18 10 DIN 17457:1985 232, 244 X12CrMo3-13 EN 10095-1999 374, 382, 402 X 6 CrNiTi 18 10 DIN 17457:1985 231, 242 X12CrS13 EN 10088-3:1995 394, 396 X 7 CrNi 18 9 DIN 28181:1985 231, 242 X12Ni5 EN 10028-3:1995 394, 396 X 7 CrNi 18 9 ISO 9328-	X 6 CrNiMo 17 13	DIN 17459:1992	230, 240	7.120110		-
X 6 CrNiMoNb 17 12 2 DIN 17458:1985 262 EN 10250-4:1999 295, 296 X 6 CrNiMoTi 17 12 ISO 9328-5:1991 144, 148 X12CrMnNiN17-7-5 EN 10088-2:1995 372, 377 X 6 CrNiMoTi 17 12 2 DIN 17457:1985 230, 241 X12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 17458:1985 230, 241 X12CrMo5 EN 10028-2:2003 127 DIN 28180:1985 230, 241 X12CrMo5-1 ISO 9327-2:1999 286 X 6 CrNiNb 18 10 DIN 17457:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 232, 244 X12CrM09-10 EN 10095:1999 374, 382, 402, 408 X 6 CrNiTi 18 10 DIN 17457:1985 231, 242 X12CrS13 EN 10088-3:1995 344, 396 X 6 CrNiTi 18 10 DIN 17457:1985 231, 242 X12CrS13 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28180:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 231, 242 X12Ni5 EN 10028-3:1995 424 DIN 28181:1985 231, 242 X12Ni5 EN 10028-3:1995 424 DIN 28181:1985 231, 242 X12Ni5 EN 10028-3:1995 446 X 7 CrNi 18 9 ISO 9328-5:1991 145, 149 X15CrNi26 EN 10095:1999 414, 416 X 7 CrNiMo B 17 12 ISO 9328-5:1991 145, 149 X15CrNi26 ISO 4955:1994 438 X 7 CrNiTI 18 10 ISO 9328-5:1991 145, 149 X15CrNi26 ISO 4955:1994 389, 391, 398, 399 X 7 CrNiTI 18 10 ISO 9328-5:1991 145, 149 X15CrNi26 ISO 4955:1994 416 X 7 CrNiMoN No 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoN No 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoN No 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1994 416 X 8 CrNiMoN No 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1994 416 X 8 CrNiMoN No 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095	X 6 CrNiMoNb 17 12	ISO 9328-5:1991	144, 148			•
X 6 CrNiMoTi 17 12 ISO 9328-5:1991 144, 148 X12CrMnNiN17-7-5 EN 10088-2:1995 372, 377 X 6 CrNiMoTi 17 12 2 DIN 17457:1985 230, 241 X12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 DIN 28180:1985 230, 241 X12CrMo5 EN 10088-2:1995 372, 377 DIN 28181:1985 230, 241 X12CrMo5-1 ISO 9327-2:1999 286 X 6 CrNiNb 18 10 DIN 17457:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17457:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17457:1985 231, 242 X12CrS13 EN 10095:1999 374, 382, 402, 408 X 6 CrNiTi 18 10 DIN 17458:1985 231, 242 X12CrS13 EN 10088-3:1995 394, 396 DIN 2818:1985 231, 242 X12Ni5 EN 10028-4:2003 134 EN 10216-4:2002 199, 201 EN 10222-3:1998 289, 290 X 7 CrNi 18 9 ISO 9328-5:1991 143, 146 X12NiCrSi35-16	X 6 CrNiMoNb 17 12 2	DIN 17458:1985	262			
X 6 CrNiMoTi 17 12 2 DIN 17457:1985 230, 241 X12CrMnNiN18-9-5 EN 10151:2002 437	X 6 CrNiMoTi 17 12	ISO 9328-5:1991	144, 148	X12CrMnNiN17-7-5		
DIN 17458:1985 230, 241 X12CrMnNiN18-9-5 EN 10088-2:1995 372, 377 230, 241 X12CrMo5 EN 10028-2:2003 127 230, 241 X12CrMo5-1 ISO 9327-2:1999 286 232, 244 X12CrMo5-1 ISO 9327-2:1999 286 232, 244 X12CrMo5-1 ISO 9327-2:1999 286 232, 244 X12CrMo9-10 EN 10028-2:2003 155 230, 241 X12CrMi23-13 EN 10095:1999 374, 382, 402, 408 240,	X 6 CrNiMoTi 17 12 2	DIN 17457:1985	230, 241	711201111111111111111111111111111111111		•
DIN 28180:1985 230, 241 X12CrMo5 EN 10028-2:2003 127		DIN 17458:1985	230, 241	X12CrMnNiN18-9-5		
X 6 CrNiNb 18 10 DIN 28181:1985 Z30, 241 X12CrMo5-1 EN 10028-2:2003 155 DIN 17457:1985 Z32, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 Z32, 244 X12CrNi23-13 EN 10095:1999 374, 382, 402, 408 X 6 CrNiTi 18 10 DIN 17457:1985 Z31, 242 X12CrS13 EN 10088-3:1995 394, 396 DIN 17458:1985 Z31, 242 DIN 28180:1985 Z31, 242 X12CrS13 EN 10088-3:1995 394, 396 EN 10088-3:1995 424 DIN 28180:1985 Z31, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 Z31, 242 X12Ni5 EN 1028-4:2003 134 EN 1022-3:1998 Z89, 290 X 7 CrNi 18 9 X 15 CrNi 18 9 X 7 CrNi 18 9 X 15 CrNi 18 9		DIN 28180:1985	230, 241			
X 6 CrNiNb 18 10 DIN 17457:1985 232, 244 X12CrMo9-10 EN 10028-2:2003 155 DIN 17458:1985 232, 244 X12CrNi23-13 EN 10095:1999 374, 382, 402, 408 X 6 CrNiTi 18 10 DIN 17457:1985 231, 242 X12CrS13 EN 10088-3:1995 394, 396 DIN 17458:1985 231, 242 X12Ni5 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 231, 242 X12Ni5 EN 10216-4:2002 199, 201 ISO 9328-5:1991 145, 149 EN 10022-3:1998 289, 290 X 7 CrNi 18 9 ISO 9328-5:1991 143, 146 X12NiCrSi35-16 EN 10095:1999 414, 416 X 7 CrNiMo 17 12 ISO 9328-5:1991 144, 147 ISO 4955:1994 416 X 7 CrNiMoB 17 12 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrNi26 ISO 4955:1994 369, 371, 389, 399 X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 <t< td=""><td></td><td>DIN 28181:1985</td><td>230, 241</td><td></td><td></td><td></td></t<>		DIN 28181:1985	230, 241			
DIN 17458:1985 232, 244 X12CrNi23-13 EN 10095:1999 374, 382, 402, 408 X 6 CrNiTi 18 10	X 6 CrNiNb 18 10	DIN 17457:1985	232, 244			
SO 9328-5:1991 145, 149 402, 408		DIN 17458:1985	232, 244			
DIN 17458:1985 231, 242 X12Ni5 EN 10088-3:1995 424 DIN 28180:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 231, 242 EN 10216-4:2002 199, 201 ISO 9328-5:1991 145, 149 EN 10222-3:1998 289, 290 X 7 CrNi 18 9 ISO 9328-5:1991 143, 146 X12NiCrSi35-16 EN 10095:1999 414, 416 X 7 CrNiMo 17 12 ISO 9328-5:1991 144, 147 ISO 4955:1994 416 X 7 CrNiMo 18 10 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4957:1999 438 X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, 398, 399 X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263		ISO 9328-5:1991	145, 149			
DIN 28180:1985 231, 242 X12Ni5 EN 10028-4:2003 134 DIN 28181:1985 231, 242 EN 10216-4:2002 199, 201 ISO 9328-5:1991 145, 149 EN 10222-3:1998 289, 290 X 7 CrNi 18 9 ISO 9328-5:1991 143, 146 X12NiCrSi35-16 EN 10095:1999 414, 416 X 7 CrNiMo 17 12 ISO 9328-5:1991 144, 147 ISO 4955:1994 416 X 7 CrNiMo 18 10 ISO 9328-5:1991 156 X14CrMoS17 EN 10088-3:1995 416 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrNiCrSi35-16 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4957:1999 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, X 7 NiCrAITi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNiCrSi35-16 EN 10095:1999 414, 416 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiCrSi30-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263	X 6 CrNiTi 18 10	DIN 17457:1985	231, 242	X12CrS13	EN 10088-3:1995	394, 396
DIN 28181:1985 231, 242 EN 10216-4:2002 199, 201 ISO 9328-5:1991 145, 149 EN 10222-3:1998 289, 290 X 7 CrNi 18 9 ISO 9328-5:1991 143, 146 X12NiCrSi35-16 EN 10095:1999 414, 416 X 7 CrNiMo 17 12 ISO 9328-5:1991 144, 147 ISO 4955:1994 416 X 7 CrNiMo B 17 12 ISO 9328-5:1991 156 X14CrMoS17 EN 10088-3:1995 416 X 7 CrNiNb 18 10 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 398, 399 X 7 NiCrAITi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 ISO 4955:1994 416		DIN 17458:1985	231, 242		EN 10088-3:1995	424
SO 9328-5:1991 145, 149 EN 10222-3:1998 289, 290		DIN 28180:1985	231, 242	X12Ni5	EN 10028-4:2003	134
X 7 CrNi 18 9 ISO 9328-5:1991 143, 146 X12NiCrSi35-16 EN 10095:1999 414, 416 X 7 CrNiMo 17 12 ISO 9328-5:1991 144, 147 ISO 9328-5:1991 156 X14CrMoS17 EN 10088-3:1995 416 X 7 CrNiNb 18 10 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4957:1994 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4957:1994 398, 399 X 7 NiCrAITi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 ISO 4955:1994 416		DIN 28181:1985	231, 242		EN 10216-4:2002	199, 201
X 7 CrNiMo 17 12 ISO 9328-5:1991 144, 147 ISO 4955:1994 416 X 7 CrNiMoB 17 12 ISO 9328-5:1991 156 X14CrMoS17 EN 10088-3:1995 416 X 7 CrNiNb 18 10 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 398, 399 X 7 NiCrAITi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263		ISO 9328-5:1991	145, 149		EN 10222-3:1998	289, 290
X 7 CrNiMoB 17 12 ISO 9328-5:1991 156 X14CrMoS17 EN 10088-3:1995 416 X 7 CrNiNb 18 10 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 398, 399 X 7 NiCrAITi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263	X 7 CrNi 18 9	ISO 9328-5:1991	143, 146	X12NiCrSi35-16	EN 10095:1999	414, 416
X 7 CrNiNb 18 10 ISO 9328-5:1991 145, 149 X153CrMoV12 ISO 4957:1999 438 X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 398, 399 X 7 NiCrAITi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263	X 7 CrNiMo 17 12	ISO 9328-5:1991	144, 147		ISO 4955:1994	416
X 7 CrNiTi 18 10 ISO 9328-5:1991 145, 149 X15CrN26 ISO 4955:1994 369, 371, X 7 NiCrAITi 32 21 TQ1 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263 ISO 4955:1994 416		ISO 9328-5:1991	156		EN 10088-3:1995	416
X 7 NiCrAlTi 32 21 TQ1 ISO 9328-5:1991 145, 149 X 7 NiCrAlTi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263 ISO 4955:1994 416	X 7 CrNiNb 18 10	ISO 9328-5:1991	145, 149	X153CrMoV12	ISO 4957:1999	438
X 7 NiCrAlTi 32 21 TQ2 ISO 9328-5:1991 145, 149 X15CrNi24-13 AFNOR NF A 49-244:1993 227, 237 X 8 CrNiMoNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263 ISO 4955:1994 416	X 7 CrNiTi 18 10	ISO 9328-5:1991	145, 149	X15CrN26	ISO 4955:1994	
X 8 CrNiMoVNb 16 16 DIN 17459:1992 263 X15CrNiSi20-12 EN 10095:1999 414, 416 X 8 CrNiMoVNb 16 13 DIN 17459:1992 263 ISO 4955:1994 416		ISO 9328-5:1991	145, 149	V1EO-NIO4 10	A ENIOD NIE A 40 044:4000	
X 8 CrNiMoVNb 16 13 DIN 17459:1992 263 ISO 4955:1994 416	X 7 NiCrAlTi 32 21 TQ2	ISO 9328-5:1991	145, 149			
A 6 CHAINIOUTHD 16 15 DITA 17459.1992 205	X 8 CrNiMoNb 16 16	DIN 17459:1992		V 13011/19150-15		
X 8 CrNiNb 16 13 DIN 17459:1992 233, 244					130 4833.1884	410
· · · · · · · · · · · · · · · · · · ·	X 8 CrNiNb 16 13	DIN 17459:1992	233, 244			

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
X15CrNiSi25-21	EN 10095:1999	402, 408	X2CrNi18-9	EN 10088-2:1995	373, 380
	ISO 4955:1994	402, 408		EN 10088-3:1995	400, 404
X15CrNiSi25-4	EN 10095:1999	414, 416		EN 10222-5:1999	298, 302
X16CrMo5-1	EN 10222-2:1999	286		EN 10250-4:1999	298, 302
	EN 10222-2:1999	286	X2CrNi19-11	DIN 17455:1999	190, 193
X17CrNi16-2	EN 10088-3:1995	394, 397		DIN 17456:1999	190, 193
	EN 10250-4:1999	313		EN 10028-7:2000	143, 146
X18CrN28	EN 10095:1999	398, 399		EN 10088-2:1995	373, 380
X1CrNi25-20	AFNOR NF A 49-244:1993	228, 237		EN 10088-3:1995	416
X1CrNi25-21	EN 10028-7:2000	156		EN 10250-4:1999	298, 302
	EN 10088-2:1995	414	X2CrNiCu19-10	EN 10222-5:1999	313
X1CrNiMoCuN20-18-7	EN 10028-7:2000	156	X2CrNiMo17-12	ISO 9327-5:1999	299, 304
	EN 10088-2:1995	374, 382	X2CrNiMo17-12-2	DIN 17455:1999	191, 194
	EN 10088-3:1995	416		DIN 17456:1999	191, 194
	EN 10250-4:1999	313		EN 10028-7:2000	144, 147
X1CrNiMoCuN25-25-5	EN 10028-7:2000	156		EN 10088-2:1995	374, 383
	EN 10088-2:1995	414		EN 10088-3:1995	401, 406
	EN 10088-3:1995	416		EN 10222-5:1999	299, 304
X1CrNiMoN25-22-2	EN 10028-7:2000	156		EN 10250-4:1999	299, 304
	EN 10088-2:1995	374, 382	X2CrNiMo17-12-3	EN 10028-7:2000	144, 147
X1CrNiSi18-15-4	EN 10088-2:1995	373, 381		EN 10088-2:1995	374, 383
	EN 10088-3:1995	416		EN 10088-3:1995	401, 406
X1NiCrMoCu25-20-5	EN 10028-7:2000	145, 149		EN 10222-5:1999	299, 304
	EN 10088-2:1995	375, 385	X2CrNiMo17-13	ISO 9327-5:1999	299, 304
	EN 10088-3:1995	402, 408	X2CrNiMo17-13-3	EN 10250-4:1999	300, 305
	EN 10088-3:1995	416	X2CrNiMo18-14-3	DIN 17455:1999	191, 194
	EN 10250-4:1999	301, 306		DIN 17456:1999	191, 194
X1NiCrMoCu31-27-4	EN 10028-7:2000	156		EN 10028-7:2000	144, 147
	EN 10088-2:1995	414		EN 10088-2:1995	374, 383
	EN 10088-3:1995	416		EN 10088-3:1995	401, 406,
	EN 10250-4:1999	313			416
X1NiCrMoCuN25-20-7	EN 10028-7:2000	145, 149		EN 10222-5:1999	299, 304
	EN 10088-3:1995	416		EN 10250-4:1999	299, 304
X1NiMoCuN25-20-7	EN 10250-4:1999	313	X2CrNiMo18-15-4	EN 10028-7:2000	144, 148
X20Cr13	EN 10088-2:1995	366, 367		EN 10088-3:1995	402, 408
	EN 10088-3:1995	394, 396	X2CrNiMoCuN25-6-3	EN 10028-7:2000	151, 152
	EN 10151:2002	437		EN 10088-2:1995	392, 393
	EN 10250-4:1999	313		EN 10088-3:1995	416
X20CrMoV11-1	EN 10216-2:2002	261		EN 10250-4:1999	309, 310
	EN 10222-2:1999	288	X2CrNiMoCuWN25-7-4	EN 10028-7:2000	151, 152
X20CrMoV12-1	ISO 9327-2:1999	288		EN 10088-2:1995	392, 393
X210Cr12	ISO 4957:1999	433		EN 10088-3:1995	416
X210CrW12	ISO 4957:1999	438		EN 10250-4:1999	309, 310
X25CrMnNiN25-9-7	EN 10095:1999	414, 416	X2CrNiMoN17-11-2	EN 10028-7:2000	144, 148
X29CrS13	EN 10088-3:1995	394, 397		EN 10088-2:1995	375, 384
X2CrAlTi18-2	EN 10088-2:1995	414		EN 10088-3:1995	401, 407
X2CrMnNiN17-7-5	EN 10088-2:1995	372, 377		EN 10222-5:1999	300, 305
X2CrMoTi17-1	EN 10088-2:1995	414		EN 10250-4:1999	300, 305
X2CrMoTi18-2	EN 10028-7:2000	141, 142	X2CrNiMoN17-12	ISO 9327-5:1999	300, 305
	EN 10088-2:1995	369, 371	X2CrNiMoN17-13	ISO 9327-5:1999	300, 305
X2CrMoTi29-4	EN 10088-2:1995	369, 371	X2CrNiMoN17-13-3	DIN 17455:1999	191, 194
X2CrMoTiS18-2	EN 10088-3:1995	398, 399		DIN 17456:1999	191, 194
X2CrNbZr17	EN 10088-2:1995	414		EN 10028-7:2000	144, 148
X2CrNi12	EN 10028-7:2000	141, 142		EN 10088-2:1995	375, 384
· 2 · · · · •	EN 10088-2:1995	368, 370		EN 10088-3:1995	401, 407
				EN 10222-5:1999	300, 305
	EN 10088-3:1995	410			
X2CrNi18-10	EN 10088-3:1995 ISO 9327-5:1999	416 298, 302	X2CrNiMoN17-13-5	DIN 17455:1999	192, 195

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
X2CrNiMoN17-13-5	EN 10028-7:2000	145, 148	X3CrNi18-10	AFNOR NF A 49-244:1993	226, 235
(continued)	EN 10088-2:1995	375, 385	X3CrNiCu18-9-4	EN 10088-3:1995	416
	EN 10088-3:1995	402, 408	X3CrNiCu19-9-2	EN 10088-3:1995	416
X2CrNiMoN18-12-4	EN 10028-7:2000	144, 148	X3CrNiCuMo17-11-3-2	EN 10088-3:1995	416
	EN 10088-2:1995	375, 385	X3CrNiMo13-4	EN 10028-7:2000	141, 142
X2CrNiMoN22-5-3	EN 10028-7:2000	151, 152		EN 10088-2:1995	414
	EN 10088-2:1995	392, 393		EN 10088-3:1995	416
	EN 10088-3:1995	412		EN 10222-5:1999	295, 296
	EN 10222-5:1999	309, 310		EN 10250-4:1999	295, 296
	EN 10250-4:1999	309, 310	X3CrNiMo17-11-2	AFNOR NF A 49-244:1993	229, 239
	ISO 9327-5:1999	309, 310	X3CrNiMo17-12-3	AFNOR NF A 49-244:1993	229, 239
X2CrNiMoN25-7-4	EN 10028-7:2000	151, 152	X3CrNiMo17-13-3	DIN 17455:1999	191, 194
	EN 10088-2:1995	392, 393		DIN 17456:1999	191, 194
	EN 10088-3:1995	416		EN 10028-7:2000	143, 147
	EN 10222-5:1999	309, 310		EN 10088-2:1995	374, 383
	EN 10250-4:1999	309, 310		EN 10088-3:1995	401, 406
X2CrNiN18-10	DIN 17455:1999	190, 193		EN 10222-5:1999	299, 303
	DIN 17456:1999	190, 193		EN 10250-4:1999	299, 303
	EN 10028-7:2000	143, 146	X3CrNiMo18-12-3	AFNOR NF A 49-244:1993	229, 239
	EN 10088-2:1995	373, 381		EN 10222-5:1999	313
	EN 10088-3:1995	400, 405	X3CrNiMo19-15-4	AFNOR NF A 49-244:1993	231, 242
	EN 10222-5:1999	298, 303	X3CrNiMoBN17-13-3	EN 10028-7:2000	156
	EN 10250-4:1999	298, 303	X3CrNiMoCu22-7	AFNOR NF A 49-244:1993	263
	ISO 9327-5:1999	298, 303	X3CrNiMoCuN25-6	AFNOR NF A 49-244:1993	263
X2CrNiN18-7	EN 10028-7:2000	143, 146	X3CrNiMoCuN25-7	AFNOR NF A 49-244:1993	263
	EN 10088-2:1995	372, 379	X3CrNiMoN17-11	AFNOR NF A 49-244:1993	230, 240
X2CrNiN18-9	EN 10028-7:2000	143, 146	X3CrNiMoN17-12	AFNOR NF A 49-244:1993	230, 240
X2CrNiN23-4	EN 10028-7:2000	151, 152	X3CrNiMoN17-13-3	EN 10222-5:1999	313
	EN 10088-2:1995	392, 393	X3CrNiMoN18-14-5	AFNOR NF A 49-244:1993	233, 244
	EN 10088-3:1995	416	X3CrNiMoN19-14	AFNOR NF A 49-244:1993	263
	EN 10250-4:1999	309, 310	X3CrNiMoN22-5	AFNOR NF A 49-244:1993	263
	ISO 9327-5:1999	309, 310	X3CrNiMoN25-6	AFNOR NF A 49-244:1993	263
X2CrTi12	DIN 17455:1999	188, 189	X3CrNiMoN25-7	AFNOR NF A 49-244:1993	263
	DIN 17456:1999	188, 189	X3CrNiMoN27-5-2	EN 10088-3:1995	416
	EN 10088-2:1995	368, 370		EN 10250-4:1999	309, 310
X2CrTi17	EN 10028-7:2000	156	X3CrNiN18-10	AFNOR NF A 49-244:1993	226, 236
	EN 10088-2:1995	368, 370	X3CrNiN23-4	AFNOR NF A 49-244:1993	263
X2CrTiNb18	EN 10028-7:2000	141, 142	X3CrTi17	DIN 17455:1999	188, 189
	EN 10088-2:1995	368, 371		DIN 17456:1999	188, 189
X2NiCrMo18-15-4	EN 10088-2:1995	375, 384		EN 10028-7:2000	141, 142
X2NiCrMoCu25-20	AFNOR NF A 49-244:1993	233, 245		EN 10088-2:1995	368, 370
X2NiCrMoCu25-20-5	ISO 9327-5:1999	301, 306	X40Cr14	ISO 4957:1999	438
X30Cr13	EN 10088-2:1995	366, 367	X40CrMoV5-1	ISO 4957:1999	434
	EN 10088-3:1995	394, 396	X42 - PSL 1	API 5L-2004	246, 247
	EN 10151:2002	429	X42 - PSL 2	API 5L-2004	250, 253
	EN 10250-4:1999	313	X46 - PSL 1	API 5L-2004	246, 248
X30WCrV9-3	ISO 4957:1999	434	X46 - PSL 2	API 5L-2004	250, 253
X35CrWMoV5	ISO 4957:1999	434	X46Cr13	EN 10088-2:1995	414
X37CrMoV5-1	ISO 4957:1999	434		EN 10088-3:1995	416
X38CrMo16	ISO 4957:1999	438	X4CrMnNi18-8-7	AFNOR NF A 49-244:1993	263
X38CrMoV5-3	ISO 4957:1999	438	X4CrNi18-12	EN 10088-2:1995	373, 381
X39Cr13	EN 10088-2:1995	414		EN 10088-3:1995	401, 405
	EN 10088-3:1995	416	X4CrNiMo16-5-1	EN 10028-7:2000	156
	EN 10151:2002	429	-	EN 10088-2:1995	414
X39CrMo17-1	EN 10088-2:1995	414		EN 10088-3:1995	416
	EN 10088-3:1995	416		EN 10250-4:1999	313
X3CrAlTi18-2	EN 10005 3.1333 EN 10095:1999	414, 416	X50CrMoV15	EN 10088-2:1995	414
X3CrNb17	EN 10088-2:1995	368, 370		EN 10088-3:1995	416
ACCITACT	_14 10000 £.1000	300, 370		-	-

Steel Grade/Name	Specification Designation	Page	Steel Grade/Name	Specification Designation	Page
X52 - PSL 1	API 5L-2004	246, 248	X6CrNi23-14	ISO 4955:1994	374, 382,
X52 - PSL 2	API 5L-2004	251, 254	V00 N'05 00	EN 40000 7 0000	401, 405
X56 - PSL 1	API 5L-2004	246, 248	X6CrNi25-20	EN 10028-7:2000	143, 147
X56 - PSL 2	API 5L-2004	251, 254	X6CrNi25-21	ISO 4955:1994	374, 382, 401, 405
X5CrNi18-10	DIN 17455:1999	190, 193		ISO 9327-5:1999	299, 303
	DIN 17456:1999	190, 193	X6CrNiMo17-11-2	AFNOR NF A 49-244:1993	230, 241
	EN 10028-7:2000	143, 146	X6CrNiMoNb17-12-2	EN 10028-7:2000	144, 148
	EN 10088-2:1995	373, 380	7.00111111011017 12 2	EN 10088-2:1995	375, 384
	EN 10088-3:1995	400, 404		EN 10088-3:1995	416
	EN 10151:2002	429	X6CrNiMoTi17-12	ISO 9327-5:1999	300, 305
	EN 10222-5:1999	298, 302	X6CrNiMoTi17-12-2	EN 10028-7:2000	144, 148
	EN 10250-4:1999	298, 302	ACCITATION 11 12 2	EN 10088-2:1995	375, 384
X5CrNi18-9	ISO 9327-5:1999	298, 302		EN 10088-3:1995	402, 407
X5CrNiCuNb16-4	EN 10088-2:1995	387, 389		EN 10250-4:1999	300, 305
	EN 10088-3:1995	409, 410	X6CrNiN19-9	AFNOR NF A 49-244:1993	226, 236
	EN 10250-4:1999	307, 308	X6CrNiNb18-10	DIN 17455:1999	192, 195
X5CrNiMo17-12	ISO 9327-5:1999	299, 303	AUCHNIND 10-10	DIN 17455:1999 DIN 17456:1999	192, 195
X5CrNiMo17-12-2	DIN 17455:1999	191, 194		EN 10028-7:2000	145, 149
	DIN 17456:1999	191, 194		EN 10028-7.2000 EN 10088-2:1995	376, 386
	EN 10028-7:2000	143, 147		EN 10088-3:1995	
	EN 10088-2:1995	374, 383			402, 408
	EN 10088-3:1995	401, 406		EN 10222-5:1999	301, 306
	EN 10151:2002	429		EN 10250-4:1999	313
	EN 10222-5:1999	299, 303	V00-NIOINO-40-40	ISO 9327-5:1999	301, 306
	EN 10270-3:2001	437	X6CrNiSiNCe19-10	EN 10095:1999	414, 416
X5CrNiMo17-12-2	EN 10250-4:1999	299, 303	X6CrNiTi12	EN 10028-7:2000	141, 142
X5CrNiMo17-13	ISO 9327-5:1999	299, 303	V00-N:T:40-40	EN 10088-2:1995	414
X5CrNiMoCuNb14-5	EN 10088-3:1995	416	X6CrNiTi18-10	AFNOR NF A 49-244:1993	231, 242
X5CrNiN19-9	EN 10028-7:2000	143, 146		DIN 17455:1999	192, 195
X5NiCr32-21	AFNOR NF A 49-244:1993	233, 245		DIN 17456:1999	192, 195
X5NiCrAlTi31-20 (+RA)	EN 10028-7:2000	156		EN 10028-7:2000	145, 149
X60 - PSL 1	API 5L-2004	246, 248		EN 10088-2:1995	376, 386
X60 - PSL 2	API 5L-2004	251, 255		EN 10088-3:1995	402, 408
X65 - PSL 1	API 5L-2004	246, 248		EN 10222-5:1999	300, 306
X65 - PSL 2	API 5L-2004	252, 255		EN 10250-4:1999	300, 306
X6Cr13	EN 10088-2:1995	366, 367		ISO 9327-5:1999	300, 306
100110	EN 10088-3:1995	398, 399	X6CrNiTiB18-10	EN 10028-7:2000	145, 149
	ISO 4955:1994	366, 367,		EN 10222-5:1999	313
	100 1000.1001	398, 399	X6CrTi12	ISO 4955:1994	416
X6Cr17	DIN 17455:1999	188, 189	X6NiCrCuS18-9-2	EN 10088-3:1995	416
	DIN 17456:1999	188, 189	X6NiCrNbCe32-27	EN 10095:1999	414, 416
	EN 10088-2:1995	368, 370	X6NiCrSi36-19	ISO 4955:1994	416
	EN 10088-3:1995	398, 399	X6NiCrSiNCe35-25	EN 10095:1999	414, 416
	EN 10151:2002	437	X70 - PSL 1	API 5L-2004	246, 249
	EN 10250-4:1999	297	X70 - PSL 2	API 5L-2004	252, 256
	ISO 4955:1994	398, 399	X70CrMo15	EN 10088-3:1995	394, 397
X6CrAl13	DIN 17456:1999	188, 189	X7CrNi18-9	AFNOR NF A 49-244:1993	225, 234
	EN 10088-2:1995	368, 370		ISO 4955:1994	373, 380
	EN 10250-4:1999	313		ISO 9327-5:1999	298, 302
X6CrMo17-1	EN 10088-2:1995	368, 370	X7CrNiAl17-7	EN 10088-2:1995	387, 390
	EN 10088-3:1995	398, 399		EN 10088-3:1995	409, 411
X6CrMoNb17-1	EN 10088-2:1995	414		EN 10151:2002	429
X6CrMoS17	EN 10088-3:1995	398, 399		EN 10270-3:2001	437
X6CrNi17-1	EN 10088-2:1995	414	X7CrNiMo17-11-2	AFNOR NF A 49-244:1993	228, 238
X6CrNi18-10	EN 10086-2:1995 EN 10028-7:2000	143, 146	X7CrNiMo17-12	ISO 9327-5:1999	300, 305
VOCHNITO- IO	LIV 10020-1.2000	•			301, 306
	EN 10222-5:1000	208 302	V/C	EN 10222-5.1999	
X6CrNi23-13	EN 10222-5:1999 EN 10028-7:2000	298, 302 143, 147	X7CrNiNb18-10	EN 10222-5:1999 ISO 4955:1994	376, 386

X7CrNiNb18-10	Steel Grade/Name	Specification Designation	Page
X7CrNiSinCe21-11	X7CrNiNb18-10	ISO 9327-5:1999	
X7Cr/NiTi18-10 ISO 4955:1994 376, 386, 402, 408, 402, 408 X7Ni9 EN 10028-4:2003 300, 306 X80 - PSL 2 API 5L-2004 252, 256 X80rNi25-20 AFNOR NF A 49-244:1993 263 X80rNi25-21 EN 10095:1999 414, 416 X80rNiNbA15-7-2 EN 10088-2:1995 387, 391 X80rNiNb16-13 EN 10028-7:2000 145, 149 X80rNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 410 X80rNiTi18-10 EN 10095:1999 414, 416 X80rNiTi18-10 EN 10028-4:2003 135, 136 EN 10028-3:1999 414, 416 X8NiGrAITi32-21 EN 10028-7:2000 145, 150 ISO 9327-3:1999 289, 290 X8DCrNISINCe21-11-2 EN 10088-3:1995 416 X9DCrMoV18 EN 10088-3:1995 416 X9DCrNISINCe21-11-2 EN 10088-3:1999 414, 416 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 664-03 413			
March Marc			-
ISO 9327-5:1999 300, 306 X7Ni9 EN 10028-4:2003 135, 136 252, 256 X8CrNi25-20 AFNOR NF A 49-244:1993 263 X8CrNi25-21 EN 10095:1999 414, 416 X8CrNiMoAl15-7-2 EN 10088-2:1995 387, 391 X8CrNiNb16-13 EN 10028-7:2000 145, 144 162 X8CrNiNb16-13 EN 10028-2:1995 414 416 EN 10088-2:1995 414 416 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 ISO 9327-3:1999 289, 290 ISO 9327-3:1999 416 416 EN 10028-7:2000 145, 150 ISO 4955:1994 416 EN 10028-7:2000 415, 150 ISO 4955:1994 416 EN 10088-3:1995 416	X7CrNiTi18-10	ISO 4955:1994	
X7Ni9		ISO 0337 5:1000	,
X80 - PSL 2 API 5L-2004 252, 256 X8CrNi25-20 AFNOR NF A 49-244:1993 263 X8CrNiMoAl15-7-2 EN 10095:1999 414, 416 X8CrNiMoAl15-7-2 EN 10088-2:1995 387, 391 X8CrNiMo16-13 EN 10028-7:2000 145, 149 X8CrNiNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 400, 403, 424 X8CrNiTi18-10 EN 10095:1999 414, 416 X8Nig EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 ISO 9327-3:1999 289, 290 ISO 9327-3:1999 414, 416 X90crMoV18 EN 10028-7:2000 145, 150 X90crMoV18 EN 10088-3:1995 416 X90crMoV18 EN 10088-3:1995 416 XM-1 ASTM 276-03 415 XM-1 ASTM 276-03 415 XM-10 ASTM 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 664-03	VZNIO		
X8CrNi25-20 AFNOR NF A 49-244:1993 263 X8CrNi25-21 EN 10095:1999 414, 416 X8CrNiNohl6-13 EN 10088-2:1995 387, 391 X8CrNiNb16-13 EN 10088-2:1995 414 X8CrNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 400, 403, 424 X8CrNiS18-9 EN 10095:1999 414, 416 X8NiGrNiS18-9 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 ISO 9327-3:1999 289, 290 ISO 9327-3:1999 289, 290 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X90CrMiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM 475-03 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 669-03 413 XM-13 ASTM A 564/A 564M-02a 415 XM-14 ASTM A 260-03 413 XM-15			
X8CrNi25-21 EN 10095:1999 414, 416 X8CrNiMoAl15-7-2 EN 10088-2:1995 387, 391 X8CrNiNb16-13 EN 10028-7:2000 145, 149 X8CrNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 400, 403, 424 X8CrNiTi18-10 EN 10095:1999 414, 416 X8Ni9 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 X8NiCrAITi32-21 EN 10028-7:2000 145, 150 X90CrMoV18 EN 10088-3:1995 416 X90CrMoV18 EN 10095:1999 414, 416 X90CrMiSiNCe21-11-2 EN 10095:1999 414, 416 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 666-03 413 XM-13 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-14 ASTM A 213/A 213M-03a 261 XM-15 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 240/A 240M-03c			
X8CrNiMoAl15-7-2 EN 10088-2:1995 387, 391 X8CrNiNb16-13 EN 10028-7:2000 145, 149 X8CrNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 400, 403, 424 X8CrNiTi18-10 EN 10095:1999 414, 416 X8Ni9 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 3927-3:1999 289, 290 ISO 4955:1994 416 X90CrMoV18 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM 476-03 415 XM-1 ASTM A 276-03 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 666-03 413 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-13 ASTM A 666-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 240/A			
X8CrNiNb16-13 EN 10028-7:2000 145, 149 X8CrNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 400, 403, 424 X8CrNiTi18-10 EN 10095:1999 414, 416 X8Ni9 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 X8NiCrAITi32-21 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X90CrMiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM 4276-03 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-13 ASTM A 666-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 668-03 413 XM-16 ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 2			
X8CrNiS18-9 EN 10088-2:1995 414 EN 10088-3:1995 400, 403, 424 X8CrNiTi18-10 EN 10095:1999 414, 416 X8Ni9 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 X8NiCrAITi32-21 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM 476-03 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 666-03 413 XM-13 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-02a 415 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 <td< td=""><td></td><td></td><td></td></td<>			
EN 10088-3:1995 400, 403, 424 X8CrNiTi18-10 EN 10095:1999 414, 416 X8Ni9 EN 10028-4:2003 135, 136			-, -
X8CrNiTi18-10 EN 10095:1999 414, 416 X8Ni9 EN 10028-4:2003 135, 136 EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 X8NiCrAITi32-21 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X9CrNiSiNCe21-11-2 EN 10088-3:1995 416 X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 X5TM A 276-03 415 ASTM A 276-03 415 ASTM A 666-03 413 XM-10 ASTM A 276-03 415 ASTM A 693-03 413 XM-12 ASTM A 666-03 413 XM-13 ASTM A 666-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 693-03 413 XM-15 ASTM A 666-03 413 XM-16 ASTM A 213/A 213M-03a 261 ASTM A 693-03 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 313/A 313M-03 437 XM-19 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 260/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 693-03 413 ASTM A 276-03 415	VOCIINIO 10-9		
X8Ni9		EN 10066-3.1995	424
EN 10222-3:1998 289, 290 ISO 9327-3:1999 289, 290 X8NiCrAlTi32-21 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM A 276-03 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 666-03 413 XM-12 ASTM A 666-03 413 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-13 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 666-03 413 XM-16 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 XM-26 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415	X8CrNiTi18-10	EN 10095:1999	414, 416
ISO 9327-3:1999 289, 290 X8NiCrAlTi32-21 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X90CrNiSiNCe21-11-2 EN 10095:1999 414, 416 X45 A582/A 582M-95b (2000) XM-10 ASTM A 276-03 415 ASTM A 666-03 413 XM-11 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-12 ASTM A 666-03 413 XM-13 ASTM A 666-03 413 XM-13 ASTM A 666-03 413 XM-14 ASTM A 693-03 415 ASTM A 693-03 413 XM-15 ASTM A 666-03 413 XM-15 ASTM A 666-03 413 XM-16 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-16 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 260/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 260/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 2	X8Ni9	EN 10028-4:2003	
X8NiCrAlTi32-21 EN 10028-7:2000 145, 150 ISO 4955:1994 416 X90CrMoV18 EN 10088-3:1995 416 X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 668-03 413 XM-13 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-15 ASTM A 564/A 564M-02a 415 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 276-03 415 ASTM A 276-03 415 A		EN 10222-3:1998	289, 290
ISO 4955:1994		ISO 9327-3:1999	
X90CrMoV18 EN 10088-3:1995 416 X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM A 582/A 582M-95b (2000) 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-11 ASTM A 666-03 413 XM-12 ASTM A 693-03 413 XM-13 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 666-03 413 XM-16 ASTM A 213/A 213M-03a 261 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 XM-21 ASTM A 276-03 400, 405 XM	X8NiCrAlTi32-21	EN 10028-7:2000	145, 150
X9CrNiSiNCe21-11-2 EN 10095:1999 414, 416 XM-1 ASTM 415 XM-10 ASTM A 276-03 415 XM-11 ASTM A 276-03 415 XM-12 ASTM A 666-03 413 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-13 ASTM A 693-03 413 XM-14 ASTM A 693-03 413 XM-15 ASTM A 666-03 413 XM-16 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 400, 405 XM-21 ASTM A 276-03 <td< td=""><td></td><td>ISO 4955:1994</td><td>416</td></td<>		ISO 4955:1994	416
XM-1	X90CrMoV18	EN 10088-3:1995	416
XM-10 XM-10 ASTM A 276-03 XM-11 ASTM A 276-03 ASTM A 666-03 XM-12 ASTM A 666-03 XM-12 ASTM A 693-03 XM-13 XM-13 XM-13 ASTM A 693-03 XM-14 ASTM A 693-03 XM-15 ASTM A 693-03 XM-15 ASTM A 693-03 XM-15 ASTM A 693-03 XM-16 ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c ASTM A 693-03 XM-17 ASTM A 693-03 XM-18 XM-19 ASTM A 240/A 240M-03c ASTM A 240/A 240M-03c ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 ASTM A 276-03 XM-21 ASTM A 256/A 564M-02a ASTM A 276-03 ASTM A 276-03 XM-25 ASTM A 276-03 ASTM A 276-03 ASTM A 276-03 XM-26 ASTM A 276-03 ASTM A 276-0	X9CrNiSiNCe21-11-2	EN 10095:1999	414, 416
XM-10 XM-11 ASTM A 276-03 ASTM A 666-03 XM-12 ASTM A 564/A 564M-02a ASTM A 693-03 XM-13 XM-13 ASTM A 693-03 XM-14 ASTM A 666-03 XM-15 ASTM A 666-03 ASTM A 564/A 564M-02a ASTM A 693-03 XM-14 ASTM A 666-03 XM-15 ASTM A 666-03 XM-15 ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 693-03 ASTM A 313/A 313M-03 ASTM A 313/A 313M-03 ASTM A 240/A 240M-03c 156, 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 ASTM A 276-03 XM-21 ASTM A 276-03 ASTM A 276-03 ASTM A 276-03 ASTM A 276-03 XM-25 ASTM A 264/A 564M-02a 415 ASTM A 276-03 ASTM A 276	XM-1	ASTM	415
XM-11 ASTM A 276-03 415 ASTM A 666-03 413 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-13 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 2213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 2513/A 213M-03a 261 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 400, 405 XM-21 ASTM A 264/A 264M-02a 415 ASTM A 276-03 400, 405 XM-25 ASTM A 264/A 564M-02a 415 ASTM A 276-03 415		` ,	
XM-12 ASTM A 666-03 413 XM-12 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-13 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 693-03 413 XM-16 ASTM A 693-03 413 XM-17 ASTM A 693-03 413 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 693-03 413 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 XM-29 ASTM A 276-03 415			
XM-12	XM-11		_
XM-13 ASTM A 693-03 ASTM A 693-03 XM-14 ASTM A 666-03 XM-15 ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c ASTM A 693-03 XM-16 ASTM A 693-03 XM-16 ASTM A 564/A 564M-02a ASTM A 693-03 ASTM A 693-03 ASTM A 313/A 313M-03 ASTM A 313/A 313M-03 ASTM A 240/A 240M-03c 156, 413 XM-17 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 ASTM A 358/A 358M-01 262 XM-2 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 ASTM A 276-03 XM-21 ASTM A 264/A 564M-02a 415 ASTM A 693-03 XM-25 ASTM A 693-03 XM-26 ASTM A 564/A 564M-02a 415 ASTM A 276-03 400, 405 XM-27 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 ASTM A 276-03 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 ASTM A 258/A 358M-01 262	V44.40		_
XM-13 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 276-03 415 ASTM A 358/A 358M-01 262 XM-2 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 400, 405 XM-21 ASTM A 276-03 415 ASTM A 276-03 415 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 276-03 415 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 XM-28 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415	XM-12		
ASTM A 693-03 413 XM-14 ASTM A 666-03 413 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 276-03 415 ASTM A 358/A 358M-01 262 XM-2 ASTM A 240/A 240M-03c 156, 413 XM-21 ASTM A 240/A 240M-03c 156, 413 XM-25 ASTM A 240/A 240M-03c 156, 413 XM-26 ASTM A 276-03 400, 405 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 XM-29 ASTM A 276-03 415 ASTM A 276-03 415 XM-29 ASTM A 276-03 415	V44.45		-
XM-14 XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 240/A 240M-03c 156, 413 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 400, 405 XM-21 ASTM A 276-03 400, 405 XM-25 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415	XM-13		-
XM-15 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 240/A 240M-03c 156, 413 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 400, 405 XM-21 ASTM A 276-03 400, 405 XM-25 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 XM-28 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 276-03 415	VM 44		_
ASTM A 240/A 240M-03c 156, 413 XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262 XM-2 ASTM A 240/A 240M-03c 156, 413 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415			_
XM-16 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 240/A 240M-03c 156, 413 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 400, 405 XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 276-03 415 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415	XIVI-15		-
ASTM A 693-03 413 ASTM A 313/A 313M-03 437 XM-17 ASTM A 240/A 240M-03c 156, 413 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a 261 ASTM A 276-03 415 ASTM A 240/A 240M-03c 156, 413 ASTM A 358/A 358M-01 262 XM-2 ASTM A 240/A 240M-03c 156, 413 XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 276-03 415 ASTM A 276-03 415 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 XM-28 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415	VM 40		
ASTM A 313/A 313M-03	XIVI-16		-
XM-17 XM-18 ASTM A 240/A 240M-03c 156, 413 XM-19 ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c 156, 413 ASTM A 213/A 213M-03a 261 ASTM A 276-03 ASTM A 276-03 XM-2 XM-2 ASTM A 25/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c ASTM A 276-03 ASTM A 276-03 ASTM A 276-03 XM-25 ASTM A 564/A 564M-02a ASTM A 693-03 XM-26 ASTM A 276-03 XM-27 ASTM A 240/A 240M-03c ASTM A 276-03 XM-28 ASTM A 276-03 ASTM A 276-03 XM-27 ASTM A 276-03 ASTM A 276-03 XM-27 ASTM A 240/A 240M-03c ASTM A 276-03 ASTM A 276-03 ASTM A 276-03 XM-28 ASTM A 276-03 ASTM A 358/A 358M-01			-
XM-18 XM-19 ASTM A 240/A 240M-03c ASTM A 213/A 213M-03a ASTM A 240/A 240M-03c ASTM A 276-03 ASTM A 358/A 358M-01 XM-2 XM-2 ASTM A 240/A 240M-03c ASTM A 358/A 358M-01 262 XM-2 XM-2 ASTM A 582/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c ASTM A 276-03 ASTM A 276-03 XM-25 ASTM A 564/A 564M-02a ASTM A 693-03 XM-26 ASTM A 276-03 XM-27 ASTM A 240/A 240M-03c ASTM A 276-03 XM-27 ASTM A 276-03 ASTM A 276-03 XM-27 ASTM A 276-03 ASTM A 276-03 XM-28 ASTM A 276-03 ASTM A 240/A 240M-03c ASTM A 276-03 ASTM A 358/A 358M-01 262	VM 17		
XM-19 ASTM A 213/A 213M-03a 261 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262 XM-2 ASTM A 25/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 XM-27 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 358/A 358M-01 262			
ASTM A 240/A 240M-03c			,
ASTM A 276-03 415 ASTM A 358/A 358M-01 262 XM-2 ASTM A 582/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	VIAL- IA		
ASTM A 358/A 358M-01 262 XM-2 ASTM A 582/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415			
XM-2 ASTM A 582/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262			
A 582/A 582M-95b (2000) XM-21 ASTM A 240/A 240M-03c ASTM A 276-03 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 ASTM A 358/A 358M-01 262	YM-2		
XM-21 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 400, 405 XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	Alvi-2		415
XM-25 ASTM A 564/A 564M-02a 415 ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	XM-21		156, 413
ASTM A 693-03 413 XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262		ASTM A 276-03	400, 405
XM-26 ASTM A 276-03 415 XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	XM-25	ASTM A 564/A 564M-02a	415
XM-27 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262		ASTM A 693-03	413
ASTM A 276-03 398, 399 XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	XM-26	ASTM A 276-03	415
XM-28 ASTM A 276-03 415 ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	XM-27	ASTM A 240/A 240M-03c	156, 413
ASTM A 313/A 313M-03 437 XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262		ASTM A 276-03	398, 399
XM-29 ASTM A 240/A 240M-03c 156, 413 ASTM A 276-03 415 ASTM A 358/A 358M-01 262	XM-28	ASTM A 276-03	415
ASTM A 276-03 415 ASTM A 358/A 358M-01 262		ASTM A 313/A 313M-03	437
ASTM A 358/A 358M-01 262	XM-29	ASTM A 240/A 240M-03c	156, 413
		ASTM A 276-03	415
XM-30 ASTM A 276-03 415		ASTM A 358/A 358M-01	262
	XM-30	ASTM A 276-03	415

Steel Grade/Name	Specification Designation	Page
XM-31	ASTM A 240/A 240M-03c	156, 413
XM-33	ASTM A 240/A 240M-03c	156, 413
XM-34	ASTM	415
XM-5	A 582/A 582M-95b (2000) ASTM	415
XM-6	A 582/A 582M-95b (2000) ASTM	415
7441 0	A 582/A 582M-95b (2000)	110
XM-9	ASTM A 693-03	413
Z 10 CNWT 17-13 B	AFNOR NF A 49-214:1978	263
Z 100 CD 6 1-M	AFNOR NF A 32-058:1984	360
Z 160 CDV 12-M	AFNOR NF A 32-058:1984	360
Z 200 C 12-M	AFNOR NF A 32-058:1984	360
Z 270 C 27-M	AFNOR NF A 32-058:1984	360
Z 280CD 16 3-M	AFNOR NF A 32-058:1984	360
Z 320 CD 16 3-M	AFNOR NF A 32-058:1984	360
Z 3CN13.4-M	AFNOR NF A 32-053:1992	339, 340
Z 5CN19.10-M	AFNOR NF A 32-053:1992	341, 344
Z 6 CN 19-10	AFNOR NF A 49-214:1978	227, 236
Z 6 CN Nb 18-12 B	AFNOR NF A 49-214:1978	233, 244
Z 6 CND 17-12 B	AFNOR NF A 49-214:1978	230, 240
Z 6 CNT 18-12 B	AFNOR NF A 49-214:1978	232, 243
Z 8 CNDT 17-13 B	AFNOR NF A 49-214:1978	230, 241
Z100MD8 1-M	AFNOR NF A 32-058:1984	328, 329
Z100MN13 4-M	AFNOR NF A 32-058:1984	328, 329
Z110MD12 1-M	AFNOR NF A 32-058:1984	328, 329
Z120M12-M	AFNOR NF A 32-058:1984	328, 329
Z120MC12-M	AFNOR NF A 32-058:1984	328, 329
Z120MC17 2-M	AFNOR NF A 32-058:1984	328, 329

UNS NUMBER INDEX

602 UNS Number Index

UNS Number	Page Number	UNS Number	Page Number
G10050	23	G11090	43, 420
G10060	23	G11094	423
G10080	23, 165, 166, 168, 169, 176, 177, 178, 179	G11100	43, 170, 180, 420
G10090	44	G11150	257
G10100	23, 165, 166, 167, 168, 169, 176, 177, 178, 179,	G11160	43, 436
0.0	180	G11170	43, 257, 420
G10110	43, 170, 180	G11174	423
G10120	23	G11180	43, 420
G10130	43, 44	G11190	43, 436
G10150	24, 165, 166, 168, 169, 170, 171, 176, 177, 178,	G11260	436
G10160	179, 181 24, 171, 181	G11320	43, 436
G10170	24, 171, 181	G11370	43, 420
G10170	24, 171, 181	G11374	423
G10190	24, 44	G11380	420
G10190	25, 166, 167, 169, 170, 171, 172, 177, 178, 179,	G11390	43, 420
G10200	180, 181, 182	G11400	43, 421
G10210	25, 167, 169, 171, 172, 177, 178, 180, 181, 182	G11410	43, 421
G10220	25	G11414	423
G10230	25	G11440	43, 421
G10250	26, 167, 168, 170, 171, 172, 173, 178, 180, 181,	G11444	423
	182	G11450	43, 421, 436
G10260	26, 169, 171, 173, 179, 181, 182, 183	G11460	43, 421
G10290	26	G11464	423
G10300	26, 169, 170, 171, 173, 174, 179, 180, 181, 183,	G11510	43, 421
0.10000	437	G11700	420
G10330	44	G12110	43, 436
G10340	27,	G12120	43, 422
G10350	27, 169, 170, 171, 173, 174, 179, 180, 181, 182,	G12130	43, 422
G10370	183, 184, 437 27, 44	G12134	424
G10380	27	G12144	424
G10390	28	G12150	43, 422
G10400	28, 170, 171, 174, 180, 181, 183, 184, 425	G12154	424
G10420	28	G13300	43, 44, 257
G10430	28	G13350	43, 44, 257
G10440	29	G13400	43, 44, 257
G10450	29, 170, 172, 174, 180, 182, 183, 184, 437	G13450	43, 44, 257
G10460	29	G15180	43
G10490	30	G15220	34
G10500	30, 171, 173, 174, 181, 182, 183, 425	G15240	43, 44, 171, 174, 181, 183, 184
G10530	30	G15250	43
G10550	31, 425	G15260	43, 44
G10590	31	G15270	43, 44
G10600	31, 425	G15300	43
G10640	32, 425	G15360	34, 44
G10650	32, 425	G15410	34
G10690	32	G15470	43, 44
G10700	32, 425	G15480	43, 44
G10710	32	G15510	43
G10740	32, 44, 425	G15520	43, 44
G10750	32, 44	G15610	43
G10780	32, 425	G15660	43, 44
G10800	33, 437	G15720	43
G10840	33, 44, 426	G31400	258
G10850	44, 426	G33106	258
G10860	33, 426	G40120	43, 258
G10900	33	G40230	43, 44, 258
G10950	33, 426	G40240	43, 258
G11080	436	G40270	43, 44, 258

UNS Number	Page Number	UNS Number	Page Number
G40280	43, 185, 186	G51500	43, 44, 258
G40370	43, 44, 258	G51550	43, 258, 427
G40420	43, 258	G51600	43, 44, 258, 427, 439
G40470	43, 44, 258	G51601	41, 428
G40630	258	G51950	439
G41180	37, 258	G51986	258
G41200	37	G52986	44, 258
G41210	37	G61180	
G41300			43, 258
	37, 185, 186 42, 44, 195, 197	G61200	258
G41350	43, 44, 185, 187	G61500	42, 258, 428
G41370	38, 185, 187	G81150	43, 258
G41400	38, 185, 187	G81451	43, 258
G41420	43, 44, 185, 187	G86150	43, 44, 258
G41450	38, 257	G86170	43, 44, 258
G41470	43, 258	G86200	39, 258
G41500	38, 258	G86220	43, 44, 258
G41610	428	G86250	43, 44, 258
G41670	43	G86270	43, 44, 258
G43200	39, 258	G86300	43, 44, 258
G43320	43	G86370	43, 44, 258
G43370	258	G86400	39, 258
G43376	258	G86420	43, 258
G43400	39, 258	G86450	43, 44, 258
G43406	39, 258	G86451	258
	43		
G44190		G86500	43, 258
G44220	43, 258	G86550	43, 44, 258
G44270	43, 258	G86600	43, 258
G45200	258	G87200	43, 44, 258
G46150	43, 258	G87350	258
G46170	44, 258	G87400	43, 44, 258
G46180	44	G87420	258
G46200	43, 44, 258	G88200	43, 44
G46210	43, 258	G88220	258
G46260	43	G92540	43, 44
G47150	43	G92550	43, 258
G47180	43, 258	G92590	43, 44
G47200	43, 258	G92600	43, 44, 258, 427
G48150	43, 258	G92620	258
G48170	43, 258	G93106	39, 258
G48200	43, 44, 258	G94151	258
G50150	43, 258	G94171	43, 258
G50401	258	G94301	43, 258
G50441			
	41, 258	G94401	258
G50460	43, 258	G98400	258
G50461	41, 258	G98500	258
G50501	41, 258	J02500	319, 323
G50601	41, 258	J02501	320, 323
G50611	258	J02502	326
G50986	258	J02503	326, 327
G51150	43, 44, 258	J02504	327
G51170	43	J02505	327
G51200	35, 258	J03000	319, 323
G51300	35, 258	J03001	319, 323
G51320	35, 258	J03002	326, 327
G51350	35, 258	J03003	327
G51400	36, 258	J03501	320, 323
G51450	258	J11872	360
G51450 G51470	43, 258	J12072	335, 336
G51470	TU, ZUU	012012	000, 000

604 UNS Number Index

J12080	UNS Number	Page Number	UNS Number	Page Number
J12984 390	J12080	360	J92605	351, 355
J12084 360 J92615 361 J12522 337, 338 J92710 341, 344, 349, 350 J12522 337, 338 J92803 342, 445, 349, 350 J12522 359 J92803 351, 356 J17802 360 J92801 361, 345, 349, 350 J13005 360 J92801 361 J13047 360 J92871 361 J13080 380 J92872 361 J13081 380 J92891 342, 345, 361 J13085 380 J92891 342, 446, 361 J13856 380 J93800 381, 355 J13850 380 J93800 381, 355 J22800 380 J93800 381, 355 J22801 335, 336 J93800 381, 356 J22802 360 J93801 381, 356 J22803 337, 338 J93401 381 J22804 343, 346, 361 382, 356 J22805 382, 386 J93401	J12082	360	J92613	351, 355
J1292 335, 336	J12084	360	J92615	361
J12522 337, 338 J92710 341, 344, 349, 350 J12524 359 J92803 351, 356 J13002 360 J92803 351, 356 J13005 360 J92801 341, 345, 349, 350 J13047 380 J92972 361 J13047 380 J92972 361 J13045 380 J92972 361 J13045 380 J92091 342, 346, 361 J13045 380 J93000 342, 346, 361 J15860 380 J93001 361 J15860 380 J93001 351, 355 J22000 960 J93015 351, 355 J22001 337, 338 J93003 382, 356 J22001 337, 338 J9300 361 J32001 360 J93400 361 J31300 361 393 366 J31300 361 393 366 J31400 361 361 361	J12092	335, 336		361
J12824 335, 336 J98800 J42, 345, 349, 350 J12832 369 J92800 341, 345, 349, 350 J13006 360 J92801 341, 345, 349, 350 J13047 360 J92891 361 J134361 380 J92892 342, 346, 361 J13455 380 J93000 342, 345, 361 J1855 380 J93000 342, 345, 361 J18585 380 J93001 351, 355 J22000 385, 336 J93015 351, 355 J22001 335, 336 J93015 351, 355 J22002 397, 388 J83070 349, 350 J22015 380 J93015 351, 366 J22016 387, 388 J8300 361 J22017 387, 388 J8300 361 J2201 387, 388 J83010 361 J31200 360 J93101 361 J31200 360 J9301 361 J31200 361, 366		337, 338		
J12582 359				
J13002 360 J22901 341, 345, 349, 350 J13047 360 J2291 36				
J15005 360 J25971 361 J15080 J25971 361 J15080 360 J25971 361 J15080 360 J25972 361 J15080 360 J25972 361 J15080 360 J25972 361 J15080 360 J25989 342, 345, 361 J15580 360 J25090 342, 345, 361 J25080 355, 336 J25000 361 355 355 J25000 360 J25080 351, 355 J25000 353, 336 J25080 351, 355 J25080 353, 336 J25080 351, 355 J25080 351, 356 J25080 J25080				
J19047 \$60				
J13080 360 J92972 361 J92111 361 J92896 342, 346, 361 J1385 360 J93000 342, 345, 361 J1385 360 J93000 342, 345, 361 J15880 360 J93001 361 J93001 362 J93001				
J1345 360 J92999 342, 346, 361 J13855 360 J93001 361 351, 355 J22991 335, 336 J93001 361, 355 J22901 335, 336 J93015 351, 355 J22901 335, 336 J93254 343, 346, 361 J22902 369 J93303 362, 356 J93270 349, 350 J22500 337, 338 J93400 361 J22501 379, 338 J93400 361 J22501 379, 338 J93400 361 J32015 360 J93401 361 J32015 360 J93403 351, 356 J32015 J32015 379, 338 J93423 361 J31575 322, 325 J93503 J93433 352, 356 J32015 J32				
J1855 S60 J93000 342, 345, 361 J18580 380 J93001 361 J21800 335, 336 J9305 351, 355 J22200 360 J9303 352, 356 J22202 S59 J9303 352, 356 J22250 337, 338 J9337 348, 361 J22250 337, 338 J9337 348, 361 J31200 360 J93401 361 J31200 360 J93402 342, 346, 361 J31300 359 J93403 351, 356 J31500 337, 338 J93413 352, 356 J41500 359 J93633 352, 356 J4215 357, 338 J9403 352, 356 J4220 359 J93633 352, 356 J42215 337, 338 J9403 352, 356 J42215 337, 338 J9403 352, 356 J42220 359 J94020 361 J82000 338, 339 J9423 351 J82000 338, 339 J9423 352, 356 J82000 338, 339 J9423 352, 356 J82000 338, 339 J9423 352, 356 J82100 360 J94203 352, 356 J82100 360 J94204 352, 357 J91109 328, 329 J94214 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94561 343, 346, 361 J91149 328, 329 J94561 343, 346, 361 J9115 339, 340, 360 K01200 C06, 210 J9115 347, 348 K01700 153 J9115 347, 348 K01700 153 J91149 328, 329 K01800 153 J91159 328, 329 K01800 153 J9139 328, 329 K01800 163 J91404 361 K02000 64, 71 J9115 347, 348 K02000 171, 181 J91404 361 K02000 171, 181 J9150 347, 348 K02000 171, 181 J91409 339, 340, 347, 348 K02000 171, 181 J91409 339, 340, 347, 348 K02000 171, 181 J91400 339, 340, 347, 348 K02000 171, 181 J91400 339, 340, 347, 348 K02000 171, 181 J91500 341, 344, 349, 350 K02204 65				
J1580				
Jacob Jaco				
J22000 360 J3301 J3315 351, 355 J22092 359 J3303 352, 356 J33254 J33, 346, 361 J32092 J357, 338 J39370 349, 350 J323015 360 J39401 361 J31200 360 J39401 361 J31300 359 J39403 J39403 351, 356 J31500 337, 338 J39413 351, 356 J31500 337, 338 J39413 351, 356 J31575 322, 325 J39503 J39413 351, 356 J31575 322, 325 J39503 J39503 352, 356 J41501 359 J39503 352, 356 J42045 335, 336 J39633 352, 356 J42045 353, 336 J39633 352, 356 J42045 353, 336 J39633 352, 356 J42045 353, 336 J39633 352, 356 J42045 359 J39603 352, 356 J42045 352, 356 J420				
J22001 335, 336 J36254 343, 346, 361 J22501 337, 338 J93400 361 J22501 337, 338 J93400 361 J22501 337, 338 J93400 361 J31200 360 J93402 342, 346, 361 J31300 359 J93403 351, 356 J31500 337, 338 J93413 351, 356 J31501 337, 338 J93413 351, 356 J31500 337, 338 J93413 351, 356 J31500 359 J93503 352, 356 J41500 359 J93503 352, 356 J41500 359 J93603 352, 356 J42045 335, 336 J93633 352, 356 J42045 335, 336 J93633 352, 356 J42206 359 J94003 352, 356 J42207 359 J94003 352, 356 J42208 359 J94003 352, 356 J42209 359 J94003 352, 356 J42200 359 J94003 352, 356 J42215 337, 338 J94013 352, 356 J42216 335, 336 J9403 352, 356 J42217 339, 340, 340 J94202 361 J4218 328, 329 J94214 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94651 343, 346, 361 J91130 328, 329 J94651 343, 346, 361 J91149 328, 329 J94651 343, 346, 361 J91151 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 347, 348 J94651 343, 346, 361 J91152 339, 340, 347, 348 J94651 343, 346, 361 J91154 361 K01600 59, 70 J91155 339, 340, 347, 348 K01700 153 J91130 328, 329 K01800 153 J91330 328, 329 K01800 153 J91340 328, 329 K01800 154 J91350 347, 348 K02005 717, 181 J91450 339, 340, 347, 348 K02006 717, 181 J91550 347, 348 K02006 717, 181 J91550 341, 344, 349, 350 K02204				
192002 359				
J22500 337, 338 J93370 349, 350 J92501 37, 338 J93401 361 J92601 361 J93401 361 J93401 361 J93402 342, 346, 361 J93403 351, 356 J93403 352, 356 J93403 J93403 J93403 J93403 J93403 J93403 J93403				
J22501 337, 338 J93400 361 J93401 361 J93401 361 J93402 342, 346, 361 J93403 351, 356 J93403 352, 356 J93503 352, 356 J93503 352, 356 J93603 351, 356 J93603 352, 356 J93603 J936030 J93603 J93603 J93603 J93603 J93603 J93603 J936030 J93603 J93603 J93603 J93603 J93603 J93603 J9360				
J23015 360		·		
J31200 360 J93402 342, 346, 361 J31300 359 J93403 351, 356 J31500 337, 338 J93413 351, 356 J31575 322, 325 J93503 352, 356 J41501 359 J93513 352, 356 J41501 359 J93603 351, 356 J42065 359, 336 J93633 352, 356 J42215 337, 338 J94013 352, 356 J422215 337, 338 J94013 352, 356 J422215 337, 338 J94013 352, 356 J42220 359 J94020 361 J82090 359, 336 J94203 352, 356 J82090 359, 329 J94203 352, 356 J82090 361 J94204 352, 357 J91119 328, 329 J94214 353, 367 J91119 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91151 339,				
J31500 359 J3413 351, 356 J35150 337, 338 J3413 351, 356 J31575 322, 325 J3357 J33513 352, 356 J351575 322, 325 J351575 J351313 352, 356 J41501 359 359 359 J41501 359 359 359 J41501 359				
J31500 337, 338 J93423 351, 356 J31575 322, 325 J93503 352, 356 J41500 359 J93603 352, 356 J41501 359 J93603 352, 356 J42065 359 J93603 352, 356 J42065 359 J94003 352, 356 J42206 359 J94003 352, 356 J42200 358, 336 J94013 352, 356 J42200 358, 336 J94013 352, 356 J82000 353, 336 J94202 361 J94202 361 J94204 352, 357 J91119 328, 329 J94204 352, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94224 352, 366 J91139 328, 329 J94650 361 J91149 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 342, 346 349, 346, 361 J91151 339, 340, 360 K01200 206, 210 J91154 361 K01800 153 J91139 328, 329 K01800 153 J91309 328, 329 K01800 77, 75 J91429 328, 329 K01800 153 J91309 328, 329 K01800 153 J91300 328, 329 K01800 153 J91300 339, 340, 347, 348 K02005 171, 181 J91550 341, 344 K02003 114, 116 K02200 153 J92500 341, 344, 3				
J31550 337, 338 J93423 361 J31575 322, 325 J93503 352, 356 J41501 359 J93603 351, 356 J42045 335, 336 J93603 351, 356 J42085 359 J94003 352, 356 J42215 337, 338 J94013 352, 356 J42220 359 J94202 361 J82090 335, 336 J94203 352, 356 J84090 360 J94204 352, 357 J91109 328, 329 J94213 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94244 352, 356 J91199 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 347, 348 J94652 342, 346 J91154 361 K01600 59, 70 J911249 328, 329 K01700 153 J91349 32				
J31575 322, 325 J93503 352, 356 J41500 359 J93603 351, 356 J42045 335, 336 J93603 351, 356 J42045 335, 336 J93603 351, 356 J42045 335, 336 J94003 352, 356 J42065 359 J94003 352, 356 J42020 359 J94013 352, 356 J42020 359 J94003 352, 356 J94003 352, 356 J82090 335, 336 J94003 352, 356 J94003 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94254 352, 356 J91139 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340, 360 K01200 206, 210 J91154 361 K01600 59, 70 J91149 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91309 328, 329 K01800 153 J91309 328, 329 K01800 153 J91309 328, 329 K01802 72, 75 J91340 339, 340, 347, 348 K02004 171, 181 J91550 347, 348 K02005 171, 181 J91550 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91604 361 K02200 36				
J41500 359 J93613 352, 356 J41501 359 J93603 351, 356 J42045 335, 336 J93603 352, 356 J42215 337, 338 J94003 352, 356 J42220 359 J94202 361 J82090 335, 336 J94203 352, 356 J84090 360 J94204 352, 357 J91119 328, 329 J94213 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94224 352, 356 J91149 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91154 361 K01600 59, 70 J91157 347, 348 K01700 153 J91309 328, 329 K01800 153 J91340 328, 329 K01800 72, 75 J91340 328, 329 </td <td></td> <td></td> <td></td> <td></td>				
J41501 359 J93603 351, 356 J42045 335, 336 J93633 352, 356 J42045 359 J94003 352, 356 J42215 337, 338 J94013 352, 356 J42220 359 J94202 361 J82090 335, 336 J94203 352, 356 J84090 360 J94204 352, 357 J911199 328, 329 J94214 353, 357 J911191 328, 329 J94244 352, 356 J91139 328, 329 J94650 361 J911491 328, 329 J94650 361 J911501 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340, 347, 348 K01200 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91309 328, 329 K01800 153 J91340 <td< td=""><td></td><td></td><td></td><td></td></td<>				
J42045 335, 336 J93633 352, 356 J42065 359 J94003 352, 356 J42210 359 J94131 352, 356 J82090 335, 336 J94203 352, 356 J84090 360 J94204 352, 357 J91109 328, 329 J94214 353, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94650 361 J91139 328, 329 J94650 361 J91149 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 347, 348 J94652 342, 346 J91154 361 K01200 206, 210 J91157 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91340 328, 329 K01800 153 J91340 328, 3				
J42065 359 J94003 352, 356 J42215 337, 338 J94013 352, 356 J42220 359 J94202 361 J82090 335, 336 J94203 352, 356 J84090 360 J94204 352, 357 J91119 328, 329 J94214 353, 357 J91119 328, 329 J94244 353, 357 J91119 328, 329 J94650 361 J91119 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01200 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91309 328, 329 K01701 113, 115 J91339 328, 329 K01800 72, 75 J91340 328, 329 K01800 72, 75 J91340 328, 32	J42045			
J42215 337, 338 J94013 352, 356 J42220 359 J94202 361 J82090 335, 336 J94204 352, 356 J84090 360 J94204 352, 357 J911109 328, 329 J94213 353, 357 J91119 328, 329 J94214 352, 356 J91139 328, 329 J94650 361 J91149 328, 329 J94650 361 J91150 339, 340, 347, 348 J94652 343, 346, 361 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91309 328, 329 K01701 113, 115 J91339 328, 329 K01800 153 J91340 328, 329 K01807 206, 210 J91429 361 K02002 64, 71 J91459 328,	J42065	359	J94003	352, 356
J42220 359 J94202 361 J82090 335, 336 J94203 352, 356 J84090 360 J94204 352, 357 J91109 328, 329 J94214 353, 357 J91119 328, 329 J94214 353, 357 J91139 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01800 153 J91339 328, 329 K01800 153 J91340 328, 329 K01800 153 J91459 328, 329 K01802 72, 75 J91459 328, 329 K01802 72, 75 J91459 328, 329 K02004 171, 181 J91550 347, 34	J42215	337, 338	J94013	
J84090 360 J94204 352, 357 J91109 328, 329 J94213 353, 357 J91119 328, 329 J94214 353, 357 J91129 328, 329 J94244 352, 356 J91139 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01800 153 J91339 328, 329 K01800 153 J91340 328, 329 K01800 206, 210 J91429 361 K02002 64, 71 J91459 328, 329 K01801 171, 181 J9150 347, 348 K02005 171, 181 J91803	J42220		J94202	
J91109 328, 329 J94213 353, 357 J91119 328, 329 J94214 353, 357 J91129 328, 329 J9450 361 J91139 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91309 328, 329 K01800 153 J91309 328, 329 K01800 153 J91340 328, 329 K01802 72, 75 J91340 328, 329 K01807 206, 210 J91459 328, 329 K01807 206, 210 J91459 328, 329 K02004 171, 181 J9150 347, 348 K02005 171, 181 J9150 <t< td=""><td>J82090</td><td>335, 336</td><td>J94203</td><td>352, 356</td></t<>	J82090	335, 336	J94203	352, 356
J91119 328, 329 J9424 353, 357 J91129 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91339 328, 329 K01802 72, 75 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590	J84090	360	J94204	352, 357
J91129 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91339 328, 329 K01800 72, 75 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K0203 114, 116 J92500	J91109	328, 329	J94213	353, 357
J91139 328, 329 J94650 361 J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01800 153 J91339 328, 329 K01800 153 J91340 328, 329 K01802 72, 75 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02002 64, 71 J91550 347, 348 K02005 171, 181 J91803 361 K02100 104, 109 J91804 361 K0200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 34	J91119	328, 329	J94214	353, 357
J91149 328, 329 J94651 343, 346, 361 J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01600 59, 70 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91339 328, 329 K01800 153 J91340 328, 329 K01802 72, 75 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J9150 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K0200 153 J92500 341, 344 K02203 114, 116 J92500 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91129	328, 329	J94224	352, 356
J91150 339, 340, 347, 348 J94652 342, 346 J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91139	328, 329	J94650	361
J91151 339, 340, 360 K01200 206, 210 J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01800 153 J91309 328, 329 K01800 153 J91339 328, 329 K01802 72, 75 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02005 171, 181 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91149	328, 329	J94651	343, 346, 361
J91153 339, 340 K01201 206, 210 J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91340 328, 329 K01802 72, 75 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91150	339, 340, 347, 348	J94652	342, 346
J91154 361 K01600 59, 70 J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91339 328, 329 K01802 72, 75 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91151	339, 340, 360	K01200	206, 210
J91171 347, 348 K01700 153 J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91339 328, 329 K01802 72, 75 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91153	339, 340	K01201	206, 210
J91249 328, 329 K01701 113, 115 J91309 328, 329 K01800 153 J91339 328, 329 K01802 72, 75 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91154	361	K01600	59, 70
J91309 328, 329 K01800 153 J91339 328, 329 K01802 72, 75 J91420 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				153
J91339 328, 329 K01802 72, 75 J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91540 339, 340, 347, 348 K02004 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91249	328, 329	K01701	113, 115
J91340 328, 329 K01807 206, 210 J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91309		K01800	
J91422 361 K02002 64, 71 J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68	J91339	328, 329	K01802	
J91459 328, 329 K02004 171, 181 J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J91540 339, 340, 347, 348 K02005 171, 181 J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J91550 347, 348 K02007 114, 116 J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J91803 361 K02100 104, 109 J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J91804 361 K02200 153 J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J92500 341, 344 K02203 114, 116 J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J92590 361 K02204 65, 71 J92600 341, 344, 349, 350 K02301 54, 68				
J92600 341, 344, 349, 350 K02301 54, 68				
J920U2 341, 344 KU24U1 54, 68, 104, 109				
	J92002	041, 044	NU∠4U I	54, 66, 104, 109

K02404 5 K02501 2 K02502 5 K02504 2 K02507 5 K02595 5 K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	105, 110 58, 69 206, 210 50, 52, 53, 54, 66, 67, 68 202, 204 56, 58, 59, 69, 70 54, 68 54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211 105, 110	K11646 K11683 K11720 K11742 K11757 K11789 K11820 K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023 K12023	82, 86, 153 82, 86, 153 154 153 122 123 117, 119 154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215 154
K02501 2 K02502 5 K02504 2 K02507 5 K02595 5 K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	206, 210 50, 52, 53, 54, 66, 67, 68 202, 204 56, 58, 59, 69, 70 54, 68 54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11720 K11742 K11757 K11789 K11820 K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	154 153 122 123 117, 119 154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02502 5 K02504 2 K02507 5 K02595 5 K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	50, 52, 53, 54, 66, 67, 68 202, 204 56, 58, 59, 69, 70 54, 68 54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11742 K11757 K11789 K11820 K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	153 122 123 117, 119 154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02504 2 K02507 5 K02595 5 K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	202, 204 56, 58, 59, 69, 70 54, 68 54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11757 K11789 K11820 K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	122 123 117, 119 154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02507 5 K02595 5 K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	56, 58, 59, 69, 70 54, 68 54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11789 K11820 K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	123 117, 119 154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02595 5 K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	54, 68 54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11820 K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	117, 119 154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02596 5 K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11831 K11856 K12000 K12001 K12020 K12021 K12022 K12023	154 82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02597 5 K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	54, 68 54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K11856 K12000 K12001 K12020 K12021 K12022 K12023	82, 86, 153 74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02598 5 K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	54, 68 54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K12000 K12001 K12020 K12021 K12022 K12023	74, 77 105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02599 5 K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	54, 68 105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K12001 K12020 K12021 K12022 K12023	105, 108, 111, 112 117, 119 117, 119 118, 120 214, 215
K02700 1 K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	105, 111 59, 70 56, 69 59, 70 169, 180 208, 211	K12020 K12021 K12022 K12023	117, 119 117, 119 118, 120 214, 215
K02701 5 K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	59, 70 56, 69 59, 70 169, 180 208, 211	K12021 K12022 K12023	117, 119 118, 120 214, 215
K02702 5 K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	56, 69 59, 70 169, 180 208, 211	K12022 K12023	118, 120 214, 215
K02703 5 K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	59, 70 169, 180 208, 211	K12023	214, 215
K02705 1 K02707 2 K02800 1 K02801 1 K02803 1	169, 180 208, 211		
K02707 2 K02800 1 K02801 1 K02803 1	208, 211	K12031	
K02800 1 K02801 1 K02803 1		V10007	
K02801 1 K02803 1	105, 110	K12037	74, 77, 154
K02803 1	4.50	K12039	137, 138
	153	K12042	293
K02900 1	153	K12043	73, 77, 81, 85
	108, 112	K12045	293
K03000 1	166, 168, 177, 179	K12047	261
	203, 205	K12054	139, 140
K03004 2	203, 205	K12122	280
K03005 2	203, 205	K12143	121
K03006 1	197, 198 208, 209, 211, 212	K12202	74, 78, 97, 108, 112, 312
K03008 1	196, 198	K12320	117, 119
K03009 2	272, 275	K12437	105, 108, 111, 112
	203, 205	K12520	279
	273, 275	K12521	118, 120
	203, 205	K12524	153
	273, 275	K12529	153
	105, 111	K12539	137, 138
	153	K12542	153
	209, 212	K12554	139, 140
	272, 275	K12765	292
	208, 211 272, 275	K12766	292
	273, 275	K12822	279
	273, 275	K13050	312
	311	K13502	273, 275
	154	K19195	439
	153	K19526	439
	260	K19667	435
	214, 215	K19965	439
	73, 77	K19990	439
K11510 7	73, 77	K20747	79, 80, 81, 84, 85, 154
K11511 8	82, 86, 153	K21205	154
K11522 2	214, 215	K21390	283, 284
K11538 7	73, 77	K21590	124, 125, 153, 220, 283, 284
	216	K21604	82, 86, 153
	217, 218, 312	K21650	82, 86, 153
	281	K21703	131
	282	K21903	260
	32, 86, 153	K22035	260, 312
	261	K22036	312
	219, 312	K22030	131
		K24065	
	32, 86, 153 32, 86, 153	K24065 K31545	40, 258 126, 261, 285

606 UNS Number Index

UNS Number	Page Number	UNS Number	Page Number
K31718	132, 133	S20103	156, 372, 377
K31830	153, 154, 285	S20153	156, 372, 377
K31835	283, 284, 312	S20160	415
K31918	197, 198, 199, 200	S20161	156, 413
K32018	132, 133	S20162	413
K32025	289, 290	S20200	156, 261, 262, 372, 377, 400, 403
K41245	261	S20300	415
K41545	127, 286	S20400	156, 262, 413
K41583	154	S20430	437
K41650	260, 312	S20500	413, 415
K42339	153	S20910	156, 259, 261, 262, 313, 413, 415
K42544	286	S21400	156, 413
K51545	261	S21460	413
K71340	135, 136	S21500	261
K81340	135, 136, 197, 198, 199, 201	S21600	156, 413
K90901	128	S21603	156, 413
K90941	287	S21800	156, 413, 415
K91061	260, 261	S21900	259, 262, 415
K91560	261	S21904	259, 262, 313, 413, 415
K92460	260, 261	S24000	156, 259, 262, 413, 415
K92930	260, 313	S24100	415, 437
K90901	312	S24565	259, 262
N06006	354, 358	S25700	261
N08004	353, 358	S28200	413
N08005	353, 358	S28300	262
N08006	354, 358	S30100	156, 259, 372, 378
N08007	342, 346, 349, 350	S30103	156, 372, 379
N08020	156, 262, 313, 413	S30153	143, 146, 372, 379
N08031	413, 415	S30200	156, 259, 372, 379, 400, 403, 429
N08050	353, 357	S30215	372, 380, 415
N08151	361	S30300	400, 403, 424
N08366	375, 385, 415	S30310	415
N08367	156, 233, 245, 259, 262, 313, 375, 385, 402, 408,	S30323	400, 403, 436
Nonno	415	S30345	415
N08603	353, 357	S30400	143, 146,190, 193, 225, 234, 298, 302, 373, 380,
N08604	352, 357 252, 257	000400	400, 404 429
N08605	353, 357 350, 357	S30403	143, 146, 190, 193, 226, 235, 298, 302, 373, 380, 400, 404
N08613	352, 357 352, 357	S30409	143, 146, 227, 236, 298, 302, 413
N08614	352, 357 353, 357	S30415	156, 262, 413
N08705	353, 357	S30432	261
N08800 N08810	145, 149, 233, 245, 262, 413	S30451	143, 146, 261, 262, 298, 302, 373, 381, 400, 404
	145, 150, 233, 245, 262, 413	S30452	156, 400, 405, 413
N08811 N08904	145, 150, 413 145, 149, 233, 245, 259, 262, 375, 385, 402, 408	S30453	143, 146, 190, 193, 226, 235, 262, 298, 303, 373,
N08904 N08925	413, 415		381, 400, 405
N08926	145, 149, 233, 245, 259, 262, 413, 415	S30454	415
N08932	413	S30500	156, 259, 262, 373, 381, 401, 405, 437
R20033	413, 415	S30600	156, 259, 262, 313, 373, 381
S13800	413, 415	S30601	156, 413
S15500	413, 415	S30615	156, 227, 236, 261, 262, 413
S15500 S15700	387, 391, 415	S30800	413, 415
S16800	262	S30815	156, 261, 262, 313, 413, 415
S10000 S17400	307, 308, 387, 388, 409, 410	S30900	373, 381, 402, 408
S17400 S17600	413, 415	S30908	156, 227, 236, 259, 262, 374, 382, 401, 405
S17000 S17700	387, 390, 409, 411, 429	S30909	143, 147, 227, 237, 262, 313, 413
S18200	415	S30940	156, 259, 261, 262, 413, 415
S18235	398, 399	S30941	156, 261, 262, 413
S20100	156, 261, 262, 372, 377, 400, 403	S31000	259, 299, 303, 374, 382, 402, 408
3_0.00		S31002	261, 262

UNS Number	Page Number	UNS Number	Page Number
S31008	156, 227, 237, 259, 262, 374, 382, 401, 405	S34809	156, 261, 262, 313, 413
S31009	143, 147, 228, 237, 262, 299, 303, 413	S35000	413
S31040	156, 261, 262, 413, 415	S35045	156, 259, 262, 413
S31041	156, 261, 262, 413	S35135	156, 413
S31042	261	S35315	156, 262, 413
S31050	156, 228, 237, 261, 262, 313, 374, 382	S35500	413, 415
S31100	415	S36200	413
S31200	156, 309, 310, 413	S38100	156, 259, 261, 262, 413
S31254	156, 228, 237, 259, 261, 262, 313, 374, 382, 415	S38815	413
S31260	156, 413	S39274	313
S31266	156, 262, 313, 413	S39277	313
S31272	261, 262	S40300	259, 366, 367, 394, 396
S31277	145, 149, 413	S40500	141, 142, 188, 189, 368, 370, 398, 399
S31400	415	S40800	259
S31600	143, 147, 191, 194, 228, 238, 299, 303, 374, 383,	S40900	188, 189, 223, 224, 413
00.000	401, 406, 429	S40910	156, 413
S31603	144, 147, 191, 194, 229, 239, 299, 304, 374, 383,	S40920	156, 413
	401, 406	S40920 S40930	156, 413
S31609	144, 147, 230, 240, 300, 305, 413	S40930 S40945	156, 413
S31635	144, 148, 262, 375, 384, 402, 407		
S31640	144, 148, 375, 384, 415	S40975	141, 142, 413
S31651	156, 261, 262, 299, 304, 374, 384, 401, 407	S40976	415
S31653	144, 148, 191, 194, 230, 240, 262, 300, 305, 375,	S40977	156, 259, 368, 370
	384, 401, 407	S41000	156, 188, 189, 223, 224, 295, 296, 312, 366, 367,
S31654	415	S41003	394, 396 156, 366, 367
S31700	156, 231, 241, 259, 300, 305, 375, 402, 407	S41003 S41008	156, 366, 367
S31703	144, 148, 231, 241, 259, 300, 305, 384, 413		
S31725	156, 192, 195, 233, 244, 313, 413, 415	S41026	295, 296
S31726	145, 148, 259, 261, 262 313, 375, 385, 415	S41040	415
S31751	262	S41045	156, 413
S31753	144, 148, 375, 385	S41050	156, 368, 370
S31803	156, 309, 310, 412, 413	S41400	259, 415
S32001	156, 413	S41425	415
S32003	413	S41500	141, 142, 259, 295, 296, 413, 415
S32050	156, 261, 262, 413	S41600	394, 396, 424
S32100	145, 149, 192, 195, 231, 242, 300, 306, 376, 386,	S41603	415
	402, 408, 437	S41610	415
S32101	413	S41623	259, 415, 436
S32109	145, 149, 232, 243, 300, 306, 413	S42000	366, 367, 413
S32205	151, 152, 309, 310, 392, 393, 412	S42010	415
S32304	151, 152, 392, 393, 415	S42020	394, 397, 436
S32520	151, 152, 309, 310, 392, 393	S42023	415, 436
S32550	156, 309, 310, 313, 413, 415	S42035	156, 259, 413
S32615	156, 261, 262, 413	S42200	413
S32654	156, 259, 262, 413, 415	S42900	156, 259, 313, 413, 415
S32750	151, 152, 309, 310, 392, 393	S43000	156, 188, 189, 223, 224, 297, 368, 370, 398, 399
S32760	151, 152, 309, 310, 392, 393, 415	S43020	398, 399, 436
S32803	156, 259, 413	S43023	415, 436
S32900	156, 413	S43035	141, 142, 188, 189, 262, 368, 371
S32906	413	S43036	259
		S43100	259, 394, 397, 413
S32950	156, 313, 413	S43400	156, 368, 370
S33100	313	S43600	156, 413
S33228	156, 261, 262, 313, 413	S43932	141, 142, 368, 371
S33400	156, 413	S43940	141, 142, 259, 368, 371
S34565	156, 261, 262, 313, 413, 415		
S34700	145, 149, 192, 195, 232, 243, 301, 306, 376, 386,	S44002	259, 394, 397
C24700	402, 408, 437	S44003	394, 397
S34709	145, 149, 233, 244, 301, 306, 413	S44004	395, 397
S34751	261	S44020	415
S34800	156, 259, 261, 262, 313, 413, 415	S44023	415

608 UNS Number Index

LINC Number	Daga Number
UNS Number S44200	Page Number 413
S44300	259
S44400	141, 142, 259, 261, 262, 369, 371, 415
S44500	156, 413
S44600	259, 369, 371, 398, 399
S44626	156, 259, 262, 413
S44627	156, 223, 224, 259, 313, 398, 399, 413
S44635	156, 259, 262, 413
S44660	156, 259, 262, 413
S44700	156, 259, 262, 398, 399, 413, 437
S44735	156, 259, 262, 369, 371
S44800	156, 259, 262, 413, 415
S45000	413, 415
S45500	413, 415, 437
S45503	415
S46500	413, 415
S46800	156, 259, 413
S50100	127
S50200	127
S50400	153, 222
T11301	432, 438
T11304	432
T11306	438
T11307	432
T11310	438 432
T11313 T11323	432
T11323	438
T11333	438
T11334	438
T11336	432
T11341	438
T11342	432
T11343	438
T11344	438
T11346	438
T11347	438
T11350	438
T11352	438
T12001	431
T12002	438
T12004	431
T12005	431
T12006	438
T12008 T12015	438
T20810	431 434
T20811	434
T20812	434
T20813	434
T20814	438
T20819	434
T20821	434
T20822	438
T20823	438
T20824	438
T20825	438
T20826	438

UNS Number	Page Number
T20841	438
T20842	438
T20843	438
T30102	433
T30103	438
T30104	438
T30105	438
T30106	438
T30107	438
T30108	438
T30109	438
T30110	438
T30402	433
T30403	433
T30404	438
T30405	438
T30407	438
T31501	438
T31502	438
T31506	438
T31507	438
T41901	438
T41902	438
T41904	438
T41905	438
T41906	438
T41907	438
T51602	438
T51603	438
T51604	438
T51605	438
T51606	438
T51620	438
T51621	438
T60601	438
T60602	434
T61202	438
T61203	438
T61206	434
T72301	430, 438
T72302	438
T72305	438

STEEL NUMBER INDEX

610 Steel Number Index

Steel Number	Page Number	Steel Number	Page Number
1.0031	165, 176	1.0414	25
1.0033	165, 176	1.0415	26
1.0033	165, 167, 168, 176, 177, 179	1.0416	24
1.0034	165, 166, 167, 169, 176, 178, 180	1.0418	250, 253
1.0035	50, 66, 165, 176	1.0420	319, 323
1.0036	52, 67	1.0425	104, 109, 208, 211
1.0037	52, 67	1.0426	273, 275
1.0038	52, 67, 268, 271	1.0429	250, 253
1.0044	57, 69	1.0436	273, 275
1.0045	62, 71	1.0446	319, 323
1.0050	60, 70	1.0451	196, 198
1.0060	65, 71	1.0452	196, 198
1.0070	65, 71	1.0453	197, 198
1.0107	202, 204	1.0456	167, 169, 178, 179
1.0108	202, 204	1.0457	250, 253
1.0114	52, 67	1.0458	263
1.0116	53, 67, 268, 271	1.0459	246, 247
1.0117	53, 67	1.0471	261
1.0143	57, 69	1.0473	107, 112
1.0144	57, 69	1.0477	272, 275
1.0145	58, 69	1.0478	272, 275
1.0212	165, 168, 169, 176, 178, 180	1.0481	105, 110
1.0215	166, 177	1.0483	246, 247
1.0220	167, 177	1.0484	250, 253
1.0225	168, 169, 170, 172, 174, 178, 179, 182, 183	1.0487	104, 109
1.0236	170, 180	1.0488	113, 115, 259, 261
1.0237	169, 179	1.0490	98
1.0237	169, 179	1.0491	98
1.0254	202, 204	1.0499	246, 248
1.0254	207, 210	1.0501	27, 269, 271
1.0255	202, 204	1.0503	29, 270, 271
1.0255	207, 210	1.0509	173, 174, 175, 182, 183, 184,
1.0257	208, 211	1.0511	28, 269, 271
1.0258	203, 205	1.0516	27
1.0259	203, 205	1.0517	29
1.0261	171, 180, 181	1.0518	31
1.0300	23	1.0528	26, 269, 271
1.0304	23	1.0530	27
1.0305	207, 210	1.0535	270, 271
1.0308	166, 167, 168, 169, 170, 171, 172, 177, 178, 179,	1.0536	175, 184
1.0310	180, 181, 182 23	1.0540	30, 270, 271
1.0311	23	1.0541	28
1.0313	23	1.0545	73, 77
1.0315	207, 210	1.0546	73, 77
1.0319	246, 247	1.0552	320, 324
1.0345	103, 109, 207, 210	1.0553	62, 71
1.0348	206, 210	1.0558	321, 324
1.0348	206, 210	1.0562	106, 111, 114, 116, 259, 261
1.0352	272, 275	1.0565 1.0566	106, 111, 114, 116, 259, 261, 273, 275 261
1.0356	206, 210		
1.0356	206, 207, 210	1.0570 1.0571	62, 71, 311 172, 182, 273, 275
1.0402	25	1.0571	172, 182, 273, 275 63, 71
1.0402	26		63, 71
1.0402	268, 271	1.0578	251, 254 170, 171, 172, 173, 174, 175, 180, 181, 172, 173
1.0406	268, 271	1.0580	170, 171, 172, 173, 174, 175, 180, 181, 172, 173, 180, 182, 183, 184
1.0408	168, 170, 173, 174, 178, 180, 182, 183	1.0581	209, 212
1.0413	24	1.0582	251, 254

Steel Number	Page Number	Steel Number	Page Number
1.0586	30	1.1127	175, 184
1.0588	30	1.1129	24
1.0595	63, 71	1.1131	327
1.0596	63, 71	1.1133	311
1.0599	174, 184	1.1137	25
1.0601	31, 311	1.1139	26
1.0609	31	1.1140	24, 257
1.0610	31	1.1141	24, 257
1.0611	32	1.1143	26
1.0612	32	1.1145	27
1.0613	32	1.1148	24
1.0614	32	1.1149	25
1.0615	32	1.1150	27
1.0616	33	1.1151	25, 169, 172, 180, 182
1.0617	32	1.1153	28
1.0618	33	1.1154	28
1.0619	326	1.1158	268, 271
1.0620	32		
1.0621	326	1.1161	175, 184
1.0622	32	1.1162	29
1.0625	326	1.1164	29
1.0626	32	1.1165	320, 324
		1.1170	311
1.0628	33	1.1171	30
1.0644	175, 184	1.1178	26
1.0710	257	1.1179	26
1.0711	257	1.1180	27
1.0712	257	1.1181	27, 170, 171, 172, 173, 174, 175, 180, 181, 182,
1.0713	257	1 1100	183, 184, 269, 271
1.0715	422	1.1186	28
1.0715	422	1.1189	28
1.0718	424	1.1191	29, 172, 173, 175, 182, 184, 270, 271
1.0721	420	1.1201	29
1.0722	423	1.1202	30
1.0725	420	1.1203	31
1.0726	420	1.1204	425
1.0727	421	1.1206	30
1.0736	422	1.1207	23
1.0737	424	1.1208	24
1.0756	436	1.1209	31
1.0757	423	1.1211	425
1.0760	420	1.1212	31
1.0761	423	1.1217	426
1.0762	421	1.1220	31
1.0762	421	1.1221	31, 257, 311
1.0763	423	1.1222	32
1.0764	420	1.1223	31
1.0765	423	1.1224	437
1.0835	31	1.1228	31
1.0920	257, 258	1.1231	425
1.1104	113, 115, 196, 198, 261	1.1232	32
1.1106	114, 116, 259, 261	1.1236	32
1.1110	23	1.1241	30
1.1111	23	1.1242	32
1.1113	23	1.1248	425
1.1114	23	1.1251	32
1.1121	23, 257	1.1252	32
1.1124	23	1.1253	32
1.1126	24	1.1255	32
5	- ·		

612 Steel Number Index

Steel Number	Page Number	Steel Number	Page Number
1.1262	32	1.4373	372, 377
1.1265	33	1.4401	143, 147, 191, 194, 228, 238, 299, 303, 374, 383,
1.1269	426		401, 406, 437
1.1272	33	1.4404	144, 147, 191, 194, 229, 239, 299, 304, 374, 383,
1.1274	426	1 4405	401, 406
1.1282	33	1.4405	339, 340, 359
1.1283	33	1.4406	144, 148, 300, 305, 375, 384, 401, 407
1.2002	437	1.4408	341, 345, 349, 350
1.2067	437	1.4409	342, 345, 349, 350
1.2235	437	1.4410	151, 152, 309, 310, 392, 393, 416
1.4000	366, 367, 398, 399	1.4411	361
1.4002	188, 189, 313, 368, 370	1.4412	342, 345
1.4003	141, 142, 368, 370, 416	1.4416	342, 346
1.4005	394, 396, 424	1.4417	361
1.4006	188, 189, 295, 296, 366, 367, 394, 396	1.4418	156, 313, 414, 416
1.4008	339, 340	1.4429	144, 148, 191, 194, 230, 240, 300, 305, 375, 384,
		4.4400	401, 407
1.4011	339, 340	1.4432	144, 147, 299, 304, 374, 383, 401, 406
1.4016	188, 189, 297, 368, 370, 398, 399, 437	1.4434	144, 148, 375, 385
1.4017	414	1.4435	144, 147, 191, 194, 229, 239, 299, 304, 374, 383,
1.4021	313, 366, 367, 394, 396, 437	1.4436	401, 406, 416 143, 147, 191, 194, 228, 238, 299, 303, 374, 383,
1.4028	313, 366, 367, 394, 396, 429	1.4430	401, 406
1.4029	394, 397	1.4438	144, 148, 375, 384, 402, 408
1.4031	414, 416, 429	1.4439	145, 148, 192, 195, 233, 244, 375, 385, 402, 408
1.4034	414, 416	1.4446	342, 345
1.4057	313, 394, 397	1.4449	313
1.4104	416	1.4458	342, 346, 349, 350
1.4105	398, 399	1.4460	309, 310, 416
1.4107	347, 348	1.4462	151, 152, 309, 310, 392, 393, 412
1.4109	394, 397	1.4466	156, 374, 382
1.4112	416	1.4468	361
1.4113	368, 370, 398, 399	1.4469	361
1.4116	414, 416	1.4470	361
1.4122	414, 416		
1.4125	395, 397	1.4501	151, 152, 309, 310, 392, 393, 416
1.4301	143, 146, 190, 193, 225, 234, 298, 302, 373, 380,	1.4507	151, 152, 416
	400, 404, 429	1.4507	309, 310, 392, 393
1.4303	373, 381, 401, 405	1.4509	141, 142, 368, 371
1.4305	400, 403, 414, 424	1.4510	141, 142, 188, 189, 368, 370
1.4306	143, 146, 190, 193, 226, 235, 298, 302, 373, 380,	1.4511	368, 370
1 4207	416	1.4512	188, 189, 368, 370
1.4307	143, 146, 298, 302, 373, 380, 400, 404	1.4513	414
1.4308	341, 344, 349, 350	1.4516	141, 142, 414
1.4309	341, 344, 349, 350	1.4517	349, 350, 361
1.4310	429	1.4520	156, 368, 370
1.4310	372, 378, 400, 403	1.4521	141, 142, 369, 371
1.4311	143, 146, 190, 193	1.4523	398, 399
1.4311	226, 235, 298, 303, 373, 381, 400, 405	1.4525	361
1.4313	141, 142, 414, 416, 295, 296	1.4526	414
1.4315	143, 146	1.4529	145, 149, 313, 375, 385, 416
1.4317	339, 340, 347, 348	1.4532	387, 391
1.4318	143, 146, 372, 379	1.4537	156, 414, 416
1.4335	156, 414	1.4539	145, 149, 301, 306, 375, 385, 402, 408, 416
1.4347	361	1.4541	145, 149, 192, 195, 231, 242, 300, 306, 376, 386,
1.4361	373, 381, 416		402, 408
1.4362	151, 152, 309, 310, 392, 393, 416	1.4542	307, 308, 387, 389, 409, 410
1.4369	437	1.4547	156, 313, 374, 382, 416
1.4371	372, 377	1.4550	145, 149, 192, 195, 232, 244, 301, 306, 313, 376,
1.4372	372, 377, 437	1 4550	386, 402, 408 341, 344, 349, 350
		1.4552	341, 344, 349, 350

Steel Number	Page Number	Steel Number	Page Number
1.4563	156, 313, 416	1.4874	354, 358
1.4567	416	1.4876	414, 416
1.4568	387, 390, 409, 411, 429, 437	1.4877	414, 416
1.4570	416	1.4878	414, 416
1.4571	144, 148, 230, 241, 300, 305, 375, 384, 402, 407	1.4886	414, 416
1.4572	342, 346	1.4887	414, 416
1.4578	416	1.4889	362
1.4580	144, 148, 262, 375, 384, 416	1.4903	128, 222, 287
1.4581	342, 345, 349, 350	1.4910	156, 230, 240, 313
1.4584	361	1.4912	301, 306
1.4587	361	1.4919	230, 240
1.4588	343, 346	1.4922	261, 288
1.4590	414	1.4931	347, 348
1.4592	369, 371	1.4941	145, 149, 263, 313
1.4593	343, 346	1.4948	143, 146, 227, 236, 298, 302
1.4594	416	1.4949	263
1.4605	414	1.4950	143, 147
1.4650	313	1.4951	143, 147
1.4710	335, 336	1.4958	233, 245
1.4713	414, 416	1.4958 (+RA)	156
1.4724	414, 416	1.4958 RK	245
1.4729	351, 355	1.4959	145, 150, 233, 245
1.4736	414, 416	1.4961	145, 149, 233, 244
1.4740	351, 355	1.4981	263
1.4742	414, 416	1.4988	263
1.4743	362	1.5021	437
1.4745	351, 355	1.5023	425
1.4749	398, 399	1.5024	425
1.4762	414, 416	1.5026	425, 437
1.4776	351, 355	1.5402	312
1.4777	351, 355	1.5414	117, 119
1.4805	353, 357	1.5415	117, 119, 213, 279
1.4806	353, 357	1.5417	185, 186
1.4807	353, 358	1.5419	335, 336
1.4818	414, 416	1.5422	337, 338
1.4821	414, 416	1.5450	214, 215
1.4823	351, 355	1.5530	44
1.4825	351, 356	1.5531	44
1.4826	351, 356	1.5532	44
1.4828	414, 416	1.5634	437
1.4832	352, 356	1.5636	337, 338
1.4833	374, 382, 402, 408	1.5637	132, 133, 199, 200, 289, 290
1.4835	414, 416	1.5638	337, 338
1.4837	352, 356	1.5662	135, 136, 289, 290
1.4841	402, 408	1.5663	135, 136
1.4845	414, 416	1.5680	134, 199, 201, 289, 290
1.4848	352, 357	1.5682	199, 201
1.4849	353, 358	1.5714	44
1.4852	353, 357	1.5715	44
1.4854	414, 416	1.5752	38
1.4855	353, 357	1.5805	44
1.4857	353, 357	1.5810	44
1.4859	362	1.5918	44
1.4864	414, 416	1.6212	129, 199, 200
1.4865	353, 358	1.6217	129, 199, 200, 291
1.4869	362	1.6220	327
1.4872	414, 416	1.6228	130, 289, 290
		1.6308	312

614 Steel Number Index

Steel Number	Page Number	Steel Number	Page Number
1.6311	137, 138, 311	1.7239	428
1.6368	139, 140, 261	1.7240	428
1.6511	44, 258,311	1.7241	428
1.6515	359	1.7243	37, 311
1.6523	39, 258	1.7244	37
1.6526	39	1.7319	37
1.6563	258	1.7320	37
1.6566	44	1.7321	37
1.6569	44	1.7323	37
1.6570	359	1.7333	37
1.6571	39	1.7335	122, 217, 218, 281
1.6580	44, 258, 311	1.7336	123
1.6582	44, 311, 359	1.7338	219
1.6657	39, 44	1.7357	335, 336
1.6740	330, 334	1.7361	311
1.6773	44, 311	1.7362	127
1.6781	337, 338	1.7365	335, 336
1.6920	312	1.7366	286
1.6932	311	1.7375	155
1.6956	311	1.7379	335, 336
1.6982	347, 348	1.7380	124, 125, 220
1.7003	44, 311	1.7383	220, 283, 284
1.7006	311	1.7386+I	222
1.7014	35	1.7386+NT	222
1.7016	35	1.7701	437
1.7023	44	1.7703	155
1.7025	44	1.7706	335, 336
1.7030	35	1.7707	311
1.7033	35, 44, 311	1.7715	216, 312
1.7034	35, 311	1.7720	359
1.7035	36, 258, 311	1.7725	359
1.7036	35	1.7755	359
1.7037	35	1.7767	155
1.7038	35	1.7779	261
1.7039	36	1.8062	437
1.7102	427	1.8063	437
1.7106	437	1.8151	437
1.7108	437	1.8152	428
1.7117	437	1.8153	437
1.7131	44, 258	1.8159	42, 311, 428
1.7139	44, 258	1.8505	40
1.7147	44	1.8507	40
1.7149	44	1.8509	40
1.7160	44	1.8515	44
1.7176	427	1.8516	44
1.7177	427	1.8519	44
1.7182	41	1.8522	44
1.7185	41	1.8523	44, 311
1.7189	41	1.8550	40
1.7213	37	1.8818	98
1.7216	185, 186	1.8819	98
1.7218	37, 261, 185, 186, 277, 278, 330, 331	1.8821	155
1.7219	199, 201	1.8823	72, 76
1.7220	38, 185, 187, 277, 278, 330, 332	1.8824	155
1.7225	38, 185, 187, 277, 278, 330, 333	1.8825	74, 77
1.7226	38	1.8826	155
1.7227	38	1.8827	98
1.7228	38, 277, 278	1.8828	155

Steel Number	Page Number
1.8831	155
1.8832	155
1.8833	155
1.8834	72, 76
1.8835	155
1.8836	74, 77
1.8837	155
1.8838	98
1.8864	155
1.8865	155
1.8866	155
1.8867	155
1.8868	155
1.8869	155
1.8870	155
1.8871	155
1.8872	155
1.8873	155
1.8874	155
1.8875	155
1.8876	259
1.8877	259
1.8879	155, 259
1.8880	155, 259
1.8881	155, 259
1.8888	155, 259
1.8890	259
1.8891	257, 258
1.8893	258
1.8895	257
1.8896	257
1.8897	257
1.8898	257
1.8901	98
1.8902	98
1.8903	98
1.8904	81, 85
1.8905	259, 261
1.8906	80, 84
1.8908	80, 84
1.8909	80, 84
1.8912	98
1.8914	82, 86
1.8915	155, 259, 261
1.8916	80, 84
1.8918	155, 259, 261
1.8924	80, 84
1.8925	98 81, 85
1.8926	
1.8927 1.8928	82, 86 82, 87
	82, 87 82, 87
1.8931	62, 67 274, 276
1.8932 1.8933	98
1.8935	155, 259, 261
1.8936	274, 276
1.8940	98
1.00-0	

Steel Number	Page Number
1.8941	98
1.8945	92, 96
1.8946	92, 96
1.8947	251, 255
1.8948	251, 254
1.8952	252, 255
1.8955	252, 256
1.8957	252, 256
1.8958	88, 94
1.8959	92, 96
1.8961	88, 94
1.8963	92, 96
1.8965	92, 96
1.8966	92, 96
1.8967	93, 96
1.8972	251, 255
1.8973	251, 255
1.8975	252, 255
1.8977	252, 256
1.8978	252, 256
1.8980	81, 85
1.8983	98
1.8984	80, 84
1.8986	81, 85
1.8987	82, 86
1.8988	82, 87
1.8990	81, 85
1.8991	81, 85
1.8992	81, 85
1.8993	82, 86
1.8994	82, 86
1.8995	82, 87
1.8996	82, 87
2.4680	353, 358
2.4778	354, 358
2.4815	354, 358
2.4816	414, 416
2.4851	414, 416
2.4856	414, 416
2.4879	354, 358
2.4889	414, 416
2.4951	414, 416

SPECIFICATION DESIGNATION INDEX

618 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
AFNOR NF A 32-053:1992	10 N14-M	359	AFNOR NF A 49-141:1978	TS 37-a	167
	10 N19-M	359		TS 37-a (NE)	179
	10 N6-M	359	AFNOR NF A 49-214:1978	Z 10 CNWT 17-13 B	263
	16 M5-M	359		Z 6 CN 19-10	227, 236
	18 NCD12.6-M	359		Z 6 CN Nb 18-12 B	233, 244
	20 D5-M	330, 331		Z 6 CND 17-12 B	230, 240
	20 M5-M	320, 324		Z 6 CNT 18-12 B	232, 243
	20 NCD4-M	359		Z 8 CNDT 17-13 B	230, 241
	Z 3CN13.4-M	339, 340	AFNOR NF A 49-217:1987		228, 237
	Z 5CN19.10-M	341, 344	74 14011141 71 40 Z17.1007	TU Z 1 CNDU 20 18 06 AZ	228, 237
AFNOR NF A 32-054:1994		359		TU Z 1 CNS 18 15	227, 236
N NOR NI A 32-034.1994	G15CrMoV6	359		TU Z 1 NCDU 25 20 04	263
	G16Mn5	319, 323		TU Z 1 NCDU 31 27 03	263
		·			
	G20Mn6	320, 324		TU Z 10 C 17	223, 224
	G20NiCrMo12	359		TU Z 12 C 13	223, 224
	G25CrMo4	330, 331		TU Z 2 CN 18 10	226, 235
	G30Mn6	321, 322,		TU Z 2 CN 18 10 AZ	226, 235
	0000110-144	324, 325		TU Z 2 CN Nb 25 20	263
	G30NiCrMo14	359		TU Z 2 CND 17 12	229, 239
	G30NiCrMo8	330, 334		TU Z 2 CND 17 12 AZ	230, 240
	G35CrMo4	330, 332		TU Z 2 CND 18 05 03	263
	G35NiCrMo6	359		TU Z 2 CND 22 05 03	232, 243
	G42CrMo4	330, 333		TU Z 2 CND 25 07 03	232, 243
	GE230	319, 323		TU Z 2 CNDU 17 16	263
	GE280	320, 323		TU Z 5 CNDU 21 08 02	263
	GE320	321, 324		TU Z 6 CN 18 09	225, 234
	GE370	322, 325		TU Z 6 CND 17 11	228, 238
	GX4CrNi13-4	339, 340		TU Z 6 CNT 18 10	231, 242
	GX4CrNi16-4	339, 340	A ENOD NE A 40 000:1000		-
FNOR NF A 32-058:1984		360	AFNOR NF A 49-220:1990		219
	18 CDBB2-M	360		TU 10 CD 9-10	220
	20 NCD 8-M	360		TU 13 CD 4-04	217, 218
	25 MCDV 6-M	360		TU 15 CD 2-05	216
				TU 15 D 3	213
	30 MSCB 6.4-M	360		TU 37 C	207, 210
	30 NSCDV 86-M	360		TU 42 C	208, 211
	32 NCD 8-M	360		TU 48 C	209, 212
	35 CD 4-M	360		TU 52 C	209, 212
	35 CDV 10 4-M	360	AFNOR NF A 49-244:1993	TU Z 2 CND 18 14	229, 239
	42 CD 4-M	360		X15CrNi24-13	227, 237
	42 NCD 16-M	360		X1CrNi25-20	228, 237
	45 CSD 6-M	360		X2NiCrMoCu25-20	233, 245
	45 S7-M	360		X3CrNi18-10	226, 235
	50 CD 4-M	360		X3CrNiMo17-11-2	229, 239
	50 NSCDV 5-M	360			229, 239
	85 CDV 12-M	360		X3CrNiMo17-12-3	,
	Z 100 CD 6 1-M	360		X3CrNiMo18-12-3	229, 239
	Z 160 CDV 12-M	360		X3CrNiMo19-15-4	231, 242
	Z 200 C 12-M	360		X3CrNiMoCu22-7	263
				X3CrNiMoCuN25-6	263
	Z 270 C 27-M	360		X3CrNiMoCuN25-7	263
	Z 280CD 16 3-M	360		X3CrNiMoN17-11	230, 240
	Z 320 CD 16 3-M	360		X3CrNiMoN17-12	230, 240
	Z100MD8 1-M	328, 329		X3CrNiMoN18-14-5	233, 244
	Z100MN13 4-M	328, 329		X3CrNiMoN19-14	263
	Z110MD12 1-M	328, 329		X3CrNiMoN22-5	263
	Z120M12-M	328, 329		X3CrNiMoN25-6	263
	Z120MC12-M	328, 329		X3CrNiMoN25-7	263
	Z120MC17 2-M	328, 329		X3CrNiN18-10	226, 236
		•			
				X3CrNiN23-4	263

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
AFNOR NF A 49-244:1993	X4CrMnNi18-8-7	263	ASTM A 1011/A 1011M-03	50 [340], Class 1	72
(continued)	X5NiCr32-21	233, 245	(continued)	50 [340], Class 2	72
	X6CrNiMo17-11-2	230, 241		55 [380]	59, 70
	X6CrNiN19-9	226, 236		55 [380], Class 1	73
	X6CrNiTi18-10	231, 242		55 [380], Class 2	72
	X7CrNi18-9	225, 234		60 [410], Class 1	74
	X7CrNiMo17-11-2	228, 238		60 [410], Class 2	73
	X8CrNi25-20	263		65 [450], Class 1	74
AFNOR NF A 49-247:1981	TS Z 2 CN 18-10	226, 235		65 [450], Class 2	74
	TS Z 2 CND 17-12	229, 239		70 [480], Class 2	74
	TS Z 2 CND 19-15	231, 242		70 [480], Class 1	97
	TS Z 6 CN 18-09	225, 234		CS Type A	97
	TS Z 6 CND 17-11	228, 238		CS Type B	97
	TS Z 6 CNT 18-10	231, 242		CS Type C	97
AFNOR NF A 49-250:1979	TS E 24-a	167, 178		DS Type A	97
	TS E 26-b	169, 179		DS Type B	97
AFNOR NF A 49-317:1980	TU Z 2 CN 18-10	190, 193	ASTM A 1021-02	A, Class 1	295, 296
	TU Z 2 CND 17-12	191, 194		A, Class 2	295, 296
AFNOR NF A 49-341:1975		171		B, Class 1	295, 296
AFNOR NF A 49-647:1979		259	ASTM A 105/A 105M-03		273, 275
	TS Z 2 CN 18-10	190, 193	ASTM A 106-02a	Α	206, 210
	TS Z 6 CN 18-09	190, 193	7.6771.766.624	В	208, 211
	TS Z 6 CND 17-11	191, 194		C	209, 212
	TS Z 8 C 17	188, 189	ASTM A 108-03	1008	23
API 5L-2004	A - PSL 1	246, 247	7.67. 166 66	1010	23
7 1 02 200 .	A25 Class I - PSL 1	246, 247		1015	24
	A25 Class II - PSL 1	246, 247		1016	24
	B - PSL 1	246, 247		1018	24
	B - PSL 2	250, 253		1020	25
	X42 - PSL 1	246, 247		1022	25
	X42 - PSL 2	250, 253		1025	26
	X46 - PSL 1	246, 248		1030	26
	X46 - PSL 2	250, 253		1035	27
	X52 - PSL 1	246, 248		1040	28
	X52 - PSL 2	251, 254		1045	29
	X56 - PSL 1	246, 248		1050	30
	X56 - PSL 2	251, 254		1095	33
	X60 - PSL 1	246, 248	ASTM	A	328, 329
	X60 - PSL 2	251, 255	A 128/A 128M-93 (2003)	,,	020, 020
	X65 - PSL 1	246, 248	,	B-1	328, 329
	X65 - PSL 2	252, 255		B-2	328, 329
	X70 - PSL 1	246, 249		B-3	328, 329
	X70 - PSL 2	252, 256		B-4	328, 329
	X80 - PSL 2	252, 256		С	328, 329
ASTM A 1005/A 1005M-00	35	250, 253		D	328, 329
7.6 TW 7. T000/7. T000/W 00	50	263		E-1	328, 329
	60	251, 255		E-2	328, 329
	70	252, 256		F	328, 329
	80	252, 256	ASTM A 135-01	Α	202, 204
ASTM A 1011/A 1011M-03	30 [205]	50, 66		В	203, 205
7.51W/7.1511/A 1011W-05	33 [230]	50, 60 52, 67	ASTM A 139-00	Α	202, 204
	36 [250], Type 1	53, 67		В	203, 205
	36 [250], Type 1	53, 67 54, 68		С	203, 205
	40 [275]	54, 68		D	203, 205
				E	203, 205
	45 [310] 45 [310], Class 1	56, 69 72	ASTM A 148/A 148M-03	105-85	322, 325
	45 [310] Class 2	97		115-95	359
				130-115	359
	50 [340]	58, 69			-

620 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 148/A 148M-03	135-125	359	ASTM A 182/A 182M-02	F 316N	299, 304
(continued)	150-135	359	(continued)	F 317	300, 305
	160-145	359		F 317L	300, 305
	165-150	359		F 321	300, 306
	165-150L	359		F 321H	300, 306
	210-180	359		F 347	301, 306
	210-180L	359		F 347H	301, 306
	260-210	359		F 348	313
	260-210L	359		F 348H	313
	80-40	321, 324		F 3V	285
	80-50	321, 324		F 3VCb	312
	90-60	321, 324		F 429	313
ASTM A 167-99	302B	372, 380		F 44	313
	308	413		F 45	313
	309	373, 381		F 46	313
	310	374, 382		F 47	313
ASTM A 176-99	403	366, 367		F 48	313
7.61W 7.176 66	420	366, 367		F 49	313
	422	413		F 5	286
	431	413		F 50	309, 310
	442	413		F 51	•
	446			F 52	309, 310
ASTM A 178/A 178M-02		369, 371 206, 210		F 53	313
ASTIVI A 176/A 176IVI-UZ	A	•			309, 310
	С	208, 211		F 54	313
A C.T. A	D	209, 212		F 55	309, 310
ASTM A 179/A 179M-90a (2001)		206, 210		F 56	313
ASTM A 181/A 181M-01	60	272, 275		F 57	313
7.61W 7.16177.161W 61	70	273, 275		F 58	313
ASTM A 182/A 182M-02	430	297		F 59	309, 310
A31W A 102/A 102W-02	F 1	279		F 5a	286
	F 10	313		F 60	309, 310
		312		F 61	313
	F 11, Class 1	282		F 62	313
	F 11, Class 2			F 6a, Class 1	295, 296
	F 11, Class 3	282		F 6a, Class 2	295, 296
	F 12, Class 1	312		F 6a, Class 3	295, 296
	F 12, Class 2	281		F 6a, Class 4	295, 296
	F 122	313		F 6b	295, 296
	F 2	280		F 6NM	295, 296
	F 20	313		F 9	287
	F 21	285		F 91	312
	F 22, Class 1	283, 284		F 911	312
	F 22, Class 3	283, 284		F 92	312
	F 22V	283, 284		F XM-11	313
	F 23	312		F XM-19	313
	F 24	312		F XM-27Cb	313
	F 304	298, 302		F310H	299, 303
	F 304H	298, 302		FR	312
	F 304L	298, 302	ASTM A 192/A 192M-02		206, 210
	F 304LN	298, 303	ASTM A 202/A 202M-03	Α	153
	F 304N	298, 302		В	153
	F 309H	313	ASTM	A	131
	F 310	299, 303	A 203/A 203M-97 (2003)		
	F 310MoLN	313	,,	В	131
	F 316	299, 303		D	132, 133
	F 316H	300, 305		E	132, 133
	F 316L	299, 304		F	132, 133
	1 010	_00,001			

ASTM A 204A 204A 024A 024A 024A 024A 024A 02	Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
C	ASTM A 204/A 204M-03	Α	117, 119	ASTM A 213/A 213M-03a	XM-19	261
ASTM A 209/A 209M-03 T1 214, 215 A 214/A 214M-96 (2001) CO 206 ASTM A 210A 210M-02 A-1 214, 215 A 216A 216M-93 (2003) MCB 326 ASTM A 210A 210M-02 A-1 200, 212 A STM A 217/A 217M-02 C12 335, 336 ASTM A 213/A 213M-03 233, 244 A STM A 217/A 217M-02 C12 335, 336 T11 219 CA15 347, 348 C12 335, 336 T112 217, 218 CA15 347, 348 C11 335, 336 T112 261 WC1 355, 336 C3 336, 336 T12 261 WC1 350, 336 WC1 350, 336 T21 261 WC4 360 353, 336 T22 260 WC5 350, 336 T22 261 ASTM A 225/A 225M-03 C 153 T24 261 ASTM A 240/A 240M-03 C 153 T25 221 ASTM A 240/A 240M-03 C 153, 149		В	117, 119			
Time		С	117, 119			206, 210
T14	ASTM A 209/A 209M-03	T1	214, 215	` ,	14/04	000
T1b		T1a			WCA	326
ASTM A 210/A 210M-02				A 216/A 216W-93 (2003)	WCB	326
C 209, 212 ASTM A 217/A 217M-Q2 C12 335, 336 ASTM A 213/A 213M-03	ASTM A 210/A 210M-02					
ASTM A 213/A 213M-03a	7.6 TW 7. 2 TO 7. 2 TO W 62			ACTM A 017/A 017M 00		
261	ACTM A 212/A 212M 022		·	ASTM A 217/A 217M-02		
T11	A31W A 213/A 213W-03a					
T12		T11				•
T122						
T17 261 WC1 360 T2 2166 WC5 360 T21 261 WC5 360 T22 220 WC9 335, 336 T23 261 ASTM A 225/A 225M-03 C 153 T24 261 D 153 T35 221 ASTM A 240/A 240M-036 D 153 T36 221 ASTM A 240/A 240M-036 D 153 T39 221 ASTM A 240/A 240M-036 D 153 T39 222 S 153 T39 222 S 153 T39 222 S 154 T39 222 S 154 T39 1 261 T37, 371 T39 2 161 T37, 381 T39 3 17, 381 T39 3 17, 381 T39 3 181 T39						
T2 216 WC5 360 T21 221 220 WC6 335, 336 T22 220 WC9 335, 336 T23 261 ASTM A 225/A 225M-03 D 153 D 153 T55 221 ASTM A 240/A 240M-03c 141, 142, 145, 149, 155 T55 221 ASTM A 240/A 240M-03c 141, 142, 145, 149, 155 T9 222 T9 T9 T9 T9 T9 T						
T21 261 WC6 335, 336 T22 220 WC9 335, 336 T23 261 ASTM A 225/A 225M-03 C 153 T54 221 ASTM A 240/A 240M-03c 141, 142, 145, 149, 155 T55 221 ASTM A 240/A 240M-03c 141, 142, 145, 149, 155 T56 261 S1						
T22 220 WCG 353, 336 T23 261 ASTM A 225/A 225M-03 C 153 T24 261 D 153 T5 221 ASTM A 240/A 240M-03c 141, 142, 145, 149, 155 T5 221 ASTM A 240/A 240M-03c 141, 142, 145, 149, 156 T5 221 TATM A 240/A 240M-03c 141, 142, 145, 149, 159 T5 221 TSTM A 240/A 240M-03c 141, 142, 145, 149, 159 T9 222 TSTM TSTM TSTM TSTM TSTM TSTM TSTM					WC5	360
T23					WC6	335, 336
T24 261 ASTM A 220/A 220/H-30 C 153 T5 221 ASTM A 240/A 240/M-03c 141, 142, 149, 149, 149, 149, 149, 149, 149, 149					WC9	335, 336
T5				ASTM A 225/A 225M-03	С	153
T5b					D	153
155				ASTM A 240/A 240M-03c		141, 142,
T9 222 158, 159, 159, 159, 159, 159, 159, 159, 159						
T91 222 366, 367, 7911 261 368, 368, 368, 368, 368, 368, 368, 369, 371, 372, 374, 372, 374, 372, 374, 374, 372, 374, 372, 374, 375, 381, 375, 381, 375, 381, 375, 381, 372, 375, 381, 372, 376, 381, 372, 376, 377, 376, 377, 377, 377, 377, 377						150, 151,
T911 261 368, 369, 370, 371, 1792 261 373, 374, 375, 381, 17920 261 375, 381, 17920 261 375, 381, 179204 225, 234 382, 385, 179304 225, 234 382, 385, 377, 371, 371, 371, 371, 371, 371, 371		Т9	222			
T92 261 373, 371, 771, 77201 261 373, 374, 77201 261 375, 381, 77202 261 375, 381, 77202 261 382, 385, 77304 225, 234 382, 385, 77304 225, 234 382, 385, 77304 226, 235 201-1 156, 372, 775, 775, 775, 775, 775, 775, 775, 7		T91	222			
192 261 373, 374, 17201 261 375, 381, 17202 261 375, 381, 17202 261 382, 385, 17304 225, 234 392, 393, 17304H 227, 236 201-1 156, 372, 377 17304L 226, 235 201-2 175, 377 17304L 266, 235 201-2 175, 377 17309Cb 261 201L 156, 372, 377 17309H 277, 237 377 17309HCb 261 201L 156, 372, 377 17309HCb 261 201LN 156, 372, 377 17300H 228, 237 202 156, 372, 377 17310H 228, 237 202 156, 372, 377 17310H 228, 237 205 151, 152, 17310HCb 261 202 205 151, 152, 203		T911	261			
TP201		T92	261			
TP202 261 382, 385, 793 TP304H 225, 234 392, 393, 393, 393, 393, 393, 392, 393, 393		TP201	261			
FP904		TP202	261			
TP304H 227, 236 201-1 156, 372, 377 TP304LN 226, 235 201-2 156, 372, 377 TP309W 261 27, 237 TP309H 227, 237 TP309HCb 261 201LN 156, 372, 377 TP309S 227, 236 201LN 156, 372, 377 TP310Cb 261 201LN 156, 372, 377 TP310H 228, 237 202 156, 372, 377 TP310HCb 261 209 151, 152, 392, 393 TP310HCbN 261 209 209 151, 152, 392, 393 TP316H 228, 238 2507 151, 152, 392, 393 TP316L 229, 239 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316LN 230, 240 255 156, 413 TP316LN 230, 240 301 36, 372, 378 TP316LN 230, 240 301 156, 372, 378 TP316LN 230, 240 301 156, 372, 378 TP317L 231, 241 301LN 143, 146, 71321 231, 241 372, 379 TP317L 231, 241 301LN 143, 146, 71347H 233, 244 TP347H 233, 244 TP347H 233, 244 TP347H 233, 244 TP347HG 261 304L 143, 146, 7134B 261 TP348H 261 304LN 143, 146, 7134B 261 TP348H 261 304LN 143, 146, 7134B 261 TP348H 261 304LN 143, 146, 7134B 145, 145, 145, 145, 145, 145, 145, 145,		TP304	225, 234			
TP304L 226, 235 TP304LN 226, 235 TP304LN 226, 235 TP304N 261 TP309Cb 261 TP309H 227, 237 TP309HCb 261 TP309HCb 261 TP309S 227, 236 TP310Cb 261 TP310Cb 261 TP310HCb 27, 237 TP310HCb 261 TP310HCb 28, 238 TP310HCb 29, 239 TP316H 230, 240 TP316H 230, 240 TP316L 229, 239 TP316L 229, 239 TP316L 229, 239 TP316L 230, 240 TP317 TP31			·			
TP304LN 226, 235 201-2 377 TP304N 261 377 TP309Cb 261 201L 156, 372, 377 TP309H 227, 237 377 TP309HCb 261 201LN 156, 372, 377 TP309S 227, 236 202 156, 372, 377 TP310Cb 261 377 377 TP310HCb 261 205 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316L 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 230, 240 301 156, 372, 378 TP316N 230, 240 301 156, 372, 378 TP316N 231, 241 301L 156, 372, 378 TP317 231, 241 301LN 143, 146, 372, 379 TP347H 232, 243 3					201-1	156, 372,
TP304N 261 377 TP309Cb 261 201L 156, 372, 377 TP309H 227, 237 TP309HCb 261 201LN 156, 372, 377 TP309S 227, 236 202 156, 372, 377 TP310Cb 261 202 156, 372, 377 TP310H 228, 237 205 151, 152, 383 TP310HCbN 261 2304 151, 152, 383 TP310HCbN 261 2304 151, 152, 383 TP316H 230, 240 255 151, 152, 383 TP316H 230, 240 255 156, 413 TP316LN 230, 240 255 156, 413 TP316LN 230, 240 301 156, 372, 378 TP316LN 230, 240 301 156, 372, 378 TP316LN 231, 241 301LN 156, 372, 378 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321 232, 243 304 143, 146, 373, 380 TP347H 233, 244 304 304 313 TP348 261 304L 443, 146, 373, 380						377
TP309Cb 261 201L 156, 372, TP309H 227, 237 TP309H 227, 237 TP309S 261 201LN 156, 377, 377 TP309S 227, 236 202 156, 372, 377 TP310Cb 261 202 156, 372, 377 TP310H 228, 237 205 151, 152, TP310HCb 261 2304 151, 152, TP310HCb 261 2304 151, 152, TP310S 227, 237 TP310B 228, 238 2507 151, 152, TP310B 228, 238 2507 151, 152, TP316 228, 238 2507 151, 152, TP316 228, 238 2507 151, 152, TP316L 229, 239 301 156, 372, TP316L 229, 239 301 156, 372, TP316L 229, 239 301 156, 372, TP316LN 230, 240 378 TP316N 261 301L 156, 372, TP316N 261 301L 156, 372, TP317 231, 241 301LN 143, 146, TP347L 231, 241 301LN 143, 146, TP347H 232, 243 302 156, 372, 379 TP347 232, 243 304 304 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 304LN 143, 146, TP34					201-2	
TP309H 227, 237 377 TP309HCb 261 201LN 156, 372, 377 TP309Cb 261 202 156, 372, 377 TP310Cb 261 202 156, 372, 377 TP310H 228, 237 2205 151, 152, 377 TP310HCb 261 2304 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, TP310B 227, 237 TP316B 228, 238 2507 151, 152, 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316L 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 261 301L 156, 372, 378 TP317 231, 241 301LN 143, 146, TP321 231, 241 301LN 143, 146, TP321 231, 242 302 156, 372, 379 TP347 232, 243 304 304 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 304K TP348 261 304LN 144, 146, 143, 146, TP348 261 304LN 144, 146, TP348 261 304LN					0041	
TP309HCb 261 201LN 156, 372, 377 TP309S 227, 236 202 156, 372, 377 TP310Cb 261 377 TP310HCb 226, 237 2205 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP310S 227, 237 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316H 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 261 301L 156, 372, 378 TP317 231, 241 301L 156, 372, 379 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 304 143, 146, 373, 380 TP347HFG 261 304H 143, 146, 373, 380 TP347LN 261 304L 143, 146, 373, 380 TP348H 261 304L 143, 146, 373, 380 TP34					201L	
TP309S 227, 236 377 TP310Cb 261 202 156, 372, 377 TP310H 228, 237 2205 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316H 230, 240 255 156, 413 TP316L 229, 239 301 556, 372, 378 TP316N 261 301L 156, 372, 378 TP316N 261 301L 156, 372, 379 TP317 231, 241 301LN 143, 146, 379 TP321 231, 242 302 156, 372, 379 TP321 231, 242 302 156, 372, 379 TP347 232, 243 304 143, 146, TP347H 233, 244 TP347H 233, 244 TP347HFG 261 304L 413, 146, 179347LN 261 TP348 261 304L 413, 146, 179348 261 TP348 261 304L 4146, 143, 146, 179348 261 TP348 261 304L 4146, 144, 146, 179348 261 TP348 261 304L 414, 146, 146, 146, 146, 146, 146, 146,			·		2011 N	
TP310Cb 261 202 156, 372, 377 TP310H 228, 237 205 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP310HCbN 261 2304 151, 152, 392, 393 TP316B 228, 238 2507 151, 152, 392, 393 TP316B 228, 238 2507 151, 152, 392, 393 TP316H 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 261 301L 156, 372, 378 TP317 231, 241 301LN 143, 146, 379 TP321 231, 242 302 156, 379 TP321H 232, 243 304 143, 146, TP347H 233, 244 TP347H 237, 346 TP348H 261					201214	
TP310H 228, 237 205 151, 152, 392, 393 TP310HCbb 261 2304 151, 152, 392, 393 TP310S 227, 237 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316H 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 261 301L 156, 372, 378 TP317 231, 241 301LN 143, 146, 372, 379 TP317 231, 241 301LN 143, 146, 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 17947H 233, 244 TP347H 233, 344 TP348H 261 304L 143, 146, 373, 380 TP348H 261 304LN 143, 146, 373, 380					202	
TP310HCb 261 392, 393 TP310HCbN 261 2304 151, 152, TP310S 227, 237 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316H 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, TP316N 230, 240 301 156, 372, TP316N 261 301L 156, 372, TP317 231, 241 301LN 143, 146, TP321 231, 242 372, 379 TP321H 232, 243 302 156, 372, TP347 232, 243 304 379 TP347 232, 243 304 379 TP347H 233, 244 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 304L 143, 146, TP348 261 304L 143, 146, TP348H 261 304LN 143, 146,						377
TP310HCbN 261 2304 151, 152, 152, 152, 152, 152, 152, 152,					2205	
TP310S 227, 237 392, 393 TP316 228, 238 2507 151, 152, 392, 393 TP316H 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 261 301L 156, 372, 378 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 372, 379 TP347HFG 261 304H 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 143, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 145, 146, 144, 144, 146, 144, 144, 144, 146, 144, 145, 146, 144, 144, 146, 144, 144, 144, 144					0004	
TP316 228, 238 TP316H 230, 240 TP316L 229, 239 TP316LN 230, 240 TP316LN 230, 240 TP316N 261 TP317 231, 241 TP321 231, 242 TP321H 232, 243 TP347 232, 243 TP347H 233, 244 TP347H 233, 244 TP348 261 TP348H 261 TP348H 261 TP348 261 TP348H 261 TP348 261 TP348 304LN TP348 304LN TP348 304LN TP348 304LN TP348 304LN TP348 304LN TP348, 373, 380 TP348 261 TP348H 304LN TP348H 3					2304	
TP316H 230, 240 255 156, 413 TP316L 229, 239 301 156, 372, 378 TP316N 261 301L 156, 372, 379 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 304 143, 146, 379 TP347 232, 243 304 143, 146, 379 TP347HFG 261 304H 143, 146, 413 TP348H 261 304LN 143, 146, 373, 380 TP348H 261 304LN 143, 146, 373, 380					2507	
TP316L 230, 240 255 156, 413 TP316LN 230, 240 301 156, 372, TP316LN 230, 240 378 TP316N 261 301L 156, 372, TP317 231, 241 301LN 143, 146, TP321 231, 242 302 156, 372, TP321H 232, 243 304 143, 146, TP347H 233, 244 304 304 143, 146, TP347H 233, 244 304 143, 146, TP347H 233, 244 304 143, 146, TP347LN 261 304L 143, 146, TP348H 261 304L 143, 146, TP348H 261 304LN 143, 146,			•		∠30/	
TP316LN 230, 240 301 156, 372, 378 TP316N 261 301L 156, 372, 379 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 379 TP347H 233, 244 373, 380 TP347HG 261 304H 143, 146, 413 TP348 261 304L 143, 146, 373, 380 TP348 261 304LN 143, 146, 373, 380		TP316H	230, 240		255	
TP316LN 230, 240 378 TP316N 261 301L 156, 372, 379 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 379, 380 TP347HFG 261 304H 143, 146, 143, 14		TP316L	229, 239			
TP316N 261 301L 156, 372, 379 TP317 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 373, 380 TP347H 233, 244 373, 380 373, 380 TP347LN 261 304L 413 TP348B 261 304L 143, 146, 373, 380 TP348H 261 304LN 143, 146, 373, 380		TP316LN	230, 240		301	
TP317 231, 241 379 TP317L 231, 241 301LN 143, 146, TP321 231, 242 302 156, 372, TP321H 232, 243 302 156, 372, TP347 232, 243 304 143, 146, TP347H 233, 244 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 304L 143, 146, TP348 261 304L 143, 146, TP348H 261 304LN 143, 146,		TP316N	261		301L	
TP317L 231, 241 301LN 143, 146, 372, 379 TP321 231, 242 302 156, 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 146, 143, 146, 1			231, 241			
TP321 231, 242 372, 379 TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, 373, 380 TP347H 233, 244 373, 380 TP347HFG 261 304H 143, 146, 413 TP347LN 261 304L 143, 146, 373, 380 TP348 261 304L 143, 146, 373, 380 TP348H 261 304LN 143, 146,					301LN	
TP321H 232, 243 302 156, 372, 379 TP347 232, 243 304 143, 146, TP347H 233, 244 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 304L 143, 146, TP348 261 304L 143, 146, TP348H 261 304L 143, 146, 373, 380						372, 379
TP347 232, 243 304 143, 146, TP347H 233, 244 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 413 TP348 261 304L 143, 146, TP348H 261 304L 373, 380					302	
TP347H 233, 244 373, 380 TP347HFG 261 304H 143, 146, TP347LN 261 413 TP348 261 304L 143, 146, TP348H 261 304LN 143, 146,					004	
TP347HFG 261 304H 143, 146, TP347LN 261 413 TP348 261 304L 143, 146, TP348H 261 304LN 143, 146,					304	
TP347LN 261 413 TP348 261 304L 143, 146, TP348H 261 304LN 143, 146,					304H	
TP348 261 304L 143, 146, 373, 380 TP348H 261 304LN 143, 146,					JU4∏	
373, 380 TP348H 261 304LN 143, 146,					3041	
1P348H 261 304LN 143, 146,					JU 12	
VM 4F 0C4					304LN	
•		XM-15	261			

622 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 240/A 240M-03c	304N	143, 146,	ASTM A 240/A 240M-03c	439	141, 142,
(continued)		373, 381	(continued)		368, 371
	305	156, 373,		444	141, 142,
	309Cb	381 156, 413		800	369, 371 145, 149,
	309H	143, 147,		000	233, 245,
	00011	413			413
	309HCb	156, 413		800H	145, 150,
	309S	156, 374,			233, 245,
	04001	382		904L	413 145, 149,
	310Cb	156, 413		004L	375, 385
	310H	143, 147, 413		XM-15	156, 413
	310HCb	156, 413		XM-17	156, 413
	310MoLN	156, 374,		XM-18	156, 413
		382		XM-19	156, 413
	310S	156, 374,		XM-21	156, 413
	040	382		XM-27	156, 413
	316	143, 147, 374, 383		XM-29	156, 413,
	316Cb	144, 148,		XM-31	156, 413
	0.000	375, 384		XM-33	156, 413
	316H	144, 147,	ASTM A 242/A 242M-03a	Type 1	73, 77
		413	ASTM A 249/A 249M-03		227, 228,
	316L	144, 147,			233, 236,
	316LN	374, 383 144, 148,			237, 244, 245, 262
	STOLIN	375, 384		TP201	262
	316N	156, 374,		TP202	262
		384		TP304	225, 234
	316Ti	144, 148,		TP304H	227, 236
	317	375, 384		TP304L	226, 235
	317L	156, 375 144, 148,		TP304LN	226, 235
	317L	384, 413		TP305	262
	317LM	156, 413		TP309Cb	262
	317LMN	145, 148,		TP309H	227, 237
		375, 385		TP309HCb	262
	317LN	144, 148,		TP309S	227, 236
	321	375, 385 145, 149,		TP310Cb	262
	JZ I	376, 386		TP310H	262
	321H	145, 149,		TP310HCb	262
		413		TP310S	227, 237
	329	156, 413		TP316	228, 238
	334	156, 413		TP316H	230, 240
	347	145, 149,		TP316L	229, 239
	347H	376, 386 145, 149,		TP316LN	230, 240
	04/11	413		TP316N	262
	348	156, 413		TP317	231, 241
	348H	156, 413		TP317L	231, 241
	405	141, 142,		TP321	231, 242
		368, 370		TP321H	232, 243
	409	413		TP347	232, 243
	410	156, 366,		TP347H	233, 244
	410S	367 156, 366,		TP348	262
		367		TP348H	262
	429	156, 413		TPXM-15	262
	430	156, 368,		TPXM-19	262
		370	4.0714	TPXM-29	262
	434	156, 368,	ASTM A 250/A 250M 05 (2001)	T1	214, 215
	436	370 156 <i>4</i> 13	A 250/A 250M-95 (2001)	T11	219
	- 700	156, 413		T12	217, 218
				· ·-	2.7, 2.10

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM	T1a	214, 215	ASTM A 276-03 (continued	d) 302B	415
A 250/A 250M-95 (2001)				304	400, 404
(continued)	T1b	214, 215		304L	400, 404
	T2	216		304LN	400, 405
	T22	220		304N	400, 404
ASTM A 266/A 266M-03a	1	272, 275		305	401, 405
	2	273, 275		308	415
ASTM A 266/A 266M-03a ASTM A 268/A 268M-03	3	311		309	402, 408
	4	273, 275		309Cb	415
ASTM A 268/A 268M-03		259		309S	401, 405
	18Cr-2Mo	259		310	402, 408
	25-4-4	259		310Cb	415
	26-3-3	259		310S	401, 405
	29-4	259		314	415
	29-4-2	259		316	401, 406
	TP403Ti	259		316Cb	415
	TP405	188, 189		316L	401, 406
	TP409	188, 189,		316LN	401, 407
	TD440	223, 224		316N	401, 407
	TP410	188, 189, 223, 224		316Ti	402, 407
	TP429	259		317	402, 407
	TP430	188, 189,		321	402, 408
		223, 224		347	402, 408
	TP439	188, 189		348	415
	TP443	259		403	394, 396
	TP446-1	259		405	398, 399
	TP446-2	259		410	394, 396
	TP468	259		414	415
	TPXM-27	259		429	415
	TPXM-33	259		430	398, 399
ASTM A 269-02a		192, 195,		431	394, 397
		259		440A	394, 397
	TP304	190, 193		440B	394, 397
	TP304L	190, 193		440C	395, 397
	TP304LN	190, 193		444	415
	TP316	191, 194		446	398, 399
	TP316L	191, 194		447	398, 399
	TP316LN	191, 194		XM-10	415
	TP317	259		XM-11	415
	TP321	192, 195		XM-19	415
	TP347	192, 195		XM-21	400, 405
	TP348	259		XM-26	415
	TPXM-10	259		XM-27	398, 399
	TPXM-11	259		XM-28	415
	TPXM-15	259		XM-29	415
	TPXM-19	259		XM-30	415
ACTIA A 07/A 07IA 00	TPXM29	259	ASTM A 283/A 283M-03	Α	50, 66
ASTM A 27/A 27M-03	60-30	319, 323		В	51, 66
	65-35	319, 323		С	54, 68
	70-36	320, 323		D	56, 69
	70-40	320, 323	ASTM A 285/A 285M-03	Α	153
	N-1	359		В	153
	N-2	359		С	153
AOTM A 070 00	U-60-30	319, 323	ASTM A 29/A 29M-03		43
ASTM A 276-03		412, 415		1005	23
	201	400, 403		1006	23
	202	400, 403		1008	23
	205	415		1010	23
	302	400, 403			

624 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 29/A 29M-03	1011	43	ASTM A 29/A 29M-03	1119	436
(continued)	1012	23	(continued)	1132	436
	1013	43		1137	420
	1015	24		1139	420
	1016	24		1140	421
	1017	24		1141	421
	1018	24		1144	421
	1019	24		1145	436
	1020	25		1146	421
	1021	25		1151	421
	1022	25		12 L 13	424
	1023	25		12 L 14	424
	1025	26		12 L 15	424
	1026	26		1211	436
	1029	26		1212	422
	1030	26		1213	422
	1034	27		1215	422
	1034	27 27		1330	43
	1037	27 27		1335	43
		27 27		1340	43 43
	1038				43 43
	1039	28		1345	
	1040	28		1513	43
	1042	28		1518	43
	1043	28		1522	34
	1044	29		1524	43
	1045	29		1525	43
	1046	29		1526	43
	1049	30		1527	43
	1050	30		1536	34
	1053	30		1541	34
	1055	31		1547	43
	1059	31		1548	43
	1060	31		1551	43
	1064	32		1552	43
	1065	32		1561	43
	1069	32		1566	43
	1070	32		1572	43
	1071	32		4012	43
	1074	32		4023	43
	1075	32		4024	43
	1078	32		4027	43
	1080	33		4028	43
	1084	33		4032	43
	1086	33		4037	43
	1090	33		4042	43
	1095	33		4047	43
	11 L 09	423		4118	37
	11 L 17	423		4120	37
	11 L 37	423		4121	37
	11 L 41	423		4130	37
	11 L 44	423		4135	43
	11 L 44	423 423		4137	43 38
	1108	436		4140	38
	1109	420		4142	43
	1110	420		4145	38
	1116	436		4147	43
	1117	420		4150	38
	1118	420		4161	43

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 29/A 29M-03	4320	39	ASTM A 29/A 29M-03	94B17	43
(continued)	4340	39	(continued)	94B30	43
	4419	43		E4340	39
	4422	43		E9310	39
	4427	43	ASTM A 295-98		439
	4615	43		1070M	439
	4620	43		5160	439
	4621	43		5195	439
	4626	43		52100	435
	4715	43	ASTM	HC	351, 355
	4718	43	A 297/A 297M-97 (2003)		,
	4720	43		HD	351, 355
	4815	43		HE	351, 356
	4817	43		HF	351, 356
	4820	43		HH	352, 356
	5015	43		HI	352, 356
	5046	43		HK	352, 356
	50B44	41		HL	352, 357
	50B46	41		HN	353, 357
	50B50	41		HP	353, 357
	50B60	41		HT	353, 357
	5115	43		HU	353, 358
	5120	35		HX	354, 358
	5130	35		HW	354, 358
	5132	35 35	ASTM A 299/A 299M-02		153
	5135	35 35	ASTM A 302/A 302M-03	Α	117, 119
		36		В	118, 120
	5140 5145	36		С	137, 138
	5145 5147	43		D	139, 140
	5147 5150		ASTM A 312/A 312M-03		233, 244,
	5150	43			245, 262
	5155	43		TP304	225, 234
	5160 51860	43		TP304H	227, 236
	51B60	41		TP304L	226, 235
	6118	43		TP304LN	262
	6150	42		TP304N	262
	8115	43		TP309Cb	262
	81B45	43		TP309H	262
	8615	43		TP309HCb	262
	8617	43		TP309S	227, 236
	8620	39		TP310Cb	262
	8622	43		TP310H	262
	8625	43		TP310HCb	262
	8627	43		TP310S	227, 237
	8630	43		TP316	228, 238
	8637	43		TP316H	230, 240
	8640	39		TP316L	229, 239
	8642	43		TP316LN	262
	8645	43		TP316N	262
	8650	43		TP317	231, 241
	8655	43		TP317L	231, 241
	8660	43		TP321	231, 242
	8720	43		TP321H	232, 243
	8740	43		TP347	232, 243
	8822	43		TP347H	232, 243
	9254	43		TP347LN	262
	9255	43		TP348	262
	9259	43		TP348H	262
	9260	43		TPXM-10	262
				I IT AIVIT IU	202

626 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 312/A 312M-03	TPXM-11	262	ASTM A 322-91 (2001)	8617	43
(continued)	TPXM-15	262	(continued)	8620	39
	TPXM-19	262		8622	43
	TPXM-29	262		8625	43
ASTM A 313/A 313M-03		437		8627	43
	305	437		8630	43
	321	437		8637	43
	347	437		8640	39
	XM-16	437		8642	43
	XM-28	437		8645	43
ASTM A 322-91 (2001)		37		8655	43
ASTIVI A 322-91 (2001)	1330	43		8720	43
				8740	
	1335	43			43
	1340	43		8822	43
	1345	43		9259	43
	4023	43		9260	43
	4024	43		94B17	43
	4027	43		94B30	43
	4028	43		E4340	39
	4037	43	ASTM A 331/A 313M-03	302	429
	4047	43		304	429
	4118	37		316	429
	4130	37		631	429
	4137	38	ASTM A 333/A 333M-99	1	196, 198
	4140	38		10	260
	4142	43		11	260
	4145	38		3	197, 198
	4147	43		3	199, 20
	4150	38		4	260
	4161	43		6	197, 198
	4320	39		7	260
	4340	39		8	197, 198
	4615	43		8	199, 20
	4620	43		9	260
	4621	43		P122	260
	4626	43		P23	260
	4720	43		P911	260
	4815	43		P92	260
	4817	43	ASTM A 334/A 334M-99	1	196, 19
	4820	43		11	260
	50B44	41		3	199, 20
	50B46	41		6	197, 19
	50B50	41		7	260
	50B60	41		8	
	5117	43		9	199, 20 260
			ACTM A COE/A COENA CO	9 P1	
	5120	35	ASTM A 335/A 335M-03		214, 21
	5130	35		P11	219
	5132	35		P12	217, 21
	5135	35		P15	261
	5140	36		P2	216
	5150	43		P21	261
	5155	43		P22	220
	5160	43		P5	221
	51B60	41		P5b	261
	6118	43		P5c	261
	6150	42		P9	222
					261
	81B45	43		P91	りんコ

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 336/A 336M-03a	F1	279	ASTM A 352/A 352M-03	CA6NM	347, 348
	F11, Class 1	312		LC1	337, 338
	F11, Class 2	282		LC2	337, 338
	F11, Class 3	282		LC2-1	337, 338
	F12	281		LC3	337, 338
	F21, Class 1	285		LC4	359
	F21, Class 3	285		LC9	359
	F22, Class 1	283, 284		LCA	327
	F22, Class 3	283, 284		LCB	327
	F22V	283, 284		LCC	327
	F3V	285	ASTM		135, 136
	F3VCb	312	A 353/A 353M-93 (1999)		
	F5	286	ASTM A 355-89 (2000)	Α	40
	F5A	286		В	43
	F6	312		С	43
	F9	287		D	43
	F91	312	ASTM A 358/A 358M-01		233, 244,
	F911	312		004	245, 262
ASTM A 350/A 350M-02b	LF1, Class 1	272, 275		304	225, 234
	LF2, Class 1	273, 275		304H	227, 236
	LF2, Class 2	273, 275		304L	226, 235
	LF3, Class 1	289, 290		304LN	262
	LF3, Class 2	289, 290		304N	262
	LF5	312		309Cb	262
	LF6	312		309S	227, 236
	LF787	312		310Cb	262
	LF9	312		310S	227, 237
ASTM A 351/A 351M-03	CD3MWCuN	361		316	228, 238
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	CD-4MCu	349, 350		316H	230, 240
	CE20N	361		316L	229, 239
	CE8MN	361		316LN	262
	CF10	361		316N	262
	CF10M	361		321	231, 242
	CF10MC	361		347	232, 243
	CF10SMnN	361		348	262
	CF-3	349, 350		XM-19	262
	CF-3A	349, 350		XM-29	262
	CF-3M	349, 350	ASTM A 36/A 36M-03a		54, 68
	CF-3MA	349, 350	ASTM A 376/A 376M-02a		233, 244,
	CF3-MN	361		16-8-2H	262 262
	CF-8	349, 350		TP304	225, 234
	CF-8A	349, 350		TP304H	227, 236
	CF-8C	349, 350		TP304LN	226, 235
	CF-8M	349, 350		TP316	228, 238
	CG-3M	361		TP316H	230, 240
	CG6MMN	361		TP316LN	230, 240
	CG-8M	361		TP316N	262
	CH10	361		TP321	231, 242
	CH-20	361		TP321H	
	CH8	361		TP347	232, 243 232, 243
	CK-20	361		TP347 TP347H	232, 243
	CK3MnCuN	361		TP3476	262 262
	CN3MN	361	ASTM A 387/A 387M-03		202 123
	CN-7M	349, 350	ASTIVI A 30//A 30/IVI-U3	11, Class 1	
	CT15C	361		11, Class 2	123
	HK30	352, 356		12, Class 1	122
	HK40	352, 350 352, 357		12, Class 2	122
	HT30	353, 357		2, Class 1	121
	.1100	000, 007		2, Class 2	121

628 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 387/A 387M-03	21 L, Class 1	126	ASTM	1	360
(continued)	21, Class 1	126	A 487/A 487M-93 (2003)		
	21, Class 2	126		10	360
	22 L, Class 1	124, 125		11	360
	22, Class 1	124, 125		12	360
	22, Class 2	124, 125		13	360
	5, Class 1	127		14	360
	5, Class 1	127		16	360
	5, Class 1	127		2	360
	5, Class 2	127		4	360
	5, Class 2	127		6	360
	5, Class 2	127		7	360
	9, Class 1	153		8, Class A	335, 336
	9, Class 2	153		8, Class B	335, 336
	91, Class 2	128		8, Class C	335, 336
	911, Class 2	128		9	360
ASTM A 389/A 389M-03	C23	360		CA15 Class A	347
	C24	335, 336		CA15, Class A	348
ASTM A 409/A 409M-01		233, 244,		CA15, Class B	348
	TD004	262		CA15, Class C	348
	TP304	225, 234		CA15, Class D	348
	TP304L	226, 235		CA15M	360
	TP309Cb	262		CA6NM	347
	TP309S	262		CA6NM, Class A	348
	TP310Cb	262	A CTNA A 500 00	CA6NM, Class B	348
	TP310S	262	ASTM A 500-03	A	166, 177
	TP316	228, 238		В	168, 179
	TP316L	229, 239		С	169, 180
	TP317	231, 241	ACTM A 504 04	D	168, 179
	TP321	231, 242	ASTM A 501-01		168, 179
	TP347	232, 243	ASTM A 508/A 508M-03a	1	273, 275
ASTM	TP348	262		1a	273, 275
A 447/A 447M-93 (2003)	Type I	352, 356		2, Class 1	292
A 447/A 447/W 30 (2000)	Type II	352, 356		2, Class 2	292
ASTM A 455/A 455M-03		153		22, Class 3	283, 284
ASTM A 473-01		295, 296,		3, Class 1	293
		309, 310		3, Class 2	293
	304	298, 302		3V	285
	304L	298, 302		3VCb	312
	310	299, 303		4N, Class 1	312
	316	299, 303		4N, Class 2	312
	316L	299, 304		4N, Class 3	294
	317	300, 305		5, Class 1	312
	321	300, 306	ACTM A 511 OC	5, Class 2	312
	347	301, 306	ASTM A 511-96	29-4	259
	410	295, 296		29-4-2	259
	430	297		MT 302	259
ASTM A 485-03	1	435		MT 303Se	259
	B2, 100CrMnSi4-4	435		MT 304	190, 193
	B3, 100CrMnSi6-4	435		MT 304L	190, 193
	B4, 100CrMnSi6-6	435		MT 305	259
	B5, 100CrMo7	435		MT 309S	259
	B6, 100CrMo7-3	435		MT 310S	259
	B7, 100CrMo7-4	435		MT 316	191, 194
	B8, 100CrMnMoSi8-4-6	435		MT 316L	191, 194
	Grade 2	439		MT 317	259
	Grade 3	439		MT 321 MT 347	192, 195 192, 195
				Na 1 '2/1 /	

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 511-96 (continued) MT 403	259	ASTM A 513-03a	1026	169, 171,
	MT 405	188, 189	(continued)		173, 179,
	MT 410	188, 189			181, 182,
	MT 414	259		1030	183
	MT 416Se	259		1030	169, 171, 173, 174,
	MT 429	259			179, 174,
	MT 430	188, 189			183
	MT 431	259		1035	170, 171,
	MT 440A	259			173, 174,
	MT 443	259			180, 181,
	MT 446-1	259		1010	183, 184
	MT 446-2	259		1040	170, 171,
ASTM A 512-96 (2001)	1010	176			174, 180, 181, 183,
AOTWA 312 30 (2001)	1011	170, 180			184
	1012			1524	171, 174,
	1012	166, 176, 177			181, 183,
	1015	166, 177			184
	1016	171, 181		4118	258
	1018	171, 181		4130	185, 186
	1025	172, 182		4140	185, 187
	1030	172, 182		5130	258
				8620	258
	10S10	257		8630	258
	1110	170, 180	ASTM A 514/A 514M-00a	Α	82, 86
	1115	257		В	82, 86
	1117	257		С	82, 86
	15S10	257		E	82, 86
	18S10	257		F	82, 86
	37S10	257		H	82, 86
	MT 1010	165, 169,		J	82, 86
	MT 1015	176, 180		K	82, 86
	MT 1015	165, 171, 176, 181		M	82, 86
	MT 1017	171, 181		P	82, 86
	MT 1020	167, 172,		Q	82, 86
	1111 1020	177, 182		R	82, 86
	MT 1025	167, 178		S	
	MT 1030	170, 180		T	82, 86
ASTM A 513-03a	1008	165, 166,	A OTA A 545/A 545M 00		82, 86
		168, 169,	ASTM A 515/A 515M-03	60 [415]	104, 109
		176, 177,		65 [450]	105, 110
		178, 179		70 [485]	105, 111
	1010	165, 166,	ASTM A 516/A 516M-03	55 [380]	153
		167, 168, 169, 176,		60 [415]	104, 109
		177, 178,		65 [450]	105, 110
		179		70 [485]	105, 111
	1015	166, 168,	ASTM	Α	153
		169, 170,	A 517/A 517M-93 (1999)	D	150
		177, 178,		В	153
	1000	179		С	153
	1020	167, 169,		E	153
		170, 171, 177, 179,		F	153
		181		H	153
	1021	167, 169,		J	153
	- -	171, 172,		K	153
		177, 178,		M	153
		180, 181,		P	153
		182		Q	153
	1025	168, 170,		S	153
		171, 173,		Т	153
		178, 180, 181, 182			
		101, 102			

630 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
STM A 519-03	1020	166, 167,	ASTM A 519-03	50B46	258
		170, 171, 177, 178,	(continued)	50B50	258
		180, 181		50B60	258
	1025	167, 168,		5115	258
	.020	171, 173,		5120	258
		178, 181,		5130	258
		182		5132	258
	1035	169, 170,		5135	258
		173, 174,		5140	258
		179, 180, 182, 183		5145	258
	1045	170, 172,		5147	258
	10-10	174, 180,		5150	258
		182, 183,		5155	258
		184		5160	258
	1050	171, 173,		51B61	258
		174, 181,		6118	258
	1000	182, 183		6120	258
	1330	257		6150	258
	1335	257		8115	258
	1340	257		81B45	258
	1345	257		8615	258
	3140	258		8617	258
	4012	258		8620	258
	4023	258			
	4024	258		8622	258
	4027	258		8625	258
	4028	185, 186		8627	258
	4037	258		8630	258
	4042	258		8637	258
	4047	258		8640	258
	4063	258		8642	258
	4118	258		8645	258
	4130	185, 186		8650	258
	4135	185, 187		8655	258
	4137	185, 187		8660	258
	4140	185, 187		86B45	258
	4142	185, 187		8720	258
	4145	257		8735	258
	4147	258		8740	258
	4150	258		8742	258
	4320	258		8822	258
	4337	258		9255	258
	4340	258		9260	258
	4422	258		9262	258
	4427	258		94B15	258
	4520	258		94B17	258
				94B30	258
	4615 4617	258		94B40	258
	4617	258		9840	258
	4620	258		9850	258
	4621	258		E3310	258
	4718	258		E4337	258
	4720	258		E4340	258
	4815	258		E50100	258
	4817	258			
	4820	258		E51100	258
	5015	258		E52100	258
	5046	258		E7140	258
	50B40	258		E9310	258
	50B44	258			

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 529/A 529M-03	50 [345]	59, 70	ASTM A 542/A 542M-99	Type D, Class 1	153
	55 [380]	59, 70		Type D, Class 2	153
ASTM A 53/A 53M-02	Type E, Grade A	202, 204		Type D, Class 3	153
	Type E, Grade B	203, 205		Type D, Class 4	153
	Type F, Grade A	202, 204		Type D, Class 4a	153
	Type S, Grade A	202, 204		Type E, Class 4	153
	Type S, Grade B	203, 205		Type E, Class 4a	153
ASTM		118, 120	ASTM		
A 533/A 533M-93 (1999)	Type A, Class 1		A 543/A 543M-93 (1999)	Type B, Class 1	153
	Type A, Class 2	118, 120		Type B, Class 2	153
	Type A, Class 3	118, 120		Type B, Class 3	153
	Type C, Class 2	139, 140		Type C, Class 1	153
	Type C, Class 3	139, 140		Type C, Class 2	153
	Type D, Class 1	153		Type C, Class 3	153
	Type D, Class 2	153	ASTM	Type I	135, 136
	Type D, Class 3	153	A 553/A 553M-95 (2000)	2.	
	Type B, Class 1	137, 138		Type II	135, 136
	Type B, Class 2	137, 138	ASTM A 554-03	MT-301	259
	Type B, Class 3	137, 138		MT-302	259
				MT-304	190, 193
ACTA	Type C, Class 1	139, 140		MT-304L	190, 193
ASTM	1	105, 111		MT-305	259
A 537/A 537M-95 (2000)	2	108, 112		MT-309S	259
	3	108, 112		MT-309S-Cb	259
ASTM	1			MT-310S	259
A 541/A 541M-95 (1999)	I	273, 275			
A 341/A 341W-93 (1999)	11, Class 4	312		MT-316	191, 194
	1A	273, 275		MT-316L	191, 194
	1C	312		MT-317	259
	2, Class 1	292		MT-321	192, 195
				MT-330	259
	2, Class 2	292		MT-347	192, 195
	22, Class 3	283, 284		MT-429	259
	22, Class 4	312		MT-430	188, 189
	22, Class 5	312		MT-430-Ti	259
	22V	283, 284	ASTM	C2	209, 212
	3, Class 1	293	A 556/A 556M-96 (2001)		
	3, Class 2	293		A2	206, 210
	3V	285		B2	208, 211
	3VCb	312	ASTM A 564/A 564M-02a		415
	4N, Class 1	312		630	409, 410
	4N, Class 2	312		631	409, 411
	4N, Class 3	294		632	415
	5, Class 1	312		634	415
	5, Class 2	312		635	415
ASTM A 542/A 542M-99	Type A, Class 1	153		XM-12	415
701W 7 042/7 042W 00	• •	153		XM-13	415
	Type A, Class 2				
	Type A, Class 3	153		XM-16	415
	Type A, Class 4	153		XM-25	415
	Type A, Class 4a	153	ASTM A 572/A 572M-03a	42 [290], Type 1	72, 75
	Type B, Class 1	153		42 [290], Type 2	72, 75
	Type B, Class 2	153		42 [290], Type 3	72, 75
	Type B, Class 3	153		42 [290], Type 4	72, 75
	Type B, Class 4	153		42 [290], Type 5	72, 75
	Type B, Class 4a	153		50 [345], Type 1	72, 76
	Type C, Class 1	153		50 [345], Type 2	72, 76
	Type C, Class 2	153		50 [345], Type 3	72, 76
	Type C, Class 3	153		50 [345], Type 4	72, 76
	Type C, Class 4	153		50 [345], Type 5	72, 76
	Type C, Class 4a	153		55 [380], Type 1	73, 77
	. , po 0, 01000 Tu	.55		-0 [000], 1,p0 1	. 0,

632 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 572/A 572M-03a	55 [380], Type 2	73, 77	ASTM A 576-90b (2000)	11 L 44	423
(continued)	55 [380], Type 3	73, 77	(continued)	11 L 46	423
	55 [380], Type 4	73, 77		1109	43, 420
	55 [380], Type 5	73, 77		1110	43, 420
	60 [415], Type 1	74, 78		1116	43, 436
	60 [415], Type 2	74, 78		1117	43, 420
	60 [415], Type 3	74, 78		1118	43, 420
	60 [415], Type 4	74, 78		1119	43, 436
	60 [415], Type 5	74, 78		1132	43, 436
	65 [450], Type 1	74, 78		1137	43, 420
	65 [450], Type 2	74, 78		1139	43, 420
	65 [450], Type 3	74, 78		1140	43, 421
	65 [450], Type 4	74, 78		1141	43, 421
	65 [450], Type 5	74, 78		1144	43, 421
ASTM A 573/A 573M-00a	58 [400]	54, 68		1145	43, 421
	65 [450]	58, 69		1146	43, 421
	70 [485]	59, 70		1151	43, 421
ASTM A 576-90b (2000)	1008	23		12 L 13	424
	1010	23		12 L 14	424
	1012	23		12 L 15	424
	1015	24		1211	43, 436
	1016	24		1212	43, 422
	1017	24		1213	43, 422
	1018	24		1215	43, 422
	1019	24		12L14	43
	1020	25		1513	43
	1021	25		1518	43
	1022	25		1522	34
	1023	25		1524	43
	1025	26		1525	43
	1026	26		1526	43
	1029	26		1527	43
	1030	26		1536	34
	1035	27		1541	34
	1037	27		1547	43
	1038	27		1548	43
	1039	28		1551	43
	1040	28		1552	43
	1042	28		1561	43
	1043	28		1566	43
	1044	29		1572	43
	1045	29	ASTM		398, 399,
	1046	29	A 582/A 582M-95b (2000)		415
	1049	30	,	303	400, 403
	1050	30		303Se	400, 403
	1053	30		416	394, 396
		31		416Se	415
	1055	31		420F	394, 397
	1060 1070	32		420FSe	415
	1070	32 32		430F	398, 399
				430FSe	415
	1080	33		440F	415
	1084	33		440FSe	415
	1090	33		XM-1	415
	1095	33		XM-2	415
	11 L 09	423		XM-34	415
	11 L 17	423		XM-5	415
	11 L 37	423			415
	11 L 41	423		XM-6	410

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 588/A 588M-03a	A	73, 77	ASTM A 632-02a	TP 316	191, 194
	В	73, 77	(continued)	TP 316L	191, 194
	C	73, 77	(**************************************	TP 317	259
	K	73, 77		TP 321	192, 195
ACTM A FOE OR (2002)					
ASTM A 595-98 (2002)	A	171, 181		TP 347	192, 195
	В	171, 181		TP 348	259
	С	257	ASTM A 633/A 633M-01	Α	72, 75
ASTM A 600-92a (1999)	M1	438		С	74, 77
	M10	438		D	74, 77
	M2	432		E	74, 78
	M3, Class 1	432	ASTM A 645/A 645M-99a		154
	M3, Class 2	432	ASTM A 656/A 656M-03	50 [345], Type 3	72, 75
	M30	438	7.67. 333,7. 333 33	50 [345], Type 7	72, 75
	M33	438		60 [415], Type 3	73, 77
	M34	438		60 [415], Type 7	73, 77
	M36	432		70 [485], Type 3	74, 78
	M4	432		70 [485], Type 7	74, 78
	M41	438		80	98
	M42	432	ASTM A 662/A 662M-03	Α	113, 115
	M43	438		В	114, 116
	M44	438		С	114, 116
	M46	438	ASTM A 666-03		413
	M47	438	7.6114171.000.00	201, Class 1	
					372, 377
	M48	438		201, Class 2	372, 377
	M50	438		201L	372, 377
	M52	438		201LN	372, 377
	M6	438		202	372, 377
	M62	438		205	413
	M7	432		301	372, 378
	T1	431		301L	372, 379
	T15	431		301LN	372, 379
	T2	438		302	372, 379
	T4	431		304	
					373, 380
	T5	431		304L	373, 380
	T6	438		304LN	373, 381
	T8	438		304N	373, 381
ASTM A 606-01	Type 2	90, 95		316	374, 383
	Type 4	90, 95		316L	374, 383
ASTM A 608/A 608M-02	HC30	351, 355		316N	374, 384
	HD50	351, 355		XM-11	413
	HE35	351, 356		XM-14	413
	HF30	351, 356	ASTM A 668/A 668M-03	A	268, 271
			ASTIVI A 000/A 000IVI-03		
	HH30	352, 356		В	268, 271
	HH33	352, 356		С	268, 271
	HI35	352, 356		D	269, 271
	HK30	352, 356		E	270, 271
	HK40	352, 357		F	270, 271
	HL30	352, 357		G (GH)	311
	HL40	352, 357		H (HH)	311
	HN40	353, 357		J (JH)	311
	HT50	353, 357		K (KH)	311
	HU50	353, 358		L (LH)	311
	HW50	354, 358		M (MH)	311
	HX50	354, 358		N (NH)	311
ASTM A 612/A 612M-03		108, 112	ASTM A 678/A 678M-00a	Α	59, 70
ASTM A 632-02a	TP 304	190, 193		В	64, 71
	TP 304L	190, 193		С	65, 71
	TP 310	259		D	97
		=			

634 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 681-94 (1999)	A10	438	ASTM A 682/A 682M-02	1064	425
	A2	433	(continued)	1065	425
	A3	438		1070	425
	A4	438		1074	425
	A5	438		1080	437
	A6	438		1085	426
	A7	438		1086	426
	A8	438		1095	426
	A9	438	ASTM A 686-92 (1999)	W1-A-10	430
	D2	433		W1-A-11½	430
	D3	433		W1-A-8	430
	D4	438		W1-A-8½	430
	D5	438		W1-A-9	430
	D7	438		W1-C	438
	F1	438		W2-A-81/2	430
	F2	434		W2-A-9½	430
	H10	434		W2-C	438
	H11	434		W5	438
	H12	434	ASTM A 688/A 688M-03		228, 23
	H13	434	710 Till 71 000/71 000ill 00		237, 24
	H14	438			262
	H19	434		TP 316N	262
	H21	434		TP XM-29	262
	H22	438		TP304	225, 23
				TP304L	226, 23
	H23	438		TP304LN	226, 23
	H24	438		TP316	228, 23
	H25	438		TP316L	229, 23
	H26	438		TP316LN	230, 24
	H41	438	ASTM A 689-97 (2000)	1040	425
	H42	438	,	1050	425
	H43	438		1055	425
	L2	438		1060	425
	L3	438		1070	425
	L6	434		1095	426
	01	438		1078	425
	O2	438		4161	428
	O6	438		51 B 60	428
	07	438		5155	427
	P2	438		5160	427
	P20	438		6150	428
	P21	438		9260	427
	P3	438	ASTM A 693-03		413
	P4	438	ASTIM A 093-03	630	
	P5	438			387, 38
	P6	438		631	387, 39
	S1	438		632	387, 39
	S2	438		633	413
	S4	438		634	413
	S5	438		635	413
	S6	438		XM-12	413
	S7	438		XM-13	413
STM A 682/A 682M-02	1030	437		XM-16	413
	1035	437		XM-25	413
	1040	425		XM-9	413
	1045	437	ASTM	630	307, 30
	1050	425	A 705/A 705M-95(2000)		
			ACTRA A 700/A 700M 00-	100 (600)	00
			ASTM A 709/A 709M-03a	100 [690]	82
	1055 1060	425 425	ASTM A 709/A 709M-03a	100 [690], Type A 100 [690], Type B	86 86

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 709/A 709M-03a	100 [690], Type C	86	ASTM A 736/A 736M-03	C, Class 1	154
(continued)	100 [690], Type E	87	(continued)	C, Class 3	154
	100 [690], Type F	87	ASTM A 737/A 737M-99	В	105, 111
	100 [690], Type H	87		С	108, 112
	100 [690], Type J	87	ASTM A 738/A 738M-03a	В	108, 112
	100 [690], Type M	87		С	108, 112
	100 [690], Type P	87		D	154
	100 [690], Type Q	87		E	154
	100W [690W]	82	ASTM A 743/A 743M-03	CA15	339, 340
	100W [690W], Type A	86		CA15M	339, 340
	100W [690W], Type B	86		CA-28MWV	361
	100W [690W], Type C	86		CA40	339, 340
	100W [690W], Type E	87		CA-40F	361
	100W [690W], Type F	87		CA6N	361
	100W [690W], Type H	87		CA6NM	339, 340
	100W [690W], Type J	87		CB-30	361
	100W [690W], Type M	87		CB-6	361
	100W [690W], Type P	87		CC-50	361
	100W [690W], Type Q	87		CE-30	361
	36 [250]	54, 68		CF10SMnN	361
	50 [345], Type 1	72, 75		CF16F	361
	50 [345], Type 2	72, 75 72, 75		CF16Fa	361
	50 [345], Type 3	72, 75 72, 75		CF20	341, 344
	50 [345], Type 4	72, 75 72, 75		CF3	341, 344
		72, 75 72, 75		CF3M	342, 345
	50 [345], Type 5 50S [345S]	72, 73 97		CF3MN	342, 345
				CF8	
	50W [345W], Type A	79, 84		CF8C	341, 344
	50W [345W], Type B	79, 84			341, 344
	50W [345W], Type C	79, 84		CF8M	341, 345
	HPS 50W [HPS 345W]	97		CG-12	361
ACTM A 740/A 740M 00	HPS 70W [HPS 485W]	80, 84		CG3M	342, 346
ASTM A 710/A 710M-02	A, Class 1	81, 85		CG6MMN	361
	A, Class 2	79, 84		CG8M	342, 345
	A, Class 3	80, 84		CH-10	361
AOTNA A 740 04	B	98		CH20	342, 346
ASTM A 713-04	1055	425		CK20	361
	1060	425		CK-35MN	361
	1064	425		CK3MCuN	343, 346
	1065	425		CN3M	342, 346
	1070	425		CN3MN	343, 346
	1074	425		CN7M	342, 346
	1078	425	AOTA A 744/A 744A 00	CN-7MS	361
	1084	426	ASTM A 744/A 744M-00	CF3	341, 344
	1086	426		CF3M	342, 345
AOTHA A 704/A 704/A 00	1095	426		CF8	341, 344
ASTM A 724/A 724M-99	A	154		CF8C	341, 344
	В	154		CF8M	341, 345
	C	154		CG3M	342, 346
ASTM	Α	154		CG8M	342, 345
A 734/A 734M-87a (2003)	В	154		CK3MCuN	343, 346
ASTM A 735/A 735M-03	1	154		CN3MN	343, 346
ACTIVITA TOOLA TOOINITOO	2	154		CN7M	342, 346
	3	154		CN7MS	361
	4	154	ASTM A 757/A 757M-00	A1Q	327
ASTM A 736/A 736M-03				A2Q	327
70 I IVI A 700/A 700IVI-03	A, Class 1 A, Class 2	154 154		B2N	337, 338
	A, Class 2 A, Class 3	154 154		B2Q	337, 338
	n, 01000 0	104		B3N	337, 338

636 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 757/A 757M-00	B3Q	337, 338	ASTM A 871/A 871M-03	60 [415], Type IV	93, 96
(continued)	B4N	359	(continued)	65 [450], Type I	93, 96
	B4Q	359		65 [450], Type II	93, 96
	C1Q	359		65 [450], Type III	93, 96
	D1N1	359		65 [450], Type IV	93, 96
	D1N2	359	ASTM A 895-89 (2000)		436
	D1N3	359		303	424
	D1Q1	359		416	424
	D1Q2	359	ASTM A 958-00	SC 4130 Class 105/85	330, 332
	D1Q3	359		SC 4130 Class 115/95	330, 332
	E1Q	359		SC 4130 Class 130/115	330, 332
	E2N1	337, 338		SC 4130 Class 135/125	330, 332
	E2N2	337, 338		SC 4130 Class 150/135	330, 332
	E2N3	337, 338		SC 4130 Class 65/35	330, 332
	E2Q1	337, 338		SC 4130 Class 70/36	330, 332
	E2Q2	337, 338		SC 4130 Class 80/40	330, 332
	E2Q3	337, 338		SC 4130 Class 80/50	330, 332
	E3N	359		SC 4130 Class 90/60	330, 332
	E3N	347, 348		SC 4140 Class 105/85	330, 333
ASTM A 778-01	TP 304L	190, 193		SC 4140 Class 115/95	330, 333
	TP 316L	191, 194		SC 4140 Class 130/115	330, 333
	TP 317L	259		SC 4140 Class 135/125	330, 333
	TP 321	192, 195		SC 4140 Class 150/135	330, 333
	TP 347	192, 195		SC 4140 Class 160/145	330, 333
ASTM A 782/A 782M-90	Class 1	154		SC 4140 Class 165/150	330, 333
(2001)				SC 4140 Class 65/35	330, 333
	Class 2	154		SC 4140 Class 70/36	330, 333
	Class 3	154		SC 4140 Class 80/40	330, 333
ASTM A 803/A 803M-03	18-2	262		SC 4140 Class 80/50	330, 333
	25-4-4	262		SC 4140 Class 90/60	330, 333
	26-3-3	262		SC 4330 Class 105/85	330, 334
	29-4	262		SC 4330 Class 115/95	330, 334
	29-4-2	262		SC 4330 Class 130/115	330, 334
	29-4C	262		SC 4330 Class 135/125	330, 334
	TP XM-27	223, 224		SC 4330 Class 150/135	330, 334
	TP XM-33	262		SC 4330 Class 160/145	330, 334
	TP409	223, 224		SC 4330 Class 165/150	330, 334
	TP439	262		SC 4330 Class 210/180	330, 334
ASTM A 832/A 832M-99	21V	154		SC 4330 Class 65/35	330, 334
	22V	154		SC 4330 Class 70/36	330, 334
	23V	154		SC 4330 Class 80/40	330, 334
ASTM A 841/A 841M-03a	A, Class 1	114, 116		SC 4330 Class 80/50	330, 334
	A, Class 2	114, 116		SC 4330 Class 90/60	330, 334
	B, Class 1	114, 116		SC 4340	359
	B, Class 2	114, 116		SC 8620	359
	C, Class 1	114, 116		SC 8625	359
	C, Class 2	114, 116		SC 8630	359
	D, Class 3	154		SC 1020, Class 65/35	319, 323
	E, Class 4	154		SC 1020, Class 70/36	320, 323
	E, Class 5	154		SC 1025, Class 65/35	319, 323
	F, Class 6	154		SC 1025, Class 05/35 SC 1025, Class 70/36	320, 323
	F, Class 7	154		SC 1025, Class 70/36 SC 1030, Class 65/35	
	F, Class 8	154			319, 323
ASTM		135, 136		SC 1030, Class 70/36	320, 323
A 844/A 844M-93 (1999)		,		SC 1030, Class 80/40	321, 324
ASTM A 852/A 852M-03		81, 85		SC 1030, Class 80/50	321, 324
ASTM A 871/A 871M-03	60 [415], Type I	93, 96		SC 1040 Class 90/60	321, 324
	60 [415], Type II	93, 96		SC 1040, Class 70/36	320, 323
				SC 1040, Class 80/40	321, 324

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ASTM A 958-00	SC 1040, Class 80/50	321, 324	BS 3100:1991 AMD 1:1992	347C17	341, 344
(continued)	SC 1045 Class 105/85	322, 325	(continued)	410C21	339, 340
	SC 1045 Class 90/60	321, 324		420C24	351, 355
	SC 1045, Class 80/40	321, 324		420C28	339, 340
	SC 1045, Class 80/50	321, 324		420C29	339, 340
ASTM A 965/A 965M-02	F 304	298, 302		425C11	339, 340
	F 304H	298, 302		425C12	339, 340
	F 304L	298, 302		452C11	351, 355
	F 304LN	298, 303		452C12	351, 355
	F 304N	298, 302		A1	319, 323
	F 310	299, 303		A2	320, 323
	F 316	299, 303		A3	320, 324
	F 316H	300, 305		A4	320, 324
	F 316L	299, 304		A5	
				A6	321, 324
	F 316LN	300, 305			322, 325
	F 316N	299, 304		AL1	359
	F 321	300, 306		AL2	359
	F 321H	300, 306		AL3	359
	F 347	301, 306		AM1	359
	F310H	299, 303		AM2	359
ASTM A 984/A 984M-03	35	250, 253		AW1	359
	50	251, 254		AW2	359
	60	252, 255		AW3	359
	70	263		B1	330, 331
	80	252, 256		B2	359
ASTM B 625-99		375, 385,		B3	359
ACTN D 040 00		413		B4	359
ASTM B 649-02		402, 408,		B5	359
ASTM B 688-96		415 375, 385		B6	359
ASTM B 691-02				B7	359
ASTW B 091-02		402, 408, 415		BL2	359
BS 3100:1991 AMD 1:1992	302C25	359		BT1	359
	302C35	351, 356		BT2	359
	304C12	341, 344		BT3	359
	304C12LT196	341, 344		BW10	328, 329
	304C15	341, 344		BW2	359
	304C15LT196	341, 344		BW3	359
	309C30	352, 356		BW4	359
	309C32	352, 356	BS 3604-2:1991	620	217, 218
	309C35	352, 356	20 000 / 2//001	621	219
	309C40	351, 356		622	220
	310C40	352, 357	BS 3605-1:1991	215S15	262
			AMD 2:1997	210010	202
	310C45	352, 357		304S11	226, 235
	311C11	353, 357		304S31	225, 234
	316C12	342, 345		304S51	227, 236
	316C12LT196	342, 345		316S11	229, 239
	316C16	341, 345		316S13	229, 239
	316C16LT196	341, 345		316S31	228, 238
	317C16	342, 345		316S33	228, 238
	318C17	342, 345		316S51	230, 240
	330C11	353, 357		316S52	230, 240
	330C12	353, 357		321S31	231, 242
	331C40	353, 358		321S51	232, 243
	331C60	353, 358		347S31	
	332C11	342, 346			232, 243
	332C13	343, 346		347S51	233, 244
	332C15	343, 346			
	334C11	354, 358			

638 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
BS 3605-2:1992	304S11	226, 235	CSA Z245.1-2002	386 - Category II	251, 254
AMD 1:1997	00.100.1	005 004	(continued)	386 - Category III	251, 254
	304S31	225, 234		414 - Category I	246, 248
	316S11	229, 239		414 - Category II	251, 255
	316S13	229, 239		414 - Category III	251, 255
	316S31	228, 238		448 - Category I	246, 248
	316S33	228, 238		448 - Category II	252, 255
	321S31	231, 242		448 - Category III	252, 255
DO 0000 0 4000	347S31	232, 243		483 - Category I	246, 249
BS 6323-8:1982 AMD 2:1989	LW 12	188, 189		483 - Category II	252, 256
AIVID 2.1909	LW 19	188, 189		483 - Category III	252, 256
	LW 20	190, 193		550 - Category I	246, 249
	LW 21	190, 193		550 - Category II	252, 256
	LW 22	191, 194		550 - Category III	252, 256
	LW 23	191, 194		620 Category I	263
	LW 24	192, 195		620 Category II	263
	LWCF 20	190, 193		620 Category III	263
	LWCF 21	190, 193		690 Category I	263
	LWCF 22	191, 194		690 Category II	263
	LWCF 23	191, 194		690 Category III	263
	LWCF 24	192, 195	DIN 1615:1984	St 33	165, 176
CSA G40,21-04	260W (38W)	72, 75	DIN 1630:1984	St 37.4	207, 210
	260WT (38WT)	72, 75		St 44.4	208, 211
	300W (44W)	72, 76		St 52.4	209, 212
	300WT (44WT)	72, 76	DIN 1681:1985	GS-38	319, 323
	350A (50A)	90, 95		GS-45	319, 323
	350AT (50AT)	90, 95		GS-52	320, 324
	350R (50R)	90, 95		GS-60	321, 324
	350W (50W)	73, 77	DIN 17205:1992	GS-25 CrMo 4	330, 331
	350WT (50WT)	73, 77		GS-25 CrMo 4, Class I	330, 331
	380W (55W)	73, 77		GS-25 CrMo 4, Class II	330, 331
	400A (60A)	93, 96		GS-25 CrNiMo 4	359
	400AT (60AT)	93, 96		GS-30 CrMoV 6 4	359
	400W (60W)	74, 78		GS-30 CrNiMo 8 5	359
	400WT (60WT)	74, 78		GS-30 Mn 5	320, 324
	480A (70A)	93, 96		GS-33 CrNiMo 7 4 4	330, 334
	480AT (70AT)	93, 96		GS-33 CrNiMo 7 4 4,	330, 334
	480W (70W)	98		Class I GS-33 CrNiMo 7 4 4,	330, 334
	480WT (70WT)	80, 84		Class II	000, 004
	550A (80A)	93, 96		GS-34 CrMo 4	330, 332
	550AT (80AT)	93, 96		GS-34 CrMo 4, Class I	330, 332
	550W (80W)	98		GS-34 CrMo 4, Class II	330, 332
	550WT (80WT)	81, 85		GS-34 CrNiMo 6	359
	700Q (100Q)	83, 87		GS-35 CrMoV 10 4	359
	700QT (100QT)	83, 87		GS-42 CrMo 4	330, 333
CSA Z245.1-2002	241 - Category I	246, 247		GS-42 CrMo 4, Class I	330, 333
	241 - Category II	250, 253		GS-42 CrMo 4, Class II	330, 333
	241 - Category III	250, 253	DIN 17455:1999	X2CrNi19-11	190, 193
	290 - Category I	246, 247		X2CrNiMo17-12-2	191, 194
	290 - Category II	250, 253		X2CrNiMo18-14-3	191, 194
	290 - Category III	250, 253		X2CrNiMoN17-13-3	191, 194
	317 - Category I	246, 248		X2CrNiMoN17-13-5	192, 195
	317 - Category II	250, 253		X2CrNiN18-10	190, 193
	317 - Category III	250, 253		X2CrTi12	188, 189
	359 - Category I	246, 248		X3CrNiMo17-13-3	191, 194
	359 - Category II	251, 254		X3CrTi17	188, 189
	ooo oalogory n	201, 201			
	359 - Category III	251, 254		X5CrNi18-10	190, 193

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
DIN 17455:1999	X6Cr17	188, 189	DIN 28180:1985	St 37.0	207, 210
(continued)	X6CrNiNb18-10	192, 195	(continued)	TTSt 35 N	206, 207,
	X6CrNiTi18-10	192, 195		V E C-N; 10 10	210
DIN 17456:1999	X12Cr13	188, 189		X 5 CrNi 18 10 X 5 CrNiMo 17 12 2	225, 234
	X2CrNi19-11	190, 193		X 6 CrNiMoTi 17 12 2	228, 238 230, 241
	X2CrNiMo17-12-2	191, 194		X 6 CrNiTi 18 10	230, 241
	X2CrNiMo18-14-3	191, 194	DIN 28181:1985	St 37.0	207, 242
	X2CrNiMoN17-13-3	191, 194	DIN 20101.1905	St 37.8	207, 210
	X2CrNiMoN17-13-5	192, 195		TTSt 35 N	206, 210
	X2CrNiN18-10	190, 193		X 5 CrNi 18 10	225, 234
	X2CrTi12	188, 189		X 5 CrNiMo 17 12 2	228, 238
	X3CrNiMo17-13-3	191, 194		X 6 CrNiMoTi 17 12 2	230, 241
	X3CrTi17	188, 189		X 6 CrNiTi 18 10	231, 242
	X5CrNi18-10	190, 193	EN 10016-2:1995	C10D	231, 242
	X5CrNiMo17-12-2	191, 194	LN 10010-2.1993	C12D	23
	X6Cr17	188, 189		C15D	24
	X6CrAl13	188, 189		C18D	24
	X6CrNiNb18-10	192, 195		C20D	25
	X6CrNiTi18-10	192, 195		C26D	26
DIN 17457:1985	X 2 CrNi 19 11	226, 235		C32D	2 0 27
	X 2 CrNiMo 17 13 2	229, 239		C32D C38D	27 27
	X 2 CrNiMo 18 14 3	229, 239		C42D	28
	X 2 CrNiMoN 17 13 3	230, 240		C48D	29
	X 2 CrNiMoN 17 13 5	233, 244		C40D	23
	X 2 CrNiN 18 10	226, 235			30
	X 5 CrNi 18 10	225, 234		C50D	30
	X 5 CrNiMo 17 12 2	228, 238		C52D C56D	31
	X 5 CrNiMo17 13 3	228, 238		C58D	31
	X 6 CrNiMoTi 17 12 2	230, 241		C60D	31
	X 6 CrNiNb 18 10	232, 244		C62D	32
	X 6 CrNiTi 18 10	231, 242		C62D C66D	32 32
DIN 17458:1985	X 2 CrNi 19 11	226, 235		C68D	32
	X 2 CrNiMo 17 13 2	229, 239		C70D	32
	X 2 CrNiMo 18 14 3	229, 239		C72D	32
	X 2 CrNiMoN 17 13 3	230, 240		C76D	32
	X 2 CrNiMoN 17 13 5	233, 244		C78D	32
	X 2 CrNiN 18 10	226, 235		C70D	23
	X 5 CrNi 18 10	225, 234		C80D	32
	X 5 CrNiMo 17 12 2	228, 238		C82D	32
	X 5 CrNiMo17 13 3	228, 238		C86D	33
	X 6 CrNiMoNb 17 12 2	262		C88D	33
	X 6 CrNiMoTi 17 12 2	230, 241		C92D	33
	X 6 CrNiNb 18 10	232, 244		C9D	23
	X 6 CrNiTi 18 10	231, 242	EN 10016-4:1995	C10D2	23
DIN 17459:1992	X 3 CrNiMoN 17 13	230, 240	LN 10010-4.1995	C10D2 C12D2	23
	X 3 CrNiN 18 11	263		C15D2	24
	X 5 NiCrAlTi 31 20	233, 245		C18D2	24
	X 5 NiCrAlTi 31 20 RK	245		C20D2	24 25
	X 6 CrNi 18 11	227, 236		C26D2	26
	X 6 CrNiMo 17 13	230, 240		C32D2	26
	X 8 CrNiMoNb 16 16	263			
	X 8 CrNiMoVNb 16 13	263		C36D2	27 27
	X 8 CrNiNb 16 13	233, 244		C38D2	27
	X 8 CrNiTi 18 10	263		C3D2	23
	X 8 NiCrAlTi 32 21	233, 245		C40D2	28
DIN 28180:1985	13 CrMo 4 4	217, 218		C42D2	28
	15 Mo 3	213		C46D2	29
	St 35.8	207, 210		C48D2	29

640 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10016-4:1995	C50D2	30	EN 10028-3:2003	P275NL2	113, 115
(continued)	C52D2	30	(continued)	P355N	106, 111
	C56D2	31			114, 116
	C58D2	31		P355NH	106, 111
	C5D2	23		DOCENII 4	114, 116
	C60D2	31		P355NL1	114, 116
	C62D2	32		P355NL2	114, 116
	C66D2	32		P460NH	155
	C68D2	32		P460NL1	155
	C70D2	32		P460NL2	155
	C72D2	32	EN 10028-4:2003	11MnNi5-3	129
	C76D2	32		12Ni14	132, 133
	C78D2	32		13MnNi6-3	129
				15NiMn6	130
	C80D2	32		X12Ni5	134
	C82D2	32		X7Ni9	135, 136
	C86D2	33		X8Ni9	135, 136
	C88D2	33	EN 10028-5:2003	P355M	155
	C8D2	23		P355M1	155
	C92D2	33		P355M2	155
	C98D2	33		P420M	155
EN 10025:1993	E 295	60, 70		P420M1	155
	E 335	65, 71		P420M2	155
	E 360	65, 71		P460M	155
	S185	50, 66			
	S235J0	52, 67		P460M1	155
	S235J2G3	53, 67	EN 10000 0 0000	P460M2	155
	S235J2G4	53, 67	EN 10028-6:2003	P355Q	155
	S235JR	52, 67		P355QH	155
	S235JRG1	52, 67		P355QL1	155
	S235JRG2	52, 67		P355QL2	155
	S275J0	57, 69		P460Q	155
	S275J2G3	57, 69		P460QH	155
	S275J2G4	58, 69		P460QL1	155
				P460QL2	155
	S275JR	57, 69		P500Q	155
	S355J0	62, 71		P500QH	155
	S355J2G3	62, 71		P500QL1	155
	S355J2G4	63, 71		P500QL2	155
	S355JR	62, 71		P690Q	155
	S355K2G3	63, 71		P690QH	155
	S355K2G4	63, 71		P690QL1	155
EN 10028-2:2003	10CrMo9-10	124, 125		P690QL2	155
	12CrMoV12-10	155	EN 10028-7:2000	X1CrNi25-21	156
	13CrMo4-5	122	LIV 10020 7.2000	X1CrNiMoCuN20-18-7	156
	13CrMoSi5-5	123			
	13CrMoV9-10	155		X1CrNiMoCuN25-25-5	156
	15NiCuMoNb5-6-4	139, 140		X1CrNiMoN25-22-2	156
	16Mo3	117, 119		X1NiCrMoCu25-20-5	145, 149
	18MnMo4-5	117, 119		X1NiCrMoCu31-27-4	156
	20MnMoNi4-5	137, 138		X1NiCrMoCuN25-20-7	145, 149
	P235GH	103, 109		X2CrMoTi18-2	141, 142
	P265GH	104, 109		X2CrNi12	141, 142
	P295GH			X2CrNi19-11	143, 146
		105, 110		X2CrNiMo17-12-2	144, 147
	P355GH	107, 112		X2CrNiMo17-12-3	144, 147
	X10CrMoVNb9-1	128		X2CrNiMo18-14-3	144, 147
	X12CrMo5	127		X2CrNiMo18-15-4	144, 148
	X12CrMo9-10	155		X2CrNiMoCuN25-6-3	151, 152
	P275NH	104, 109			
	I ZI JINI I	104, 109		X2CrNiMoCuWN25-7-4	151, 152

EN 10028-7:2000 (Continued) X2CNIMON17-13-5 144, 148 (Continued) X2CNIMON18-12-4 X2CNIMON18-12-4 X2CNIMON18-7 X2CNIMON18-7 X2CNIMON18-7 X2CNIMON18-7 X2CNIMON18-7 X2CNIMON18-7 X2CNIMON18-7 X2CNIMON18-9 X2CNIMON18-9 X2CNIMON18-14 X2CNIMON18-9 X2CNIMON18-14 X2CNIMON18-15 X2CNIMON18-15 X2CNIMON18-16 X2CNIMON18-18 X2	Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
X2CNMMoN18-12-4 144, 148 C35E X2CNMMoN25-7-4 151, 152 C40E X2CNMMoN25-7-4 151, 152 C40E X2CNMN18-10 143, 146 C45E X2CNMN18-9 143, 146 C45R X2CNMN18-9 143, 146 C45R X2CNMN18-9 X2CNMN18-9 X2CNMN18-9 X2CNMN18-9 X2CNMN18-9 X2CNMN18-9 X2CNMN18-9 X2CNMN18-9 X2CNMN18-1 X2CMMN18-1 X2CNMN18-1 X2CMMN18-1	EN 10028-7:2000	X2CrNiMoN17-13-3	144, 148	EN 10083-1:1991	C30E	26
X2C/NIMON25-5-3 151, 152 C35R X2C/NIMON25-7-4 151, 152 C40E X2C/NIN18-10 143, 146 C45R X2C/NIN18-7 143, 146 C45R X2C/NIN18-9 143, 146 C45R X2C/NIN18-9 143, 146 C45R X2C/NIN18-9 143, 146 C45R X2C/NIN18-1 151, 152 C50E X2C/TIN18 141, 142 C55E X2C/TIN18 141, 142 C55E X3C/NIM013-4 141, 142 C55R X3C/NIM017-13-3 156 C60P X3C/NIM017-13-3 156 C60P X3C/NIM016-5-1 156 C25 X3C/NIM017-12-2 143, 146 C30 X5C/NIM017-12-2 143, 147 C35 X5C/NIM19-10 143, 146 C40 X5NC/AIT31-20 (HRA) 156 C45 X5C/NIB-10 143, 146 C40 X5NC/AIT31-20 (HRA) 156 C45 X5C/NIB-10 143, 146 C50 X5C/NIB-10 143, 146 C50 X5C/NIB-10 143, 147 C55 X5C/NIB-11 143, 146 C50 X5C/NIB-12 144, 148 EN 10083-3:1995 20MnB5 X5C/NIB-10 145, 149 S60 S60 X5C/NIB-11 145, 149 S60 S60 X5C/NITI18-10 145, 149 S60 S60 S60 S60 X5C/NITI18-10 145, 149 S60	(continued)	X2CrNiMoN17-13-5	145, 148	(continued)	C30R	26
X2C/NIM0R36-7-4 151, 152 C40E X2C/NIN18-10 143, 146 C45F X2C/NIN18-7 143, 146 C45F X2C/NIN18-9 143, 146 C45F X2C/NIN18-9 143, 146 C45F X2C/NIN18-9 143, 146 C45F X2C/NIN18-9 143, 146 C50F X2C/TIN17 156 C50R X2C/TIN17 156 C50R X2C/TIN18 141, 142 C55F X3C/NIM013-4 141, 142 C55F X3C/NIM013-4 X3C/NIM013-4 X3C/NIM013-4 X3C/NIM013-4 X3C/NIM015-1-3 143, 147 C60E X3C/NIM015-1 156 C25 X3C/NIM16-5-1 156 C25 X3C/NIM16-5-1 156 C25 X3C/NIM16-1-12 143, 146 C30 C30 X3C/NIM16-1-12 143, 146 C40 X3C/NIM16-1 X3C/NIM1		X2CrNiMoN18-12-4	144, 148		C35E	27
X2C/NIN18-10		X2CrNiMoN22-5-3	151, 152		C35R	27
X2C/NIN18-7		X2CrNiMoN25-7-4	151, 152		C40E	28
X2C/NIN18-9		X2CrNiN18-10	143, 146		C40R	28
X2C/NIN23-4		X2CrNiN18-7	143, 146		C45E	29
X2C/TIT17		X2CrNiN18-9	143, 146		C45R	29
X2C/TINID18		X2CrNiN23-4	151, 152		C50E	30
X2C/TINID18		X2CrTi17			C50R	30
N3C/NIMO17-13-3		X2CrTiNb18	141, 142		C55E	31
X3C/NIMO17-13-3		X3CrNiMo13-4	•			31
N3C/NIMOBN17-13-3 156						31
X3C/Ti17						31
X4Cr\MiMo16-5-1 156 C25 X5Cr\MiMo17-12-2 143, 146 C30 X5Cr\MiMo17-12-2 143, 147 C35 X5Cr\MiMo17-13-20 (+RA) 156 C45 X5Cr\MiMo18-10 143, 146 C50 X6Cr\Mi23-13 143, 147 C55 X6Cr\Mi25-20 143, 147 C55 X6Cr\MiMo18-10 143, 148 EN 10083-3:1995 20MnB5 X6Cr\MiMo117-12-2 144, 148 EN 10083-3:1995 20MnB5 X6Cr\MiMo117-12-2 144, 148 EN 10083-3:1995 20MnB5 X6Cr\MiMo118-10 145, 149 30MnB5 X6Cr\MiT18-10 145, 149 30MnB5 X6Cr\MiT18-10 145, 149 EN 10084:1998 10NiCr5-4 X8Cr\MiNb16-13 145, 149 EN				FN 10083-2:1991		25
X5C/NiNe1-10						26
XSC/NIN19-9						26
X5C/NIN19-9						27
X5NICrAITi31-20 (+RA)						28
X6CrNi18-10						29
X6CrNi23-13		, ,				30
X6CrNi25-20			•			
X6CrNiMoNb17-12-2						31
X6CrNiMoTi17-12-2				EN 10002 2:1005		31
X6CrNiNb18-10				EN 10083-3:1995		44
X6CrNiTi12			•			41
X6CrNiTil18-10 145, 149 38MnB5 X6CrNiTiB18-10 145, 149 39MnCrB5-2 X8CrNiNb16-13 145, 149 EN 10084:1998 10NiCr5-4 X8NiCrAITi32-21 145, 150 14NiCrMo13-4 EN 10083-1:1991 25CrMo64 37 15NiCr13 25CrMoS4 37 16MnCrB 28Mn6 34 16MnCrB 30 CrNiMo 8 44 16MnCrB5 34 CrNiMo 6 44 16NiCr4 34CrMo4 35 17Cr3 34CrMo54 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 37CrG4 35 17CrS3 36 CrNiMo 16 44 17NiCrMo6-4 37CrS4 35 18CrMoA 38Cr2 44 18NiCr5-4 41Cr4 36 20MnCr3 41Cr4 36 20MnCr5 41Cr64 36 20MnCr5 42CrMo54 38 20MoCr3 42CrMo54 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td>44</td>						44
X6CrNiTiB18-10						41
X8CrNiNb16-13						44
EN 10083-1:1991 X8NiCrAITi32-21 145, 150 14NiCrMo13-4 EN 10083-1:1991 25CrMo4 37 15NiCr13 25CrMo54 37 16MnCr5 28Mn6 34 16MnCr85 30 CrNiMo 8 44 16MiCr85 34 CrNiMo 6 44 16NiCr84 34CrMo4 35 16NiCr84 34CrMo54 38 17Cr03 34CrS4 35 17CrNi6-6 34CrS4 35 17CrNi6-6 36 CrNiMo 4 44 17NiCrMo6-4 37Cr4 35 18CrMo4 37Cr54 35 18CrMo4 37Cr54 35 18CrMo4 37Cr54 35 18CrMo4 38Cr2 44 18NiCr5-4 41Cr4 36 20MnCr5 41Cr4 36 20MnCr5 42CrMo4 38 20MoCr4 42CrMo4 38 20MoCr4 42CrMo54 38 20MoCr53 46Cr4 44 20MoCr53 46Cr54 44 20MoCr54 46Cr64						41
EN 10083-1:1991 25CrMoS4 37 15NiCr13 25CrMoS4 37 16MnCr5 28Mn6 34 16MnCr85 30 CrNiMo 8 44 16MnCrS5 34 CrNiMo 6 44 16NiCr4 34Cr4 35 17Cr3 34CrMo94 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 37Cr4 35 18CrMo54 37CrS4 35 18CrMo54 38Cr2 44 18CrMoS4 38CrS2 44 18NiCr5-4 41CrS4 36 20MnCr5 41CrS4 36 20MnCr5 42CrMoS4 38 20MoCr3 42CrMoS4 38 20MoCr3 42CrMoS4 38 20MoCr53 46Cr4 44 20MoCrS3 46CrS4 50CrMo4 38 20MoCrS4				EN 10084:1998		44
25CrMoS4 37 16MnCr5 28Mn6 34 16MnCr85 30 CrNiMo 8 44 16MnCr85 34 CrNiMo 6 44 16NiCr4 34Cr4 35 16NiCrS4 34CrMoS4 38 17Cr3 34CrMoS4 35 17CrS3 36 CrNiMo 6 44 17NiCrMo6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMoS4 38Cr2 44 18CrMoS4 38CrS2 44 18CrMo7-6 38CrS2 44 18CrMo7-6 41CrS4 36 20MnCr5 41CrS4 36 20MnCr5 41CrS4 37CrS4 38 20MoCrS 42CrMoS4 44 20MoCrS3 46CrS4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20MoCrS4						39
28Mn6 34 16MnCrB5 30 CrNiMo 8 44 16MnCrS5 34 CrNiMo 6 44 16NiCr4 34Cr4 35 16NiCrS4 34CrMo4 38 17Cr3 34CrMoS4 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMo54 38CrS2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41CrS4 36 20MnCr5 41CrS4 36 20MnCr5 42CrMo4 38 20MoCr3 42CrMo54 38 20MoCr3 42CrMo54 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2	EN 10083-1:1991					38
30 CrNiMo 8		25CrMoS4			16MnCr5	44
34 CrNiMo 6 44 16NiCr4 34Cr4 35 16NiCrS4 34CrMo4 38 17Cr3 34CrMoS4 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMo54 38CrS2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41CrS4 36 20MnCrS5 41CrS4 38 20MoCrS4 42CrMoS4 38 20MoCrS4 46CrS4 44 20MoCrS3 46CrS4 50CrMo4 38 20MoCrS4		28Mn6	34			44
34Cr4 35 16NiCrS4 34CrMo4 38 17Cr3 34CrMoS4 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46Cr54 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2			44		16MnCrS5	44
34CrMo4 38 17Cr3 34CrMoS4 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCr5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		34 CrNiMo 6	44		16NiCr4	44
34CrMoS4 38 17CrNi6-6 34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18NiCr5-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCr5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20MicrMo2-2		34Cr4	35		16NiCrS4	44
34CrS4 35 17CrS3 36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCr55 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		34CrMo4	38		17Cr3	35
36 CrNiMo 4 44 17NiCrMo6-4 36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		34CrMoS4	38		17CrNi6-6	44
36 NiCrMo 16 44 17NiCrMoS6-4 37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		34CrS4	35		17CrS3	35
37Cr4 35 18CrMo4 37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		36 CrNiMo 4	44		17NiCrMo6-4	44
37CrS4 35 18CrMoS4 38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		36 NiCrMo 16	44		17NiCrMoS6-4	44
38Cr2 44 18CrNiMo7-6 38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		37Cr4	35		18CrMo4	37
38CrS2 44 18NiCr5-4 41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		37CrS4	35		18CrMoS4	37
41Cr4 36 20MnCr5 41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		38Cr2	44		18CrNiMo7-6	44
41CrS4 36 20MnCrS5 42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		38CrS2	44		18NiCr5-4	44
42CrMo4 38 20MoCr3 42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		41Cr4	36		20MnCr5	44
42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		41CrS4	36		20MnCrS5	44
42CrMoS4 38 20MoCr4 46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2		42CrMo4	38		20MoCr3	37
46Cr4 44 20MoCrS3 46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2						37
46CrS4 44 20MoCrS4 50CrMo4 38 20NiCrMo2-2						37
50CrMo4 38 20NiCrMo2-2						37
						39
51CrV4 42 20NiCrMoS2-2		51CrV4	42		20NiCrMoS2-2	39
C22E 25 20NiCrMoS6-4						39
C22R 25 22CrMoS3-5						37
C25E 26 28Cr4						35
C25E 26 28CrS4						35 35
02311 20 200134		02011	20		200104	55

642 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10084:1998	C10E	23	EN 10088-2:1995	X2CrNiMoCuWN25-7-4	392, 393
(continued)	C10R	23	(continued)	X2CrNiMoN17-11-2	375, 384
	C15E	24		X2CrNiMoN17-13-3	375, 384
	C15R	24		X2CrNiMoN17-13-5	375, 385
	C16E	24		X2CrNiMoN18-12-4	375, 385
	C16R	24		X2CrNiMoN22-5-3	392, 393
EN 10085:2001	24CrMo13-6	44		X2CrNiMoN25-7-4	392, 393
	31CrMo12	44		X2CrNiN18-10	373, 381
	31CrMoV9	44		X2CrNiN18-7	372, 379
	32CrAlMo7-10	40		X2CrNiN23-4	392, 393
	33CrMoV12-9	44		X2CrTi12	368, 370
	34CrAlMo5-10	40		X2CrTi17	368, 370
	34CrAlNi7-10	40		X2CrTiNb18	368, 371
	40CrMoV13-9	44		X2NiCrMo18-15-4	375, 384
	41CrAlMo7-10	40		X30Cr13	366, 367
EN 10087:1998	10S20	420		X39Cr13	414
	10SPb20	423		X39CrMo17-1	414
	11SMn30	422		X3CrNb17	368, 370
	11SMn37	422		X3CrNiMo13-4	414
	11SMnPb30	424		X3CrNiMo17-13-3	374, 383
	11SMnPb37	424		X3CrTi17	368, 370
	15SMn13	420		X46Cr13	414
	35S20	420		X4CrNi18-12	373, 381
	35SPb20	436		X4CrNiMo16-5-1	414
	36SMn14	420		X50CrMoV15	414
	36SMnPb14	423		X5CrNi18-10	373, 380
	38SMn28	420		X5CrNiCuNb16-4	387, 389
	38SMnPb28	423		X5CrNiMo17-12-2	374, 383
	44SMn28	421		X6Cr13	366, 367
	44SMnPb28	423		X6Cr17	368, 370
	46S20	421		X6CrAl13	368, 370
EN 40000 0 4005	46SPb20	423		X6CrMo17-1	368, 370
EN 10088-2:1995	1XNiCrMoCuN25-20-7	375, 385		X6CrMoNb17-1	414
	X10CrNi18-8	372, 378		X6CrNi17-1	414
	X12Cr13	366, 367		X6CrNiMoNb17-12-2	375, 384
	X12CrMnNiN17-7-5	372, 377		X6CrNiMoTi17-12-2	375, 384
	X12CrMnNiN18-9-5	372, 377		X6CrNiNb18-10	376, 386
	X1CrNi25-21	414		X6CrNiTi12	414
	X1CrNiMoCuN20-18-7	374, 382		X6CrNiTi18-10	376, 386
	X1CrNiMoCuN25-25-5	414		X7CrNiAl17-7	387, 390
	X1CrNiMoN25-22-2	374, 382		X8CrNiMoAl15-7-2	387, 391
	X1CrNiSi18-15-4	373, 381		X8CrNiS18-9	414
	X1NiCrMoCu25-20-5	375, 385	EN 10088-3:1995	X105CrMo17	395, 397
	X1NiCrMoCu31-27-4	414		X10CrNi18-8	400, 403
	X20Cr13	366, 367		X12Cr13	394, 396
	X2CrAlTi18-2	414		X12CrS13	424
	X2CrMnNiN17-7-5	372, 377		X12CrS13	394, 396
	X2CrMoTi17-1	414		X14CrMoS17	416
	X2CrMoTi18-2	369, 371		X17CrNi16-2	394, 397
	X2CrMoTi29-4	369, 371		X1CrNiMoCuN20-18-7	416
	X2CrNbZr17	414		X1CrNiMoCuN25-25-5	416
	X2CrNi12	368, 370		X1CrNiSi18-15-4	416
	X2CrNi18-9	373, 380		X1NiCrMoCu25-20-5	416
	X2CrNi19-11	373, 380		X1NiCrMoCu25-20-5	402, 408
	X2CrNiMo17-12-2	374, 383		X1NiCrMoCu31-27-4	416
	X2CrNiMo17-12-3	374, 383		X1NiCrMoCuN25-20-7	416
	X2CrNiMo18-14-3	374, 383		X20Cr13	394, 396
	X2CrNiMoCuN25-6-3	392, 393		X29CrS13	394, 397
		,			,

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10088-3:1995	X2CrMoTiS18-2	398, 399	EN 10089:2002	54SiCrV6	428
(continued)	X2CrNi12	416	(continued)	55Cr3	427
	X2CrNi18-9	400, 404		56Si7	425
	X2CrNi19-11	416		56SiCr7	437
	X2CrNiMo17-12-2	401, 406		60Cr3	427
	X2CrNiMo17-12-3	401, 406		60CrMo3-1	428
	X2CrNiMo18-14-3	401, 406,		60CrMo3-2	428
	V00-N!M-40-45-4	416		60CrMo3-3	428
	X2CrNiMo18-15-4	402, 408		60SiCrV7	437
	X2CrNiMoCuN25-6-3	416		61SiCr7	437
	X2CrNiMoCuWN25-7-4	416	EN 10095:1999	NiCr15Fe	414, 416
	X2CrNiMoN17-11-2	401, 407		NiCr20Ti	414, 416
	X2CrNiMoN17-13-3	401, 407		NiCr22Mo9Nb	414, 416
	X2CrNiMoN17-13-5	402, 408		NiCr23Fe	414, 416
	X2CrNiMoN22-5-3	412		NiCr28FeSiCe	414, 416
	X2CrNiMoN25-7-4	416		X10CrAlSi13	414, 416
	X2CrNiN18-10	400, 405		X10CrAlSi18	414, 416
	X2CrNiN23-4	416		X10CrAlSi25	414, 416
	X30Cr13	394, 396		X10CrAlSi7	414, 416
	X39Cr13	416		X10NiCrAlTi32-21	414, 416
	X39CrMo17-1	416		X10NiCrSi35-19	414, 416
	X3CrNiCu18-9-4	416		X10NiCrSiNb35-22	414, 416
	X3CrNiCu19-9-2	416		X12CrNi23-13	374, 382,
	X3CrNiCuMo17-11-3-2	416			402, 408
	X3CrNiMo13-4	416		X12NiCrSi35-16	414, 416
	X3CrNiMo17-13-3	401, 406		X15CrNiSi20-12	414, 416
	X3CrNiMoN27-5-2	416		X15CrNiSi25-21	402, 408
	X46Cr13	416		X15CrNiSi25-4	414, 416
	X4CrNi18-12	401, 405		X18CrN28	398, 399
	X4CrNiMo16-5-1	416		X25CrMnNiN25-9-7	414, 416
	X50CrMoV15	416		X3CrAlTi18-2	414, 416
	X5CrNi18-10	400, 404		X6CrNiSiNCe19-10	414, 416
	X5CrNiCuNb16-4	409, 410		X6NiCrNbCe32-27	414, 416
	X5CrNiMo17-12-2	401, 406		X6NiCrSiNCe35-25	414, 416
	X5CrNiMoCuNb14-5	416		X8CrNi25-21	414, 416
	X6Cr13	398, 399		X8CrNiTi18-10	414, 416
	X6Cr17	398, 399		X9CrNiSiNCe21-11-2	414, 416
	X6CrMo17-1	398, 399	EN 10113-2:1998	S275N	98
	X6CrMoS17	398, 399		S275NL	98
	X6CrNiMoNb17-12-2	416		S355N	73, 77
	X6CrNiMoTi17-12-2	402, 407		S355NL	73, 77
	X6CrNiNb18-10	402, 408		S420N	98
	X6CrNiTi18-10	402, 408		S420NL	98
	X6NiCrCuS18-9-2	416		S460N	98
	X70CrMo15	394, 397		S460NL	98
	X7CrNiAl17-7	409, 411	EN 10113-3:1993	S275M	98
	X8CrNiS18-9	400, 403, 424		S275ML	98
	X90CrMoV18	416		S355M	72, 76
EN 10089:2002	38Si7	425		S355ML	72, 76
214 10000:2002	45SiCrV6-2	437		S420M	74, 77
	46Si7	425		S420ML	74, 77
	46SiCrMo6	437		S460M	98
	50SicrMo6	437		S460ML	98
	51CrV4	428	EN 10132-4:2000	102Cr6	437
	52SiCrNi5	437		125Cr2	437
	52crMoV4	437		48Si7	437
	54SiCr6	427		56Si7	437
	5.0.0.0	,			

644 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10132-4:2000	75Ni8	437	EN 10155:1993 (continued)		93, 96
(continued)	80CrV2	437	EN 10208-1:1997	L210GA	246, 247
	C100S	426		L235GA	263
	C125S	437		L245GA	246, 247
	C55S	425		L290GA	246, 247
	C60S	425		L360GA	246, 248
	C67S	425	EN 10208-2:1996	L245MB	250, 253
	C75S	425		L245NB	250, 253
	C85S	426		L290MB	250, 253
	C90S	426		L290NB	250, 253
	51CrV4	428		L360MB	251, 254
EN 10137-2:1996	S460Q	80, 84		L360NB	251, 254
	S460QL	80, 84		L360QB	251, 254
	S460QL1	80, 84		L415MB	251, 255
	S500Q	80, 84		L415NB	251, 255
	S500QL	80, 84		L415QB	251, 255
	S500QL1	80, 84		L450MB	252, 255
	S550Q	81, 85		L450QB	252, 255
	S550QL	81, 85		L485MB	252, 256
	S550QL1	81, 85		L485QB	252, 256 252, 256
	S620Q				
	S620QL	82, 86 82, 86		L555MB	252, 256 252, 256
		•	EN 10213-2:1995	L555QB	-
	S620QL1	82, 86	EN 10213-2:1995	G12MoCrV5-2	359
	S690Q	82, 87		G17CrMo5-5	335, 336
	S690QL	82, 87		G17CrMo9-10	335, 336
	S690QL1	82, 87		G17CrMoV5-10	335, 336
	S890Q	98		G20Mo5	335, 336
	S890QL	98		GP240GH	326
	S890QL1	98		GP240GR	326
	S960Q	98		GP280GH	326
	S960QL	98		GX15CrMo5	335, 336
EN 10137-3:1996	S500A	81, 85		GX23CrMoV12-1	347, 348
	S500AL	81, 85		GX4CrNi13-4	347, 348
	S550A	81, 85		GX4CrNiMo16-5-1	359
	S550AL	81, 85		GX8CrNi12	347, 348
	S620A	82, 86	EN 10213-3:1995	G17Mn5	327
	S620AL	82, 86		G17NiCrMo13-6	337, 338
	S690A	82, 87		G18Mo5	337, 338
	S690AL	82, 87		G20Mn5	327
EN 10151:2002	X10CrNi18-8	429		G9Ni10	337, 338
	X11CrNiMnN19-8-6	437		G9Ni14	337, 338
	X12CrMnNiN17-7-5	437		GX3CrNi13-4	347, 348
	X20Cr13	437	EN 10213-4:1995	GX2CrNi19-11	349, 350
	X30Cr13	429		GX2CrNiMo19-11-2	349, 350
	X39Cr13	429		GX2CrNiMoCuN25-6-3-3	349, 350
	X5CrNi18-10	429		GX2CrNiMoN22-5-3	361
	X5CrNiMo17-12-2	429		GX2CrNiMoN26-7-4	361
	X6Cr17	437		GX2NiCrMo28-20-2	349, 350
	X7CrNiAl17-7	429		GX5CrNi19-10	349, 350
EN 10155:1993	S235J0W	88, 94		GX5CrNiMo19-11-2	349, 350
	S235J2W	88, 94		GX5CrNiMoNb19-11-2	349, 350
	S355J0W	92, 96		GX5CrNiNb19-11	349, 350
	S355J0WP	92, 96	EN 10216-1:2002	P195TR1	202, 204
	S355J2G1W	92, 96		P195TR2	202, 204
	S355J2G2W	92, 96		P235TR1	202, 204
	S355J2WP	92, 96		P235TR2	202, 204
	S355K2G1W	92, 96		P265TR1	203, 205
	5555172G 1 VV	JZ, JU		1 2001111	200, 200

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10216-1:2002	P265TR2	203, 205	EN 10217-2:2002	P235GH	207, 210
(continued)	400-14-5 5	040	(continued)	P265GH	208, 211
EN 10216-2:2002	10CrMo5-5	219	EN 10217-3:2002	P275NL1	261
	10CrMo9-10	220		P275NL2	261
	11CrMo9-10	220		P355N	261
	13CrMo4-5	217, 218		P355NH	261
	14MoV6-3	216		P355NL1	261
	15NiCuMoNb5-6-4	261		P355NL2	261
	16Mo3	213		P460N	261
	20CrMoV13-5-5	261		P460NH	261
	20MnNb6	261		P460NL1	261
	25CrMo4	261		P460NL2	261
	8MoB5-4	214, 215	EN 10217-4:2002	P215NL	196, 198
	P195GH	206, 210		P265NL	197, 198
	P235GH	207, 210	EN 10217-5:2002	16Mo3	213
	P265GH	208, 211		P235GH	207, 210
	X10CrMoVNb9-1	222		P265GH	208, 211
	X11CrMo5+I	221	EN 10217-6:2002	P215NL	196, 198
	X11CrMo5+NT1	221		P265NL	197, 198
	X11CrMo5+NT2	221	EN 10222-2:1999	11CrMo9-10	283, 284
	X11CrMo9-1+I	222		13CrMo4-5	281
	X11CrMo9-1+NT	222		14MoV6-3	312
	X20CrMoV11-1	261		15MnCrMoNiV5-3	312
EN 10216-3:2002	P275NL1	259		15MnMoV4-5	312
	P275NL2	196, 198		16Mo3	279
	P355N	259		18MnMoNi5-5	312
	P355NH	259		P245GH	272, 275
	P355NL1	259		P280GH	
	P355NL2	259		P305GH	273, 275
	P460N	259			273, 275
	P460NH	259		X10CrMoVNb9-1	287
	P460NL1	259		X16CrMo5-1	286
	P460NL2	259		X16CrMo5-1	286
	P620Q	259	EN 10000 0 1000	X20CrMoV11-1	288
	P620QH	259	EN 10222-3:1998	12Ni14	289, 290
	P620QL	259		13MnNi6-3	291
	P690Q	259		15NiMn6	289, 290
	P690QH	259		X12Ni5	289, 290
	P690QL1	259		X8Ni9	289, 290
	P690QL2	259	EN 10222-4:1998 A1:2001	P285NH	272, 275
EN 10216-4:2002	11MnNi5-3	199, 200		P285QH	272, 275
EN 10210-4.2002	12Ni14			P355NH	273, 275
		199, 200		P355QH1	273, 275
	13MnNi6-3	199, 200		P420NH	274, 276
	26CrMo4-2	199, 201		P420QH	274, 276
	P215NL	196, 198	EN 10222-5:1999	X2CrNi18-9	298, 302
	P255QL	196, 198		X2CrNiCu19-10	313
	P265NL	197, 198		X2CrNiMo17-12-2	299, 304
	X10Ni9	199, 201		X2CrNiMo17-12-3	299, 304
	X12Ni5	199, 201		X2CrNiMo18-14-3	299, 304
EN 10217-1:2002	P195TR1	202, 204		X2CrNiMoN17-11-2	300, 305
	P195TR2	202, 204		X2CrNiMoN17-13-3	300, 305
	P235TR1	202, 204		X2CrNiMoN22-5-3	309, 310
	P235TR2	202, 204		X2CrNiMoN25-7-4	309, 310
	P265TR1	203, 205		X2CrNiN18-10	298, 303
	P265TR2	203, 205		X3CrNiMo13-4	295, 296
EN 10217-2:2002	16Mo3	213		X3CrNiMo17-13-3	299, 303
	P195GH				,

646 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10222-5:1999	X3CrNiMoN17-13-3	313	EN 10250-4:1999	X2CrNiMo17-12-2	299, 304
(continued)	X5CrNi18-10	298, 302	(continued)	X2CrNiMo17-13-3	300, 305
	X5CrNiMo17-12-2	299, 303		X2CrNiMo18-14-3	299, 304
	X6CrNi18-10	298, 302		X2CrNiMoCuN25-6-3	309, 310
	X6CrNiNb18-10	301, 306		X2CrNiMoCuWN27-7-4	309, 310
	X6CrNiTi18-10	300, 306		X2CrNiMoN17-11-2	300, 305
	X6CrNiTiB18-10	313		X2CrNiMoN22-5-3	309, 310
	X7CrNiNb18-10	301, 306		X2CrNiMoN25-7-4	309, 310
EN 10250-2:1999	20Mn5	311		X2CrNiN18-10	298, 303
	28Mn6	311		X2CrNiN23-4	309, 310
	C22	268, 271		X30Cr13	313
	C25	268, 271		X3CrNiMo13-4	295, 296
	C25E	268, 271		X3CrNiMo17-13-3	299, 303
	C30	269, 271		X3CrNiMoN27-5-2	309, 310
	C35	269, 271		X4CrNiMo16-5-1	313
	C35E	269, 271		X5CrNi18-10	298, 302
	C40	269, 271		X5CrNiCuNb16-4	307, 308
	C45	270, 271		X5CrNiMo17-12-2	299, 303
	C45E	270, 271		X6Cr17	297
	C50	270, 271		X6CrAl13	313
	C55	270, 271		X6CrNiMoTi17-12-2	300, 305
	C55E	270, 271		X6CrNiNb18-10	313
	C60	311		X6CrNiTi18-10	300, 306
	C60E	311	EN 10270-3:2001	X10CrNi18-8	429
S	S235J2G3	268, 271		X5CrNiMo17-12-2	437
	S235JRG2	268, 271		X7CrNiAl17-7	437
	S355J2G3	311	EN 10277-3:1999	10S20	420
EN 10050 2:1000				10SPb20	423
EN 10250-3:1999	18CrMo4	311		11SMn30	422
	20MnMoNi4-5	311		11SMn37	422
	25CrMo4	277, 278		11SMnPb30	424
	28NiCrMoV8-5	311		11SMnPb37	424
	30CrMoV9	311		15SMn13	420
	30CrNiMo8	311		35S20	420
	32CrMo12	311		35SPb20	436
	33NiCrMoV14-5	311		36SMn14	420
	34Cr4	311		36SMnPb14	423
	34CrMo4	277, 278		38SMn28	420
	34CrNiMo6	311		38SMnPb28	423
	36CrNiMo4	311		44SMn28	421
	36NiCrMo16	311		44SMnPb28	423
	37Cr4	311		46S20	421
	38Cr2	311		46SPb20	423
	40CrMoV13-9	311	EN 10283:1998	GX12Cr12	339, 340
	41Cr4	311	LN 10203.1990	GX2CrNi19-11	341, 344
	42CrMo4	277, 278		GX2CrNiMo19-11-2	342, 345
	46Cr2	311		GX2CrNiMoCuN20-18-6	
	50CrMo4	277, 278			343, 346
	51CrV4	311		GX2CrNiMoCuN25-6-3-3	361
EN 10250-4:1999	X12Cr13	295, 296		GX2CrNiMoCuN29-25-5	361
	X17CrNi16-2	313		GX2CrNiMoN17-13-4	342, 345
	X1CrNiMoCuN20-18-7	313		GX2CrNiMoN22-5-3	361
	X1NiCrMoCu25-20-5	301, 306		GX2CrNiMoN25-6-3	361
	X1NiCrMoCu31-27-4	313		GX2CrNiMoN25-7-3	361
	X1NiMoCuN25-20-7	313		GX2CrNiMoN26-7-4	361
	X20Cr13	313		GX2NiCrMo28-20-2	342, 346
	X2CrNi18-9	298, 302		GX2NiCrMoCu25-20-5	361 343, 346
				GX2NiCrMoCuN25-20-6	

(GX2NiCrMoN25-20-5 GX4CrNi13-4	342, 346 339, 340	EN 10296-1:2003	E370	171, 181
(330 340			
(000, 040	(continued)	E420M	257
	GX4CrNiMo16-5-1	339, 340		E460K2	257
(GX4CrNiMo16-5-2	361		E460M	257
`	GX4NiCrCuMo30-20-4	342, 346	EN 10297-1:2003	16MnCr5	258
(GX5CrNi19-10	341, 344		16MnCrS5	258
(GX5CrNiCu16-4	361		20NiCrMo2-2	258
(GX5CrNiMo19-11-2	341, 345		25CrMo4	185, 186
(GX5CrNiMo19-11-3	342, 345		30CrMo4	185, 186
	GX5CrNiMoNb19-11-2	342, 345		30CrNiMo8	258
(GX5CrNiNb19-11	341, 344		34CrMo4	185, 187
(GX6CrNiN26-7	361		36CrNiMo4	258
	GX7CrNiMo12-1	339, 340		38Mn6	175, 184
	G-CoCr28	354, 358		41Cr4	258
(G-NiCr15	354, 358		41NiCrMo7-3-2	258
(G-NiCr28W	354, 358		42CrMo4	185, 187
(G-NiCr50Nb	353, 358		C10E	257
(GX10NiCrSiNb32-20	362		C15E	257
	GX130CrSi29	351, 355		C15R	257
(GX160CrSi18	362		C22E	169, 172,
(GX25CrNiSi18-9	351, 356		0055	180, 182
(GX25CrNiSi20-14	352, 356		C35E	173, 175, 183, 184
(GX30CrSi7	335, 336		C45E	174, 175,
(GX35NiCrSi25-21	353, 357		0.02	184
(GX40CrNiSi22-10	351, 356		C60E	257
(GX40CrNiSi25-12	352, 356		E235	167, 178
	GX40CrNiSi25-20	352, 357		E275	168, 179
(GX40CrNiSi27-4	351, 355		E275K2	169, 179
(GX40CrNiSiNb24-24	353, 357		E315	170, 180
	GX40CrSi13	351, 355		E355	171, 181
(GX40CrSi17	351, 355		E355K2	258
(GX40CrSi24	351, 355		E420J2	174, 184
	GX40CrSi28	351, 355		E460K2	258
(GX40NiCrNb45-35	362		E470	175, 184
(GX40NiCrSi35-17	353, 357		E590K2	175, 184
	GX40NiCrSi35-26	353, 357		E730K2	258
(GX40NiCrSi38-19	353, 358	EN 10305-1:2002	1340	258
(GX40NiCrSiNb35-18	353, 358		25CrMo4	185, 186
	GX40NiCrSiNb35-26	353, 357		26Mn5	175, 184
	GX40NiCrSiNb38-19	353, 358		26Mo2	185, 186
(GX50NiCrCo20-20-20	354, 358		42CrMo4	185, 187
	GX50NiCrCoW35-25-15-5	362		C35E	170, 171,
EN 10296-1:2003	E155	165, 176			173, 174,
E	E195	166			180, 181,
	E220	166, 177		C45E	182, 183 172, 173,
E	E235	166, 168,		040L	172, 173, 175, 182,
		177, 178			184
	E260	167, 177		E215	165, 168,
E	E275	168, 170,			169, 176,
-	F0751/0	178, 179		F005	178, 180
	E275K2	167, 178		E235	166, 169, 171, 177,
	E275M	257			179, 181
	E320	169, 179		E255	168, 170,
E	E355	171, 172,			173, 174,
		173, 181, 183			178, 180,
E	E355K2	257			182, 183
	E355M	257			

648 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
EN 10305-1:2002	E355	170, 172,	ISO 11973:1999	GX25CrNiSi18-9	351, 356
(continued)		174, 175,	(continued)	GX25CrNiSi20-14	352, 356
		180, 183,		GX30CoCr50-28	354, 358
	E410	184 173, 174,		GX30CrSi7	335, 336
	20	175, 182,		GX40CrNiSi22-10	351, 356
		183, 184,		GX40CrNiSi25-12	352, 356
EN 10305-2:2002	E155	165, 167,		GX40CrNiSi25-20	352, 357
		168, 176,		GX40CrNiSi27-4	351, 355
	E195	177, 179 165, 166,		GX40CrNiSiNb24-24	353, 357
	2100	167, 169,		GX40CrSi13	351, 355
		176, 178,		GX40CrSi17	351, 355
		180		GX40CrSi24	351, 355
	E235	166, 170,		GX40CrSi28	351, 355
		172, 177, 180, 182		GX40NiCrCo20-20-20	354, 358
	E275	168, 169,		GX40NiCrSi35-17	353, 357
		172, 174,		GX40NiCrSi35-26	353, 357
		178, 179,		GX40NiCrSi38-19	353, 358
	F055	182, 183		GX40NiCrSiNb35-26	353, 357
	E355	170, 172, 174, 175,		GX40NiCrSiNb38-19	353, 358
		174, 175, 180, 183,		GX45NiCrCoW35-25-15-5	362
		184		GX45NiCrWSi48-28-5	354, 358
EN 10305-3:2002	E155	165, 176		GX50NiCr52-19	362
	E190	165, 176		GX50NiCr65-15	354, 358
	E195	165, 166,	ISO 13521:1999	GX100Mn13	328, 329
		176		GX110MnMo13-1	328, 329
	E220	166, 177		GX120Mn13	328, 329
	E235	166, 167,		GX120Mn17	360
		168, 177,		GX120MnCr13-2	328, 329
	E260	178 167, 177		GX120MnCr7-2	328, 329
	E275	168, 169,		GX120MnMo7-1	328, 329
	2270	170, 178,		GX120MnNi13-3	328, 329
		179		GX90MnMo14	328, 329
	E320	169, 179	ISO 2604-II:1975	TS 1	206, 210
	E355	170, 172,		TS 10	208, 211
		173, 180,		TS 13	209, 212
	E370	182 171, 180		TS 14	209, 212
	E420	171, 180		TS 15	209, 212
ISO 11972:1998	GX 12 Cr 12	339, 340		TS 18	209, 212
100 11072.1000	GX 2 CrNi 18 10	341, 344		TS 2	206, 210
	GX 2 CrNiCuMoN 26 5 3 3	•		TS 26	213
	GX 2 CrNiMo 19 11 2	342, 345		TS 32	217, 218
	GX 2 CrNiMo 19 11 3	342, 346		TS 33	216
	GX 2 CrNiMoN 19 11 2	342, 345		TS 34	220
	GX 2 CrNiMoN 19 11 3	342, 345		TS 37	221
	GX 2 CrNiMoN 26 5 3	343, 346		TS 38	222
	GX 2 CrNiN 18 10	361		TS 39	223, 224
	GX 4 CrNiMo 16 5 1	339, 340		TS 4	207, 210
	GX 4CrNi 12 4	339, 340		TS 40	260
		•		TS 43	260
	GX 5 CrNi 19 9 GX 5 CrNiMo 19 11 2	341, 344		TS 45	260
	GX 5 CrNiMo 19 11 2	341, 345		TS 46	226, 235
		341, 345		TS 47	225, 234
	GX 6 CrNiMoNb 19 11 2	342, 345		TS 48	227, 236
	GX 6 CrNiNb 19 10	341, 344		TS 5	207, 210
100 11070.1000	GX 8 CrNiMo 12 1	339, 340		TS 50	232, 244
ISO 11973:1999	GX10NiCrNb31-20	362		TS 53	231, 242
	GX10NiCrNb50-50	353, 358		TS 54	232, 243
	GX130CrSi29	351, 355			_5_, _5

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ISO 2604-III:1975	TS 56	233, 244	ISO 3183-2:1996	L360QB	251, 254
(continued)	TS 57	229, 239	(continued)	L415MB	251, 255
	TS 58	229, 239		L415NB	251, 255
	TS 6	207, 210		L415QB	251, 255
	TS 60	229, 238		L450MB	252, 255
	TS 61	229, 238		L450QB	252, 255
	TS 63	230, 240		L485MB	252, 256
	TS 67	260		L485QB	252, 256
	TS 68	228, 237		L555MB	252, 256
	TS 69	260		L555QB	252, 256
	TS 9	208, 211	ISO 3304:1985	R28	165, 167,
	TS 9H	208, 211			168, 176,
	TW 1	206, 210		R33	177, 179
	TW 10	208, 211		ทอง	166, 167, 169, 177,
	TW 13	209, 212			178, 179
	TW 14	209, 212		R37	166, 167,
	TW 15	209, 212			168, 170,
	TW 2	206, 210			177, 178,
	TW 26	213		R44	179, 180 168, 169,
	TW 32	217, 218		N 44	170, 173,
	TW 4	207, 210			179, 180,
	TW 5	207, 210			182
	TW 6	207, 210		R50	171, 173,
	TW 9	208, 211			174, 181,
	TW 9H	208, 211	ISO 3305:1985	R28	183, 184 165, 167,
ISO 2604-V:1975	TW 69	263	100 0000.1000	TILO	168, 176,
	TW 46	226, 235			177, 179
	TW 47	225, 234		R33	166, 167,
	TW 50	232, 244			169, 177,
	TW 53	231, 242		R37	178, 179 166, 167,
	TW 57	229, 239		1107	168, 170,
	TW 58	229, 239			177, 178,
	TW 60	229, 238			179, 180
	TW 61	229, 238		R44	168, 169,
ISO 2937:1974	C 35	173, 182			170, 173, 179, 180,
	TS 1	166, 177			182
	TS 18	172, 181		R50	171, 172,
	TS 4	167, 177			173, 174,
	TS 9	169, 179			181, 183,
ISO 3183-1:1996	L175, Class I	246, 247	ISO 3306:1985	E190	184 165, 176
	L175, Class II	246, 247	100 0000.1000	R28	165, 176
	L210	246, 247		HZ0	176, 177
	L245	246, 247		R33	166, 177
	L290	246, 247		R37	166, 167,
	L320	246, 248			168, 177,
	L360	246, 248		D.4.4	178, 179
	L390	246, 248		R44	168, 169, 179
	L415	246, 248		R50	171, 172,
	L450	246, 248		1100	173, 181,
	L485	246, 249			182
	L555	246, 249	ISO 3755:1991	200-400	319, 323
ISO 3183-2:1996	L245MB	250, 253		200-400W	319, 323
	L245NB	250, 253		230-450	319, 323
	L290MB	250, 253		230-450W	319, 323
	L290NB	250, 253		270-480	320, 323
	L360MB	251, 254		270-480W	320, 323

650 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ISO 3755:1991 (continued)	340-550W	321, 324	ISO 4957:1999	70MnMoCr8	438
ISO 4950-2:1995	E 355 DD	79, 84	(continued)	90MnCrV8	438
	E 355 E	79, 84		95MnWCr5	438
	E 460 CC	97		C105U	430
	E 460 DD	97		C120U	430
	E 460 E	97		C45U	438
ISO 4950-3:1995	E 460 DD	80, 84		C70U	430
	E 460 E	80, 84		C80U	430
	E 550 DD	97		C90U	430
	E 550 E	97		HS0-4-1	438
	E 690 DD	97		HS10-4-3-10	432
	E 690 E	97		HS1-4-2	438
ISO 4952:2003	Fe 235W, Quality B	88, 94		HS18-0-1	431
	Fe 235W, Quality C	88, 94		HS1-8-1	438
	Fe 235W, Quality D	88, 94		HS2-9-1-8	432
	Fe 355W, Quality 1A	90, 95		HS2-9-2	432
	Fe 355W, Quality 1D	90, 95		HS3-3-2	438
	Fe 355W, Quality 2B	90, 95		HS6-5-2	432
	Fe 355W, Quality 2C	90, 95		HS6-5-2-5	432
	Fe 355W, Quality 2D	90, 95		HS6-5-2C	438
ISO 4955:1994	NiCr15Fe8	416		HS6-5-3	432
	NiCr20Ti	416		HS6-5-3-8	438
	NiCr22Mo9Nb	416		HS6-5-3C	438
	X10CrAlSi13	416		HS6-5-4	432
	X10CrAlSi18	416		HS6-6-2	432
	X10CrAlSi25	416		X100CrMoV5	433
	X12NiCrSi35-16	416		X153CrMoV12	438
	X15CrN26	369, 371,		X210Cr12	433
	7.100.1120	398, 399		X210CrW12	438
	X15CrNiSi20-12	416		X30WCrV9-3	434
	X15CrNiSi25-21	402, 408		X35CrWMoV5	434
	X6Cr13	366, 367,		X37CrMoV5-1	434
		398, 399		X38CrMo16	438
	X6Cr17	398, 399		X38CrMoV5-3	438
	X6CrNi23-14	374, 382,		X40Cr14	438
	X6CrNi25-21	401, 405 374, 382,		X40CrMoV5-1	434
	A00111125-21	401, 405	ISO 4991:1994	C23-45A	326
	X6CrTi12	416	130 4991.1994	C23-45AH	326
	X6NiCrSi36-19	416		C23-45ATT	326
	X7CrNi18-9	373, 380		C23-45BH	326
	X7CrNiNb18-10	376, 386		C23-45BL	327
	X7CrNiNb18-10	402, 408		C26-52	326
	X7CrNiSiNCe21-11	416			
	X7CrNiTi18-10	376, 386,		C26-52H C26-52L	326 327
		402, 408			
	X8NiCrAlTi32-21	416		C28H	335, 336
ISO 4957:1999	102Cr6	438		C31L	359
	105V	430		C32H	335, 336
	21MnCr5	438		C33H	359
	32CrMoV12-28	434		C34AH	335, 336
	35CrMo7	438		C34BH	335, 336
	38CrCoWV18-17-17	434		C34BL	359
	40CrMnNiMo8-6-4	438		C35BH	335, 336
	45NiCrMo16	438		C37H	335, 336
	50CrMoV13-15	438		C38H	335, 336
	50WCrV8	438		C39CH	347, 348
	-			COOCNELL	247 240
	55NiCrMoV7	434		C39CNiH C39NiH	347, 348 347, 348

Specification Designation		Page	Specification Designation	Steel Grade/Name	Page
SO 4991:1994	C39NiL	347, 348	ISO 683-1:1987	42 CrMoS 4	38
continued)	C40H	347, 348	(continued)	42 Mn 6	34
	C43C1L	359		50 CrMo 4	38
	C43E2aL	337, 338		51 CrV 4	42
	C43E2bL	337, 338		C 25	26
	C43L	337, 338		C 25 E 4	26
	C46	349, 350		C 25 M 2	26
	C47	349, 350		C 30	26
	C47H	359		C 30 E 4	26
	C47L	349, 350		C 30 M 2	26
	C50	349, 350		C 35	27
	C57	349, 350		C 35 E 4	27
	C60	349, 350		C 35 M 2	27
	C60H	359		C 40	28
	C60Nb	349, 350		C 40 E 4	28
	C61	349, 350		C 40 M 2	28
	C61LC	349, 350		C 45	29
SO 5952:1998	HSA 235W, Class B	88, 94		C 45 E4	29
	HSA 235W, Class D	88, 94		C 45 M2	29
	HSA 245W, Class B	89, 94		C 50	30
	HSA 245W, Class D	89, 94		C 50 E4	30
	HSA 365W, Class B	91, 95		C 50 M2	30
	HSA 365W, Class D	91, 95		C 55	31
	HSA355W1, Class A	93, 96		C 55 E4	31
	HSA355W1, Class D	93, 96		C 55 M2	31
	HSA355W2, Class C	93, 96		C 60	31
	HSA355W2, Class D	93, 96		C 60 E 4	31
ISO 630:1995	E 185	50, 66		C 60 M 2	31
130 030.1993	E 235 A	51, 66	ISO 683-10:1987	31 CrMo 12	45
	E 235 B		100 000 10.1007	33 CrAlMo 5 4	45
		51, 66		41 CrAlMo 7 4	40
	E 235 B NF	51, 66	ISO 683-11:1987	15 NiCr 13	38
	E 235 C	51, 66	130 003-11.1907		45
	E 235 D	51, 66		16 MnCr 5	
	E 275 A	56, 69		16 MnCrS 5	45 20
	E 275 B	56, 69		17 NiCrMo 6	39
	E 275 C	56, 69		18 CrMo 4	37
	E 275 D	56, 69		18 CrMoS 4	37
	E 355 C	60, 70		18 CrNiMo 7	45
	E 355 D	61, 70		20 Cr 4	35
SO 683-1:1987	20 MnCr 5	45		20 CrS 4	35
	20 MnCrS 5	45		20 NiCrMo 2	39
	22 Mn 6	34		20 NiCrMoS 2	39
	25 CrMo 4	37		34 CrS 4	35
	25 CrMoS 4	37		37 CrS 4	35
	28 Mn 6	34		41 CrS 4	36
	31 CrNiMo 8	45		C 10	23
	34 Cr 4	35		C 15 E4	24
	34 CrMo 4	38		C 15 M2	24
	34 CrMoS 4	38		C 16 E4	24
	36 CrNiMo 4	45		C 16 M2	24
	36 CrNiMo 6	45	ISO 683-14:1992	51 CrV 4	428
	36 Mn 6	34		52 CrMoV 4	437
	37 Cr 4	35		55 Cr 3	427
	41 Cr 4	36		55 SiCr 6 3	427
	41 CrNiMo 2	39		56 SiCr 7	437
	41 CrNiMoS 2	39		59 Si 7	427

652 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
ISO 683-14:1992	60 CrMo 3 1	437	ISO 9327-3:1999	11MnNi5-3	291
(continued)	60 CrMo 3 3	428		12Ni14G1	289, 290
	61 SiCr 7	437		12Ni14G2	289, 290
ISO 683-17:1999	B1, 100Cr6	435		12Ni19	289, 290
	B2, 100CrMnSi4-4	435		13MnNi6-3	291
	B20, 20Cr3	439		15NiMn6	289, 290
	B21, 20Cr4	439		X8Ni9	289, 290
	B22, 20MnCr4-2	439	ISO 9327-4:1999	P 28	272, 275
	B23, 17MnCr5	439		P 35	273, 275
	B24, 19MnCr5	439		P 42	274, 276
	B25, 15CrMo4	439	ISO 9327-4:1999	P 46	311
	B26, 20CrMo4	439	(continued)	PH 28	272, 275
	B27, 20MnCrMo4-2	439		PH 35	273, 275
	B28, 20NiCrMo2	439		PH 42	274, 276
	B29, 20NiCrMo7	439		PH 46	311
	B3, 100CrMnSi6-4	435		PL 28	272, 275
	B30, 18CrNiMo7-6	439		PL 35	273, 275
	B31, 18NiCrMo14-6	439		PL 42	274, 276
	B32, 16NiCrMo16-5	439		PL 46	311
	B4, 100CrMnSi6-6	435		PLH 35	273, 275
	B40, C56E2	439		PLH 42	274, 276
	B41, 56Mn4	439		PLH 46	311
	B42, 70Mn4	439	ISO 9327-5:1999	X2CrNi18-10	298, 302
	B43, 43CrMo4	439		X2CrNiMo17-12	299, 304
	B5, 100CrMo7	435		X2CrNiMo17-13	299, 304
	B50, X47Cr14	439		X2CrNiMoN17-12	300, 305
	B51, X65Cr14	439		X2CrNiMoN17-13	300, 305
	B52, X106CrMo17	439		X2CrNiMoN22-5-3	309, 310
	B53, X89CrMoV18-1	439		X2CrNiN18-10	298, 303
	B6, 100CrMo7-3	435		X2CrNiN23-4	309, 310
	B60, 80MoCrV42-16	439		X2NiCrMoCu25-20-5	301, 306
	B61, 13MoCrNi42-16-14	439		X5CrNi18-9	298, 302
	B62, X82WMoCrV6-5-4	439		X5CrNiMo17-12	299, 303
	B63, X75WCrV18-4-1	439		X5CrNiMo17-13	299, 303
	B7, 100CrMo7-4	435		X6CrNi25-21	299, 303
	B8, 100CrMnMoSi8-4-6	435		X6CrNiMoTi17-12	300, 305
ISO 683-9:1988	10 S 20	420		X6CrNiNb18-10	301, 306
100 000 3.1300	10 SPb 20	423		X6CrNiTi18-10	300, 306
	11 SMn 28	422		X7CrNi18-9	298, 302
	11 SMnPb 28	424		X7CrNiMo17-12	300, 305
	12 SMn 35	422		X7CrNiNb18-10	301, 306
	12 SMnPb 35	424		X7CrNiTi18-10	300, 306
	17 SMn 20	420	ISO 9328-2:1991	13 CrMo 9 10 T1	124, 125
	35 S 20	420	130 9320-2.1991	13 CrMo 9 10 T1	
	35 SMn 20	420		14 CrMo 4 5	124, 125 122
				16 Mo 3	
	44 SMn 28	421			117, 119
	46 S 20	421		P 235	103, 109
100 0007 0:1000	9 S 20	422		P 265	104, 109
ISO 9327-2:1999	13CrMo9-10	283, 284		P 290	105, 110
	14CrMo4-5	281		P 315	106, 111
	16Mo3	279		P 355	107, 112
	20MnMoNi5	312		PH 235	103, 109
	PH 26	268, 271		PH 265	104, 109
	PH 29	268, 271		PH 290	105, 110
	PH 31	269, 271		PH 315	106, 111
	X12CrMo5-1	286		PH 355	107, 112
	X20CrMoV12-1	288			

SO 9328-3:1991	144, 148 143, 146 143, 147 143, 147 12 144, 148 12 144, 148 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 145, 149 145, 149 145, 149 145, 149 145, 149 145, 149
12 Ni 14 G2	144, 148 143, 146 143, 147 143, 147 12 144, 148 12 144, 148 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 145, 149 145, 149 145, 149 145, 149 145, 149 145, 149
13 MnNi 6 3 129 X 5 CrNi 18 9 15 NiMn 6 130 X 5 CrNi Mo 17 12 X 8 Ni 9 135, 136 X 5 CrNi Mo 17 12 X 8 Ni 9 135, 136 X 5 CrNi Mo 17 13 X 6 CrNi Mo 17 17 X 6 CrNi Mo 18 10 X 7 CrNi Mo 18 10 X 8 Ni CrAI Mo 13 2 X 8 Ni CrAI Mo 13 Mo 16 -3 X 8 Ni Mo 17 X 8 Ni Mo 18	143, 146 143, 147 12 144, 148 12 144, 148 145, 149 145, 149 143, 146 1 144, 147 12 156 145, 149 1 17Q1 145, 149 1 TQ1 145, 149 1 TQ1 145, 150
15 NiMn 6	143, 147 12 144, 148 12 144, 148 145, 149 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
X 8 Ni 9 135, 136 X 5 CrNiMo 17 13	143, 147 12 144, 148 12 144, 148 145, 149 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
X 8 Ni 9 135, 136 X 5 CrNiMo 17 13	143, 147 12 144, 148 12 144, 148 145, 149 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
ISO 9328-4:1991 P 255 TN 113, 115 X 6 CrNiMoNb 17 P 285 TN 113, 115 X 6 CrNiMoTi 17 P 315 TN 104, 109 X 6 CrNiNb 18 10 P 355 TN 114, 116 X 6 CrNiTi 18 10 P 390 TN 155 X 7 CrNiMo 17 12 P 460 TN 155 X 7 CrNiMoB 17 12 P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAlTi 32 2 P 620 TQ 155 X 7 NiCrAlTi 32 2 P 690 TQ 155 X 8 NiCrAlTi 32 2 P 690 TQ 155 X 8 NiCrAlTi 32 2 P H 255 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116	12 144, 148 12 144, 148 145, 149 145, 149 143, 146 144, 147 12 156 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 285 TN 113, 115 X 6 CrNiMoTi 17 P 315 TN 104, 109 X 6 CrNiNb 18 10 P 355 TN 114, 116 X 6 CrNiTi 18 10 P 390 TN 155 X 7 CrNi 18 9 P 420 TN 155 X 7 CrNiMo 17 12 P 460 TN 155 X 7 CrNiMoB 17 P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P H 255 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116	12 144, 148 145, 149 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 150
P 315 TN 104, 109 X 6 CrNiNb 18 10 P 355 TN 114, 116 X 6 CrNiTi 18 10 P 390 TN 155 X 7 CrNi 18 9 P 420 TN 155 X 7 CrNiMo 17 12 P 460 TN 155 X 7 CrNiMo 17 12 P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiNb 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 135 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 P 135 TN 104, 109 12 Ni 14 P 1355 TN 114, 116	145, 149 145, 149 143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 355 TN 114, 116 X 6 CrNiTi 18 10 P 390 TN 155 X 7 CrNi 18 9 P 420 TN 155 X 7 CrNiMo 17 12 P 460 TN 155 X 7 CrNiMo B 17 P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 135 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 P 1315 TN 104, 109 12 Ni 14 P 1355 TN 114, 116	145, 149 143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 150
P 390 TN 155 X 7 CrNi 18 9 P 420 TN 155 X 7 CrNiMo 17 12 P 460 TN 155 X 7 CrNiMoB 17 17 P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 135 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116	143, 146 144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 420 TN 155 X 7 CrNiMo 17 12 P 460 TN 155 X 7 CrNiMoB 17 12 P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P H 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116	144, 147 12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 460 TN 155 X 7 CrNiMoB 17 TP 460 TQ 155 X 7 CrNiMoB 18 10 TP 500 TQ 155 X 7 CrNiTi 18 10 TP 550 TQ 155 X 7 NiCrAITi 32 2 TP 620 TQ 155 X 7 NiCrAITi 32 2 TP 690 TQ 155 X 8 NiCrAITi 32 2 TP 690 TQ 155 X 8 NiCrAITi 32 2 TP 135 TN 113, 115 TP 135 TN 114, 115 TP 14, 116 TP 150 TN 114 TP 155 TN 114, 116 TP 150 TN 114 TP 155 TN 114, 116 TP 150 TN 1150 T	12 156 145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 460 TQ 155 X 7 CrNiNb 18 10 P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 PH 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	145, 149 145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 500 TQ 155 X 7 CrNiTi 18 10 P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 PH 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	145, 149 1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 550 TQ 155 X 7 NiCrAITi 32 2 P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 PH 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	1 TQ1 145, 149 1 TQ2 145, 149 1 TQ1 145, 150
P 620 TQ 155 X 7 NiCrAITi 32 2 P 690 TQ 155 X 8 NiCrAITi 32 2 PH 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	1 TQ2 145, 149 1 TQ1 145, 150
P 690 TQ 155 X 8 NiCrAITi 32 2 PH 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	1 TQ1 145, 150
PH 255 TN 113, 115 X 8 NiCrAITi 32 2 PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	
PH 285 TN 113, 115 ISO 9329-3:1997 11 MnNi 5-3 PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	
PH 315 TN 104, 109 12 Ni 14 PH 355 TN 114, 116 13 MnNi 6-3	
PH 355 TN 114, 116 13 MnNi 6-3	199, 200
·	199, 200
	199, 200
PH 390 TN 155 26 CrMo 4	199, 201
PH 420 TN 155 PL 21	196, 198
PH 460 TN 155 PL 23	197, 198
PH 460 TQ 155 PL 25	196, 198
PH 500 TQ 155 PL 26	260
PH 550 TQ 155 X 10 Ni 9	199, 201
PH 620 TQ 155 X 12 Ni 5	199, 201
PH 690 TQ 155 ISO 9330-3:1997 11 MnNi 5-3	199, 200
PL 255 TN 113, 115 12 Ni 14	199, 200
PL 285 TN 113, 115 13 MnNi 6-3	199, 200
PL 315 TN 104, 109 PL 21	196, 198
PL 355 TN 114, 116 PL 23	197, 198
PL 390 TN 155 PL 25	196, 198
PL 420 TN 155 PL 26	260
PL 460 TN 155 X 12 Ni 5	199, 201
PL 460 TQ 155 ISO 9330-5:2000 11 MnNi 5-3	199, 200
PL 500 TQ 155 12 Ni 14	199, 200
PL 550 TQ 155 13 MnNi 6-3	199, 200
PL 620 TQ 155 PL 21	196, 198
PL 690 TQ 155 PL 23	197, 198
PLH 355 TN 114, 116 PL 25	196, 198
PLH 390 TN 155 PL 26	260
PLH 420 TN 155 X 10 Ni 9	199, 201
PLH 460 TN 155 X 12 Ni 5	199, 201
PLH 460 TQ 155 JIS G 3101:1995 SS330	50, 66
PLH 500 TQ 155 SS400	54, 68
PLH 550 TQ 155 SS490	59, 70
PLH 620 TQ 155 SS540	64, 71
PLH 690 TQ 155 JIS G 3103:1987 SB 410	104, 109
ISO 9328-5:1991 X 2 CrNi 18 10 143, 146 SB 450	105, 110
X 2 CrNiMo 17 12 144, 147 SB 450 M	117, 119
X 2 CrNiMo 17 13 144, 147 SB 480	105, 110
X 2 CrNiMoN 17 12 144, 148 SB 480 M	117, 119
X 2 CrNiMoN 17 13 144, 148	.,
X 2 CrNiMoN 17 13 5 145, 148	

654 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
JIS G 3106:1999	SM400A	54, 68	JIS G 3126:2000	SLA 325 A	113, 115
	SM400B	54, 68		SLA 325 B	113, 115
	SM400C	55, 68		SLA 365	114, 116
	SM490A	59, 70		SLA 410	114, 116
	SM490B	59, 70	JIS G 3127:2000	SL2N255	131
	SM490C	59, 70		SL3N255	132, 133
	SM490YA	60, 70		SL3N275	132, 133
	SM490YB	60, 70		SL3N440	132, 133
	SM520B	64, 71		SL5N590	134
	SM520C	64, 71		SL9N520	135, 136
	SM570	65, 71		SL9N590	135, 136
JIS G 3114:1998	SMA400AP	89, 94	JIS G 3128:1999	SHY 685	83, 87
	SMA400AW	89, 94		SHY 685 N	83, 87
	SMA400BP	89, 94		SHY 685 NS	83, 87
	SMA400BW	89, 94	JIS G 3136:1994	SN400A	55, 68
	SMA400CP	89, 94		SN400B	55, 68
	SMA400CW	89, 94		SN400C	55, 68
	SMA490AP	91, 95		SN490B	60, 70
	SMA490AW	90, 95		SN490C	60, 70
	SMA490BP	91, 95	JIS G 3201:1988	SF 340 A	268, 271
	SMA490BW	91, 95		SF 390 A	268, 271
	SMA490CP	91, 95		SF 440 A	268, 271
	SMA490CW	91, 95		SF 490 A	269, 271
	SMA570P	93, 96		SF 540 A	269, 271
	SMA570W	93, 96		SF 540 B	269, 271
JIS G 3115:2000	SPV235	104, 109		SF 590 A	270, 271
010 0 0110.2000	SPV315	106, 111		SF 590 B	270, 271
	SPV410	108, 112		SF 640 B	270, 271
	SPV450	108, 112	JIS G 3202:1988	SFVC 1	270, 271
	SPV490	155	313 G 3202.1986	SFVC 2 A	272, 275
JIS G 3118:2000	SGV410	104, 109		SFVC 2 B	
010 0 0110.2000	SGV450	105, 110	JIS G 3203:1988	SFVA F 1	273, 275 279
	SGV480	105, 110	JIS G 3203.1966	SFVA F 11 A	279 282
JIS G 3119:1987	SBV 1 A	117, 119			
313 G 3119.1907	SBV 1 B	118, 120		SFVA F 11 B SFVA F 12	282
	SBV 2	137, 138			281
	SBV 3	139, 140		SFVA F 2	280
JIS G 3120:1987	SB 42	·		SFVA F 21 A	285
313 G 3120.1967	SB 46	155 155		SFVA F 21 B	285
				SFVA F 22 A	283, 284
	SB 46 M	155		SFVA F 22 B	283, 284
	SB 49	155		SFVA F 5 A	286
	SB 49 M	155		SFVA F 5 B	286
	SQV 1 A	118, 120		SFVA F 5 C	286
	SQV 1 B	118, 120		SFVA F 5 D	286
	SQV 2 A	137, 138		SFVA F 9	287
	SQV 2 B	137, 138	JIS G 3204:1988	SFVQ 1 A	293
	SQV 3 A	139, 140		SFVQ 1 B	293
UO O 0404 400 -	SQV 3 B	139, 140		SFVQ 2A	292
JIS G 3124:1987	SEV 245	107, 112		SFVQ 2B	292
	SEV 25	155		SFVQ 3	294
	SEV 295	117, 119	JIS G 3205:1988	SFL 1	272, 275
	SEV 30	155		SFL 2	273, 275
	SEV 345	118, 120		SFL 3	289, 290
	SEV 35	155	JIS G 3206:1993	SFVCM F22B	283, 284
JIS G 3125:1987	SPA-C	90, 95		SFVCM F22V	283, 284
	SPA-H	90, 95		SFVCM F3V	285

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
JIS G 3214:1991	SUS 316	299, 303	JIS G 3441:1988	SCM 440 TK	185, 187
	SUS 316H	300, 305	(continued)	OTKOOO	405 470
	SUS 317	300, 305	JIS G 3444:1994	STK290	165, 176
	SUS F 304	298, 302		STK400	168, 179
	SUS F 304H	298, 302		STK490	172, 181
	SUS F 304L	298, 302		STK500	172, 182
	SUS F 304LN	298, 303		STK540	173, 182
	SUS F 304N	298, 302	JIS G 3445:1988	STKM 11 A	165, 176
	SUS F 310	299, 303		STKM 12 A	166, 177
	SUS F 316L	299, 304		STKM 12 B	168, 178
	SUS F 316LN	300, 305		STKM 12 C	171, 181
	SUS F 316N	299, 304		STKM 13 A	167, 178
	SUS F 317L	300, 305		STKM 13 B	170, 180
	SUS F 321	300, 306		STKM 13 C	172, 182
	SUS F 321H	300, 306		STKM 14 A	169, 179
	SUS F 347	301, 306		STKM 14 B	172, 182
	SUS F 347H	301, 306		STKM 14 C	173, 183
	SUS F 410-A	295, 296		STKM 15 A	171, 181
	SUS F 410-B	295, 296		STKM 15 C	174, 183
	SUS F 410-C	295, 296		STKM 16 A	172, 182
	SUS F 410-D	295, 296		STKM 16 C	174, 184
	SUS F 630	307, 308		STKM 17 A	173, 183
	SUS F 6B	295, 296		STKM 17 C	175, 184
	SUS F 6NM	295, 296		STKM 18 A	170, 180
JIS G 3221:1988	SFCM 590 D	311		STKM 18 B	172, 181
JIS G 3221.1900	SFCM 590 R	311		STKM 18 C	172, 182
	SFCM 590 S	311		STKM 19 A	172, 181
	SFCM 640 D	311		STKM 19 C	173, 183
	SFCM 640 R	311		STKM 20 A	173, 182
	SFCM 640 S	311	JIS G 3446:1994	SUS304TKA	190, 193
				SUS304TKC	190, 193
	SFCM 690 D	311		SUS316TKA	191, 194
	SFCM 690 R	311		SUS316TKC	191, 194
	SFCM 690 S	277, 278		SUS321TKA	192, 195
	SFCM 740 D	311		SUS347TKA	192, 195
	SFCM 740 R	311		SUS410TKA	188, 189
	SFCM 740 S	277, 278		SUS410TKC	188, 189
	SFCM 780 D	311		SUS420J1TKA	259
	SFCM 780 R	311		SUS420J2TKA	259
	SFCM 780 S	277, 278		SUS430TKA	188, 189
	SFCM 830 D	311		SUS430TKC	188, 189
	SFCM 830 R	311	JIS G 3452:1997	SGP	165, 176
	SFCM 830 S	311	JIS G 3454:1988	STPG 370	202, 204
	SFCM 880 D	311	013 G 3434.1900	STPG 410	202, 204
	SFCM 880 R	311	JIS G 3455:1988	STS 370	203, 203
	SFCM 880 S	311	JIS G 5455.1966	STS 410	207, 210
	SFCM 930 D	311			
	SFCM 930 R	311	UC C 2456:1000	STS 480	209, 212
	SFCM 930 S	311	JIS G 3456:1988	STPT 370	207, 210
	SFCM 980 D	311		STPT 410	208, 211
	SFCM 980 R	311	UC C 0457:4000	STPT 480	209, 212
	SFCM 980 S	311	JIS G 3457:1988	STPY 400	203, 205
JIS G 3441:1988	S CM 415 TK	258	JIS G 3458:1988	STPA 12	214, 215
	S Cr 420 TK	258		STPA 20	216
	SCM 418 TK	185, 186		STPA 22	217, 218
	SCM 420 TK	185, 186		STPA 23	219
	SCM 430 TK	185, 186		STPA 24	220
	SCM 435 TK	185, 187		STPA 25	221

656 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
JIS G 3458:1988	STPA 26	222	JIS G 3463:1994	SUS317LTB	231, 241
(continued)	OLIOGOALITD	007 000	(continued)	SUS317TB	231, 241
JIS G 3459:1997	SUS304HTP	227, 236		SUS321HTB	232, 243
	SUS304LTP	226, 235		SUS321TB	231, 242
	SUS304TP	225, 234		SUS329J1TB	263
	SUS309STP	227, 236		SUS329J3LTB	232, 243
	SUS309TP	227, 237		SUS329J4LTB	232, 243
	SUS310STP	227, 237		SUS347HTB	233, 244
	SUS310TP	263		SUS347TB	232, 243
	SUS316HTP	230, 240		SUS405TB	263
	SUS316LTP	229, 239		SUS409LTB	263
	SUS316TiTP	230, 241		SUS409TB	223, 224
	SUS316TP	228, 238		SUS410TB	223, 224
	SUS317LTP	231, 241		SUS410TiTB	263
	SUS317TP	231, 241		SUS430J1LTB	263
	SUS321HTP	232, 243		SUS430LXTB	223, 224
	SUS321J1TP	263		SUS430TB	223, 224
	SUS321J3LTP	263		SUS436LTB	263
	SUS321J4LTP	263		SUS444TB	263
	SUS321TP	231, 242		SUS836LTB	233, 245
	SUS347HTP	233, 244		SUS890LTB	233, 245
	SUS347TP	232, 243		SUSXM15J1TB	263
	SUS405TP	263		SUSXM27TB	223, 224
	SUS409LTP	263		SUSXM8TB	263
	SUS430J1LTP	263	JIS G 3464:1988	STBL 380	196, 198
	SUS430LXTP	263		STBL 450	199, 200
	SUS430TP	263		STBL 690	199, 201
	SUS436LTP	263	JIS G 3467:1988	NCF 800 TF	233, 245
	SUS444TP	263	0.0 0.07.1000	NCF 800H TF	233, 245
	SUS836LTP	263		STF 410	208, 211
	SUS890LTP	233, 245		STFA 12	214, 215
JIS G 3460:1988	STPL 380	196, 198		STFA 22	217, 218
	STPL 450	197, 198,		STFA 23	219
		199, 200		STFA 24	220
	STPL 690	197, 198,		STFA 25	221
JIS G 3461:1988	CTD 240	199, 201		STFA 26	222
JIS G 3401.1900	STB 340 STB 410	206, 210		SUS 304 TF	225, 234
		208, 211		SUS 304 TF	227, 236
IIC C 2460:1000	STB 510 STBA 12	209, 212		SUS 309 TF	260
JIS G 3462:1988		214, 215		SUS 316 TF	228, 238
	STBA 13	214, 215			230, 240
	STBA 20	216		SUS 316H TF	
	STBA 22	217, 218		SUS 321 TF	231, 242
	STBA 23	219		SUS 321H TF	232, 243
	STBA 24	220		SUS 347 TF	232, 243
	STBA 25	221		SUS 347H TF	233, 244
	STBA 26	222	110.0.0400.4004	SUS310TF	228, 237
JIS G 3463:1994	SUS304HTB	227, 236	JIS G 3468:1994	SUS304	225, 234
	SUS304LTB	226, 235		SUS304L	226, 235
	SUS304TB	225, 234		SUS309S	227, 236
	SUS309STB	227, 236		SUS310S	227, 237
	SUS309TB	227, 237		SUS316	228, 238
	SUS310STB	227, 237		SUS316L	229, 239
	SUS310TB	228, 237		SUS317	231, 241
	SUS316HTB	230, 240		SUS317L	231, 241
	SUS316LTB	229, 239		SUS321	231, 242
	SUS316TB	228, 238		SUS329J1	263
					232, 243

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
IIS G 3472:1988	STAM 290 GA	165, 176	JIS G 4053:2003	SCr 435	35
	STAM 290 GB	165, 176	(continued)	SCr 440	36
	STAM 340 G	166, 177		SCr 445	36
	STAM 390 G	168, 178		SMn 420	34
	STAM 440 G	170, 180		SMn 433	34
	STAM 440 H	170, 180		SMn 438	34
	STAM 470 G	171, 181		SMn 443	34
	STAM 470 H	171, 181		SMnC 420	34
	STAM 500 G	172, 182		SMnC 443	34
	STAM 500 H	172, 182		SNC 236	44
	STAM 540 H	173, 183		SNC 415	44
IIS G 3473:1988	STC 370	167, 178		SNC 631	44
	STC 440	170, 180		SNC 815	38
	STC 510A	172, 182		SNC 836	44
	STC 510B	172, 182		SNCM 220	39
	STC 540	173, 182		SNCM 240	39
	STC 590A	174, 183		SNCM 415	39
	STC 590B	174, 183		SNCM 420	39
JIS G 3474:1995	STKT 540	173, 183		SNCM 431	44
	STKT 590	174, 183		SNCM 439	39
IIS G 4051:1979	S 09 CK	23		SNCM 447	44
	S 10 C	23		SNCM 616	44
	S 12 C	23		SNCM 625	44
	S 15 C	24		SNCM 630	44
	S 15 CK	24		SNCM 815	44
	S 17 C	24	JIS G 4103:1979	SNCM 431	44
	S 20 C	25	010 G 4100.1070	SNCM 447	44
	S 20 CK	25		SNCM 616	44
	S 22 C	25		SNCM 625	44
	S 25 C	26		SNCM 630	44
	S 28 C	26		SNCM 815	44
			UC C 4105.1070		
	S 30 C	26	JIS G 4105:1979	SCM 415	44
	S 33 C	27	JIS G 4109:1987	SCMV 1 Div 1	121
	S 35 C	27		SCMV 1 Div 2	121
	S 38 C	27		SCMV 2 Div 1	122
	S 40 C	28		SCMV 2 Div 2	122
	S 43 C	28		SCMV 3 Div 1	123
	S 45 C	29		SCMV 3 Div 2	123
	S 48 C	29		SCMV 4 Div 1	124, 125
	S 50 C	30		SCMV 4 Div 2	124, 12
	S 53 C	30		SCMV 5 Div 1	126
	S 55 C	31		SCMV 5 Div 2	126
	S 58 C	31		SCMV 6 Div 1	127
IS G 4053:2003	SCM 415	44		SCMV 6 Div 2	127
	SCM 418	37	JIS G 4110:1993	SCMQ4E	124, 12
	SCM 420	37		SCMQ4V	155
	SCM 421	37		SCMQ5V	155
	SCM 425	37	JIS G 4202:1979	SACM 645	40
	SCM 430	37	JIS G 4303:1998	SUS 317J1	402, 408
	SCM 432	37		SUS 329J3L	412
	SCM 435	38		SUS201	400, 40
	SCM 440	38		SUS202	400, 40
	SCM 445	38		SUS301	400, 40
	SCM 822	37		SUS302	400, 40
	SCr 415	35		SUS303	400, 400
	SCr 420	35		SUS303Cu	415

658 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
JIS G 4303:1998	SUS304	400, 404	JIS G 4304:1999	SUS304	373, 380
(continued)	SUS304J3	415	(continued)	SUS304J1	413
	SUS304L	400, 404		SUS304J2	413
	SUS304LN	400, 405		SUS304L	373, 380
	SUS304N1	400, 404		SUS304LN	373, 381
	SUS304N2	400, 405		SUS304N1	373, 381
	SUS305	401, 405		SUS304N2	413
	SUS309S	401, 405		SUS305	373, 381
	SUS310S	401, 405		SUS309S	374, 382
	SUS316	401, 406		SUS310S	374, 382
	SUS316F	415		SUS315J1	413
	SUS316J1	415		SUS315J2	413
	SUS316J1L	415		SUS316	374, 383
	SUS316L	401, 406		SUS316J1	413
JIS G 4303:1998	SUS316LN	401, 407		SUS316J1L	413
	SUS316N	401, 407		SUS316L	374, 383
	SUS316Ti	402, 407		SUS316LN	375, 384
	SUS317	402, 407		SUS316N	374, 384
	SUS317L	402, 408		SUS316Ti	375, 384
	SUS317LN	415		SUS317	413
	SUS321	402, 408		SUS317J1	375, 385
	SUS329J1	415		SUS317J2	413
	SUS329J4L	415		SUS317J3L	413
	SUS347	402, 408		SUS317L	375, 384
	SUS403	394, 396		SUS317LN	375, 385
	SUS405	398, 399		SUS321	376, 386
	SUS410	394, 396		SUS329J1	413
	SUS410F2	415		SUS329J3L	392, 393
	SUS410J1	415		SUS329J4L	413
	SUS410L	415		SUS347	376, 386
	SUS416	394, 396		SUS403	366, 367
	SUS420F	394, 397		SUS405	368, 370
	SUS420F2	415		SUS410	366, 367
	SUS420J1	394, 396		SUS410L	
	SUS420J2	394, 396			366, 367
	SUS430	398, 399		SUS410S	366, 367
	SUS430F	398, 399		SUS420J1	366, 367
	SUS431	394, 397		SUS420J2	366, 367
		•		SUS429	413
	SUS434	398, 399		SUS429J1	413
	SUS440A	394, 397		SUS430	368, 370
	SUS440B	394, 397		SUS430J1L	413
	SUS440C	395, 397		SUS430LX	368, 370
	SUS440F	415		SUS434	368, 370
	SUS447J1	398, 399		SUS436J1L	413
	SUS630	409, 410		SUS436L	413
	SUS631	409, 411		SUS440A	413
	SUS836L	402, 408		SUS444	369, 371
	SUS890L	402, 408		SUS445J1	413
	SUSXM15J1	415		SUS445J2	413
	SUSXM27	398, 399		SUS447J1	413
	SUSXM7	415		SUS630	387, 388
JIS G 4304:1999	SUS301	372, 378		SUS631	387, 390
	SUS301J1	372, 378		SUS836L	375, 385
	SUS301L	372, 379		SUS890L	375, 385
	SUS302	372, 379		SUSXM15J1	413
	SUS302B	372, 380		SUSXM27	413

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
JIS G 4305:1999	SUS301	372, 378	JIS G 4305:1999	SUS836L	375, 385
	SUS301J1	372, 378	(continued)	SUS890L	375, 385
	SUS301L	372, 379		SUSXM15J1	414
	SUS302	372, 379		SUSXM27	414
	SUS302B	372, 380		SUSXM7	414
	SUS304	373, 380	JIS G 4311:1991	SUH1	415
	SUS304J1	414		SUH11	415
	SUS304J2	414		SUH3	415
	SUS304L	373, 380		SUH309	402, 408
	SUS304LN	373, 381		SUH31	415
	SUS304N1	373, 381		SUH310	402, 408
	SUS304N2	414		SUH330	415
	SUS305	373, 381		SUH35	415
	SUS309S	374, 382		SUH36	415
	SUS310S	374, 382		SUH37	415
	SUS315J1	414		SUH38	415
	SUS315J2	414		SUH4	415
	SUS316	374, 383		SUH446	398, 399
	SUS316J1	414		SUH600	415
	SUS316J1L	414		SUH616	415
	SUS316L	374, 383		SUH660	415
	SUS316LN	375, 384		SUH661	415
	SUS316N	374, 384		SUS304	400, 404
	SUS316Ti	375, 384		SUS309S	401, 405
	SUS317	414		SUS310S	401, 405
	SUS317J1	375, 385		SUS316	401, 406
	SUS317J2	414		SUS316Ti	402, 407
	SUS317J3L	414		SUS317	402, 407
	SUS317L	375, 384		SUS321	402, 408
	SUS317LN	375, 385		SUS347	402, 408
	SUS321	376, 386		SUS403	394, 396
	SUS329J1	414		SUS405	398, 399
	SUS329J3L	392, 393		SUS410	394, 396
	SUS329J4L	414		SUS410J1	415
	SUS347	376, 386		SUS410L	415
	SUS403	366, 367		SUS430	398, 399
	SUS405	368, 370		SUS431	394, 397
	SUS410	366, 367		SUS630	409, 410
	SUS410L	366, 367		SUS631	409, 411
	SUS410S	366, 367		SUSXM15J1	415
	SUS420J1	366, 367	JIS G 4312:1991	SUH21	414
	SUS420J2	366, 367	010 0 4012.1001	SUH309	373, 381
	SUS429	414		SUH310	374, 382
	SUS429J1	414		SUH330	414
	SUS430	368, 370		SUH409	414
	SUS430J1L	414		SUH409L	368, 370
	SUS430LX	368, 370		SUH446	369, 371
		•		SUH660	414
	SUS434	368, 370			
	SUS436J1L	414 414		SUH661 SUS302B	414 372 380
	SUS436L	414			372, 380
	SUS440A	414		SUS304	373, 380
	SUS444	369, 371		SUS309S	374, 382
	SUS445J1	414		SUS310S	374, 382
	SUS445J2	414		SUS316	374, 383
	SUS447J1	414		SUS316Ti	375, 384
	SUS630	387, 389		SUS317	414
	SUS631	387, 390		SUS321	376, 386

660 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
JIS G 4312:1991	SUS347	376, 386	JIS G 4403:2000	SKH10	431
continued)	SUS403	366, 367		SKH2	431
	SUS405	368, 370		SKH3	431
	SUS410	414		SKH4	431
	SUS410L	414		SKH40	438
	SUS430	368, 370		SKH50	438
	SUS430J1L	414		SKH51	432
	SUS436J1L	414		SKH52	432
	SUS630	387, 389		SKH53	432
	SUS631	387, 390		SKH54	432
	SUSXM151J1	414		SKH55	432
IIS G 4313:1996	SUS 301-CSP	429		SKH56	432
	SUS 304-CSP	429		SKH57	432
	SUS 420J2-CSP	429		SKH58	432
	SUS 631-CSP	429		SKH59	432
	SUS 632J1-CSP	437	JIS G 4404:2000	SKD 1	433
IS G 4318:1998	SUS302	400, 403		SKD 10	438
	SUS303	400, 403		SKD 11	433
	SUS303Cu	415		SKD 12	433
	SUS303Se	400, 403		SKD 2	438
	SUS304	400, 404		SKD 4	438
	SUS304J3	415		SKD 5	434
	SUS304L	400, 404		SKD 6	434
	SUS305	401, 405		SKD 61	434
	SUS305J1	415		SKD 62	434
	SUS309S	401, 405		SKD 7	434
	SUS310S	401, 405		SKD 8	434
	SUS316	401, 406		SKS 11	434
	SUS316F	415		SKS 2	438
	SUS316L	401, 406		SKS 21	438
	SUS321	402, 408		SKS 3	438
	SUS329J1	415		SKS 31	438
	SUS347	402, 408		SKS 4	438
	SUS403			SKS 41	438
	SUS410	394, 396 394, 396			430
		•		SKS 43	
	SUS410F2 SUS416	415		SKS 44	430
		394, 396		SKS 5	438
	SUS420F	394, 397		SKS 51	434
	SUS420F2	415		SKS 7	438
	SUS420J1	394, 396		SKS 8	438
	SUS420J2	394, 396		SKS 81	438
	SUS430	398, 399		SKS 93	438
	SUS430F	398, 399		SKS 94	438
	SUS440C	395, 397		SKS 95	438
IIS G 4401:2000	SK105	430		SKT 3	438
	SK120	430		SKT 4	434
	SK140	438		SKT 6	438
	SK60	438	JIS G 4801:1984	SUP 10	428
	SK65	430		SUP 11 A	428
	SK70	438		SUP 12	427
	SK75	430		SUP 13	428
	SK80	438		SUP 3	425
	SK85	430		SUP 6	427
	SK90	438		SUP 7	427
	SK95	430		SUP 9	427
				SUP 9 A	427

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
IIS G 4802:1999	S50C-CSP	425	JIS G 5111:1991	SCMn 5A	325
	S55C-CSP	425	(continued)	SCMn 5B	325
	S60C-CSP	425		SCMnCr 2	359
	S65C-CSP	425		SCMnCr 3	359
	S70C-CSP	425		SCMnCr 4	359
	SK4-CSP	426		SCMnCrM 2	359
	SK5-CSP	426		SCMnCrM 3	359
110 0 4004 4000	SUP10-CSP	428		SCMnM 3	359
IIS G 4804:1999	SUM 11	420		SCNCrM 2A	330, 334
	SUM 12	420		SCNCrM 2B	330, 334
	SUM 21	422		SCSiMn 2	321
	SUM 22	422		SCSiMn 2A	324
	SUM 22 L	424		SCSiMn 2B	324
	SUM 23	422	JIS G 5121:2003	SCS 1	339, 340
	SUM 23 L	424		SCS 10	361
	SUM 24 L	424		SCS 11	361
	SUM 25	422		SCS 12	341, 344
	SUM 31	420		SCS 13	341, 344
	SUM 31 L	423		SCS 13A	341, 344
	SUM 32	420		SCS 14	341, 345
	SUM 41	420		SCS 14A	341, 345
	SUM 42	421		SCS 15	361
	SUM 43	421		SCS 16	361
JIS G 4805:1999	SUJ 1	439		SCS 16 A	342, 345
	SUJ 2	435		SCS 17	342, 346
	SUJ 3	435		SCS 18	361
	SUJ 4	439		SCS 19	341, 344
	SUJ 5	439		SCS 19A	341, 344
JIS G 5101:1991	SC 360	319, 323		SCS 2	339, 340
	SC 410	319, 323		SCS 20	361
	SC 450	319, 323		SCS 21	341, 344
	SC 480	320, 323		SCS 22	342, 345
IIS G 5102:1991	SCW 410	319, 323		SCS 23	342, 346
	SCW 450	319, 323		SCS 24	361
	SCW 480	320, 323		SCS 2A	339, 340
	SCW 550	321, 324		SCS 3	339, 340
	SCW 620	321, 324		SCS 4	361
IIS G 5111:1991	SCC 3	320, 321		SCS 5	339, 340
	SCC 3A	324		SCS 6	339, 340
	SCC 3B	324	JIS G 5122:2003	SCH 1	351, 355
	SCC 5	321, 322		SCH 11	351, 355
	SCC 5A	324		SCH 12	351, 356
	SCC 5B	325		SCH 13	352, 356
	SCCrM 1A	330, 331		SCH 13A	352, 356
	SCCrM 1B	330, 331		SCH 15	353, 357
	SCCrM 3A	330, 332		SCH 16	353, 357
	SCCrM 3B	330, 332		SCH 17	351, 356
	SCMn 1	320, 321		SCH 18	352, 356
	SCMn 1A	324		SCH 19	353, 357
	SCMn 1B	324		SCH 2	351, 355
	SCMn 2	321, 321		SCH 20	353, 358
	SCMn 2A	324		SCH 21	352, 356
	SCMn 2B	324		SCH 22	352, 357
	SCMn 3			SCH 23	352, 357
		321, 322 324		SCH 24	353, 357
	SCMn 3A	324		SCH 3	351, 355
	SCMn 3B	325		3UN 3	רכינ. וכני

662 Specification Designation Index

Specification Designation	Steel Grade/Name	Page	Specification Designation	Steel Grade/Name	Page
IIS G 5131:1991	SCMnH 1	328, 329	SAE J403 NOV01	1078	32
	SCMnH 11	328, 329	(continued)	1080	33
	SCMnH 2	328, 329		1084	44
	SCMnH 21	360		1085	44
	SCMnH 3	328, 329		1086	33
IIS G 5151:1991	SCPH 1	326		1090	33
	SCPH 11	335, 336		1095	33
	SCPH 2	326		1117	420
	SCPH 21	335, 336		1118	420
	SCPH 22	359		1126	436
	SCPH 23	335, 336		1132	436
	SCPH 32	335, 336		1137	420
	SCPH 61	335, 336		1138	420
JIS G 5152:1991	SCPL 1	327		1140	421
	SCPL 11	337, 338		1141	421
	SCPL 21	337, 338		1144	421
	SCPL 31	337, 338		1146	421
SAE J403 NOV01	1005	23		1151	421
	1006	23		11L17	423
	1008	23		11L37	423
	1009	44		11L41	423
				11L44	423
	1010	23		11L44	423
	1012	23		1212	422
	1013	44			
	1015	24		1213	422
	1016	24		1215	422
	1017	24		12L13	424
	1018	24		12L14	424
	1019	44		12L15	424
	1020	25		1522	34
	1021	25		1524	44
	1022	25		1526	44
	1023	25		1527	44
	1025	26		1536	44
	1026	26		1541	34
	1029	26		1547	44
	1030	26		1548	44
	1033	44		1552	44
	1035	27		1566	44
	1037	44	SAE J404 JUN00	1330	44
	1038	27		1335	44
	1039	28		1340	44
	1040	28		1345	44
	1042	28		4023	44
	1043	28		4027	44
	1044	29		4037	44
	1045	29		4047	44
	1046	29		4118	37
	1049	30		4120	37
	1050	30		4130	37
	1053	30		4135	44
	1055	31		4137	38
	1060	31		4140	38
		32		4142	44
	1065			4145	38
	1070	32			
	1071	4.4			
	1074 1075	44 44		4150 4320	38 39

Specification Designation	Steel Grade/Name	Page
SAE J404 JUN00	4340	39
(continued)	4615	44
	4617	44
	4620	44
	4820	44
	50B46	41
	5115	44
	5120	35
	5130	35
	5132	35
	5140	36
	5150	44
	5160	44
	51B60	41
	6150	42
	8615	44
	8617	44
	8620	39
	8622	44
	8625	44
	8627	44
	8630	44
	8637	44
	8640	39
	8645	44
	8655	44
	8720	44
	8740	44
	8822	44
	9254	44
	9259	44
	9260	44
	E4340	39
	E52100	44
SAE J438-1970	A2	433
	D2	433
	D3	433
	D5	438
	D7	438
	H11	434
	H12	434
	H13	434
	H21	434
	L6	434
	L7	438
	M1	438
	M2	432
	M3	432
	M4	432
	01	438
	02	438
	O6	438
	S1	438
	S2	438
	S5	438
	T1	431
	T2	438

Specification Designation	Steel Grade/Name	Page
	T4	431
	T5	431
	T8	438
	W108	430
	W109	430
	W110	430
	W112	430
	W209	438
	W210	438
	W310	438
SAE J526 JAN 00		165, 176