

Student 20 **MRAVITEJA** 192312295RA

4 / 4 submitted

Q1. ARRAYS**CODE**

```
#include <stdio.h>
int main()
{
    int n,i,j=0;
    scanf("%d",&n);
    int arr[n];
    for(i=0 ; i<n; i++){
        scanf("%d",&arr[i]);
    }
    for(i=0;i<n;i++){
        if (arr[i]!=0){
            arr[j++]=arr[i];
        }
    }
    while(j<n){
        arr[j++]=0;
    }
    for(i=0;i<n;i++){
        printf("%d",arr[i]);
    }
    return 0;
}
```

INPUT

```
6
0 1 9 8 0 2
```

OUTPUT

(no output)

Q2. ARRAYS

CODE

```
#include <stdio.h>
int main()
{
    int n,i,j,count;
    scanf("%d",&n);
    int arr[n];
    int visited[n];
    for (i=0 ; i<n ; i++) {
        scanf("%d",&arr[i]);
        visited[i]=0;
    }
    for(i=0;i<n;i++){
        if(visited[i]==1)
            continue;
        count=1;
        for(j=i+1;j<n;j++){
            if(arr[i]==arr[j]){
                count++;
                visited[i]=1;
            }
        }
        printf("%d: %d", arr[i],count);
        if(count==1)
            printf("times\n");
        else
            printf("times\n");
    }
    return 0;
}
```

INPUT

```
7
2 2 1 5 1 3 3
```

OUTPUT

```
(no output)
```

Q3. ARRAYS**CODE**

```
#include <stdio.h>
int main()
{
    int n;
    scanf("%d",&n);
    int arr[n];
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);

    }
    int last=arr[n-1];
    for (int i=n;i>0;i--){
        arr[i]=arr[i-1];
    }
    arr[0]=last;
    for(int i=0;i<n;i++){
        printf("%d",arr[i]);
    }
    return 0;
}
```

INPUT

5
1 2 3 4 5

OUTPUT

(no output)

Q4. ARRAYS**CODE**

```
#include <stdio.h>
int main()
{
    int n,i,j;
    scanf("%d",&n);
    int a[n][n];
    for (i=0;i<n;i++){
        for(j=0;j<n;j++){
            scanf("%d",&a[i][j]);
        }
    }
    for (i=0;i<n;i++){
        for (j=n-1;j≥0;j--){
            printf("%d ",a[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

INPUT

3
1 2 3
4 5 6
7 8 9

OUTPUT

(no output)