BINF2111 - Introduction to Bioinformatics Computing UNIX 101 - enter the coding zone



Richard Allen White III, PhD RAW Lab Lecture 6 - Thursday Sep 8th, 2021

Learning Objectives

- Review quiz and bonus
- wget/zip/tar
- tr/printf command
- text editors
- Sort/uniq/cut commands review
- Quiz 6

- grep -v -e '^\$' file.txt

- A) delete all empty lines
- B) cut all empty lines
- C) print all empty files
- D) append all empty lines

- grep -v -e '^\$' file.txt

A) delete all empty lines

- B) cut all empty lines
- C) print all empty files
- D) append all empty lines

- cut -f1,4 -d "," file.csv --complement

- A) print only columns 1 and 4
- B) print all but columns 1 and 4
- C) cut only columns 1 and 4 but not print
- D) will email Dr. White and Jose the columns

- cut -f1,4 -d "," file.csv --complement

- A) print only columns 1 and 4
- B) print all but columns 1 and 4
- C) cut only columns 1 and 4 but not print
- D) will email Dr. White and Jose the columns

Count the numbers of 'A', 'T', 'G', 'C' using multiple or single grep commands in example.fasta?

Count the numbers of 'A', 'T', 'G', 'C' using multiple or single grep commands in example.fasta?

egrep -o 'A|T|G|C' example.fasta | wc -l grep -oE 'A|T|G|C' example.fasta | wc -l

168?

Count the numbers of 'A', 'T', 'G', 'C' using multiple or single grep commands in example.fasta?

egrep -o 'A|T|G|C' example.fasta | wc -l grep -oE 'A|T|G|C' example.fasta | wc -l

168?

THIS WOULD BE WRONG! But, why?

>chr1 geneA CTAAGGCTATCTTGACAACTGACT >chr1 geneB CTAAGGCTATGTTGGCAACTGACT >chr1 geneC CTAAGGCTACCTTGACAACTGACT >chr1 geneD AAAAGGCTATCTTGACAACTGACT >chr1 geneX CTAAGGCTATCTTGATTTCTGACT >chr1 geneY GGGGGCTATCTTGACAACTGACT >chr1 geneZ CTAAGGCTATCNNGACAACTGACT

>chr1 geneA CTAAGGCTATCTTGACAACTGACT >chr1 geneB CTAAGGCTATGTTGGCAACTGACT >chr1 geneC CTAAGGCTACCTTGACAACTGACT >chr1 geneD AAAAGGCTATCTTGACAACTGACT >chr1 geneX CTAAGGCTATCTTGATTTCTGACT >chr1 geneY GGGGGCTATCTTGACAACTGACT >chr1 geneZ CTAAGGCTATCNNGACAACTGACT

>chr1 geneA CTAAGGCTATCTTGACAACTGACT >chr1 geneB CTAAGGCTATGTTGGCAACTGACT >chr1 geneC CTAAGGCTACCTTGACAACTGACT >chr1 geneD AAAAGGCTATCTTGACAACTGACT >chr1 geneX CTAAGGCTATCTTGATTTCTGACT >chr1 geneY GGGGGCTATCTTGACAACTGACT >chr1 geneZ CTAAGGCTATCNNGACAACTGACT

Write a command where you could fix this?

```
>chr1 geneA
CTAAGGCTATCTTGACAACTGACT
>chr1 geneB
CTAAGGCTATGTTGGCAACTGACT
>chr1 geneC
CTAAGGCTACCTTGACAACTGACT
>chr1 geneD
AAAAGGCTATCTTGACAACTGACT
>chr1 geneX
CTAAGGCTATCTTGATTTCTGACT
>chr1 geneY
GGGGGCTATCTTGACAACTGACT
>chr1 geneZ
CTAAGGCTATCNNGACAACTGACT
```

sed 's/geneA/geneX2/g' example.fasta | sed 's/geneC/geneX3/g' | egrep -o 'A|T|C|G' | wc -

```
>chr1 geneA
CTAAGGCTATCTTGACAACTGACT
>chr1 geneB
CTAAGGCTATGTTGGCAACTGACT
>chr1 geneC
CTAAGGCTACCTTGACAACTGACT
>chr1 geneD
AAAAGGCTATCTTGACAACTGACT
>chr1 geneX
CTAAGGCTATCTTGATTTCTGACT
>chr1 geneY
GGGGGCTATCTTGACAACTGACT
>chr1 geneZ
CTAAGGCTATCNNGACAACTGACT
```

Always check your data! ;-)

Bonus 4


- Convert name game file (name_game.csv) to tsv with:

- \rightarrow tr
- → awk


Bonus 4


- Convert name game file (name_game.csv) to tsv with:
- → tr: cat name_game.csv | tr -s ',' '\t' >name_game.tsv
- → awk: cat name_game.csv | awk -F ',' '{\$1=\$1}1'
- >name game.tsv


wget examples





wget examples




















Tr (translate) – syntax anatomy UNIX tool

tr [OPTION] SET1 [SET2]


- -c : complements the set of characters in string (i.e., operations apply to characters not in the given set)
- -d: delete characters in the first set from the output.
- -s : replaces repeated characters listed in the set1 with single occurrence
- -t: truncates set1

tr (no option) = substitute [original] [new]














printf – syntax anatomy UNIX

For percent % symbol

%%

printf [-v var] format [arguments]

```
For signed decimal numbers
%i For signed decimal numbers
      For unsigned decimal numbers
%u
      For unsigned octal numbers
%o
      For unsigned hexadecimal numbers with lower case letters (a-f)
%X
      For unsigned hexadecimal numbers with upper case letters (A-F)
%X
%f For floating point numbers
%s
      For string
```

printf – syntax anatomy UNIX

printf [-v var] format [arguments]

```
--help display this help and exit
```

--version output version information and exit

```
\xHH byte with hexadecimal value HH (1 to 2 digits)
\uHHHH Unicode (ISO/IEC 10646) character with hex
value HHHH (4 digits)
\UHHHHHHHHH
Unicode character with hex value HHHHHHHHH (8 digits)
%% a single %
%b ARGUMENT as a string with '\' escapes interpreted,
```

except that octal escapes are of the form \0 or \0NNN

\" double quote \\NNN character with octal value NNN (1 to 3 digits)

\\ backslash

\a alert (BEL)

\b backspace

\c produce no further output

\f form feed

In new line

\r carriage return

\t horizontal tab

vertical tab

printf – syntax anatomy UNIX

printf [-v var] format [arguments]


- N This specifies the width of the field for output.
- This is the placeholder for the width.
- To left align output in the field. (Default: Right align)
- 0 Pad result with leading 0s.
- + To put + sign before positive numbers and sign for negative numbers.
- printf() function of C programming language. We can say that printf is a successor of echo command.

printf examples


























Text editors - nano




Text editors - vim



Text editors - gedit




Text editors - atom





cut – syntax anatomy UNIX's scissors


cut [options] file.txt

- -d (--delimiter) "," set field delimiter (default tab)
- -f (--fields=LIST) Select by specifying a field
 - -f 2 select a field to cut (left is 1)
 - -f 2-8,12 select multiple fields to cut
- -b (--bytes=LIST) Select by specifying a byte
- -c (--characters=LIST) Select by specifying a character
- --complement Complement the selection.
- -s (--only-delimited) suppress non-matches










sort – syntax anatomy of sort

sort [options] file.txt


- -t "t" set the delimiter when using -k default is non-blank to blank transition
- -k 3 sort column #3 (left is 1)
- -k 2,3 sort multiple columns
- -n sort numerically
- -r reverse sort order
- -u drop duplicates from the result
- -b, --ignore-leading-blanks, ignore leading blanks
- -d, --dictionary-order consider only blanks and alphanumeric characters
- -f, --ignore-case fold lower case to upper case characters
- No options: sort alphabetically from leftmost character.


Æ








Æ

















uniq – syntax anatomy of uniq

uniq [options] file.txt


- Only works on sorted files and adjacent lines!
- -c count lines for each unique value
- -d only report duplicated lines
- -u only report non-duplicated lines
- No options: drop all duplicated lines (keeps 1 copy)








SE A-




4 david abdul chi bill bill abdul david 4 mary


All together now examples



All together now examples



All together now examples



Quiz 6

- On canvas now

Bonus 5

- In the doppelganger_names.txt count how many times the name 'chi' is left to the name 'bill'

Using grep only command:

Using grep with printf command:

Only awk: