

HYDRA:

- Hydra is an offensive cybersecurity tool which is a brute force online password cracking program. It is used for penetration testing to test whether a login system can be broken using many password guesses automatically. Hydra works with many network services: SSH, FTP, HTTP, RDP, MySQL etc

Hydra commands:

a) For SSH ~~on~~ and a web form (POST METHOD)

```
hydra -l <username> -P <full path to pass> <Machine IP>
-t 4 ssh
```

- l = specifies SSH username for login
- P = indicates list of passwords
- t = sets the no. of threads to spawn. It means hydra will make 4 login attempts at the same time instead of one at a time. But make sure not to make threads very high.

b) For web forms: For this you must know what type of request it is making: GET or POST. It can be seen in browser's network tab (in developer tools) to see request type of view source code.

```
sudo hydra -l <username> -P <wordlist> <Machine IP> http-post-form
<path>:<login-credentials>:<invalid-response>
```

<path>: login page URL

<login-credentials>: the username and password used to login
It tells hydra how the website sends username and password to the server

<invalid response>: part of the response when login fails, or you tell the hydra that if the login fails of the server response will contain something like this string and if it doesn't contain it means the login was successful.

- If the web server is listening on a non-default port number then you can specify the port number using:
-s <port>

- In <login-credentials> we will put <username:USER &password=^{^PASS^}~~pass~~>

This ^pass^ mean hydra will replace password from list ~~and~~ here and username is fixed as user because its not inside " ^ ^ ".

If we want both varying then in place of username I will put username list and use ^user^ which means now username is also varying.

- If username or password is ~~not~~ a wordlist then use -L or -P otherwise if its single word use -l or -p.