

CYBERCHEF: THE BASICS

- It is a simple, intuitive web-based application designed to help with various "cyber" operation tasks within your web browser. It is like a magical toolbox of different tools designed to do a specific task.

- Cyberchef consists of 4 areas, each having different components or feature:

a) Operations: This area contains all the operations that cyberchef can perform. Below are some operations that you might use throughout your journey:

Operations	Description
i) From Morse Code	And Translates morse code into alphanumeric -ic characters (Upper case)
ii) URL encode	Encodes all problematic characters into percent-encoding, a format supported by URL/URI
iii) To Base 64	Translates raw data into an ASCII Base 64 string
iv) ROT 13	A simple caesar substitution cipher which rotates alphabet by the specified amount

b) Recipe area: In this area you can seamlessly select, arrange and fine tune operations to suit your needs.

- Save recipe: Allows user to save selected operations.
- Load recipe: Allows user to load previously saved recipe

- Clear recipe: Allows user to clear the chosen recipe.

c) Input area: In this area we can easily input text or files by pasting, typing or dragging them to perform operations.

- Add a new input tab: This is used to create an additional tab where we can use different values from the previous tab.

- ~~Add~~ open folder as input
- Open file as input
- Clear input and output

d) Output area: In this area we will see the results of the data processing.

- Save output to file
- Copy raw output to the clipboard
- Replace input with output
- Maximise output pane

- The operations area is divided broadly into many categories, inside which there are many operations. Some of the categories are:

a) Extractor: i) Extract IP addresses: Extract all IPV4 and V6 addresse
 ii) Extract URL: Extract URL from input, ^{but} (HTTP, FTP) protocol is required
 iii) Extract email addresses

b) Date and Time: i) From UNIX timestamp: Convert UNIX timestamp to
 a datetime string

ii) To UNIX timestamp: Parses a Datetime string in UTC and returns corresponding UNIX timestamp.

A UNIX timestamp is a 32bit value representing the no. of seconds since January 1, 1970 UTC (the UNIX epoch)

c) Data format: i) From Base 64

ii) URL decode

iii) From Base 85

iv) From Base 54

v) To base 62