THAAP

Agent Trust Runtime

Product Strategy, Security Architecture and Implementation Roadmap

North Star

Every autonomous economic action should be attributable, authorized, constrained, explainable and recoverable.

Core thesis

THAAP should own the boundary between "an AI agent wants to act" and "the financial system permits that action." It should be model-neutral, agent-neutral, protocol-neutral and payment-rail-neutral.

Working strategy document | Version 1.0 | October 2026

THAAP = Threat Hunting & Adaptive Analytics for Payments

Wajo/Fo is used in this document as an illustrative market signal and integration example, not as a partner or dependency.

1. Executive Summary

Agentic commerce changes the core assumption of digital payments: the person who owns the money may no longer be the entity directly clicking "buy."

THAAP should evolve from an AI-native fraud/risk platform into the trust and authorization control plane for autonomous economic actors. Its job is not to make an agent smarter; its job is to determine whether an agent is allowed to act, under what constraints, with what evidence, and what should happen when the action is risky or ambiguous.

- **Wedge:** Agent Authorization Gateway returning ALLOW, DENY, STEP-UP, REPLAN or REQUEST_EVIDENCE for sensitive actions.
- **Primitive:** Cryptographically verifiable mandates that express user intent, delegation, scope, limits and expiry.
- **Moat:** A cross-ecosystem Trust Graph connecting principals, agents, providers, merchants, credentials, tools and transactions.
- **Risk layer:** Agent-behavior analytics, semantic intent matching, prompt-injection/compromise detection and transaction fraud signals.
- **Evidence layer:** Decision Ledger + Replay that reconstructs what was authorized, what the agent proposed, why THAAP decided, and what actually happened.
- **Positioning:** Do not build the shopping agent or the settlement rail. Build the independent trust layer between intelligence and money.

Strategic positioning

Intelligence providers (OpenAI, Anthropic, Google, Wajo and others) decide what to do. Payment rails (banks, networks, PSPs, wallets and stablecoin infrastructure) move the money. THAAP decides whether the proposed action is trustworthy enough to be permitted.

Target market architecture

AGENT / INTELLIGENCE	THAAP TRUST CONTROL PLANE	MONEY / EXECUTION RAILS
OpenAI Claude Gemini Wajo/Fo Enterprise agents	Identity Mandates Policy Risk Evidence Threat hunting	Banks Visa / Mastercard UPI / wallets Stripe / PSPs Stablecoins
proposed action ->	**decision / credential ->**	**execution + outcome**
Probabilistic planning	*Deterministic controls + adaptive risk*	*Settlement / fulfillment*

2. Why This Matters Now: The Wajo/Fo Signal

Wajo is useful to THAAP not because THAAP should copy Fo, but because Fo exposes the security and authorization problems that appear when software agents become economic actors.

Fo is an action agent that can call, email, coordinate with people, use one-time payment cards, and bring in human assistance when the AI cannot complete a task. Wajo also describes agents with their own inbox, phone number, voice and credit card. [1][2]

The key THAAP implication: once an agent can communicate, authenticate and spend on behalf of a user, the industry needs a separate trust layer that can verify identity, delegation, intent, constraints, risk and accountability before execution.

Wajo/Fo capability	New trust problem	THAAP opportunity
Agent can pay	Was this exact purchase actually authorized?	Mandate verification + scoped execution credential
Agent has its own identity	How does a merchant/bank know which agent is acting?	Agent Identity Registry + attestation
Agent can call/email	Did the agent expose data or follow malicious instructions?	Behavior monitoring + prompt-injection/compromise detection
Agent can act autonomously	How do we enforce limits when the human is absent?	Open mandate + deterministic policy runtime
Agent can use human fallback	Who performed the final action and under whose authority?	Delegation chain + actor provenance
Agent can use commerce protocols	How do we normalize trust across protocols/providers?	Protocol adapters + common THAAP authorization API

> **Important boundary**
>
> THAAP should not become a Wajo competitor. Wajo-like systems are potential clients, partners or upstream action agents. THAAP should provide the authorization and risk infrastructure they can call before sensitive economic actions.

Industry validation

The broader payment ecosystem is converging on the same primitives: explicit user intent, agent identity, constrained credentials, cryptographic evidence and deterministic verification. Google AP2 defines open/closed mandates and receipts; Mastercard Verifiable Intent links identity, intent and action; Visa Intelligent Commerce describes agent-bound credentials, authentication and controls; Stripe Shared Payment Tokens scope payments by seller, amount and time. [4][5][6][7]

3. Problem Definition

Traditional fraud systems were designed for a world in which the account owner or cardholder directly initiated the transaction. Agentic systems break that assumption.

Question	Traditional answer	Agentic-era requirement
Who acted?	Cardholder / logged-in user	Human principal + agent + provider + runtime identity
What was authorized?	Checkout click / OTP / cardholder authentication	Machine-readable mandate representing delegated intent
What can the actor do?	Account permissions / card limits	Fine-grained policy: merchant, category, purpose, time, amount, recurrence, substitutions
Is it safe?	Transaction risk score	Transaction risk + agent trust + semantic intent match + behavior anomaly
What if it goes wrong?	Dispute and logs	Cryptographic evidence + full decision replay + delegation provenance

The THAAP problem statement: Given a principal, an agent, a mandate, a proposed economic action and current risk context, determine whether to permit execution and produce verifiable evidence for that decision.

4. Product North Star and Design Principles

Principle	Meaning in THAAP
Attributable	Every action has a provable actor chain: principal -> agent -> provider/runtime -> tool/credential.
Authorized	An action must trace to authenticated, explicit user or business delegation.
Constrained	Authorization is least-privilege: purpose, amount, merchant, category, time, recurrence and data-sharing boundaries.
Explainable	Every decision records machine-readable reasons, evidence, policy results and model outputs.
Recoverable	The platform supports step-up, revocation, credential kill-switches, dispute evidence and safe retries.
Deterministic at the boundary	LLMs can interpret and score; deterministic code must enforce money-moving controls.
Protocol-neutral	AP2/UCP/network/PSP-specific mechanisms are adapters, not the core domain model.
Privacy-minimizing	Reveal only the information required to evaluate

	the requested action.

Product definition

THAAP Agent Trust Runtime = Identity + Delegation + Intent + Policy + Risk + Evidence + Threat Hunting, exposed through one real-time authorization plane.

5. Reference Architecture

The runtime is split into a synchronous authorization path and asynchronous intelligence/evidence paths. The synchronous path must remain small, deterministic, observable and fail-safe.



5.1 Core services

Service	Primary responsibility	MVP?
Authorization Gateway	Single entry point for agent-sensitive economic actions; idempotency, authn, schema validation, routing.	YES
Agent Identity Registry	Agent/provider identity, public keys, capabilities, attestations, versions and revocation state.	YES
Principal & Delegation Service	Human/business principal, delegation chain, consent record, revocation.	YES
Mandate / Intent Service	Create, sign, store, validate and close open mandates; semantic constraints.	YES
Policy Runtime	Deterministic evaluation of hard constraints and regulatory/business policy.	YES
Risk Engine	Agent trust score, transaction risk, behavioral anomalies and confidence.	YES, narrow
Step-Up Orchestrator	Human approval,	YES

	passkey/biometric/bank auth, additional evidence requests.	
Decision Ledger	Immutable append-only decision/evidence records with integrity verification.	YES
Decision Replay	Reconstruct policy version, signals, inputs, outputs and receipts.	YES
Trust Graph	Cross-entity graph for relationship and reputation features.	Phase 2
Agent SOC / Threat Hunting	Detect compromised agents, prompt injection, tool misuse and abnormal delegation.	Phase 2
Protocol Gateway	AP2/UCP/network/PSP adapters; maps external artifacts to THAAP canonical model.	Phase 2

5.2 Synchronous decision path

1. **Authenticate caller.** Verify the agent application/provider and request integrity.
2. **Resolve principal and delegation.** Confirm which user/business is ultimately represented and whether the delegation is live.
3. **Validate mandate.** Signature, expiry, scope, proof-of-possession, replay prevention and constraint schema.
4. **Normalize action.** Convert protocol-specific request into THAAP canonical economic action.
5. **Run deterministic policy.** Hard limits: merchant, amount, currency, category, purpose, geography, time, recurrence, data disclosure.
6. **Run adaptive risk.** Transaction risk, behavior anomaly, intent similarity, reputation, environment and compromise signals.
7. **Resolve decision.** ALLOW, ALLOW_WITH_LIMITS, STEP_UP, REPLAN, REQUEST_EVIDENCE or DENY.
8. **Issue capability.** Optional single-purpose, short-lived execution authorization bound to the action.
9. **Record evidence.** Persist input hashes, policy version, scores, reasons, decision and later execution receipts.

6. Canonical Domain Model

The canonical model is the key to staying protocol-neutral. External standards map into these primitives rather than becoming the internal architecture.

Entity	Key fields / semantics
Principal	principal_id, type, authentication strength, jurisdiction, organization/account links
Agent	agent_id, provider_id, public key, version,

	capabilities, runtime attestation, status
Delegation	principal -> agent/provider authority, scopes, issuance time, expiry, revocation
Mandate	goal, constraints, allowed action types, disclosure policy, proof, open/closed state
EconomicAction	purchase/transfer/subscription/refund/ beneficiary/etc.; amount, merchant, asset, destination, purpose
Credential	credential_id, issuer, scope, binding, expiry, usage count, revocation state
RiskContext	behavioral, device/runtime, merchant, network, fraud and threat intelligence signals
Decision	outcome, reasons, policy version, scores, required next action, expiry
Receipt	what executed, when, by whom, external processor refs, hashes/signatures
EvidenceBundle	mandate + action + decision + receipts + provenance used for replay/disputes

6.1 The THAAP Trust Graph



Why the graph matters: conventional transaction checks may see individually valid entities. THAAP can identify that the relationship itself is abnormal - for example, a travel agent suddenly purchasing high-value gift cards from a new merchant, outside the semantic intent of the mandate.

7. Mandates and Semantic Authorization

The mandate is the machine-verifiable representation of delegated authority. It is the contract between human intent and autonomous execution.

Constraint family	Examples
Financial	maximum amount, cumulative budget, currency, per-transaction cap
Merchant	allowlist/denylist, merchant ID, category, reputation threshold

Purpose	flight booking, laptop purchase, cloud compute, invoice payment
Product/service	SKU, class of service, quantity, substitution rules
Temporal	not-before, expiry, recurrence cadence, usage count
Geographic	allowed country/region, beneficiary domicile
Data disclosure	what personal attributes the agent may reveal to merchant/provider
Human oversight	approval threshold, biometric/passkey requirement, co-signature
Agent scope	specific agent/provider/key, allowed tools, delegation-to-subagent rules

Example mandate

```
{
  "mandate_id": "mandate_18472",
  "principal_id": "principal_raj",
  "agent_id": "wajo.fo.82714",
  "goal": "buy_one_laptop",
  "constraints": {
    "max_amount": 150000,
    "currency": "INR",
    "allowed_merchants": ["Apple India", "Croma", "Reliance Digital"],
    "quantity": 1,
    "substitution": "DENY",
    "expires_at": "2026-10-06T23:59:00+05:30",
    "step_up_if_amount_gt": 140000
  },
  "proof": "<signed-verifiable-authorization>"
}
```

7.1 Why semantic authorization is different from payment authorization

A transaction may satisfy a numeric budget and still violate user intent. THAAP should compare the proposed action against the meaning of the instruction, not only the amount. Example: a flight under budget that violates "no overnight layover" should be REPLAN or DENY even though the payment is affordable.

> **Rule**
>
> LLMs may interpret intent and generate semantic features; final enforcement must be deterministic and reproducible from stored policy + mandate + evidence.

8. Decision Engine

THAAP should return a richer set of control outcomes than binary payment authorization.

Decision	Meaning	Example
ALLOW	Execute as proposed.	Low-risk purchase fully inside mandate.
ALLOW_WITH_LIMITS	Execute only with a narrower credential or modified limit.	Issue a one-time token for exactly INR 12,500.
STEP_UP	Require human or stronger authentication.	High-value action outside normal autonomous range.
REPLAN	Agent goal is valid but proposed execution violates intent.	Flight has forbidden overnight layover.
REQUEST_EVIDENCE	Need additional proof before deciding.	Merchant identity or agent attestation missing.
DENY	Do not execute.	Gift-card purchase unrelated to laptop mandate.
QUARANTINE	Suspend agent/credential and trigger investigation.	Strong compromise or prompt-injection indicators.

8.1 Decision inputs

- **Agent Trust Score:** identity confidence, attestation, provider reputation, version history, anomaly rate, compromise indicators.
- **Mandate Match:** hard-constraint validation + semantic similarity between user intent and proposed action.
- **Transaction Risk:** merchant/payee risk, amount anomaly, payment credential risk, device/network signals, known fraud patterns.
- **Behavior Deviation:** difference from principal-agent historical behavior and from the agent class baseline.
- **Threat Signals:** prompt injection, suspicious external instructions, tool-chain deviation, credential abuse, unexpected destination.
- **Policy Context:** tenant rules, regulatory constraints, product controls, authentication strength and risk appetite.

8.2 Explainability contract

```
Decision: STEP_UP
Reason codes:
  - AMOUNT_OUTSIDE_NORMAL_AGENT_RANGE
  - NEW_MERCHANT_FOR_AGENT
  - HIGH_VALUE_AUTONOMOUS_ACTION
Required action:
  - PASSKEY_OR_BIOMETRIC_APPROVAL
Evidence:
  - mandate_hash
  - action_hash
  - policy_version
  - agent_attestation_id
  - risk_feature_snapshot
```

9. Agentic Threat Hunting

This is where THAAP can differentiate from pure protocol and token providers. A valid signature does not prove that an agent has not been manipulated.

Threat	Detection idea	Control
Prompt injection from merchant/site/email	Action intent diverges sharply after exposure to untrusted content.	Deny/replan; isolate content; require clean-context re-evaluation.
Credential theft	Valid credential used by wrong agent key/runtime or from abnormal context.	Proof-of-possession; bind credential; revoke.
Mandate replay	Same open authorization reused without valid rejection/closure semantics.	Nonce, idempotency, usage counter, receipt chain.
Authorization drift	Agent gradually broadens interpretation of a standing instruction.	Semantic drift score; cumulative budget/purpose controls.
Tool-chain hijack	Unexpected tool, endpoint or sub-agent appears in execution path.	Tool allowlist + signed provenance + step-up.
Malicious/compromised agent update	Behavior changes after version change or attestation mismatch.	Version trust score, rollout guard, quarantine.
Merchant-agent collusion	Repeated anomalous patterns across merchants/agents/principals.	Graph analytics + ecosystem reputation.
Human-fallback ambiguity	Human operator completes action without clear delegation.	Actor provenance, scoped sub-delegation, auditable receipt.

Critical insight

Cryptographic authorization answers "was authority granted?" Threat hunting answers "is the currently acting system still behaving consistently with that authority?" THAAP needs both.

10. Scoped Execution Credentials

Where integrations allow it, THAAP should issue or broker short-lived capabilities that are useless outside the approved context.

```
THAAP-CAPABILITY
agent          = wajo.fo.82714
principal      = principal_raj
action         = purchase
merchant       = Apple India
max_amount     = INR 150000
purpose        = laptop
valid_for      = 10 minutes
```

```
usage          = 1
proof_of_possession = required
replay         = forbidden
```

The underlying payment rail can be a network token, PSP token, UPI flow, wallet authorization or future payment primitive. THAAP should not need to own the settlement instrument. It should decide whether a scoped credential can be issued and what constraints it must carry.

11. Decision Ledger and Replay

Decision Replay should become a flagship capability because disputes in agentic commerce are disputes about delegated intent, not just card possession.

Recorded artifact	Purpose
Principal authentication evidence	Who authorized delegation and at what assurance level?
Agent identity + key + attestation	Which exact agent/runtime acted?
Mandate + signature + version	What was authorized and under what constraints?
Proposed action	What did the agent actually ask to do?
Policy version + evaluation	Which deterministic rules were applied?
Risk features + model versions	What adaptive intelligence influenced the decision?
Decision + reason codes	Why was it allowed/blocked/escalated?
Scoped credential metadata	What capability was granted?
Execution receipts	What ultimately happened on the external rail?
Post-event outcomes	Refund, chargeback, dispute, fraud label, user confirmation.

```
THAAP DECISION REPLAY
Decision ID: thaap_dec_01H...
Principal: principal_raj
Agent: wajo.fo.82714
Intent: "Buy one MacBook under INR 150,000"
Mandate: VALID
Merchant: Apple India
Amount: INR 146,999
Hard policy: PASS
Semantic match: 0.99
Agent trust: 0.97
Transaction risk: 0.04
Decision: ALLOW
Credential: single-use, 10-minute TTL
Execution receipt: VERIFIED
Outcome: completed
```

12. Protocol and Ecosystem Strategy

THAAP should integrate with emerging standards without becoming captive to any one standard.

External ecosystem	Use in THAAP
Google AP2	Map open/closed checkout/payment mandates and receipts into THAAP Mandate, Action and Evidence models. AP2 explicitly requires deterministic processing for verification. [4]
Mastercard Verifiable Intent / Agent Pay	Consume or produce proof linking identity, intent and action; enrich with THAAP risk and policy. [5]
Visa Intelligent Commerce	Use agent-bound credentials, authentication and user-instruction controls as execution mechanisms/signals. [6]
Stripe Shared Payment Tokens	Treat seller/amount/time-scoped tokens as downstream execution credentials; add cross-provider policy/risk. [7]
Wajo/Fo	Potential upstream action agent calling THAAP before payment or other sensitive action; ingest Wajo agent identity/mandate context. [1][3]
Future agent protocols	Build adapters to canonical THAAP entities, never fork the core decision engine per protocol.

Interoperability principle

Protocols prove and transport intent. THAAP evaluates whether that intent should be trusted in current context and whether the resulting action should be permitted.

13. Developer Product: Authorization API

The first product must be extremely easy for an agent platform, bank, PSP or merchant to integrate.

13.1 Request

```
POST /v1/authorize

{
  "principal": { "id": "principal_raj" },
  "agent": { "id": "wajo.fo.82714", "provider": "wajo" },
  "mandate_id": "mandate_18472",
  "action": {
    "type": "purchase",
    "merchant": "Apple India",
    "amount": 146999,
    "currency": "INR",
    "purpose": "laptop",
    "item": "MacBook Pro"
  },
  "context": {
    "autonomous": true,
    "requested_at": "2026-10-06T21:14:32+05:30"
  }
}
```

13.2 ALLOW response

```
{
  "decision": "ALLOW",
  "decision_id": "thaap_dec_01H...",
  "agent_trust_score": 0.97,
  "transaction_risk_score": 0.04,
  "mandate_match": 1.00,
  "capability": {
    "scope": "single_transaction",
    "expires_in_seconds": 600
  },
  "reason_codes": ["MANDATE_VALID", "POLICY_PASS", "LOW_RISK"]
}
```

13.3 STEP_UP response

```
{
  "decision": "STEP_UP",
  "decision_id": "thaap_dec_01J...",
  "reason_codes": [
    "HIGH_VALUE_AUTONOMOUS_ACTION",
    "AMOUNT_OUTSIDE_NORMAL_AGENT_RANGE"
  ],
  "required_action": {
    "type": "PASSKEY_OR_BIOMETRIC_APPROVAL",
    "expires_in_seconds": 300
  }
}
```

14. Build Plan: From Prototype to Platform

The first goal is not comprehensive agentic commerce. It is a credible end-to-end authorization loop with verifiable intent, deterministic controls and replay.

Phase	Outcome	What to build
Phase 0 - 1 week	Executable design	Canonical schemas; decision taxonomy; threat model; OpenAPI contract; sample policies; fake agent + fake merchant simulator.
Phase 1 - 3 to 4 weeks	MVP Authorization Gateway	Agent/principal registry, mandate service, deterministic policy runtime, /authorize API, decision ledger, replay UI/CLI.
Phase 2 - 3 to 4 weeks	Adaptive trust	Risk features, semantic mandate match, anomaly detection, step-up flow, prompt-injection simulations.
Phase 3 - 4 to 6 weeks	Protocol interoperability	AP2 adapter, mock network/PSP adapter, scoped capability broker, signed receipts.
Phase 4	Trust Graph + SOC	Graph model, cross-entity anomaly features, agent version reputation, threat hunting and

		quarantine workflows.
Phase 5	Commercial platform	Multi-tenancy, tenant policy, audit export, SLA/HA, compliance controls, SDKs, partner integrations, pricing/metering.

14.1 MVP demo scenario

10. User authorizes a shopping agent to buy one laptop under INR 150,000 from an allowlisted merchant set.
11. Agent proposes a compliant purchase. THAAP validates the mandate and returns ALLOW with a single-use capability.
12. Agent proposes gift cards after reading a malicious prompt injection on a merchant page. THAAP detects severe intent deviation and returns DENY/QUARANTINE.
13. Agent proposes a valid but unusually high purchase near the maximum. THAAP returns STEP_UP and resumes only after passkey approval.
14. Replay screen reconstructs the complete evidence chain for each decision.

Demo success criterion

A viewer should understand in under five minutes that THAAP is not another fraud score. It is the decision boundary that safely converts delegated AI intent into permission to move money.

15. Suggested Technical Architecture

The implementation should optimize for auditability, low latency, deterministic replay and the ability to evolve ML independently from policy enforcement.

Layer	Suggested direction
API / services	Java + Spring Boot or Kotlin for core authorization services; gRPC internally where useful; REST/OpenAPI externally.
Policy	OPA/Rego or a constrained internal DSL for deterministic policy; version every policy bundle used in a decision.
Eventing	Kafka for decision/outcome events, threat signals, model features and asynchronous graph updates.
Operational data	PostgreSQL/Aurora PostgreSQL for principals, agents, mandates, policies and configuration.
Fast state/cache	Redis for nonce/replay protection, short-lived capability state, rate limits and hot risk features.
Evidence ledger	Append-only evidence records in immutable/object storage with hashes/signatures; relational index for lookup.

Graph	Start with relational edge tables; introduce graph database only when graph queries/features justify operational complexity.
ML / semantic risk	Python services for feature pipelines and model inference; keep outputs as signals, not direct money-moving authority.
Cryptography	KMS/HSM-backed signing keys; JWS/JWT/SD-JWT-compatible primitives; key rotation and revocation.
Observability	OpenTelemetry traces with decision_id correlation; Prometheus metrics; immutable audit logs; security alerts.
Deployment	Kubernetes for control plane services; isolate key/credential operations; multi-AZ first, multi-region when product/SLA demands it.

15.1 Non-functional targets for the prototype

- **Determinism:** Given the same stored inputs, policy version and model outputs, replay yields the same control decision.
- **Idempotency:** Retries never create multiple capabilities or duplicate authorizations.
- **Fail closed for hard controls:** Unverifiable mandate, unknown constraint or invalid signature cannot silently degrade to allow.
- **Low-latency core:** Keep cryptographic and deterministic evaluation on the synchronous path; expensive investigation runs asynchronously unless needed for risk.
- **End-to-end traceability:** Every request, decision, step-up and downstream receipt shares a decision_id / correlation chain.
- **Privacy:** Selective disclosure and data minimization by default; do not centralize raw personal data unless needed.

16. Competitive Positioning and Moat

THAAP should avoid competing where incumbents already have structural advantage and instead become the neutral layer that improves every participant.

Player type	They naturally own	THAAP should own
Agent platforms	User experience, planning, memory, tools, action execution.	Independent authorization, risk and proof before economic execution.
Card networks	Network identity, tokenization, authorization rails, network fraud data.	Cross-network + cross-agent trust intelligence and policy orchestration.
PSPs	Merchant checkout, tokens, payment orchestration, merchant risk.	Principal-agent mandate semantics, cross-provider agent reputation, decision replay.

Banks / issuers	Account/customer identity, balances, issuer authorization and fraud.	Reusable agent risk/intent layer across banks, merchants and protocols.
Identity vendors	Authentication and credentials.	Economic delegation + behavioral trust + transaction policy + evidence chain.

16.1 Potential moat flywheel

```
More agent platforms / banks / merchants
                |
                v
More authorized + blocked + disputed agent actions
                |
                v
Richer Trust Graph + better threat intelligence
                |
                v
Better decisions + lower friction + stronger evidence
                |
                v
More ecosystem adoption
```

The defensible asset is not a single model. It is the combination of canonical trust primitives, cross-ecosystem graph data, behavioral histories, policy integrations, evidence infrastructure and operational credibility in high-stakes money movement.

17. Initial Buyers and Business Model

Buyer	Pain	Possible commercial model
Agent platforms	Need safe payments/actions without building a financial trust stack.	Per authorization + premium risk/evidence tiers.
Banks / issuers	Need to distinguish legitimate agent transactions from fraud and enforce delegation.	Enterprise platform + per-decision usage.
PSPs / acquirers	Need agent-aware risk and dispute evidence across merchants.	API usage + risk modules.
Large merchants / marketplaces	Need to accept high-quality agents while blocking bots/compromised agents.	Per authorization / per protected GMV.
Enterprises	Need controls for procurement, AP, treasury and machine spending.	Per agent / policy seat + transaction usage.

18. Product and Risk Metrics

Metric	Why it matters
Authorization latency P50/P95/P99	THAAP cannot become the bottleneck for autonomous execution.
False allow rate	Unsafe actions incorrectly permitted.
False step-up / false deny rate	Measures friction imposed on valid autonomous activity.
Mandate mismatch detection rate	Core semantic authorization quality.
Prompt-injection compromise detection	Security effectiveness against agent manipulation.
Credential misuse / replay prevented	Value of scoped capabilities and proof-of-possession.
Dispute evidence completeness	Percentage of disputed actions reconstructable end-to-end.
Agent trust calibration	Whether trust scores predict future unsafe outcomes.
Time to revoke / quarantine	Operational containment effectiveness.
Autonomous completion uplift after safe step-up/replan	Shows THAAP improves outcomes, not only blocks risk.

19. What THAAP Should Not Build First

- A general consumer shopping assistant.
- A ChatGPT/Claude/Gemini competitor.
- A browser automation framework as the core product.
- A new card network or settlement rail.
- A full merchant checkout stack.
- A graph database before graph use cases justify it.
- A black-box LLM that directly returns ALLOW/DENY with no deterministic policy layer.
- A huge fraud model before the mandate/identity/evidence foundation works end-to-end.

Focus rule

If a feature makes THAAP better at proving authority, constraining action, detecting misuse, deciding risk or explaining an outcome, it is probably core. If it mainly makes an agent more capable at shopping, browsing or chatting, it is probably not.

20. Key Risks and Mitigations

Risk	Mitigation
Standards evolve quickly	Canonical internal model + adapter architecture;

	do not hard-code AP2/UCP semantics into core domain.
Networks/PSPs build overlapping features	Be cross-network, cross-agent and risk/policy focused; integrate rather than replace.
Insufficient early data for ML	Start with deterministic mandate/policy checks + simulation; introduce learning after evidence accumulates.
Privacy / sensitive data concentration	Selective disclosure, tokenization, hashes, tenant isolation, retention minimization.
LLM non-determinism	Never make model output the only authority for money movement; persist model version/output as an advisory signal.
Latency from too many checks	Tiered decision path; cache stable identity/reputation; move non-critical enrichment async.
Ambiguous liability	Evidence-first design, explicit role/delegation model, clear integration contracts and immutable receipts.
Low adoption by agent developers	One-call API, SDKs, sandbox, protocol adapters and a compelling replay/debugging experience.

21. Recommended 90-Day Founder/CTO Execution Plan

Window	Founder/CTO objective	Deliverable
Days 1-15	Nail the primitive	Canonical model, threat model, decision taxonomy, mandate schema, OpenAPI, demo scenarios, architecture ADRs.
Days 16-45	Ship the trust boundary	Working /authorize path, deterministic policy, signed mandate, decision ledger, replay, mocked credential issuance.
Days 46-70	Make it agent-native	Semantic intent match, anomaly signals, prompt-injection scenario, step-up UX/API, risk reason codes.
Days 71-90	Prove interoperability	AP2-compatible demo adapter, agent SDK, merchant/PSP simulator, polished technical demo and design-partner pitch.

21.1 The demo I would show investors/design partners

15. A user delegates a constrained purchase mandate to an AI agent.
16. The agent makes a compliant purchase: THAAP allows it and produces a scoped capability.
17. A malicious page injects a new instruction: the agent attempts an unrelated payment; THAAP blocks and quarantines it.
18. A legitimate but high-risk purchase triggers passkey step-up, then succeeds.
19. The operator opens Decision Replay and sees the complete chain from human intent to external receipt.
20. The same demo is repeated through an AP2 adapter to prove protocol interoperability.

22. Final Product Vision

THAAP wins if it becomes infrastructure that users never need to think about but every serious autonomous transaction can rely on.

> **THAAP mission**
>
> Make autonomous economic action trustworthy enough to become normal.

The long-term category: Trust infrastructure for the autonomous economy.

The long-term boundary THAAP should own: the moment where probabilistic machine intent becomes permission to create a real-world financial consequence.

The five guarantees: Attributable. Authorized. Constrained. Explainable. Recoverable.

References

These sources validate the market direction and external protocol landscape. They are references, not implementation dependencies.

[1] Wajo - Fo product page - https://wajo.ai/

[2] Wajo - Unveiling Wajo - https://wajo.ai/blog/unveiling-wajo/

[3] Wajo Terms of Service - agent actions, delegation and payments - https://wajo.ai/terms-of-service

[4] Google Agent Payments Protocol (AP2) specification - https://github.com/google-agentic-commerce/AP2/blob/main/docs/ap2/specification.md

[5] Mastercard - Verifiable Intent - https://www.mastercard.com/us/en/news-and-trends/stories/2026/verifiable-intent.html

[6] Visa Intelligent Commerce - https://www.visa.com/en-us/solutions/intelligent-commerce

[7] Stripe - Agentic Commerce Suite / Shared Payment Tokens - https://stripe.com/blog/agentic-commerce-suite

[8] TechCrunch - Vinod Khosla on Wajo and trust - https://techcrunch.com/2026/10/06/vinod-khosla-believes-ex-deepmind-engineers-wajo-will-win-agent-market-on-trust/

Prepared as a THAAP product strategy and technical architecture working document. External product specifications and standards will evolve; protocol integrations should be versioned and validated against current specifications before production use.