

WATER PERMEABILITY APPARATUS

STD: DIN 1048 | EN 12390-8 | IS 516

Product Description:

This apparatus is used to determine the depth of penetration of water under pressure in the concrete specimens. The test is performed clamping the specimen - cubic, cylindrical or prismatic of length of edge, or diameter not less than 100 mm - between two flanges with special circular gaskets. The water, under controlled pressure, is then applied to the surface of the concrete specimen. The penetration of water is measured, after the testing period, by breaking the specimen. The quantity of penetrated water, can also be measured through the graduated burettes fitted on top of the apparatus.

Quick Applications:

The apparatus consists of a robust steel frame with clamping system, incorporating the circuit, valves, gauge to check the water pressure and measuring transparent burettes mounted on top of the apparatus. The clamping system can accept cube or prismatic specimens up to 200 mm. The apparatus must be fit with a suitable air compressor, max. working pressure 5-16 bar. All versions are supplied complete with gaskets for 150 mm cube specimens.

Five Models available:

*CIE-WP-3C Three Cell model

*CIE-WP-9C Nine Cell model

*CIE-WP-24C Twenty-Four Cell model



Advantages & Features:

- New design that allows space-saving increased and functionality.
- Determination of the depth of penetration of water under pressure in the cube and prismatic concrete specimens up to 200 mm Cube and Cylinders.
- Easy to Lock & Unlock
- Control valves & gauges for live pressure reading.
- Laboratory air compressor. 20 BAR max constant pressure. 230V/50Hz/1-3Ph
- Set of 24 gaskets for permeability test on 200 mm side/dia samples,
- Set of 24 gaskets for permeability test on 150 mm side/dia samples.



Description	Value	Units
Standard	DIN 1048 EN 12390-8 IS 516	
Item Code.	WP-3C/6C/9C/12C/24C	
Test Pressure	5-20	Bar
Dimensions	800 x 300 x 1450	mm
Approx. weight	20-60	kg
Water Tank	25-150	Ltrs
Display	Analogue Pressure Indicator	
Included in delivery:	Setup with Circuit, Valves, Gauges, Air Compressor (as per request) 3/6/9/12/24 nos. of Gaskets.	