RPractical_Tignero

Raydric Tignero

2026-11-11

Part A: Basic Operations

A1 Create v as the sequence 5, 10, 15, . . . , 50 using seq(). Print its length, sum and mean

```
v <- seq(5, 50, by = 5)
length(v)
```

```
## [1] 10
```

```
sum(v)
```

```
## [1] 275
```

```
mean(v)
```

```
## [1] 27.5
```

A2 Create w that repeats the vector c(1, 2, 3) four times, and z that repeats each element of c(1, 2, 3) four times. Print both.

```
w <- rep(c(1, 2, 3), times = 4)
z <- rep(c(1, 2, 3), each = 4)
w
```

```
##  [1] 1 2 3 1 2 3 1 2 3 1 2 3
```

```
z
```

```
##  [1] 1 1 1 1 2 2 2 2 3 3 3 3
```

A3 Compute and print: the remainder of 17 divided by 5. the integer division of 17 by 5, 2 to the power of 10, the square root of 144, and pi rounded to 3 decimals

```r
17 %% 5
```

```
## [1] 2
```

```r
17 %/% 5
```

```
## [1] 3
```

```r
2^10
```

```
## [1] 1024
```

```r
sqrt(144)
```

```
## [1] 12
```

```r
round(pi, 3)
```

```
## [1] 3.142
```

A4 Given a <- c(2, 4, 6, 8) and b <- c(1, 3, 5, 7), print a+b, a*b, the logical comparison a > b, and the dot product sum(a*b)

```r
a <- c(2, 4, 6, 8)
b <- c(1, 3, 5, 7)
a + b
```

```
## [1]  3  7 11 15
```

```r
a * b
```

```
## [1]  2 12 30 56
```

```r
a > b
```

```
## [1] TRUE TRUE TRUE TRUE
```

```r
sum(a * b)
```

```
## [1] 100
```

A5 Use paste() to produce "Student-1" "Student-2" "Student-3". Then identify the datatype of 42, 42L, "42", 41i, and TRUE. What are are its output?

```r
paste("Student", 1:3, sep = "-")
```

```
## [1] "Student-1" "Student-2" "Student-3"
```

```r
class(42)
```

```
## [1] "numeric"
```

```r
class(42L)
```

```
## [1] "integer"
```

```r
class("42")
```

```
## [1] "character"
```

```r
class(41i)
```

```
## [1] "complex"
```

```r
class(TRUE)
```

```
## [1] "logical"
```

```r
sapply(list(42, 42L, "42", 41i, TRUE), class)
```

```
## [1] "numeric"   "integer"   "character" "complex"   "logical"
```

Part B: Data Frames and Conditional Statements

B1 Create a data frame students with 8 rows and these columns (use stringsAsFactors = FALSE; sex is "M" or "F"):

```r
students <- data.frame(
  id         = 1:8,
  name       = c("Alice", "Bruno", "Chen", "Dana", "Elif", "Farid", "Grace", "Hiro"),
  sex        = c("F", "M", "M", "F", "F", "M", "F", "M"),
  section    = c("A", "B", "A", "C", "B", "C", "A", "B"),
  midterm    = c(78, 85, 92, 67, 74, 88, 95, 59),
  final      = c(82, 79, 96, 71, 80, 91, 93, 65),
  attendance = c(95, 88, 100, 72, 90, 85, 98, 60),
  stringsAsFactors = FALSE
)
students
```

```
##   id  name sex section midterm final attendance
## 1  1 Alice   F       A      78    82         95
## 2  2 Bruno   M       B      85    79         88
## 3  3  Chen   M       A      92    96        100
## 4  4  Dana   F       C      67    71         72
## 5  5  Elif   F       B      74    80         90
## 6  6 Farid   M       C      88    91         85
## 7  7 Grace   F       A      95    93         98
## 8  8  Hiro   M       B      59    65         60
```

B2 Display the structure, dimensions, column names, and summary of students

```
str(students)
```

```
## 'data.frame':    8 obs. of  7 variables:
##  $ id        : int  1 2 3 4 5 6 7 8
##  $ name      : chr  "Alice" "Bruno" "Chen" "Dana" ...
##  $ sex       : chr  "F" "M" "M" "F" ...
##  $ section   : chr  "A" "B" "A" "C" ...
##  $ midterm   : num  78 85 92 67 74 88 95 59
##  $ final     : num  82 79 96 71 80 91 93 65
##  $ attendance: num  95 88 100 72 90 85 98 60
```

```
dim(students)
```

```
## [1] 8 7
```

```
names(students)
```

```
## [1] "id"         "name"       "sex"        "section"    "midterm"
## [6] "final"      "attendance"
```

```
summary(students)
```

```
##        id              name               sex             section     
##  Min.   :1.00   Length   :8   Length   :8   Length   :8   Min.   :59.00
##  1st Qu.:2.75   N.unique :8   N.unique :2   N.unique :3   1st Qu.:72.25
##  Median :4.50   N.blank  :0   N.blank  :0   N.blank  :0   Median :81.50
##  Mean   :4.50   Min.nchar:4   Min.nchar:1   Min.nchar:1   Mean   :79.75
##  3rd Qu.:6.25   Max.nchar:5   Max.nchar:1   Max.nchar:1   3rd Qu.:89.00
##  Max.   :8.00                                           Max.   :95.00
##      final         attendance
##  Min.   :65.00   Min.   : 60.00
##  1st Qu.:77.00   1st Qu.: 81.75
##  Median :81.00   Median : 89.00
##  Mean   :82.12   Mean   : 86.00
##  3rd Qu.:91.50   3rd Qu.: 95.75
##  Max.   :96.00   Max.   :100.00
```

B3 Add a column average = the mean of midterm and final for each student, rounded to 1 decimal

```
students$average <- round((students$midterm + students$final) / 2, 1)
students
```

```
##   id  name sex section midterm final attendance average
## 1  1 Alice   F       A      78    82         95    80.0
## 2  2 Bruno   M       B      85    79         88    82.0
## 3  3  Chen   M       A      92    96        100    94.0
## 4  4  Dana   F       C      67    71         72    69.0
## 5  5  Elif   F       B      74    80         90    77.0
## 6  6 Farid   M       C      88    91         85    89.5
## 7  7 Grace   F       A      95    93         98    94.0
## 8  8  Hiro   M       B      59    65         60    62.0
```

B4 Add a logical column passed that is TRUE when average >= 70 and attendance >= 75

```
students$passed <- students$average >= 70 & students$attendance >= 75
students
```

```
##   id  name sex section midterm final attendance average passed
## 1  1 Alice   F       A      78    82         95    80.0   TRUE
## 2  2 Bruno   M       B      85    79         88    82.0   TRUE
## 3  3  Chen   M       A      92    96        100    94.0   TRUE
## 4  4  Dana   F       C      67    71         72    69.0  FALSE
## 5  5  Elif   F       B      74    80         90    77.0   TRUE
## 6  6 Farid   M       C      88    91         85    89.5   TRUE
## 7  7 Grace   F       A      95    93         98    94.0   TRUE
## 8  8  Hiro   M       B      59    65         60    62.0  FALSE
```

B5 Using ifelse(), add a column standing with these values based on average:

"Honors" if average >= 90

"God" if average >= 75 (and below 90)

"Needs Support" otherwise

```
students$standing <- ifelse(students$average >= 90, "Honors",
                     ifelse(students$average >= 75, "Good", "Needs Support"))
students
```

```
##   id  name sex section midterm final attendance average passed      standing
## 1  1 Alice   F       A      78    82         95    80.0   TRUE          Good
## 2  2 Bruno   M       B      85    79         88    82.0   TRUE          Good
```

```
## 3  3  Chen   M       A      92    96        100    94.0   TRUE        Honors
## 4  4  Dana   F       C      67    71         72    69.0  FALSE Needs Support
## 5  5  Elif   F       B      74    80         90    77.0   TRUE          Good
## 6  6 Farid   M       C      88    91         85    89.5   TRUE          Good
## 7  7 Grace   F       A      95    93         98    94.0   TRUE        Honors
## 8  8  Hiro   M       B      59    65         60    62.0  FALSE Needs Support
```

B6 Write a function classify(score) that uses an if / else if / else chain and returns "Distinction" for 85 or above, "Merit" for 70 to 84, "Pass" for 50 to 69, and "Fail" below 50. Test it with sapply(c(90, 73, 55, 40), classify) and print the result.

```r
classify <- function(score) {
  if (score >= 85) {
    "Distinction"
  } else if (score >= 70) {
    "Merit"
  } else if (score >= 50) {
    "Pass"
  } else {
    "Fail"
  }
}

result <- sapply(c(90, 73, 55, 40), classify)
print(result)
```

```
## [1] "Distinction" "Merit"       "Pass"        "Fail"
```

Part C: rbind() and cbind()

C1 Create a data frame new_students with two students. Its columns must match the original, including average, passed and standing, computing the same way:

id 9, Ines, F, section C, midterm 81, final 84, attendance 92

id 10, Jamal, M, section A, midterm 70, final 68, attendance 80

Use rbind() to append them to students, saving the result as students_all

```r
new_students <- data.frame(
  id         = c(9, 10),
  name       = c("Ines", "Jamal"),
  sex        = c("F", "M"),
  section    = c("C", "A"),
  midterm    = c(81, 70),
```

```
  final      = c(84, 68),
  attendance = c(92, 80),
  stringsAsFactors = FALSE
)
new_students$average <- round((new_students$midterm + new_students$final) / 2, 1)
new_students$passed <- new_students$average >= 70 & new_students$attendance >= 75
new_students$standing <- ifelse(new_students$average >= 90, "Honors",
                         ifelse(new_students$average >= 75, "Good", "Needs Support"))

students_all <- rbind(students, new_students)
students_all
```

```
##    id  name sex section midterm final attendance average passed      standing
## 1   1 Alice   F       A      78    82         95    80.0   TRUE          Good
## 2   2 Bruno   M       B      85    79         88    82.0   TRUE          Good
## 3   3  Chen   M       A      92    96        100    94.0   TRUE        Honors
## 4   4  Dana   F       C      67    71         72    69.0  FALSE Needs Support
## 5   5  Elif   F       B      74    80         90    77.0   TRUE          Good
## 6   6 Farid   M       C      88    91         85    89.5   TRUE          Good
## 7   7 Grace   F       A      95    93         98    94.0   TRUE        Honors
## 8   8  Hiro   M       B      59    65         60    62.0  FALSE Needs Support
## 9   9  Ines   F       C      81    84         92    82.5   TRUE          Good
## 10 10 Jamal   M       A      70    68         80    69.0  FALSE Needs Support
```

C2 Create the numeric vector quiz <- c(8, 7, 10, 6, 7, 9, 10, 5, 8, 6). Use cbind() to attach it to students_all as a column named quiz. Confirm the result is still a data frame with class()

```
quiz <- c(8, 7, 10, 6, 7, 9, 10, 5, 8, 6)
students_all <- cbind(students_all, quiz = quiz)
students_all
```

```
##    id  name sex section midterm final attendance average passed      standing
## 1   1 Alice   F       A      78    82         95    80.0   TRUE          Good
## 2   2 Bruno   M       B      85    79         88    82.0   TRUE          Good
## 3   3  Chen   M       A      92    96        100    94.0   TRUE        Honors
## 4   4  Dana   F       C      67    71         72    69.0  FALSE Needs Support
## 5   5  Elif   F       B      74    80         90    77.0   TRUE          Good
## 6   6 Farid   M       C      88    91         85    89.5   TRUE          Good
## 7   7 Grace   F       A      95    93         98    94.0   TRUE        Honors
## 8   8  Hiro   M       B      59    65         60    62.0  FALSE Needs Support
## 9   9  Ines   F       C      81    84         92    82.5   TRUE          Good
## 10 10 Jamal   M       A      70    68         80    69.0  FALSE Needs Support
##    quiz
## 1     8
## 2     7
## 3    10
## 4     6
## 5     7
## 6     9
```

```
## 7    10
## 8     5
## 9     8
## 10    6
```

```
class(students_all)
```

```
## [1] "data.frame"
```

C3 Create the matrix m <- cbind(midterm = students_all$midterm, final = students_all$final) and use rbind() to append a final row containing the column means, leabelled "mean".

```
m <- cbind(midterm = students_all$midterm, final = students_all$final)
m <- rbind(m, mean = colMeans(m))
m
```

```
##      midterm final
##         78.0  82.0
##         85.0  79.0
##         92.0  96.0
##         67.0  71.0
##         74.0  80.0
##         88.0  91.0
##         95.0  93.0
##         59.0  65.0
##         81.0  84.0
##         70.0  68.0
## mean    78.9  80.9
```

C4 In a commnt (2-3 sentences), explain what error rbind()

```
# rbind() on data frames requires the same number of columns with matching
# names. If they differ, R stops with an error such as "numbers of columns of
# arguments do not match" (or "names do not match previous names"). tryCatch()
# lets us catch that error and print a friendly message instead of crashing.
bad <- data.frame(id = 11, name = "Kai")

tryCatch(rbind(students, bad),
         error = function(e) {
           message("rbind failed: ", conditionMessage(e))
           NULL
         })
```

```
## rbind failed: numbers of columns of arguments do not match
```

```
## NULL
```

Part D: Subsetting

D1

```
students_all$name
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```
students_all[["name"]]
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```
students_all[, "name"]
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

D2

```
students_all[2:5, c("name", "midterm", "final")]
```

```
##    name midterm final
## 2 Bruno      85    79
## 3  Chen      92    96
## 4  Dana      67    71
## 5  Elif      74    80
```

D3

```
students_all[students_all$attendance > 90, ]
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 1  1 Alice   F       A      78    82         95    80.0   TRUE     Good    8
## 3  3  Chen   M       A      92    96        100    94.0   TRUE   Honors   10
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 9  9  Ines   F       C      81    84         92    82.5   TRUE     Good    8
```

D4

```
subset(students_all,
       sex == "F" & section %in% c("A", "C") & final >= 75,
       select = c(name, section, final))
```

```
##    name section final
## 1 Alice       A    82
## 7 Grace       A    93
## 9  Ines       C    84
```

D5

```
students_all$name[which.max(students_all$average)]
```

```
## [1] "Chen"
```

```
students_all$name[which.min(students_all$average)]
```

```
## [1] "Hiro"
```

D6

```
sorted <- students_all[order(students_all$average, decreasing = TRUE), ]
head(sorted, 3)
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 3  3  Chen   M       A      92    96        100    94.0   TRUE   Honors   10
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 6  6 Farid   M       C      88    91         85    89.5   TRUE     Good    9
```