

SQUARE 67

Sliding Aluminium System — Full Technical Reference

Complete, reorganised transcription of the ALLUCO product catalogue

Contents

1. Company & Product Range
2. Material — Aluminium Alloy
3. Technical Characteristics & Performance
4. Dimensions & Glazing
5. Profile Range (dimensions, weight, inertia)
6. Accessories (plugs, hardware, handles)
7. Joints, Seals & Glazing Selection
8. Assembly Principles
9. Typical Cross-Section Assemblies
10. Machining Reference Dimensions
11. Cutting Lists / Bill of Materials
12. Wind Load & Deflection
13. Certifications
14. Other ALLUCO Aluminium Systems
15. Contact

ALLUCO — Aluminium Building Systems

BP: 47, Z.I. Moknine, 5050, Tunisia

Tel: Moknine (+216) 73 415 300 | Tunis (+216) 71 757 228

Email: info@alluco.com | www.alluco.com

1. Company & Product Range

ALLUCO provides solutions adapted to all high-end custom-made aluminium joinery projects. The company has an in-house design office working on 3D software, a workshop equipped with CNC machines, and experienced installation teams — ALLUCO designs, manufactures and installs, working directly with architectural projects.

ALLUCO is positioned on the national and international aluminium market with innovative concepts adapted to contemporary architecture, working toward three goals: **(1)** improved energy performance of buildings (energy saving), **(2)** a healthy and comfortable home, and **(3)** a splendid design.

Brand taglines used in the catalogue: "success in progress" and "Engagé pour l'environnement" (Committed to the environment) — tied to ALLUCO's CO2 Neutral certification (see Section 12).

Full ALLUCO product range includes:

- Complete aluminium profile system series: sliding, tilt-turn (oscillo-battant) and swing (ouvrant) openings
- Curtain walling
- Gates/portals (portails)
- Aluminium railings (garde-corps) for balconies and verandas, and aluminium-profile staircases — anodised inox-look or glazed finishes
- Extruded or injected roller-shutter slats for security
- Sun-protection systems: fixed or sliding sun-breakers (brise-soleil), pergolas, screens, camargue systems
- Ventilation grilles for healthy, ventilated spaces
- Thermal-break aluminium systems (rupture de pont thermique), environmentally respectful

2. Material — Aluminium Alloy & Extrusion

Raw material: 6000–6063 series aluminium alloy (Al, Mg, Si 0.5), state T5. Chemical composition conforms to standard ISO 209-1:1989 (F). Mechanical characteristics conform to standard ISO 6362-2.

Mechanical property	Minimum value
Hardness	68 HB
Breaking load	Rm = 200 MPa
Elastic limit	R0.2 = 160 MPa
Elongation	A = 10%

- Theoretical weights per linear metre shown in the catalogue are theoretical; actual weight is $\pm 10\%$.
- Standard bar length: 6.5 m (lacquered profiles).
- Plan an end-cut allowance of up to 10 cm per bar after surface treatment (lacquering) — mainly due to adhesion testing and hanging/handling marks.

3. Technical Characteristics & Performance

3.1 General characteristics

- Frame (dormant) depth: 40 mm
- Leaf (ouvrant) depth: 29 mm
- Reference overall installed section: from 86 mm
- Frame and leaf corners assembled with high-quality framing squares
- High-quality fittings, accessories and gaskets/joints — own manufacturing
- Straight and curved joint-cover (couvre-joint) design options
- Wide range of design options

3.2 Performance ratings

Performance	Rating	Standard
Air Permeability	Class 1	EN 12207
Water Sealing	7A	EN 12208
Wind Resistance	C3	EN 12210
Security (burglar resistance)	CR2	EN 1630

4. Dimensions & Glazing

Parameter	Value
Maximum glass thickness	24 mm
Medium theoretical glazing-bead thickness	1.4 mm
Maximum panel width (L)	2200 mm
Maximum panel height (H)	3200 mm
Maximum weight per leaf	1800 kg *
Acoustic insulation	Rw = 27 dB (EN ISO 140-3 / EN ISO 717-1, areas ≤ 2.27 m ²)

* Always consult the exact weight and maximum dimensions for the specific configuration/reinforcement used.

Standard opening configurations

Configuration	Description
2 Doors	2 sliding panels on a single rail
3 Doors on 3 Rails	3 sliding panels, each running on its own rail
6 Doors on 3 Rails	6 sliding panels across 3 rails (2 panels per rail)

5. Profile Range

Weights are theoretical (kg/ml, $\pm 10\%$ actual). "Perim." is the profile's external perimeter (mm), used for lacquering/surface-treatment calculations. $I(X)/I(Y)$ are moments of inertia (cm^4) where published. "Section (W×H, mm)" gives the overall cross-section envelope as dimensioned on the technical drawings.

5.1 Frames (Dormant)

Ref.	Designation (EN)	Section W×H (mm)	Weight (kg/ml)	$I(X)/I(Y) \text{ cm}^4$	Perim. (mm)
CSQ 101	Two-rail frame, water collector, no joint cover	65 × 37	0.902	3.81 / 12.96	394.3
CSQ 102	Two-rail frame, water collector, straight joint cover	65 × 59	1.001	6.91 / 13.63	454.2
CSQ 103	Two-rail frame, water collector, attached joint cover	65 × 37	0.927	4.08 / 12.95	405.4
CSQ 110	Three-rail frame, water collector, attached joint cover	102 × 37 (77 int.)	1.451	6.11 / 47.47	595.5
CSQ 201	Frame without water collector, no joint cover	49 × 37	0.763	3.46 / 7.74	319.1
CSQ 202	Two-rail frame, no water collector, straight joint cover	49 × 59	0.863	6.40 / 8.97	379.1
CSQ 203	Two-rail frame, no water collector, attached joint cover	49 × 37	0.789	3.71 / 7.81	330.3
CSQ 210	Three-rail frame, no water collector, attached joint cover	85 × 37 (77 int.)	1.294	5.72 / —	512.6
CSQ 537	2-rail sleeper, water collector, attached gasket cover + drip edge	65.45 × 37.4	0.953	— / —	417
CSQ 538	2-rail sleeper, no water collector, attached gasket cover + drip edge	48.5 × 37.4	0.814	— / —	341

5.2 Sash / Mullions (Montants)

Ref.	Designation (EN)	Section W×H (mm)	Weight (kg/ml)	$I(X)/I(Y) \text{ cm}^4$	Perim. (mm)
CSQ 104	Side post — sash (montant latéral ouvrant)	60 × 29 (26 int.)	0.735	3.97 / 7.68	307.3
CSQ 105	Central sash post (montant central ouvrant)	34 × 38 (29/26 int.)	0.564	2.52 / 3.34	211.9
CSQ 106	Central opening post / top & bottom transom	26 × 54	0.638	5.17 / 2.90	338.6
CSQ 107	Reinforced central opening post	67 × 26/29	1.112	7.33 / 22.74	279.2
CSQ 108	Reinforced side opening post	60 × 45/24 (15 tube)	1.021	10.98 / 12.68	356.3
CSQ 450	Minimum central post	33.5 × 29	0.581	1.26 / 3.18	182
CSQ 451	Minimum reinforced central post	83.6 × 29	1.347	5.19 / 39.13	208
CSQ 114	Glazing bead reducer, single glazing	26 × 16	0.140	— / —	89

5.3 Rails, Water Drainage & Mosquito-Screen Profile

Ref.	Designation (EN)	Section W×H (mm)	Weight (kg/ml)	$I(X)/I(Y) \text{ cm}^4$	Perim. (mm)
CSQ 116	Attached rail (rail rapporté)	6 × 13	0.194	— / —	33.6
CSQ 124	Water drain (rejet d'eau)	22 × 35 (11 int.)	0.204	— / —	157.3
CSQ 125	Water drain cover (cache rejet d'eau)	8 × 11	0.080	— / —	53
CSQ 126	Central bead (battement central)	21 × 21 (12 int.)	0.244	0.24 / 0.34	128.8

Ref.	Designation (EN)	Section W×H (mm)	Weight (kg/ml)	I(X)/I(Y) cm ⁴	Perim. (mm)
FSQ 153	Frame assembly adapter	37 × 9.1	0.307	— / —	136
FSQ 534	20 mm flange / flashing (bavette)	28.7 × 7	0.135	— / —	78
CSQ 539	Mosquito-screen frame profile	12 × 30.5	0.319	1.1 / 0.24	162

5.4 Joint Covers (Couvre-Joints)

Ref.	Designation (EN)	Section W×H (mm)	Weight (kg/ml)	I(X)/I(Y) cm ⁴	Perim. (mm)
CSQ 301	35 mm offset straight joint cover	13.6 × 35	0.202	— / —	108
CSQ 302	35 mm straight joint cover	8.6 × 35	0.178	— / —	108
CSQ 303	35 mm rounded joint cover	9 × 25	0.166	— / —	88.8
CSQ 304	45 mm rounded joint cover	13.03 × 45	0.178	— / —	128
CSQ 305	45 mm offset straight joint cover	13.6 × 45	0.240	— / —	128
CSQ 306	45 mm straight joint cover	8.6 × 45	0.216	— / —	118
CSQ 460	60 mm straight joint cover	20 × 60	0.380	— / —	210

6. Accessories

6.1 Plugs & End Caps (Bouchons)

Ref.	Designation
118 40	Alignment bracket (équerre d'alignement)
ACC 67 250	Central sealing (étanchéité central)
ACC 67 251	Stop pad (patin arrêtoire)
ACC 67 252	Central post cap (bouchon montant central)
ACC 67 253	Side post stopper cap (bouchon butée montant latéral)
ACC 67 254	Reinforced side post cap (bouchon montant latéral renforcé)
ACC 67 255	Reinforced central post cap (bouchon montant central renforcé)
ACC 67 256	Water busette for frame (busette d'eau dormant)
ACC 67 257	Central post stopper cap (bouchon butée montant central)
ACC 67 258	Water collector cap (bouchon récupérateur d'eau)
ACC 67 259	Water drain cap (bouchon rejet d'eau)
ACC67K2V	Reinforced-mullion corner assembly kit (multi-part plug set for reinforced central/side posts)

6.2 Hardware, Rollers & Locking

Ref.	Designation
03120000	Adjustable carrera (roller) — max. weight per carrera 90 kg
13622 CO	Frame alignment bracket (équerre d'alignement dormant)
04579000	Recessed / flush closure (fermeture encastrée)
033280000	Strike plate (gâche)
07ma1p250	Single-point lock (serrure 1 pts)
07ma3p660	Two-point lock (serrure 2 pts)
07ma3p1130	Three-point lock (serrure 3 pts)
06004	BRIO straight-line closure (fermeture BRIO ligne droite)
04694000	Strike / spoil hardware (gâche)
Vis 4.8×25 SIP	Cruciform SCRIP TH screw
Vis 3.2×25	Screw for water-discharge plug fixing
JB5×5	Roller-carriage fixing screw (seen on top/bottom rail sections)
04730 (dia. 4mm)	Self-tapping fixing screw, 4 mm (top rail / mosquito-screen fixing)
136 22	Frame-to-wall fixing screw / anchor (used at every perimeter section)
00312	Strike-plate mortise insert (used with CSQ 106 sash traverse)
051 80	Mullion-cap fixing screw (central & lateral mullion caps)
00997	Support wedge / packer block (under reinforced mullions, 3-and-4-panel configs)

6.3 Handles — Supra7 Range

Universal-application handles with a minimalist design, offered in several styles and an extensive range of finishes (white, black, dark grey/anthracite, blue, silver/aluminium and more — "infinite finishes").

Ref.	Style
04153	Supra7 — Asia
04154	Supra7 — Kora
04155	Supra7 — Prima

Ref.	Style
04156	Supra7 — Aria

7. Joints, Seals & Glazing Selection

7.1 Joint / seal references

Ref.	Designation
J5007	3 mm single-glazing seal
J5006	4 mm single-glazing seal
J5005	5 mm single-glazing seal
J5004	6 mm single-glazing seal
J220	2 mm glazing seal
JBR7X6	6 mm brush seal
JBR7X6 fin seal	6 mm fine brush seal
J2055	Central bead (battement) seal
JU6mm	6 mm U-shaped glazing gasket
JU8mm	8 mm U-shaped glazing gasket
JU18mm	18 mm U-shaped glazing gasket

7.2 Glazing-bead / seal selection tables

With glazing bead CSQ 114 — 16.5 mm rebate (parclose droite feuillure 16.5 mm)

Glass thickness (mm)	Outer gasket	Inner gasket
6	J5004	J5005
8	J5005	J5006
10	J5006	J5007

With glazing bead CSQ 106 — 25.6 mm rebate (parclose droite feuillure 25.6 mm)

Glass thickness (mm)	Outer gasket	Inner gasket
18	J5006	J5006
20	J5007	J5007
22	J220	J220

With a 16.5 mm rabbet reducer (CSQ 114 used as reducer)

Glass thickness (mm)	Reducer	U-gasket
6	CSQ 114	JU6mm
8	CSQ 114	JU8mm

With CSQ 106 used as reducer

Glass thickness (mm)	Reducer	U-gasket
18	CSQ 106	JU18mm

8. Assembly Principles

Mitred frame assembly (Assemblage dormant coupe d'onglet)

Frames are mitre-cut at the corners and mounted with a pin bracket (équerre à pion), then mechanically tightened by screwing (e.g. reference CSQ 103 corners).

Water-recovery plug mounting (base transom)

The water-recovery plug (ACC 67 258) is fitted to the bottom transom of the frame (e.g. CSQ 103 / CSQ 203 combination) as part of the mitred frame assembly.

Sash mitre-cut assembly (Assemblage ouvrant coupe d'onglet)

The strike-plate (gâche) is assembled into the mitre-cut sash frame (CSQ 106 with part 00312).

Central mullion assembly for sash

The central mullion (CSQ 105 or CSQ 106, depending on configuration) is assembled with cap ACC 67 257 (fixing screw 051 80).

Lateral mullion assembly for sash

The lateral mullion (CSQ 104, with CSQ 106) is assembled with cap ACC 67 253 (fixing screw 051 80).

Handle & multi-point lock assembly

The espagnolette/multi-point lock and handle are mortised into the lock-side sash upright. Key drilling dimensions from the sash edge: 21.5 mm and 37.5 mm offsets, hole diameters dia. 8 mm (upper/lower fixings) and dia. 10 mm (centre/lock body), with the handle centred at 54 mm from the reference edge and 12.5 mm inset.

Water-discharge plug assembly

The water-discharge plug (ACC 67 259) is fitted to the frame together with the water-drain profile (CSQ 124) and its cover (CSQ 125), onto frame CSQ 203.

9. Typical Cross-Section Assemblies (Coupes)

The catalogue's section drawings (pages 32–46) show, for each junction of the system, exactly which profiles and accessories stack together. Component lists extracted from each drawing:

Section	Components
Sliding window — bottom rail (2-rail frame, CSQ 102)	ACC67 252, CSQ 116, ACC67 257, ACC67 256, ACC67 250, CSQ 106, JV220 (J220), 136 22, 03120000 (roller), ACC67 258, JBR7x6
Sliding window + door — bottom rail (3-rail frame, CSQ 110)	ACC67 252, CSQ 116, ACC67 257, ACC67 256, ACC67 250, CSQ 106, CSQ 114, JV220, 136 22, 03120000, ACC67 258, JBR7x6
Sliding window + door — bottom rail (CSQ 202, no water collector)	ACC67 252, ACC67 250, ACC67 257, CSQ 125, CSQ 106, CSQ 114, JV220, CSQ 124, JBR7x6, 136 22
Sliding window + door — top rail (CSQ 210)	ACC67 252, ACC67 250, ACC67 257, CSQ 125, CSQ 106, CSQ 114, JV220, CSQ 124, JBR7x6
Sliding window + door — side upright (CSQ 104 / CSQ 202)	CSQ 104, CSQ 202, JV220, ACC67 253, JBR7X6, ACC67 258, 136 22, 04579000, 04694000, 06004
Sliding window + door — reinforced lateral upright (CSQ 108)	CSQ 108, ACC67 254, JV220, JBR7x6, CSQ 203, 04694000, ACC67 253, 04579000, 136 22, ACC67 258, 00997
Sliding window + door — reinforced central upright (CSQ 107)	CSQ 107, ACC67 252, J2055, JBR7x6, ACC67 255, ACC67 257, ACC67 250, JV220 (reinforcement types 1–4, see Section 11)
4-panel — central post, same rail (CSQ 108)	CSQ 108, CSQ 126, ACC67 253, ACC67 254, JV220, JBR7x6, 04694000, 00997
Sliding window (no door) — bottom rail, with mosquito screen	ACC67 252, CSQ 116, ACC67 257, ACC67 256, ACC67 250, CSQ 106, CSQ 102, JV220, 136 22, 03120000, ACC67 258, JBR7x6, CSQ 124, CSQ 125, CSQ 539, JB5x5, 04730 (dia. 4mm)
Sliding window (no door) — side upright, with mosquito screen	CSQ 104, CSQ 202, JV220, ACC67 253, JBR7X6, ACC67 258, 136 22, 04579000, 04694000, 06004, CSQ 124, CSQ 125, CSQ 539, JB5x5, 04730 (dia. 4mm)
Sliding window + door — top rail, with bavette (FSQ 537 / CSQ 537)	ACC67 252, ACC67 250, ACC67 257, FSQ 537, CSQ 106, CSQ 114, CSQ 537, JV220, JBR7x6, 136 22
Sliding window + door — side upright, with bavette (FSQ 538)	CSQ 104, FSQ 538, JV220, ACC67 253, JBR7X6, ACC67 258, 04694000, 04579000, 06004, FSQ 537
Sliding window + door — reinforced central upright, minimal (CSQ 450/451)	CSQ 450, CSQ 451, JBR 7x6, JV220

Note: "JV220" in the original drawings refers to the J220 glazing seal.

10. Machining Reference Dimensions (Usage)

The catalogue provides CNC machining templates (frame/traverse machining for the pin square, and central/lateral upright machining) as dimensioned CAD drawings. Key numeric callouts extracted from those drawings are listed below for reference; the original dimensioned drawings (catalogue pages 58–61) remain the authoritative source for production tooling.

9.1 Frame / traverse machining (CSQ 106) — principle

Key dimensions (mm): 16, 23, 10.5, 12, 11, 6, 26.7, 20.6, 5.5, 2.5, 12.5, 17, 8.5, 13.1, 186, 250, 60, 130, 28, 5, 9, 42, 21, 71, 187.

9.2 Central upright machining (CSQ 105 / 107)

Key dimensions (mm): 18, 25, 24.5, 33.5, 38, 6, 130, 43, 187, 250.

9.3 Lateral (side) upright machining (CSQ 104 / 108)

Key dimensions (mm): 24.5, 15, 60, 130, 250, 6.

9.4 Central mullion sash machining (with cap ACC 67 252)

Applies to reinforced central mullion CSQ 107 pairs joined at the cap.

■ *These machining figures were transcribed from scanned dimensioned drawings and grouped by drawing rather than fully mapped point-by-point. Before cutting/CNC programming, cross-check against the original catalogue drawings (pages 58–61) to avoid transcription error.*

11. Cutting Lists / Bill of Materials (Débitage)

The tables below give the profile cutting-length formulas (L = window width, H = window height, all in mm) and quantities for standard SQUARE 67 sliding window configurations, as published in the catalogue (pages 64–69).

■ Some accessory reference/quantity groupings in the source catalogue scan were ambiguous (reference numbers and quantities are printed in separate columns that can shift during OCR). Profile cutting formulas below were cross-checked and are reliable; accessory quantities are reproduced as printed but should be verified against catalogue pages 64–69 before ordering hardware for production.

10.1 2-Panel Sliding Window (2vtx, 2 rails) — standard

Base frame CSQ 103 / CSQ 203 (attached joint cover).

Profiles

Ref.	Designation	Cutting formula	Qty
CSQ 103	Frame, water collector, joint cover	L	1
CSQ 203	Frame, no water collector, joint cover	L / H	1 / 2
CSQ 104	Lateral mullion sash	H – 60	2
CSQ 105	Central mullion sash	H – 60	1
CSQ 106	Top & bottom transom	(L – 156) / 2	4
CSQ 114	Glazing rebate reducer	(L – 156)/2 & H – 170	4 / 4
CSQ 116	Reported rail	L – 75	2
CSQ 124	Water discharge	L	1
CSQ 125	Water discharge cache	L	1
CSQ 302	35 mm straight joint cover	L+62 / H+62	2 / 2

Accessories

Ref.	Designation	Qty
13622CO	Frame assembly square	4
ACC67K2V	Kit for 2-leaf window	1 kit
Vis 4.8×25 SIP	Cruciform screw	8
Vis 3.2×25	Water-discharge screw	3
06004	BRIO straight-line closure	2
04694000	Strike (gâche)	2
04579000	Crochet / hook	2
0312000	Double adjustable roller	4

Joints

Ref.	Designation	Length formula
J220	Glazing seal	4L + 8H m
J2055	Central-bead seal	2H m
JBR7X6 FS	6 mm fine brush seal	4L + 6H m

Glazing (glass cutting size)

Type	Width formula	Height formula	Qty
With reducer	(L – 183)/2	H – 152	2
Without reducer	(L – 175)/2	H – 148	2

10.2 3-Panel Sliding Window (3vtx, 2 rails)

Profiles

Ref.	Designation	Cutting formula	Qty
CSQ 103	Frame, water collector, joint cover	L	1
CSQ 203	Frame, no water collector, joint cover	L / H	1 / 2
CSQ 104	Lateral mullion sash	H – 60	2
CSQ 105	Central mullion sash	H – 60	2
CSQ 106	Top & bottom transom	(L – 156) / 2	6
CSQ 114	Glazing rebate reducer	(L – 156)/2 & H – 170	4 / 6
CSQ 116	Reported rail	L – 75	2
CSQ 124	Water discharge	L	1
CSQ 125	Water discharge cache	L	1
CSQ 302	35 mm straight joint cover	L+62 / H+62	2 / 2

Accessories

Ref.	Designation	Qty
13622CO	Frame assembly square	4
ACC67K2V	Kit for 2-leaf window	1 kit
Vis 4.8×25 SIP	Cruciform screw	12
Vis 3.2×25	Water-discharge screw	3
06004	BRIO straight-line closure	2
04694000	Strike (gâche)	2
04579000	Crochet / hook (ACC 67 252, central post cap)	2
—	Central waterproof seal	2
ACC 67 252	Central upright cap	2
—	Central upright stopper	2
0312000	Double adjustable roller	6

Joints

Ref.	Designation	Length formula
J220	Glazing seal	4L + 12H m
J2055	Central-bead seal	4H m
JBR7X6 FS	6 mm fine brush seal	4L + 8H m

Glazing (glass cutting size)

Type	Width formula	Height formula	Qty
With reducer	(L – 203)/2	H – 152	3
Without reducer	(L – 191)/2	H – 148	3

10.3 3-Panel Sliding Window (3vtx, 3 rails)

Reinforced frame CSQ 110 / CSQ 210 (3-rail, attached joint cover).

Profiles

Ref.	Designation	Cutting formula	Qty
CSQ 110	3-rail frame, water collector, joint cover	L	1
CSQ 210	3-rail frame, no water collector, joint cover	L / H	1 / 2
CSQ 108	Reinforced lateral mullion sash	H – 60	2
CSQ 107	Reinforced central mullion sash	H – 60	2
CSQ 106	Top & bottom transom	(L – 161) / 3	6
CSQ 114	Glazing rebate reducer	(L – 161)/3 & H – 170	4 / 6
CSQ 116	Reported rail	L – 75	2
CSQ 302	35 mm straight joint cover	L+62 / H+62	3 / 2

Accessories

Ref.	Designation	Qty
13622CO	Frame assembly square	8
00997	Support wedge / block	1 kit
Vis 4.8×25 SIP	Cruciform screw	12
04694000	Strike (gâche)	2
04579000	Crochet / hook	2
—	Central waterproof seal	2
ACC 67 252	Central upright cap	2
ACC 67 254	Reinforced side upright cap	2
ACC 67 255	Reinforced central upright cap	4
—	Central upright stopper	2
0312000	Double adjustable roller	6

Joints

Ref.	Designation	Length formula
J220	Glazing seal	4L + 12H m
J2055	Central-bead seal	4H m
JBR7X6 FS	6 mm fine brush seal	4L + 8H m

Glazing (glass cutting size)

Type	Width formula	Height formula	Qty
With reducer	(L – 203)/3 *	H – 152	3
Without reducer	(L – 191)/2 *	H – 148	3

* Printed exactly as shown in the source catalogue — the divisor differs between the two rows; verify against the original drawing before cutting glass.

10.4 4-Panel Sliding Window (4vtx, 2 rails)

Base frame CSQ 103 / CSQ 203 (attached joint cover), central mullions meet on the same rail.

Profiles

Ref.	Designation	Cutting formula	Qty
CSQ 103	Frame, water collector, joint cover	L	1
CSQ 203	Frame, no water collector, joint cover	L / H	2 / 1
CSQ 104	Lateral mullion sash	H – 60	4

Ref.	Designation	Cutting formula	Qty
CSQ 105	Central mullion sash	$H - 60$	8
CSQ 106	Top & bottom transom	$(L - 254) / 4$	4
CSQ 114	Glazing rebate reducer	$(L - 254)/4$ & $H - 170$	8 / 8
CSQ 116	Reported rail	$L - 75$	2
CSQ 302	35 mm straight joint cover	$L+62$ / $H+62$	2 / 2

Accessories

Ref.	Designation	Qty
13622CO	Frame assembly square	4
00997	Support wedge / block	3
Vis 4.8x25 SIP	Cruciform screw	16
04694000	Strike (gâche)	2
04579000	Crochet / hook	2
—	Central waterproof seal	2
ACC 67 252	Central upright cap	2
—	Side upright stopper	2
—	Central upright stopper	2

Joints

Ref.	Designation	Length formula
J220	Glazing seal	$4L + 16H$ m
J2055	Central-bead seal	$4H$ m
JBR7X6 FS	6 mm fine brush seal	$4L + 10H$ m

Glazing (glass cutting size)

Type	Width formula	Height formula	Qty
With reducer	$(L - 311)/4$	$H - 152$	4
Without reducer	$(L - 295)/4$	$H - 148$	4

Two further catalogue variants of the 2-panel window follow the same base list with substitutions: **with mosquito screen** (adds profile CSQ 539 mosquito frame + compression seal at dia. 5 mm, formula $((L-64)/2)+19$ for width and $H-65$ for height); and **with bavette/flashings** (frame CSQ 537/CSQ 538 replaces CSQ 103/CSQ 203, with 20 mm flap FSQ 534 cut to $L-4$ / $H-8$, and flush closure ACC 67 XXX + double adjustable roller in place of the BRIO closure).

12. Wind Load & Deflection

Design wind pressure: **600 Pascal** ($\approx 61 \text{ kg/m}^2$, $\approx 113 \text{ km/h}$). Maximum allowable deflection (arrow): **span / 300** (Fleche max 1/300). Two deflection curves are published, one per central-mullion reinforcement inertia:

Reinforcement (Jx)	Approx. usable span at chart's flat portion (B, cm)	Approx. max height (H, cm) at that span
Jx = 22.7 cm ⁴	$\approx 190 - 250$	≈ 230
Jx = 33 cm ⁴	$\approx 140 - 250$	≈ 150

Readings are approximate values taken from the published H(cm) vs B(cm) deflection charts (catalogue pages 70–71); consult the original charts for exact intermediate values. For window heights above 1800 mm, more hinges/locking points are recommended.

Central-mullion reinforcement types (Ix)

Type	Moment of inertia (cm ⁴)
1	6.68
2	26.07
3	26.07
4	45.46

13. Certifications

- CO2 Neutral — ALLUCO reduces local/global CO2 impact and offsets residual emissions.
- Profiles certified by the Italian laboratory Istituto Giordano ("certified by" mark, Beyond Certification).
- Company quality management system certified ISO 9001:2015, confirmed by Bureau Veritas.

14. Other ALLUCO Aluminium Systems

SQUARE 67 is part of ALLUCO's broader aluminium building systems range, which also includes:

- ALTO 15400 — swing/opening window system
- Oikos 4700 — swing/opening window system
- Supra 6000 — swing/opening window system
- Prima 6300 — swing/opening window system
- Klima 7400 & Klima PLUS — thermal-break window systems
- Entrance Doors MG90 — insulated entrance door system
- JEALOUSY — louvre / jalousie system
- Square 40 — sliding system (40 mm)
- Rolling Shutter systems
- Shadow Systems — sun-shading
- Curtain Wall systems
- UNION LINE — railings/balustrades
- ULTIMATE SKY — glass railings
- PURE LINE — glass railing/partition profiles
- Pergola AZORE

15. Contact

Address	BP: 47, Z.I. Moknine, 5050, Tunisia
Tel.	Moknine (+216) 73 415 300 Tunis (+216) 71 757 228
Fax	(+216) 73 416 317
Email	info@alluco.com
Website	www.alluco.com
Social	@Allucoworldwide