

# Proxy and Interceptor Patterns



**DEVELOPMENTOR**

DEVELOPING PEOPLE WHO DEVELOP SOFTWARE




- Single threaded type now needs to live in a multi threaded environment
  - Control access so only one caller at a time
  - Or marshal all calls to a given thread
- The same invocation is made by lots of callers, producing the same response, this is hurting performance
  - Cache request/response pairs
- Object is actually remote
  - Need to convert the invocation into a serialized message ready for network transportation
- Object has methods only certain users can invoke
  - Need to check security policy prior to invoking

In essence we want to control access



- Controlling access
  - Prior to the object functionality being invoked we wish to perform some additional steps
  - We don't want to modify the existing code
    - "Closed for modification open for extension"
- To achieve this create a type that
  - Is compatible with the one we wish to control access too.
    - Create a common base type
  - Have this type wrap up the object being protected
  - Have the client work with an instance of this type, but in terms of the common base type


# Proxy Pattern





- Common use of proxy pattern is for invocations that cross app domain boundaries
  - RPC aka RMI
  - Web Services
- WCF utilises this pattern to produce client side proxies
  - Remote object only created on first call
  - Client continues to use in app domain programming model
    - Aspects of the implementation do leak


# Proxies for Remote Invocation






- In multi user applications the same request can be made many times
  - Get the Stock price for CSCO
  - What's on Channel X now
  - What's the IP address of `www.google.com`
- It would therefore seem sensible for expensive operations to be cached
- Solution
  - Create a Caching proxy
  - The Proxy records requests and replays responses
    - If reoccurring request, return the cached result
    - Otherwise invoke the real subject, and cache the result


# Non-Caching Data Service







# Caching in action





- Thread safety when not required increases overhead
- Types are often written not to be thread safe
- Synchronization proxies allow the addition of synchronization code at runtime when it is required
- Object can only be accessed by one thread at a time
  - Proxy method wraps each with a synchronization primitive similar to Java's synchronized keyword
- Object can only be accessed on a given thread
  - Proxy method provides a means of marshalling the call on to the appropriate thread. Typically done via `ThreadSynchronizationContext`



```
class SynchronizedAccount : Account {  
    private Account account;  
    private object sync = new object();  
  
    public SynchronizedAccount(Account account){  
        this.account = account;  
    }  
  
    public override void Credit(decimal amount){  
        lock (sync) {  
            account.Credit(amount);  
        }  
    }  
}
```



- In the code below assume
  - queue is a Synchronized Wrapped version
  - You can't de-queue an empty queue
  - Multiple threads are using this method
- Are there any problems with this code ?

```
void ProcessQueue(IQueue queue)
{
    if ( queue.Empty() == false )
    {
        object item = queue.Dequeue();
    }
}
```




- Security always comes last ;-)
  - Not a problem if you implement with a proxy
- Separate logic and security
  - Allows both to evolve independently
  - Security rules can be clearly seen and understood
- Security Proxies can
  - Validate that the method can be invoked by the user
  - Provide Audit trail of method invocation
    - Who did what and when



- Building some proxy types can be tedious
  - RMI
  - Security
  - Synchronization
- Managed runtimes offer the ability to build a proxy at runtime
  - Write once and can be used for a range of types
- Dynamic Proxy has two parts
  - Transparent Proxy(TP)
    - Client makes method calls against TP
  - Real Proxy, Implementation of the proxy
    - Derives from RealProxy
    - Creates the TP
    - Handles method calls to TP through a single invoke method




- Not all types can have a Transparent Proxy
  - Type must derive from MarshalByRefObject (MBRO )
  - Type then has JIT compiling inlining disabled for type





# Dynamic Proxy in action





```
class Subject : MarshalByRefObject {}

class MyProxy : RealProxy {
    private Subject subject;

    MyProxy(Subject subject) : base(typeof(Subject) ){
        this.subject = subject;
    }

    // All calls against TP routed to here
    public override IMessage Invoke(IMessage msg) { }
}

...
MyProxy proxy = new MyProxy(subject);

Subject subject = (Subject)proxy.GetTransparentProxy();
```



```
class SubjectAuditProxy : RealProxy {
    private Subject realInstance;

    public SubjectAuditProxy(Subject instance) :
        base(typeof(Subject)) {
        realInstance = instance;
    }

    // One method call for every method on the subject
    public override IMessage Invoke(IMessage msg) {
        IMethodCallMessage methodCall = (IMethodCallMessage)msg;

        Console.WriteLine("{0} on object {2} has invoked {1}",
            Thread.CurrentPrincipal.Identity.Name,
            methodCall.MethodName ,
            realInstance );

        // Invoke the message against the realInstance
        return RemotingServices.ExecuteMessage(realInstance,
            (IMethodCallMessage) msg);
    }
}
```

# Single xxxProxy for all types



```
class AuditProxy<T> : RealProxy where T:MarshalByRefObject {
    private T realInstance;

    public AuditProxy(T instance) : base(typeof(T))
    {
        realInstance = instance;
    }

    public override IMessage Invoke(IMessage msg) {
        IMethodCallMessage methodCall = (IMethodCallMessage)msg;

        // Pre call code

        IMessage returnMsg = RemotingServices.ExecuteMessage(realInstance,
                                                                (IMethodCallMessage) msg);

        // Post call code

        return returnMsg;
    }
}
```



- CLR based proxies limited use due to dependency on MBRO
- Prefer to use runtime code generation
  - NuGet “Castle Windsor Core, Dynamic Proxy”
- Framework dynamically builds proxy for a given interface
- Interceptors implement standard interface
  - Allows building general purpose interceptors
- Generated proxy keeps list of interceptors
- Calls to proxy, results in proxy calling first interceptor
  - Interceptors can
    - Modify call parameters before proceeding
    - Modify return parameters
    - Decide if to call other interceptors



- **Interceptor** implements **Intercept** method
  - **IInvocation** object contains call information
  - Calling **Proceed** will result in next interceptor being called or final target

```
public class AuditInterceptor : IInterceptor {
    public void Intercept(IInvocation invocation)
    {
        Console.WriteLine("{0}({1})", invocation.Method.Name,
                           String.Join(",", invocation.Arguments));

        invocation.Proceed();


        if (invocation.ReturnValue != null){
            Console.WriteLine("Returns {0}" , invocation.ReturnValue);
        }
    }
}
```



- **Proxy Generator** used to create general purpose proxy
  - Set of interceptors supplied
- Calls to proxy will result in calling the supplied interceptor **auditInterceptor**

```
IBankAccount account = new Account();  
AuditInterceptor auditInterceptor = new AuditInterceptor();  
  
var proxyGenerator = new ProxyGenerator();  
  
IBankAccount accountProxy = proxyGenerator  
    .CreateInterfaceProxyWithTarget<IBankAccount>(  
        account, auditInterceptor);  
accountProxy.Credit(100);  
  
Console.WriteLine(accountProxy.Balance);
```

# Castle Windsor Interceptor in action






# Caching Interceptor



- Caching interceptor decides if to call final target if no cache value for current method/arguments





- If you need to control access to methods consider the Proxy Pattern
- For general purpose proxies consider a Dynamic Proxy
- Proxy Pattern is similar to decorator in structure but differs in intent
  - Proxy controls access
  - Decorator adds behaviour
- Dynamic proxies + Interceptors allow the building of general purpose proxies