

Creation Patterns



DEVELOPMENTOR
DEVELOPING PEOPLE WHO DEVELOP SOFTWARE



- Replace the use of new for more loosely coupled alternatives
 - Factory patterns
 - Builder
 - Prototype



- Use of **new** keyword implies tight coupling
- What if
 - You want to test a component that needs to create another component
 - The choice of which type to create is complex
 - The type you need to create hasn't been written yet
 - Extension points, Plugins

```
public void MakeAnimalNoise(string type) {  
    Animal animal = null;  
  
    switch (type.ToLower()) {  
        case "dog": animal = new Dog(); break;  
        case "chicken": animal = new Chicken(); break;  
        case "cow": animal = new Cow(); break;  
        case "sheep": animal = new Sheep(); break;  
    }  
    animal.Speak();  
}
```



- Is this the factory pattern ?

```
public void MakeAnimalNoise(string type) {  
    Animal animal = AnimalCreator.Create(type);  
  
    animal.Speak();  
}
```

```
public static class AnimalCreator {  
    public static Animal Create(string type) {  
        Animal animal = null; ;  
        switch (type.ToLower()) {  
            case "dog": animal = new Dog(); break;  
            case "chicken": animal = new Chicken(); break;  
            case "cow": animal = new Cow(); break;  
            case "sheep": animal = new Sheep(); break;  
        }  
        return animal;  
    }  
}
```




- Simplified the caller, encapsulated creation logic but still
 - Tightly coupled to the AnimalCreator class
 - Hard to test
- Sometimes known as “Creation Method” pattern
- To produce a true factory pattern solution
 - The creation logic needs to be able to vary

Factory Method Pattern



- “Encapsulate what varies and separate from code that’s constant”
- Creation abstraction is constant
 - Create(string type)
- Implementation varies
 - Create real Animals or perhaps fake ones for testing





- Method is now **loosely coupled** from implementation of animal creation logic
- Animal creation logic can now therefore vary

```
public static void MakeAnimalNoise(string type,  
                                   AnimalFactory factory)  
{  
    Animal animal = factory.Create(type);  
  
    animal.Speak();  
}
```

Implementing the factory



- **Abstract** class provides abstraction for creation
- **Derived** classes provide implementation of creation logic

```
public abstract class AnimalFactory{
    public abstract Animal Create(string type);
}

public class FarmAnimalFactory : AnimalFactory{
    public override Animal Create(string type) {
        Animal animal = null;

        switch (type.ToLower()){
            case "dog": animal = new Dog(); break;
            case "chicken": animal = new Chicken(); break;
            case "cow": animal = new Cow(); break;
            case "sheep": animal = new Sheep(); break;
        }
        return animal;
    }
}
```




- Base factory class provides **base implementation** providing common point of interception
- **Delegates** to derived class for specific creation logic
- Can layer in caching, singleton behaviour, lazy creation


```
public abstract class AnimalFactory{
    public virtual Animal Create(string type) {
        // Do something before creation
        Animal animal = InternalCreate(type);
        // Do something after creation
        return animal;
    }

    protected abstract Animal InternalCreate(string type);
}
}
```

Factory Method Pattern



- Define an interface for creating an object, but let subclasses decide which class to instantiate.
- Factory Method lets a class defer instantiation to subclasses





- Replacing New offers flexibility
- Utilise **reflection** to create types unknown at compile time

```
public class AnimalAttribute : Attribute {  
    public string Type {get;set;}  
}
```

```
[AnimalAttribute(Type="cow")]  
public class Cow:Animal {  
}
```

```
public class ReflectionAnimalFactory : AnimalFactory {  
    private readonly Dictionary<string, Type> animals;  
    public ReflectionAnimalFactory(){  
        animals =  
        (from type in this.GetType().Assembly.GetTypes()  
         let animalAttrs = type  
             .GetCustomAttributes(typeof(AnimalAttribute), false)  
             .OfType<AnimalAttribute>()  
         where animalAttrs.Count() > 0  
         select new { Type = type, Kind = animalAttrs.First().Type }  
        ).ToDictionary(e => e.Kind, e => e.Type);  
    }  
    public override Animal Create(string type){  
        return (Animal) Activator.CreateInstance(animals[type.ToLower()]);  
    }  
}
```




- Suppose we want to create a number of related objects
 - Database connection, command, parameter, permission
 - Would want a single factory to create all products
 - One 'create' method would not be enough
- Factory type contains **many** create methods
- Objects from same factory are **compatible**

```
public abstract class DbProviderFactory {  
    public virtual DbCommand CreateCommand();  
    public virtual DbConnection CreateConnection();  
    . . .  
}
```


```
DbProviderFactory factory = DbProviderFactories  
                            .GetFactory("System.Data.SqlClient");  
DbConnection connection = factory.CreateConnection();  
DbCommand cmd = factory.CreateCommand();  
cmd.Connection = connection;
```

ADO.NET Abstract Factories






- Often as the number of concrete objects increases the number of factories increases too
 - As we add new document types we may need to add additional factories
 - XPSDocument, XPSDocumentFactory
- What if the concrete objects had knowledge of cloning themselves, we could do away with factories



Prototype pattern




- Objects know how to clone themselves
- Application creates prototype object
 - Configures object for initial settings
- Client utilises New method rather than relying on a factory



Prototype pattern (cont)



- Prototype objects can sometimes be used instead of creating additional classes
- Creates the illusion of new types at runtime
 - Instantiate from prototype rather than by class





- Factories are great at single step construction
- What if constructing complex object that requires many parts
 - Factory methods start to grow
 - Providing every permutation not practical

```
public abstract class Mail {  
    public abstract void Send();  
}  
  
public abstract class MailFactory {  
    public abstract Mail Create(string from, string to, string subject,  
                                string body);  
    public abstract Mail Create(string from, string to, string subject,  
                                string body, string[] attachments);  
    public abstract Mail Create(string from , string to , string cc,  
                                string subject , string body )  
    . . .  
}
```



- Builders allow the construction of a complex object over a series of steps
 - Builder hides the complexity of the construction
 - Complex object representation is independent of method of construction
- **Construction** methods typically return self to allow natural method chaining
- **Build** method returns complex object

```
public abstract class MailBuilder {  
    public abstract MailBuilder SetFrom(string name);  
    public abstract MailBuilder SetBody(string body);  
    public abstract MailBuilder SetSubject(string subject);  
    public abstract MailBuilder AddTo(string name);  
    public abstract MailBuilder AddCC(string name);  
    public abstract MailBuilder AddAttachment(string filename);  
  
    public abstract Mail Build();  
}
```



- Client
 - creates **new builder** for each construction
 - Calls **construction** methods
 - When construction complete, calls **Build** to return complex object

```
MailBuilder builder = new SmtplibMailBuilder();
```

```
builder
```

```
.SetFrom("aclymer@develop.com")  
.SetSubject("Patterns are cool")  
.SetBody("...")  
.AddTo("rich@develop.com")  
.AddCC("kev@develop.com")  
.AddAttachment("uml.png")  
.Build()  
.Send();
```



- StringBuilder
- SqlConnectionStringBuilder
- UriBuilder
 - Define Scheme, Host, Port, Path, Query variables and it builds Uri

```
var connectionStringBuilder = new SqlConnectionStringBuilder()
{
    DataSource = @".\SQL2008",
    InitialCatalog = "pubs",
    IntegratedSecurity = true
};

Console.WriteLine(connectionStringBuilder.ConnectionString);
```



- Replacing the direct use of new creates flexible designs
- Creation Method
 - Commonly used to encapsulate creation logic, often wrongly thought of as factory pattern
- Factory Method
 - Replaces the new keyword with a virtual method for creation, allowing creation logic to vary
- Abstract Factory
 - Creates families of related products
- Prototype
 - Used to prevent factory and product type explosion
- Builder
 - Used instead of factories for complex object creation
 - Separates complex object representation from construction