

Homework #1 Running Times

1. Show that $\Theta(\log n)$ is a reasonable notation by showing that for every base $b > 1$,

$$\log_b n = \Theta(\log_2 n).$$

2. Show that $\sum_{i=1}^n i^{15} = \Theta(n^{16})$.
3. Show that $n! = \mathcal{O}(n^n)$ but that $n^n \neq \Theta(n!)$.
4. Show that the Fibonacci numbers grow exponentially.
5. Plot the following 3 types of functions on the following 2 types of plots:
- (a) An exponential function (like 2^n)
 - (b) A polynomial function (like $10n^2$)
 - (c) A bounded function (like $10 + \sin n$)
- (a) a semi-log plot (X=linear scale, Y=logarithmic scale)
- (b) a log-log plot (X=logarithmic scale, Y=logarithmic scale)

Which types of functions give STRAIGHT LINES in which types of PLOTS?

6. Plot the following empirical data values:

Input Size (first row)				Execution Time (second row)								
12	13	14	15	16	17	18	19	20	21	22	23	24
0.028	0.055	0.109	0.165	0.330	0.660	1.32	2.58	5.05	10.2	20.3	40.7	81.4

What is the best kind of graph to use for this data set and why?

What would you guess the complexity of this function is and why? (for instance: linear, polynomial, exponential, etc.)

7. What is the following algorithm computing?
Choose an inductive variable and state an inductive hypothesis you would use to prove that this algorithm does the job you claim it does.

```
WHILE B > 0
    Subtract 1 from B
    Add      1 to   A
ENDWHILE
```

8. Use the data in the following table to decide if the run time has the form $\Theta(2^n)$. Use this data to predict the run time for $n = 30$.

n	Time (ms)	$T(n)/T(n-1)$
5	10	
6	30	3
7	230	7.7
8	250	1.1
9	1287	5.1
10	1810	1.4
11	4270	2.4
12	10471	2.5
13	19398	1.9
14	39447	2.0
15	77669	2.0
16	147832	1.9
17	301652	2.0

Run Times for Prog-A and Prog-B as functions of n			
n	Prog-A Time (ms)	n	Prog-B Time (ms)
2	0	2	0
4	0	4	0
8	0	8	0
16	0	16	0
32	0	32	15
64	0	64	31
128	15	128	78
256	31	256	218
512	140	512	625
1024	500	1024	1875
2048	2000	2048	5578
4096	8000	4096	16812
8192	32000	8192	50438
16384	128094	16384	151578
32768	512376	32768	454734

9. Use the data in the above table for Prog-A and Prog-B. Plot this data and decide if the run times can be reasonably be written in the form $\Theta(n^k)$. Use you plot to estimate a k_A for Prog-A and a k_B for Prog-B. Which program do you expect to be asymptotically faster?

Important note from the grader: Besides getting the “right answers”, you will want to make sure your work is *neat* and *clear*. When doing graphs, for example, this means:

- labeling your graph with a title or description,
- labeling and numbering your axes, and
- choosing appropriate aspect ratios.