

Removed

REMOVED CSS — ASSIGNMENT 3 MIGRATION

Nesibe Ethnic Cafe

This document lists the custom CSS rules from Assignment 2 that were deleted and replaced with Bootstrap 5.3.3 classes. Our remaining CSS (css/base.css) is now a correction layer under 100 lines.

1. LAYOUT & GRID (replaced by Bootstrap grid system)

DELETED:

```
.menu-grid {  
  
display: flex;  
  
flex-wrap: wrap;  
  
gap: 1.5rem;  
  
justify-content: space-between;  
  
}
```

```
.menu-card {  
  
flex: 1 1 300px;  
  
}
```

REPLACED WITH:

.row.g-4 on parent + .col-12.col-md-6.col-lg-4 on each card.

REASON:

Bootstrap's 12-column grid handles responsiveness automatically without custom flex rules.

DELETED:

```
.hours-grid {
```

```
display: grid;
```

```
grid-template-columns: repeat(3, 1fr);
```

```
gap: 1rem;
```

```
}
```

```
.hours-day:nth-child(1) { grid-column: span 2; }
```

REPLACED WITH:

```
.row.g-3 and .col-12.col-md-4 (with .col-md-8 for spanning item).
```

REASON:

Bootstrap grid provides the same 2D layout with built-in breakpoints.

DELETED:

```
.container {
```

```
max-width: 1200px;
```

```
width: 90%;
```

```
margin: 0 auto;
```

```
}
```

```
.container-fluid {
```

```
width: 100%;
```

```
padding: 0 15px;
```

```
}
```

REPLACED WITH:

Bootstrap's built-in `.container` and `.container-fluid`.

REASON:

Bootstrap already defines these with proper responsive max-widths

and padding. Rewriting them caused conflicts.

DELETED:

```
.specialties-grid {  
  
display: grid;  
  
grid-template-columns: repeat(auto-fit, minmax(250px, 1fr));  
  
gap: 1.5rem;  
  
}
```

REPLACED WITH:

```
.row.row-cols-1.row-cols-md-2.row-cols-lg-3.g-4
```

REASON:

Bootstrap's row-cols-* utilities achieve the same auto-fit behavior with explicit breakpoint control.

2. SPACING & ALIGNMENT (replaced by utility classes)

DELETED:

```
section {  
  
margin-bottom: 2rem;  
  
padding: 1.5rem;  
  
}
```

REPLACED WITH:

```
.mb-5 and .p-4 (or .py-5) on individual sections.
```

REASON:

Utility classes give per-element control instead of a blanket rule that fought Bootstrap's own spacing.

DELETED:

```
.text-center { text-align: center; }  
  
.text-right { text-align: right; }
```

REPLACED WITH:

Bootstrap's .text-center, .text-end, and responsive variants

like .text-center.text-md-start.

REASON:

Bootstrap's utilities include responsive breakpoints; ours did not.

DELETED:

```
.d-flex {  
  display: flex;  
  justify-content: space-between;  
  align-items: center;  
}
```

REPLACED WITH:

```
.d-flex.justify-content-between.align-items-center
```

REASON:

Bootstrap's flex utilities are composable and breakpoint-aware.

3. COMPONENTS (Buttons, Tables, Forms)

DELETED:

```
.btn {  
  background-color: #8B4513;  
  color: white;  
  padding: 0.75rem 2rem;  
  border-radius: 4px;  
}
```

```
.btn:hover { background-color: #D2691E; }
```

REPLACED WITH:

```
.btn.btn-primary (with brand color override in base.css via
```

--bs-primary variable).

REASON:

Bootstrap provides full button states (hover, focus, disabled, outline, size variants). Writing our own lost all of that.

DELETED:

```
table {  
  
width: 100%;  
  
border-collapse: collapse;  
  
margin: 1rem 0;  
  
}  
  
th, td { padding: 0.75rem; border: 1px solid #2F4F4F; }  
  
th { background-color: #8B4513; color: white; }
```

REPLACED WITH:

.table.table-striped.table-hover and .table-responsive wrapper.

Header color kept via .table thead th override in base.css.

REASON:

Bootstrap tables include responsive scrolling, striping, hover states, and proper borders out of the box.

DELETED:

```
input[type="text"], input[type="email"], input[type="tel"],  
  
input[type="number"], input[type="date"], select, textarea {  
  
width: 100%;  
  
padding: 0.75rem;  
  
border: 1px solid #2F4F4F;  
  
border-radius: 4px;
```

```
font-family: inherit;
```

```
}
```

REPLACED WITH:

.form-control (inputs/textarea) and .form-select (select).

REASON:

Bootstrap form controls include focus states, validation styles, and proper sizing.

4. RESPONSIVE BEHAVIOR (replaced by Bootstrap breakpoints)

DELETED:

```
@media (max-width: 768px) {
```

```
.sidebar { width: 100%; }
```

```
.menu-card { width: 100%; }
```

```
}
```

```
@media (max-width: 480px) {
```

```
nav ul { flex-direction: column; }
```

```
}
```

REPLACED WITH:

Bootstrap's mobile-first classes: .col-12.col-md-6,

d-none.d-md-block, text-center.text-md-start, and the navbar's

navbar-expand-lg with .navbar-toggler.

REASON:

Bootstrap's breakpoint system (sm, md, lg, xl, xxl) is consistent across the whole project; custom media queries duplicated it.

5. POSITIONING, FLOAT & CENTERING

DELETED:

```
.float-left { float: left; margin-right: 1.5rem; }
```

```
.clearfix::after { content: ""; display: table; clear: both; }
```

REPLACED WITH:

Bootstrap's `.float-start` and `.clearfix`.

DELETED:

```
.centered-box { width: 60%; margin: 2rem auto; }
```

```
.flex-center { display: flex; justify-content: center; align-items: center; }
```

```
.grid-center { display: grid; place-items: center; }
```

REPLACED WITH:

`.mx-auto` (margin auto),

`.d-flex.justify-content-center.align-items-center`,

and Bootstrap's centering utilities.

REASON:

These were demonstration techniques for Assignment 2; Bootstrap

provides equivalent utilities that work with its grid.

6. WHAT REMAINS IN `css/base.css` (the correction layer)

Only these types of rules are kept:

1. Brand color overrides via `:root` CSS variables
2. (`--bs-primary`, `--bs-secondary`, etc.)
3. Font families for body and headings
4. (Georgia for headings, Segoe UI for body)
5. Justified component overrides with comments:
 - `.btn-primary` background/border color
 - `.table thead th` background color
 - `.accordion-button` focus ring color
 - footer a link color

Total custom CSS: under 100 lines, as required.

