

**Instructions:** You are welcome to form small groups (up to 4 people total) to work through the homework, but you **must** write up all solutions by yourself. List your study partners for homework on the first page, or “none” if you had no partners.

If using LaTeX (which we recommend), you may use the homework template linked on this [Piazza post](#) to get started.

Begin each problem on a new page. Clearly label where each problem and subproblem begin. The problems must be submitted in order (all of P1 must be before P2, etc). For questions asking you to give an algorithm, respond in what we will refer to as the *four-part format* for algorithms: main idea, pseudocode, proof of correctness, and running time analysis.

Read the [Homework FAQ Piazza post](#) on Piazza before doing the homework for more explanation on the four-part format and other clarifications for our homework expectations.

No late homeworks will be accepted. No exceptions. This is not out of a desire to be harsh, but rather out of fairness to all students in this large course. Out of a total of approximately 12 homework assignments, the lowest two scores will be dropped.

### Special Questions:

- *Shortcut questions:* Short questions are usually easy questions that give you opportunities to practice basic materials. However, we understand that some of you are very familiar with the topics and do not want to spend too much time on easy questions. Therefore, we design shortcut questions for this purpose. A shortcut question usually has multiple parts that build upon each other and are ordered by their difficulty level. You can work on those in order or start from wherever you like. However you only need to submit the last part you are able to solve. For example, if a question has 5 parts (a, b, c, d, e), you are confident about part e, you should submit part e without any of the previous four parts. If you are confident about d but not sure about e, you should submit d for grading purposes. Please clearly indicate in your submission which part you are submitting.
- *Redemption questions:* It is important that you carefully read the posted solutions, even for problems you got right. To encourage this, you have the option of submitting a redemption file, a few paragraphs in which you explain, for each problem you choose to cover, what you did wrong and what the right idea was in your own words (not cutting and pasting from the solution!), and appending it to your homework. For example, suppose that as you review your solutions to HW1, you realize you had misunderstood question 3 and answered it incorrectly. You would write down what you just learned, and then submit it in your HW2 assignment the following week. Because these are mainly for your benefit, feel free to format them however is most useful for you.
- *Extra credit questions:* We might have some extra credit questions in the homework for people who really enjoy the materials. However, please note that you should do the extra credit problems only if you really enjoy working on these problems and want an extra challenge. It is likely not the most efficient manner in which to maximize your score.

**1. (★ level) Course Syllabus**

Before you answer any of the following questions, please read over the syllabus carefully. The syllabus is pinned on the Piazza site. For each statement below, write *OK* if it is allowed by the course policies and *Not OK* otherwise.

- (a) You ask a friend who took CS 170 previously for her homework solutions, some of which overlap with this semester's problem sets. You look at her solutions, then later write them down in your own words.

**Solution** Not OK

- (b) You had 5 midterms on the same day and are behind on your homework. You decide to ask your classmate, who's already done the homework, for help. He tells you how to do the first three problems.

**Solution** Not OK

- (c) You look up a problem online to search an algorithm, write it in your words and cite the source.

**Solution** Not OK

- (d) You were looking up Dijkstra's on the internet, and run into a website with a problem very similar to one on your homework. You read it, including the solution, and then you close the website, write up your solution, and cite the website URL in your homework writeup.

**Solution** OK

- (e) You are working on the homework in one of the TA's office hours with other people. You hear that student John Doe asked the TA if his solution is correct or not and the TA is explaining it. You join their conversation to understand what John has done.

**Solution** OK

**2. (★★ level) Asymptotic Complexity Comparisons**

- (a) Order the following functions so that  $f_i \in O(f_j) \iff i \leq j$ . Do not justify your answers.

(i)  $f_1(n) = 3^n$

(ii)  $f_2(n) = n^{\frac{1}{3}}$

(iii)  $f_3(n) = 12$

(iv)  $f_4(n) = 2^{\log_2 n}$

(v)  $f_5(n) = \sqrt{n}$

(vi)  $f_6(n) = 2^n$

(vii)  $f_7(n) = \log_2 n$

(viii)  $f_8(n) = 2^{\sqrt{n}}$

(ix)  $f_9(n) = n^3$

**Solution**

$$O(12) \in O(\log_2(n)) \in O(2^{\log_2(n)}) \in O(n^{\frac{1}{3}}) \in O(n^{\frac{1}{2}}) \in O(n^3) \in O(2^{\sqrt{n}}) \in O(2^n) \in O(3^n)$$

$$3, 7, 4, 2, 5, 9, 8, 6, 1$$

(b) In each of the following, indicate whether  $f = O(g)$ ,  $f = \Omega(g)$ , or both (in which case  $f = \Theta(g)$ ).

**Briefly** justify each of your answers.

	$f(n)$	$g(n)$
(i)	$\log_3 n$	$\log_4 n$
(ii)	$n \log(n^4)$	$n^2 \log(n^3)$
(iii)	$\sqrt{n}$	$(\log n)^3$
(iv)	$2^n$	$2^{n+1}$
(v)	$n$	$(\log n)^{\log \log n}$
(vi)	$n + \log n$	$n + (\log n)^2$
(vii)	$\log n!$	$n \log n$

**Solution:**

i.

$$\frac{\ln(n)}{\ln(3)} \in \theta\left(\frac{\ln(n)}{\ln(4)}\right) \Rightarrow f \in \theta(g)$$

ii.

$$\lim_{n \rightarrow \infty} \frac{4 \log(n)}{3n \log(n)} = 0$$

$$f \in O(g)$$

iii.

$$\lim_{n \rightarrow \infty} \frac{\sqrt{n}}{(\log(3n))^3}$$

Take the derivative wrt  $n$  of numerator and denominator five times, and L'Hopital gives:

$$\lim_{n \rightarrow \infty} \frac{\sqrt{n}}{48} = \infty \Rightarrow f \in \Omega(g)$$

iv.

$$\forall n \in \mathbb{R}, a * 2^n \leq 2^{n+1} \leq b * 2^n, a = \frac{1}{4}, b = 4$$

$$f \in \theta(g)$$

v. For large  $n$ .

$$2 \log(\log(\log(n))) \leq \log(\log(n))$$

$$\Rightarrow (\log(\log(n)))^2 \leq \log(n)$$

$$\Rightarrow \log((\log(n))^{\log(\log(n))}) \leq \log(n)$$

$$\Rightarrow (\log(n))^{\log(\log(n))} \leq n$$

$$\Rightarrow g \leq f$$

$$f \in \Omega(g)$$

vi. I omit the calculus.

$$\lim_{n \rightarrow \infty} \frac{f}{g} = 0 \Rightarrow f \in O(g)$$

vii.

$$\left(\frac{n}{2}\right)^{\frac{n}{2}} \leq n!$$

$$\frac{n}{2}(\log(n) - \log(2)) \leq \log(n!)$$

$$O(n \log(n)) \in O(\log(n!))$$

$$f \in \Omega(g)$$

(c) Let  $f(\cdot)$  be a function. Consider the equality

$$\sum_{i=1}^n f(i) \in \Theta(f(n)),$$

give a function  $f_1$  such that the equality holds, and a function  $f_2$  such that the equality does not hold.

**Solution:**

$$\sum_{i=1}^n 2^n = 2^{n+1} \in \theta(2^n)$$

$$\sum_{i=1}^n i = \frac{n(n+1)}{2} \in \theta(n^2)$$

$$f_1(n) = 2^n, f_2(n) = n$$

(d) Prove or disprove: If  $f : \mathbb{N} \rightarrow \mathbb{N}$  is any positive-valued function, then either (1) there exists a constant  $c > 0$  so that  $f(n) \in O(n^c)$ , or (2) there exists a constant  $\alpha > 1$  so that  $f(n) \in \Omega(\alpha^n)$ .

**Solution:**

### 3. (★★★ level) Recurrence Relations

Derive an asymptotic *tight* bound for the following  $T(n)$ . Cite any theorem you use.

(a)  $T(n) = 2 \cdot T\left(\frac{n}{2}\right) + \sqrt{n}$ .

**Solution:** Using the Master Theorem, we have:

$$a = 2, b = 2, d = \frac{1}{2}$$

$$T(n) \in \theta(n^{\log_b(a)}) = \theta(n)$$

(b)  $T(n) = T(n-1) + c^n$  for constants  $c > 0$ .

**Solution:** Each call of the function on  $n$  recursively calls itself on  $n-1$ , and then does  $c^n$  work. The call  $T(1)$  returns 1, and so all the work can be seen as the sum of  $c^n$  from 2 to  $n$ .

$$\sum_{i=2}^n c^i = \frac{a_1(1-r^n)}{1-r} = \frac{c^2(1-c^{n-1})}{1-c} \in \theta(c^n)$$

(c)  $T(n) = 2T(\sqrt{n}) + 3$ , and  $T(2) = 3$ .

**Solution:**

$$T(n) = 2T(\sqrt{n}) + 3$$

$$T(n) = 2(2T(\sqrt{\sqrt{n}}) + 3) + 3$$

Because we are taking the square root of  $n$  each time, and we stop when  $n = 2$ , we can think of the recursion as halving the exponent each level deeper. Thus, because  $n = 2^{\log_2(n)}$ , the number of halvings before the exponent becomes 1 is  $\log(\log(n))$ . Thus:

$$T(n) = 2^{\log(\log n)} T(2) + 3 * \sum_{i=0}^{\log(\log n)} \in \theta(\log(n))$$

#### 4. (★★★★ level) Recurrence Relations Part II

Solve the following recurrence relations and give a  $\Theta$  bound for each of them.

(a) Using the Master theorem, where

(i)  $T(n) = 3T(n/4) + 4n^2$  **Solution:**

$$a = 3, b = 4, d = 2, d > \log_b(a)$$

$$T(n) \in \theta(n^2)$$

(ii)  $T(n) = 45T(n/3) + .1n^3$  Using the Master theorem, where **Solution:**

$$a = 45, b = 3, d = 3, d < \log_b(a)$$

$$T(n) \in \theta(n^{\log_3(45)})$$

(iii)  $T(n) = 2T(\sqrt{n}) + 5$ , and  $T(2) = 5$ . (Hint: this means the recursion tree stops when the problem size is 2)

(b) **Solution:** This is similar to problem 4.a.3, so we can go about it the same way.

$$T(n) = 2T(\sqrt{n}) + 5$$

$$T(n) = 2((2T(\sqrt{\sqrt{n}}) + 5)) + 5$$

Thus, we know from before that there will be a depth of  $\log(\log(n))$  in the recursive tree, and so we can express  $T(n)$  as

$$T(n) = 2^{\log(\log(n))} T(2) + 5 * \sum_{i=0}^{\log(\log(n))} 2^i \in \theta(\log(n))$$

- (i) Consider the recurrence relation  $T(n) = 2T(n/2) + n \log n$ . We can't plug it directly into the Master theorem, so solve it by adding the size of each layer.  
*Hint: split up the  $\log(n/(2^i))$  terms into  $\log n - \log(2^i)$ , and use the formula for arithmetic series.*
- (ii) A more general version of Master theorem, like the one on [Wikipedia](#), incorporates this result. The case of the master theorem which applies to this problem is:  
*If  $T(n) = aT(n/b) + f(n)$  where  $a \geq 1$ ,  $b > 1$ , and  $f(n) = \Theta(n^c \log^k n)$  where  $c = \log_b a$ , then  $T(n) = \Theta(n^c \log^{k+1} n)$ .*  
 Use the general Master theorem to solve the following recurrence relation:  
 $T(n) = 9T(n/3) + n^2 \log^3 n$ .

**Solution:**

**5. (★★★★ level) Two Sorted Arrays**

You are given two sorted arrays, each of size  $n$ . Give as efficient an algorithm as possible to find the  $k$ -th smallest element in the union of the two arrays. What is the running time of your algorithm as a function of  $k$  and  $n$ ? (*You need to give a four-part solution for this problem.*)

**Solution:**

**6. (★★★★★ level) Merged Median**

Given  $k$  sorted arrays of length  $l$ , design an efficient algorithm to finding the median element of all the  $n = kl$  elements. Your algorithm should run asymptotically faster than  $O(n)$ . Your answer from 5 may be helpful.  
 (*You need to give a four-part solution for this problem.*)

**Solution:**