

</> API Documentation

[🔑 API Management](#)

GRAML SOCIAL API

Complete documentation for integrating with our services

Base URL

<https://gramlsocial.com/api/v1/>

🔑 Authentication

All API requests require an API key. Include it in the request headers:

```
X-API-Key: your_api_key_here
```

[🔑 Get Your API Key](#)

🔌 API Endpoints

GET </health>

Check if the API is operational (no authentication required).

Example:

```
curl https://gramlsocial.com/api/v1/health
```

Response:

```
{
  "status": "success",
  "data": {
    "healthy": true,
    "time": "2026-05-02 08:37:14"
```

```
}  
}
```

GET `/products`

Retrieve all available products with real-time stock levels.

Parameters:

- `limit` - Number of products (default: 50, max: 100)

Example:

```
curl -H "X-API-Key: YOUR_API_KEY" \  
  "https://gramlsocial.com/api/v1/products?limit=10"
```

Response:

```
{  
  "status": "success",  
  "data": [  
    {  
      "id": 1468,  
      "name": "X (TWITTER) CREATED AROUND 1 MONTH",  
      "price": 500,  
      "stock": 185,  
      "price_formatted": "₦500.00"  
    }  
  ]  
}
```

GET `/my/balance`

View your wallet balance in Nigerian Naira (₦).

Example:

```
curl -H "X-API-Key: YOUR_API_KEY" \  
  "https://gramlsocial.com/api/v1/my/balance"
```

```
https://gramlsocial.com/api/v1/my/balance
```

Response:

```
{
  "status": "success",
  "data": {
    "balance": 8500.50,
    "currency": "NGN",
    "balance_formatted": "₦8,500.50",
    "username": "Rexpress12"
  }
}
```

POST `/purchase`

Purchase a product using your wallet balance. Account details delivered instantly.

Request Body:

```
{
  "product_id": 1468,
  "quantity": 1
}
```

Example:

```
curl -X POST \
  -H "X-API-Key: YOUR_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{"product_id":1468,"quantity":1}' \
  https://gramlsocial.com/api/v1/purchase
```

Response (Success):

```
{
  "status": "success",
  "message": "Purchase successful",
  "data": {
```

```
"order_id": 42920,
"transaction_id": "API-69F5B7BAA10B6-1777711034",
"product": {
  "id": 1468,
  "name": "X(TWITTER) CREATED AROUND 1 MONTH",
  "price": 500
},
"quantity": 1,
"total": 500,
"total_formatted": "₦500.00",
"balance_remaining": 8500.50,
"balance_formatted": "₦8,500.50",
"accounts": ["username:password@email.com:password"]
}
```

GET `/my/orders`

Retrieve your purchase history.

Parameters:

- `limit` - Number of orders (default: 20)

Example:

```
curl -H "X-API-Key: YOUR_API_KEY" \
  "https://gramlsocial.com/api/v1/my/orders?limit=10"
```

</> Code Examples

PHP Example

```
<?php
class GramlSocialAPI {
  private $apiKey;
  private $baseUrl = 'https://gramlsocial.com/api/v1/';

  public function __construct($apiKey) {
    $this->apiKey = $apiKey;
  }
}
```

```

    }

    private function request($endpoint, $method = 'GET', $
        $ch = curl_init($this->baseUrl . $endpoint);
        curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
        curl_setopt($ch, CURLOPT_HTTPHEADER, [
            'X-API-Key: ' . $this->apiKey,
            'Content-Type: application/json'
        ]);

        if ($method == 'POST' && $data) {
            curl_setopt($ch, CURLOPT_POST, true);
            curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
        }

        return json_decode(curl_exec($ch), true);
    }

    public function getBalance() {
        return $this->request('my/balance');
    }

    public function getProducts($limit = 50) {
        return $this->request("products?limit=$limit");
    }

    public function purchase($productId, $quantity = 1) {
        return $this->request('purchase', 'POST', [
            'product_id' => $productId,
            'quantity' => $quantity
        ]);
    }

    public function getOrders($limit = 20) {
        return $this->request("my/orders?limit=$limit");
    }
}

// Usage
$api = new GramlSocialAPI('YOUR_API_KEY');
$balance = $api->getBalance();
echo $balance['data']['balance_formatted'];
?>

```

Python Example

```
import requests

class GramlSocialAPI:
    def __init__(self, api_key):
        self.api_key = api_key
        self.base_url = "https://gramlsocial.com/api/v1/"
        self.headers = {"X-API-Key": api_key}

    def get_balance(self):
        response = requests.get(f"{self.base_url}my/balance")
        return response.json()

    def get_products(self, limit=50):
        response = requests.get(f"{self.base_url}products?limit={limit}")
        return response.json()

    def purchase(self, product_id, quantity=1):
        data = {"product_id": product_id, "quantity": quantity}
        response = requests.post(f"{self.base_url}purchase", json=data)
        return response.json()

    def get_orders(self, limit=20):
        response = requests.get(f"{self.base_url}my/orders?limit={limit}")
        return response.json()

# Usage
api = GramlSocialAPI("YOUR_API_KEY")
balance = api.get_balance()
print(balance['data']['balance_formatted'])
```

⚠ Error Codes

- 200 - Success
- 400 - Bad Request (invalid parameters)
- 401 - Unauthorized (invalid API key)
- 404 - Not Found
- 500 - Internal Server Error

[← Back to API Management](#)

[🖨️ Print Documentation](#)