

Chapter 6

How to code summary queries

Objectives

Applied

- Code summary queries that use aggregate functions, including queries that use the WITH ROLLUP operator.

Knowledge

- Describe summary queries.
- Describe the differences between the HAVING clause and the WHERE clause.
- Describe the use of the WITH ROLLUP operator.

The syntax of the aggregate functions

`AVG([ALL | DISTINCT] expression)`

`SUM([ALL | DISTINCT] expression)`

`MIN([ALL | DISTINCT] expression)`

`MAX([ALL | DISTINCT] expression)`

`COUNT([ALL | DISTINCT] expression)`

`COUNT(*)`

A summary query

```
SELECT COUNT(*) AS number_of_invoices,  
       SUM(invoice_total - payment_total -  
credit_total)  
       AS total_due
```

▶

	number_of_invoices	total_due
▶	11	32020.42

```
WHERE invoice_total - payment_total -  
credit_total > 0
```

A summary query with COUNT(*), AVG, and SUM

```
SELECT 'After 1/1/2014' AS  
selection_date,  
       COUNT(*) AS  
number_of_invoices,  
       ROUND(AVG(invoice_total), 2)  
AS avg_invoice_amt,  
       SUM(invoice_total) AS  
total_invoice_amt  
FROM invoices  
WHERE invoice_date > '2014-01-01'
```

	selection_date	number_of_invoices	avg_invoice_amt	total_invoice_amt
▶	After 1/1/2014	114	1879.74	214290.51

A summary query with MIN and MAX

```
SELECT 'After 1/1/2014' AS  
selection_date,  
       COUNT(*) AS number_of_invoices,  
       MAX(invoice_total) AS  
highest_invoice_total,  
       MIN(invoice_total) AS  
lowest_invoice_total  
FROM invoices  
WHERE invoice_date > '2014-01-01'
```

	selection_date	number_of_invoices	highest_invoice_total	lowest_invoice_total
►	After 1/1/2014	114	37966.19	6.00

A summary query for non-numeric columns

```
SELECT MIN(vendor_name) AS first_vendor,  
       MAX(vendor_name) AS last_vendor,  
       COUNT(vendor_name) AS  
number_of_vendors  
FROM vendors
```

	first_vendor	last_vendor	number_of_vendors
▶	Abbey Office Furnishings	Zylka Design	122

A summary query with the DISTINCT keyword

```
SELECT COUNT(DISTINCT vendor_id) AS  
number_of_vendors,  
       COUNT(vendor_id) AS  
number_of_invoices,  
       ROUND(AVG(invoice_total), 2) AS  
avg_invoice_amt,  
       SUM(invoice_total) AS  
total_invoice_amt  
FROM invoices  
WHERE invoice_date > '2014-01-01'
```

	number_of_vendors	number_of_invoices	avg_invoice_amt	total_invoice_amt
▶	34	114	1879.74	214290.51

The syntax of a SELECT statement with GROUP BY and HAVING clauses

```
SELECT select_list  
FROM table_source  
[WHERE search_condition]  
[GROUP BY group_by_list]  
[HAVING search_condition]  
[ORDER BY order_by_list]
```

A summary query that calculates the average invoice amount by vendor

```
SELECT vendor_id,  
       ROUND(AVG(invoice_total), 2)  
         AS average_invoice_amount  
FROM invoices  
GROUP BY vendor_id  
HAVING AVG(invoice_total) > 2000  
ORDER BY average_invoice_amount DESC
```

	vendor_id	average_invoice_amount
▶	110	23978.48
	72	10963.66
	104	7125.34
	99	6940.25
	119	4901.26
	122	2575.33
	86	2433.00
	100	2184.50

(8 rows)

A summary query that counts the number of invoices by vendor

```
SELECT vendor_id, COUNT(*) AS  
invoice_qty  
FROM invoices  
GROUP BY vendor_id
```

	vendor_id	invoice_qty
▶	34	2
	37	3
	48	1
	72	2

(34 rows)

Save a summary query with a join in a table

```
CREATE TABLE newtable SELECT vendor_state, vendor_city,  
COUNT(*) AS invoice_qty,  
    ROUND(AVG(invoice_total), 2) AS invoice_avg  
FROM invoices JOIN vendors  
    ON invoices.vendor_id = vendors.vendor_id  
GROUP BY vendor_state, vendor_city
```

	vendor_state	vendor_city	invoice_qty	invoice_avg
▶	AZ	Phoenix	1	662.00
	CA	Fresno	19	1208.75
	CA	Los Angeles	1	503.20
	CA	Oxnard	3	188.00

(20 rows)

A summary query that limits the groups to those with two or more invoices

```
SELECT vendor_state, vendor_city,  
COUNT(*) AS invoice_qty,  
        ROUND(AVG(invoice_total), 2) AS  
invoice_avg  
FROM invoices JOIN vendors  
        ON invoices.vendor_id =  
vendors.vendor_id  
GROUP BY vendor_state, vendor_city  
HAVING COUNT(*) >= 2
```

	vendor_state	vendor_city	invoice_qty	invoice_avg
▶	CA	Fresno	19	1208.75
	CA	Oxnard	3	188.00
	CA	Pasadena	5	196.12
	CA	Sacramento	7	253.00

(12 rows)

A summary query with a search condition in the HAVING clause

```
SELECT vendor_name,  
       COUNT(*) AS invoice_qty,  
       ROUND(AVG(invoice_total),2) AS  
invoice_avg  
FROM vendors JOIN invoices  
       ON vendors.vendor_id =  
invoices.vendor_id  
GROUP BY vendor_name  
HAVING AVG(invoice_total) > 500  
ORDER BY invoice_qty DESC
```

(19 rows)

	vendor_name	invoice_qty	invoice_avg	▲
▶	United Parcel Service	9	2575.33	
	Zylka Design	8	867.53	
	Malloy Lithographing Inc	5	23978.48	
	Ingram	2	1077.21	▼

A summary query with a search condition in the WHERE clause

```
SELECT vendor_name,  
       COUNT(*) AS invoice_qty,  
       ROUND(AVG(invoice_total),2) AS  
invoice_avg  
FROM vendors JOIN invoices  
       ON vendors.vendor_id =  
invoices.vendor_id  
WHERE invoice_total > 500  
GROUP BY vendor_name  
ORDER BY invoice_qty DESC
```

	vendor_name	invoice_qty	invoice_avg
▶	United Parcel Service	9	2575.33
	Zylka Design	7	946.67
	Malloy Lithographing Inc	5	23978.48
	Ingram	2	1077.21

(20 rows)

A summary query with a compound condition in the HAVING clause

```
SELECT
    invoice_date,
    COUNT(*) AS invoice_qty,
    SUM(invoice_total) AS invoice_sum
FROM invoices
GROUP BY invoice_date
HAVING invoice_date BETWEEN '2014-05-01' AND '2014-05-31'
    AND COUNT(*) > 1
    AND SUM(invoice_total) > 100
ORDER BY invoice_date DESC
```

The result set

	invoice_date	invoice_qty	invoice_sum
▶	2014-05-31	2	453.75
	2014-05-25	3	2201.15
	2014-05-23	2	347.75
	2014-05-21	2	8078.44

(7 rows)

The same query coded with a WHERE clause

```
SELECT
    invoice_date,
    COUNT(*) AS invoice_qty,
    SUM(invoice_total) AS invoice_sum
FROM invoices
WHERE invoice_date BETWEEN '2014-05-01' AND '2014-05-31'
GROUP BY invoice_date
HAVING COUNT(*) > 1
      AND SUM(invoice_total) > 100
ORDER BY invoice_date DESC
```

The same result set

	invoice_date	invoice_qty	invoice_sum
▶	2014-05-31	2	453.75
	2014-05-25	3	2201.15
	2014-05-23	2	347.75
	2014-05-21	2	8078.44

(7 rows)

A summary query with a final summary row

```
SELECT vendor_id, COUNT(*) AS invoice_count,  
       SUM(invoice_total) AS invoice_total  
FROM invoices  
GROUP BY vendor_id WITH ROLLUP
```

	vendor_id	invoice_count	invoice_total
▶	34	2	1200.12
	37	3	564.00
	48	1	856.92
	72	2	21927.31

(35 rows)

A summary query with a summary row for each grouping level

```
SELECT vendor_state, vendor_city, COUNT(*) AS qty_vendors
FROM vendors
WHERE vendor_state IN ('IA', 'NJ')
GROUP BY vendor_state ASC, vendor_city ASC WITH ROLLUP
```

	vendor_state	vendor_city	qty_vendors
▶	IA	Fairfield	1
	IA	Washington	1
	IA	NULL	2
	NJ	East Brunswick	2
	NJ	Fairfield	1
	NJ	Washington	1
	NJ	NULL	4
	NULL	NULL	6