Voliro T

SPECIFICATIONS & LIMITATIONS



Drone Specifications

- Weight : 3.7 Kg
- Max takeoff weight : 6.0 Kg
- Max Payload weight : 1.0 Kg
- Dimension (Fully Assembled) : 118x109x34 cm
- Camera System : 4K 12 MP (Narrow lens) 2K 12 MP (Wide Lens)
- Flight Time : 10 Min
- Flight Mode : Manual, Altitude, Position (GPS & Optical Flow)
- Emergency Flight Mode: Intelligent Auto Descent / Position Hold
- Max transmission distance : 300 m
- Wind Resistance : 8 m/s
- Battery Type : LiPo 6s 9000 mAh

Drone Limitations

- The drone is not water resistant.
- Wind resistance during measurement operations is limited to 8 m/s.
- The RTK base used for GPS positioning must remain in line of sight with the drone; failing to do so may result in the loss of RTK reception, which can lead to degraded or lost GPS positioning.
- The RTK base must be securely positioned and cannot be placed on a moving platform such as a ship or boat.
- The optical-flow sensor may not work properly when the drone is flown in reflective environments such as glossy paint surfaces or bodies of water.
- The drone may be unable to maintain its position and could crash if both RTK positioning and optical-flow positioning fail.
- A minimum obstacle-free area of 5 × 5 meters is required for safe takeoff and landing.
- The drone cannot be operated from a moving platform, such as a boat or ship.

UT Sensor Limitations

- The minimum pipe diameter that can be measured is 2 inches.
- The maximum temperature that can be measured with a non–high-temperature probe is 60°C (140°F).
- The maximum temperature that can be measured with a high-temperature probe is 260°C (500°F).
- The measurable thickness range is 2–150 mm.
- The surface should be clean and not too rough at the time of measurement.
- The resolution is 0.06 mm (0.002 in).

EMAT Sensor Limitations

- The minimum surface diameter that can be measured is 5 mm (0.2 in).
- The maximum temperature that can be measured is 60°C (140°F).
- The measurable thickness range is 2–150 mm.
- The surface should be clean and not too rough at the time of measurement.
- The resolution is 0.06 mm (0.002 in).