Voliro T – Specifications & Limitations

Drone Specifications

- Weight: 3.7 kg
- Max takeoff weight: 6.0 kg
- Max payload weight: 1.0 kg
- Dimensions (Fully Assembled): 118 × 109 × 34 cm
- Camera System: 4K 12 MP (Narrow Lens), 2K 12 MP (Wide Lens)
- Flight Time: 10 minutes
- Flight Mode: Manual, Altitude, Position (GPS & Optical Flow)
- Emergency Flight Mode: Intelligent Auto Descent / Position Hold
- Max transmission distance: 300 m
- Wind resistance: 8 m/s
- Battery Type: LiPo 6s 9000 mAh

Drone Limitations

- The drone is not water resistant.
- Wind resistance during measurement operations is limited to 8 m/s.
- The RTK base used for GPS positioning must remain in line of sight with the drone.
- The RTK base cannot be placed on a moving platform such as a ship or boat.
- The optical-flow sensor may not work properly in reflective environments such as glossy paint or bodies of water.
- The drone may lose position hold and crash if both RTK and optical-flow positioning fail.
- A minimum obstacle-free area of 5 × 5 meters is required for safe takeoff and landing.
- The drone cannot be operated from a moving platform such as a boat or ship.

UT Sensor Limitations

- The minimum pipe diameter measurable is 2 inches.
- Max temperature with non–high-temperature probe: 60°C (140°F).
- Max temperature with high-temperature probe: 260°C (500°F).
- Thickness measurement range: 2–150 mm.
- Surface must be clean and not too rough.
- Resolution: 0.06 mm (0.002 in).

EMAT Sensor Limitations

- Minimum surface diameter measurable: 5 mm (0.2 in).
- Maximum temperature measurable: 60°C (140°F).
- Thickness measurement range: 2–150 mm.
- Surface must be clean and not too rough.
- Resolution: 0.06 mm (0.002 in).