


Example (CORBA/JTS)




□ Project:

- ☆ Replace Application A with Middleware (middleware has own DB with customer information)
- ☆ Replication App B with Flight
- ☆ Instead of DB M / DB B we have things so far in main memory

COMP-512: Distributed Systems

24


Example I



COMP-512: Distributed Systems

25


Example 2



COMP-512: Distributed Systems

26


Example 3



COMP-512: Distributed Systems

27


Example 4



COMP-512: Distributed Systems

28


Example 5



COMP-512: Distributed Systems

29


Example 6



COMP-512: Distributed Systems

30


Example 7



COMP-512: Distributed Systems

31


Example 8



COMP-512: Distributed Systems

32


Example 9



COMP-512: Distributed Systems

33


Example 10



COMP-512: Distributed Systems

34


Example 11



COMP-512: Distributed Systems

35


Example 12



COMP-512: Distributed Systems

36


Example 13




COMP-512: Distributed Systems

37

Example 14



OTS Sequence of Messages




Resource Registration

- ❑ Registration is necessary in order to tell the OTS who will participate in the 2PC protocol and what type of interface is supported. Registration can be manual or automatic
- ❑ Example Interface:
 - ☆ XA supported by many DBS
 - ☆ allows exchange of transaction identifier
 - Hence, the OTS can tell the DBS, which transaction it wants to terminate

Protocol Topologies

- ❑ Centralized Protocols:
 - ☆ A coordinator manages the protocol flow
 - ☆ Communication is only between coordinator and individual participant
 - ☆ Participants do not need to know each other and do not communicate with each other



- ❑ Alternatives:
 - ☆ Decentralized 2PC
 - ☆ Linear 2PC
 - ☆ Hierarchical 2PC


Decentralized 2PC

□ Protocol

- ☆ Coordinator multicasts YES/NO to all participants (indicates also start of 2PC)
- ☆ Upon receipt of vote from coordinator, participant multicasts YES/NO vote all other participants and the coordinator
- ☆ Whenever participant or coordinator has votes from all other sites, terminate transaction accordingly

□ Complexity

- ☆ Rounds: 2 (coordinator's vote + votes of the others)
- ☆ Number of messages (n+1 sites):
 - Point-to-point: $n * (n+1)$
 - Broadcast: $n+1$




COMP-512: Distributed Systems

42

Linear 2PC

- Linear 2PC commit exploits a particular network configuration to minimize the number of messages:




COMP-512: Distributed Systems

43

Linear 2PC

❑ Abort Case



44

Linear 2PC

❑ Complexity

☆ Message rounds: $2n-2$

☆ Number of messages: $2n-2$ (broadcast cannot be exploited)

❑ Often implemented when only two sites

❑ Coordinator delegation: last site takes over to be the coordinator for decision phase


☆ other coordinator delegation protocol implemented in Oracle

COMP-512: Distributed Systems

45

Hierarchical 2PC

- ❑ Truly distributed systems can have hierarchical calling histories
 - ☆ An instance can be server and client at the same time
 - ☆ E-Commerce Applications J2 Enterprise Edition



COMP-512: Distributed Systems

46

Hierarchical execution

- ❑ During normal execution
 - ☆ Processes dynamically form tree
 - ☆ New edges are added whenever one processes calls another process to perform a subtransaction
 - ☆ Once a link is created it can be reused for subsequent requests
- ❑ Atomic Commit Protocol
 - ☆ Flattened:
 - Propagation of one global transaction identifier
 - all resources register with the same transaction service
 - ☆ Hierarchical:
 - Root is main coordinator
 - Intermediate nodes are coordinator for children and participant to parent process

COMP-512: Distributed Systems

47

Main steps of hierarchical 2PC

- ❑ Main coordinator (as before)
- ❑ Intermediate process
 - ☆ Upon receipt of vote-request from parent,
 - If own vote is YES, then submit vote-request to all children
 - If own vote is NO, then abort transaction and forward NO to parent and to all children
 - ☆ Upon receipt of NO from parent
 - Abort transaction and forward NO to children
 - ☆ Upon receipt of all votes from children
 - If all vote YES and process itself votes YES, then send YES vote to parent
 - If at least one votes NO, then abort transaction and send NO vote to parent
 - ☆ Upon receipt of commit/abort from parent
 - Commit/abort locally and send commit/abort to all children
- ❑ Leaf process (similar to before)