

Singular Value Decomposition

for recommender systems

Singular Value Decomposition

Used in LSA/LSI, PCA...

Singular Value Decomposition

Used in LSA/LSI, PCA...

$$A = U \Sigma V^{\top}$$

Singular Value Decomposition

Used in LSA/LSI, PCA...

$$A = U \Sigma V^{\top}$$


columns are orthonormal:

$$U^{\top}U = V^{\top}V = I$$

Singular Value Decomposition

Used in LSA/LSI, PCA...

Truncated SVD of rank r




columns are orthonormal:

$$U^T U = V^T V = I$$

Singular Value Decomposition

Used in LSA/LSI, PCA...

Truncated SVD of rank r



columns are orthonormal:

$$U^T U = V^T V = I$$

$$\|A - A_r\|_F^2 \rightarrow \min$$


$$A_r = U \Sigma V^T$$

$$\|X\|_F^2 = \sum_{ij} x_{ij}^2$$

Singular Value Decomposition

Used in LSA/LSI, PCA...

Truncated SVD of rank r



columns are orthonormal:

$$U^T U = V^T V = I$$

$$\|A - A_r\|_F^2 \rightarrow \min$$


$$A_r = U \Sigma V^T$$

$$\|X\|_F^2 = \sum_{ij} x_{ij}^2$$

Undefined for incomplete matrix!

Singular Value Decomposition Used in LSA/LSI, PCA...

Truncated SVD of rank r



columns are orthonormal:

$$U^T U = V^T V = I$$

$$\|A - A_r\|_F^2 \rightarrow \min$$

$$A_r = U \Sigma V^T$$


$$\|X\|_F^2 = \sum_{ij} x_{ij}^2$$

Undefined for incomplete matrix!

Let's impute zeros - PureSVD model.

Singular Value Decomposition Used in LSA/LSI, PCA...

Truncated SVD of rank r



columns are orthonormal:

$$U^T U = V^T V = I$$

$$\|A - A_r\|_F^2 \rightarrow \min$$

$$A_r = U \Sigma V^T$$



$$\|X\|_F^2 = \sum_{ij} x_{ij}^2$$

Undefined for incomplete matrix!

Let's impute zeros - PureSVD model.

- values are highly biased towards 0
- not good for rating prediction
- its not a big problem for ranking task

PureSVD – quality of recommendations



Netflix data: complete dataset (left) and “long-tail” (right).

P. Cremonesi, Y.Koren, R.Turrin, “Performance of Recommender Algorithms on Top-N Recommendation Tasks“, Proceedings of the 4th ACM conference on Recommender systems, 2011.


Note: Funk SVD, SVD++, TimeSVD++, Asymmetric SVD ... **are not** the SVD!

PureSVD – recommending online


$$A \approx U \Sigma V^T$$

The diagram illustrates the PureSVD decomposition of matrix A into matrices U , Σ , and V^T . Matrix A is an 8x8 grid with 12 yellow squares representing non-zero entries. Matrix U is an 8x8 grid where all squares are yellow. Matrix Σ is an 8x8 grid with 4 yellow squares on the main diagonal and all other squares are white. Matrix V^T is an 8x8 grid where all squares are yellow. The matrices are arranged in the equation $A \approx U \Sigma V^T$, with U and Σ separated by a multiplication symbol (\times), and Σ and V^T separated by another multiplication symbol (\times). An approximation symbol (\approx) is placed between A and the product of the three matrices.


PureSVD – recommending online




PureSVD – recommending online



PureSVD – recommending online




PureSVD – recommending online




*G. Furnas, S. Deerwester, and S. Dumais, "Information Retrieval Using a Singular Value Decomposition Model of Latent Semantic Structure," Proceedings of ACM SIGIR Conference, 1988

PureSVD – recommending online



*G. Furnas, S. Deerwester, and S. Dumais, "Information Retrieval Using a Singular Value Decomposition Model of Latent Semantic Structure," Proceedings of ACM SIGIR Conference, 1988

PureSVD – recommending online



Summary

Summary

- You know what SVD is and what its key features are

Summary

- You know what SVD is and what its key features are
- You understand the role it plays in the **PureSVD** model

Summary

- You know what SVD is and what its key features are
- You understand the role it plays in the **PureSVD** model
- You can explain how **folding-in** approach works and how to use it for online recommendations