

Cucumber.java (abstract class)
Instance variables: - name: String - nutrition: int - ripeDuration: int - value: int
Methods: + void grow() + void plant() + int getNutrition() + int getRipeDuration() + int getDaysToGrow() + int getValue() + void setRipeDuration(int)

CucumberA.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name: String</i> - <i>nutrition: int</i> - <i>ripeDuration: int</i> - <i>value: int</i>
Methods: + String about() (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getToDaysGrow()</i> + <i>int getValue()</i> + <i>void setRipeDuration(int)</i>

CucumberB.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name</i> : <i>String</i> - <i>nutrition</i> : <i>int</i> - <i>ripeDuration</i> : <i>int</i> - <i>value</i> : <i>int</i>
Methods: + String about() (inherited from Cucumber) + <i>void</i> grow() + <i>void</i> plant() + <i>int</i> getNutrition() + <i>int</i> getRipeDuration() + <i>int</i> getToDaysGrow() + <i>int</i> getValue() + <i>void</i> setRipeDuration(<i>int</i>)

CucumberC.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name</i> : <i>String</i> - <i>nutrition</i> : <i>int</i> - <i>ripeDuration</i> : <i>int</i> - <i>value</i> : <i>int</i>
Methods: + String about() (inherited from Cucumber) + <i>void</i> grow() + <i>void</i> plant() + <i>int</i> getNutrition() + <i>int</i> getRipeDuration() + <i>int</i> getToDaysGrow() + <i>int</i> getValue() + <i>void</i> setRipeDuration(<i>int</i>)

CucumberD.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name</i> : <i>String</i> - <i>nutrition</i> : <i>int</i> - <i>ripeDuration</i> : <i>int</i> - <i>value</i> : <i>int</i>
Methods: + String about() (inherited from Cucumber) + <i>void</i> grow() + <i>void</i> plant() + <i>int</i> getNutrition() + <i>int</i> getRipeDuration() + <i>int</i> getToDaysGrow() + <i>int</i> getValue() + <i>void</i> setRipeDuration(<i>int</i>)

CucumberE.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name</i> : <i>String</i> - <i>nutrition</i> : <i>int</i> - <i>ripeDuration</i> : <i>int</i> - <i>value</i> : <i>int</i>
Methods: + String about() (inherited from Cucumber) + <i>void</i> grow() + <i>void</i> plant() + <i>int</i> getNutrition() + <i>int</i> getRipeDuration() + <i>int</i> getToDaysGrow() + <i>int</i> getValue() + <i>void</i> setRipeDuration(<i>int</i>)

Farm.java
Instance variables: - farm: String[][]
Methods: + String getCucumber(int, int) + String setCucumber(int, int, String) + String toString()

User.java
Instance variables: - money: int
Methods: + void plant(int,int, Object) + void harvest(int, int) + int getMoney() + void setMoney(int)

Woo.java
Instance variables: - weeksElapsed: int
Methods: + void main(String[])