

Cucumber.java (abstract class)
Instance variables: <ul style="list-style-type: none">- name: String- nutrition: int- ripeDuration: int- value: int
Methods: <ul style="list-style-type: none">+ void grow()+ void plant()+ int getNutrition()+ int getRipeDuration()+ int getValue()+ String toString()

CucumberA.java (extends Cucumber)
Instance variables: (inherited from Cucumber) <ul style="list-style-type: none">- <i>name: String</i>- <i>nutrition: int</i>- <i>ripeDuration: int</i>- <i>value: int</i>
Methods: <ul style="list-style-type: none">+ String about()+ String toString() (inherited from Cucumber) <ul style="list-style-type: none">+ <i>void grow()</i>+ <i>void plant()</i>+ <i>int getNutrition()</i>+ <i>int getRipeDuration()</i>+ <i>int getValue()</i>

CucumberB.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name: String</i> - <i>nutrition: int</i> - <i>ripeDuration: int</i> - <i>value: int</i>
Methods: + String about() + String toString() (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getValue()</i>

CucumberC.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name: String</i> - <i>nutrition: int</i> - <i>ripeDuration: int</i> - <i>value: int</i>
Methods: + String about() + String toString() (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getValue()</i>

CucumberD.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name: String</i> - <i>nutrition: int</i> - <i>ripeDuration: int</i> - <i>value: int</i>
Methods: + String about() + String toString() (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getValue()</i>

CucumberE.java (extends Cucumber)
Instance variables: (inherited from Cucumber) - <i>name: String</i> - <i>nutrition: int</i> - <i>ripeDuration: int</i> - <i>value: int</i>
Methods: + String about() + String toString() (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getValue()</i>

Farm.java
Instance variables: - farm: ArrayList[] <Object>
Methods: + Object getCucumber(int, int) + void setCucumber(int, int, Object) + String toString()

User.java
Instance variables: - money: int
Methods: + void plant(int,int, Object) + void harvest(int, int) + int getMoney() + void setMoney(int)

Woo.java
Instance variables: - weeksElapsed: int
Methods: + void main(String[])