

Cucumber.java (abstract class)
Instance variables: - name: String - nutrition: int - ripeDuration: int - value: int
Methods:  + void grow() + void plant() + int getNutrition() + int getRipeDuration() + int getDaysToGrow() + int getValue() + void setRipeDuration(int) + String toString()

CucumberA.java (extends Cucumber)
Instance variables:  (inherited from Cucumber) - <i>name: String</i> - <i>nutrition: int</i> - <i>ripeDuration: int</i> - <i>value: int</i>
Methods:  + String about() + String toString()  (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getToDaysGrow()</i> + <i>int getValue()</i> + <i>void setRipeDuration(int)</i>

CucumberB.java (extends Cucumber)
Instance variables:  (inherited from Cucumber) - <i>name</i> : <i>String</i> - <i>nutrition</i> : <i>int</i> - <i>ripeDuration</i> : <i>int</i> - <i>value</i> : <i>int</i>
Methods:  + String about() + String toString()  (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getToDaysGrow()</i> + <i>int getValue()</i> + <i>void setRipeDuration(int)</i>

CucumberC.java (extends Cucumber)
Instance variables:  (inherited from Cucumber) - <i>name</i> : <i>String</i> - <i>nutrition</i> : <i>int</i> - <i>ripeDuration</i> : <i>int</i> - <i>value</i> : <i>int</i>
Methods:  + String about() + String toString()  (inherited from Cucumber) + <i>void grow()</i> + <i>void plant()</i> + <i>int getNutrition()</i> + <i>int getRipeDuration()</i> + <i>int getToDaysGrow()</i> + <i>int getValue()</i> + <i>void setRipeDuration(int)</i>

CucumberD.java (extends Cucumber)
<p>Instance variables:</p> <p>(inherited from Cucumber)</p> <ul style="list-style-type: none"><li>- <i>name</i>: <i>String</i></li><li>- <i>nutrition</i>: <i>int</i></li><li>- <i>ripeDuration</i>: <i>int</i></li><li>- <i>value</i>: <i>int</i></li></ul>
<p>Methods:</p> <ul style="list-style-type: none"><li>+ <i>String</i> about()</li><li>+ <i>String</i> toString()</li></ul> <p>(inherited from Cucumber)</p> <ul style="list-style-type: none"><li>+ <i>void</i> grow()</li><li>+ <i>void</i> plant()</li><li>+ <i>int</i> getNutrition()</li><li>+ <i>int</i> getRipeDuration()</li><li>+ <i>int</i> getToDaysGrow()</li><li>+ <i>int</i> getValue()</li><li>+ <i>void</i> setRipeDuration(<i>int</i>)</li></ul>

CucumberE.java (extends Cucumber)
<p>Instance variables:</p> <p>(inherited from Cucumber)</p> <ul style="list-style-type: none"><li>- <i>name</i>: <i>String</i></li><li>- <i>nutrition</i>: <i>int</i></li><li>- <i>ripeDuration</i>: <i>int</i></li><li>- <i>value</i>: <i>int</i></li></ul>
<p>Methods:</p> <ul style="list-style-type: none"><li>+ <i>String</i> about()</li><li>+ <i>String</i> toString()</li></ul> <p>(inherited from Cucumber)</p> <ul style="list-style-type: none"><li>+ <i>void</i> grow()</li><li>+ <i>void</i> plant()</li><li>+ <i>int</i> getNutrition()</li><li>+ <i>int</i> getRipeDuration()</li><li>+ <i>int</i> getToDaysGrow()</li><li>+ <i>int</i> getValue()</li><li>+ <i>void</i> setRipeDuration(<i>int</i>)</li></ul>

Farm.java
Instance variables:  - farm: ArrayList<> <String>
Methods:  + String getCucumber(int, int) + String setCucumber(int, int, String) + String toString()

User.java
Instance variables:  - money: int
Methods:  + void plant(int,int, Object) + void harvest(int, int) + int getMoney() + void setMoney(int)

Woo.java
Instance variables:  - weeksElapsed: int
Methods:  + void main(String[])