Comparison of Ordinary Blind Session Reuse vs. HACER Adaptive Cache Policy under Dynamic Evidence

Scenario A	Scenario B	Scenario C	Scenario D	Scenario E
Content Update (Stipend 400→800)	Revocation / Deletion (Childcare Subsidy)	Changed Ordering ([C2, C1] vs [C1, C2])	Partial Update (C1 same, C2 1200→1600)	Corrupt Cache File (0-byte / invalid header)
Ordinary Blind Reuse	**Ordinary Blind Reuse**	**Ordinary Blind Reuse**	**Ordinary Blind Reuse**	**Ordinary Blind Reuse**
Blind Reuse: Outputs '$400 USD' [Stale Hallucination!]	Blind Reuse: Outputs '$500' [Hallucinates Revoked Fact!]	Blind Reuse: Evaluates full prompt online (0% reuse)	Blind Reuse: Outputs '$1,200' [Stale Price Fact!]	Blind Reuse: Native runtime SIGSEGV [Uncaught Crash!]
HACER Adaptive Policy	**HACER Adaptive Policy**	**HACER Adaptive Policy**	**HACER Adaptive Policy**	**HACER Adaptive Policy**
HACER Adaptive: Detects Hash Mismatch Invalidates & Repairs Outputs '$800 USD' [100%]	HACER Adaptive: Detects Absence Evicts Cache Outputs 'None' [Safe Abstain]	HACER Adaptive: Canonicalizes chunk order Preserves prefix cache hit Outputs correct answer	HACER Adaptive: Preserves C1 Prefix KV Re-prefills C2 online Outputs '$1,600' [Fresh]	HACER Adaptive: Validates file header Safe scratch fallback Outputs correct answer