

# LoRa technology for Internet of Things(IoT):A brief Survey

Liya M L

Center for Wireless Networks & Applications (WNA)  
Amrita Vishwa Vidyapeetham, Amritapuri, India  
Email: liyامل@am.amrita.edu

Aswathy M

Center for Wireless Networks & Applications (WNA)  
Amrita Vishwa Vidyapeetham, Amritapuri, India  
Email: aswathym@am.amrita.edu

**Abstract**—IoT is one of the most emerging technologies for the growth of the research and development sector. This technology enables the connectivity of the devices so that they can talk to each other. A wide variety of communication techniques, standards and modules are available for data transmission and reception. In this work, the LoRaWAN techniques are being focused on sensor systems. The literature are being reviewed for finding possibilities of LoRaWAN for applying to different applications. This will be beneficial for the researchers and designers to know the feasibility of LoRaWAN in their system design.

**Keywords**—LoRa WAN, Sensor Networks, LoRa Module, LPWAN, LoRa classes, IoT system.

## I. INTRODUCTION

One of the fastest growing sectors in the internet of things is wireless sensor networking, which allows the collection of environmental information by utilizing simple and basic sensor networks. Miniaturization of electronics equipment, development of different protocols and the falling price will enable the rise of wireless sensor networks based IoT systems. This survey focuses on LoRaWAN WAN in Low Power Wide Area Network technology - LPWAN [1]. Common LPWAN technology including LORA, SIGFOX, NB-IoT. figure.1 shows range and bandwidth comparison for LPWAN technology. The data from end nodes being collected and sent to the base station and then to cloud service, where the client can collect data from cloud sources. The new trends in this technology[2] are to incorporate the LoRa with other sensor networks technology and transfer information from end nodes to base stations.

By this survey, the new trends in LoRa technology also is wished to resolve. This paper is mainly based on a technical overview of LoRa WAN [3]. LPWAN technology will provide low power wide area connectivity at a low bit rate. LoRa can handle a large number of sensor nodes and will cover kilometers. Range of a LoRa Module only depends on the environmental obstacles.




Figure1: Range and bandwidth comparison for different techniques.

Figure 1. Shows range and bandwidth comparison for different techniques with LPWAN. Modulation technique is based on the chirp spread spectrum and it is incorporated with forward error correction techniques. It operates in ISM bandwidth. LoRa Modulation [4] can be used by different protocol architectures such as a star, mesh. Bandwidth used are (Europe: 433MHz,868 MHz, USA: 915 MHz) [5]. Figure 2 shows the communication protocol of the LoRa WAN. LoRa physical layer will allow long-range communication and LoRaWAN networks can transfer data to multiple base stations [6]. A standardized MAC protocol by LoRa alliance is called LoRa WAN 1st version of LoRa WAN was published by LoRa alliance in 2015 and second version 2017[7]. Figure 2. Shows an architecture of LoRa WAN. Data collected in the sensor nodes is sent to the client via gateway and base station with the help of internet service.




Fig 2. System architecture of LoRa WAN

The structure of this paper I. Literature survey II. Technical Analysis and benefits III. future research and Conclusion.

## II. LITERATURE SURVEY

LoRa is a wireless Modulation or the physical layer. Most of the wireless system follows frequency shift keying [FSK] which is used to achieve low power. For creating a long-range communication and a low power most of the military and long-distance communication sector will follow the chirp spread spectrum [8]. For effective and robust modulation LoRa is also following the chirp spread spectrum. The long-range communication capability is the most important advantage of LoRa technology. By the help of base stations and gateway, LoRa technology can cover kilometers in a smart city area. Link budget [9] which is expressed in (dB) is the primary factor for measuring range in given environmental conditions. Compared to other technology LoRa has a greater link budget. For determining the range of LoRa in a particular environment, it mainly depends on the obstacles and constructions in the same area.

LoRa WAN is the communication protocol and LoRa is the physical layer which ensures long-range communication. The protocol determines security, network capacity and quality of service [10]. LoRaWAN WAN is technically not suitable for high bandwidth, like transmission of real-time video and images and is only suitable for sending data of 0.3kbps to 50 kbps. LoRa technology has long battery life. Which sends sensor data in IoT based systems and industrial applications[11].

### 1) LoRa classes

IEEE 802.15.4 is the protocol security of LoRa WAN. Every LoRaWAN node has its own App Key [12]. Three different classes of LoRaWAN are Class A, Class B, Class C.

- Class A devices need more Latency time and LoRa class A devices are more energy efficient which is used in many low powered sensor networks.
- Class B has time Synchronization with a beacon. It is also associated with low power devices but beacons will allow the end nodes about the listening period.
- Class C has low latency time but has maximum reception slots. These are bidirectional but need an external power supply.
- LoRa classification.

TABLE I. LORA CLASSIFICATION.

Class A [13]	Class B	Class C
Battery powered	Low latency	Low latency
End devices initiate communication	Ping slots	Server can initiate communication
At a predetermined response window, the server can communicate with the end device.	At a fixed interval of time, the server can initiate communication.	End devices are constantly receiving
Bidirectional	Bidirectional with receive slots.	Bidirectional
Small payload	Small payload	Small payload
Unicast	Unicast and multicast	Unicast and multicast

### 2) Analysis

The main aim of this section is to collect the significance and benefits of LoRa technology via many different applications shown in different papers[16]. The analysis of the comparative study shows LoRa technology has a large influence in IoT [19]. The outdoor range of LoRa is almost 10 to 15 km. Battery consumption is very less compared to other technologies but data throughput is low compared to Wi-Fi, GSM [20 22]. LoRa base station can handle thousands of end nodes at the same time but it has several security issues. Different research and surveys show that LoRa technology practically matches certain real-time requirements. Most of the work shows real field implementation of LoRa for monitoring environmental changes. All these techniques are IoT based works. Most of the smart city related papers show the implementation of LoRa technology in various sectors. Few papers show the sustainability of LoRa WAN technology and performance of LoRa devices outdoors [21] to measure different environmental conditions.




Fig.3 Comparative representation of Lora with other technologies.

Most of the studies in different papers show a comparative survey, paper [23-24] shows a comparative study between different classes of LoRa. Figure 3. Shows representation of LoRa with other technologies. When comparing other technologies such as sigfox, NB-IoT with LoRaWAN such as its architecture, security, LoRaWAN technology is a good choice[25]. A comparative analysis [26] shows that unlicensed LoRa has better performance in terms of capacity and battery lifetime but licensed NB- IoT shows advantages in terms of range and reliability. Compared to other technologies both LoRa and NB IoT could offer better performance. Security issues are discussed in [23,25] different studies. LoRa offers two layers of security, one for application and other for the network layer. But there are many security vulnerabilities in LoRa technology due to similar spread factor and frequency.

### 3) Technical details

Real deployment of LoRa in a test environment, for testing some technical features such as scalability and QoS [35 27 36 37 38] explained in a large number of papers. The testing of LoRa technology, especially LoRa technology is tested indoors and outdoors [39 40 41 42 27]. By measuring the packet delivery ratio LoRa can be tested. More studies can be discussed in the licence free ISM bands signals [43 36 44]. A number of LoRa devices were tested with the help of programming, some were modeled by software without any implementation, research studies shows the same.

## III. TECHNICAL ANALYSIS

### B. Network Architecture

Star architecture [15] is more suitable for LoRa than mesh network architecture. For long-range application star architecture preserve battery life. Mesh network architecture is deployed in many existing networks. While increasing range It adds more complexity to the system and it reduces battery lifetime.




Fig.4 System architecture.

In a LoRaWAN network end nodes will send data to multiple gateways and by cellular, Wi-Fi or any other medium gateway will forward data from the end node to distant cloud-based network server [17]. The network server will perform all other activities like security check, acknowledgement of the received packets. Figure 4 shows the overall the system architecture.

### D. Network Capacity

Data rate changes with the spreading factor. A gateway can receive multiple data rates on the same channel. Battery lifetime can be increased by proper use of data rate. All these make LoRaWAN a higher capacity network than other LPWAN networks. Compared to other LPWAN techniques LoRaWAN is a more scalable network. With minimal infrastructure, LoRaWAN can add more gateways and shift data rates. The high network capacity [18] in LoRaWAN is achieved by multichannel in the gateway and thereby simultaneous message transfer is possible. The main parameters depend on the network capacity are the number of channels, data rate and spreading factors which will change with data rate.

### A. Security

The LoRaWAN has 2 layers of security, one for the application layer and the other for the network layer. Authenticity [14] of a node assured by the network layer. application layer offers security to the application data of the end-user.

### C. Battery Lifetime

LoRaWAN networks are asynchronous; it will transfer data whenever it has data ready. This type of protocol is referred to as aloha. Unlike the synchronous network nodes frequently wake-up to check messages and the same will reduce battery lifetime compared to LoRaWAN.

## E. Applications

In many applications for real-time monitoring, LoRa is selected for long-range communication. Health care services like blood transfusion services [45] and some other health care services [40]. Monitoring road conditions by sensor nodes [46]. For cost-effective air conditioning, temperature difference and humidity changes in different rooms had to be monitored by different sensor units [47]. At the same time, air quality can be measured by various gas sensors [48]. LoRa modules are also used to monitor environmental information in the sea such as sailing of sea boats [30]. Reference [32] shows various geolocation tracking applications for livestock management. Tracking devices communicate with the gateway by LoRa [29]. For safety driving vehicles tracking is also possible by LoRa and gateway [49]. LoRa has been used effectively indoors and outdoors, health monitoring, environmental, tracking.

## H. Limitations and Benefits

### Limitations

- Small packets of data [52] in the kbps range can only be supported
- Sending video files better to go with Wi-Fi compared to LoRa
- Bluetooth or ZigBee is better for indoor home automation compared to LoRa
- Compared to LoRa, LTE/GPRS can be better for phone calls

### Benefits

TABLE II. BENEFITS OF LORA WAN.

Benefits	Explanations
Security[50]	Network layer and application layer security is defined.
Network capacity[51]	Simultaneous messages can be received on multiple channels. It is achieved by adaptive data rates[54].
Battery lifetime	Nodes communicate when it has to send data[52].
Classes	Three classes A, B, C has chosen depending on the device lifetime.

## IV. FUTURE SCOPE AND CONCLUSION

This Survey includes the research area in the performance and deployment of LoRa. Which is one of the major networking elements in many IoT applications. Paper mainly based on comparative analysis and trends in LoRa based communication in IoT. LoRa has many applications and future relevance in the field of IoT. As compared to other LPWAN techniques LoRa WAN has so many advantages like long battery life, long-range and low cost. One of the main limitations of LoRa is its low data rate. Technical details and analysis are briefly explained in this paper.

## V. ACKNOWLEDGMENT

Our sincere gratitude is expressed to our beloved Chancellor and world-renowned humanitarian leader Dr. Mata Amritanandamayi Devi (Amma), for the inspiration and motivation in all our endeavors. The authors would also like to acknowledge the contributions of Ms. Anjana M.S, Ph.D student of AmritaWNA.

## REFERENCES

- [1] D. Patel and M. Won, "Experimental Study on Low Power Wide Area Networks (LPWAN) for Mobile Internet of Things," 2017 IEEE 85th Vehicular Technology Conference (VTC Spring), Sydney, NSW, 2017, pp. 1-5.
- [2] Bashar, D. A. & "Review on sustainable green Internet of Things and its application." J. Sustain. Wireless Syst. 1, no. 4 (2020): 256-264.
- [3] LoRa Alliance Technical Marketing Workgroup, "A technical overview of LoRa and LoRaWAN," p. 20, 2015.
- [4] X. Tang, H. Li, Y. Zhang and X. Zhao, "Performance Analysis of LoRa Modulation with Residual Frequency Offset," 2018 IEEE 4th International Conference on Computer and Communications (ICCC), Chengdu, China, 2018, pp. 835-839.
- [5] M. El-Aasser, A. Gasser, M. Ashour and T. Elshabrawy, "Performance Analysis Comparison between LoRa and Frequency Hopping-based LPWAN," 2019 IEEE Global Conference on Internet of Things (GCIOT), Dubai, United Arab Emirates, 2019, pp. 1-6.
- [6] Y. Lu, Y. Liu, C. Hu, J. Xu, Z. Wang and S. Chen, "LoRa-based Communication Technology for Overhead Line Internet of Things," 2019 4th International Conference on Intelligent Green Building and Smart Grid (IGBSG), Hubei, Yi-chang, China, 2019, pp. 471-474.
- [7] [Online] Available: <https://lora-alliance.org/>
- [8] T. T. Nguyen, H. H. Nguyen, R. Barton and P. Grossetete, "Efficient Design of Chirp Spread Spectrum Modulation for Low-Power Wide-Area Networks," in IEEE Internet of Things Journal, vol. 6, no. 6, pp. 9503-9515, Dec. 2019.
- [9] N. H. Abd Rahman, Y. Yamada, M. H. Husni and N. H. Abdul Aziz, "Analysis of Propagation Link for Remote Weather Monitoring System through LoRa Gateway," 2018 2nd International Conference on Telematics and Future Generation Networks (TAFGEN), Kuching, 2018, pp. 55-60.
- [10] B. Robbe and W. Danny, "A QoS-Aware Adaptive Mobility Handling Approach for LoRa-Based IoT Systems," 2018 IEEE 12th International Conference on Self-Adaptive and Self-Organizing Systems (SASO), Trento, Italy, 2018, pp. 130-139.
- [11] [Online] Available: <https://www.semtech.com/lora/lora-applications>

- [12] K. Tsai, F. Leu, I. You, S. Chang, S. Hu and H. Park, "Low-Power AES Data Encryption Architecture for a LoRaWAN," in *IEEE Access*, vol. 7, pp. 146348-146357, 2019.
- [13] A. Zourmand, A. L. Kun Hing, C. Wai Hung and M. AbdulRehman, "Internet of Things (IoT) using LoRa technology," 2019 IEEE International Conference on Automatic Control and Intelligent Systems (2CACSIS), Selangor, Malaysia, 2019, pp. 324-330.
- [14] J. P. Shanmuga Sundaram, W. Du and Z. Zhao, "A Survey on LoRa Networking: Research Problems, Current Solutions, and Open Issues," in *IEEE Communications Surveys & Tutorials*, vol. 22, no. 1, pp. 371-388, Firstquarter 2020.
- [15] R. Li et al., "Applications of LoRa Technology in Smart Distribution Grid," 2019 IEEE 4th Advanced Information Technology, Electronic and Automation Control Conference (IAEAC), Chengdu, China, 2019, pp. 1554-1557.
- [16] Haoxiang, Wang. "Trust management of communication architectures of internet of things." *Journal of trends in Computer Science and Smart technology (TCSST)* 1, no.02 (2019): 121-130.
- [17] J. So, D. Kim, H. Kim, H. Lee and S. Park, "LoRaCloud: LoRa platform on OpenStack," 2016 IEEE NetSoft Conference and Workshops (NetSoft), Seoul, 2016, pp. 431-434.
- [18] M. Centenaro and L. Vangelista, "Boosting Network Capacity in LoRaWAN Through Time-Power Multiplexing," 2018 IEEE 29th Annual International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC), Bologna, 2018, pp. 1-6.
- [19] S. Wang et al., "Performance of LoRa-Based IoT Applications on Campus," 2017 IEEE 86th Vehicular Technology Conference (VTC-Fall), Toronto, ON, 2017, pp. 1-6.
- [20] S. C. Gaddam and M. K. Rai, "A Comparative Study on Various LPWAN and Cellular Communication Technologies for IoT Based Smart Applications," 2018 International Conference on Emerging Trends and Innovations In Engineering And Technological Research (ICETIETR), Ernakulam, 2018, pp. 1-8.
- [21] K. Lam, C. Cheung and W. Lee, "LoRa-based localization systems for noisy outdoor environment," 2017 IEEE 13th International Conference on Wireless and Mobile Computing, Networking and Communications (WiMob), Rome, 2017, pp. 278-284.
- [22] Murugesh, Remya, Aravind Hanumanthaiah, Ullas Ramanadhan, and Nirmala Vasudevan. "Designing a Wireless Solar Power Monitor for Wireless Sensor Network Applications." In 2018 IEEE 8th International Advance Computing Conference (IACC), pp. 79-84. IEEE, 2018.
- [23] V. A. Stan, R. S. Timnea, and R. A. Gheorghiu, "Overview of high reliable radio data infrastructures for public automation applications: LoRa networks," in 2016 8th International Conference on Electronics, Computers and Artificial Intelligence (ECAI). IEEE, pp. 1-4, 2016.
- [24] G. Aishwarya and R. Sujatha, "Analytical Study of Dedicated Network for IoT Using LoRaWAN Technologies," *International Research Journal of Engineering and Technology*, pp. 2395-56, 2017.
- [25] J. de Carvalho Silva, J. J. P. C. Rodrigues, A. M. Alberti, P. Solic, and A. L. L. Aquino, "LoRaWAN - A low power WAN protocol for Internet of Things: A review and opportunities," 2017 2nd International Multidisciplinary Conference on Computer and Energy Science (SpliTech), pp. 1-6, 2017.
- [26] R. S. Sinha, Y. Wei, and S.-H. Hwang, "A survey on LPWA technology: LoRa and NB-IoT," *ICT Express*, vol. 3, no. 1, pp. 14-21, 2017.
- [27] D. Magrin, M. Centenaro, and L. Vangelista, "Performance evaluation of LoRa networks in a smart city scenario," in 2017 IEEE International Conference on Communications (ICC). IEEE, , pp. 1-7 2017
- [28] S. Kumar, P. V. Rangan, and M. V. Ramesh, "Pilot deployment of early warning system for landslides in eastern himalayas," in *Proceedings of the Tenth ACM International Workshop on Wireless Network Testbeds, Experimental Evaluation, and Characterization - WiNTECH '16*, vol. 03-07-Octo. New York, New York, USA: ACM Press, pp. 97-99, 2016.
- [29] D. H. Kim, J. B. Park, J. H. Shin, and J. D. Kim, "Design and implementation of object tracking system based on LoRa," 2017 International Conference on Information Networking (ICOIN), pp. 463-467, 2017.
- [30] L. Li, J. Ren, and Q. Zhu, "On the application of LoRa LPWAN technology in Sailing Monitoring System," 2017 13th Annual Conference on Wireless On-Demand Network Systems and Services, WONS 2017 - Proceedings, pp. 77-80, 2017
- [31] W. San-Um, P. Lekbunyasim, M. Kodyoo, W. Wongsuwan, J. Makfak, and J. Kerd Sri, "A long-range low-power wireless sensor network based on U-LoRa technology for tactical troops tracking systems," in 2017 Third Asian Conference on Defence Technology (ACDT). IEEE, pp. 32-35, 2017.
- [32] B. C. Fargas and M. N. Petersen, "GPS-free geolocation using LoRa in low-power WANs," in 2017 Global Internet of Things Summit (GIoTS). IEEE, pp. 1-6, 2017.
- [33] V. Li Vigni, A. Di Stefano, R. Candela, and E. Riva Sanseverino, "A two-end traveling wave fault location system for MV cables based on LoRa technology," *Conference Proceedings - 2017 17th IEEE International Conference on Environment and Electrical Engineering and 2017 1st IEEE Industrial and Commercial Power Systems Europe, IEEEIC / I and CPS Europe 2017*, pp. 1-6, 2017.
- [34] O. Matthews, A. O. Ajala, A. A. Atayero, and S. I. Popoola, "Solar Photovoltaic Automobile Recognition System for Smart - Green Access Control using RFID and LoRa LPWAN technologies," *Journal of Engineering and Applied Sciences*, 2017.
- [35] O. Georgiou and U. Raza, "Low Power Wide Area Network Analysis: Can LoRa Scale?" *IEEE Wireless Communications Letters*, vol. 6, no. 2, pp. 162-165, 2017.
- [36] K. Mikhaylov, J. Petajajarvi, and J. Janhunen, "On LoRaWAN scalability: Empirical evaluation of susceptibility to inter-network interference," 2017 European Conference on Networks and Communications (EuCNC), pp. 1-6, 2017.
- [37] A. Dvornikov, P. Abramov, S. Efremov, and L. Voskov, "QoS Metrics Measurement in Long Range IoT Networks," 2017 IEEE 19th Conference on Business Informatics (CBI), vol. 2017, pp. 15- 20, 2017.
- [38] T. Petric, M. Goessens, L. Nuaymi, L. Toutain, and A. Pelov, "Measurements, performance and analysis of LoRa FABIAN, a real-world implementation of LPWAN," in 2016 IEEE 27th Annual International Symposium on Personal, Indoor, and Mobile Radio Communications (PIMRC). IEEE, pp. 1-7, 2016.
- [39] L. Gregora, L. Vojtech, and M. Neruda, "Indoor Signal Propagation of LoRa Technology," 2016 17th International Conference on Mechatronics - Mechatronika (ME), pp. 13-16, 2016.
- [40] J. Petajajarvi, K. Mikhaylov, M. Hamalainen, and J. Iinatti, "Evaluation of LoRa LPWAN technology for remote health and wellbeing monitoring," 2016 10th International Symposium on Medical Information and Communication Technology (ISMICT), pp. 1-5, 2016.
- [41] M. Aref and A. Sikora, "Free space range measurements with Semtech LoraTM technology," pp. 19-23, 2014.
- [42] A. J. Wixted, P. Kinnaird, H. Larijani, A. Tait, A. Ahmadi, and N. Strachan, "Evaluation of LoRa and LoRaWAN for wireless sensor networks," in 2016 IEEE SENSORS, vol. 0. IEEE, pp. 1-3, 2016.
- [43] J. Haxhibeqiri, F. Van den Abeele, I. Moerman, and J. Hoebeke, "LoRa Scalability: A Simulation Model Based on Interference Measurements," *Sensors*, vol. 17, no. 6, p. 1193, 2017.
- [44] M. Lauridsen, B. Vejlgaard, I. Z. Kovacs, H. Nguyen, and P. Mogensen, "Interference Measurements in the European 868 MHz ISM Band with Focus on LoRa and SigFox," in 2017 IEEE Wireless Communications and Networking Conference (WCNC). IEEE, pp. 1-6, 2017.
- [45] G. S. Ramachandran, F. Yang, P. Lawrence, S. Michiels, W. Joosen, and D. Hughes, "PnP-WAN: Experiences with LoRa and its deployment in DR Congo," in 2017 9th International Conference on Communication Systems and Networks (COMSNETS). IEEE, pp. 63-70, 2017.
- [46] F. Orfei, C. Benedetta Mezzetti, and F. Cottone, "Vibrations powered LoRa sensor: An electromechanical energy harvester working on a real bridge," *Proceedings of IEEE Sensors*, pp. 51- 53, 2017.
- [47] M. Centenaro, L. Vangelista, A. Zanella, and M. Zorzi, "Long Range communications in unlicensed bands: the rising stars in the IoT and

- smart city scenarios," IEEE Wireless Communications, vol. 23, no. 5, pp. 60–67, oct 2016
- [48] S. Liu, C. Xia, and Z. Zhao, "A Low-power Real-time Air Quality Monitoring System Using LPWAN based on LoRa," pp. 3–5, 2016.
  - [49] Y.-S. Chou, Y.-C. Mo, J.-P. Su, W.-J. Chang, L.-B. Chen, J.-J. Tang, and C.-T. Yu, "i-Car system: A LoRa-based low power wide area networks vehicle diagnostic system for driving safety," in 2017 International Conference on Applied System Innovation (ICASI). IEEE, pp. 789–791, 2017.
  - [50] B. Oniga, V. Dadarlat, E. De Poorter and A. Munteanu, "Analysis, design and implementation of secure LoRaWAN sensor networks" 2017 13th IEEE International Conference on Intelligent Computer Communication and Processing (ICCP), Cluj-Napoca, 2017, pp. 421–428.
  - [51] U. Noreen, A. Bounceur and L. Clavier, "A study of LoRa low power and wide area network technology," 2017 International Conference on Advanced Technologies for Signal and Image Processing (ATSIP), Fez, 2017, pp. 1–6.
  - [52] Liya, M. L., Shaji, A., Jayakrishnan, V. M., & Nair, A. (2017, August). Petal shaped semicircular resonator for RFID tags. In 2017 IEEE International Conference on Smart Technologies and Management for Computing, Communication, Controls, Energy and Materials (ICSTM) (pp. 313–316). IEEE.
  - [53] Liya, M. L., Jayakrishnan, V. M., & Menon, S. K. (2017, March). Investigations on microstrip patch as band pass filter. In 2017 International Conference on Wireless Communications, Signal Processing and Networking (WiSPNET) (pp. 365–367). IEEE.
  - [54] Rajeswaran, D., & Nair, A. K. (2016, February). MIMO Interference rejection in MIMO-Beamforming Systems. In 2016 3rd International