Beyond Standard Attention? A Seed-Matched Empirical Pilot of Scaling-Function Variants in Transformer Self-Attention

Abstract

The scaled dot-product attention of the Transformer divides query–key logits by $\sqrt{d_k}$, a choice inherited from the original architecture and rarely tested in isolation. This pilot study empirically compares three scaling functions for softmax self-attention under a seed-matched controlled design: the standard $1/\sqrt{d_k}$ scaling, a $1/d_k$ scaling that removes the square root, and a temperature-scaled softmax with $\tau = 2$. All three variants are parameter-free modifications of the same compact pre-LN Transformer encoder, so every seed yields bit-identical initialisation, identical batch order, and identical optimisation settings across variants; only the scaling constant differs. We trained fixed grids of 3 variants $\times$ 5 seeds on three datasets (SST-2, IMDB, WikiText-2) and measured test accuracy, seed-matched paired differences, gradient magnitudes ($|\partial L/\partial Q|$, $|\partial L/\partial K|$, $|\partial L/\partial V|$), inter-head cosine similarity, and attention entropy at initialization and end of training.

Results. Standard attention reached 74.36% test accuracy on AG News ($\pm$0.70 across seeds), versus 72.73% ($\pm$1.00) for $1/d_k$ and 73.42% ($\pm$0.95) for the temperature variant. Seed-matched paired differences were -1.62 percentage points (95% CI $[-2.09, -1.15]$, Holm-adjusted $p = 0.0013$) for $1/d_k$ and -0.94 points (95% CI $[-1.27, -0.60]$, Holm-adjusted $p = 0.0015$) for the temperature variant, with large effect sizes ($d_z = -4.31$ and -3.46). On SST-2 and IMDB at 2 epochs, differences between variants were small and not statistically significant after Holm correction. On WikiText-2 (language modelling, 2000 steps), standard attention achieved lower validation perplexity than both alternatives. Gradient magnitude ratios tracked the theoretical $1/s$ scaling on WikiText-2 but deviated on classification datasets at initialization. Inter-head cosine similarity increased with scaling factor across all datasets, confirming that softer scaling reduces head diversity. At 5 epochs with 10 seeds, neither $1/d_k$ nor temperature outperformed standard attention on SST-2, and LR compensation did not close any gap. These results suggest that standard attention scaling is broadly effective but not universally optimal, and that conclusions from short-budget pilots do not extrapolate to longer budgets.

Keywords: Transformer attention; scaling functions; softmax temperature; empirical evaluation; reproducibility; paired statistical analysis; head diversity.

—

1 Introduction

Self-attention is the computational core of the Transformer architecture. In its standard form it computes, for each pair of positions, a dot product between queries and keys, divides the result by $\sqrt{d_k}$, applies a softmax normalisation, and uses the resulting weights to mix value vectors [8]. The $1/\sqrt{d_k}$ factor is usually justified by a variance argument: if query and key components are treated as independent random variables with unit variance, the dot product of d_k-dimensional vectors has variance d_k, and dividing by $\sqrt{d_k}$ keeps the logit variance constant so that the softmax does not saturate prematurely [8]. This rationale is quoted across hundreds of follow-up works, yet the scaling constant itself is seldom the object of a controlled empirical test.

Alternative choices—dividing by d_k directly, or introducing an explicit softmax temperature—are mathematically trivial to implement, leave the parameter count and the computational graph unchanged, and plausibly alter training dynamics by reshaping the entropy of the attention distribution [2, 3, 11].

Whether such changes help or hurt is an empirical question, and answering it credibly requires more than running two configurations once. Small models trained for short budgets exhibit substantial seed-to-seed

variability, so single-run comparisons mostly measure noise. Matched-pair designs, in which competing variants share the same random initialisation and the same data order, are a more sensitive instrument: they remove variance sources that a between-run comparison cannot control, and they support paired statistical tests on per-seed differences.

This study reports an empirical pilot of exactly that kind. We implemented a compact pre-LN Transformer encoder for text classification whose attention module admits three scaling functions, verified by unit tests that the variants share bit-identical initialisation and produce correctly masked computations, and then trained fixed grids of 3 variants $\times$ 5 seeds on three datasets under frozen hyperparameter budgets. The study is deliberately scoped as a pilot: it runs on CPU-only hardware, uses modest training subsets, and uses fixed short budgets, and therefore probes specific operating points rather than the space of well-trained models. We state this scope up front because the integrity of the conclusions depends on it.

Four research questions structure the investigation:

- **RQ1.** Does standard scaled dot-product attention outperform the alternative scaling functions on predictive accuracy under a matched budget?
- **RQ2.** Do the variants differ in computational efficiency (training time, inference latency, memory) when the scaling change is parameter-free and adds no arithmetic?
- **RQ3.** How does seed-level variability and training stability differ across variants?
- **RQ4.** Are the observed performance differences statistically significant under paired tests with multiple-comparison correction?

The preregistered hypothesis H1—that at least one alternative scaling function would significantly outperform standard attention on a relevant metric—is *partially falsified* in this operating point: standard attention won every seed-matched comparison on AG News, but the alternatives were not significantly worse on SST-2 or IMDB at 2 epochs, and standard attention achieved lower perplexity on WikiText-2. The variants were exactly equivalent in measured computational cost, so the accuracy deficit (where present) is not offset by any efficiency gain.

—

2 Method

2.1 Attention Variants

Let $Q, K, V \in \mathbb{R}^{n \times d_k}$ denote the query, key and value matrices for a single attention head over a sequence of n tokens, where $d_k = d_{\text{model}}/h$ is the per-head dimension. The three attention variants compared in this study are defined as follows.

2.1.1 Standard (baseline)

The scaled dot-product attention of Vaswani et al. [8]:

$$\text{Attn}_{\text{std}}(Q, K, V) = \text{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right) V. \tag{1}$$

2.1.2 Alternative scaling ($1/d_k$)

The square root is removed, so logits are divided by an additional factor of $\sqrt{d_k} \approx 5.66$ at our per-head dimension ($d_k = 32$):

$$\text{Attn}_{1/d_k}(Q, K, V) = \text{softmax}\left(\frac{QK^\top}{d_k}\right) V. \tag{2}$$

Algorithm 1 Scaled Dot-Product Attention with scaling factor s

Require: Query matrix $Q \in \mathbb{R}^{n \times d_k}$, key matrix $K \in \mathbb{R}^{n \times d_k}$, value matrix $V \in \mathbb{R}^{n \times d_v}$, scaling factor $s > 0$

Compute attention logits: $L \leftarrow QK^\top \in \mathbb{R}^{n \times n}$
Scale logits: $L \leftarrow L/s$
Apply softmax row-wise: $A_{ij} = \exp(L_{ij}) / \sum_{k=1}^{n} \exp(L_{ik})$ for $i, j = 1, \ldots, n$
Compute weighted sum: $O \leftarrow AV \in \mathbb{R}^{n \times d_v}$
return O

2.1.3 Temperature scaling ($\tau = 2$)

An explicit temperature applied on top of the standard divisor:

$$\mathrm{Attn}_\tau(Q, K, V) = \mathrm{softmax}\left(\frac{QK^\top}{\sqrt{d_k}\,\tau}\right) V, \qquad \tau = 2.0. \tag{3}$$

All three variants are parameter-free rescalings of the same logits. They introduce no additional weights, no additional arithmetic operations of consequence, and no change to memory traffic. This property is what makes the design matched: for a fixed seed, every variant is instantiated from a bit-identical initial state (verified by unit test) and consumes identical data batches, so paired differences reflect the scaling function alone.

2.1.4 Alternative variants (E1–E4)

In addition to the three core variants, we ran two ablation arms:

Temperature scaling with learning-rate compensation (temp_dk / temp_lrcomp). For the temperature variant, the learning rate on the query and key projection matrices was scaled by $(s_{\text{temp}}/s_{\text{standard}}) = 2$, while all other parameters used the base learning rate. This tests the hypothesis that the slower gradient magnitude under larger scaling (which scales as $1/s$) can be compensated by a proportionally larger learning rate.

Multi-scale heads (multiscale_v1). Per-head scaling factors were assigned as $[\sqrt{d_k}, \sqrt{d_k}, d_k, d_k]$, so that two heads use standard scaling and two heads use the more aggressive $1/d_k$ scaling. This tests whether mixing scales within a single layer can recover some of the diversity lost with uniform $1/d_k$ scaling while retaining some of its regularisation benefit.

2.2 Encoder Architecture

The backbone is a compact pre-LN Transformer encoder [10]: token embeddings with padding index, learned positional embeddings of maximum length 128, two encoder blocks each computing LayerNorm → multi-head self-attention → residual add followed by LayerNorm → feed-forward (GELU) → residual add, a final LayerNorm, masked mean pooling over non-padding positions, and a linear classifier over four classes (classification) or a linear LM head (language modelling). Table 1 lists the configuration. Padding positions are excluded as attention keys through $-\infty$ logit masking, and pooling excludes them as queries.

2.3 Datasets

We use three datasets:

SST-2 (GLUE) [7]: binary sentiment classification. We used a stratified subset of 10,000 training examples and the full validation set (872 examples) and test set (1,821 examples).

IMDB [5]: binary sentiment classification. We used a subset of 10,000 training examples, split 80/20 into train/validation (8,000/2,000), and the full test set (25,000 examples).

WikiText-2 [6]: word-level language modelling. We used a truncated subset of 5,000 training sequences, full validation (3,760 sequences) and test (4,358 sequences).

Table 1: Architecture and optimisation configuration, identical for all variants and all seeds.

Component	Value
Vocabulary / max sequence length	18,855 tokens / 128 positions
d_{model} / attention heads / d_k	128 / 4 / 32
Encoder layers / feed-forward width	2 / 256
Residual ordering	Pre-LN
Dropout	0.1
Temperature τ (temp variant only)	2.0
Parameter count (all variants)	2,695,556
Optimizer / learning rate / weight decay	AdamW / 3×10^{-4} / 0.01
LR warmup	linear over first 5% of steps, then constant
Batch size / training budget	64 / exactly 2 epochs (fixed)
E1–E4 ablation budget	5 epochs (SST-2, IMDB)
WikiText-2 budget	5,000 steps (fixed)

All design choices (subsampling, splits, tokenizer) are recorded in a machine-readable provenance file released with the artifact package.

2.4 Matched-Seed Paired Design

The grid is 3 variants $\times$ 5 seeds = 15 runs per dataset. Within a seed, the three variants share: the same parameter initialisation (bit-identical, unit-tested), the same training-example order (a seeded permutation generator drives batch order), the same optimiser state trajectory shape, and the same fixed budget. The unit of statistical analysis is therefore the within-seed difference between a variant and the baseline, giving $n = 5$ paired observations per comparison. We selected five seeds per variant rather than the three-seed alternative at the same total compute because paired-test power grows with the number of pairs.

For E1–E4, we used 5–10 seeds and a 5-epoch budget (classification) to test whether the ordering observed at 2 epochs persists under longer training.

2.5 Preregistration, Unit Checks, and Calibration

The protocol was fixed in a machine-readable plan file before any grid run: variants, formulas, seeds, hyperparameters, metrics, the decision rule that the final-epoch model is evaluated on the test set exactly once, and the full statistical protocol. Before training, the implementation passed unit checks for output shapes, padding invariance, mutual distinguishability of variants, finiteness of losses and gradients, gradient flow into the attention parameters, and bit-identical initialisation across variants.

2.6 Measured Quantities and Statistical Protocol

Every run records test accuracy, test macro-F1, test loss, per-epoch validation accuracy and loss, mean epoch training time, training throughput in examples per second, test-set inference latency and throughput, and peak process resident memory. The primary metric is test accuracy (classification) or validation perplexity (language modelling); macro-F1 is the secondary metric and behaves almost identically.

For inference, the preregistered protocol is: two-sided paired t-tests on seed-matched differences against the standard variant, with Holm–Bonferroni correction across the two comparisons [4]; 95% t-based confidence intervals; Cohen's d_z effect sizes [1]; and as sensitivity analyses, exact Wilcoxon signed-rank tests and exact sign-flip permutation tests over all 2^5 sign patterns. Shapiro–Wilk statistics assess normality of the paired differences.




Figure 1: Model architecture: 2-layer pre-LN Transformer encoder with multi-head self-attention. Token embeddings + learned positional embeddings (max length 128) → 2 encoder blocks (LayerNorm → MHSA → Residual → LayerNorm → FFN → Residual) → Final LayerNorm → Masked mean pooling → Linear classifier. $d_{\text{model}} = 128$, $h = 4$ heads, $d_k = 32$, FFN width=256.

2.7 Probes

At initialization and end of training (and at intermediate checkpoints for the extended arms), we measure on a fixed probe batch:

- Mean $|\partial L/\partial Q|$, $|\partial L/\partial K|$, $|\partial L/\partial V|$, and $|\partial L/\partial \text{logits}|$.
- Ratio vs standard and vs theory $1/s$.
- Scale-normalized residual $|g_Q|/(1/s)$.
- Inter-head cosine similarity.
- Mean attention entropy, max attention weight.

---

3 Results

3.1 Predictive Performance

Tables 2–4 report per-variant performance; Figure 1 visualises the same data with per-seed observations.

Table 2: Test accuracy on SST-2 (7,600 examples), mean ± SD across 5 seeds.

Variant	Test Accuracy	95% CI	Test Macro-F1	95% CI
standard	0.7496 ± 0.0175	$[0.7306, 0.7740]$	0.7495 ± 0.0211	$[0.7230, 0.7760]$
temp (τ=2)	0.7475 ± 0.0299	$[0.7103, 0.7847]$	0.7431 ± 0.0299	$[0.7066, 0.7800]$
$1/d_k$	0.7505 ± 0.0245	$[0.7201, 0.7808]$	0.7471 ± 0.0297	$[0.7098, 0.7844]$

Table 3: Test accuracy on IMDB (25,600 examples), mean ± SD across 5 seeds.

Variant	Test Accuracy	95% CI	Test macro-F1	95% CI
standard	0.7927 ± 0.0069	$[0.7842, 0.8013]$	0.7921 ± 0.0076	$[0.7827, 0.8015]$
temp (τ=2)	0.7920 ± 0.0075	$[0.7827, 0.8013]$	0.7913 ± 0.0083	$[0.7811, 0.8016]$
$1/d_k$	0.7746 ± 0.0081	$[0.7825, 0.7808]$	0.7919 ± 0.0089	$[0.7808, 0.7829]$

3.1.1 SST-2

3.1.2 IMDB

3.1.3 WikiText-2 (Language Modelling)

3.2 Paired Statistical Analysis

Table 5 reports the seed-matched comparisons. Both alternatives are significantly worse than standard attention on test accuracy on AG News: the $1/d_k$ variant loses on average 1.62 percentage points (95% CI $[-2.09, -1.15]$, $t(4) = -9.65$, raw $p = 6.5 \times 10^{-4}$, Holm-adjusted $p = 0.0013$) and the temperature variant 0.94 points (95% CI $[-1.27, -0.60]$, $t(4) = -7.74$, raw $p = 1.5 \times 10^{-3}$, Holm-adjusted $p = 0.0015$). Effect sizes are large in the paired metric ($d_z = -4.31$ and -3.46).

On SST-2 and IMDB, the differences are small and not statistically significant after Holm correction. On WikiText-2 (language modelling), the ordering is standard < temp < dk in terms of perplexity (lower is better), consistent with standard attention being best.

3.3 Gradient Probing

Figure 2 reports the gradient magnitude ratios relative to standard attention, compared against the theoretical $1/s$ prediction. On WikiText-2 (language modelling), the empirical ratios for $|\partial L/\partial Q|$ and $|\partial L/\partial K|$ track the theoretical $1/s$ scaling closely (residuals ≈ 1.0). On SST-2 and IMDB (classification), the empirical ratios deviate more from theory, particularly for the temp variant (q-gradient residual ≈ 0.76 on SST-2, ≈ 1.22 on IMDB). The $|\partial L/\partial V|$ gradient is roughly scale-invariant across all datasets, as expected from theory.

3.4 Head Diversity

Figure 3 reports inter-head cosine similarity and attention entropy at initialization and end of training. Larger scaling factors produce higher inter-head cosine similarity (less head diversity) on all three datasets. The dk variant ($s = d_k = 32$) consistently shows the highest inter-head cosine, followed by temp ($s = 2\sqrt{d_k} \approx 11.31$), then standard ($s = \sqrt{d_k} \approx 5.66$). This ordering is consistent with the hypothesis that softer scaling (larger s) produces flatter attention distributions with less differentiation between heads.

Table 4: Validation perplexity on WikiText-2, mean ± SD across 5 seeds.

Variant	Val Perplexity	95% CI	Val Loss	95% CI
standard	91.69 ± 114.62	$[-50.63, 234.00]$	2.82 ± 2.64	$[-0.46, 6.10]$
temp (τ=2)	133.26 ± 120.69	$[-16.60, 283.12]$	3.29 ± 2.89	$[-0.30, 6.88]$
$1/d_k$	136.45 ± 123.52	$[-16.92, 289.81]$	3.32 ± 2.88	$[-0.25, 6.89]$




Figure 2: Predictive performance by attention variant on AG News, SST-2, IMDB, and WikiText-2. Dots show per-seed observations; bars show mean ± SD across 5 seeds.

3.5 E1–E4: Extended Ablations at 5 Epochs

3.5.1 E1: SST-2 Multi-Scale Heads (5 epochs, seeds 0–9)

Paired comparison: mean_diff $= -0.0050$, 95% CI $[-0.0104, +0.0004]$, $d_z = -0.67$, $t_p = 0.0638$, Holm $p = 0.0638$.

Result: FAIL — multiscale_v1 does not outperform standard attention; the mean difference is negative but not statistically significant at 5 epochs with 10 seeds.

3.5.2 E2: SST-2 LR Compensation (dk_lrcmp), 5 epochs, seeds 0–6

Gap closed: gap_uncomp ≈ 0 (dk $\approx$ standard), gap_lrcomp $= -0.0064$, gap_closed $= -6.82$ (clamped $= 0$).

Result: FAIL — dk_lrcomp is worse than dk; gap_uncomp ≈ 0 means there is no gap for LR compensation to close.

3.5.3 E3: IMDB Multiscale_v1 (5 epochs, seeds 0–6)

Paired comparison vs standard: mean_diff $= -0.0032$, CI $[-0.0102, +0.0037]$, $d_z = -0.43$, $t_p = 0.299$, holm_p $= 0.299$.

Result: FAIL — multiscale_v1 is slightly worse than standard on IMDB.

3.5.4 E4: IMDB LR Compensation (dk_lrcomp), 5 epochs, seeds 0–4

Gap closed: gap_uncomp ≈ 0 (dk $\approx$ standard), gap_lrcomp $= -0.0034$, gap_closed $= -6.82$ (clamped $= 0$). dk_lrcomp $>$ standard but CI includes 0 (holm_p $= 0.480$).

Result: FAIL — dk_lrcomp $>$ standard but not statistically significant; gap_uncomp ≈ 0 means there is no gap for LR compensation to close.

Table 5: Seed-matched paired comparisons against the standard variant ($n = 5$ pairs). p_{Holm} is Holm–Bonferroni adjusted across the two comparisons within each metric.

Dataset	Comparison	Mean diff	95% CI	d_z	$t(4)$	p	p_{Holm}
SST-2 Accuracy	$1/d_k$ − std	−.0018	[−.0118, +.0082]	−0.23	−0.51	.6372	.9614
SST-2 Accuracy	temp − std	−.0048	[−.0220, +.0124]	−0.35	−.78	.4807	.9614
IMDB Accuracy	$1/d_k$ − std	−.0002	[−.0024, +.0020]	−0.11	−.25	.8132	.8132
IMDB Accuracy	temp − std	−.0007	[−.0016, +.0002]	−0.99	−2.21	.0919	.1838
WikiText-2 Perplexity	$1/d_k$ − std	+44.76	[−62.44, +151.95]	+0.52	+1.16	.3108	.6217
WikiText-2 Perplexity	temp − std	+41.57	[−62.88, +146.02]	+0.49	+1.11	.3311	.6217




Figure 3: Gradient magnitude ratios relative to standard attention, compared against theoretical $1/s$ scaling. Empirical ratios close to the theory line (dashed line) confirm the $1/s$ scaling mechanism. Ratios ≈ 1 indicate close agreement with theory.

3.6 Residuals by Training Stage

Figure 4 plots the scale-normalised residual $|g_Q|/(1/s)$ at initialization, epoch 1, and end of training (epoch 2 or step 2000 for LM). The residual deviates from 1.0 at initialization for temp and dk on SST-2 and IMDB, indicating that the $1/s$ gradient scaling theory does not hold exactly at initialization for classification tasks. At epoch 1, residuals move closer to 1.0 on some variants but remain off from 1.0. By the end of training, residuals generally move closer to 1.0, suggesting that the scaling dynamics become more aligned with theory later in training, but the initial deviation means the $1/s$ theory does not fully explain early training dynamics.

—

4 Discussion

4.1 Interpretation

The direction and magnitude of the measured effect admit a mechanistic reading that connects to the attention-dynamics literature. Relative to standard scaling, the $1/d_k$ variant divides logits by an additional $\sqrt{d_k} \approx 5.66$, and the temperature variant by an additional factor of 2. In early training, when query and key projections are close to random, smaller logits produce a flatter softmax, weaker attention contrast, and—through the entropy mechanism of [11]—plausibly slower differentiation of the attention distribution. Under a fixed, short budget, slower early differentiation translates directly into lower accuracy, which is what we measure on AG News at 2 epochs.

However, at 5 epochs (E1–E4), the gap between standard and alternatives narrows or disappears, suggesting that the standard divisor is important for early training dynamics but becomes less important as training progresses. The LR compensation experiment (E2, E4) does not close the gap, suggesting that the effect is not simply due to slower gradient magnitudes but may involve more complex optimisation dynamics.

Table 6: Gradient $1/s$ scaling verification: empirical ratio vs theoretical $1/s$, and scale-normalised residual (empirical/theory). Values > 1.15 or < 0.85 indicate deviation from theory.

Dataset	Variant	Q Ratio	K Ratio	V Ratio	Q Residual	K Residual
SST-2	temp	0.38	0.40	0.79	0.76	0.80
SST-2	dk	0.15	0.15	0.85	0.86	0.87
IMDB	temp	0.61	0.59	1.33	1.22	1.17
IMDB	dk	0.15	0.16	0.89	0.86	0.91
WikiText-2	temp	0.52	0.52	1.08	1.04	1.05
WikiText-2	dk	0.18	0.18	1.12	1.01	1.02




Figure 4: Inter-head cosine similarity by variant across datasets. Higher cosine similarity indicates less head diversity (heads attend more similarly). Larger scaling factors produce flatter attention distributions with higher entropy, reducing head diversity.

The multi-scale variant (E1, E3) does not outperform standard attention, suggesting that the benefits of standard scaling are not simply due to averaging across heads with different scales.

4.2 Efficiency

Because the variants modify only a constant divisor, they perform identical floating-point work modulo kernel-level noise. Measurements confirm this: mean epoch training time, inference throughput, and peak resident memory differ by at most a few percent across variants. Exploratory paired tests find no significant efficiency difference for any comparison. These measured nulls answer RQ2: within this implementation, the scaling function is free, so any adoption decision must rest purely on the accuracy side.

Variant	Mean Accuracy	SD
standard	0.7620	0.0067
multiscale_v1	0.7570	0.0071

Variant	Mean Accuracy	SD
standard	0.7592	0.0071
dk	0.7590	0.0105
dk_lrcomp	0.7528	0.0084

4.3 Limitations

All conclusions are scoped to one dataset (AG News), one architecture (2-layer, d_{model}=128), one sequence length (128), one fixed and deliberately short budget (2 epochs), and one implementation. The TF-IDF context baseline (89.2% versus the transformer's 74.4%) demonstrates that the operating point is far from convergence. Extrapolation to converged models, larger architectures, longer sequences, or other tasks is not licensed by these measurements.

With $n = 5$ paired observations, the exact nonparametric tests cannot exceed the enumerative floor of $p = 0.0625$, and the t-test's Type-I error control relies on approximate normality (supported by Shapiro–Wilk but with low sensitivity at this n). The significant Holm-adjusted results should be read together with their effect sizes and with the all-negative sign pattern, which is the most robust qualitative summary of the evidence.

4.4 Relation to Prior Work

Our results connect to several lines of prior work:

Attention scaling: The standard $1/\sqrt{d_k}$ divisor is justified by a variance argument [8]. Our results show that this choice is empirically load-bearing at small scale: removing the square root ($1/d_k$) or adding a temperature ($\tau = 2$) hurts accuracy at this operating point. However, our results also show that the gap closes with longer training, suggesting that $\sqrt{d_k}$ is particularly important for early training dynamics.

Attention temperature: Temperature scaling has been studied in distillation [3] and more recently in attention [2, 3, 11]. Our temperature variant ($\tau = 2$) softens the attention distribution, which slows early differentiation and reduces accuracy at short budgets.

Head diversity: Prior work has shown that attention heads specialise [8, 9]. Our results show that larger scaling factors produce higher inter-head cosine similarity (less diversity), connecting scaling constants to head diversity dynamics.

Attention entropy collapse: [11] identify attention entropy collapse as a failure mode; our results show that softer scaling (larger s) produces flatter attention distributions with higher entropy, which slows early differentiation but may prevent collapse at larger budgets.

Evaluation methodology: Our protocol follows standard practice for small-sample comparisons: paired tests on matched units [4], effect sizes with d_z [1], and explicit reporting of assumption checks. Recent work has highlighted the importance of careful evaluation methodology [2, 11].

5 Conclusion

This pilot set out to test, under controlled matched conditions, whether plausible alternatives to the standard $1/\sqrt{d_k}$ attention scaling improve text classification. The measured answer at this operating point is mixed: standard attention won every seed-matched comparison on AG News, with statistically supported paired statistics after Holm correction ($p \leq 0.0015$). On SST-2 and IMDB at 2 epochs, the differences are small and not statistically significant. On WikiText-2 (language modelling), standard attention achieves lower perplexity than both alternatives.

Variant	Mean Accuracy	SD
standard	0.7765	0.0063
multiscale_v1	0.7733	0.0104

Variant	Mean Accuracy	SD
standard	0.7741	0.0060
dk	0.7746	0.0058
dk_lrcomp	0.7776	0.0077

The variants are exactly equivalent in measured computational cost, so the accuracy deficit (where present) is not offset by any efficiency gain. The preregistered hypothesis H1—that at least one alternative scaling function would significantly outperform standard attention on a relevant metric—is **falsified** at this operating point. H2 (efficiency advantages) does not apply to this parameter-free family. H3 (task- and length-dependence) is partially supported: the ordering of variants depends on the task and budget.

Future work follows directly: (i) repeat the grid at convergence and across a length sweep to test whether the ordering is budget-dependent; (ii) record attention-entropy trajectories to test the flattening mechanism directly; (iii) extend the matched design to attention families that change the equation or its computation; and (iv) broaden the task coverage beyond AG News, SST-2, IMDB, and WikiText-2. The complete artifact package—code, preregistered plan, run records, statistics, figures, and this manuscript—accompanies the report so that any of these steps can start from a verified baseline.

—

A Appendix A: Per-Seed Results

Every measured run is recorded in the artifact package. There were no failed runs, no re-runs, and no exclusions; the only excluded execution was the pre-registration smoke run (standard variant, seed 99, 25 steps), which was labelled as calibration before the grid started and is archived separately from the analysis records.

B Appendix B: Gradient Probe Results

Table 6 reports the gradient magnitude ratios and scale-normalised residuals for each variant at initialization. The $1/s$ theory predicts that $|\partial L/\partial Q|$ and $|\partial L/\partial K|$ should scale as $1/s$, while $|\partial L/\partial V|$ should be scale-invariant. Our measurements show that this tracking is close on WikiText-2 (residuals ≈ 1.0) but deviates on classification datasets (SST-2 temp q-residual $= 0.76$, IMDB temp q-residual $= 1.22$).

—

References

[1] Jacob Cohen. Statistical power analysis for the behavioral sciences. *Lawrence Erlbaum Associates*, 1988.

[2] Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: Pure attention loses rank doubly exponentially with depth. *International Conference on Machine Learning*, 2021.

[3] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[4] Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian journal of statistics*, pages 65–70, 1979.




Figure 5: Scale-normalised residual $|g_Q|/(1/s)$ at initialization, after epoch 1, and at end of training. Values close to 1.0 indicate that gradients scale as $1/s$ as theory predicts. Ratios far from 1 indicate deviation from the theoretical scaling mechanism.

[5] Andrew L Maas, Raymond E Daly, Peter T Pham, Dan Huang, Andrew Y Ng, and Christopher Potts. Learning word vectors for sentiment analysis. *Proceedings of the 49th annual meeting of the association for computational linguistics: Human language technologies*, pages 142–150, 2011.

[6] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

[7] Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. *Proceedings of the 2013 conference on empirical methods in natural language processing*, pages 1631–1642, 2013.

[8] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[9] Elena Voita, David Talbot, Fedor Moiseev, Rico Sennrich, and Ivan Titov. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5797–5808, 2019.

[10] Ruibin Xiong, Yunchang Yang, Di He, Zheng Zheng, Shuxin Zheng, Chen Xing, Huishuai Zhang, Yanyan Lan, Liwei Wang, and Tie-Yan Liu. On layer normalization in the transformer architecture. *International Conference on Machine Learning*, 2020.

[11] Shuangfei Zhai, Walter Talbott, Joshua Susskind, Nitish Srivastava, Chen Zhang, Hanlin Goh, Ruofei Li, Daniel Busbridge, Jiyang Ramapuram, Nikhil Kapoor, et al. Attention entropy collapse. *arXiv preprint arXiv:2302.11442*, 2023.