

Configuration Options

Jeff Valore
CodingWithSpike.wordpress.com
@CodingWithSpike



pluralsight 
hardcore dev and IT training

Configuration Options

<http://requirejs.org/docs/api.html#config>

Covered in this course:

- `baseUrl`
- `paths`
- `shim`
- `config`
- `waitSeconds`
- `deps & callback`
- `urlArgs`

Not covered in this course:

- `bundles`
- `map`
- `packages`
- `nodeIdCompat`
- `context`
- `enforceDefine`
- `xhtml`
- `scriptType`
- `skipDataMain`

Configuration Option

baseUrl



Documentation:

The root path to use for all module lookups.

baseUrl Priority

1. The **baseUrl** specified in the configuration.
2. If **data-main** attribute used, baseUrl set to the path of the file specified by data-main.
3. The path of the **HTML page** that loads require.js.

Configuration Option

paths




Documentation:

Path mappings for module names not found directly under **baseUrl**. The path settings are assumed to be relative to **baseUrl**, unless the paths setting starts with a "/" or has a URL protocol in it ("like http:").

Configuration Option

shim



Documentation:

Configure the dependencies, exports, and custom initialization for older, traditional "**browser globals**" scripts that do not use **define()** to declare the dependencies and set a module value.

Configuration Option

config



Documentation:

There is a common need to pass configuration info to a module. That configuration info is usually known as part of the application, and there needs to be a way to pass that down to a module. In RequireJS, that is done with the **config** option. Modules can then read that info by asking for the special dependency "module" and calling **module.config()**

Configuration Option

waitSeconds




Documentation:

The number of seconds to wait before giving up on loading a script. Setting it to 0 disables the timeout. The default is 7 seconds.

Configuration Option

deps & callback



Documentation:

Deps: An array of dependencies to load.

Callback: A function to execute after **deps** have been loaded.

Configuration Option

urlArgs



Documentation:

Extra query string arguments appended to URLs that RequireJS uses to fetch resources.