

Npm as Build Script Summary



Marcus Hammarberg

www.marcusoft.net | [@marcusoftnet](https://twitter.com/marcusoftnet) |
github.com/marcusoftnet



GRUNT





+



```

1 {
2   "name": "stupidlittlewebsite",
3   "version": "1.6.0",
4   "description": "Small test utility for npm scripting",
5   "main": "index.js",
6   "scripts": {
7     "test": "mocha test -u bdd -R spec",
8     "test:deploy": "npm t -- -R dot",
9     "start": "node index.js",
10    "start:dev": "node index.js 4000",
11    "lint": "jshint --exclude ./lib/*.js *.js **/*.js",
12    "pretest": "npm run compile && npm run lint",
13    "compile:coffee": "coffee --compile --output ./lib ./src/coffeescripts",
14    "compile:ts": "tsc --outDir ./lib --module commonjs ./src/typescripts/tsCode.ts",
15    "compile": "npm run compile:coffee && npm run compile:ts",
16    "precompile": "npm run clean",
17    "clean": "rimraf lib/*",
18    "build:less": "lessc client/less/demo.less public/css/site.css",
19    "build:bundle": "browserify ./client/js/app.js | uglifyjs -mc > ./public/js/bundle.js",
20    "build:clean": "rimraf public/css/*, public/js/*",
21    "prebuild": "npm run build:clean",
22    "build": "npm run build:less && npm run build:bundle",
23    "watch:test": "npm run test -- -w -R min",
24    "watch:lint": "watch 'npm run lint' .",
25    "watch:server": "nodemon --ignore client --ignore public index.js",
26    "watch:coffee": "coffee --compile -w --output ./lib ./src/coffeescripts",
27    "watch:ts": "tsc -w --outDir ./lib --module commonjs ./src/typescripts/tsCode.ts",
28    "watch:bundle": "watch 'npm run build:bundle' client",
29    "watch:browser": "live-reload --port 9091 public/",
30    "watch": "npm run watch:test & npm run watch:bundle & npm run watch:server & npm run watch:browser",
31    "version:major": "npm version major",
32    "version:minor": "npm version minor",
33    "version:patch": "npm version patch",
34    "prepush:origin": "echo '####>Pushing code to GitHub'",
35    "push:origin": "git push --tags origin HEAD:master",
36    "prepush:heroku": "echo '####>Pushing code to Heroku'",
37    "push:heroku": "git push heroku master",
38    "push": "npm run push:origin && npm run push:heroku",
39    "launch:prod": "heroku open",
40    "external:script": "bash ./aLongComplicatedScript.sh",
41    "test:options": "mocha",
42    "test:configoptions": "mocha test --reporter $npm_package_config_reporter",
43    "test:configoptions:json": "npm run test:configoptions --stupidlittlewebsite:reporter=json",
44    "deploy:prod": "bash ./deployProd.sh",
45    "deploy:prod:time": "time(npm run deploy:prod)"
46  },
47  "config": {
48    "reporter": "landing"
49  },
50  "jshintConfig": {
51    "esnext": "true",
52    "noyield": "true"
53  },
54  "repository": {
55    "type": "git",
56    "url": "."
57  },
58  "keywords": [
59    "npm",
60    "scripting"
61  ],
62  "author": "Marcus Hammarberg @marcusoftnet",

```




Npm as Build Script Summary



Marcus Hammarberg

www.marcusoft.net | [@marcusoftnet](https://twitter.com/marcusoftnet) | github.com/marcusoftnet
