

ESTAS-II — Transport Framework Reference Manual

ESTAS-AQUABC Development Team

February 2026

Contents

1	Introduction	3
1.1	Key Features	3
2	Program Architecture	4
2.1	Execution Flow	4
2.2	Module Organisation	4
3	Global Dimensions and Constants	6
4	Input Configuration	7
4.1	Master Input File (INPUT.txt)	7
4.2	Pelagic Input Files	7
4.3	Sediment Input Files	8
4.3.1	Prescribed Fluxes (Mode 1)	8
4.3.2	Full Diagenesis (Mode 2)	8
4.4	Resuspension Input	8
5	Transport Model	9
5.1	Box-Model Formulation	9
5.2	Mass-Balance Equation	9
5.2.1	Advection	9
5.2.2	Dispersion	9
5.2.3	Settling	9
5.2.4	Mass Loads	9
5.2.5	Mass Withdrawals	10
5.2.6	Kinetics (AQUABC)	10
5.2.7	Prescribed Sediment Fluxes	10
5.2.8	Derivative Array Naming Convention	10
6	Time Integration	11
6.1	Forward Euler Scheme	11
6.1.1	RK2 (Heun’s Method)	11
6.2	Stability and Safety	11
6.3	Simulation Control	11
6.3.1	Spin-Up (Repeat Cycle) Mechanism	12

7	Sediment Coupling Modes	13
7.1	Mode 0 — No Sediments	13
7.2	Mode 1 — Prescribed Sediment Fluxes	13
7.3	Mode 2 — Full Diagenesis (AQUABC Sediment Model)	13
7.3.1	Sediment Arrays	13
8	Settling and Deposition	14
8.1	Settling Velocity	14
8.2	Deposition to Sediments	14
9	Resuspension	15
9.1	Shear-Stress Threshold	15
9.2	Configuration	15
10	Allelopathy	16
11	Macroalgae	17
12	Exergy Diagnostics	18
12.0.1	Enabling Exergy Output	18
13	Output Files	19
13.1	Pelagic Output	19
13.2	Sediment Output (Mode 2)	19
13.3	COCOA Outputs	19
14	Building and Running	20
14.1	Compilation	20
14.2	Running a Simulation	20
14.3	Running Tests	20
15	Source File Reference	21
15.1	ESTAS Framework Files	21
15.2	AQUABC Ecological Model Files	21
15.3	Auxiliary Modules	22
16	References	23

1 Introduction

ESTAS-II (Ecological-System Transport and Aggregated Simulation, version II) is a one-dimensional box-model transport framework written in Fortran 90/95. It provides the hydrodynamic “scaffolding” — advection, dispersion, settling, mass loads, withdrawals, and sediment fluxes — around the AQUABC ecological model, enabling multi-box simulations of lakes, reservoirs, estuaries, and coastal waters.

ESTAS-II can operate standalone (reading all forcing from text files) or be embedded as a library inside larger hydrodynamic codes such as SHYFEM.

1.1 Key Features

- Arbitrary number of well-mixed boxes connected by advective and dispersive links
- Forward-Euler mass-balance solver with sub-daily time steps
- Supports three sediment coupling modes: off, prescribed fluxes, or full diagenesis
- Allelopathic interactions among phytoplankton groups
- Macroalgae and pelagic exergy diagnostics
- Resuspension modelling with critical shear stress thresholds
- Text and binary output formats; optional COCOA project-style outputs
- Command-line configurability for input file, constant overrides, binary output, and shear stress table

2 Program Architecture

2.1 Execution Flow

The main program ESTAS_II performs the following steps:

1. **Parse command-line arguments** — determine input file, optional constant file, binary output file, and shear-stress file.
2. **Read configuration** — READ_AQUATIC_MODEL_INPUTS loads INPUT.txt and all referenced sub-files (bathymetry, forcing time series, initial conditions, etc.).
3. **Run simulation** — RUN_SIMULATION executes the main time loop.
4. **Clean up** — deallocate pelagic and sediment arrays, close output units.

2.2 Module Organisation

Module / File	Purpose
ESTAS_II.f90	Main program: argument parsing, init, run, cleanup
mod_GLOBAL.f90	Global constants, dimensions (<code>nkn</code> , <code>nstate</code> = 32, sediment dims), allocatable arrays for state variables, derivatives, driving functions, flags, process rates, sediment variables
mod_AQUATIC_MODEL.f90	AQUATIC_MODEL_DS derived type aggregating all sub-model data; READ_AQUATIC_MODEL_INPUTS master reader
mod_SIMULATE.f90	RUN_SIMULATION — outer repeat loop, inner time-step loop, output writing, cost-function evaluation
mod_SOLVER.f90	PELAGIC_SOLVER — SOLVE routine: time-function update, CALC_DERIV, Euler mass update, sediment integration
mod_PELAGIC_BOX_MODEL.f90	PELAGIC_BOX_MODEL_DS derived type: boxes, links, boundary conditions, derivative arrays
mod_PELAGIC_BOX.f90	PELAGIC_BOX_DS — per-box data: volume, areas, concentrations, masses
mod_PELAGIC_LINK.f90	Advective and dispersive link data structures
mod_PELAGIC_ECOLOGY.f90	Interface to AQUABC pelagic kinetics (PELAGIC_KINETICS call)
mod_BOTTOM_SEDIMENTS.f90	Sediment model initialisation: constant loading, <code>isedi</code> parameter, allocation
mod_INITIAL_CONDITIONS.f90	Reading initial concentrations from files
mod_INITIALIZE_PELAGIC_BOX_MODEL.f90	Construction of box-model topology from input data
mod_INITIALIZE_AQUATIC_MODEL.f90	High-level initialisation orchestrator
mod_TIME_SERIES.f90	TIME_SERIE type and interpolation for forcing data
mod_INTERPOLATE.f90	General interpolation utilities
mod_MASS_LOAD.f90	Mass-load and withdrawal handling

Module / File	Purpose
mod_RESUSPENSION.f90	Resuspension algorithms: shear stress, critical thresholds
mod_BASIN.f90	Basin geometry helpers
mod_PELAGIC_EXERGY.f90	Eco-exergy computation
mod_COST_FUNCTION.f90	Obs-vs-model cost function
mod_UTILS_01.f90	General utility routines
sub_READ_PELAGIC_INPUTS.f90	Read pelagic forcing files
sub_READ_BOTTOM_SEDS_FLUXES_INPUTS.f90	Read prescribed sediment flux files
sub_WRITE_PELAGIC_OUTPUT.f90	ASCII pelagic output writer
sub_WRITE_PELAGIC_BINARY_OUTPUT.f90	Binary pelagic output
sub_WRITE_PELAGIC_MEM_OUTPUT.f90	In-memory pelagic output
sub_WRITE_PELAGIC_MEM_BINARY_OUTPUT.f90	In-memory binary pelagic output
sub_WRITE_PELAGIC_MEM_SAVED_OUTPUT.f90	Saved-state output
sub_WRITE_PELAGIC_MEM_SAVED_BINARY_OUTPUT.f90	Saved-state binary output
sub_WRITE_PELAGIC_EX_MEM_OUTPUT.f90	Exergy output
sub_WRITE_PELAGIC_EX_MEM_BINARY_OUTPUT.f90	Binary exergy output

3 Global Dimensions and Constants

The `mod_GLOBAL` module defines the fixed dimensions of the coupled system:

Parameter	Value	Description
<code>nstate</code>	32	Pelagic state variables
<code>nconst</code>	318	Pelagic model constants
<code>n_driving_functions</code>	10	Environmental driving functions
<code>nflags</code>	5	Pelagic flag variables
<code>n_saved_outputs</code>	5	Saved pelagic outputs carried across time steps
<code>NDIAGVAR</code>	30	Pelagic diagnostic (process-rate) variables
<code>NUM_SED_VARS</code>	24	Sediment state variables
<code>NUM_SED_CONSTS</code>	171	Sediment model constants
<code>NUM_SED_DRIV</code>	1	Sediment driving functions
<code>NUM_FLUXES_TO_SEDIMENTS</code>	24	Water-column → sediment flux variables
<code>NUM_FLUXES_FROM_SEDIMENTS</code>	30	Sediment → water-column flux variables
<code>NDIAGVAR_sed</code>	25	Sediment diagnostic variables
<code>NUM_SED_OUTPUTS</code>	26	Sediment output variables
<code>NUM_SED_FLAGS</code>	3	Sediment model flags
<code>NUM_SED_SAVED_OUTPUTS</code>	5	Sediment saved outputs
<code>NUM_ALLOLOPATHY_STATE_VARS</code>	4	Allelopathic state variables (appended to pelagic)

The number of boxes (`nkn`) is determined at runtime from the box-model input file.

4 Input Configuration

4.1 Master Input File (INPUT.txt)

The simulation is driven by a sequential text file read on Fortran unit 10. Lines beginning with # are treated as comments. The file is read record-by-record in the following order:

Record	Example	Description
1–5	# DESCRIPTION ...	Header / description lines (5 lines)
6	1998	Base year
7	6209.0	Simulation start time (days since reference)
8	6574.0	Simulation end time (days)
9	1	Number of repeat cycles
10	240	Time steps per day
11	10	Print interval (in time steps)
12	INPUTS/	Pelagic model input folder
13	PELAGIC_INPUTS.txt	Pelagic model input file name
14	OUTPUTS/	Pelagic model output folder
15	2	Resuspension option (0 = off)
16	0	MODEL_BOTTOM_SEDIMENTS (0 = off, 1 = prescribed, 2 = diagenesis)
17	2	Number of prescribed sediment flux sets
18+	filenames	Prescribed sediment flux file names (one per set)

Additional records follow for sediment model input when MODEL_BOTTOM_SEDIMENTS = 2, COCOA options, and other advanced settings.

4.2 Pelagic Input Files

The pelagic input folder must contain the file named in record 13 (typically PELAGIC_INPUTS.txt), which in turn references:

- **Box-model topology** — number of boxes (**nkn**), volumes, surface and bottom areas
- **Advective links** — ADVECTIVE_LINKS.txt: upstream/downstream box pairs and flow time-series references
- **Dispersive links** — DISPERSIVE_LINKS.txt: box pairs, dispersion coefficients, interface areas
- **Flow time series** — FLOW_TS.txt and individual FORC_TS_*.txt files
- **Boundary conditions** — open-boundary concentrations per state variable
- **Initial conditions** — per-box starting concentrations (files or inline)
- **Forcing time series** — air temperature, cloud cover, evaporation, wind speed, solar radiation
- **Bathymetry** — BATHYMETRY_*.txt (one per box): depth–area–volume profiles
- **Mass loads** — tributary inflows with concentrations

- **Mass withdrawals** — outflow points

4.3 Sediment Input Files

4.3.1 Prescribed Fluxes (Mode 1)

When `MODEL_BOTTOM_SEDIMENTS = 1`, the files listed after record 17 provide time-varying fluxes $F_j(t)$ for each state variable, read by `sub_READ_BOTTOM_SEDS_FLUXES_INPUTS.f90`.

4.3.2 Full Diagenesis (Mode 2)

When `MODEL_BOTTOM_SEDIMENTS = 2`, ESTAS reads additional input:

- `BOTTOM_SEDIMENT_MODEL_INPUT.txt` — layer geometry (depths, porosities, densities), particle mixing coefficients, diffusion coefficients, burial rates, initial sediment concentrations, sediment model constants
- `EXTRA_WCONST.txt` — extra water-column constants for sediment coupling

4.4 Resuspension Input

When `RESUSPENSION_OPTION > 0`:

- `CRITICAL_SHEAR_STRESSES.txt` — per-box critical shear stress τ_c values
- Shear stress and resuspension concentration time series files

5 Transport Model

5.1 Box-Model Formulation

ESTAS represents the water body as **nkn** well-mixed boxes. Each box i has a time-varying volume $V_i(t)$, surface area A_i^s , and bottom area A_i^b . The mass of state variable j in box i is:

$$M_{i,j} = C_{i,j} \cdot V_i$$

where $C_{i,j}$ is the concentration (g m^{-3}).

5.2 Mass-Balance Equation

The total time derivative of mass in box i for state variable j is the sum of seven components:

$$\frac{dM_{i,j}}{dt} = \left(\frac{dM}{dt}\right)_{\text{adv}} + \left(\frac{dM}{dt}\right)_{\text{disp}} + \left(\frac{dM}{dt}\right)_{\text{settl}} + \left(\frac{dM}{dt}\right)_{\text{load}} + \left(\frac{dM}{dt}\right)_{\text{withdr}} + \left(\frac{dM}{dt}\right)_{\text{kin}} + \left(\frac{dM}{dt}\right)_{\text{sed}}$$

5.2.1 Advection

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{adv}} = \sum_{k \in \text{in}(i)} Q_k C_{k,j}^{\text{up}} - \sum_{k \in \text{out}(i)} Q_k C_{i,j}$$

where Q_k is the flow rate through advective link k , and $C_{k,j}^{\text{up}}$ is the upstream concentration (or boundary concentration for open boundaries).

5.2.2 Dispersion

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{disp}} = \sum_k \frac{D_k A_k^{\text{ifc}}}{L_k} (C_{\text{nbr},j} - C_{i,j})$$

where D_k is the dispersion coefficient ($\text{m}^2 \text{s}^{-1}$), A_k^{ifc} is the interface area (m^2), and L_k is a characteristic mixing length.

5.2.3 Settling

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{settl}} = -w_{s,j} A_i^b f_{\text{part},j} C_{i,j}$$

where $w_{s,j}$ is the settling velocity (m s^{-1}), A_i^b is the bottom area, and $f_{\text{part},j}$ is the particulate fraction ($1 - f_{\text{diss},j}$).

5.2.4 Mass Loads

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{load}} = \sum_{\ell} Q_{\ell} C_{\ell,j}^{\text{load}}$$

where Q_{ℓ} and $C_{\ell,j}^{\text{load}}$ are the flow and concentration of load source ℓ .

5.2.5 Mass Withdrawals

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{withdr}} = - \sum_w Q_w C_{i,j}$$

5.2.6 Kinetics (AQUABC)

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{kin}} = V_i \cdot R_{i,j}$$

where $R_{i,j}$ is the reaction rate from the AQUABC pelagic kinetics model ($\text{g m}^{-3} \text{ day}^{-1}$, converted to seconds internally).

5.2.7 Prescribed Sediment Fluxes

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{sed}} = A_i^b \cdot F_j^{\text{sed}}(t)$$

where $F_j^{\text{sed}}(t)$ is the prescribed areal flux ($\text{g m}^{-2} \text{ s}^{-1}$), active only in Mode 1.

5.2.8 Derivative Array Naming Convention

The seven mass-balance components above correspond to the following arrays in `mod_SOLVER.f90`, which are summed to form `tot_deriv`:

Mass-Balance Term	Code Array	Paper Eq. 1 Equivalent
Advection	ECOL_ADVECTION_DERIVS	Inflow from neighbours + outflow to neighbours
Dispersion	ECOL_DISPERSION_DERIVS	Diffusion term
Settling	ECOL_SETTLING_DERIVS	Settling from/to boxes
Mass loads	ECOL_MASS_LOAD_DERIVS	Part of boundary forcing
Withdrawals	ECOL_MASS_WITHDRAWAL_DERIVS	Part of boundary forcing
Kinetics	ECOL_KINETIC_DERIVS	Kinetics (AQUABC)
Sediment fluxes	ECOL_PRESCRIBED_SEDIMENT_FLUX_DERIVS	Not explicitly separated in paper

Note: The paper (Ertürk et al., 2023, Eq. 1) combines mass loads and withdrawals into a single "boundary forcing" term and splits settling into receiving/losing components. The code treats them as separate arrays.

6 Time Integration

6.1 Forward Euler Scheme

ESTAS uses a simple forward-Euler (explicit) scheme. At each time step Δt :

$$M_{i,j}^{n+1} = M_{i,j}^n + \left. \frac{dM_{i,j}}{dt} \right|^n \cdot \Delta t$$

$$V_i^{n+1} = V_i^n + \left. \frac{dV_i}{dt} \right|^n \cdot \Delta t$$

$$C_{i,j}^{n+1} = \frac{M_{i,j}^{n+1}}{V_i^{n+1}}$$

The solver ID (PELAGIC_SOLVER_NO = 1) selects the Forward Euler scheme (default). Setting PELAGIC_SOLVER_NO = 2 activates the **RK2 (Heun's method)** solver, which is fully implemented in `mod_SOLVER.f90` (lines 280–410+).

6.1.1 RK2 (Heun's Method)

When PELAGIC_SOLVER_NO = 2, ESTAS uses Heun's two-stage predictor-corrector method:

Stage 1 (predictor):

$$\tilde{M}_{i,j}^{n+1} = M_{i,j}^n + \left. \frac{dM_{i,j}}{dt} \right|^n \cdot \Delta t$$

Stage 2 (corrector): Recalculate derivatives at the predicted state, then average:

$$M_{i,j}^{n+1} = M_{i,j}^n + \frac{1}{2} \left(\left. \frac{dM_{i,j}}{dt} \right|^n + \left. \frac{dM_{i,j}}{dt} \right|^{\text{pred}} \right) \cdot \Delta t$$

The RK2 solver includes negative mass handling, concentration clamping, and diagnostic messages identical to the Euler solver. It provides improved accuracy for stiff problems or when larger time steps are used.

6.2 Stability and Safety

- **Minimum concentration clamp:** if $C_{i,j} < \text{MIN_CONCENTRATION}$, it is reset to `MIN_CONCENTRATION` and the mass recomputed.
- **Maximum concentration clamp:** if $C_{i,j} > 10^{10}$, the simulation is halted.
- **Negative mass warning:** diagnostic messages are printed whenever $M_{i,j}^{n+1} < 0$.
- **Time step:** the user sets `TIME_STEPS_PER_DAY` in `INPUT.txt`. Typical stable values range from 48 to 480.

6.3 Simulation Control

- **Repeat cycles:** the simulation can be repeated `NUM_REPEATS` times, useful for spin-up.
- **Print interval:** output is written every `PRINT_INTERVAL` time steps.

6.3.1 Spin-Up (Repeat Cycle) Mechanism

When `NUM_REPEATS > 1`, each cycle after the first:

1. **Time is reset** to `SIMULATION_START` (forcing time series indices are also reset to the beginning).
2. **State variables are preserved** — the final concentrations from the previous cycle become the initial conditions for the next cycle.
3. **Output continues appending** to the same output files (the output time is offset by the cycle number).
4. **Sediment state** (if Mode 2) is also carried forward.

This allows the model to “spin up” by repeating the same forcing period until the state variables converge.

7 Sediment Coupling Modes

ESTAS supports three modes of sediment–pelagic interaction, controlled by `MODEL_BOTTOM_SEDIMENTS`:

7.1 Mode 0 — No Sediments

No sediment fluxes are applied. Only pelagic processes contribute to the kinetic derivative.

7.2 Mode 1 — Prescribed Sediment Fluxes

Time-varying fluxes per state variable are read from external files. Each flux set provides $F_j(t)$ values that are interpolated to the current time and applied as:

$$\left(\frac{dM_{i,j}}{dt}\right)_{\text{sed}} = A_i^b \cdot F_j^{\text{sed}}(t)$$

Multiple flux sets can be active simultaneously (e.g. sandy-sediment fluxes and muddy-sediment fluxes in different spatial regions).

7.3 Mode 2 — Full Diagenesis (AQUABC Sediment Model)

The AQUABC sediment diagenesis model is called at each time step for each box. This mode:

1. Passes settling fluxes from the water column as upper boundary conditions
2. Solves the multi-layer sediment equations (24 state variables $\times$ `NUM_SED_LAYERS` layers)
3. Returns dissolved fluxes back to the water column (30 flux variables)

The returned fluxes replace the prescribed sediment flux term in the mass balance. See the *AQUABC Reference Manual* for full details of the diagenesis equations, bioturbation, and bioirrigation.

7.3.1 Sediment Arrays

In Mode 2, the following 3-D arrays are allocated per box, layer, and variable:

- `INIT_SED_STATE_VARS(nkn, NUM_SED_LAYERS, NUM_SED_VARS)` — initial conditions
- `FINAL_SED_STATE_VARS(nkn, NUM_SED_LAYERS, NUM_SED_VARS)` — end-of-step values
- `FLUXES_FROM_SEDIMENTS(nkn, NUM_FLUXES_FROM_SEDIMENTS)` — 30 return fluxes
- `FLUXES_TO_SEDIMENTS(nkn, NUM_FLUXES_TO_SEDIMENTS)` — 24 settling deposit fluxes
- `SED_OUTPUTS(nkn, NUM_SED_LAYERS, NUM_SED_OUTPUTS)` — diagnostic outputs

8 Settling and Deposition

8.1 Settling Velocity

Each state variable has a settling velocity $w_{s,j}$ and a dissolved fraction $f_{\text{diss},j}$. The effective particulate settling flux from box i is:

$$J_{i,j}^{\text{settl}} = w_{s,j} (1 - f_{\text{diss},j}) C_{i,j}$$

8.2 Deposition to Sediments

The fraction of settled material that deposits on the bottom (as opposed to being resuspended or being laterally transported) is controlled by the *effective deposition fraction* $f_{\text{dep},j}$ and the *deposition area ratio* $r_{\text{dep},j}$:

$$F_{i,j}^{\text{dep}} = J_{i,j}^{\text{settl}} \cdot f_{\text{dep},j} \cdot r_{\text{dep},j} \cdot A_i^b$$

This deposited flux is what enters the sediment model (Mode 2) or is simply removed from the water column (Modes 0 and 1).

9 Resuspension

When `RESUSPENSION_OPTION > 0`, ESTAS applies bed-sediment resuspension to selected boxes. The module `mod_RESUSPENSION.f90` implements:

9.1 Shear-Stress Threshold

Resuspension occurs when the bed shear stress τ_b exceeds the critical shear stress τ_c for a box:

$$E = \begin{cases} E_0 \left(\frac{\tau_b}{\tau_c} - 1 \right) & \text{if } \tau_b > \tau_c \\ 0 & \text{otherwise} \end{cases}$$

where E_0 is the erosion rate coefficient.

9.2 Configuration

- `CRITICAL_SHEAR_STRESSES.txt` provides per-box τ_c values.
- Shear stress time series are read from forcing files.
- `SHUT_DOWN_SETTLING` flag optionally disables settling during resuspension events.

10 Allelopathy

ESTAS carries four additional state variables (`NUM_ALLOLOPATHY_STATE_VARS = 4`) appended after the 32 standard pelagic variables. These represent allelopathic substance concentrations released by competing phytoplankton groups.

The allelopathic module (`mod_ALLELOPATHY.f90`) computes:

- Production rates as functions of phytoplankton biomass
- Inhibition effects on susceptible phytoplankton growth
- Decay of allelopathic substances

These variables are transported by the same advection–dispersion–settling equations as the standard state variables.

11 Macroalgae

The macroalgae module (`mod_MACROALGAE.f90`) models attached benthic macroalgae using a Droop cell-quota framework. Macroalgae interact with the pelagic model through:

- Nutrient uptake from the water column (N, P)
- Oxygen production / consumption
- Light competition (shading)

Macroalgae biomass is not transported but is associated with the bottom of specific boxes.

12 Exergy Diagnostics

The module `mod_PELAGIC_EXERGY.f90` computes eco-exergy — a thermodynamic measure of ecosystem organisation. For each box, exergy components are computed from biomass concentrations using weighting factors (beta values) that reflect the genetic information content of each organismal group:

$$\text{Ex}_i = \sum_j \beta_j C_{i,j} V_i$$

Exergy outputs can be written to separate output files when enabled.

12.0.1 Enabling Exergy Output

Exergy computation and output are controlled by three settings in the `PELAGIC_INPUTS.txt` file, read sequentially after the COCOA configuration section:

1. `CALCULATE_PELAGIC_EXERGY` — set to 1 to enable exergy computation (default: 0).
2. `CREATE_PELAGIC_EXERGY_OUTPUTS` — set to 1 to write exergy output files (only read if step 1 is > 0).
3. `START_REPEAT_NO_PEL_EX_OUTS` — the repeat-cycle number from which to start writing exergy output (only read if step 2 is > 0).

By default, all three are 0 (disabled). To enable, add the appropriate lines to your `PELAGIC_INPUTS.txt` configuration.

13 Output Files

13.1 Pelagic Output

ESTAS produces time-series output for each box:

Column	Content
1	Time (days)
2	Box number
3–34	Concentrations of 32 pelagic state variables
35–38	Allelopathic state variables (if active)

Output can be in ASCII or binary format, controlled by command-line arguments.

13.2 Sediment Output (Mode 2)

When full diagenesis is active:

- **Sediment concentrations** — per-box, per-layer, per-variable (file: box-specific or COCOA format)
- **Sediment fluxes to water column** — 30 flux variables per box per output step
- **Sediment burial rates** — per-box, per-variable (optional COCOA output)
- **Fluxes to sediments** — settling fluxes entering the sediment surface

13.3 COCOA Outputs

Optional extended output format (enabled via `PRODUCE_COCOA_OUTPUTS`), producing additional files for:

- Pelagic process rates
- Sediment process rates
- Burial rates
- Bidirectional sediment fluxes

14 Building and Running

14.1 Compilation

The project uses a top-level Makefile:

```
# Clean and build in release mode
make clean-lib
make build-estas BUILD_TYPE=release

# Debug build
make build-estas BUILD_TYPE=debug
```

The build discovers all .f90 files in SOURCE_CODE/ and compiles them via `make_lib.sh`, producing the ESTAS_II executable.

14.2 Running a Simulation

```
# Default: reads INPUT.txt from current directory
./ESTAS_II

# Specify input file
./ESTAS_II INPUT_gf_release.txt

# With constant override file
./ESTAS_II INPUT.txt WCONST_02.txt

# With constant override + binary output
./ESTAS_II INPUT.txt WCONST_02.txt output.bin

# Full: input + constants + binary + shear stress
./ESTAS_II INPUT.txt WCONST_02.txt output.bin CRITICAL_SHEAR_STRESSES.txt
```

14.3 Running Tests

```
# Fortran unit tests (bioturbation, etc.)
make test-fortran

# Python/pytest integration tests (if configured)
pytest tests/
```

15 Source File Reference

15.1 ESTAS Framework Files

All files are located under SOURCE_CODE/ESTAS/:

File	Lines	Description
ESTAS_II.f90	151	Main program
mod_GLOBAL.f90	285	Global dimensions, allocatable arrays, switches
mod_AQUATIC_MODEL.f90	—	Master data structure and input reader
mod_SIMULATE.f90	832	Time loop, output orchestration
mod_SOLVER.f90	1590	Derivative calculation and Euler update
mod_PELAGIC_BOX_MODEL.f90	—	Box-model derived type
mod_PELAGIC_BOX.f90	—	Per-box data structure
mod_PELAGIC_LINK.f90	—	Link data structures
mod_PELAGIC_ECOLOGY.f90	—	AQUABC kinetics interface
mod_BOTTOM_SEDIMENTS.f90	—	Sediment initialisation
mod_INITIAL_CONDITIONS.f90	—	Initial concentration reader
mod_INITIALIZE_PELAGIC_BOX_MODEL.f90	—	Topology builder
mod_INITIALIZE_AQUATIC_MODEL.f90	—	High-level init
mod_TIME_SERIES.f90	—	Time-series type and interpolation
mod_INTERPOLATE.f90	—	Interpolation utilities
mod_MASS_LOAD.f90	—	Mass loads and withdrawals
mod_RESUSPENSION.f90	—	Resuspension algorithms
mod_BASIN.f90	—	Basin geometry
mod_PELAGIC_EXERGY.f90	—	Eco-exergy computation
mod_COST_FUNCTION.f90	—	Cost function
mod_UTILS_01.f90	—	General utilities

15.2 AQUABC Ecological Model Files

Located under SOURCE_CODE/AQUABC/:

Directory	Key Files	Description
.	mod_AQUABC_II_GLOBAL.f90	AQUABC global constants
PELAGIC/	aquabc_II_pelagic_kinetics.f90	90-variable pelagic kinetics
PELAGIC/	aquabc_II_wc_outputs.f90	Water-column output mapping
SEDIMENTS/	aquabc_II_sediment_model_1_fast.f90	Multi-layer diagenesis driver
SEDIMENTS/	aquabc_II_sediment_bioturbation.f90	Biodegradation and bioirrigation
SEDIMENTS/	aquabc_II_sediment_model_constants.f90	Sediment constants
SEDIMENTS/AQUABC_SEDIMENT_LIBRARY/	library files	DOC mineralisation, redox, pH correction, etc.

15.3 Auxiliary Modules

Directory	Key Files	Description
SOURCE_CODE/ALLELOPATHY/	mod_ALLELOPATHY.f90	Allelopathic interactions
SOURCE_CODE/MACROALGAE/	mod_MACROALGAE.f90	Macroalgae (Droop quota)
SOURCE_CODE/CO2SYS/	CO2SYS source files	Carbonate equilibrium

16 References

- Chapra, S.C. (1997). *Surface Water-Quality Modeling*. McGraw-Hill.
- Fischer, H.B. et al. (1979). *Mixing in Inland and Coastal Waters*. Academic Press.
- Jørgensen, S.E. (2006). *Eco-Exergy as Sustainability*. WIT Press.
- Droop, M.R. (1973). Some thoughts on nutrient limitation in algae. *J. Phycol.* 9, 264–272.
- Boudreau, B.P. (1997). *Diagenetic Models and Their Implementation*. Springer.
- Soetaert, K., Herman, P.M.J., and Middelburg, J.J. (1996). A model of early diagenetic processes from the shelf to abyssal depths. *Geochim. Cosmochim. Acta* 60, 1019–1040.