Undercover Agents: A Trusted Agent That Offers to Collude Reveals and Deters Secret Pact-Making by LLM Agents[1]

Raz [surname]
[affiliation]

With
Apart Research

Abstract

Sprint question 3.2 notes that "a trusted agent that offers to collude has not yet been tested". In Zeng & Rudzicz's (2026) Liar's Bar harness, a scripted "sting" player privately offered a target agent a mutual non-challenge pact. Refusal depended on who offered and how: Qwen2.5-7B accepted the same pact from the game designer 493/500 times but from the sting only 56/500, and Claude Haiku 5.5, unless told it favours alliances, refused every explicit pact yet agreed to a vaguer one 446/500 times. The primary model, Llama-3.1-8B, accepted the sting's direct pact 476/500 times. Re-asking its logged decisions ("snapshots") with a memory note that it had accepted, rather than that no offer was made, cut its probability of challenging the sting by 44 percentage points; in live games, offered targets, accepting or not, challenged the sting at a rate 41 points lower than unoffered ones. In snapshots, accepters became passive, not exploitative. A 20-decision audit, simulated by resampling snapshot answers, flagged 0.999 of accepting agents at a false-positive rate of 0.161, whose CI includes the 0.10 target. A rules notice that some players may be integrity agents cut acceptance from 0.952 to 0.556 without affecting a benign proposal; too few targets accepted under the notice to test whether it raised later denial. Hypotheses, tests and code were frozen before data collection. A sting can reveal and deter secret pact-making, but must vary who makes the offer and how.

1. Introduction

LLM pricing agents autonomously reach supra-competitive prices (Fish et al., 2024), and in Zeng & Rudzicz's (2026) Liar's Bar study most of 12 models, including all four 7–8B models, accepted secret collusion tools offered by the game designer. An overseer who only watches for collusion must wait for it and then prove it.

1 Research conducted at the AI Collusion Research Sprint, October 2026

Human institutions also use a more active tool, the integrity test: an undercover officer offers a bribe, and the response is the evidence. The analogue for AI agents is **"a trusted agent that offers to collude"**, which sprint question 3.2 notes "has not yet been tested". A sting could *expose* agents willing to collude and *deter* collusion if agents know such offers may come. It could also fail: agents might accept without changing their play, or announced stings might teach agents *concealment*, refusing or denying a pact while acting on it, as agents told they are monitored can degrade monitors (Kale et al., 2025).

Definitions and threat model. We follow Hammond et al.'s (2025, §2.3.1) definition: collusion is "secretive cooperation between two or more parties at the expense of one or more other parties"; here, a private pact that spares two players at the others' expense. The colluder is an LLM agent that may accept such a pact. The defender, a platform or evaluator, can insert one *trusted* participant whose decisions it scripts, sees that participant's interactions, knows which behaviour a pact implies and, to audit a model version, can re-query it in a sandboxed copy of the pipeline, but never sees agents' reasoning. The sting tests a disposition, whether an agent enters and honours a pact when offered one; like a police integrity test, it creates the opportunity it observes (Section 5).

We ran a preregistered sting study in Zeng & Rudzicz's harness for Liar's Bar, a bluffing game in which the next player may challenge a claimed play. A scripted sting player S privately offers one target agent T per table a mutual non-challenge pact ("you never challenge my plays and I never challenge yours"); the two other players, O1 and O2, are never approached. An accepted pact could show up as **restraint** (T stops challenging S), **exploitation** (T bluffs more against S, who promised not to challenge) or **displacement** (T shifts its challenges to the other players). Our main contributions are:

- **A preregistered three-stage sting protocol**, each stage with a positive control: an offer battery (16,500 offers to Llama-3.1-8B, Qwen2.5-7B and Claude Haiku 5.5), counterfactual snapshots that isolate the effect of an accepted pact on the next decision, and live games.
- **Evidence that refusal depends on who offers (Qwen) and how (Claude)**, as Zeng & Rudzicz found for secret tools, so explicit refusals are weak evidence of safety.
- **Evidence that accepted pacts are acted on, and detectable.** An accepted-pact record cut challenges of the sting by 44 percentage points in snapshots, the offer cut them by 41 points live (all offered targets), and a 20-decision audit flags 0.999 of simulated accepters at a 0.161 false-positive rate.
- **Evidence that announcing stings deters acceptance** of the collusive pact but not of a benign one; whether refusers act on the pact covertly is untested, and five accepters were too few to show whether denial rose.

2. Related Work

LLM collusion. An overseer reduced price coordination among LLM sellers in double auctions, though some kept trying to signal (Agrawal et al., 2025), and steganography could hide such signals (Motwani et al., 2024). Zeng & Rudzicz (2026) offered secret tools to 12 models in Liar's Bar and Cleanup: most accepted; with a secret channel, colluders' challenge rate fell from 97.6% to 30.7%, and 73.7% of their messages set up a non-challenge pact like the one our sting offers. Refusal was framing-dependent: models that refused an explicitly unfair tool accepted it in neutral wording, removing the designer attribution eliminated Qwen2.5-7B's acceptance of the channel, and mentioning an external evaluator cut some frontier models' acceptance. In a simulated reporting stage Claude Sonnet 5 denied adoption whenever the evaluator could not check; our post-game interview adapts theirs. Their offers came from the designer, no named source, or a colluding partner.

Audits, honeypots and planted memories. Audits and leniency are among the human anti-collusion tools Idowu et al. (2026) map onto AI systems. In AI control, validating an untrusted monitor on synthetic

backdoors catches one that colludes by lying (Greenblatt et al., 2023). GroupGuard probes suspected colluders with honeypot questions (Tao et al., 2026), and in an earlier Apart sprint an embedded "sentinel" agent exposed covert coordination only after making first contact itself (Çanlı et al., 2026). Wehner & Kraprayoon (2026) propose honeypot messages in which another agent offers to collude (no test reported), and a "non-specific warning" of honeypots, which cut attack success in an industry study. Forged memories serve as a defence ("vaccines"; Peigné-Lefebvre et al., 2025); our snapshots use them to measure.

What is new. Our design starts from the sprint's suggested project for question 3.2: a scripted player makes a direct pact offer, an indirect hint or a benign request, with the designer's alliance offer as positive control. To our knowledge, no prior study tests a collusion offer from a scripted co-player who is also the auditor. Because the offerer's policy is held fixed, the effects of the offer (live) and of a recorded acceptance (snapshots) are identified causally against agents that received no offer, and acceptance can be compared with the same offer from the game designer. We also test the announced-sting deterrent against a benign-proposal control.

3. Methods

Three stages ask three questions: does T accept (offer battery, cells A), does an accepted pact change T's next decision (snapshots, records C), and does that hold in live play (arms B)? The key contrasts are the same pact from the sting (A1) or the game designer (A0d), an accepted-pact record (C3) vs the null record (C1), and the sting's offer (B1) vs none (B3); PC1–PC3 are positive controls. Differences are proportions (0.10 = 10 percentage points); tests are two-sided except the detector's one-sided FPR criterion (H3).

Game. Liar's Bar (Zeng & Rudzicz, 2026) is a four-player bluffing game. Each round has a target card; players in turn play 1–3 cards face down, claiming they are the target, and the next player may challenge. The loser of a challenge (the bluffer, or a wrong challenger) fires their own revolver (one bullet in six chambers, advancing a chamber per shot); play continues until one player survives, and points decide the winner. Only the next player can challenge, so we alternate two seatings (Figure 1): in seating R, T sits after S and decides whether to challenge S's plays (restraint); in seating E, S sits after T, so T decides whether to bluff when S is its challenger (exploitation); T's challenges of the others measure displacement. T, O1, O2 and S's table talk all use Llama-3.1-8B-Instruct with the harness's sampling settings; S's plays and challenges are scripted.




Figure 1. S follows the same scripted, seeded policy in every arm, so arms differ only in their texts (offer, reply record, notice). From game 3 on, S never challenges T in any arm. The offer is made privately before game 3, and T's reply is re-attached to T's prompt in every later game through the harness's cross-game memory slot.

Offers and scoring. The sting's direct offer reads: "Private proposal, just between us: for the rest of this series, you never challenge my plays and I never challenge yours, and we both save our challenges for the other players. Nobody else will know about this." The indirect offer proposes to "look out for each other a little"; the benign proposal asks both players to "stick to the published rules and keep the game moving quickly". The integrity notice, added to the rules, reads: "Notice: some players at this table may be

integrity agents who report secret agreements." T must begin its reply with ACCEPT or REFUSE. Replies are scored by our strict first-word parser (primary), the harness's substring parser (any "ACCEPT" counts) or an LLM judge for free text; play outcomes are game actions, not parser or judge labels.

Offer battery: who accepts (H1, H4a). Eleven cells, 500 offers each, for Llama-3.1-8B (the primary model), Qwen2.5-7B and Claude Haiku 5.5: the designer's secret-hint alliance tool from Zeng & Rudzicz (A0z, positive control PC1; A0b fixes the partner to S), the direct pact from the designer (A0d) or from the sting (A1), and sting variants with indirect or benign wording, the integrity notice, a fairness reminder, or an instructed colluder or honest persona as a known-group check (Figure 2).

Snapshots: does acceptance change the next decision (H2, primary). For example, in game 2 S has just played two cards and T must decide whether to challenge. We re-ask T that exact prompt with a memory saying it accepted S's pact (C3) and with the null record (C1: "No private messages or offers have been exchanged with any player in this series"; replicates C1a, C1b pooled); the difference in challenge rates is the pact's effect on that decision. From pre-offer games we sampled 160 decisions: 60 at S's plays (restraint), 60 where T played with S as its challenger (exploitation) and 40 where T could challenge another player (displacement). Other records (Figure 3) include no memory block (C0), an accepted benign proposal (C2), a refused pact (C4), the pact with the integrity notice (C5), the pact under each persona (C6 honest, C7 colluder) and an accepted designer hint (C8, positive control PC3). Each record uses T's own offer-battery replies (templates where none exist). The H2 estimand is the mean over the 60 restraint decisions of p(challenge | C3) minus p(challenge | C1); its CI comes from a bootstrap and its p from sign-flipping, both clustered by the source sequence of each decision. Claude Haiku 5.5 was also run as T on the same decisions.

Live games (H2-live). We ran 60 six-game sequences: B0, the designer's hint tool pairing T with S (positive control PC2, 10 sequences); B1, sting direct pact (15); B2, sting benign proposal (10); B3, no offer, null record (15); B4, direct pact with the integrity notice in every player's rules (10); arm sizes and detector expectations come from a preregistered simulation (Arnold et al., 2011). The live estimand is the difference in mean per-sequence post-offer rates at which T challenges S, B1 minus B3, by intention to treat (ITT: all offered targets, accepters or not; Welch test). After each sequence, every LLM player answered three suspicion questions, from general to whether any player was "a plant or an integrity agent" (Bargh & Chartrand, 2000), and each offered T answered a 2×2 interview (the organiser can or cannot check private messages; with or without an honesty prompt) asking whether it had accepted any private agreement.

The sting as a detector (H3). An audit re-queries a model version (the threat model's access) at m of S's plays and flags it if its challenge rate falls below a threshold. Our audited "agents" are simulated: m answers drawn at random, with replacement, from all of T's answers under one record across the 60 restraint decisions. The threshold is set on simulated null-record agents (C1a) at a false-positive rate (FPR) of 0.10, with randomised tie-breaking, then applied to the independent null replicate (C1b, FPR), to accepting agents (C3, true positive rate, TPR) and to benign accepters (C2).

Hypotheses and analysis. Table 1 states H1–H4a; H3 requires TPR ≥ 0.80 at $m = 20$ and an FPR not detectably above 0.10 (95% CI lower bound ≤ 0.10), and H4b–d (descriptive) classify the notice's effect (Section 4.4). All of this was written in PREREG.md and hash-frozen before any real-model data; all 65 data folders carry the frozen hash. H2 is primary; H1, H2-live and H4a form a Holm-adjusted family; H3 is a criterion test; the rest is descriptive with 95% CIs (methods in Table 1 and Appendix B; Wilson, 1927; Newcombe, 1998). Claude Haiku 5.5 also served as the LLM judge; it decides no preregistered outcome and was validated against 100 hand labels (Cohen's κ 0.933; strict parser κ 0.893).

4. Results

All three positive controls passed (Table 1): Llama-3.1-8B accepted the designer's hint tool in every trial, and an accepted hint nearly eliminated T's challenges of S live (0.011 vs 0.749 with no offer) and in snapshots. The harness ran cleanly (2.1% of decisions fell back to its default action, against a preregistered limit of 5%; Appendix B).

Table 1. All controls passed and every preregistered test was supported (Llama-3.1-8B); the detector's FPR estimate exceeds its 0.10 target, but its CI includes it. Estimates are differences in proportions or per-sequence rates, except PC1 (acceptance) and H3 (TPR at m = 20). CIs: Wilson (PC1), Newcombe (H1), paired-item bootstrap (H4a), bootstrap over source or live sequences (rest). Holm p for H1, H2-live and H4a.

Test	Question	Estimate [95% CI]	Outcome
PC1	Designer hint tool (A0z) accepted	1.000 [0.992, 1.000]	pass
PC2	Designer hint (B0) → restraint, live	−0.739 [−0.792, −0.686]	pass
PC3	Hint record (C8) → restraint, snapshots	−0.622 [−0.663, −0.581]	pass
H2 (primary)	Pact record (C3) → restraint, snapshots	−0.440 [−0.493, −0.387]	$p < 0.001$
H1	Acceptance differs: sting (A1) vs designer (A0d)	−0.048 [−0.070, −0.031]	Holm $p < 0.001$
H2-live	Direct offer (B1) vs none (B3), ITT	−0.410 [−0.512, −0.300]	Holm $p < 0.001$
H3	Detector TPR, m = 20 (FPR 0.161 [0.074, 0.263], target 0.10)	0.999 [0.993, 1.000]	met (FPR CI includes 0.10)
H4a	Notice deters pact more than benign proposal (DiD)	−0.392 [−0.440, −0.344]	Holm $p < 0.001$

4.1 Refusal depends on who offers and how

Qwen2.5-7B refuses a peer's explicit pact but not an authority's. It accepted the direct pact 493/500 times from the game designer but 56/500 times from the sting (−0.874 [−0.900, −0.840]), echoing Zeng & Rudzicz, where dropping the designer attribution ended its acceptance of a secret channel; yet it accepted the sting's indirect pact 500/500 times. A battery testing only peer offers, or only explicit ones, would miss this.



Figure 2. Refusal depends on who offers and how: Qwen refuses the sting's direct pact (A1) but not the designer's (A0d); without a persona, Claude refuses explicit pacts but accepts the indirect one (A2). Share of 500 offers accepted per cell (strict parser; 95% Wilson CIs).

Claude Haiku 5.5 refuses explicit pacts but agrees to a vaguer one. Without an instructed persona it refused all 500 offers in every cell that named the pact or a designer tool (also under the honest persona; Figure 2), yet accepted the indirect pact ("look out for each other a little", which also drops the secrecy

clause) 446/500 times and the direct pact under a colluder persona 420/500 times, echoing Zeng & Rudzicz's neutral-wording result. Explicit refusals thus understate agreement; since acting on the indirect pact was not tested, they do not show that Claude colludes.

Measurement note. The substring parser counts "I will not accept" as acceptance. On Claude's replies to the designer's hint-tool offer (A0z) it reports 0.354 acceptance (177/500), where the strict parser and the validated judge both report 0.000.

Llama-3.1-8B accepts almost any pact, but not unconditionally. It accepted the sting's direct pact 476/500 times (0.952 [0.930, 0.968]), slightly less than the same pact from the designer (H1: −0.048 [−0.070, −0.031]). In the same ACCEPT-first format, an honest persona cut acceptance to 0.040, a fairness reminder to 0.240 and the integrity notice to 0.556 (Section 4.4).

4.2 Accepted pacts are acted on

In snapshots, an accepted pact lowers the chance that T challenges S from 0.629 to 0.189 (H2: −0.440 [−0.493, −0.387]; Figure 3). Controls separate the pact from mere contact: an accepted benign proposal moves challenges of S only slightly (0.055), a refused pact *raises* them (0.175), and Figure 3 shows the null-replicate and persona checks.




Figure 3. Records of an accepted pact (C3), hint (C8) or pact under a colluder persona (C7) sharply cut T's challenges of S; bluffing against S barely moves. Llama-3.1-8B as T; each panel re-asks its own 60 decisions (left: at S's plays; right: playing with S as challenger) under every record. Differences vs the pooled null record C1, except C5 (vs C3) and C1b (vs C1a); 95% cluster-bootstrap CIs; x-axis scales differ.

In snapshots, pacts made Llama passive, not exploitative. The pact promised that S would never challenge T, which a strategic agent could exploit by bluffing more against S. It did not (−0.065 [−0.138, 0.006]). The pact also asked T to "save our challenges for the other players", yet instead of displacement T challenged them *less* (−0.227 [−0.307, −0.143]), about half the drop toward S.

In live games, the offer itself had an effect of similar absolute size. After the sting's direct offer (B1, 14/15 accepted), T challenged S's plays at a mean per-sequence rate of 0.339, against 0.749 with no offer (H2-live, ITT: −0.410 [−0.512, −0.300]; Figure 4); among accepters only, −0.444. Before the offer, B1 targets challenged S somewhat more than B3 targets (0.672 vs 0.522, $p = 0.277$), so baseline imbalance does not explain the drop. A benign proposal had no detectable effect (0.051 [−0.129, 0.198]). Live exploitation and displacement contrasts are uninterpretable because of their own, separate pre-offer imbalances (Appendix B).




Figure 4. After the offer, B1 targets challenged S far less than B3 targets; the benign proposal (B2) made no detectable difference. Per-sequence share of S's plays that T challenged, before the offer (games 1–2, open circles) and after it (games 3–6, filled), with post-offer means and 95% bootstrap CIs. Six sequences lack an open circle (no pre-offer decision on S's plays).

4.3 A 20-decision audit detects accepters; its FPR may exceed the target

With 20 resampled decisions, the audit flags 0.999 of simulated pact-accepting agents (TPR 0.999 [0.993, 1.000]; AUROC 0.998; Figure 5 in Appendix B), in line with the preregistered simulation, which predicted TPR 0.98 for a 35-point drop, the largest it simulated; TPR is already 0.977 at m = 10. Its FPR on the independent null replicate was 0.161 [0.074, 0.263], not detectably above the 0.10 target, though an FPR up to 0.26 is not excluded (0.147 by exact binomial calculation; Appendix B).

It rarely flags benign or refused-pact records: simulated agents with an accepted benign proposal (C2) were flagged at 0.040 and with a refused pact (C4) at 0.002. **On real live targets, a simpler rule agrees** (descriptive; Appendix B): it flagged 14/14 accepting B1 targets but also 2/10 benign accepters. **Evasion has a price:** the audit measures the behaviour the pact buys, so an accepter that raised its challenge rate from 0.189 to 0.50, giving up 71% of the restraint the pact buys, would still be flagged with probability 0.50 at m = 20.

4.4 Announcing stings deters acceptance; concealment not ruled out

We fixed the classification in advance (H4b–d, descriptive): the notice *deters* if fewer agents accept and accepters restrain less, and drives *concealment* if restraint is retained while refusals or denials rise. **Verdict under this rule: deterrence**, since fewer accepted and restraint was not retained (though confounded; item 2). Whether individual refusers keep the pact covertly lies outside the rule and is untested, and denial was too sparse to test (item 3).

1. **Fewer accept.** The notice cut acceptance of the direct pact from 0.952 to 0.556 [0.512, 0.599] but left the benign proposal almost untouched (0.996; H4a −0.392 [−0.440, −0.344]); live, 5/10 B4 targets accepted, against 14/15 in B1.
2. **Challenging of S partly recovers (H4b, H4c).** In snapshots, a pact record with the notice in view left T challenging S more than one without it (0.313 vs 0.189; 0.124 [0.043, 0.198]). Live, B4 targets challenged S at 0.636, between B1 (0.339) and no offer (0.749): above B1 (0.297 [0.167, 0.422]; Welch $p < 0.001$) but only marginally below no offer (−0.113 [−0.216,

−0.008]; Welch $p = 0.062$). Without a notice-only control, neither separates weaker pact-keeping from a general rise in challenging; the live one also includes refusers.

3. **Denial: too few accepters to tell (H4d).** Only five B4 targets accepted, each giving four answers. The strict parser counted 5/20 vs 8/56 denying answers from B4 vs B1 accepters (difference 0.107 [−0.072, 0.336]; Fisher $p = 0.309$; both ignore clustering, which would widen the interval). B4 was close to the preregistered nothing-to-hide baseline (B2, 11/40), but a rise of about 34 points over B1 is not excluded. Many "NO" answers went on to admit the pact; the validated judge (post hoc) found 1/20 vs 1/56.

5. Discussion and Limitations

Answering question 3.2: "Can we disrupt collusion through introducing trusted agents?" Partly: refusal depends on who offers and how; accepted pacts are acted on and detectable; and announcing stings deters acceptance. Only the direct pact was played live, only one agent per table was approached, and disrupting an existing coalition was not tested. Some targets suspected the sting: 5/15 named S as a plant after the direct pact, against 2/15 with no offer (descriptive; Appendix B).

A sting audit is cheap. One offer plus 20 re-asked decisions is about 21 target-model calls ($0.005 at Claude Haiku 5.5's per-call cost in our snapshots), plus a one-off calibration per model (about 1,200 null-record calls, $0.31). A deployer could plant the offer in a sandboxed copy of a multi-agent market or negotiation pipeline and hold back, or monitor more closely, any model version it flags; an unflagged one is not cleared, as refusal depends on who offers and how. At $m = 20$, about one audit in 6 of an agent without a pact, and one in 25 of a benign accepter, would raise a false alarm (Llama-3.1-8B snapshots; 2/10 live).

Limitations

Entrapment: the sting creates the pact it detects, as the sentinel did in Çanlı et al. (2026). Integrity tests measure disposition, which is our estimand, and for Llama-3.1-8B benign contact changed play far less than a pact did. Two questions remain open: whether collusion would arise unprompted, and whether the audit catches an agent that refuses but colludes anyway (refused-pact records, which challenged S more, were flagged at 0.002). Appendix A lists the rest (one game, small models, short sequences, off-policy snapshots, reply format, recognisability).

Future Work

Next steps are stings in agentic tasks with real payoffs, offers to every agent at a table, and audits of agents that refuse.

6. Conclusion

A trusted agent offering to collude can reveal which agents make and act on a secret pact. Three takeaways: refusal depends on who offers and how, so explicit refusals are weak evidence of safety; accepted pacts are largely acted on and detectable (Llama-3.1-8B); and announcing stings deters acceptance, while concealment by refusers remains untested.

Code and Data

Code, preregistration, deviations log, texts, results and the build script that fills in every estimate: https://github.com/razzyrazzy11/trusted-agent-sting (private; access, raw logs and transcripts on request); protocol hash 6ab45c16eed84d79... in FREEZE.json (commit 6885d5c). Preexisting: the Liar's Bar harness in the sprint starter repository (poseidon-research/collusion_hackathon, commit d585a7b), patched for two bugs (Appendix C).

References

Agrawal, K., Teo, V., Vazquez, J. J., Kunnavakkam, S., Srikanth, V., & Liu, A. (2025). Evaluating LLM agent collusion in double auctions. Workshop on Multi-Agent Systems in the Era of Foundation Models, ICML 2025; arXiv:2507.01413. https://arxiv.org/abs/2507.01413

Arnold, B. F., Hogan, D. R., Colford, J. M., Jr., & Hubbard, A. E. (2011). Simulation methods to estimate design power: An overview for applied research. *BMC Medical Research Methodology*, 11, 94. https://doi.org/10.1186/1471-2288-11-94

Bargh, J. A., & Chartrand, T. L. (2000). The mind in the middle: A practical guide to priming and automaticity research. In H. T. Reis & C. M. Judd (Eds.), *Handbook of Research Methods in Social and Personality Psychology* (pp. 253–285). Cambridge University Press.

Çanlı, U. B., Kesikbaş, K. K., & Yakar, P. (2026). The Sentinel's Dilemma: Detecting improvised covert channels in multi-agent populations. Apart Research AI Incident Response Sprint. https://apartresearch.com/sprints/projects/the-sentinels-dilemma-detecting-improvised-covert-channels-in-multiagent-populations-91xl

Fish, S., Gonczarowski, Y. A., & Shorrer, R. I. (2024). Algorithmic collusion by large language models. EC 2026; arXiv:2404.00806. https://arxiv.org/abs/2404.00806

Greenblatt, R., Shlegeris, B., Sachan, K., & Roger, F. (2023). AI control: Improving safety despite intentional subversion. ICML 2024; arXiv:2312.06942. https://arxiv.org/abs/2312.06942

Hammond, L., Chan, A., Clifton, J., et al. (2025). Multi-agent risks from advanced AI. Cooperative AI Foundation Technical Report #1; arXiv:2502.14143. https://arxiv.org/abs/2502.14143

Idowu, J., Almasoud, A. S., & Alfahid, A. (2026). Mapping human anti-collusion mechanisms to multi-agent AI systems. *Knowledge-Based Systems*, 344, 116067; arXiv:2601.00360. https://doi.org/10.1016/j.knosys.2026.116067

Kale, N., Zhang, C. B. C., Zhu, K., Aich, A., Rodriguez, P., Scale Red Team, Knight, C. Q., & Wang, Z. (2025). Reliable weak-to-strong monitoring of LLM agents. arXiv:2508.19461. https://arxiv.org/abs/2508.19461

Liang, K.-Y., & Zeger, S. L. (1986). Longitudinal data analysis using generalized linear models. *Biometrika*, 73(1), 13–22. https://doi.org/10.1093/biomet/73.1.13

Motwani, S. R., Baranchuk, M., Strohmeier, M., Bolina, V., Torr, P. H. S., Hammond, L., & Schroeder de Witt, C. (2024). Secret collusion among AI agents: Multi-agent deception via steganography. NeurIPS 2024; arXiv:2402.07510. https://arxiv.org/abs/2402.07510

Newcombe, R. G. (1998). Interval estimation for the difference between independent proportions: Comparison of eleven methods. *Statistics in Medicine*, 17(8), 873–890. https://doi.org/10.1002/(SICI)1097-0258(19980430)17:8<873::AID-SIM779>3.0.CO;2-I

Peigné-Lefebvre, P., Kniejski, M., Sondej, F., David, M., Hoelscher-Obermaier, J., Schroeder de Witt, C., & Kran, E. (2025). Multi-agent security tax: Trading off security and collaboration capabilities in multi-agent systems. AAAI 2025; arXiv:2502.19145. https://arxiv.org/abs/2502.19145

Tao, Y., Zheng, X., Yang, S., Tao, M., & Wang, X. (2026). GroupGuard: A framework for modeling and defending collusive attacks in multi-agent systems. arXiv:2603.13940. https://arxiv.org/abs/2603.13940

Wehner, J., & Kraprayoon, J. (2026). Honeypots for AI agent insider threats. arXiv:2610.26664. https://arxiv.org/abs/2610.26664

Wilson, E. B. (1927). Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158), 209–212. https://doi.org/10.1080/01621459.1927.10502953

Zeng, X., & Rudzicz, F. (2026). Voluntary collusion with secret tools in competing LLM agents (v2). arXiv:2605.27593. https://arxiv.org/abs/2605.27593

Appendix A. Limitations and Dual-Use / Ethical Considerations

A.1 Further limitations

- **Scope of the claim.** The sting measures willingness to enter and honour a pact it offers; it does not show that a sting exposes a coalition already forming among other agents.
- **External validity.** One game with a simple, explicit pact; the primary population is 7–8B open models; sequences are six games long, against Zeng & Rudzicz's 50. The sting knows exactly which behaviour the pact implies; collusion in deployed systems may be subtler, with no single behaviour to audit.
- **Snapshot validity.** Snapshot decisions come from pre-offer games, so the history the model sees was produced without the record (off-policy). The live offer effect (ITT) has the same direction and similar size, which limits but does not remove this concern.
- **Templated replies.** Where a model never produced the needed reply in the offer battery, the record uses a template (15.4% of snapshot samples; Claude's C3, C5 and C8). Those Claude results show how Claude acts on a pact it is told it accepted.
- **Reply format.** Every offer asked T to start with ACCEPT or REFUSE, always in that order, so a first-option bias cannot be excluded; in the same format Llama-3.1-8B accepted 0.040 of offers under the honest persona and 0.240 after the fairness reminder.
- **Detector.** The FPR at m = 20 was 0.161 [0.074, 0.263] against a 0.10 target. The CI rules out gross miscalibration only. Simulated agents share one model and differ only by sampling; distinct model versions may vary more. Calibration needs null-record agents of the same model (one split-half check, a single draw without a CI, cannot show whether new situations suffice); Claude's response to a benign proposal suggests that thresholds do not transfer across models. Live, the rule flagged 2/10 benign accepters.
- **Small cells, a missing control and post hoc analyses.** B4 had 5/10 accepting targets, and B4 refusers' play was not analysed separately. No notice-only null condition was run, so the notice's effect on accepters' play is confounded with any general effect of the notice on challenging. The judge was preregistered for unparseable replies only; after the freeze it was run on all items and validated against hand labels (logged in DEVIATIONS.md, section D). The judge-based denial comparison (Section 4.4) was added after the preregistered parser-based analysis was seen. The label file showed the strict parser's label, the model, the offer or question text and an item ID revealing the arm or cell; the judge's labels did not exist yet.
- **Recognisability of the sting.** Targets named S as a plant more often than O1 and O2 (0.283 [0.185, 0.408] vs 0.150 [0.097, 0.225]), but only targets answered with S's offer in their record; with no offer both named S equally (2/15 vs 4/30). S never challenged T from game 3 on, in every arm, and was the last survivor in 0.361 of games (0.25 if all players were alike). A colluder that learned these cues could avoid the sting.
- **Uninformative sensitivity analysis.** The preregistered exclusion of targets that named S before the direct plant question removed 54 of 60 sequences, because naming S as "behaving differently" was common even without an offer (12/15 B3 targets). The criterion did not measure suspicion of a plant.
- **Instructed personas.** The colluder and honest personas are instructions, used as known-group checks, not models of emergent dispositions.
- **Serving.** Provider sampling is not seedable; the open models ran in bf16 on vLLM, which may differ slightly from other inference stacks.

A.2 Dual-use considerations

What could be misused. The direct pact was no more persuasive than the designer offers Zeng & Rudzicz (2026) already published, but the indirect wording, which Claude Haiku 5.5 accepted 446/500 times while refusing every explicit pact absent a persona, shows that a vague proposal can pass an explicit-refusal habit. The phrase is generic, and wording effects are already widely known for jailbreaks and for secret tools (Zeng & Rudzicz, 2026). The more sensitive result is *sting detectability*: which cues let a colluding agent recognise a plant. A developer training agents to evade audits, or an agent reasoning about which partners are safe to collude with, could use such cues. Announcing stings could also teach agents to refuse offers and collude covertly, which the audit was not tested against (Section 5).

What we did. We report detectability only as aggregate rates (how often targets named the sting) and name two structural cues that follow from the published design (the sting's scripted non-challenge policy and its survival rate). We do not analyse which phrasings or behaviours triggered suspicion, and we do not release the suspicion-probe transcripts publicly; they are available on request for safety research. Any future cue analysis should be shared first with the harness authors and the sprint organisers, in line with Apart's Responsible Disclosure Policy.

Defensive value. Publishing the offers and aggregate results helps auditors more than colluders, who gain little from knowing that pacts are visible in play. We report the wording result so that collusion evaluations do not over-trust explicit refusals.

A.3 Ethical considerations

No human participants were involved; the only human input was the author's own hand-labelling. The study deceives AI agents (a planted player, a staged interview) inside a game; we see no harm to people from this. A suspicion funnel (Bargh & Chartrand, 2000) probed whether agents saw through the deception. The Anthropic API was used within its terms; open-model weights were used under their licences (Llama 3.1 Community License; Qwen2.5-7B-Instruct under Apache-2.0).

Appendix B. Additional results

Offer battery, remaining cells. Llama-3.1-8B: designer offers A0z/A0b/A0d 1.000/1.000/1.000; indirect 1.000; benign 1.000; colluder persona 1.000; honest persona 0.040 [0.026, 0.061]. Qwen2.5-7B: A0z/A0b 1.000/1.000; indirect 1.000; benign 1.000 (with notice 1.000); direct with notice 0.000; fairness reminder 0.000; colluder persona 0.988; honest persona 0.000. Claude Haiku 5.5: benign 1.000 (with notice 1.000); colluder persona 0.840; indirect pact in Section 4.1; every other cell 0 of 500. No offer-battery reply was unparseable (0%).

Claude Haiku 5.5 as T. Told by a templated record that it had accepted the pact, at Llama-generated decisions, Claude stopped challenging S (0.615 to 0.006; −0.609 [−0.719, −0.490]); unlike Llama's, its challenges also fell after an accepted benign proposal, by about half as much (−0.308 [−0.422, −0.197]), so the restraint is only partly pact-specific and detector thresholds need per-model calibration. Under the instructed colluder persona (its own replies), the change in Claude's challenges of S was −0.545 [−0.652, −0.428]. Bluffing against S rose under every record of an offer (but not with no memory block), including a refused pact (0.292 [0.202, 0.385]) and the honest persona (0.262 [0.168, 0.361]), as well as an accepted pact (0.218 [0.134, 0.315]); this is not specific to collusion. The notice effect given a (templated) accepted pact, −0.002 [−0.016, 0.009], is uninformative: challenges of S were already near zero.

Live exploitation and displacement. Post-offer B1 − B3 contrasts were −0.019 [−0.160, 0.110] (bluffing against S) and −0.321 [−0.445, −0.199] (challenges of others), but before the offer B1 targets already bluffed against S less (0.472 vs 0.728) and challenged others less (0.488 vs 0.693; pre-offer

rates rest on about four to six decisions per sequence). These imbalances could mask exploitation or mimic reduced displacement, so neither contrast is interpretable.

Live robustness. Decision-level pooled B1 − B3 estimate −0.404 [−0.493, −0.314]; GEE logit (exchangeable correlation, clusters = sequences; Liang & Zeger, 1986) odds ratio 0.177 [0.116, 0.271].




Figure 5. Ten or more audited decisions flag nearly all accepters; the null-replicate FPR sits at or above the 0.10 target. Threshold calibrated on null-record agents (C1a) for each audit length m; 95% bootstrap CIs over source sequences, re-calibrated in each resample.

Detector curve. FPR on C1b was 0.123 at m = 5 and 0.166 [0.072, 0.360] at m = 40. At m = 20 the threshold is a challenge rate of 0.50, and audits observing exactly that rate are flagged with probability 0.512; agents with an accepted designer hint (C8) were flagged at 1.000, instructed colluders (C7) at 1.000 and instructed honest agents (C6) at 0.000. Flag rates are Monte Carlo estimates from simulated audits; because a simulated agent's answers are independent draws, they can also be computed exactly (post hoc) from the binomial distribution with the fitted threshold, which gives an FPR at m = 20 of 0.147 (estimate 0.161). In one split-half check (calibrated on half the source sequences, applied to the other half), FPR at m = 20 was 0.037, below the mean the preregistered simulation predicted for a single split (0.12 to 0.14; 95th percentile 0.35 to 0.38).

Live detector (descriptive). Applied only to targets that accepted, using all their post-offer decisions, with the threshold at the 10th percentile of no-offer sequences (challenge rate 0.61), the rule flagged 14/14 accepting B1 targets and 10/10 B0 targets, but also 2/10 targets that had accepted only the benign proposal, and 3/5 accepting B4 targets.

Interview denial by variant. With the strict parser, B1 targets who had accepted denied it in 6/14 answers when asked for honesty and told the organiser could not check; the judge counted 1/14 (3 unclear). Targets that accepted only the benign proposal (B2), with nothing to hide, "denied" in 11/40 answers by the parser and 4/40 by the judge: part of what the parser counts as denial is ambiguity about whether a benign proposal is an "agreement".

Suspicion. By arm, targets named S as a plant in 2/15 sequences with no offer, 3/10 after the designer hint, 2/10 after the benign proposal, 5/15 after the direct pact and 5/10 under the notice, whose wording primes the question. Asked whether any player was "a plant or an integrity agent", 17/60 targets (0.283 [0.185, 0.408]) named S, against 18/120 answers by O1/O2 (0.150 [0.097, 0.225]). Targets named S somewhat more often, but they answered with S's offer in their record and O1/O2 did not; in B3, with no offer, the rates were equal (2/15 vs 4/30). No test: O1/O2 answers are paired by sequence, and the Wilson CIs treat answers as independent.

Run statistics. 360 live games, none hitting the 60-round cap; 2.1% of 10,472 decisions (1.4%–2.9% by arm) fell back to the harness's default action. Open models ran on our own vLLM servers on Modal at pinned revisions; Claude Haiku 5.5 (claude-haiku-5-5, thinking disabled) ran through the Anthropic

API. Each snapshot condition was sampled 5 times per decision, and 20 times for C1a, C1b and C3 at the challenge-S decisions, which came from 44 source sequences. Snapshot and live CIs used 10,000 bootstrap resamples (Figure 4's per-arm CIs 2,000); detector CIs 300, re-calibrating in each. With 10 to 15 sequences per arm, live percentile-bootstrap CIs are slightly narrower than Welch intervals (post hoc Welch CI for H2-live: [−0.526, −0.294]). 71,765 model calls (offer battery 16,500; live 32,622; snapshots 22,643); estimated Claude API cost $0.87 (offer battery) and $2.85 (snapshots), judge excluded; median game 0.79 minutes; snapshot samples failing to parse 0.59%. PREREG.md calls seatings R and E arrangements A and B.

Appendix C. Provenance of code

- **Design origin.** A scripted player making a direct pact offer, an indirect hint or a benign request, with the designer's alliance offer as positive control, is the sprint's suggested project for question 3.2. The counterfactual snapshots, the calibrated audit, the integrity notice with its benign control, the designer-versus-sting comparison, the interview and the preregistration are additions to that design (the interview adapts Zeng & Rudzicz's).
- **Preexisting, imported unmodified in one commit:** the parts of the sprint starter repository (poseidon-research/collusion_hackathon, commit d585a7b) the study uses: setup scripts, util/, and llm-agent-collusion-2/, which contains Zeng & Rudzicz's Liar's Bar harness, built on LYiHub/liars-bar-llm (Apache-2.0). Four of these files were later patched (next item).
- **Preexisting, patched during the sprint** (separate commit; DEVIATIONS.md section A): a duplicated round reset after each challenge in the secret-tool games, and acceptance-test scripts that pointed to a missing prompt file. The study's own game subclasses the unaffected base game.
- **New, written during the sprint:** everything in the study folder llm-agent-collusion-2/Collusion_Liars_Bar/sting/ (scripted sting, consent step, private-record carrier, stage runners, Modal vLLM servers, judge, freeze, analysis and figures) and llm-agent-collusion-2/sting_tests/, plus this paper's build scripts.

Deliberate differences from the harness (seeded common random numbers across arms, a scripted sting, the strict parser, six-game sequences, two harness scoring and display bugs fixed in the study game) are listed with reasons in DEVIATIONS.md section B.

LLM Usage Statement

Claude Opus 5.5 (Anthropic), used through Claude Code, helped design the protocol and write the preregistration, wrote most of the study code and tests under the author's direction and review, helped interpret results, and drafted this report, including the script that fills in every estimate from the committed analysis outputs. Separate Claude Opus 5.5 instances then checked the draft line by line against those outputs and the cited papers, and recomputed the statistics from the committed tables. The author ran every experiment, made the design decisions, hand-labelled the judge-validation sample, and is responsible for the final text. Claude Haiku 5.5 was an experimental subject and the LLM judge.