

Lexmark X950 Series Product Specifications

	Lexmark X950de	Lexmark X952dte	Lexmark X954dhe
Printing			
Print Technology	Color LED		
Print Speed (Letter, Black): Up to	45 ppm	50 ppm	55 ppm
Print Speed (Letter, Color): Up to	40 ppm	45 ppm	50 ppm
Time to First Page (Black)	As fast as 5.5 seconds	As fast as 5.2 seconds	As fast as 5.0 seconds
Time to First Page (Color)	As fast as 7.7 seconds	As fast as 7.7 seconds	As fast as 7.2 seconds
Print Resolution, Black	1200 x 1200 dpi, 2400 Image Quality		
Print Resolution, Color	1200 x 1200 dpi, 2400 Image Quality		
Memory, Standard	1024 MB	1024 MB	2048 MB
Memory, Maximum	2048 MB		
Hard Disk	Included in configuration		
Print Noise Level, Operating	52 dBA	52 dBA	53 dBA
Noise Level, Idle	24 dBA		
Maximum Monthly Duty Cycle: Up to	200000 pages per month	225000 pages per month	250000 pages per month
Recommended Monthly Page Volume	5000 - 33000 pages		
Supplies			
Supplies Yield	22,000 ² -page color (CMY) Toner Cartridges, 32,000 ² -page Black Toner Cartridge		
Copying			
Copy Speed (Letter, Black): Up to	45 cpm	50 cpm	55 cpm
Copy Speed (Letter, Color): Up to	40 cpm	45 cpm	50 cpm
Scanning			
ADF Scan		RADF (Reversing Duplex)	RADF (Reversing Duplex)
Scanning Resolution	600 X 600 dpi		
Reduce / Enlarge Range	25 - 400 %		
Faxing			
Modem Speed	33.6 Kbps		
Paper Handling			
Paper Handling Standard	500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray	500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray, 3 x 520-Sheet Drawer Stand	500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray, 2,520-Sheet Tandem Tray Module
Paper Handling Optional	2,000-Sheet High-Capacity Feeder, 3,500-Sheet Finisher, 3 x 520-Sheet Drawer Stand, Booklet Finisher, 2,520-Sheet Tandem Tray Module, 520-Sheet Drawer Stand	2,000-Sheet High-Capacity Feeder, 3,500-Sheet Finisher, Booklet Finisher	2,000-Sheet High-Capacity Feeder, 3,500-Sheet Finisher, Booklet Finisher
Paper Input Capacity, Standard: Up to	620 pages 20 lb or 75 gsm bond	2180 pages 20 lb or 75 gsm bond	3140 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum: Up to	5140 pages 20 lb or 75 gsm bond	4180 pages 20 lb or 75 gsm bond	5140 pages 20 lb or 75 gsm bond
ADF Paper Input Capacity : Up to	110 pages 20 lb or 75 gsm bond		
Media Types Supported	Card Stock, Envelopes, Glossy Paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide		
General			
Function	Color Copying, Color Faxing, Color Printing, Color Scanning, Color Network Scanning		
Product Warranty	1-Year Onsite Service, Next Business Day		
Product Certifications		www.lexmark.com	www.lexmark.com
Size (in. - H x W x D)	30.01 x 25.20 x 26.97 in.	44.38 x 25.20 x 26.97 in.	44.38 x 25.20 x 26.97 in.
Weight (lb.)	255.8 lb.	332.2 lb.	351.8 lb.
Specified Operating Environment	Altitude: 0 - 2500 Meters (8,200 Feet), Temperature: 10 to 32°C (50 to 90°F), Humidity: 15 to 85% Relative Humidity		
	Altitude: 0 - 2500 Meters (8,200 Feet), Temperature: 10 to 32°C (50 to 90°F), Humidity: 15 to 85% Relative Humidity		

Recommended Monthly Page Volume

«Recommended Monthly Page Volume» is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

Maximum Monthly Duty Cycle

«Maximum Monthly Duty Cycle» is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

Footnotes

- ¹ Source: InfoTrends/CapVentures, Network Document Solutions Forecast 2007-2012, Network Document Solutions Consulting Service, August 2008
- ² Average continuous black or continuous composite CMY declared cartridge yield in accordance with ISO/IEC 19798.
- ³ Change Language is an option during installation.
- ⁴ Illustration shows enlarged description of touch screen.



Trademarks

Lexmark and Lexmark with the diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners. ENERGY STAR® is a U.S. registered mark. Information in this document is subject to change without notice. PANTONE® is a registered trademark of Pantone, Inc. This product features Adobe® Flash® technology. For further information, visit <http://www.adobe.com/software/flash/about/>

Print Less. Save More.

www.lexmark.com

LEXMARK
TM