

Lexmark X792 Family: product specifications

Lexmark X792de		Lexmark X792dte		Lexmark X792dtme		Lexmark X792dtpe	
Printing							
Print Technology		Color Laser					
Print Speed (Letter, Black): Up to		50 ppm					
Print Speed (Letter, Color): Up to		50 ppm					
Time to First Page (Black)		As fast as 8 seconds					
Time to First Page (Color)		As fast as 8.5 seconds					
Print Resolution, Black		1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)					
Print Resolution, Color		1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)					
Memory, Standard		1024 MB					
Memory, Maximum		2048 MB					
Hard Disk		Included in configuration					
Print Noise Level, Operating		52 dBA					
Noise Level, Idle		27 dBA					
Maximum Monthly Duty Cycle: Up to		150000 pages per month					
Recommended Monthly Page Volume		2500 - 17000 pages					
Supplies							
Supplies Yield		6,000*-page (CMYK) Print Cartridges, 20,000*-page (CMYK) Extra High Yield Print Cartridges					
(*Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.)							
Copying							
Copy Speed (Letter, Black): Up to		50 cpm					
Copy Speed (Letter, Color): Up to		50 cpm					
Scanning							
ADF Scan		DADF (Single Pass Duplex)					
Scanning Resolution		600 X 600 dpi					
Reduce / Enlarge Range		25 - 400 %					
Faxing							
Modem Speed		33.6 Kbps					
Paper Handling							
Paper Handling Standard		500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray	500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray, 2 x 550-Sheet Drawers	500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray, 2 x 550-Sheet Drawers, 5-Bin Mailbox	500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray, 2 x 550-Sheet Drawers, 500-Sheet Staple Punch		
Paper Handling Optional		5-Bin Mailbox, 550-Sheet Drawer, 2,000-Sheet High-Capacity Feeder, 500-Sheet Offset Stacker, 500-Sheet Staple Finisher, 500-Sheet Staple Punch Finisher	5-Bin Mailbox, 550-Sheet Drawer, Banner Media Tray, 500-Sheet Offset Stacker, 500-Sheet Staple Finisher, 500-Sheet Staple Punch Finisher	550-Sheet Drawer	550-Sheet Drawer		
Paper Input Capacity, Standard: Up to		650 pages 20 lb or 75 gsm bond	1750 pages 20 lb or 75 gsm bond	1750 pages 20 lb or 75 gsm bond	1750 pages 20 lb or 75 gsm bond		
Paper Input Capacity, Maximum: Up to		2650 pages 20 lb or 75 gsm bond	2300 pages 20 lb or 75 gsm bond	2300 pages 20 lb or 75 gsm bond	2300 pages 20 lb or 75 gsm bond		
ADF Paper Input Capacity : Up to		75 pages 20 lb or 75 gsm bond					
Media Types Supported		Card Stock, Dual Web Labels, Envelopes, Glossy Paper, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Card Stock & Label Guide, Outdoor Media, Banner Paper	Card Stock, Dual Web Labels, Envelopes, Glossy Paper, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Card Stock & Label Guide, Outdoor Media, Banner Paper	Card Stock, Dual Web Labels, Envelopes, Glossy Paper, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Card Stock & Label Guide, Outdoor Media	Card Stock, Dual Web Labels, Envelopes, Glossy Paper, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Card Stock & Label Guide, Outdoor Media		
General							
Function		Color Copying, Color Faxing, Color Printing, Color Scanning, Color Network Scanning					
Product Warranty		1-Year Onsite Service, Next Business Day					
Product Certifications		www.lexmark.com					
Size (in. - H x W x D)		32.5 x 22.0 x 20.0 in.	47.4 x 24.05 x 25.9 in.	47.4 x 41.55 x 25.9 in.	47.4 x 41.55 x 25.9 in.		
Weight (lb.)		161 lb.	247 lb.	279 lb.	285 lb.		
Specified Operating Environment		Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)					
Furniture							
Caster Base		Optional, (Required for floor standing configuration)	(Included)	(Included)	(Included)		
Spacer		Available					

Recommended Monthly Page Volume

«Recommended Monthly Page Volume» is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

Maximum Monthly Duty Cycle

«Maximum Monthly Duty Cycle» is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

Trademarks

Lexmark and Lexmark with the diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners. ENERGY STAR® is a U.S. registered mark. Information in this document is subject to change without notice. PANTONE® is a registered trademark of Pantone, Inc. This product features Adobe® Flash® technology. For further information, visit <http://www.adobe.com/software/flash/about/>. AirPrint and the AirPrint logo are trademarks of Apple Inc.

Print Less. Save More.

www.lexmark.com



LEXMARK
TM