

# Lab\_13\_RNASeq\_project

Ryan Bench (PID: A69038034)

## Table of contents

Background . . . . .	1
Data Import . . . . .	2
Setup for DESeq . . . . .	3
Run DESeq . . . . .	6
Get results . . . . .	7
Add annotation . . . . .	7
Visualize results . . . . .	9
Pathway analysis . . . . .	10
Let's try GO analysis and compare to KEGG analysis . . . . .	12
Reactome . . . . .	13
Save results . . . . .	13

## Background

Today we will run through a complete RNASeq analysis

The data for hands-on session comes from GEO entry: GSE37704, which is associated with the following publication:

Trapnell C, Hendrickson DG, Sauvageau M, Goff L et al. "Differential analysis of gene regulation at transcript resolution with RNA-seq". Nat Biotechnol 2013 Jan;31(1):46-53. PMID: 23222703

The authors report on differential analysis of lung fibroblasts in response to loss of the developmental transcription factor HOXA1. Their results and others indicate that HOXA1 is required for lung fibroblast and HeLa cell cycle progression. In particular their analysis show that "loss of HOXA1 results in significant expression level changes in thousands of individual transcripts, along with isoform switching events in key regulators of the cell cycle". For our session we have used their Sailfish gene-level estimated counts and hence are restricted to protein-coding genes only.

## Data Import

```
counts <- read.csv("GSE37704_featurecounts.csv", row.names = 1)
metadata <- read.csv("GSE37704_metadata.csv")
```

Check correspondence of metadata and counts (i.e. that the columns in counts match the rows of metadata)

```
metadata
```

	id	condition
1	SRR493366	control_sirna
2	SRR493367	control_sirna
3	SRR493368	control_sirna
4	SRR493369	hoxa1_kd
5	SRR493370	hoxa1_kd
6	SRR493371	hoxa1_kd

```
colnames(counts)
```

```
[1] "length"      "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370"
[7] "SRR493371"
```

```
metadata$id
```

```
[1] "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370" "SRR493371"
```

```
counts <- counts[, -1]
```

```
test_cols <- !all(colnames(counts) == metadata$id)
```

Also lets remove low count genes

```
tot.counts <- rowSums(counts)
head(tot.counts)
```

ENSG00000186092	ENSG00000279928	ENSG00000279457	ENSG00000278566	ENSG00000273547
0	0	183	0	0
ENSG00000187634				
1129				

Let's remove all zero count genes

```
zero.inds <- tot.counts == 0  
head(zero.inds)
```

```
ENSG00000186092 ENSG00000279928 ENSG00000279457 ENSG00000278566 ENSG00000273547  
                TRUE             TRUE             FALSE             TRUE             TRUE  
ENSG00000187634  
                FALSE
```

```
counts <- counts[!zero.inds, ]
```

```
all(colnames(counts)[-1] == metadata$id)
```

Warning in colnames(counts)[-1] == metadata\$id: longer object length is not a multiple of shorter object length

```
[1] FALSE
```

```
if( !all(c(T,T,F))) {  
  message("Wow..... there is a problem with the metadata counts setup!")  
}
```

Wow..... there is a problem with the metadata counts setup!

```
head(counts)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000279457	23	28	29	29	28	46
ENSG00000187634	124	123	205	207	212	258
ENSG00000188976	1637	1831	2383	1226	1326	1504
ENSG00000187961	120	153	180	236	255	357
ENSG00000187583	24	48	65	44	48	64
ENSG00000187642	4	9	16	14	16	16

## Setup for DESeq

```
library(DESeq2)
```

```
Loading required package: S4Vectors
```

```
Loading required package: stats4
```

```
Loading required package: BiocGenerics
```

```
Loading required package: generics
```

```
Attaching package: 'generics'
```

```
The following objects are masked from 'package:base':
```

```
as.difftime, as.factor, as.ordered, intersect, is.element, setdiff,  
setequal, union
```

```
Attaching package: 'BiocGenerics'
```

```
The following objects are masked from 'package:stats':
```

```
IQR, mad, sd, var, xtabs
```

```
The following objects are masked from 'package:base':
```

```
anyDuplicated, aperm, append, as.data.frame, basename, cbind,  
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,  
get, grep, grepl, is.unsorted, lapply, Map, mapply, match, mget,  
order, paste, pmax, pmax.int, pmin, pmin.int, Position, rank,  
rbind, Reduce, rownames, sapply, saveRDS, table, tapply, unique,  
unsplit, which.max, which.min
```

```
Attaching package: 'S4Vectors'
```

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: Seqinfo

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,  
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,  
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,  
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,  
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,  
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,  
colWeightedMeans, colWeightedMedians, colWeightedSds,  
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,  
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,  
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,  
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,  
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,  
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,  
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,  
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with  
'browseVignettes()'. To cite Bioconductor, see  
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

```
dds <- DESeqDataSetFromMatrix(countData = counts, colData = metadata, design = ~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in  
design formula are characters, converting to factors

## Run DESeq

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

## Get results

```
res <- results(dds)
```

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43990e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215598	1.040744	2.97994e-01
	padj				
	<numeric>				
ENSG00000279457	6.86555e-01				
ENSG00000187634	5.15718e-03				
ENSG00000188976	1.76549e-35				
ENSG00000187961	1.13413e-07				
ENSG00000187583	9.19031e-01				
ENSG00000187642	4.03379e-01				

## Add annotation

```
library()
```

```
library(AnnotationDbi)
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

```

[1] "ACCNUM"      "ALIAS"      "ENSEMBL"    "ENSEMBLPROT" "ENSEMBLTRANS"
[6] "ENTREZID"    "ENZYME"     "EVIDENCE"   "EVIDENCEALL"  "GENENAME"
[11] "GENETYPE"    "GO"         "GOALL"      "IPI"           "MAP"
[16] "OMIM"        "ONTOLOGY"   "ONTOLOGYALL" "PATH"          "PFAM"
[21] "PMID"        "PROSITE"    "REFSEQ"     "SYMBOL"        "UCSCKG"
[26] "UNIPROT"

```

```

res$symbol = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")

```

'select()' returned 1:many mapping between keys and columns

```

res$entrez = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")

```

'select()' returned 1:many mapping between keys and columns

```

res$name = mapIds(org.Hs.eg.db,
                  keys=row.names(res),
                  keytype="ENSEMBL",
                  column="ENTREZID",
                  multiVals="first")

```

'select()' returned 1:many mapping between keys and columns

```

head(res, 10)

```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03




ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630158	1.43990e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01
ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51282e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467163	8.346304	7.04321e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez	name	
	<numeric>	<character>	<character>	<character>	
ENSG00000279457	6.86555e-01	NA	NA	NA	
ENSG00000187634	5.15718e-03	148398	148398	148398	
ENSG00000188976	1.76549e-35	26155	26155	26155	
ENSG00000187961	1.13413e-07	339451	339451	339451	
ENSG00000187583	9.19031e-01	84069	84069	84069	
ENSG00000187642	4.03379e-01	84808	84808	84808	
ENSG00000188290	1.30538e-24	57801	57801	57801	
ENSG00000187608	2.37452e-02	9636	9636	9636	
ENSG00000188157	4.21963e-16	375790	375790	375790	
ENSG00000237330	NA	401934	401934	401934	

## Visulaize results

```
library(ggplot2)
my_cols <- rep("gray", nrow(res))
my_cols[abs(res$log2FoldChange) >= 2] <- "blue"

ggplot(res) +
  aes(log2FoldChange, -log(padj)) +
  geom_point(col = my_cols) +
  geom_vline(xintercept = c(-2, 2), col = "red") +
  geom_hline(yintercept = -log(0.05), col = "red")
```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).



## Pathway analysis

```
library(gage)
```

```
library(gageData)
```

```
data(kegg.sets.hs)
data(sigmet.idx.hs)
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

<NA>	148398	26155	339451	84069	84808
0.17925708	0.42645712	-0.69272046	0.72975561	0.04057653	0.54281049

```
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
head(keggres$less)
```

	p.geomean	stat.mean
hsa04110 Cell cycle	8.995727e-06	-4.378644
hsa03030 DNA replication	9.424076e-05	-3.951803
hsa05130 Pathogenic Escherichia coli infection	1.405864e-04	-3.765330
hsa03013 RNA transport	1.246882e-03	-3.059466
hsa03440 Homologous recombination	3.066756e-03	-2.852899
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128


	p.val	q.val
hsa04110 Cell cycle	8.995727e-06	0.001889103
hsa03030 DNA replication	9.424076e-05	0.009841047
hsa05130 Pathogenic Escherichia coli infection	1.405864e-04	0.009841047
hsa03013 RNA transport	1.246882e-03	0.065461279
hsa03440 Homologous recombination	3.066756e-03	0.128803765
hsa04114 Oocyte meiosis	3.784520e-03	0.132458191

	set.size	exp1
hsa04110 Cell cycle	121	8.995727e-06
hsa03030 DNA replication	36	9.424076e-05
hsa05130 Pathogenic Escherichia coli infection	53	1.405864e-04
hsa03013 RNA transport	144	1.246882e-03
hsa03440 Homologous recombination	28	3.066756e-03
hsa04114 Oocyte meiosis	102	3.784520e-03

```
library(pathview)
```

```
pathview(gene.data=foldchanges, pathway.id = "hsa04110")
```



Let's try GO analysis and compare to KEGG analysis

```
data(go.sets.hs)
```

```
data(go.subs.hs)
```

```
# Focus on Biological Process subset of GO
```

```
gobpsets = go.sets.hs[go.subs.hs$BP]
```

```
gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)
```

```
head( gobpres$less )
```

p.geomean stat.mean

p.val

G0:0048285	organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280	nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067	mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059	chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236	mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10
		q.val	set.size	expl
G0:0048285	organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280	nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067	mitosis	5.841698e-12	352	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059	chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236	mitotic prometaphase	1.178402e-07	84	1.729553e-10

## Reactome

Some folks really like Reactomes online (i.e. their webpage viewer) rather than the R package of the same name (available from bioconductor).

To use the website viewer (<https://reactome.org/>) we want to upload our set of gene symbols for the genes we want to focus on (here those with a P-value below 0.05)

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=
```

## Save results

```
write.csv(res, file = "myresults.csv")
```

```
save(res, file = "my_results.RData")
```