

Tutorials for the Digraph3 Python software resources

Release 3.7-2980+

Raymond Bisdorff

March 07, 2019

Contents

1 Preface **3**

2 Working with the *Digraph3* software resources **4**
2.1 Purpose . . . 4
2.2 Downloading of the Digraph3 resources . . . 4
2.3 Starting a python3 session . . . 5
2.4 `Digraph` object structure . . . 5
2.5 Permanent storage . . . 6
2.6 Inspecting a `Digraph` object . . . 6
2.7 Special classes . . . 8

3 Manipulating `Digraph` objects **8**
3.1 Random digraph . . . 8
3.2 Graphviz drawings . . . 10
3.3 Asymmetric and symmetric parts . . . 11
3.4 Fusion by epistemic disjunction . . . 12
3.5 Dual, converse and codual digraphs . . . 13
3.6 Symmetric and transitive closures . . . 14
3.7 Strong components . . . 14
3.8 CSV storage . . . 15
3.9 Complete, empty and indeterminate digraphs . . . 15

4 Computing the winner of an election **17**
4.1 Linear voting profiles . . . 17

4.2 Computing the winner . . . 18
4.3 The Condorcet winner . . . 19
4.4 Cyclic social preferences . . . 20

5 Working with the `outrankingDigraphs` module **21**
5.1 Outranking digraph . . . 22
5.2 Browsing the performances . . . 23
5.3 Valuation semantics . . . 24
5.4 Pairwise comparisons . . . 25
5.5 Recoding the valuation . . . 25
5.6 Codual digraph . . . 26
5.7 XMCDA 2.0 . . . 27

6 Generating random performance tableaux **27**
6.1 Introduction . . . 27
6.2 Generating standard random performance tableaux . . . 28
6.3 Generating random Cost-Benefit tableaux . . . 29
6.4 Generating three objectives tableaux . . . 32
6.5 Generating random linearly ranked performances . . . 34

7 Ranking with multiple incommensurable criteria **35**
7.1 The ranking problem . . . 36
7.2 The Copeland ranking . . . 38
7.3 The Net-Flows ranking . . . 39
7.4 Kemeny rankings . . . 39
7.5 Slater rankings . . . 40
7.6 Kohler's ranking-by-choosing rule . . . 41
7.7 Tideman's Ranked-Pairs rule . . . 42
7.8 Ranking big performance tableaux . . . 43

8 Computing a best choice recommendation **44**
8.1 What site to choose ? . . . 45
8.2 Performance tableau . . . 46
8.3 Outranking digraph . . . 47
8.4 Rubis best choice . . . 48
8.5 Strictly best choice . . . 51
8.6 Weakly ordering . . . 53

9 Rating with learned quantile norms **54**
9.1 Introduction . . . 54
9.2 Incremental learning of historical performance quantiles . . . 55
9.3 Rating performances with quantile norms . . . 57

10 Working with the `graphs` module **63**
10.1 Structure of a `Graph` object . . . 63
10.2 q-coloring of a graph . . . 65
10.3 MIS and clique enumeration . . . 66
10.4 Line graphs and maximal matchings . . . 68
10.5 Grids and the Ising model . . . 69
10.6 Simulating Metropolis random walks . . . 70
10.7 The Berge mystery story: Who is the lier ? . . . 71

11 Computing the non isomorphic MISs of the n-cycle graph **74**

12 On computing digraph kernels **77**
12.1 What is a graph kernel ? . . . 77
12.2 Initial and terminal kernels . . . 82
12.3 Kernels in lateralized digraphs . . . 84
12.4 Computing good and bad choice recommendations . . . 86

12.5 Tractability . . . 89

13 Abut permutation graphs **92**
13.1 Permutation graphs . . . 92
13.2 Properties of permutation graphs . . . 94
13.3 Recognizing permutation graphs . . . 95

14 On tree graphs and graph forests **97**
14.1 Generating random tree graphs . . . 97
14.2 Recognizing tree graphs . . . 100
14.3 Spanning trees and forests . . . 102
14.4 Maximum determined spanning forests . . . 103

15 Links and appendices **105**
15.1 References . . . 105
15.2 Footnotes . . . 105

References **105**

1 Preface

This PDF document contains a set of tutorials introducing the main objects like digraphs, outranking digraphs, performance tableaux and voting profiles available in the Digraph3 Python software resources (see html documentation here <https://digraph3.readthedocs.io/en/latest/index.html> for the corresponding HTML version).

Some of the tutorials are problem oriented and show how to compute the potential winner(s) of an election, how to build a best choice recommendation, or how to rate or linearly rank with multiple incommensurable ranking criteria.

More graph theoretical tutorials follow. One on working with undirected graphs, followed by a tutorial on how to compute non isomorphic maximal independent sets in the n-cycle graph. A last tutorial is finally devoted on how to compute kernels in graphs, digraphs and more specifically in outranking digraphs.

Author Raymond Bisdorff, Emeritus Professor, University of Luxembourg FSTC/CSC

Version Revision: Python 3.7

Copyright R. Bisdorff (https://leopold-loewenheim.uni.lu/bisdorff/) 2013-2019

List of Digraph3 tutorials

- *Working with the* Digraph3 *software resources* (page 4)
- *Manipulating* `Digraph` *objects* (page 8)
- *Computing the winner of an election* (page 17)
- *Working with the* `outrankingDigraphs` *module* (page 21)
- *Generating random performance tableaux* (page 27)
- *Ranking with multiple incommensurable criteria* (page 35)
- *Computing a best choice recommendation* (page 44)
- *Rating with learned quantile norms* (page 54)
- *Working with the* `graphs` *module* (page 63)

- *Computing the non isomorphic MISs of the n-cycle graph* (page 74)
- *On computing digraph kernels* (page 77)
- *Abut permutation graphs* (page 92)
- *On tree graphs and graph forests* (page 97)
- *Links and appendices* (page 105)

2 Working with the *Digraph3* software resources

- *Purpose* (page 4)
- *Downloading of the Digraph3 resources* (page 4)
- *Starting a python3 session* (page 5)
- `Digraph` *object structure* (page 5)
- *Permanent storage* (page 6)
- *Inspecting a* `Digraph` *object* (page 6)
- *Special classes* (page 8)

2.1 Purpose

The basic idea of the Digraph3 Python resources is to make easy python interactive sessions or write short Python3 scripts for computing all kind of results from a bipolar valued digraph or graph. These include such features as maximal independent or irredundant choices, maximal dominant or absorbent choices, rankings, outrankings, linear ordering, etc. Most of the available computing resources are meant to illustrate the *Algorithmic Decision Theory* course given at the University of Luxembourg in the context of its Master in Information and Computer Science (MICS).

The Python development of these computing resources offers the advantage of an easy to write and maintain OOP source code as expected from a performing scripting language without loosing on efficiency in execution times compared to compiled languages such as C++ or Java.

2.2 Downloading of the Digraph3 resources

Using the Digraph3 modules is easy. You only need to have installed on your system the Python (https://www.python.org/doc/) programming language of version 3.+ (readily available under Linux and Mac OS). Notice that, from Version 3.3 on, the Python standard decimal module implements very efficiently its decimal.Decimal class in C. Now, Decimal objects are mainly used in the Digraph3 characteristic r-valuation functions, which makes the recent python-3.3+ versions much faster (more than twice as fast) when extensive digraph operations are performed.

Several download options (easiest under Linux or Mac OS-X) are given.

1. Either , by using a git client either, from github:

```
...$ git clone https://github.com/rbisdorff/Digraph3
```

2. Or, from sourceforge.net:

```
...$ git clone https://git.code.sf.net/p/digraph3/code Digraph3
```

3. or a subversion client:

```
...$ svn co https://leopold-loewenheim.uni.lu/svn/repos/Digraph3
```

4. Or, with a browser access, download and extract the latest distribution zip archive either, from the github link above (https://github.com/rbisdorff/Digraph3) or, from the sourceforge page (https://sourceforge.net/projects/digraph3/) .

2.3 Starting a python3 session

You may start an interactive Python3 session in the `Digraph3` directory for exploring the classes and methods provided by the `digraphs` module. To do so, enter the `python3` commands following the session prompts marked with >>>. The lines without the prompt are output from the Python interpreter:

```
$HOME/.../Digraph3$ python3
Python 3.6.7 (default, Oct 22 2018, 11:32:17)
[GCC 8.2.0] on linux
Type "help", "copyright", "credits" or
      "license" for more information.
>>> from randomDigraphs import RandomDigraph
>>> dg = RandomDigraph(order=5,arcProbability=0.5,
                       seed=101)
>>> dg
*------- Digraph instance description ------*
Instance class   : RandomDigraph
Instance name    : randomDigraph
Digraph Order      : 5
Digraph Size       : 12
Valuation domain : [-1.00; 1.00]
Determinateness  : 100.000
Attributes       : ['actions', 'valuationdomain', 'relation',
                    'order', 'name', 'gamma', 'notGamma']
>>> dg.save('tutorialDigraph')
*--- Saving digraph in file: <tutorialDigraph.py> ---*
>>> ...
```

2.4 `Digraph` object structure

All `digraphs.Digraph` objects (see Line 12 above) contain at least the following attributes:

0. A **name** attribute, holding usually the actual name of the stored instance that was used to create the instance;
1. A collection of digraph nodes called **actions** (decision actions): an ordered dictionary of nodes with at least a 'name' attribute;
2. An **order** attribute containing the number of graph nodes (length of the actions dictionary) automatically added by the object constructor;
3. A logical characteristic **valuationdomain**, a dictionary with three decimal entries: the minimum (-1.0, means certainly false), the median (0.0, means missing information) and the maximum characteristic value (+1.0, means certainly true);
4. The digraph **relation** : a double dictionary indexed by an oriented pair of actions (nodes) and carrying a decimal characteristic value in the range of the previous valuation domain;
5. Its associated **gamma function** : a dictionary containing the direct successors, respectively predecessors of each action, automatically added by the object constructor;
6. Its associated **notGamma function** : a dictionary containing the actions that are not direct successors respectively predecessors of each action, automatically added by the object constructor.

2.5 Permanent storage

The `dg.save('tutorialDigraph')` command (see Line 19 above) stores the digraph *dg* in a file named `tutorialDigraph.py` with the following content:

```
# Saved digraph instance
actions = {
'a1': {'shortName': 'a1', 'name': 'random decision action'},
'a2': {'shortName': 'a2', 'name': 'random decision action'},
'a3': {'shortName': 'a3', 'name': 'random decision action'},
'a4': {'shortName': 'a4', 'name': 'random decision action'},
'a5': {'shortName': 'a5', 'name': 'random decision action'},
}
valuationdomain = {'hasIntegerValuation': True,
                   'min': -1.0,'med': 0.0,'max': 1.0}
relation = {
'a1': {'a1':-1.0, 'a2':-1.0, 'a3':1.0, 'a4':-1.0, 'a5':-1.0,},
'a2': {'a1':1.0, 'a2':-1.0, 'a3':-1.0, 'a4':1.0, 'a5':1.0,},
'a3': {'a1':1.0, 'a2':-1.0, 'a3':-1.0, 'a4':1.0, 'a5':-1.0,},
'a4': {'a1':1.0, 'a2':1.0, 'a3':1.0, 'a4':-1.0, 'a5':-1.0,},
'a5': {'a1':1.0, 'a2':1.0, 'a3':1.0, 'a4':-1.0, 'a5':-1.0,},
}
```

2.6 Inspecting a `Digraph` object

We may reload a previously saved `Digraph` instance from the file named `tutorialDigraph.py` with the `Digraph` class constructor and the `digraphs.Digraph.showAll()` method output reveals us that *dg* is a connected irreflexive digraph of order five evaluated in a valuation domain from -1 to 1.

```
>>> dg = Digraph('tutorialDigraph')
>>> dg.showAll()
*----- show detail -------------*
Digraph          : tutorialDigraph
*---- Actions ----*
['a1', 'a2', 'a3', 'a4', 'a5']
*---- Characteristic valuation domain ----*
{'hasIntegerValuation': True, 'min': Decimal('-1.0'), 'med': Decimal('0.0'), 'max
↪': Decimal('1.0')}
* ---- Relation Table -----
  S    |  'a1'  'a2'  'a3'  'a4'  'a5'
------|-------------------------------
 'a1' |   -1    -1     1    -1    -1
 'a2' |    1    -1    -1     1     1
 'a3' |    1    -1    -1     1    -1
 'a4' |    1     1     1    -1    -1
 'a5' |    1     1     1    -1    -1
Valuation domain: [-1;+1]
*--- Connected Components ---*
1: ['a1', 'a2', 'a3', 'a4', 'a5']
Neighborhoods:
  Gamma     :
'a1': in => {'a2', 'a4', 'a3', 'a5'}, out => {'a3'}
'a2': in => {'a5', 'a4'}, out => {'a1', 'a4', 'a5'}
'a3': in => {'a1', 'a4', 'a5'}, out => {'a1', 'a4'}
'a4': in => {'a2', 'a3'}, out => {'a1', 'a3', 'a2'}
'a5': in => {'a2'}, out => {'a1', 'a3', 'a2'}
  Not Gamma :
'a1': in => set(), out => {'a2', 'a4', 'a5'}
'a2': in => {'a1', 'a3'}, out => {'a3'}
'a3': in => {'a2'}, out => {'a2', 'a5'}
'a4': in => {'a1', 'a5'}, out => {'a5'}
```

```
'a5': in => {'a1', 'a4', 'a3'}, out => {'a4'}
>>>
```

The `digraphs.Digraph.exportGraphViz()` method generates in the current working directory a `tutorial.dot` file and a `tutorialdigraph.png` picture of the tutorial digraph *g*, if the graphviz (https://graphviz.org/) tools are installed on your system[1].

```
>>> dg.exportGraphViz('tutorialDigraph')
*---- exporting a dot file do GraphViz tools ---------*
Exporting to tutorialDigraph.dot
dot -Grankdir=BT -Tpng tutorialDigraph.dot -o tutorialDigraph.png
```



Fig. 1: *The tutorial digraph*

Some simple methods are easily applicable to this instantiated Digraph object *dg* , like the following `digraphs.Digraph.showStatistics()` method.

```
>>> dg.showStatistics()
*----- general statistics -------------*
for digraph              : <tutorialDigraph.py>
order                    :  5 nodes
size                     :  12 arcs
# undetermined           :  0 arcs
determinateness          : 1.00
arc density              : 0.60
double arc density       : 0.40
single arc density       : 0.40
absence density          : 0.20
strict single arc density: 0.40
strict absence density   : 0.20
# components             :  1
# strong components      :  1
transitivity degree      : 0.48
                         :  [0, 1, 2, 3, 4, 5]
outdegrees distribution  :  [0, 1, 1, 3, 0, 0]
indegrees distribution   :  [0, 1, 2, 1, 1, 0]
mean outdegree           : 2.40
mean indegree            : 2.40
                         :  [0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
symmetric degrees dist.  :  [0, 0, 0, 0, 1, 4, 0, 0, 0, 0, 0]
mean symmetric degree    : 4.80
outdegrees concentration index   : 0.1667
```

[1] The `exportGraphViz` method is depending on drawing tools from graphviz (https://graphviz.org/). On Linux Ubuntu or Debian you may try `sudo apt-get install graphviz` to install them. There are ready `dmg` installers for Mac OSX.

```
indegrees concentration index    : 0.2333
symdegrees concentration index   : 0.0333
                                 :  [0, 1, 2, 3, 4, 'inf']
neighbourhood depths distribution:  [0, 1, 4, 0, 0, 0]
mean neighbourhood depth         : 1.80
digraph diameter                 :  2
agglomeration distribution       :
a1 : 58.33
a2 : 33.33
a3 : 33.33
a4 : 50.00
a5 : 50.00
agglomeration coefficient        : 45.00
>>> ...
```

2.7 Special classes

Some special classes of digraphs, like the `digraphs.CompleteDigraph`, the `digraphs.EmptyDigraph` or the oriented `digraphs.GridDigraph` class for instance, are readily available.

```
>>> from digraphs import GridDigraph
>>> grid = GridDigraph(n=5,m=5,hasMedianSplitOrientation=True)
>>> grid.exportGraphViz('tutorialGrid')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutorialGrid.dot
dot -Grankdir=BT -Tpng TutorialGrid.dot -o tutorialGrid.png
```

Back to *Tutorials of the Digraph3 resources* (page 3)

3 Manipulating `Digraph` objects

- *Random digraph* (page 8)
- *Graphviz drawings* (page 10)
- *Asymmetric and symmetric parts* (page 11)
- *Fusion by epistemic disjunction* (page 12)
- *Dual, converse and codual digraphs* (page 13)
- *Symmetric and transitive closures* (page 14)
- *Strong components* (page 14)
- *CSV storage* (page 15)
- *Complete, empty and indeterminate digraphs* (page 15)

3.1 Random digraph

We are starting this tutorial with generating a randomly [-1;1]-valued (*Normalized=True*) digraph of order 7, denoted *dg* and modelling a binary relation ($x\ S\ y$) defined on the set of nodes of *dg*. For this purpose, the `Digraph3` collection contains a `randomDigraphs` module providing a specific `digraphs.RandomValuationDigraph` constructor.



Fig. 2: *The tutorial grid graph*

```
>>> from randomDigraphs import RandomValuationDigraph
>>> dg = RandomValuationDigraph(order=7,Normalized=True)
>>> dg.save('tutRandValDigraph')
```

With the `save()` method (see Line 3) we may keep a backup version for future use of *dg* which will be stored in a file called *tutRandValDigraph.py* in the current working directory. The `Digraph` class now provides some generic methods for exploring a given `Digraph` object, like the `showShort()`, `showAll()`, `showRelationTable()` and the `showNeighborhoods()` methods.

```
>>> dg.showShort()
*----- show summary -------------*
Digraph          : randomValuationDigraph
*---- Actions ----*
['1', '2', '3', '4', '5', '6', '7']
*---- Characteristic valuation domain ----*
{'med': Decimal('0.0'), 'hasIntegerValuation': False,
'min': Decimal('-1.0'), 'max': Decimal('1.0')}
*--- Connected Components ---*
1: ['1', '2', '3', '4', '5', '6', '7']
>>> dg.showRelationTable(ReflexiveTerms=False)
* ---- Relation Table -----
r(xSy) |  '1'    '2'   '3'  '4'   '5'    '6'  '7'
-------|-------------------------------------------------------
'1'    |   -   -0.48  0.70  0.86  0.30  0.38  0.44
'2'    | -0.22   -   -0.38  0.50  0.80 -0.54  0.02
'3'    | -0.42  0.08   -    0.70 -0.56  0.84 -1.00
'4'    |  0.44 -0.40 -0.62   -    0.04  0.66  0.76
'5'    |  0.32 -0.48 -0.46  0.64   -   -0.22 -0.52
'6'    | -0.84  0.00 -0.40 -0.96 -0.18   -   -0.22
'7'    |  0.88  0.72  0.82  0.52 -0.84  0.04  -
>>> dg.showNeighborhoods()
Neighborhoods observed in digraph 'randomdomValuation'
Gamma     :
'1': in => {'5', '7', '4'}, out => {'5', '7', '6', '3', '4'}
'2': in => {'7', '3'}, out => {'5', '7', '4'}
'3': in => {'7', '1'}, out => {'6', '2', '4'}
'4': in => {'5', '7', '1', '2', '3'}, out => {'5', '7', '1', '6'}
'5': in => {'1', '2', '4'}, out => {'1', '4'}
'6': in => {'7', '1', '3', '4'}, out => set()
'7': in => {'1', '2', '4'}, out => {'1', '2', '3', '4', '6'}
 Not Gamma :
'1': in => {'6', '2', '3'}, out => {'2'}
'2': in => {'5', '1', '4'}, out => {'1', '6', '3'}
'3': in => {'5', '6', '2', '4'}, out => {'5', '7', '1'}
'4': in => {'6'}, out => {'2', '3'}
'5': in => {'7', '6', '3'}, out => {'7', '6', '2', '3'}
'6': in => {'5', '2'}, out => {'5', '7', '1', '3', '4'}
'7': in => {'5', '6', '3'}, out => {'5'}
```

Warning: Notice that most Digraph class methods will ignore the reflexive couples by considering that the relation is indeterminate (the characteristic value $r(x\,S\,x)$ for all action x is put to the median, i.e. indeterminate, value) in this case (see *[BIS-2004]* (page 106))

3.2 Graphviz drawings

We may have an even better insight into the `Digraph` object *dg* by looking at a graphviz (https://graphviz.org/) drawing[1].

```
>>> dg.exportGraphViz('tutRandValDigraph')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutRandValDigraph.dot
dot -Grankdir=BT -Tpng tutRandValDigraph.dot -o tutRandValDigraph.png
```



Fig. 3: *The tutorial random valuation digraph*

Double links are drawn in bold black with an arrowhead at each end, whereas single asymmetric links are drawn in black with an arrowhead showing the direction of the link. Notice the undetermined relational situation ($r(6\,S\,2) = 0.00$) observed between nodes '6' and '2'. The corresponding link is marked in gray with an open arrowhead in the drawing.

3.3 Asymmetric and symmetric parts

We may now extract both this symmetric as well as this asymmetric part of digraph *dg* with the help of two corresponding constructors.

```
>>> from digraphs import AsymmetricPartialDigraph, SymmetricPartialDigraph
>>> asymDg = AsymmetricPartialDigraph(dg)
>>> asymDg.exportGraphViz()
>>> symDG = SymmetricPartialDigraph(dg)
>>> symDg.exportGraphViz()
```

Note: Notice that the partial objects *asymDg* and *symDg* put to the indeterminate characteristic value all not-asymmetric, respectively not-symmetric links between nodes.

Here below, for illustration the source code of *relation* constructor of the `digraphs.AsymmetricPartialDigraph` class:

```
def _constructRelation(self):
    actions = self.actions
```



Fig. 4: *Asymmetric part of the tutorial random valuation digraph*

```
    Min = self.valuationdomain['min']
    Max = self.valuationdomain['max']
    Med = self.valuationdomain['med']
    relationIn = self.relation
    relationOut = {}
    for a in actions:
        relationOut[a] = {}
        for b in actions:
            if a != b:
                if relationIn[a][b] >= Med and relationIn[b][a] <= Med:
                    relationOut[a][b] = relationIn[a][b]
                elif relationIn[a][b] <= Med and relationIn[b][a] >= Med:
                    relationOut[a][b] = relationIn[a][b]
                else:
                    relationOut[a][b] = Med
            else:
                relationOut[a][b] = Med
    return relationOut
```

3.4 Fusion by epistemic disjunction

We may recover object *dg* from both partial objects *asymDg* and *symDg* with a **bipolar fusion** constructor, also called **epistemic disjunction**, available via the `digraphs.FusionDigraph` class.

```
>>> from digraphs import FusionDigraph
>>> fusDg = FusionDigraph(asymDg,symDg,operator='o-max')
>>> fusDg.showRelationTable()
* ---- Relation Table -----
r(xSy) |  '1'    '2'    '3'   '4'    '5'    '6'   '7'
-------|-------------------------------------------------------
```

```
'1'     |  0.00 -0.48  0.70  0.86  0.30  0.38  0.44
'2'     | -0.22  0.00 -0.38  0.50  0.80 -0.54  0.02
'3'     | -0.42  0.08  0.00  0.70 -0.56  0.84 -1.00
'4'     |  0.44 -0.40 -0.62  0.00  0.04  0.66  0.76
'5'     |  0.32 -0.48 -0.46  0.64  0.00 -0.22 -0.52
'6'     | -0.84  0.00 -0.40 -0.96 -0.18  0.00 -0.22
'7'     |  0.88  0.72  0.82  0.52 -0.84  0.04  0.00
```

3.5 Dual, converse and codual digraphs

We may as readily compute the **dual**, the **converse** and the **codual** (dual and converse) of *dg*.

```
>>> from digraphs import DualDigraph, ConverseDigraph, CoDualDigraph
>>> ddg = DualDigraph(dg)
>>> ddg.showRelationTable()
-r(xSy) |  '1'    '2'   '3'  '4'   '5'    '6'  '7'
--------|-----------------------------------------
'1 '    |  0.00  0.48 -0.70 -0.86 -0.30 -0.38 -0.44
'2'     |  0.22  0.00  0.38 -0.50  0.80  0.54 -0.02
'3'     |  0.42  0.08  0.00 -0.70  0.56 -0.84  1.00
'4'     | -0.44  0.40  0.62  0.00 -0.04 -0.66 -0.76
'5'     | -0.32  0.48  0.46 -0.64  0.00  0.22  0.52
'6'     |  0.84  0.00  0.40  0.96  0.18  0.00  0.22
'7'     |  0.88 -0.72 -0.82 -0.52  0.84 -0.04  0.00
>>> cdg = ConverseDigraph(dg)
>>> cdg.showRelationTable()
* ---- Relation Table -----
 r(ySx) |  '1'    '2'   '3'   '4'   '5'   '6'   '7'
--------|-----------------------------------------
'1'     |  0.00 -0.22 -0.42  0.44  0.32 -0.84  0.88
'2'     | -0.48  0.00  0.08 -0.40 -0.48  0.00  0.72
'3'     |  0.70 -0.38  0.00 -0.62 -0.46 -0.40  0.82
'4'     |  0.86  0.50  0.70  0.00  0.64 -0.96  0.52
'5'     |  0.30  0.80 -0.56  0.04  0.00 -0.18 -0.84
'6'     |  0.38 -0.54  0.84  0.66 -0.22  0.00  0.04
'7'     |  0.44  0.02 -1.00  0.76 -0.52 -0.22  0.00
>>> cddg = CoDualDigraph(dg)
>>> cddg.showRelationTable()
* ---- Relation Table -----
-r(ySx) |  '1'    '2'   '3'   '4'   '5'   '6'   '7'
--------|-----------------------------------------------------------
'1'     |  0.00  0.22  0.42 -0.44 -0.32  0.84 -0.88
'2'     |  0.48  0.00 -0.08  0.40  0.48  0.00 -0.72
'3'     | -0.70  0.38  0.00  0.62  0.46  0.40 -0.82
'4'     | -0.86 -0.50 -0.70  0.00 -0.64  0.96 -0.52
'5'     | -0.30 -0.80  0.56 -0.04  0.00  0.18  0.84
'6'     | -0.38  0.54 -0.84 -0.66  0.22  0.00 -0.04
'7'     | -0.44 -0.02  1.00 -0.76  0.52  0.22  0.00
```

Computing the dual, respectively the converse, may also be done with prefixing the `__neg__` `(-)` or the `__invert__` (~) operator. The codual of a Digraph object may, hence, as well be computed with a **composition** (in either order) of both operations.

```
>>> ddg = -dg    # dual of dg
>>> cdg = ~dg    # converse of dg
>>> cddg = -(~dg) = ~(-dg)   # codual of dg
>>> cddg.showRelationTable()
* ---- Relation Table -----
-r(ySx) |  '1'    '2'   '3'   '4'   '5'   '6'   '7'
--------|-----------------------------------------------------------
'1'     |  0.00  0.22  0.42 -0.44 -0.32  0.84 -0.88
```

```
'2'      |  0.48  0.00 -0.08  0.40  0.48  0.00 -0.72
'3'      | -0.70  0.38  0.00  0.62  0.46  0.40 -0.82
'4'      | -0.86 -0.50 -0.70  0.00 -0.64  0.96 -0.52
'5'      | -0.30 -0.80  0.56 -0.04  0.00  0.18  0.84
'6'      | -0.38  0.54 -0.84 -0.66  0.22  0.00 -0.04
'7'      | -0.44 -0.02  1.00 -0.76  0.52  0.22  0.00
```

3.6 Symmetric and transitive closures

Symmetric and transitive closure in-site constructors are also available. Note that it is a good idea, before going ahead with these in-site operations who irreversibly modify the original *dg* object, to previously make a backup version of *dg*. The simplest storage method, always provided by the generic `diggraphs.Digraph.save()`, writes out in a named file the python content of the Digraph object in string representation.

```
>>> dg.save('tutRandValDigraph')
>>> dg.closeSymmetric()
>>> dg.closeTransitive()
>>> dg.exportGraphViz('strongComponents')
```



Fig. 5: *Symmetric amd transitive closure of the tutorial random valuation digraph*

3.7 Strong components

As the original digraph *dg* was connected (see above the result of the `dg.showShort()` command), both the symmetric and transitive closures operated together, will necessarily produce a single strong component, i.e. a complete digraph. We may sometimes wish to collapse all strong components in a given digraph and construct the so reduced digraph. Using the `digraphs.StrongComponentsCollapsedDigraph` constructor here will render a single hyper-node gathering all the original nodes.

```
>>> from digraphs import StrongComponentsCollapsedDigraph
>>> sc = StrongComponentsCollapsedDigraph(dg)
>>> sc.showAll()
*----- show detail -----*
Digraph          : tutRandValDigraph_Scc
*---- Actions ----*
['_7_1_2_6_5_3_4_']
* ---- Relation Table -----
  S      |  'Scc_1'
 -------|---------
```

```
'Scc_1' |  0.00
short        content
Scc_1        _7_1_2_6_5_3_4_
Neighborhoods:
  Gamma     :
'frozenset({'7', '1', '2', '6', '5', '3', '4'})': in => set(), out => set()
  Not Gamma :
'frozenset({'7', '1', '2', '6', '5', '3', '4'})': in => set(), out => set()
>>> ...
```

3.8 CSV storage

Sometimes it is required to exchange the graph valuation data in CSV format with a statistical package like R (https://www.r-project.org/). For this purpose it is possible to export the digraph data into a CSV file. The valuation domain is hereby normalized by default to the range [-1,1] and the diagonal put by default to the minimal value -1.

```
>>> dg = Digraph('tutRandValDigraph')
>>> dg.saveCSV('tutRandValDigraph')
# content of file tutRandValDigraph.csv
"d","1","2","3","4","5","6","7"
"1",-1.0,0.48,-0.7,-0.86,-0.3,-0.38,-0.44
"2",0.22,-1.0,0.38,-0.5,-0.8,0.54,-0.02
"3",0.42,-0.08,-1.0,-0.7,0.56,-0.84,1.0
"4",-0.44,0.4,0.62,-1.0,-0.04,-0.66,-0.76
"5",-0.32,0.48,0.46,-0.64,-1.0,0.22,0.52
"6",0.84,0.0,0.4,0.96,0.18,-1.0,0.22
"7",-0.88,-0.72,-0.82,-0.52,0.84,-0.04,-1.0
```

It is possible to reload a Digraph instance from its previously saved CSV file content.

```
>>> dgcsv = CSVDigraph('tutRandValDigraph')
>>> dgcsv.showRelationTable(ReflexiveTerms=False)
* ---- Relation Table -----
r(xSy) |   '1'   '2'   '3'   '4'   '5'   '6'   '7'
-------|------------------------------------------------------------
'1'    |   -   -0.48  0.70  0.86  0.30  0.38  0.44
'2'    | -0.22   -   -0.38  0.50  0.80 -0.54  0.02
'3'    | -0.42  0.08   -    0.70 -0.56  0.84 -1.00
'4'    |  0.44 -0.40 -0.62   -    0.04  0.66  0.76
'5'    |  0.32 -0.48 -0.46  0.64   -   -0.22 -0.52
'6'    | -0.84  0.00 -0.40 -0.96 -0.18   -   -0.22
'7'    |  0.88  0.72  0.82  0.52 -0.84  0.04   -
```

It is as well possible to show a colored version of the valued relation table in a system browser window tab.

```
>>> dgcsv.showHTMLRelationTable(tableTitle="Tutorial random digraph")
>>> ...
```

Positive arcs are shown in green and negative in red. Indeterminate -zero-valued- links, like the reflexive diagonal ones or the link between node *6* and node *2*, are shown in gray.

3.9 Complete, empty and indeterminate digraphs

Let us finally mention some special universal classes of digraphs that are readily available in the `digraphs` module, like the `digraphs.CompleteDigraph`, the `digraphs.EmptyDigraph` and the `digraphs.IndeterminateDigraph` classes, which put all characteristic values respectively to the *maximum*, the *minimum* or the median *indeterminate* characteristic value.

Tutorial random digraph

r(x S y)	1	2	3	4	5	6	7
1	0.00	-0.48	0.70	0.86	0.30	0.38	0.44
2	-0.22	0.00	-0.38	0.50	0.80	-0.54	0.02
3	-0.42	0.08	0.00	0.70	-0.56	0.84	-1.00
4	0.44	-0.40	-0.62	0.00	0.04	0.66	0.76
5	0.32	-0.48	-0.46	0.64	0.00	-0.22	-0.52
6	-0.84	0.00	-0.40	-0.96	-0.18	0.00	-0.22
7	0.88	0.72	0.82	0.52	-0.84	0.04	0.00

Fig. 6: *The valued relation table shown in a browser window*

```
>>> from digraphs import CompleteDigraph,EmptyDigraph,
...                      IndeterminateDigraph
>>> help(CompleteDigraph)
Help on class CompleteDigraph in module digraphs:
class CompleteDigraph(Digraph)
 |  Parameters:
 |      order > 0; valuationdomain=(Min,Max).
 |  Specialization of the general Digraph class for generating
 |  temporary complete graphs of order 5 in {-1,0,1} by default.
 |  Method resolution order:
 |      CompleteDigraph
 |      Digraph
 |      builtins.object
...
>>> e = EmptyDigraph(order=5)
>>> e.showRelationTable()
* ---- Relation Table -----
  S   |  '1'      '2'     '3'     '4'     '5'
---- -|----------------------------------------
'1'   |  -1.00   -1.00   -1.00   -1.00   -1.00
'2'   |  -1.00   -1.00   -1.00   -1.00   -1.00
'3'   |  -1.00   -1.00   -1.00   -1.00   -1.00
'4'   |  -1.00   -1.00   -1.00   -1.00   -1.00
'5'   |  -1.00   -1.00   -1.00   -1.00   -1.00
>>> e.showNeighborhoods()
Neighborhoods:
  Gamma     :
'1': in => set(), out => set()
'2': in => set(), out => set()
'5': in => set(), out => set()
'3': in => set(), out => set()
'4': in => set(), out => set()
  Not Gamma :
'1': in => {'2', '4', '5', '3'}, out => {'2', '4', '5', '3'}
'2': in => {'1', '4', '5', '3'}, out => {'1', '4', '5', '3'}
'5': in => {'1', '2', '4', '3'}, out => {'1', '2', '4', '3'}
'3': in => {'1', '2', '4', '5'}, out => {'1', '2', '4', '5'}
'4': in => {'1', '2', '5', '3'}, out => {'1', '2', '5', '3'}
>>> i = IndeterminateDigraph()
* ---- Relation Table -----
  S   |  '1'      '2'     '3'     '4'     '5'
```

```
------|-------------------------------------
'1'   |  0.00    0.00    0.00    0.00    0.00
'2'   |  0.00    0.00    0.00    0.00    0.00
'3'   |  0.00    0.00    0.00    0.00    0.00
'4'   |  0.00    0.00    0.00    0.00    0.00
'5'   |  0.00    0.00    0.00    0.00    0.00
>>> i.showNeighborhoods()
Neighborhoods:
  Gamma     :
'1': in => set(), out => set()
'2': in => set(), out => set()
'5': in => set(), out => set()
'3': in => set(), out => set()
'4': in => set(), out => set()
  Not Gamma :
'1': in => set(), out => set()
'2': in => set(), out => set()
'5': in => set(), out => set()
'3': in => set(), out => set()
'4': in => set(), out => set()
```

Note: Notice the subtle difference between the neighborhoods of an *empty* and the neighborhoods of an *indeterminate* digraph instance. In the first kind, the neighborhoods are known to be completely *empty* whereas, in the latter, *nothing is known* about the actual neighborhoods of the nodes. These two cases illustrate why in the case of a bipolar valuation domain, we need both a *gamma* **and** a *notGamma* function.

Back to *Tutorials of the Digraph3 resources* (page 3)

4 Computing the winner of an election

- *Linear voting profiles* (page 17)
- *Computing the winner* (page 18)
- *The Condorcet winner* (page 19)
- *Cyclic social preferences* (page 20)

4.1 Linear voting profiles

The votingProfiles-label provides resources for handling election results *[ADT-L2]* (page 105), like the `votingProfiles.LinearVotingProfile` class. We consider an election involving a finite set of candidates and finite set of weighted voters, who express their voting preferences in a complete linear ranking (without ties) of the candidates. The data is internally stored in two ordered dictionaries, one for the voters and another one for the candidates. The linear ballots are stored in a standard dictionary:

```
candidates = OrderedDict([('a1',...), ('a2',...), ('a3', ...), ...}
voters = OrderedDict([('v1',{'weight':10}), ('v2',{'weight':3}), ...}
## each voter specifies a linearly ranked list of candidates
## from the best to the worst (without ties
linearBallot = {
'v1' : ['a2','a3','a1', ...],
'v2' : ['a1','a2','a3', ...],
...
}
```

The module provides a `votingProfiles.RandomLinearVotingProfile` class for generating random instances of the `votingProfiles.LinearVotingProfile` class. In an interactive Python session we may obtain for the election of 3 candidates by 5 voters the following result.

```
>>> from votingProfiles import RandomLinearVotingProfile
>>> v = RandomLinearVotingProfile(numberOfVoters=5,
...                               numberOfCandidates=3
...                               votersWeights=[2,3,1,5,4])
>>> v.candidates
OrderedDict([('a1',{'name':'a1'}), ('a2',{'name':'a2'}), ('a3':{'name':'a3'})])
>>> v.voters
OrderedDict([('v1',{'weight': 2}), ('v2':{'weight': 3}),
 ('v3',{'weight': 1}), ('v4':{'weight': 5}),
 ('v5',{'weight': 4})])
>>> v.linearBallot
{'v4': ['a1', 'a3', 'a2'], 'v3': ['a1', 'a3', 'a2'], 'v1': ['a1', 'a2', 'a3'],
 'v5': ['a2', 'a3', 'a1'], 'v2': ['a3', 'a2', 'a1']}
 >>> ...
```

Notice that in this random example, the five voters are weighted (see Line 4). Their linear ballots can be viewed with the `showLinearBallots` method.

```
>>> v.showLinearBallots()
voters(weight)       candidates rankings
v1(2):       ['a2', 'a1', 'a3']
v2(3):       ['a3', 'a1', 'a2']
v3(1):       ['a1', 'a3', 'a2']
v4(5):       ['a1', 'a2', 'a3']
v5(4):       ['a3', 'a1', 'a2']
# voters: 15
>>> ...
```

Editing of the linear voting profile may be achieved by storing the data in a file, edit it, and reload it again.

```
>>> v.save('tutorialLinearVotingProfile')
*--- Saving linear profile in file: <tutorialLinearVotingProfile.py> ---*
>>> v = LinearVotingProfile('tutorialLinearVotingProfile')
```

4.2 Computing the winner

We may easily compute **uni-nominal votes**, i.e. how many times a candidate was ranked first, and see who is consequently the **simple majority** winner(s) in this election.

```
>>> v.computeUninominalVotes()
{'a2': 2, 'a1': 6, 'a3': 7}
>>> v.computeSimpleMajorityWinner()
['a3']
>>> ...
```

As we observe no absolute majority (8/15) of votes for any of the three candidate, we may look for the **instant runoff** winner instead (see *[ADT-L2]* (page 105)).

```
>>> v.computeInstantRunoffWinner()
['a1']
>>> ...
```

We may also follow the *Chevalier de Borda*'s advice and, after a **rank analysis** of the linear ballots, compute the **Borda score** of each candidate and hence determine the **Borda winner(s)**.

```
>>> v.computeRankAnalysis()
{'a2': [2, 5, 8], 'a1': [6, 9, 0], 'a3': [7, 1, 7]}
```

```
>>> v.computeBordaScores()
{'a2': 36, 'a1': 24, 'a3': 30}
>>> v.computeBordaWinners()
['a1']
```

The Borda **rank analysis table** may be printed out with a corresponding `show` command.

```
>>> v.showRankAnalysisTable()
*----  Borda rank analysis tableau -----*
candi- | alternative-to-rank |      Borda
dates  |   1     2     3     | score  average
-------|-------------------------------------
 'a1'  |   6     9     0     |  24     1.60
 'a3'  |   7     1     7     |  30     2.00
 'a2'  |   2     5     8     |  36     2.40
>>> ...
```

4.3 The Condorcet winner

In our randomly generated election results, we are lucky: The instant runoff winner and the Borda winner both are candidate *a1*. However, we could also follow the *Marquis de Condorcet*'s advice, and compute the **majority margins** obtained by voting for each individual pair of candidates. For instance, candidate *a1* is ranked four times before and once behind candidate *a2*. Hence the majority margin *M(a1,a2)* is 4 - 1 = +3. These majority margins define on the set of candidates what we call the **Condorcet digraph**. The `votingProfiles.CondorcetDigraph` class (a specialization of the `digraphs.Digraph` class) is available for handling such pairwise majority margins.

```
>>> from votingProfiles import CondorcetDigraph
>>> cdg = CondorcetDigraph(v,hasIntegerValuation=True)
>>> cdg.showAll()
*----- show detail -------------*
Digraph          : rel_randLinearProfile
*---- Actions ----*
['a1', 'a2', 'a3']
*---- Characteristic valuation domain ----*
{'max': Decimal('15.0'), 'med': Decimal('0'),
 'min': Decimal('-15.0'), 'hasIntegerValuation': True}
* ---- majority margins -----
   M(x,y)    |  'a1'   'a2'  'a3'
  ----------|-----------------------------------------
    'a1'     |    0     11     1
    'a2'     |  -11      0    -1
    'a3'     |   -1      1     0
Valuation domain: [-15;+15]
```

A candidate *x*, showing a positive majority margin *M(x,y)*, is beating candidate *y* with an absolute majority in a pairwise voting. Hence, a candidate showing only positive terms in her row in the Condorcet digraph relation table, beats all other candidates with absolute majority of votes. Condorcet recommends to declare this candidate (is always unique, why?) the winner of the election. Here we are lucky, it is again candidate *a1* who is hence the **Condorcet winner**-

```
>>> cdg.computeCondorcetWinner()
['a1']
```

By seeing the majority margins like a bipolarly-valued characteristic function for a global preference relation defined on the set of canditates, we may use all operational resources of the generic `Digraph` class (see *Working with the Digraph3 software resources* (page 4)), and especially its `exportGraphViz` method[1], for visualizing an election result.

```
>>> cdg.exportGraphViz('tutorialLinearBallots')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutorialLinearBallots.dot
dot -Grankdir=BT -Tpng tutorialLinearBallots.dot -o tutorialLinearBallots.png
```



Fig. 7: *Visualizing an election result*

4.4 Cyclic social preferences

Usually, when aggregating linear ballots, there appear cyclic social preferences. Let us consider for instance the following linear voting profile and construct the corresponding Condorcet digraph.

```
>>> v.showLinearBallots()
voters(weight)       candidates rankings
v1(1):       ['a1', 'a3', 'a5', 'a2', 'a4']
v2(1):       ['a1', 'a2', 'a4', 'a3', 'a5']
v3(1):       ['a5', 'a2', 'a4', 'a3', 'a1']
v4(1):       ['a3', 'a4', 'a1', 'a5', 'a2']
v5(1):       ['a4', 'a2', 'a3', 'a5', 'a1']
v6(1):       ['a2', 'a4', 'a5', 'a1', 'a3']
v7(1):       ['a5', 'a4', 'a3', 'a1', 'a2']
v8(1):       ['a2', 'a4', 'a5', 'a1', 'a3']
v9(1):       ['a5', 'a3', 'a4', 'a1', 'a2']
>>> cdg = CondorcetDigraph(v)
>>> cdg.showRelationTable()
* ---- Relation Table -----
  S    |  'a1'   'a2'   'a3'   'a4'    'a5'
------|----------------------------------------
'a1'  |   -     0.11  -0.11  -0.56   -0.33
'a2'  | -0.11    -     0.11   0.11   -0.11
'a3'  |  0.11  -0.11    -    -0.33   -0.11
'a4'  |  0.56  -0.11   0.33    -      0.11
'a5'  |  0.33   0.11   0.11  -0.11     -
```

Now, we cannot find any completely positive row in the relation table. No one of the five candidates is beating all the others with an absolute majority of votes. There is no Condorcet winner anymore. In fact, when looking at a graphviz drawing of this Condorcet digraph, we may observe cyclic preferences, like ($a1 > a2 > a3 > a1$) for instance.

```
>>> cdg.exportGraphViz('cycles')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to cycles.dot
dot -Grankdir=BT -Tpng cycles.dot -o cycles.png
```



Fig. 8: *Cyclic social preferences*

But, there may be many cycles appearing in a digraph, and, we may detect and enumerate all minimal chordless circuits in a Digraph instance with the `computeChordlessCircuits()` method.

```
>>> cdg.computeChordlessCircuits()
[(['a2', 'a3', 'a1'], frozenset({'a2', 'a3', 'a1'})),
 (['a2', 'a4', 'a5'], frozenset({'a2', 'a5', 'a4'})),
 (['a2', 'a4', 'a1'], frozenset({'a2', 'a1', 'a4'}))]
```

Condorcet's approach for determining the winner of an election is hence not decisive in all circumstances and we need to exploit more sophisticated approaches for finding the winner of the election on the basis of the majority margins of the given linear ballots (see *[BIS-2008]* (page 105)).

Many more tools for exploiting voting results are available, see the technical documentation of the votingProfiles-label.

Back to *Tutorials of the Digraph3 resources* (page 3)

5 Working with the `outrankingDigraphs` module

- *Outranking digraph* (page 22)
- *Browsing the performances* (page 23)
- *Valuation semantics* (page 24)
- *Pairwise comparisons* (page 25)
- *Recoding the valuation* (page 25)
- *Codual digraph* (page 26)
- *XMCDA 2.0* (page 27)

See also the technical documentation of the outrankingDigraphs-label.

5.1 Outranking digraph

In this *Digraph3* module, the main `outrankingDigraphs.BipolarOutrankingDigraph` class provides a generic **bipolar outranking digraph model**. A given object of this class consists in

1. a potential set of decision **actions** : a dictionary describing the potential decision actions or alternatives with 'name' and 'comment' attributes,
2. a coherent family of **criteria**: a dictionary of criteria functions used for measuring the performance of each potential decision action with respect to the preference dimension captured by each criterion,
3. the **evaluations**: a dictionary of performance evaluations for each decision action or alternative on each criterion function.
4. the digraph **valuationdomain**, a dictionary with three entries: the *minimum* (-100, means certainly no link), the *median* (0, means missing information) and the *maximum* characteristic value (+100, means certainly a link),
5. the **outranking relation** : a double dictionary defined on the Cartesian product of the set of decision alternatives capturing the credibility of the pairwise *outranking situation* computed on the basis of the performance differences observed between couples of decision alternatives on the given family if criteria functions.

With the help of the `outrankingDigraphs.RandomBipolarOutrankingDigraph` class (of type `outrankingDigraphs.BipolarOutrankingDigraph`) , let us generate for illustration a random bipolar outranking digraph consisting of 7 decision actions denoted *a01*, *a02*, . . . , *a07*.

```
>>> from outrankingDigraphs import RandomBipolarOutrankingDigraph
>>> odg = RandomBipolarOutrankingDigraph()
>>> odg.showActions()
*----- show digraphs actions --------------*
key:  a01
name:       random decision action
comment:    RandomPerformanceTableau() generated.
key:  a02
name:       random decision action
comment:    RandomPerformanceTableau() generated.
...
...
key:  a07
name:       random decision action
comment:    RandomPerformanceTableau() generated.
>>> ...
```

In this example we consider furthermore a family of seven equisignificant cardinal criteria functions *g01*, *g02*, . . . , *g07*, measuring the performance of each alternative on a rational scale from 0.0 to 100.00. In order to capture the evaluation's uncertainty and imprecision, each criterion function *g1* to *g7* admits three performance discrimination thresholds of 10, 20 and 80 pts for warranting respectively any indifference, preference and veto situations.

```
>>> odg.showCriteria()
*----  criteria -----*
g01 'digraphs.RandomPerformanceTableau() instance'
  Scale = [0.0, 100.0]
  Weight = 3.0
  Threshold pref : 20.00 + 0.00x ; percentile:  0.28
  Threshold ind : 10.00 + 0.00x ; percentile:  0.095
  Threshold veto : 80.00 + 0.00x ; percentile:  1.0
g02 'digraphs.RandomPerformanceTableau() instance'
  Scale = [0.0, 100.0]
  Weight = 3.0
  Threshold pref : 20.00 + 0.00x ; percentile:  0.33
  Threshold ind : 10.00 + 0.00x ; percentile:  0.19
  Threshold veto : 80.00 + 0.00x ; percentile:  0.95
...
...
```

```
g07 'digraphs.RandomPerformanceTableau() instance'
  Scale = [0.0, 100.0]
  Weight = 10.0
  Threshold pref : 20.00 + 0.00x ; percentile:  0.476
  Threshold ind : 10.00 + 0.00x ; percentile:  0.238
  Threshold veto : 80.00 + 0.00x ; percentile:  1.0
```

The performance evaluations of each decision alternative on each criterion are gathered in a *performance tableau*.

```
>>> odg.showPerformanceTableau()
*----  performance tableau -----*
criteria |  'a01'   'a02'   'a03'   'a04'   'a05'   'a06'   'a07'
---------|-------------------------------------------------------
  'g01'  |   9.6    48.8    21.7    37.3    81.9    48.7    87.7
  'g02'  |  90.9    11.8    96.6    41.0    34.0    53.9    46.3
  'g03'  |  97.8    46.4    83.3    30.9    61.5    85.4    82.5
  'g04'  |  40.5    43.6    53.2    17.5    38.6    21.5    67.6
  'g05'  |  33.0    40.7    96.4    55.1    46.2    58.1    52.6
  'g06'  |  47.6    19.0    92.7    55.3    51.7    26.6    40.4
  'g07'  |  41.2    64.0    87.7    71.6    57.8    59.3    34.7
>>> ...
```

5.2 Browsing the performances

We may visualize the same performance tableau in a two-colors setting in the default system browser with the command.

```
>>> odg.showHTMLPerformanceTableau()
>>> ...
```

Performance table

criterion	a01	a02	a03	a04	a05	a06	a07
g01	9.56	48.84	21.73	37.26	81.93	48.68	87.73
g02	90.94	11.79	96.56	41.03	33.96	53.90	46.27
g03	97.79	46.36	83.35	30.89	61.55	85.36	82.53
g04	40.53	43.61	53.22	17.50	38.65	21.51	67.62
g05	33.04	40.67	96.42	55.13	46.21	58.10	52.65
g06	47.57	19.00	92.65	55.32	51.70	26.64	40.39
g07	41.21	63.95	87.70	71.61	57.79	59.29	34.69

Fig. 9: *Visualizing a performance tableau in a browser window*

It is worthwhile noticing that *green* and *red* marked evaluations indicate *best*, respectively *worst*, performances of an alternative on a criterion. In this example, we may hence notice that alternative *a03* is in fact best performing on *four* out of *seven* criteria.

We may, furthermore, rank the alternatives on the basis of the weighted marginal quintiles and visualize the same performance tableau in an even more colorful and sorted setting.

```
>>> odg.showHTMLPerformanceHeatmap(quantiles=5,colorLevels=5)
>>> ...
```

Performance heatmap

criterion	g07	g06	g03	g04	g05	g02	g01
weight	10.00	7.00	6.00	5.00	3.00	3.00	3.00
a03	87.70	92.65	83.35	53.22	96.42	96.56	21.73
a04	71.61	55.32	30.89	17.50	55.13	41.03	37.26
a05	57.79	51.70	61.55	38.65	46.21	33.96	81.93
a07	34.69	40.39	82.53	67.62	52.65	46.27	87.73
a06	59.29	26.64	85.36	21.51	58.10	53.90	48.68
a01	41.21	47.57	97.79	40.53	33.04	90.94	9.56
a02	63.95	19.00	46.36	43.61	40.67	11.79	48.84

Color legend

quantile	0.2	0.4	0.6	0.8	1.0

Fig. 10: *Ranked heatmap of the performance table*

There is no doubt that action *a03*, with a performance in the highest quintile in five out of seven criteria, appears definitely to be best performing. Action *a05* shows a more or less average performance on most criteria, whereas action *a02* appears to be the weakest alternative.

5.3 Valuation semantics

Considering the given performance tableau, the `outrankingDigraphs.BipolarOutrankingDigraph` class construc

1. If $r(x\,S\,y) > 0.0$ it is more *True* than *False* that *x outranks y*, i.e. alternative x is at least as well performing than alternative y **and** there is no considerable negative performance difference observed in disfavour of x,
2. If $r(x\,S\,y) < 0.0$ it is more *False* than *True* that *x outranks y*, i.e. alternative x is **not** at least as well performing than alternative y **and** there is no considerable positive performance difference observed in favour of x,
3. If $r(x\,S\,y) = 0.0$ it is *indeterminate* whether *x outranks y or not*.

The resulting bipolarly valued outranking relation may be inspected with the following command.

```
>>> odg.showRelationTable()
* ---- Relation Table -----
r(x S y)|   'a01'   'a02'   'a03'   'a04'   'a05'   'a06'   'a07'
--------|-------------------------------------------------------------
 'a01'  |   +0.00  +29.73  -29.73  +13.51  +48.65  +40.54  +48.65
 'a02'  |  +13.51   +0.00 -100.00  +37.84  +13.51  +43.24  -37.84
 'a03'  |  +83.78 +100.00   +0.00  +91.89  +83.78  +83.78  +70.27
 'a04'  |  +24.32  +48.65  -56.76   +0.00  +24.32  +51.35  +24.32
 'a05'  |  +51.35 +100.00  -70.27  +72.97   +0.00  +51.35  +32.43
 'a06'  |  +16.22  +72.97  -51.35  +35.14  +32.43   +0.00  +37.84
 'a07'  |  +67.57  +45.95  -24.32  +27.03  +27.03  +45.95   +0.00
>>> odg.valuationdomain
{'min': Decimal('-100.0'), 'max': Decimal('100.0'), 'med': Decimal('0.0')}
```

5.4 Pairwise comparisons

From above given semantics, we may consider that *a01* outranks *a02* ($r(a_{01}\, S\, a_{02}) > 0.0$), but not *a03* ($r(a_{01}\, S\, a_{03}) < 0.0$). In order to comprehend the characteristic values shown in the relation table above, we may furthermore have a look at the pairwise multiple criteria comparison between alternatives *a01* and *a02*.

```
>>> odg.showPairwiseComparison('a01','a02')
*------------  pairwise comparison ----*
Comparing actions : (a01, a02)
crit. wght.   g(x)  g(y)    diff        | ind     p    concord  |
------------------------------ ---------------------------------
g01    3.00   9.56  48.84  -39.28       | 10.00  20.00   -3.00  |
g02    3.00  90.94  11.79  +79.15       | 10.00  20.00   +3.00  |
g03    6.00  97.79  46.36  +51.43       | 10.00  20.00   +6.00  |
g04    5.00  40.53  43.61   -3.08       | 10.00  20.00   +5.00  |
g05    3.00  33.04  40.67   -7.63       | 10.00  20.00   +3.00  |
g06    7.00  47.57  19.00  +28.57       | 10.00  20.00   +7.00  |
g07   10.00  41.21  63.95  -22.74       | 10.00  20.00  -10.00  |
-----------------------------------------------------------------
Valuation in range: -37.00 to +37.00; global concordance: +11.00
```

The outranking valuation characteristic appears as **majority margin** resulting from the difference of the weights of the criteria in favor of the statement that alternative *a01* is at least well performing as alternative *a02*. No considerable performance difference being observed, no veto or counter-veto situation is triggered in this pairwise comparison. Such a case is, however, observed for instance when we pairwise compare the performances of alternatives *a03* and *a02*.

```
>>> odg.showPairwiseComparison('a03','a02')
*------------  pairwise comparison ----*
Comparing actions : (a03, a02)
crit.  wght.  g(x)  g(y)    diff        | ind     p    concord  |  v  veto/counter-
-------------------------------------------------------------------------------------
g01    3.00  21.73  48.84  -27.11       | 10.00  20.00   -3.00  |
g02    3.00  96.56  11.79  +84.77       | 10.00  20.00   +3.00  |  80.00  +1.00
g03    6.00  83.35  46.36  +36.99       | 10.00  20.00   +6.00  |
g04    5.00  53.22  43.61   +9.61       | 10.00  20.00   +5.00  |
g05    3.00  96.42  40.67  +55.75       | 10.00  20.00   +3.00  |
g06    7.00  92.65  19.00  +73.65       | 10.00  20.00   +7.00  |
g07   10.00  87.70  63.95  +23.75       | 10.00  20.00  +10.00  |
-------------------------------------------------------------------------------------
 Valuation in range: -37.00 to +37.00; global concordance: +31.00
>>> ...
```

This time, we observe a considerable out-performance of *a03* against *a02* on criterion g02 (see second row in the relation table above). We therefore notice a positively polarized *certainly confirmed* outranking situation in this case *[BIS-2013]* (page 105).

5.5 Recoding the valuation

All outranking digraphs, being of root type `digraphs.Digraph`, inherit the methods available under this class. The characteristic valuation domain of an outranking digraph may be recoded with the `digraphs.Digraph.recodeValutaion()` method below to the integer range [-37,+37], i.e. plus or minus the global significance of the family of criteria considered in this example instance.

```
>>> odg.recodeValuation(-37,+37)
>>> odg.valuationdomain['hasIntegerValuation'] = True
>>> Digraph.showRelationTable(odg)
* ---- Relation Table -----
* ---- Relation Table -----
  S   | 'a01'   'a02'   'a03'  'a04'   'a05'   'a06'   'a07'
-----|-------------------------------------------------------
```

```
'a01' |     0     +11     -11     +5     +17     +14     +17
'a02' |   +5       0     -37    +13      +5     +15     -14
'a03' |  +31     +37       0    +34     +31     +31     +26
'a04' |   +9     +18     -21      0      +9     +19      +9
'a05' |  +19     +37     -26    +27       0     +19     +12
'a06' |   +6     +27     -19    +13     +12       0     +14
'a07' |  +25     +17      -9     +9      +9     +17       0
Valuation domain:  {'hasIntegerValuation': True, 'min': Decimal('-37'),
                    'max': Decimal('37'), 'med': Decimal('0.000')}
>>> ...
```

Note: Notice that the reflexive self comparison characteristic $r(xSx)$ is set by default to the median indeterminate valuation value 0; the reflexive terms of binary relation being generally ignored in most of the `Digraph3` resources.

5.6 Codual digraph

From the theory (see *[BIS-2013]* (page 105), *[ADT-L7]* (page 105)) we know that the bipolarly outranking relation is **weakly complete**, i.e. if $r(x\,S\,y) < 0.0$ then $r(y\,S\,x) >= 0.0$. From this property follows that the bipolarly valued outranking relation verifies the coduality principle: the dual (-) of the converse (~) of the outranking relation corresponds to its strict outranking part. We may visualize the codual (strict) outranking digraph with a graphviz drawing[1].

```
>>> cdodg = -(~odg)
>>> cdodg.exportGraphViz('codualOdg')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to codualOdg.dot
dot -Grankdir=BT -Tpng codualOdg.dot -o codualOdg.png
>>> ...
```



Fig. 11: *Codual digraph*

It becomes readily clear now from the picture above that alternative *a03* strictly outranks in fact all the other alternatives. Hence, *a03* appears as **Condorcet winner** and may be recommended as *best decision action* in this illustrative preference modelling exercise.

5.7 XMCDA 2.0

As with all Digraph instances, it is possible to store permanently a copy of the outranking digraph *odg*. As its outranking relation is automatically generated by the `outrankingDigraphs.BipolarOutrankingDigraph` class constructor on the basis of a given performance tableau, it is sufficient to save only the latter. For this purpose we are using the XMCDA 2.00 (https://www.decision-deck.org/xmcda/) XML encoding scheme of MCDA data, as provided by the Decision Deck Project (see https://www.decision-deck.org/).

```
>>> PerformanceTableau.saveXMCDA2(odg,'tutorialPerfTab')
*----- saving performance tableau in XMCDA 2.0 format  -------------*
File: tutorialPerfTab.xml saved !
>>> ...
```

The resulting XML file may be visualized in a browser window (other than Chrome or Chromium) with a corresponding XMCDA style sheet (see here). Hitting `Ctrl U` in Firefox will open a browser window showing the underlying xml encoded raw text. It is thus possible to easily edit and update as needed a given performance tableau instance. Reinstantiating again a corresponding updated *odg* object goes like follow.

```
>>> pt = XMCDA2PerformanceTableau('tutorialPerfTab')
>>> odg = BipolarOutrankingDigraph(pt)
>>> odg.showRelationTable()
* ---- Relation Table -----
  S    |  'a01'     'a02'    'a03'    'a04'    'a05'    'a06'    'a07'
------|-----------------------------------------------------------
'a01' |   +0.00   +29.73  -29.73  +13.51  +48.65  +40.54  +48.65
'a02' |   +13.51  +0.00  -100.00  +37.84  +13.51  +43.24  -37.84
'a03' |   +83.78  +100.00  +0.00  +91.89  +83.78  +83.78  +70.27
'a04' |   +24.32  +48.65  -56.76   +0.00  +24.32  +51.35  +24.32
'a05' |   +51.35  +100.00  -70.27  +72.97  +0.00  +51.35  +32.43
'a06' |   +16.22  +72.97  -51.35  +35.14  +32.43   +0.00  +37.84
'a07' |   +67.57  +45.95  -24.32  +27.03  +27.03  +45.95   +0.00
>>> ...
```

We recover the original bipolarly valued outranking characteristics, and we may restart again the preference modelling process.

Many more tools for exploiting bipolarly valued outranking digraphs are available in the Digraph3 resources (see the technical documentation of the outrankingDiGraphs-label and the perfTabs-label).

Back to *Tutorials of the Digraph3 resources* (page 3)

6 Generating random performance tableaux

- *Introduction* (page 27)
- *Generating standard random performance tableaux* (page 28)
- *Generating random Cost-Benefit tableaux* (page 29)
- *Generating three objectives tableaux* (page 32)
- *Generating random linearly ranked performances* (page 34)

6.1 Introduction

The `randomPerfTabs` module provides several constructors for random performance tableaux generators of different kind, mainly for the purpose of testing implemented methods and tools presented and discussed in the

Algorithmic Decision Theory course at the University of Luxembourg. This tutorial concerns the four most useful generators:

1. The simplest model, called **RandomPerformanceTableau**, generates a set of *n* decision actions, a set of *m* real-valued performance criteria, ranging by default from 0.0 to 100.0, associated with default discrimination thresholds: 2.5 (ind.), 5.0 (pref.) and 60.0 (veto). The generated performances are Beta(2.2) distributed on each measurement scale.

2. One of the most useful random generator, called **RandomCBPerformanceTableau**, proposes two decision objectives, named *Costs* (to be minimized) respectively *Benefits* (to be maximized) model; its purpose being to generate more or less contradictory performances on these two, usually opposed, objectives. *Low costs* will randomly be coupled with *low benefits*, whereas *high costs* will randomly be coupled with high benefits.

3. Many multiple criteria decision problems concern three decision objectives which take into account *economical*, *societal* as well as *environmental* aspects. For this type of performance tableau model, we provide a specific generator, called **Random3ObjectivesPerformanceTableau**.

4. In order to study aggregation of linear orders, we provide a model called **RandomRankPerformanceTableau** which provides linearly ordered performances without ties on multiple criteria for a given number of decision actions.

6.2 Generating standard random performance tableaux

The `randomPerfTabs.RandomPerformanceTableau` class, the simplest of the kind, specializes the generic `refTabs`

- numberOfActions := nbr of decision actions.
- numberOfCriteria := number performance criteria.
- **weightDistribution := 'random' (default) | 'fixed' | 'equisignificant'.**

  If 'random', weights are uniformly selected randomly
  from the given weight scale;
  If 'fixed', the weightScale must provided a corresponding weights
  distribution;
  If 'equisignificant', all criterion weights are put to unity.
- weightScale := [Min,Max] (default =(1,numberOfCriteria).
- IntegerWeights := True (default) | False (normalized to proportions of 1.0).
- commonScale := [a,b]; common performance measuring scales (default = [0.0,100.0])
- commonThresholds := [(q0,q1),(p0,p1),(v0,v1)]; common indifference(q), preference (p) and considerable performance difference discrimination thresholds. For each threshold type *x* in *{q,p,v}*, the float x0 value represents a constant percentage of the common scale and the float x1 value a proportional value of the actual perforamance measure. Default values are [(2.5.0,0.0),(5.0,0.0),(60.0,0,0)].
- **commonMode := common random distribution of random performance measurements:**

  ('uniform',None,None), uniformly distributed float values on the given common scales' range [Min,Max].
  ('normal',*mu*,*sigma*), truncated Gaussian distribution, by default *mu* = (*b*-*a*)/2 and *sigma* = (*b*-*a*)/4.
  ('triangular',*mode*,*repartition*), generalized triangular distribution with a probability repartition parameter specifying the probability mass accumulated until the mode value. By deafult, *mode* = (*b*-*a*)/2 and *repartition* = 0.5.
  ('beta',None,(alpha,beta)), a beta generator with standard alpha=2 and beta=2 parameters.
- valueDigits := <integer>, precision of performance measurements (2 decimal digits by default).

Code example.

```
>>> from randomPerfTabs import RandomPerformanceTableau
>>> t = RandomPerformanceTableau(numberOfActions=3,numberOfCriteria=1,seed=100)
>>> t.actions
    {'a1': {'comment': 'RandomPerformanceTableau() generated.', 'name': 'random␣
↪decision action'},
     'a2': {'comment': 'RandomPerformanceTableau() generated.', 'name': 'random␣
↪decision action'},
     'a3': {'comment': 'RandomPerformanceTableau() generated.', 'name': 'random␣
↪decision action'}}
>>> t.criteria
    {'g1': {'thresholds': {'ind' : (Decimal('10.0'), Decimal('0.0')),
                           'veto': (Decimal('80.0'), Decimal('0.0')),
                           'pref': (Decimal('20.0'), Decimal('0.0'))},
            'scale': [0.0, 100.0],
            'weight': Decimal('1'),
            'name': 'digraphs.RandomPerformanceTableau() instance',
            'comment': 'Arguments: ; weightDistribution=random;
                weightScale=(1, 1); commonMode=None'}}
>>> t.evaluation
    {'g01': {'a01': Decimal('45.95'),
             'a02': Decimal('95.17'),
             'a03': Decimal('17.47')
            }
    }
```

6.3 Generating random Cost-Benefit tableaux

We provide the `randomPerfTabs.RandomCBPerformanceTableau` class for generating random *Cost* versus *Benefit* organized performance tableaux following the directives below:

- We distinguish three types of decision actions: *cheap*, *neutral* and *expensive* ones with an equal proportion of 1/3. We also distinguish two types of weighted criteria: *cost* criteria to be *minimized*, and *benefit* criteria to be *maximized*; in the proportions 1/3 respectively 2/3.
- Random performances on each type of criteria are drawn, either from an ordinal scale [0;10], or from a cardinal scale [0.0;100.0], following a parametric triangular law of mode: 30% performance for cheap, 50% for neutral, and 70% performance for expensive decision actions, with constant probability repartition 0.5 on each side of the respective mode.
- Cost criteria use mostly cardinal scales (3/4), whereas benefit criteria use mostly ordinal scales (2/3).
- The sum of weights of the cost criteria by default equals the sum weights of the benefit criteria: weighDistribution = 'equiobjectives'.
- On cardinal criteria, both of cost or of benefit type, we observe following constant preference discrimination quantiles: 5% indifferent situations, 90% strict preference situations, and 5% veto situation.

***Parameters*:**

- If *numberOfActions* == None, a uniform random number between 10 and 31 of cheap, neutral or advantageous actions (equal 1/3 probability each type) actions is instantiated
- If *numberOfCriteria* == None, a uniform random number between 5 and 21 of cost or benefit criteria (1/3 respectively 2/3 probability) is instantiated
- *weightDistribution* = {'equiobjectives'|'fixed'|'random'|'equisignificant' (default = 'equisignificant')}
- default *weightScale* for 'random' weightDistribution is 1 - numberOfCriteria
- All cardinal criteria are evaluated with decimals between 0.0 and 100.0 whereas ordinal criteria are evaluated with integers between 0 and 10.
- commonThresholds is obsolete. Preference discrimination is specified as percentiles of concerned performance differences (see below).

- commonPercentiles = {'ind':5, 'pref':10, ['weakveto':90,] 'veto':95} are expressed in percents (reversed for vetoes) and only concern cardinal criteria.

Warning: Minimal number of decision actions required is 3 !

Example Python session

```
>>> from randomPerfTabs import RandomCBPerformanceTableau
>>> t = RandomCBPerformanceTableau(
...           numberOfActions=7,
...           numberOfCriteria=5,
...           weightDistribution='equiobjectives',
...           commonPercentiles={'ind':5,'pref':10,'veto':95},
...           seed=100)
>>> t.showActions()
*----- show decision action --------------*
key:  a1
  short name: a1
  name:       random cheap decision action
key:  a2
  short name: a2
  name:       random neutral decision action
...
key:  a7
  short name: a7
  name:       random advantageous decision action
>>> t.showCriteria()
*----  criteria -----*
g1 'random ordinal benefit criterion'
  Scale = (0, 10)
  Weight = 0.167
g2 'random cardinal cost criterion'
  Scale = (0.0, 100.0)
  Weight = 0.250
  Threshold ind  :  1.76 + 0.00x ; percentile:  0.095
  Threshold pref :  2.16 + 0.00x ; percentile:  0.143
  Threshold veto : 73.19 + 0.00x ; percentile:  0.952
...
```

In the example above, we may notice the three types of decision actions (Lines 10-19), as well as the two types (Lines 22-25) of criteria with either an **ordinal** or a **cardinal** performance measuring scale. In the latter case, by default about 5% of the random performance differences will be below the **indifference** and 10% below the **preference discriminating threshold**. About 5% will be considered as **considerably large**. More statistics about the generated performances is available as follows.

```
>>> t.showStatistics()
*-------- Performance tableau summary statistics -------*
Instance name      : randomCBperftab
#Actions           : 7
#Criteria          : 5
*Statistics per Criterion*
Criterion name       : g1
  Criterion weight     : 2
  criterion scale    : 0.00 - 10.00
  mean evaluation    : 5.14
  standard deviation : 2.64
  maximal evaluation : 8.00
  quantile Q3 (x_75) : 8.00
  median evaluation  : 6.50
  quantile Q1 (x_25) : 3.50
  minimal evaluation : 1.00
```

```
  mean absolute difference      : 2.94
  standard difference deviation : 3.74
Criterion name       : g2
  Criterion weight     : 3
  criterion scale    : -100.00 - 0.00
  mean evaluation    : -49.32
  standard deviation : 27.59
  maximal evaluation : 0.00
  quantile Q3 (x_75) : -27.51
  median evaluation  : -35.98
  quantile Q1 (x_25) : -54.02
  minimal evaluation : -91.87
  mean absolute difference      : 28.72
  standard difference deviation : 39.02
...
```

A (potentially ranked) colored heat map with 5 color levels is also provided.

```
>>> t.showHTMLPerformanceHeatmap(colorLevels=5,Ranked=False)
```

Heatmap of performance tableau

criteria	g3	g2	g5	g4	g1
weights	3	3	2	2	2
a1	-33.99	-17.92	3.00	26.68	1.00
a2	-77.77	-30.71	6.00	66.35	8.00
a3	-69.84	-41.65	8.00	53.43	8.00
a4	-16.99	-39.49	2.00	18.62	2.00
a5	-74.85	-91.87	7.00	83.09	6.00
a6	-24.91	-32.47	9.00	79.24	7.00
a7	-7.44	-91.11	7.00	48.22	4.00

Color legend:

quantile	0.20%	0.40%	0.60%	0.80%	1.00%

Fig. 12: *Unranked heatmap of a random Cost-Benefit performance tableau*

Such a performance tableau may be stored and re-accessed in the XMCDA2 encoded format.

```
>>> t.saveXMCDA2('temp')
*----- saving performance tableau in XMCDA 2.0 format  -------------*
File: temp.xml saved !
>>> from perfTabs import XMCDA2PerformanceTableau
>>> t = XMCDA2PerformanceTableau('temp')
>>> ...
```

If needed for instance in an R session, a CSV version of the performance tableau may be created as follows.

```
>>> t.saveCSV('temp')
* --- Storing performance tableau in CSV format in file temp.csv
...$ less temp.csv
"actions","g1","g2","g3","g4","g5"
"a1",1.00,-17.92,-33.99,26.68,3.00
"a2",8.00,-30.71,-77.77,66.35,6.00
"a3",8.00,-41.65,-69.84,53.43,8.00
"a4",2.00,-39.49,-16.99,18.62,2.00
"a5",6.00,-91.87,-74.85,83.09,7.00
"a6",7.00,-32.47,-24.91,79.24,9.00
"a7",4.00,-91.11,-7.44,48.22,7.00
```

Back to *Tutorials of the Digraph3 resources* (page 3)

6.4 Generating three objectives tableaux

We provide the `randomPerfTabs.Random3ObjectivesPerformanceTableau` class for generating random performance tableaux concerning three preferential decision objectives which take respectively into account *economical*, *societal* as well as *environmental* aspects.

Each decision action is qualified randomly as performing **weak** (-), **fair** (~) or **good** (+) on each of the three objectives.

Generator directives are the following:

- numberOfActions = 20 (default),
- numberOfCriteria = 13 (default),
- weightDistribution = 'equiobjectives' (default) | 'random' | 'equisignificant',
- weightScale = (1,numberOfCriteria): only used when random criterion weights are requested,
- integerWeights = True (default): False gives normlized rational weights,
- commonScale = (0.0,100.0),
- commonThresholds = [(5.0,0.0),(10.0,0.0),(60.0,0.0)]: Performance discrimination thresholds may be set for 'ind', 'pref' and 'veto',
- commonMode = ['triangular','variable',0.5]: random number generators of various other types ('uniform','beta') are available,
- valueDigits = 2 (default): evaluations are encoded as Decimals,
- missingProbability = 0.05 (default): random insertion of missing values with given probability,
- seed= None.

Note: If the mode of the **triangular** distribution is set to '*variable*', three modes at 0.3 (-), 0.5 (~), respectively 0.7 (+) of the common scale span are set at random for each coalition and action.

Warning: Minimal number of decision actions required is 3 !

Example Python session

```
>>> from randomPerfTabs import Random3ObjectivesPerformanceTableau
>>> t = Random3ObjectivesPerformanceTableau(
          numberOfActions=31,
          numberOfCriteria=13,
          weightDistribution='equiobjectives',
          seed=120)
```

```
>>> t.showObjectives()
*------ show objectives -------"
Eco: Economical aspect
   g04 criterion of objective Eco 20
   g05 criterion of objective Eco 20
   g08 criterion of objective Eco 20
   g11 criterion of objective Eco 20
  Total weight: 80.00 (4 criteria)
Soc: Societal aspect
   g06 criterion of objective Soc 16
   g07 criterion of objective Soc 16
   g09 criterion of objective Soc 16
   g10 criterion of objective Soc 16
   g13 criterion of objective Soc 16
  Total weight: 80.00 (5 criteria)
Env: Environmental aspect
   g01 criterion of objective Env 20
   g02 criterion of objective Env 20
   g03 criterion of objective Env 20
   g12 criterion of objective Env 20
  Total weight: 80.00 (4 criteria)
```

In the example code above, we notice that 5 *equisignificant* criteria (g06, g07, g09, g10, g13) evaluate for instance the performance of the decision actions from the **societal** point of view. 4 *equisignificant* criteria do the same from the **economical**, respectively the **environmental** point of view. The *equiobjectives* directive results hence in a balanced total weight (80.00) for each decision objective.

```
>>> t.showActions()
key:  a01
  name:       random decision action Eco+ Soc- Env+
  profile:    {'Eco': 'good', 'Soc': 'weak', 'Env': 'good'}
key:  a02
...
key:  a26
  name:       random decision action Eco+ Soc+ Env-
  profile:    {'Eco': 'good', 'Soc': 'good', 'Env': 'weak'}
...
key:  a30
  name:       random decision action Eco- Soc- Env-
  profile:    {'Eco': 'weak', 'Soc': 'weak', 'Env': 'weak'}
...
```

Variable triangular modes (0.3, 0.5 or 0.7 of the span of the measure scale) for each objective result in different performance status for each decision action with respect to the three objectives. Action *a01* , for instance, will probably show *good* performances wrt the *economical* and environmental aspects, and *weak* performances wrt the *societal* aspect.

For testing purposes we provifde a special `perfTabs.PartialPerformanceTableau` class for extracting a **partial performance tableau** from a given tableau instance. In the example blow, we construct the partial performance tableaux corresponding to each on of the three decision objectives.

```
>>> from perfTabs import PartialPerformanceTableau
>>> teco = PartialPerformanceTableau(t,criteriaSubset=\
                          t.objectives['Eco']['criteria'])
>>> tsoc = PartialPerformanceTableau(t,criteriaSubset=\
                          t.objectives['Soc']['criteria'])
>>> tenv = PartialPerformanceTableau(t,criteriaSubset=\
                          t.objectives['Env']['criteria'])
```

One may thus compute a partial bipolar outranking digraph for each individual objective.

```
>>> from outrankingDigraphs import BipolarOutrankingDigraph
>>> geco = BipolarOutrankingDigraph(teco)
>>> gsoc = BipolarOutrankingDigraph(tsoc)
>>> genv = BipolarOutrankingDigraph(tenv)
```

The three partial digraphs: *geco*, *gsoc* and *genv*, hence model the preferences represented in each one of the partial performance tableaux. And, we may aggregate these three outranking digraphs with an epistemic fusion operator.

```
>>> from digraphs import FusionLDigraph
>>> gfus = FusionLDigraph([geco,gsoc,genv])
>>> gfus.strongComponents()
{frozenset({'a30'}),
 frozenset({'a10', 'a03', 'a19', 'a08', 'a07', 'a04', 'a21', 'a20',
            'a13', 'a23', 'a16', 'a12', 'a24', 'a02', 'a31', 'a29',
            'a05', 'a09', 'a28', 'a25', 'a17', 'a14', 'a15', 'a06',
            'a01', 'a27', 'a11', 'a18', 'a22'}),
 frozenset({'a26'})}
>>> from digraphs import StrongComponentsCollapsedDigraph
>>> scc = StrongComponentsCollapsedDigraph(gfus)
>>> scc.showActions()
*----- show digraphs actions --------------*
key:  frozenset({'a30'})
  short name: Scc_1
  name:       _a30_
  comment:    collapsed strong component
key:  frozenset({'a10', 'a03', 'a19', 'a08', 'a07', 'a04', 'a21', 'a20', 'a13',
                 'a23', 'a16', 'a12', 'a24', 'a02', 'a31', 'a29', 'a05', 'a09',
↪'a28', 'a25',
                 'a17', 'a14', 'a15', 'a06', 'a01', 'a27', 'a11', 'a18', 'a22'})
  short name: Scc_2
  name:       _a10_a03_a19_a08_a07_a04_a21_a20_a13_a23_a16_a12_a24_a02_a31_\
               a29_a05_a09_a28_a25_a17_a14_a15_a06_a01_a27_a11_a18_a22_
  comment:    collapsed strong component
key:  frozenset({'a26'})
  short name: Scc_3
  name:       _a26_
  comment:    collapsed strong component
```

A graphviz drawing illustrates the apparent preferential links between the strong components.

```
>>> scc.exportGraphViz('scFusionObjectives')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to scFusionObjectives.dot
dot -Grankdir=BT -Tpng scFusionObjectives.dot -o scFusionObjectives.png
```

Decision action *a26* (Eco+ Soc+ Env-) appears dominating the other decision alternatives, whereas decision action *a30* (Eco- Soc- Env-) appears to be dominated by all the others.

6.5 Generating random linearly ranked performances

Finally, we provide the `randomPerfTabs.RandomRankPerformanceTableau` class for generating multiple criteria ranked performances, ie on each criterion, all decision actions appear linearly ordered without ties.

This type of random performance tabeau is matching the `votingDigrahs.RandomLinearVotingProfile` class provided by the `votingProfiles` module.

***Parameters*:**

- number of actions,
- number of performance criteria,
- weightDistribution := equisignificant | random (default, see above above)



Fig. 13: *Strong components digraph*

- weightScale := (1, 1 | numberOfCriteria (default when random))
- integerWeights := Boolean (True = default)
- **commonThresholds (default) := {**

  'ind':(0,0),
  'pref':(1,0),
  'veto':(numberOfActions,0)
  } (default)

Back to *Tutorials of the Digraph3 resources* (page 3)

7 Ranking with multiple incommensurable criteria

- *The ranking problem* (page 36)
- *The Copeland ranking* (page 38)
- *The Net-Flows ranking* (page 39)
- *Kemeny rankings* (page 39)
- *Slater rankings* (page 40)
- *Kohler's ranking-by-choosing rule* (page 41)
- *Tideman's Ranked-Pairs rule* (page 42)
- *Ranking big performance tableaux* (page 43)

7.1 The ranking problem

We need to rank without ties a set X of items (usually decision alternatives) that are evaluated on multiple incommensurable performance criteria; yet, for which we may know their pairwise valued outranking situation characteristics, i.e. r(x S y) for all x, y in X (see *[BIS-2013]* (page 105)).

Unfortunately, the Condorcet digraph, associated with such a given outranking digraph, presents only exceptionally a linear ordering. Usually, pairwise majority comparisons do not render even a complete or, at least, a transitive partial outranking relation.

Let us consider a didactic outranking digraph generated from a random Cost-Benefit performance tableau concerning 9 decision alternatives evaluated on 13 performance criteria.

```
>>> from outrankingDigraphs import *
>>> t = RandomCBPerformanceTableau(numberOfActions=9,
...                                numberOfCriteria=13,seed=2)
>>> g = BipolarOutrankingDigraph(t,Normalized=True)
>>> g.showRelationTable(ReflexiveTerms=False)
* ---- Relation Table -----
 S   |  'a1'    'a2'   'a3'    'a4'   'a5'   'a6'   'a7'   'a8'   'a9'
-----|-------------------------------------------------------------
'a1' |    -     +0.00  +0.24  +0.24  +0.00  +0.17  +0.26  +0.07  +0.00
'a2' |  +0.00    -     -0.50  +0.00  -0.13  +0.00  +0.00  -0.02  +0.00
'a3' |  +0.14  +0.50    -     +0.40  +0.36  +0.50  +0.71  +0.69  +1.00
'a4' |  +0.05  +0.00  -0.40    -     +0.00  +0.21  +0.26  -0.10  +0.10
'a5' |  +0.00  +0.36  -0.36  +0.00    -     +0.26  +0.00  +0.26  -1.00
'a6' |  -0.10  +0.00  -0.29  -0.07  +0.02    -     +0.24  +0.19  +0.04
'a7' |  -0.26  +0.00  -0.29  -0.02  +0.00  -0.10    -     +0.00  -1.00
'a8' |  -0.07  +0.33  -0.24  +0.10  +0.05  +0.29  +0.00    -     -0.02
'a9' |  +0.00  +0.00  -1.00  -0.10  +1.00  +0.33  +1.00  +0.02    -
```

Some ranking rules will work on the associated Condorcet digraph, i.e. the strict median cut polarised digraph.

```
>>> c = PolarisedOutrankingDigraph(g,level=0,KeepValues=False,
...                                StrictCut=True)
>>> c.showRelationTable(ReflexiveTerms=False,IntegerValues=True)
* ---- Relation Table -----
 S   |  'a1' 'a2' 'a3' 'a4' 'a5' 'a6' 'a7' 'a8' 'a9',
-----|-------------------------------------------------------
'a1' |    -    0   +1   +1    0   +1   +1   +1    0
'a2' |    0    -   -1    0   -1    0    0   -1    0
'a3' |   +1   +1    -   +1   +1   +1   +1   +1   +1
'a4' |   +1    0   -1    -    0   +1   +1   -1   +1
'a5' |    0   +1   -1    0    -   +1    0   +1   -1
'a6' |   -1    0   -1   -1   +1    -   +1   +1   +1
'a7' |   -1    0   -1   -1    0   -1    -    0   -1
'a8' |   -1   +1   -1   +1   +1   +1    0    -   -1
'a9' |    0    0   -1   -1   +1   +1   +1   +1    -
```

To estimate how difficult this ranking problem may be, we can have a look at the corresponding *strict* outranking digraph graphviz drawing.

```
>>> gcd = ~(-g) # converse of the negation of g
>>> gcd.exportGraphViz('rankingTutorial')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to rankingTutorial.dot
dot -Grankdir=BT -Tpng rankingTutorial.dot -o rankingTutorial.png
```

The shown strict outranking relation is apparently not transitive: for instance, alternative *a9* outranks alternative *a5* and alternative *a5* outranks *a2*, however *a9* does not outrank *a2*. We may compute the transitivity degree of the outranking digraph, ie the ratio of the number of outranking arcs over the number of arcs of the transitive closue of the digraph *gcd*.



Fig. 14: *The strict outranking digraph*

```
>>> gcd.computeTransitivityDegree()
Decimal('0.508')
```

The outranking relation is hence very far from being transitive; a serious problem when a linear ordering of the decision alternatives is looked for. Let us furthermore see if there are any cyclic outrankings.

```
>>> len(gcd.computeChordlessCircuits())
1
>>> gcd.showChordlessCircuits()
*---- Chordless circuits ----*
['a4', 'a9', 'a8'] , credibility : 0.024
```

There is one chordless circuit detected in the given strict outranking digraph *gcd*, namely *a4* outranks *a9*, the latter outranks *a8*, and *a8* outranks again *a4*. Any potential linear ordering of these three alternatives will, in fact, always contradict somehow the given outranking relation.

Several heuristic ranking rules have been proposed for constructing a linear ordering which is closest in some specific sense to a given outranking relation.

The Digraph3 resources provide some of the most common of these ranking rules, like Copeland's, Kemeny's, Slater's, Kohler and Tideman's ranking rules.

7.2 The Copeland ranking

Copeland's rule, the most intuitive one as it works well for any outranking relation which models in fact a linear order, computes for each alternative a score resulting from the difference between its crisp out-degree (number of validated (+1) crisp outranking situations) and its crisp in-degree (number of validated crisp (+1) outranked situations).

```
>>> from linearOrders import CopelandOrder
>>> cop = CopelandOrder(g,Debug=True)
Copeland score for a1 = +3  (5 - 3)
Copeland score for a2 = -3  (0 - 3)
Copeland score for a3 = +7  (8 - 1)
Copeland score for a4 = +1  (4 - 3)
Copeland score for a5 = -1  (3 - 4)
Copeland score for a6 = -2  (4 - 6)
Copeland score for a7 = -5  (0 - 5)
Copeland score for a8 = -1  (4 - 5)
Copeland score for a9 = +1  (4 - 3)
['a7', 'a2', 'a6', 'a8', 'a5', 'a9', 'a4', 'a1', 'a3']
>>> cop.showRanking()
['a3', 'a1', 'a4', 'a9', 'a5', 'a8', 'a6', 'a2', 'a7']
```

Alternative *a3* has the best score (+7), followed by alternative *a1* (+3). Alternatives *a4* and *a9* have the same score (+1); following the lexicographic rule, *a4* is hence ranked before *a9*. Same situation is observed for *a5* and *a8* with a score of -1.

Notice by the way that Copeland scores, as computed in the associated Condorcet relation table or similarly in the codual digraph drawing above, are in fact invariant under a codual - converse of the negation ~(-g) - transform of the outranking digraph.

Copeland's rule actually renders a linear order which is indeed highly correlated, in the ordinal Kendall sense (see *[BIS-2012]* (page 105)), with the given pairwise outranking relation.

```
>>> corr = g.computeOrdinalCorrelation(cop)
>>> print("Fitness of Copeland's ranking: %.3f" % corr['correlation'])
Fitness of Copeland's ranking: 0.906
```

7.3 The Net-Flows ranking

The valued version of the Copeland rule, called **Net-Flows** rule, is working directly on the given valued outranking digraph g. For each alternative x we compute a net flow score that is the sum of the differences between the **outranking** characteristics $r(x\,S\,y)$ and the **outranked** characteristics r(y S x) for all pairs of alternatives where y is different from x.

```
>>> from linearOrders import NetFlowsOrder
>>> nf = NetFlowsOrder(g)
>>> nf.netFlows
[(Decimal('7.143'), 'a3'),
 (Decimal('2.155'), 'a9'),
 (Decimal('1.214'), 'a1'),
 (Decimal('-0.429'), 'a4'),
 (Decimal('-0.690'), 'a8'),
 (Decimal('-1.631'), 'a6'),
 (Decimal('-1.774'), 'a5'),
 (Decimal('-1.845'), 'a2'),
 (Decimal('-4.143'), 'a7')]
>>> nf.showRanking()
['a3', 'a9', 'a1', 'a4', 'a8', 'a6', 'a5', 'a2', 'a7']
>>> corr = g.computeOrdinalCorrelation(nf)
>>> print("Fitness of net flows ranking: %.3f" % corr['correlation'])
Fitness of net flows ranking: 0.828
```

The **Net-Flows** ranking is here, in this didactic example, not as much correlated with the given outranking relation as its crisp cousin ranking.

To appreciate the effective quality of both the Copeland and the Net-Flows rankings, it is useful to consider Kemeny's and Slater's optimal ranking rules.

7.4 Kemeny rankings

A **Kemeny** ranking is a linear order which is closest, in the sense of the ordinal Kendall distance (see *[BIS-2012]* (page 105)), to the given valued outranking digraph g.

```
>>> from linearOrders import KemenyOrder
>>> ke = KemenyOrder(g,orderLimit=9) # default orderLimit is 7
>>> ke.showRanking()
['a1', 'a3', 'a4', 'a9', 'a5', 'a8', 'a2', 'a6', 'a7']
>>> corr = g.computeOrdinalCorrelation(ke)
>>> print("Fitness of Kemeny's ranking: %.3f" % corr['correlation'])
Fitness of Kemeny's ranking: 0.9175
```

So, **+0.9175** is the highest possible ordinal correlation (fitness) any potential ranking can achieve with the given pairwise outranking relation. A Kemeny ranking may not be unique, and the first one discovered in a brute permutation trying computation, is retained. In our example we hence obtain seven optimal Kemeny rankings with a same maximal Kemeny index of 15.095.

```
>>> ke.maximalRankings
[['a1', 'a3', 'a4', 'a9', 'a5', 'a8', 'a2', 'a6', 'a7'],
['a1', 'a3', 'a4', 'a9', 'a5', 'a8', 'a6', 'a2', 'a7'],
['a1', 'a3', 'a4', 'a9', 'a5', 'a8', 'a6', 'a7', 'a2'],
['a1', 'a3', 'a9', 'a5', 'a8', 'a2', 'a4', 'a6', 'a7'],
['a1', 'a3', 'a9', 'a5', 'a8', 'a4', 'a2', 'a6', 'a7'],
['a1', 'a3', 'a9', 'a5', 'a8', 'a4', 'a6', 'a2', 'a7'],
['a1', 'a3', 'a9', 'a5', 'a8', 'a4', 'a6', 'a7', 'a2']]
>>> ke.maxKemenyIndex
Decimal('15.095')
```

We may visualize the partial order defined by the epistemic disjunction of these seven Kemeny rankings (see weakOrders module) as follows.

```
>>> from weakOrders import KemenyWeakOrder
>>> wke = KemenyWeakOrder(g,orderLimit=9)
>>> wke.exportGraphViz('tutorialKemeny')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutorialKemeny.dot
0 { rank = same; a1; }
1 { rank = same; a3; }
2 { rank = same; a4; a9; }
3 { rank = same; a5; }
4 { rank = same; a8; }
5 { rank = same; a2; a6; }
6 { rank = same; a7; }
dot -Grankdir=TB -Tpng tutorialKemeny.dot -o tutorialKemeny.png
```



Fig. 15: *Epistemic disjunction of Kemeny rankings*

It is interesting to notice that all seven Kemeny rankings place alternative *a1* at rank 1 before alternative *a3*. This is precisely the only inversion that separates the Copeland ranking (see above) from being optimal in the Kemeny sense.

7.5 Slater rankings

The **Slater** ranking rule is similar to Kemeny's, but it is working, instead, on the associated crisp Condorcet digraph c. It renders here the following results.

```
>>> sl = KemenyOrder(c,orderLimit=9)
>>> len(sl.maximalRankings)
174
>>> sl.showRanking()
['a1', 'a3', 'a8', 'a4', 'a6', 'a9', 'a5', 'a2', 'a7']
>>> corr = g.computeOrdinalCorrelation(sl)
>>> print("Fitness of Slater's ranking: %.3f" % corr['correlation'])
Fitness of Slater's ranking: 0.844
>>> slw = KemenyWeakOrder(c,orderLimit=9)
>>> slw.exportGraphViz('tutorialSlater')
```

We notice that the first crisp Slater ranking is a rather good fit (+0.844), better apparently than the Net-Flows ranking. However, there are in fact 174 such potentially optimal Slater rankings. The corresponding epistemic disjunction gives the follwowing partial ordering.



Fig. 16: *Epistemic disjunction of Slater rankings*

What precise ranking result should we hence adopt ?

Kemeny 's as well as *Slater* 's ranking rules are furthermore computationally difficult problems and effective ranking results are only computable for tiny outranking digraphs (< 15 objects).

More efficient ranking heuristics, like the Copeland and the Net-Flows rules, are therefore needed in practice.

7.6 Kohler's ranking-by-choosing rule

Kohler's **ranking-by-choosing** rule can be formulated like this.

At step r (r goes from 1 to n) do the following:

1. Compute for each row of the valued outranking relation table (see above) the smallest value;
2. Select the row where this minimum is maximal. Ties are resolved in lexicographic order;
3. Put the selected decision alternative at rank r;
4. Delete the corresponding row and column from the relation table and restart until the table is empty.

```
>>> from linearOrders import KohlerOrder
>>> ko = KohlerOrder(g)
>>> ko.showRanking()
```

```
['a3', 'a1', 'a8', 'a4', 'a9', 'a6', 'a7', 'a5', 'a2']
>>> corr = g.computeOrdinalCorrelation(ko)
>>> print("Fitness of Kohler's ranking: %.3f" % corr['correlation'])
Fitness of Kohler's ranking: 0.868
```

Here, we find a better fitness (0.868) when compared with Slater's (0.844) or the Net-Flows result (0.828), but not as good as Copeland crisp rule's result (+0.906).

7.7 Tideman's Ranked-Pairs rule

A further ranking heuristic, the **Ranked-Pairs** rule, is based on a prudent incremental construction of linear orders that avoids on the fly any cycling outrankings. The ranking procedure may be formulated as follows:

1. Rank the ordered pairs (x, y) of alternatives in decreasing order of the outranking characteristic values $r(x\,S\,y)$;
2. Consider the pairs in that order (ties are resolved by a lexicographic rule):
   - if the next pair does not create a cycle with the pairs already blocked, block this pair;
   - if the next pair creates a cycle with the already blocked pairs, skip it.

In our didactic outranking example, we get the following result.

```
>>> from linearOrders import RankedPairsOrder
>>> rp = RankedPairsOrder(g,Debug=True)
next pair:  ('a3', 'a9') 1.00
added: (a3,a9) characteristic: 1.00 (1.0)
added: (a9,a3) characteristic: -1.00 (-1.0)
   ...
   ...
next pair:  ('a8', 'a4') 0.09523809523809523809523809524
Circuit detected !!
next pair:  ('a1', 'a8') 0.07142857142857142857142857143
added: (a1,a8) characteristic: 0.07 (1.0)
added: (a8,a1) characteristic: -0.07 (-1.0)
   ...
   ...
next pair:  ('a2', 'a4') 0.00
Circuit detected !!
next pair:  ('a2', 'a6') 0.00
added: (a2,a6) characteristic: 0.00 (1.0)
added: (a6,a2) characteristic: 0.00 (-1.0)
   ...
   ...
>>> rp.showRanking()
['a1', 'a3', 'a4', 'a9', 'a5', 'a8', 'a2', 'a6', 'a7']
```

The Ranked-Pairs rule actually renders one of the seven optimal Kemeny rankings as we may verify below.

```
>>> corr = g.computeOrdinalCorrelation(rp)
>>> print("Fitness of Tideman's ranking: %.3f" % corr['correlation'])
Fitness of Tideman's ranking: 0.918
```

Unfortunately, the Ranked-Pairs ranking rule is again not efficiently scalable to outranking digraphs of larger orders (> 100). For such outranking digraphs, with several hundred of alternatives, only the Copeland and the Net-Flows ranking rules, with a polynomial complexity of $O(n^2)$ where n is the order of the outranking digraph, remain in fact computationally efficient.

7.8 Ranking big performance tableaux

None of the previous ranking heuristics, using essentially only the information given by the outranking relation, are scalable for big outranking digraphs gathering millions of pairwise outranking situations. We may notice, however, that a given outranking digraph -the association of a set of decision alternatives and an outranking relation- is, following the methodological requirements of the outranking approach, necessarily associated with a corresponding performance tableau. And, we may use this underlying performance data for linearly decomposing big sets of decision alternatives into ordered quantiles equivalence classes. This decomposition will lead to a pre-ranked sparse outranking digraph.

In the coding example, we generate for instance, by using multiprocessing techniques, first, a cost benefit performance tableau of 100 decision alternatives and, secondly, we construct a **pre-ranked sparse outranking digraph** instance called *bg*. Notice bwt the *BigData* flag used here for generating a parcimonous performance tableau.

```
>>> from sparseOutrankingDigraphs import PreRankedOutrankingDigraph
>>> tp = RandomCBPerformanceTableau(numberOfActions=100,BigData=True,
...                                 Threading=MP,
...                                 seed=100)
>>> bg = PreRankedOutrankingDigraph(tp,quantiles=20,
...                                 LowerClosed=False,
...                                 minimalComponentSize=1,
...                                 Threading=True)
>>> print(bg)
*----- show short --------------*
Instance name     : randomCBperftab_mp
# Actions         : 100
# Criteria        : 7
Sorting by        : 10-Tiling
Ordering strategy : average
Ranking rule      : Copeland
# Components      : 20
Minimal order     : 1
Maximal order     : 20
Average order     : 5.0
fill rate         : 10.061%
----  Constructor run times (in sec.) ----
Total time        : 0.17790
QuantilesSorting  : 0.09019
Preordering       : 0.00043
Decomposing       : 0.08522
Ordering          : 0.00000
<class 'sparseOutrankingDigraphs.PreRankedOutrankingDigraph'> instance
```

The total run time of the `sparseOutrankingDigraphs.PreRankedOutrankingDigraph` constructor is less than a fifth of a second. The corresponding multiple criteria deciles sorting leads to 20 quantiles equivalence classes. The corresponding pre-ranked decomposition may be visualized as follows.

```
>>> bg.showDecomposition()
*--- quantiles decomposition in decreasing order---*
0. ]0.80-0.90] : [49, 10, 52]
1. ]0.70-0.90] : [45]
2. ]0.70-0.80] : [18, 84, 86, 79]
3. ]0.60-0.80] : [41, 70]
4. ]0.50-0.80] : [44]
5. ]0.60-0.70] : [2, 35, 68, 37, 7, 8, 75, 12, 80, 21, 55, 90, 30, 95]
6. ]0.50-0.70] : [19]
7. ]0.40-0.70] : [69]
8. ]0.50-0.60] : [96, 1, 66, 67, 38, 33, 72, 73, 71, 13, 77, 16, 82,
                 85, 22, 25, 88, 57, 87, 91]
9. ]0.30-0.70] : [42]
10. ]0.40-0.60] : [47]
11. ]0.30-0.60] : [0, 32, 48]
```

```
12. ]0.40-0.50] : [34, 5, 31, 83, 76, 78, 15, 51, 14, 54, 56, 27, 60,
                   29, 94, 63]
13. ]0.30-0.50] : [4, 50, 92, 39]
14. ]0.20-0.50] : [43]
15. ]0.30-0.40] : [97, 99, 36, 6, 89, 61, 93]
16. ]0.20-0.40] : [65, 20, 46, 62]
17. ]0.20-0.30] : [64, 81, 3, 53, 24, 40, 74, 28, 26, 58]
18. ]0.10-0.30] : [17, 98, 11]
19. ]0.10-0.20] : [9, 59, 23]
```

The best decile (]80%-90%]) gathers decision alternatives *49*, *10*, and *52*. Worst decile (]10%-20%]) gathers alternatives *9*, *59*, and *23*.

Each one of these 20 ordered components may now be locally ranked by using a suitable ranking rule. Best operational results, both in run times and quality, are more or less equally given with the Copeland and the NetFlows rules. The eventually obtained linear ordering (from the worst to best) is the following.

```
>>> print(bg.boostedOrder)
[59, 9, 23, 17, 11, 98, 26, 81, 40, 64, 3, 74,
28, 53, 24, 58, 65, 62, 46, 20, 93, 89, 97, 61,
99, 6, 36, 43, 4, 50, 39, 92, 94, 60, 14, 76, 63,
51, 56, 34, 5, 54, 27, 78, 15, 29, 31, 83, 32, 0,
48, 47, 42, 16, 1, 66, 72, 71, 38, 57, 33, 73, 88,
85, 82, 22, 96, 91, 67, 87, 13, 77, 25, 69, 19, 21,
95, 35, 80, 37, 7, 12, 68, 2, 90, 55, 30, 75, 8, 44,
41, 70, 79, 86, 84, 18, 45, 49, 10, 52]
```

Alternative *52* appears first ranked, whereas alternative *59* is last ranked. The quality of this ranking result may be assessed by computing its ordinal correlation with the corresponding standard outranking relation.

```
>>> g = BipolarOutrankingDigraph(tp,Normalized=True,Threading=True)
>>> g.computeOrderCorrelation(bg.boostedOrder)
{'correlation': 0.7485,
 'determination': 0.4173}
```

This ranking heuristic is readily scalable with ad hoc HPC tuning to several millions of decision alternatives (see *[BIS-2016]* (page 105)).

Back to *Tutorials of the Digraph3 resources* (page 3)

8 Computing a best choice recommendation

- *What site to choose ?* (page 45)
- *Performance tableau* (page 46)
- *Outranking digraph* (page 47)
- *Rubis best choice* (page 48)
- *Strictly best choice* (page 51)
- *Weakly ordering* (page 53)

See also the lecture 7 notes from the MICS Algorithmic Decision Theory course: *[ADT-L7]* (page 105).

8.1 What site to choose ?

A SME, specialized in printing and copy services, has to move into new offices, and its CEO has gathered seven **potential office sites**.

address	ID	Comment
Avenue de la liberté	A	High standing city center
Bonnevoie	B	Industrial environment
Cessange	C	Residential suburb location
Dommeldange	D	Industrial suburb environment
Esch-Belval	E	New and ambitious urbanization far from the city
Fentange	F	Out in the countryside
Avenue de la Gare	G	Main town shopping street

Three decision objectives are guiding the CEO's choice:

1. *minimize* the yearly costs induced by the moving,
2. *maximize* the future turnover of the SME,
3. *maximize* the new working conditions.

The decision consequences to take into account for evaluating the potential new office sites with respect to each of the three objectives are modelled by the following **family of criteria**.

Objective	ID	Name	Comment
Yearly costs	C	Costs	Annual rent, charges, and cleaning
Future turnover	St	Standing	Image and presentation
Future turnover	V	Visibility	Circulation of potential customers
Future turnover	Pr	Proximity	Distance from town center
Working conditions	W	Space	Working space
Working conditions	Cf	Comfort	Quality of office equipment
Working conditions	P	Parking	Available parking facilities

The evaluation of the seven potential sites on each criterion are gathered in the following **performance tableau**.

Criterion	weight	A	B	C	D	E	F	G
Costs	3.0	35.0K€	17.8K€	6.7K€	14.1K€	34.8K€	18.6K€	12.0K€
Stan	1.0	100	10	0	30	90	70	20
Visi	1.0	60	80	70	50	60	0	100
Prox	1.0	100	20	80	70	40	0	60
Wksp	1.0	75	30	0	55	100	0	50
Wkcf	1.0	0	100	10	30	60	80	50
Park	1.0	90	30	100	90	70	0	80

Except the *Costs* criterion, all other criteria admit for grading a qualitative satisfaction scale from 0% (worst) to 100% (best). We may thus notice that site *A* is the most expensive, but also 100% satisfying the *Proximity* as well as the *Standing* criterion. Whereas the site *C* is the cheapest one; providing however no satisfaction at all on both the *Standing* and the *Working Space* criteria.

All qualitative criteria, supporting their respective objective, are considered to be *equi-significant* (weights = 1.0). As a consequence, the three objectives are considered *equally important* (total weight = 3.0 each).

Concerning annual costs, we notice that the CEO is indifferent up to a performance difference of 1000€, and he actually prefers a site if there is at least a positive difference of 2500€. The grades observed on the six qualitative

criteria (measured in percentages of satisfaction) are very subjective and rather imprecise. The CEO is hence indifferent up to a satisfaction difference of 10%, and he claims a significant preference when the satisfaction difference is at least of 20%. Furthermore, a satisfaction difference of 80% represents for him a *considerably large* performance difference, triggering a *veto* situation the case given (see *[BIS-2013]* (page 105)).

In view of this performance tableau, what is now the office site we may recommend to the CEO as **best choice** ?

8.2 Performance tableau

The XMCDA 2.0 encoded version of this performance tableau is available for downloading here officeChoice.xml.

We may inspect the performance tableau data with the computing resources provided by the perfTabs-label module.

```
>>> from perfTabs import *
>>> t = XMCDA2PerformanceTableau('officeChoice')
>>> help(t) # for discovering all the methods available
>>> t.showPerformanceTableau()
*----  performance tableau -----*
criteria |   weights |     'A'      'B'      'C'       'D'       'E'       'F'
↪  'G'
---------|-------------------------------------------------------------------------
↪--------
'C'      |    3.00   | -35000.00 -17800.00 -6700.00 -14100.00 -34800.00 -18600.00 -
↪12000.00
'Cf'     |    1.00   |      0.00    100.00    10.00     30.00     60.00     80.00
↪   50.00
'P'      |    1.00   |     90.00     30.00   100.00     90.00     70.00      0.00
↪   80.00
'Pr'     |    1.00   |    100.00     20.00    80.00     70.00     40.00      0.00
↪   60.00
'St'     |    1.00   |    100.00     10.00     0.00     30.00     90.00     70.00
↪   20.00
'V'      |    1.00   |     60.00     80.00    70.00     50.00     60.00      0.00
↪  100.00
'W'      |    1.00   |     75.00     30.00     0.00     55.00    100.00      0.00
↪   50.00
```

We thus recover all the input data. To measure the actual preference discrimination we observe on each criterion, we may use the `showCriteria` method.

```
1  >>> t.showCriteria()
2  *----  criteria -----*
3  C 'Costs'
4  Scale = (Decimal('0.00'), Decimal('50000.00'))
5  Weight = 0.333
6  Threshold ind : 1000.00 + 0.00x ; percentile:  0.095
7  Threshold pref : 2500.00 + 0.00x ; percentile:  0.143
8  Cf 'Comfort'
9  Scale = (Decimal('0.00'), Decimal('100.00'))
10 Weight = 0.111
11 Threshold ind : 10.00 + 0.00x ; percentile:  0.095
12 Threshold pref : 20.00 + 0.00x ; percentile:  0.286
13 Threshold veto : 80.00 + 0.00x ; percentile:  0.905
14 ...
```

On the *Costs* criterion, 9.5% of the performance differences are considered insignificant and 14.3% below the preference discrimination threshold (lines 6-7). On the qualitative *Comfort* criterion, we observe again 9.5% of insignificant performance differences (line 11). Due to the imprecision in the subjective grading, we notice here 28.6% of performance differences below the preference discrimination threshold (line 12). Furthermore, 100.0 -

90.5 = 9.5% of the performance differences are judged *considerably large* (line 13); 80% and more of satisfaction differences triggering in fact a veto situation. Same information is available for all the other criteria.

A colorful comparison of all the performances is shown by the **heat map** statistics, illustrating the respective quantile class of each performance. As the set of potential alternatives is tiny, we choose here a classification into performance quintiles.

```
>>> t.showHTMLPerformanceHeatmap(colorLevels=5)
```

Heatmap of performance tableau officeChoice.xml

criteria	C	W	V	St	Pr	P	Cf
weights	3.00	1.00	1.00	1.00	1.00	1.00	1.00
A	-35000.00	75.00	60.00	100.00	100.00	90.00	0.00
B	-17800.00	30.00	80.00	10.00	20.00	30.00	100.00
C	-6700.00	0.00	70.00	0.00	80.00	100.00	10.00
D	-14100.00	55.00	50.00	30.00	70.00	90.00	30.00
E	-34800.00	100.00	60.00	90.00	40.00	70.00	60.00
F	-18600.00	0.00	0.00	70.00	0.00	0.00	80.00
G	-12000.00	50.00	100.00	20.00	60.00	80.00	50.00

Color legend:

quantile	0.2	0.4	0.6	0.8	1.0

Fig. 17: *Heatmap of the office choice performance tableau*

Site *A* shows extreme and contradictory performances: highest *Costs* and no *Working Comfort* on one hand, and total satisfaction with respect to *Standing*, *Proximity* and *Parking facilities* on the other hand. Similar, but opposite, situation is given for site *C*: unsatisfactory *Working Space*, no *Standing* and no *Working Comfort* on the one hand, and lowest *Costs*, best *Proximity* and *Parking facilities* on the other hand. Contrary to these contradictory alternatives, we observe two appealing compromise decision alternatives: sites *D* and *G*. Finally, site *F* is clearly the less satisfactory alternative of all.

8.3 Outranking digraph

To help now the CEO choosing the best site, we are going to compute pairwise outrankings (see *[BIS-2013]* (page 105)) on th

1. a **significant majority** of criteria concordantly supporting that site *x* is *at least as satisfactory as* site *y*, and
2. **no considerable** counter-performance observed on any discordant criterion.

The credibility of each pairwise outranking situation (see *[BIS-2013]* (page 105)), denoted r(*x* S *y*), is measured in a bipolar significance valuation [-100.00, 100.00], where **positive** terms r(*x* S *y*) > 0.0 indicate a **validated**, and **negative** terms r(*x* S *y*) < 0.0 indicate a **non-validated** outrankings; whereas the **median** value r(*x* S *y*) = 0.0 represents an **indeterminate** situation (see *[BIS-2004]* (page 106)).

For computing such a bipolar valued outranking digraph from the given performance tableau *t*, we use the `BipolarOutrankingDigraph` constructor from the outrankingDigraphs-label module. The `Digraph.showHTMLRelationTable` method shows here the resulting bipolar-valued adjacency matrix in a system browser window.

```
>>> from outrankingDigraphs import BipolarOutrankingDigraph
>>> g = BipolarOutrankingDigraph(t)
>>> g.showHTMLRelationTable()
```

Valued Adjacency Matrix

r(x S y)	A	B	C	D	E	F	G
A	0.00	0.00	100.00	11.11	55.56	0.00	0.00
B	0.00	0.00	0.00	-55.56	0.00	100.00	-55.56
C	0.00	0.00	0.00	33.33	0.00	100.00	11.11
D	33.33	55.56	11.11	0.00	33.33	100.00	22.22
E	55.56	0.00	0.00	-11.11	0.00	100.00	-11.11
F	0.00	-100.00	-100.00	-100.00	-100.00	0.00	-100.00
G	0.00	77.78	-11.11	100.00	55.56	100.00	0.00

Fig. 18: *The office choice outranking digraph*

We may notice that Alternative *D* is **positively outranking** all other potential office sites (a *Condorcet winner*). Yet, alternatives *A* (the most expensive) and *C* (the cheapest) are *not* outranked by any other site; they are in fact **weak** *Condorcet winners*.

```
>>> g.condorcetWinners()
['D']
>>> g.weakCondorcetWinners()
['A', 'C', 'D']
```

We may get even more insight in the apparent outranking situations when looking at the Condorcet digraph.

```
>>> g.exportGraphViz('officeChoice')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to officeChoice.dot
dot -Grankdir=BT -Tpng officeChoice.dot -o officeChoice.png
```

One may check that the outranking digraph *g* does not admit in fact a cyclic strict preference situation.

```
>>> g.computeChordlessCircuits()
[]
>>> g.showChordlessCircuits()
No circuits observed in this digraph.
*---- Chordless circuits ----*
0 circuits.
```

8.4 Rubis best choice

Following the Rubis outranking method (see *[BIS-2008]* (page 105)), potential best choice recommendations are determined by the outranking pre-kernels (weakly independent and strictly outranking choices) of the chordless odd circuits augmented outranking digraph. As we observe no circuits here, we may directly compute the pre-kernels of *g*.

```
>>> g.showPreKernels()
*--- Computing preKernels ---*
Dominant preKernels :
['D']
   independence :  100.0
```



Fig. 19: *The office choice outranking digraph*

```
   dominance    :  11.111
   absorbency   :  -100.0
   covering     :  1.000
['B', 'E', 'C']
   independence :  0.00
   dominance    :  11.111
   absorbency   :  -100.0
   covering     :  0.500
['A', 'G']
   independence :  0.00
   dominance    :  55.556
   absorbency   :  0.00
   covering     :  0.700
Absorbent preKernels :
['F', 'A']
   independence :  0.00
   dominance    :  0.00
   absorbency   :  100.0
   covering     :  0.700
*----- statistics -----
graph name:  rel_officeChoice.xml
number of solutions
 dominant kernels :  3
 absorbent kernels:  1
cardinality frequency distributions
cardinality     :  [0, 1, 2, 3, 4, 5, 6, 7]
dominant kernel :  [0, 1, 1, 1, 0, 0, 0, 0]
absorbent kernel:  [0, 0, 1, 0, 0, 0, 0, 0]
Execution time  : 0.00018 sec.
Results in sets: dompreKernels and abspreKernels.
```

We notice three potential best choice recommendations: the Condorcet winner D (line 4), the triplet B, C and E (line 9), and finally the pair A and G (line 14). The Rubis best choice recommendation is given by the **most determined** pre-kernel; the one supported by the most significant criteria coalition. This result is shown with the following command.

```
1  >>> g.showRubisBestChoiceRecommendation(CoDual=False)
2  ****************************************
3  Rubis best choice recommendation(s) (BCR)
4   (in decreasing order of determinateness)
5  Credibility domain: [-100.00,100.00]
6  === >> potential best choice(s)
7  * choice               : ['D']
8    +-irredundancy       : 100.00
9    independence         : 100.00
10   dominance            : 11.11
11   absorbency           : -100.00
12   covering (%)         : 100.00
13   determinateness (%)  : 55.56
14   - most credible action(s) = { 'D': 2.07, }
15 === >> potential best choice(s)
16 * choice               : ['A', 'G']
17   +-irredundancy       : 0.00
18   independence         : 0.00
19   dominance            : 55.56
20   absorbency           : 0.00
21   covering (%)         : 70.00
22   determinateness (%)  : 50.00
23   - most credible action(s) = { }
24 === >> potential best choice(s)
25 * choice               : ['B', 'C', 'E']
26   +-irredundancy       : 0.00
27   independence         : 0.00
28   dominance            : 11.11
29   absorbency           : -100.00
30   covering (%)         : 50.00
31   determinateness (%)  : 50.00
32   - most credible action(s) = { }
33 === >> potential worst choice(s)
34 * choice               : ['A', 'F']
35   +-irredundancy       : 0.00
36   independence         : 0.00
37   dominance            : 0.00
38   absorbency           : 100.00
39   covered (%)          : 70.00
40   determinateness (%)  : 50.00
41   - most credible action(s) = { }
42 Execution time: 0.014 seconds
43 ****************************
```

We notice in line 6 above that the most significantly supported best choice recommendation is indeed the Condorcet winner D with a majority of 56% of the criteria significance (see line 12). Both other potential best choice recommendations, as well as the potential worst choice recommendation, are not positively validated as best, resp. worst choices. They may or may not be considered so. Alternative A, with extreme contradictory performances, appears both, in a best and a worst choice recommendation (see lines 27 and 37) and seams hence not actually comparable to its competitors.

The same Rubis best choice recommendation, encoded in XMCDA 2.0 and presented in the default system browser, is provided by the `xmcda` module. In a python3 session working in the directory where the XMCDA encoded problem data is stored, we may proceed as follows.

```
1  >>> import xmcda
2  >>> xmcda.showXMCDARubisBestChoiveRecommendation(\
3                              prolemFileName='officeChoice',\
```

```
                                valuationType='bipolar')
```

And, in a system browser window, browse the solution file.

The `valuationType` parameter allows to work:

- on the standard bipolar outranking digraph (valuationType = 'bipolar', default),
- on the normalized –[-1,1] valued– bipolar outranking digraph (valuationType = 'normalized'),
- on the robust –ordinal criteria weights– bipolar outranking digraph (valuationType = 'robust'),
- on the confident outranking digraph (valuationType = 'confident'),
- ignoring considerable performances differences (valuationType = 'noVeto').

One may as well use the Rubis XMCDA 2.0 Web services available at the Leopold-Loewenheim Apache Server of the University of Luxembourg,

```
>>> from outrankingDigraphs import RubisRestServer
>>> solver = RubisRestServer()
>>> solver.ping()
************************************************
* This is the Leopold-Loewenheim Apache Server  *
* of the University of Luxembourg.              *
* Welcome to the Rubis XMCDA 2.0 Web service    *
* R. Bisdorff (c) 2009-2013                     *
* November 2013, version REST/D4 1.1            *
************************************************
```

We may submit the given performance tableau.

```
>>> t = XMCDA2PerformanceTableau('officeChoice')
>>> solver.submitProblem(t)
The problem submission was successful !
Server ticket: 1BYyGVwV866hSNZo
```

With the given ticket, saved in a text file in the working directory, we may request from the Rubis solver the corresponding best choice recommendation.

```
>>> solver.showSolution()
```

And, in a system browser window, browse again the solution file.

Here, we find confirmed again that alternative *D*, indeed, appears to be the most significant best choice candidate.

Yet, what about alternative *G*, the other good compromise best choice we have noticed from the performance heat map shown above?

8.5 Strictly best choice

When comparing the performances of alternatives *D* and *G* on a pairwise perspective, we notice that, with the given preference discrimination thresholds, alternative *G* is actually **certainly** *at least as good as* alternative *D* (r(*G* outranks *D*) = 100.0).

```
>>> g.showPairwiseComparison('G','D')
*------------  pairwise comparison ----*
Comparing actions : (G, D)
crit. wght.  g(x)      g(y)    diff.  |   ind     pref    concord   |
-------------------------------------------------------------------
C   3.00 -12000.00 -14100.00 +2100.00 | 1000.00 2500.00   +3.00     |
Cf  1.00     50.00     30.00   +20.00 |   10.00   20.00   +1.00     |
```

```
P   1.00     80.00     90.00   -10.00 |   10.00   20.00   +1.00     |
Pr  1.00     60.00     70.00   -10.00 |   10.00   20.00   +1.00     |
St  1.00     20.00     30.00   -10.00 |   10.00   20.00   +1.00     |
V   1.00    100.00     50.00   +50.00 |   10.00   20.00   +1.00     |
W   1.00     50.00     55.00    -5.00 |   10.00   20.00   +1.00     |
-------------------------------------------------------------------
Valuation in range: -9.00 to +9.00; global concordance: +9.00
```

However, we must as well notice that the cheapest alternative *C* is in fact **strictly outranking** alternative *G*.

```
>>> g.showPairwiseComparison('C','G')
*------------  pairwise comparison ----*
Comparing actions : (C, G)/(G, C)
crit. wght.   g(x)     g(y)      diff.  |   ind.   pref.    (C,G)/(G,C) |
-----------------------------------------------------------------------
C     3.00 -6700.00 -12000.00  +5300.00 | 1000.00 2500.00   +3.00/-3.00 |
Cf    1.00    10.00     50.00    -40.00 |   10.00   20.00   -1.00/+1.00 |
P     1.00   100.00     80.00    +20.00 |   10.00   20.00   +1.00/-1.00 |
Pr    1.00    80.00     60.00    +20.00 |   10.00   20.00   +1.00/-1.00 |
St    1.00     0.00     20.00    -20.00 |   10.00   20.00   -1.00/+1.00 |
V     1.00    70.00    100.00    -30.00 |   10.00   20.00   -1.00/+1.00 |
W     1.00     0.00     50.00    -50.00 |   10.00   20.00   -1.00/+1.00 |
-----------------------------------------------------------------------
Valuation in range: -9.00 to +9.00; global concordance: +1.00/-1.00
```

To model these *strict outranking* situations, we may compute the Rubis best choice recommendation on the **codual**, the converse (~) of the dual (-), of the outranking digraph instance *g* (see *[BIS-2013]* (page 105)), as follows.

```
1  >>> g.showRubisBestChoiceRecommendation(CoDual=True,ChoiceVector=True)
2  * --- Rubis best choice recommendation(s) ---*
3  (in decreasing order of determinateness)
4  Credibility domain:  {'min':-100.0, 'max': 100.0', 'med':0.0'}
5  === >> potential best choice(s)
6  * choice                : ['A', 'C', 'D']
7    +-irredundancy        : 0.00
8    independence          : 0.00
9    dominance             : 11.11
10   absorbency            : 0.00
11   covering (%)          : 41.67
12   determinateness (%)   : 53.17
13   characteristic vector :
14      { 'D': 11.11, 'A': 0.00, 'C': 0.00, 'G': 0.00,
15        'B': -11.11, 'E': -11.11, 'F': -11.11 }
16 === >> potential worst choice(s)
17 * choice                : ['A', 'F']
18   +-irredundancy        : 0.00
19   independence          : 0.00
20   dominance             : -55.56
21   absorbency            : 100.00
22   covered (%)           : 50.00
23   determinateness (%)   : 50.00
24   characteristic vector :
25      {'A': 0.00, 'B': 0.00, 'C': 0.00, 'D': 0.00,
26       'E': 0.00, 'F': 0.00, 'G': 0.00, }
```

It is interesting to notice that the **strict best choice recommendation** consists in the set of weak Condorcet winners: 'A', 'C' and 'D' (see line 6). In the corresponding characteristic vector (see line 14-15), representing the bipolar credibility degree with which each alternative may indeed be considered a best choice (see *[BIS-2006a]* (page 105)), we find confirmed that alternative *D* is the only positively validated one, whereas both extreme alternatives - *A* (the most expensive) and *C* (the cheapest) - stay in an indeterminate situation. They may be potential best choice candidates besides *D*. Notice furthermore that compromise alternative *G*, while not actually included in the strict best choice recommendation, shows as well an indeterminate situation with respect to being

or not a potential best choice candidate.

We may also notice (see line 17 and line 21) that both alternatives A and F are reported as certainly outranked choices, hence a **potential worst choice recommendation** . This confirms again the global incomparability status of alternative A.

8.6 Weakly ordering

To get a more complete insight in the overall strict outranking situations, we may use the `weakOrders.RankingByChoosingDigraph` constructor imported from the weakOrders-label, for computing a **ranking-by-choosing** result from the strict outranking digraph instance *gcd*.

```
>>> from weakOrders import RankingByChoosingDigraph
>>> gcd = ~(-g)
>>> rbc = RankingByChoosingDigraph(gcd)
Threading ...  ## multiprocessing if 2 cores are available
Exiting computing threads
>>> rbc.showRankingByChoosing()
Ranking by Choosing and Rejecting
1st ranked ['D'] (0.28)
   2nd ranked ['C', 'G'] (0.17)
   2nd last ranked ['B', 'C', 'E'] (0.22)
1st last ranked ['A', 'F'] (0.50)
>>> rbc.exportGraphViz('officeChoiceRanking')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to officeChoiceRanking.dot
0 { rank = same; A; C; D; }
1 { rank = same; G; }
2 { rank = same; E; B; }
3 { rank = same; F; }
dot -Grankdir=TB -Tpng officeChoiceRanking.dot -o officeChoiceRanking.png
```



Fig. 20: *Ranking-by-choosing from the office choice outranking digraph*

In this **ranking-by-choosing** method, where we operate the epistemic fusion of iterated (strict) best and worst choices, compromise alternative D is indeed ranked before compromise alternative G. If the computing node

supports multiple processor cores, best and worst choosing iterations are run in parallel. The overall partial ordering result shows again the important fact that the most expensive site *A*, and the cheapest site *C*, both appear incomparable with most of the other alternatives, as is apparent from the Hasse diagram (see above) of the ranking-by-choosing relation.

The best choice recommendation appears hence depending on the very importance the CEO is attaching to each of the three objectives he is considering. In the setting here, where he considers all three objectives to be **equally important** (minimize costs = 3.0, maximize turnover = 3.0, and maximize working conditions = 3.0), site *D* represents actually the best compromise. However, if *Costs* do not play much a role, it would be perhaps better to decide to move to the most advantageous site *A*; or if, on the contrary, *Costs* do matter a lot, moving to the cheapest alternative *C* could definitely represent a more convincing recommendation.

It might be worth, as an **exercise**, to modify on the one hand this importance balance in the XMCDA data file by lowering the significance of the *Costs* criterion; all criteria are considered **equi-significant** (weight = 1.0) for instance. It may as well be opportune, on the other hand, to **rank** the importance of the three objectives as follows: *minimize costs* (weight = 9.0) **>** *maximize turnover* (weight = 3 x 2.0) **>** *maximize working conditions* (weight = 3 x 1.0). What will become the best choice recommendation under both working hypotheses?

Back to *Tutorials of the Digraph3 resources* (page 3)

9 Rating with learned quantile norms

- *Introduction* (page 54)
- *Incremental learning of historical performance quantiles* (page 55)
- *Rating performances with quantile norms* (page 57)

9.1 Introduction

In this tutorial we address the problem of **rating multiple criteria performances** of a set of potential decision actions with respect to empirical order statistics, ie performance quantiles learned from historical performance data gathered from similar decision actions observed in the past (see *[CPSTAT-L5]* (page 105)).

To illustrate the decision problem we face, consider for a moment that, in a given decision aid study, we observe, for instance in the Table below, the multi-criteria performances of two potential decision actions, named *a1007* and *a1008*, marked on 7 seven **incommensurable** preference criteria: a unique **costs** criterion *c1* (to **minimize**) and 6 **benefit** criteria *b1* to *b6* (to **maximize**).

Criterion	c1	b1	b2	b3	b4	b5	b6
weight	6	1	1	1	1	1	1
a1007	-96.9	70.6	9	82.0	5	34.0	8
a1008	-35.7	9.4	5	62.9	6	51.0	4

The performance on the cost criterion *c1* is measured on a cardinal negative scale from -100.00 (worst) to 0.0 (best). The performances on the benefit criteria *b1*, *b3* and *b5* are measured on a cardinal scale from 0.0 (worst) to 100.00 (best), wheras the performances on benefit criteria *b2*, *b4* and *b6* are measured on an ordinal scale from 0 (worst) to 10 (best). The importance (weight) of the costs criterion is equal to the importance (sum of weights) of the benefit criteria taken all together.

The non trivial decision problem we now face here, is to decide, how the multi-criteria performances of *a1007*, respectively *a1008*, may be rated (**excellent** ? **good** ?, or **fair** ?; perhaps even, **weak** ? or **very weak** ?) in an **order statistical sense**, when compared with all potential similar multi-criteria performances one has encountered, or may encounter in the future.

To solve this absolute rating decision problem, first, we need to estimate multi-criteria **performance quantiles** from historical records.

9.2 Incremental learning of historical performance quantiles

See also the technical documentation of the performanceQuantiles-label.

Suppose that we see flying in random multiple criteria performances from a given model of random performance tableau (see the `randomPerfTabs` module). The question we address here is to estimate empirical performance quantiles on the basis of so far observed performance vectors. For this task, we are inspired by *[CHAM-2006]* (page 105) and *[NR3-2007]* (page 105), who present an efficient algorithm for incrementally updating a quantile-binned cumulative density function (CDF) with newly observed CDFs.

The `performanceQuantiles.PerformanceQuantiles` class implements such a performance quantiles estimation based on a given performance tableau. Its main components are:

- An **objectives** and a **criteria** ordered dictionary from a valid performance tableau instance;
- A list **quantileFrequencies** of quantile frequencies like *quartiles* [0.0, 0.25, 05, 0.75,1.0], *quintiles* [0.0, 0.2, 0.4, 0.6, 0.8, 1.0] or *deciles* [0.0, 0.1, 0.2, ... 1.0] for instance;
- An ordered dictionary **limitingQuantiles** of so far estimated *lower* (default) or *upper* quantile class limits for each frequency per criterion;
- An ordered dictionary **historySizes** for keeping track of the number of evaluations seen so far per criterion. Missing data may make these sizes vary from criterion to criterion.

Example python session

```
1  >>> from performanceQuantiles import PerformanceQuantiles
2  >>> from randomPerfTabs import RandomCBPerformanceTableau
3  >>> nbrActions=1000
4  >>> nbrCrit = 7
5  >>> seed = 105
6  >>> tp = RandomCBPerformanceTableau(numberOfActions=nbrActions,\
7  ...               numberOfCriteria=nbrCrit,seed=seed)
8  >>> pq = PerformanceQuantiles(tp,\
9  ...               numberOfBins = 'quartiles',\
10 ...               LowerClosed=True,Debug=False)
11 >>> pq.__dict__.keys()
12 dict_keys(['objectives', 'LowerClosed', 'name',
13 'quantilesFrequencies', 'criteria', 'historySizes',
14 'limitingQuantiles', ... ])
```

The constructor parameter *numberOfBins* (see Lines 7-9 above), choosing the wished number of quantile frequencies, may be either **quartiles**, **quintiles** (5 bins), **deciles** (10 bins) , **dodeciles** (20 bins) or any other integer number of quantile bins. The quantile bins may be either **lower closed** (default) or **upper-closed**.

```
1  >>> # Printing out the estimated quartile limits
2  >>> pq.showLimitingQuantiles(ByObjectives=True)
3  *----  performance quantiles -----*
4  Costs
5  criteria  | weights |  '0.0'   '0.25'  '0.5'   '0.75'  '1.0'
6   ---------|-------------------------------------------------
7      'c1'  |    6     | -97.12  -69.69  -50.08  -28.95  -1.85
8  Benefits
9  criteria  | weights |  '0.0'   '0.25'  '0.5'   '0.75'  '1.0'
10  ---------|-------------------------------------------------
11     'b1'  |    1     |   2.11   27.92   48.76   68.94   98.69
12     'b2'  |    1     |   0.00    3.00    5.00    7.00   10.00
13     'b3'  |    1     |   1.08   30.41   50.57   69.01   97.23
14     'b4'  |    1     |   0.00    3.00    5.00    7.00   10.00
```

```
    'b5'  |   1     |   1.84   29.77   50.62   70.14   96.40
    'b6'  |   1     |   0.00    3.00    5.00    7.00   10.00
```

Both objectives are equi-important; the weight (6) of the cost criterion balances the sum of weights (6) of the benefit criteria (see column 2). The preference direction of the cost criterion *c1* is negative; the lesser the costs the better it is, wheras all the benefit criteria *b1* to *b6* show positive preference directions, ie the higher the benefits the better it is. The columns entitled '0.0', resp. '1.0' show the quartile *Q0*, resp. *Q4*, ie the **worst**, resp. **best** performance observed so far on each criterion. Column '0.5' shows the **median** (*Q2*) observed on the criteria.

New decision actions with random multiple criteria performance vectors from the same random performance tableau model may now be generated with ad hoc random performance generators. We provide for experimental purpose, in the `randomPerfTabs` module, three such generators: one for the standard `randomPerfTabs.RandomPerformanceTableau` model, one the for the two objectives `randomPerfTabs.RandomCBPerformanceTableau` Cost-Benefit model, and one for the `randomPerfTabs.Random3ObjectivesPerformanceTableau` model with three objectives concerning respectively economic, environmental or social aspects. Given a set of 10 new decision actions with generated random performance evaluations, the so far estimated historical quantile limits may be updated as follows.

```
1 >>> # generate 100 new random decision actions
2 >>> from randomPerfTabs import RandomPerformanceGenerator
3 >>> rpg = RandomPerformanceGenerator(tp,seed=seed)
4 >>> newActions = rpg.randomActions(100)
5 >>> # Updating the quartile norms shown above
6 >>> pq.updateQuantiles(newActions,historySize=None)
```

Parameter *historySize* (see Line 6) of the `performanceQuantiles.PerformanceQuantiles.updateQuantiles()` method allows to **balance** the **new** evaluations against the **historical** ones. With **historySize = None** (the default setting), the balance in the example above is 1000/1100 (91%, weight of historical data) against 100/1100 (9%, weight of the new incoming observations). Putting **historySize = 0**, for instance, will ignore all historical data (0/100 against 100/100) and restart building the quantile estimation with solely the new incomping data. The updated quantile limits may be shown in a browser view.

```
>>> # showing the updated quantile limits in a browser view
>>> pq.showHTMLLimitingQuantiles(Transposed=True)
```

Performance quantiles

Sampling sizes between 994 and 1004.

criterion	0.00	0.25	0.50	0.75	1.00
b1	2.11	24.39	49.80	69.75	98.69
b2	0.00	5.05	6.57	7.84	10.00
b3	1.08	53.61	59.43	80.16	97.23
b4	0.00	5.10	5.89	6.52	10.00
b5	1.84	32.00	39.16	59.81	96.40
b6	0.00	3.96	4.41	7.65	10.00
c1	-97.12	-73.58	-59.89	-42.08	-1.85

Fig. 21: *Showing the updated quartiles limits*

9.3 Rating performances with quantile norms

For **absolute rating** of a newly given set of decision actions with the help of empirical performance quantiles estimated from historical data, we provide the `sortingDigraphs.NormedQuantilesRatingDigraph` class, a specialisation of the `sortingDigraphs.QuantilesSortingDigraph` class.

The constructor requires a valid `performanceQuantiles.PerformanceQuantiles` instance.

Note: It is important to notice that the `sortingDigraphs.NormedQuantilesRatingDigraph` class, contrary to the generic `outrankingDigraphs.OutrankingDigraph` class, does not inherit from the generic `perfTabs.PerformanceTableau` class, but instead from the `performanceQuantiles.PerformanceQuantiles` class. The **actions** in such a `sortingDigraphs.NormedQuantilesRatingDigraph` class instance contain not only the newly given decision actions, but also the historical quantile profiles obtained from a given `performanceQuantiles.PerformanceQuantiles` class instance, ie estimated quantile bins' performance limits from historical performance data.

We reconsider the `PerformanceQuantiles` object instance *pq* as computed in the previous section. Let *newActions* be a set of 10 random generated new decision actions of the same kind.

```
>>> from sortingDigraphs import NormedQuantilesRatingDigraph
>>> newActions = rpg.randomActions(10)
>>> nqr = NormedQuantilesRatingDigraph(pq,newActions,rankingRule='best')
>>> nqr
*-----  Object instance description -----------*
Instance class       : NormedQuantilesRatingDigraph
Instance name        : normedRatingDigraph
# Criteria           : 7
# Quantile classes   : 4
# New actions        : 10
Digraph Size         : 85
Determinateness      : 64.44%
Attributes: [
 'LowerClosed', 'actions', 'actionsRanking', 'categories', 'cdf',
 'completeRelation', 'concordanceRelation', 'criteria', 'criteriaCategoryLimits',
 'evaluation', 'gamma', 'hasNoVeto', 'historySizes', 'limitingQuantiles', 'name',
 'nbrThreads', 'newActions', 'notGamma', 'objectives', 'order', 'profileLimits',
 'profiles',
 'quantilesFrequencies', 'rankingCorrelation', 'rankingRule', 'rankingScores',
 'ratingCategories', 'relation', 'runTimes', 'valuationdomain']
*------  Constructor run times (in sec.) ------*
#Threads          : 1
Total time        : 0.54058
Data input        : 0.00191
Quantile classes  : 0.00361
Compute profiles  : 0.07990
Compute relation  : 0.41333
Compute rating    : 0.01617
Compute sorting   : 0.00000
```

Data input to the `sortingDigraphs.NormedQuantilesRatingDigraph` class constructor (see Line 2-3) are a valid PerformanceQuantiles object *pq* and a compatible set *newActions* of new decision actions generated from the same random origin. Let us have a look at the digraph's nodes, here called **actions**. Among the 10 new incoming decision actions (see below) there are 3 advantageous (high benefits, but also high costs), 4 cheap (low costs, but also low benefits) and 4 neutral decision actions. Among the new decision actions shown in the performance tableau below, we recognize actions *a1007* and *a1008* we have mentioned in our introduction.

```
>>> nqr.showPerformanceTableau(actionsSubset=nqr.newActions)
*----  performance tableau -----*
criteria |  'a1001'  'a1002'  'a1003'  'a1004'  'a1005'  'a1006'  'a1007'  'a1008'␣
 'a1009'  'a1010'
```

```
---------|------------------------------------------------------------------------
----------------
   'c1'  |   -58.5    -70.9    -70.3    -76.7    -38.1    -45.5    -96.9    -35.7
 -79.1    -48.5
   'b1'  |    80.6     49.8     65.7     34.9     18.3     20.4     70.6      9.4
  69.0     48.8
   'b2'  |     9        7        8        6        5        7        9        5
    2        5
   'b3'  |    55.0     60.0     89.0     53.0     28.0     80.0     82.0     62.0
  59.0     11.0
   'b4'  |     8        6        9        5        5        5        5        6
    3        7
   'b5'  |    57.0     30.0     64.0     35.0     30.0     29.0     34.0     51.0
  86.0     39.0
   'b6'  |     4        4        4        3        2        7        8        4
    9        5
```

The `NormedQuantilesRatingDigraphdigraph` instance's actions dictionary also contains the closed lower limits of the four quartile classes: *m1* = [0.0-0.25[, *m2* = [0.25-0.5[, *m3* =[0.5 - 0.75[, *m4* = [0.75 - 1.0[.

```
>>> nqr.showPerformanceTableau(actionsSubset=nqr.profiles)
*----  performance tableau -----*
criteria |  'm1'   'm2'   'm3'   'm4'
---------|----------------------------------------
   'c1'  | -97.1  -73.7  -60.5  -42.5,
   'b1'  |   2.1   26.4   49.8   68.9
   'b2'  |   0.0    4.0    5.0    6.8
   'b3'  |   1.1   44.4   59.8   73.5
   'b4'  |   0.0    3.4    4.0    6.1
   'b5'  |   1.8   31.9   38.9   57.9
   'b6'  |   0.0    2.2    2.8    5.7
```

The main time (0.4 out of 0.5 sec. , see Lines 21-27 of the object description above) is spent by the class constructor in computing a bipolar valued outranking relation on the extended actions set including both the new actions as well as the quartile class limits. In case of large volumes, ie many new decision actions and centile classes for instance, a multi-threading version may be used when multiple processing cores are available (see the technical description of the `sortingDigraphs.NormedQuantilesRatingDigraph` class).

The actual rating procedure will rely on a complete ranking of the new decision actions as well ass the quantile class limits obtained from the corresponding bipolar valued outranking digraph. Two efficient and scalable ranking rules, the **Copeland** and its valued version, the **Netflows** rule may be used for this purpose. The *rankingRule* parameter allows to choose one of both. With *rankingRule='best'* (see Line 2 above) the `NormedQuantilesRatingDigraph` constructor will choose the ranking rule that results in the highest ordinal correlation with the given outranking relation (see *[BIS-2012]* (page 105)).

In this rating example, the Copeland rule appears to be the more appropriate ranking rule.

```
>>> print('Ranking rule        :', nqr.rankingRule)
Ranking rule        : Copeland
>>> print('Actions ranking     :', nqr.actionsRanking)
Actions ranking     : [
'm4', 'a1008', 'a1006', 'a1005', 'a1001', 'a1003', 'a1010',
'm3', 'a1002', 'm2', 'a1004', 'a1009', 'a1007', 'm1']
>>> print('Ranking correlation :', nqr.rankingCorrelation)
Ranking correlation : {
 'determination': Decimal('0.544'),
 'correlation': Decimal('0.966') }
```

We achieve here a linear ranking without ties (from best to worst) of the digraph's actions, ie including the new decision actions as well as the quartile limits *m1* to *m4*, which is very close in an ordinal sense (*tau* = 0.97) to the underlying valued outranking relation. With the *NetFlows* rule we would get the following slightly different ranking result.

```
>>> from linearOrders import NetFlowsOrder
>>> nf = NetFlowsOrder(nqr)
>>> nf.netFlowsRanking
['m4', 'a1008', 'a1001', 'a1006', 'a1003', 'a1005', 'm3',
 'a1010', 'a1002', 'a1007', 'a1009', 'm2', 'a1004', 'm1']
>>> nqr.computeOrderCorrelation(nf.netFlowsOrder)
{'determination': Decimal('0.544'),
 'correlation': Decimal('0.892')}
```

which is, however, less correlated (*tau* = 0.89) with the underlying outranking relation.

The eventual rating procedure is based on the lower quantile limits, such that we may collect the quartile classes' contents in increasing order of the quartiles lower limits.

```
>>> print('Rating categories:', self.ratingCategories)
Rating categories: OrderedDict([
 ('m1', ['a1004', 'a1009', 'a1007']), ('m2', ['a1002']),
 ('m3', ['a1008', 'a1006', 'a1005', 'a1001', 'a1003', 'a1010']),('m4',[]) ])
```

We notice above that no decision action is rated in the highest quartile class [0.75 - 1.0]. Indeed, the rating result is shown in descending order as follows.

```
>>> nqr.showQuantilesRating()
[0.50 - 0.75[ ['a1008', 'a1006', 'a1005', 'a1001', 'a1003', 'a1010']
[0.25 - 0.50[ ['a1002']
[0.00 - 0.25[ ['a1004', 'a1009', 'a1007']
```

The same result may even more conviently be consulted in a browser view via a specialised heatmap format (see `perfTabs:PerformanceTableau.showHTMLPerformanceHeatmap()` method.

```
>>> nqr.showHTMLRatingHeatmap(pageTitle='Heatmap of Quantiles Rating',
↪Correlations=True)
```

Due to the fact that the importance weight (6) of the unique cost criterion *c1* is balancing the sum of the six benefit criteria (6) *b1* to *b6*, the marginal cost criteria ranking is highly correlated (*tau* = 0.80) with the proposed rating of the new decision actions. Is is not a surprise than, that decision action **a1008c**, of **cheap** type (low costs, but several good benfits), appears first ranked in the third quartile class [0.50-0.75[. Whereas, action **a1007a**, of **advantageous** type (excellent benefits but also highest costs), appears worst ranked in the first quartile class [0.0 - 0.25[.

Using furthermore a specialised version of the `weakOrders.WeakOrder.exportGraphViz()` method allows drawing the rating result in a Hasse diagram format.

```
>>> nqr.exportRatingGraphViz()
 *---- exporting a dot file for GraphViz tools ---------*
  Exporting to quantilesRatingDigraph.dot
  dot -Grankdir=TB -Tpng quantilesRatingDigraph.dot -o quantilesRatingDigraph.png
```

A more precise rating result may be achieved when we use **deciles** instead of quartiles for estimating the historical cumulative density functions.

```
>>> pq1 = PerformanceQuantiles(tp, numberOfBins = 'deciles',\
...              LowerClosed=True,Debug=False)
...
>>> nqr1 = NormedQuantilesRatingDigraph(pq1,newActions,rankingRule='best')
>>> nqr1.showQuantilesRating()
*-------- Quantiles rating result ---------
 [0.70 - 0.80[ ['a1008']
 [0.60 - 0.70[ ['a1006', 'a1005']
 [0.50 - 0.60[ ['a1001', 'a1010', 'a1003']
 [0.30 - 0.40[ ['a1002']
```

Heat map of the ratings

Ranking rule: **Copeland**; *Ranking correlation*: **0.966**

criteria	c1	b4	b2	b5	b3	b6	b1
weights	6	1	1	1	1	1	1
tau(*)	0.80	0.45	0.25	0.24	0.20	0.16	-0.02
[0.75 - <[	-42.08	6.52	7.84	59.81	80.16	7.65	69.75
a1008c	-35.67	6.24	5.02	50.55	61.54	4.25	9.41
a1006n	-45.50	4.96	6.81	28.91	79.89	7.41	20.35
a1005c	-38.15	5.34	5.14	30.37	27.67	1.73	18.28
a1001a	-58.49	7.96	9.07	57.27	55.31	4.01	80.59
a1003n	-70.27	8.90	7.55	63.68	89.12	4.43	65.74
a1010n	-48.50	7.00	4.87	38.87	11.36	4.74	48.83
[0.50 - 0.75[	-59.89	5.89	6.57	39.16	59.43	4.41	49.80
a1002n	-70.86	6.17	7.47	30.26	59.79	3.94	49.84
[0.25 - 0.50[	-73.58	5.10	5.05	32.00	53.61	3.96	24.39
a1004a	-76.71	5.07	6.41	35.29	53.37	3.29	34.89
a1009n	-79.10	3.28	1.81	86.11	58.78	9.32	69.03
a1007a	-96.90	5.22	8.86	34.01	82.48	8.27	70.56
[0.00 - 0.25[	-97.12	0.00	0.00	1.84	1.08	0.00	2.11

Color legend:

quantile	20.00%	40.00%	60.00%	80.00%	100.00%

(*) tau: Ordinal (Kendall) correlation between marginal criterion and global ranking relation.
Ordinal (Kendall) correlation between global ranking and outranking relation: 0.97.

Fig. 22: *Heatmap of normed quartiles ranking*



Fig. 23: *Normed quartiles rating digraph*

```
 [0.20 - 0.30[ ['a1004']
 [0.10 - 0.20[ ['a1009', 'a1007']
```

Compared with the previous quartiles rating result, we notice that the six alternatives rated before into the third quartile class [0.50 - 0.75[, are now divided up: action *a1008* attains the 8th decile class [0.7 - 0.8[, actions *a1006* and *a1005* the 7th decile class [06 - 0.7[, and actions *a1001*, *a1010* and *a1003* only the 6th decile class [0.5 - 0.6[. Of the three lowest [0.0 - 0.25[rated actions (*a1004*, *a1009* and *a1007*), action *a1004* is now rated in the third decile class [0.2 - 0.3[, and *a1009* and *a1007* in the second decile class [0.1 - 0.2[.

A browser view may again more conveniently illustrate this preciser deciles rating result.

```
>>> nqr1.showHTMLRatingHeatmap(pageTitle='Heat map of the deciles rating',\
...                            colorLevels=5,Correlations=True)
```

Heat map of the deciles rating

Ranking rule: **Copeland**; *Ranking correlation*: **0.964**

criteria	c1	b4	b2	b5	b6	b3	b1
weights	6	1	1	1	1	1	1
tau(*)	0.84	0.58	0.41	0.39	0.39	0.38	0.24
[0.90 - <[	-36.05	8.00	8.97	81.04	8.87	86.56	73.89
[0.80 - 0.90[	-39.13	7.00	7.93	60.10	7.93	81.91	69.89
a1008c	-35.67	6.24	5.02	50.55	4.25	61.54	9.41
[0.70 - 0.80[	-45.80	6.24	7.51	53.00	7.00	65.40	67.84
a1006n	-45.50	4.96	6.81	28.91	7.41	79.89	20.35
a1005c	-38.15	5.34	5.14	30.37	1.73	27.67	18.28
[0.60 - 0.70[	-48.66	6.20	6.93	46.08	4.69	61.07	56.09
a1001a	-58.49	7.96	9.07	57.27	4.01	55.31	80.59
a1010n	-48.50	7.00	4.87	38.87	4.74	11.36	48.83
a1003n	-70.27	8.90	7.55	63.68	4.43	89.12	65.74
[0.50 - 0.60[	-60.50	5.93	6.58	38.82	4.41	59.57	49.76
a1002n	-70.86	6.17	7.47	30.26	3.94	59.79	49.84
[0.30 - 0.40[	-70.83	5.17	5.11	33.97	3.99	54.36	32.47
[0.40 - 0.50[	-69.55	5.31	5.83	35.42	4.22	57.54	41.97
a1004a	-76.71	5.07	6.41	35.29	3.29	53.37	34.89
[0.20 - 0.30[	-76.62	4.98	4.94	30.35	3.75	34.79	20.37
a1009n	-79.10	3.28	1.81	86.11	9.32	58.78	69.03
a1007a	-96.90	5.22	8.86	34.01	8.27	82.48	70.56
[0.10 - 0.20[	-80.13	3.78	2.00	29.94	2.00	18.21	16.10
[0.00 - 0.10[	-97.12	0.00	0.00	1.84	0.00	1.08	2.11

Color legend:

quantile	14.29%	28.57%	42.86%	57.14%	71.43%	85.71%	100.00%

(*) tau: Ordinal (Kendall) correlation between marginal criterion and global ranking relation.

Fig. 24: *Heatmap of mormed deciles rating*

In the case of industrial production monitoring problems, where large volumes of historical performance data may be available, it could become interesting to estimate even more precisely the marginal cumulative density functions with **dodeciles** or even **centiles**. Especially if **tail** rating results, ie distinguishing **very best**, or **very worst** multiple criteria performances, becomes a critical purpose. Similarly, the *historySize* parameter may be used for monitoring on the fly **unstable** random multiple criteria performance data.

Back to *Tutorials of the Digraph3 resources* (page 3)

10 Working with the graphs module

- *Structure of a Graph object* (page 63)
- *q-coloring of a graph* (page 65)
- *MIS and clique enumeration* (page 66)
- *Line graphs and maximal matchings* (page 68)
- *Grids and the Ising model* (page 69)
- *Simulating Metropolis random walks* (page 70)
- *The Berge mystery story: Who is the lier ?* (page 71)

See also the technical documentation of the graphs-label.

10.1 Structure of a Graph object

In the graphs module, the root graphs.Graph class provides a generic **simple graph model**, without loops and multiple links. A given object of this class consists in:

1. the graph **vertices** : a dictionary of vertices with 'name' and 'shortname' attributes,
2. the graph **valuationDomain** , a dictionary with three entries: the minimum (-1, means certainly no link), the median (0, means missing information) and the maximum characteristic value (+1, means certainly a link),
3. the graph **edges** : a dictionary with frozensets of pairs of vertices as entries carrying a characteristic value in the range of the previous valuation domain,
4. and its associated **gamma function** : a dictionary containing the direct neighbors of each vertice, automatically added by the object constructor.

See the technical documentation of the graphs-label.

Example Python3 session

```
>>> from graphs import Graph
>>> g = Graph(numberOfVertices=7,edgeProbability=0.5)
>>> g.save(fileName='tutorialGraph')
```

The saved Graph instance named tutorialGraph.py is encoded in python3 as follows:

```
# Graph instance saved in Python format
vertices = {
'v1': {'shortName': 'v1', 'name': 'random vertex'},
'v2': {'shortName': 'v2', 'name': 'random vertex'},
'v3': {'shortName': 'v3', 'name': 'random vertex'},
'v4': {'shortName': 'v4', 'name': 'random vertex'},
'v5': {'shortName': 'v5', 'name': 'random vertex'},
'v6': {'shortName': 'v6', 'name': 'random vertex'},
'v7': {'shortName': 'v7', 'name': 'random vertex'},
}
valuationDomain = {'min':-1,'med':0,'max':1}
edges = {
frozenset(['v1','v2']) : -1,
frozenset(['v1','v3']) : -1,
frozenset(['v1','v4']) : -1,
frozenset(['v1','v5']) : 1,
frozenset(['v1','v6']) : -1,
frozenset(['v1','v7']) : -1,
```

```
frozenset(['v2','v3']) : 1,
frozenset(['v2','v4']) : 1,
frozenset(['v2','v5']) : -1,
frozenset(['v2','v6']) : 1,
frozenset(['v2','v7']) : -1,
frozenset(['v3','v4']) : -1,
frozenset(['v3','v5']) : -1,
frozenset(['v3','v6']) : -1,
frozenset(['v3','v7']) : -1,
frozenset(['v4','v5']) : 1,
frozenset(['v4','v6']) : -1,
frozenset(['v4','v7']) : 1,
frozenset(['v5','v6']) : 1,
frozenset(['v5','v7']) : -1,
frozenset(['v6','v7']) : -1,
}
```

The stored graph can be recalled and plotted with the generic `graphs.Graph.exportGraphViz()`[1] method as follows.

```
>>> g = Graph('tutorialGraph')
>>> g.exportGraphViz()
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutorialGraph.dot
fdp -Tpng tutorialGraph.dot -o tutorialGraph.png
>>> ...
```



Fig. 25: *Tutorial graph instance*

Properties, like the gamma function and vertex degrees and neighbourhooddepths may be shown with a *graphs.Graph.showShort()* method.

```
>>> g.showShort()
*---- short description of the graph ----*
Name              : 'tutorialGraph'
Vertices          :  ['v1', 'v2', 'v3', 'v4', 'v5', 'v6', 'v7']
Valuation domain  :  {'min': -1, 'med': 0, 'max': 1}
Gamma function    :
v1 -> ['v5']
v2 -> ['v6', 'v4', 'v3']
v3 -> ['v2']
v4 -> ['v5', 'v2', 'v7']
v5 -> ['v1', 'v6', 'v4']
```

```
v6 -> ['v2', 'v5']
v7 -> ['v4']
degrees      :  [0, 1, 2, 3, 4, 5, 6]
distribution :  [0, 3, 1, 3, 0, 0, 0]
nbh depths   :  [0, 1, 2, 3, 4, 5, 6, 'inf.']
distribution :  [0, 0, 1, 4, 2, 0, 0, 0]
>>> ...
```

A `Graph` instance corresponds bijectively to a symmetric `Digraph` instance and we may easily convert from one to the other with the `graphs.Graph.graph2Digraph()`, and vice versa with the `digraphs.Digraph.digraph2Graph()` method. Thus, all resources of the `digraphs.Digraph` class, suitable for symmetric digraphs, become readily available, and vice versa.

```
>>> dg = g.graph2Digraph()
>>> dg.showRelationTable(ndigits=0,ReflexiveTerms=False)
* ---- Relation Table -----
  S   |  'v1'  'v2'  'v3'  'v4'  'v5'  'v6'  'v7'
-----|----------------------------------------
'v1' |    -    -1    -1    -1     1    -1    -1
'v2' |   -1     -     1     1    -1     1    -1
'v3' |   -1     1     -    -1    -1    -1    -1
'v4' |   -1     1    -1     -     1    -1     1
'v5' |    1    -1    -1     1     -     1    -1
'v6' |   -1     1    -1    -1     1     -    -1
'v7' |   -1    -1    -1     1    -1    -1     -
>>> g1 = dg.digraph2Graph()
>>> g1.showShort()
*---- short description of the graph ----*
Name              : 'tutorialGraph'
Vertices          :  ['v1', 'v2', 'v3', 'v4', 'v5', 'v6', 'v7']
Valuation domain  :  {'med': 0, 'min': -1, 'max': 1}
Gamma function    :
v1 -> ['v5']
v2 -> ['v3', 'v6', 'v4']
v3 -> ['v2']
v4 -> ['v5', 'v7', 'v2']
v5 -> ['v6', 'v1', 'v4']
v6 -> ['v5', 'v2']
v7 -> ['v4']
degrees      :  [0, 1, 2, 3, 4, 5, 6]
distribution :  [0, 3, 1, 3, 0, 0, 0]
nbh depths   :  [0, 1, 2, 3, 4, 5, 6, 'inf.']
distribution :  [0, 0, 1, 4, 2, 0, 0, 0]
>>> ...
```

10.2 q-coloring of a graph

A 3-coloring of the tutorial graph g may for instance be computed and plotted with the `graphs.Q_Coloring` class as follows.

```
>>> from graphs import Q_Coloring
>>> qc = Q_Coloring(g)
Running a Gibbs Sampler for 42 step !
The q-coloring with 3 colors is feasible !!
>>> qc.showConfiguration()
v5 lightblue
v3 gold
v7 gold
v2 lightblue
v4 lightcoral
```

```
v1 gold
v6 lightcoral
>>> qc.exportGraphViz('tutorial-3-coloring')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutorial-3-coloring.dot
fdp -Tpng tutorial-3-coloring.dot -o tutorial-3-coloring.png
```



Fig. 26: *3-Coloring of the tutorial graph*

Actually, with the given tutorial graph instance, a 2-coloring is already feasible.

```
>>> qc = Q_Coloring(g,colors=['gold','coral'])
Running a Gibbs Sampler for 42 step !
The q-coloring with 2 colors is feasible !!
>>> qc.showConfiguration()
v5 gold
v3 coral
v7 gold
v2 gold
v4 coral
v1 coral
v6 coral
>>> qc.exportGraphViz('tutorial-2-coloring')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutorial-2-coloring.dot
fdp -Tpng tutorial-2-coloring.dot -o tutorial-2-coloring.png
```

10.3 MIS and clique enumeration

2-colorings define independent sets of vertices that are maximal in cardinality; for short called a **MIS**. Computing such MISs in a given `Graph` instance may be achieved by the *graphs.Graph.showMIS()* method.

```
>>> g = Graph('tutorialGraph')
>>> g.showMIS()
*---  Maximal Independent Sets ---*
['v2', 'v5', 'v7']
['v3', 'v5', 'v7']
['v1', 'v2', 'v7']
['v1', 'v3', 'v6', 'v7']
['v1', 'v3', 'v4', 'v6']
```



Fig. 27: *2-coloring of the tutorial graph*

```
number of solutions:  5
cardinality distribution
card.:  [0, 1, 2, 3, 4, 5, 6, 7]
freq.:  [0, 0, 0, 3, 2, 0, 0, 0]
execution time: 0.00032 sec.
Results in self.misset
>>> g.misset
[frozenset({'v7', 'v2', 'v5'}),
 frozenset({'v3', 'v7', 'v5'}),
 frozenset({'v1', 'v2', 'v7'}),
 frozenset({'v1', 'v6', 'v7', 'v3'}),
 frozenset({'v1', 'v6', 'v4', 'v3'})]
```

A MIS in the dual of a graph instance *g* (its negation -*g*), corresponds to a maximal **clique**, ie a maximal complete subgraph in *g*. Maximal cliques may be directly enumerated with the *graphs.Graph.showCliques()* method.

```
>>> g.showCliques()
*---  Maximal Cliques ---*
['v2', 'v3']
['v4', 'v7']
['v2', 'v4']
['v4', 'v5']
['v1', 'v5']
['v2', 'v6']
['v5', 'v6']
number of solutions:  7
cardinality distribution
card.:  [0, 1, 2, 3, 4, 5, 6, 7]
freq.:  [0, 0, 7, 0, 0, 0, 0, 0]
execution time: 0.00049 sec.
Results in self.cliques
>>> g.cliques
[frozenset({'v2', 'v3'}), frozenset({'v4', 'v7'}),
 frozenset({'v2', 'v4'}), frozenset({'v4', 'v5'}),
 frozenset({'v1', 'v5'}), frozenset({'v6', 'v2'}),
 frozenset({'v6', 'v5'})]
>>> ...
```

10.4 Line graphs and maximal matchings

The module also provides a `graphs.LineGraph` constructor. A **line graph** represents the **adjacencies between edges** of the given graph instance. We may compute for instance the line graph of the 5-cycle graph.

```
>>> g = CycleGraph(order=5)
>>> g
*------- Graph instance description ------*
Instance class   : CycleGraph
Instance name    : cycleGraph
Graph Order      : 5
Graph Size       : 5
Valuation domain : [-1.00; 1.00]
Attributes       : ['name', 'order', 'vertices', 'valuationDomain',
                    'edges', 'size', 'gamma']
>>> lg = LineGraph(g)
>>> lg
*------- Graph instance description ------*
Instance class   : LineGraph
Instance name    : line-cycleGraph
Graph Order      : 5
Graph Size       : 5
Valuation domain : [-1.00; 1.00]
Attributes       : ['name', 'graph', 'valuationDomain', 'vertices',
                    'order', 'edges', 'size', 'gamma']
>>> lg.showShort()
*---- short description of the graph ----*
Name             : 'line-cycleGraph'
Vertices         :  [frozenset({'v1', 'v2'}), frozenset({'v1', 'v5'}), frozenset({
↪'v2', 'v3'}),
                     frozenset({'v3', 'v4'}), frozenset({'v4', 'v5'})]
Valuation domain :  {'min': Decimal('-1'), 'med': Decimal('0'), 'max': Decimal('1
↪')}
Gamma function   :
frozenset({'v1', 'v2'}) -> [frozenset({'v2', 'v3'}), frozenset({'v1', 'v5'})]
frozenset({'v1', 'v5'}) -> [frozenset({'v1', 'v2'}), frozenset({'v4', 'v5'})]
frozenset({'v2', 'v3'}) -> [frozenset({'v1', 'v2'}), frozenset({'v3', 'v4'})]
frozenset({'v3', 'v4'}) -> [frozenset({'v2', 'v3'}), frozenset({'v4', 'v5'})]
frozenset({'v4', 'v5'}) -> [frozenset({'v4', 'v3'}), frozenset({'v1', 'v5'})]
degrees      :  [0, 1, 2, 3, 4]
distribution :  [0, 0, 5, 0, 0]
nbh depths   :  [0, 1, 2, 3, 4, 'inf.']
distribution :  [0, 0, 5, 0, 0, 0]
```

Iterated line graph constructions are usually expanding, except for *chordless cycles*, where the same cycle is repeated, and for *non-closed paths*, where iterated line graphs progressively reduce one by one the number of vertices and edges and become eventually an empty graph.

Notice that the MISs in the line graph provide **maximal matchings** - *maximal sets of independent edges* - of the original graph.

```
>>> c8 = CycleGraph(order=8)
>>> lc8 = LineGraph(c8)
>>> lc8.showMIS()
*---  Maximal Independent Sets ---*
[frozenset({'v3', 'v4'}), frozenset({'v5', 'v6'}), frozenset({'v1', 'v8'})]
[frozenset({'v2', 'v3'}), frozenset({'v5', 'v6'}), frozenset({'v1', 'v8'})]
[frozenset({'v8', 'v7'}), frozenset({'v2', 'v3'}), frozenset({'v5', 'v6'})]
[frozenset({'v8', 'v7'}), frozenset({'v2', 'v3'}), frozenset({'v4', 'v5'})]
[frozenset({'v7', 'v6'}), frozenset({'v3', 'v4'}), frozenset({'v1', 'v8'})]
[frozenset({'v2', 'v1'}), frozenset({'v8', 'v7'}), frozenset({'v4', 'v5'})]
[frozenset({'v2', 'v1'}), frozenset({'v7', 'v6'}), frozenset({'v4', 'v5'})]
[frozenset({'v2', 'v1'}), frozenset({'v7', 'v6'}), frozenset({'v3', 'v4'})]
```

```
13 [frozenset({'v7', 'v6'}), frozenset({'v2', 'v3'}), frozenset({'v1', 'v8'}),
14  frozenset({'v4', 'v5'})]
15 [frozenset({'v2', 'v1'}), frozenset({'v8', 'v7'}), frozenset({'v3', 'v4'}),
16  frozenset({'v5', 'v6'})]
17 number of solutions:  10
18 cardinality distribution
19 card.:  [0, 1, 2, 3, 4, 5, 6, 7, 8]
20 freq.:  [0, 0, 0, 8, 2, 0, 0, 0, 0]
21 execution time: 0.00029 sec.
```

The two last MISs of cardinality 4 (see Lines 13-16 above) give **isomorphic perfect maximum matchings** of the 8-cycle graph. Every vertex of the cycle is adjacent to a matching edge. Odd cyle graphs do not admid any perfect matching.

```
>>> maxMatching = c8.computeMaximumMatching()
>>> c8.exportGraphViz(fileName='maxMatchingcycleGraph',
...                   matching=maxMatching)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to maxMatchingcyleGraph.dot
Matching:  {frozenset({'v1', 'v2'}), frozenset({'v5', 'v6'}),
            frozenset({'v3', 'v4'}), frozenset({'v7', 'v8'}) }
circo -Tpng maxMatchingcyleGraph.dot -o maxMatchingcyleGraph.png
```



Fig. 28: *A perfect maximum matching of the 8-cycle graph*

10.5 Grids and the Ising model

Special classes of graphs, like n x m **rectangular** or **triangular grids** (`graphs.GridGraph` and `graphs.IsingModel`) are available in the `graphs` module. For instance, we may use a Gibbs sampler again for simulating an **Ising Model** on such a grid.

```
>>> from graphs import GridGraph, IsingModel
>>> g = GridGraph(n=15,m=15)
>>> g.showShort()
*----- show short --------------*
Grid graph    :  grid-6-6
```

```
n               :  6
m               :  6
order           :  36
>>> im = IsingModel(g,beta=0.3,nSim=100000,Debug=False)
Running a Gibbs Sampler for 100000 step !
>>> im.exportGraphViz(colors=['lightblue','lightcoral'])
*---- exporting a dot file for GraphViz tools ---------*
Exporting to grid-15-15-ising.dot
fdp -Tpng grid-15-15-ising.dot -o grid-15-15-ising.png
```



Fig. 29: *Ising model of the 15x15 grid graph*

10.6 Simulating Metropolis random walks

Finally, we provide the `graphs.MetropolisChain` class, a specialization of the `graphs.Graph` class, for implementing a generic **Metropolis MCMC** (Monte Carlo Markov Chain) sampler for simulating random walks on a given graph following a given probability `probs = {'v1': x, 'v2': y, ...}` for visiting each vertex (see lines 14-22).

```
1  >>> from graphs import MetropolisChain
2  >>> g = Graph(numberOfVertices=5,edgeProbability=0.5)
3  >>> g.showShort()
4  *---- short description of the graph ----*
```

```
5  Name              : 'randomGraph'
6  Vertices          :  ['v1', 'v2', 'v3', 'v4', 'v5']
7  Valuation domain :  {'max': 1, 'med': 0, 'min': -1}
8  Gamma function    :
9  v1 -> ['v2', 'v3', 'v4']
10 v2 -> ['v1', 'v4']
11 v3 -> ['v5', 'v1']
12 v4 -> ['v2', 'v5', 'v1']
13 v5 -> ['v3', 'v4']
14 >>> probs = {}  # initialize a potential stationary probability vector
15 >>> n = g.order # for instance: probs[v_i] = n-i/Sum(1:n) for i in 1:n
16 >>> i = 0
17 >>> verticesList = [x for x in g.vertices]
18 >>> verticesList.sort()
19 >>> for v in verticesList:
20 ...     probs[v] = (n - i)/(n*(n+1)/2)
21 ...     i += 1
22 >>> met = MetropolisChain(g,probs)
23 >>> frequency = met.checkSampling(verticesList[0],nSim=30000)
24 >>> for v in verticesList:
25 ...     print(v,probs[v],frequency[v])
26 v1 0.3333 0.3343
27 v2 0.2666 0.2680
28 v3 0.2    0.2030
29 v4 0.1333 0.1311
30 v5 0.0666 0.0635
31 >>> met.showTransitionMatrix()
32 * ---- Transition Matrix -----
33   Pij  | 'v1'    'v2'    'v3'    'v4'    'v5'
34   -----|-----------------------------------
35   'v1' |  0.23   0.33    0.30    0.13    0.00
36   'v2' |  0.42   0.42    0.00    0.17    0.00
37   'v3' |  0.50   0.00    0.33    0.00    0.17
38   'v4' |  0.33   0.33    0.00    0.08    0.25
39   'v5' |  0.00   0.00    0.50    0.50    0.00
```

The `checkSampling()` method (see line 23) generates a random walk of *nSim=30000* steps on the given graph and records by the way the observed relative frequency with which each vertex is passed by. In this example, the stationary transition probability distribution, shown by the `showTransitionMatrix()` method above (see lines 31-), is quite adequately simulated.

For more technical information and more code examples, look into the technical documentation of the graphs-label. For the readers interested in algorithmic applications of Markov Chains we may recommend consulting O. Häggström's 2002 book: *[FMCAA]* (page 106).

10.7 The Berge mystery story: Who is the lier ?

Suppose that the file `berge.py` contains the following `graphs.Graph` instance data:

```
vertices = {
'A': {'name': 'Abe', 'shortName': 'A'},
'B': {'name': 'Burt', 'shortName': 'B'},
'C': {'name': 'Charlotte', 'shortName': 'C'},
'D': {'name': 'Desmond', 'shortName': 'D'},
'E': {'name': 'Eddie', 'shortName': 'E'},
'I': {'name': 'Ida', 'shortName': 'I'},
}
valuationDomain = {'min':-1,'med':0,'max':1}
edges = {
frozenset(['A','B']) : 1,
frozenset(['A','C']) : -1,
```

```
frozenset(['A','D']) : 1,
frozenset(['A','E']) : 1,
frozenset(['A','I']) : -1,
frozenset(['B','C']) : -1,
frozenset(['B','D']) : -1,
frozenset(['B','E']) : 1,
frozenset(['B','I']) : 1,
frozenset(['C','D']) : 1,
frozenset(['C','E']) : 1,
frozenset(['C','I']) : 1,
frozenset(['D','E']) : -1,
frozenset(['D','I']) : 1,
frozenset(['E','I']) : 1,
}
```

This data concerns the famous *Berge mystery story* (see Golumbic, M. C. Algorithmic Graph Theory and Perfect Graphs, *Annals of Discrete Mathematics* 57 p. 20) Six professors (labeled *A*, *B*, *C*, *D*, *E* and *I*) had been to the library on the day that a rare tractate was stolen. Each entered once, stayed for some time, and then left. If two professors were in the library at the same time, then at least one of them saw the other. Detectives questioned the professors and gathered the testimonies that *A* saw *B* and *E*; *B* saw *A* and *I*; *C* saw *D* and *I*; *D* saw *A* and *I*; *E* saw *B* and *I*; and *I* saw *C* and *E*. This data is gathered in the previous file, where each positive edge $\{x, y\}$ models the testimony that, either *x* saw *y*, or, *y* saw *x*.

Example Python3 session

```
>>> from graphs import Graph
>>> g = Graph('berge')
>>> g.showShort()
*---- short description of the graph ----*
Name              : 'berge'
Vertices          :  ['A', 'B', 'C', 'D', 'E', 'I']
Valuation domain  :  {'min': -1, 'med': 0, 'max': 1}
Gamma function    :
A -> ['D', 'B', 'E']
B -> ['E', 'I', 'A']
C -> ['E', 'D', 'I']
D -> ['C', 'I', 'A']
E -> ['C', 'B', 'I', 'A']
I -> ['C', 'E', 'B', 'D']
```

The graph data can be plotted as follows.

```
>>> g.exportGraphViz('berge1')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to berge1.dot
fdp -Tpng berge1.dot -o berge1.png
```

From graph theory we know that time interval intersection graphs must in fact be triangulated. The testimonies graph should therefore not contain any chordless cycles of four and more vertices. Now, the presence or not of chordless cycles may be checked as follows.

```
>>> g.computeChordlessCycles()
Chordless cycle certificate -->>>  ['D', 'C', 'E', 'A', 'D']
Chordless cycle certificate -->>>  ['D', 'I', 'E', 'A', 'D']
Chordless cycle certificate -->>>  ['D', 'I', 'B', 'A', 'D']
[(['D', 'C', 'E', 'A', 'D'], frozenset({'C', 'D', 'E', 'A'})),
(['D', 'I', 'E', 'A', 'D'], frozenset({'D', 'E', 'I', 'A'})),
(['D', 'I', 'B', 'A', 'D'], frozenset({'D', 'B', 'I', 'A'}))]
```

We see three intersection cycles of length 4, which is impossible to occur on the linear time line. Obviously one professor lied! And it is *D* ; if we put to doubt the testimony that he indeed saw *A*, we obtain indeed a triangulated graph instance whose dual is a *comparability* graph. Hence it is, as required, a valid *interval graph* instance.



Fig. 30: *Graph representation of the testimonies of the professors*

```
>>> g.setEdgeValue( ('D','A'), 0)
>>> g.showShort()
*---- short description of the graph ----*
Name              : 'berge'
Vertices          :  ['A', 'B', 'C', 'D', 'E', 'I']
Valuation domain :  {'med': 0, 'min': -1, 'max': 1}
Gamma function    :
A -> ['B', 'E']
B -> ['A', 'I', 'E']
C -> ['I', 'E', 'D']
D -> ['I', 'C']
E -> ['A', 'I', 'B', 'C']
I -> ['B', 'E', 'D', 'C']
>>> g.isIntervalGraph(Comments=True)
Graph 'berge' is triangulated.
Graph 'dual_berge' is transitively orientable.
=> Graph 'berge' is an interval graph.
>>> g.exportGraphViz('berge2')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to berge2.dot
fdp -Tpng berge2.dot -o berge2.png
```



Fig. 31: *The triangulated testominies graph*

Back to *Tutorials of the Digraph3 resources* (page 3)

11 Computing the non isomorphic MISs of the n-cycle graph

Due to the public success of our common 2008 publication with Jean-Luc Marichal *[ISOMIS-08]* (page 105) , we present in this tutorial an example Python session for computing the **non isomorphic maximal independent sets** (MISs) from the 12-cycle graph, i.e. a `digraphs.CirculantDigraph` class instance of order 12 and symmetric circulants 1 and -1.

```
>>> from digraphs import CirculantDigraph
>>> c12 = CirculantDigraph(order=12,circulants=[1,-1])
>>> c12 # 12-cycle digraph instance
*------- Digraph instance description ------*
Instance class   : CirculantDigraph
Instance name    : c12
Digraph Order    : 12
Digraph Size     : 24
Valuation domain : [-1.0, 1.0]
Determinateness  : 100.000
Attributes       : ['name', 'order', 'circulants', 'actions',
                    'valuationdomain', 'relation', 'gamma',
                    'notGamma']
```

Such n-cycle graphs are also provided as undirected graph instances by the `graphs.CycleGraph` class.

```
>>> from graphs import CycleGraph
>>> cg12 = CycleGraph(order=12)
>>> cg12
*------- Graph instance description ------*
Instance class   : CycleGraph
Instance name    : cycleGraph
Graph Order      : 12
Graph Size       : 12
Valuation domain : [-1.0, 1.0]
Attributes       : ['name', 'order', 'vertices', 'valuationDomain',
                    'edges', 'size', 'gamma']
>>> cg12.exportGraphViz('cg12')
```

A non isomorphic MIS corresponds in fact to a set of isomorphic MISs, i.e. an orbit of MISs under the automorphism group of the 12-cycle graph. We are now first computing all maximal independent sets that are detectable in the 12-cycle digraph with the `digraphs.Digraph.showMIS()` method.

```
>>> c12.showMIS(withListing=False)
  *---  Maximal independent choices ---*
  number of solutions:  29
  cardinality distribution
  card.:  [0, 1, 2, 3, 4,  5,  6, 7, 8, 9, 10, 11, 12]
  freq.:  [0, 0, 0, 0, 3, 24,  2, 0, 0, 0,  0,  0,  0]
  Results in c12.misset
```

In the 12-cycle graph, we observe 29 labelled MISs: – 3 of cardinality 4, 24 of cardinality 5, and 2 of cardinality 6. In case of n-cycle graphs with $n > 20$, as the cardinality of the MISs becomes big, it is preferable to use the shell `perrinMIS` command compiled from C and installed[3] along with all the Digraphs3 python modules for computing the set of MISs observed in the graph:

[3] The `perrinMIS` shell command may be installed system wide with the command `.../Digraph3$ make installPerrin` from the main Digraph3 directory. It is stored by default into `</usr/local/bin/>`. This may be changed with the `INSTALLDIR` flag. The command `.../Digraph3$ make installPerrinUser` installs it instead without sudo into the user's private `<$Home/.bin>` directory.



Fig. 32: *The 12-cycle graph*

```
...$ echo 12 | /usr/local/bin/perrinMIS
# ------------------------------------ #
# Generating MIS set of Cn with the    #
# Perrin sequence algorithm.           #
# Temporary files used.                #
# even versus odd order optimized.     #
# RB December 2006                     #
# Current revision Dec 2018            #
# ------------------------------------ #
Input cycle order ? <-- 12
mis 1 : 100100100100
mis 2 : 010010010010
mis 3 : 001001001001
...
...
...
mis 27 : 001001010101
mis 28 : 101010101010
mis 29 : 010101010101
Cardinalities:
0 : 0
1 : 0
2 : 0
3 : 0
4 : 3
5 : 24
6 : 2
7 : 0
8 : 0
```

```
9 : 0
10 : 0
11 : 0
12 : 0
Total: 29
execution time: 0 sec. and 2 millisec.
```

Reading in the result of the `perrinMIS` shell command, stored in a file called by default `curd.dat`, may be operated with the `digraphs.Digraph.readPerrinMisset()` method.

```
>>> c12.readPerrinMisset(file='curd.dat')
>>> c12.misset
{frozenset({'5', '7', '10', '1', '3'}),
 frozenset({'9', '11', '5', '2', '7'}),
 frozenset({'7', '2', '4', '10', '12'}),
 ...
 ...
 ...
 frozenset({'8', '4', '10', '1', '6'}),
 frozenset({'11', '4', '1', '9', '6'}),
 frozenset({'8', '2', '4', '10', '12', '6'})
}
```

For computing the corresponding non isomorphic MISs, we actually need the automorphism group of the c12-cycle graph. The `digraphs.Digraph` class therefore provides the `digraphs.Digraph.automorphismGenerators()` method which adds automorphism group generators to a `digraphs.Digraph` class instance with the help of the external shell <`dreadnaut`> command from the **nauty** software package[2].

```
>>> c12.automorphismGenerators()
...
  Permutations
  {'1': '1', '2': '12', '3': '11', '4': '10', '5':
   '9', '6': '8', '7': '7', '8': '6', '9': '5', '10':
   '4', '11': '3', '12': '2'}
  {'1': '2', '2': '1', '3': '12', '4': '11', '5': '10',
   '6': '9', '7': '8', '8': '7', '9': '6', '10': '5',
   '11': '4', '12': '3'}
>>> print('grpsize = ', c12.automorphismGroupSize)
  grpsize = 24
```

The 12-cycle graph automorphism group is generated with both the permutations above and has group size 24.

The command `digraphs.Digraph.showOrbits()` renders now the labelled representatives of each of the four orbits of isomorphic MISs observed in the 12-cycle graph (see Lines 7-10).

```
1  >>> c12.showOrbits(c12.misset,withListing=False)
2  ...
3    *---- Global result ----
4    Number of MIS:  29
5    Number of orbits :  4
6    Labelled representatives and cardinality:
7    1: ['2','4','6','8','10','12'], 2
8    2: ['2','5','8','11'], 3
9    3: ['2','4','6','9','11'], 12
10   4: ['1','4','7','9','11'], 12
11   Symmetry vector
12   stabilizer size: [1, 2, 3, ..., 8, 9, ..., 12, 13, ...]
13   frequency      : [0, 2, 0, ..., 1, 0, ...,  1,  0, ...]
```

[2] Dependency: The `digraphs.Digraph.automorphismGenerators()` method uses the shell `dreadnaut` command from the nauty software package. See https://www3.cs.stonybrook.edu/~algorith/implement/nauty/implement.shtml . On Mac OS there exist dmg installers and on Ubuntu Linux or Debian, one may easily install it with `...$ sudo apt-get install nauty`.

The corresponding group stabilizers' sizes and frequencies – orbit 1 with 12 symmetry axes, orbit 2 with 8 symmetry axes, and orbits 3 and 4 both with one symmetry axis (see Lines 11-13), are illustrated in the corresponding unlabelled graphs of *Fig. 33* below.



Fig. 33: *The symmetry axes of the four non isomorphic MISs of the 12-cycle graph*:

The non isomorphic MISs in the 12-cycle graph represent in fact all the ways one may write the number 12 as the circular sum of '2's and '3's without distinguishing opposite directions of writing. The first orbit corresponds to writing six times a '2'; the second orbit corresponds to writing four times a '3'. The third and fourth orbit correspond to writing two times a '3' and three times a '2'. There are two non isomorphic ways to do this latter circular sum. Either separating the '3's by one and two '2's, or by zero and three '2's (see Bisdorff & Marichal *[ISOMIS-08]* (page 105)).

Back to *Tutorials of the Digraph3 resources* (page 3)

12 On computing digraph kernels

- *What is a graph kernel ?* (page 77)
- *Initial and terminal kernels* (page 82)
- *Kernels in lateralized digraphs* (page 84)
- *Computing good and bad choice recommendations* (page 86)
- *Tractability* (page 89)

12.1 What is a graph kernel ?

We call **choice** in a graph, respectively a digraph, a subset of its vertices, resp. of its nodes or actions. A choice Y is called **internally stable** or **independent** when there exist **no links** (edges) or relations (arcs) between its members. Furthermore, a choice Y is called **externally stable** when for each vertex, node or action x not in Y,

there exists at least a member y of Y such that x is linked or related to y. Now, an internally **and** externally stable choice is called a **kernel**.

A first trivial example is immediately given by the maximal independent vertices sets (MISs) of the n-cycle graph (see *Computing the non isomorphic MISs of the n-cycle graph* (page 74)). Indeed, each MIS in the n-cycle graph is by definition independent, ie internally stable, and each non selected vertex in the n-cycle graph is in relation with either one or even two members of the MIS. See, for instance, the four non isomorphic MISs of the 12-cycle graph as shown in Fig. 34.

In all graph or symmetric digraph, the *maximality condition* imposed on the internal stability is equivalent to the external stability condition. Indeed, if there would exist a vertex or node not related to any of the elements of a choice, then we may safely add this vertex or node to the given choice without violating its internal stability. All kernels must hence be maximal independent choices. In fact, in a topological sense, they correspond to maximal **holes** in the given graph.

We may illustrate this coincidence between MISs and kernels in graphs and symmetric digraphs with the following random 3-regular graph instance.

```
>>> from graphs import RandomRegularGraph
>>> g = RandomRegularGraph(order=12,degree=3,seed=100)
>>> g.exportGraphViz('random3RegularGraph')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to random3RegularGraph.dot
fdp -Tpng random3RegularGraph.dot -o random3RegularGraph.png
```



Fig. 34: *A random 3-regular graph instance*

A random MIS in this graph may be computed for instance by using the `graphs.MISModel` class.

```
>>> from graphs import MISModel
>>> mg = MISModel(g)
Iteration:  1
Running a Gibbs Sampler for 660 step !
{'a06', 'a02', 'a12', 'a10'}  is maximal !
>>> mg.exportGraphViz('random3RegularGraph_mis')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to random3RegularGraph-mis.dot
fdp -Tpng random3RegularGraph-mis.dot -o random3RegularGraph-mis.png
```

It is easily verified in Fig. 35 above, that the computed MIS renders indeed a valid kernel of the given graph. The complete set of kernels of this 3-regular graph instance coincides hence with the set of its MISs.



Fig. 35: *A random MIS colored in the random 3-regular graph*

```
>>> g.showMIS()
*---  Maximal Independent Sets ---*
['a01', 'a02', 'a03', 'a07']
['a01', 'a04', 'a05', 'a08']
['a04', 'a05', 'a08', 'a09']
['a01', 'a04', 'a05', 'a10']
['a04', 'a05', 'a09', 'a10']
['a02', 'a03', 'a07', 'a12']
['a01', 'a03', 'a07', 'a11']
['a05', 'a08', 'a09', 'a11']
['a03', 'a07', 'a11', 'a12']
['a07', 'a09', 'a11', 'a12']
['a08', 'a09', 'a11', 'a12']
['a04', 'a05', 'a06', 'a08']
['a04', 'a05', 'a06', 'a10']
['a02', 'a04', 'a06', 'a10']
['a02', 'a03', 'a06', 'a12']
['a02', 'a06', 'a10', 'a12']
['a01', 'a02', 'a04', 'a07', 'a10']
['a02', 'a04', 'a07', 'a09', 'a10']
['a02', 'a07', 'a09', 'a10', 'a12']
['a01', 'a03', 'a05', 'a08', 'a11']
['a03', 'a05', 'a06', 'a08', 'a11']
['a03', 'a06', 'a08', 'a11', 'a12']
number of solutions:  22
cardinality distribution
card.:  [0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12]
freq.:  [0, 0, 0, 0, 16, 6, 0, 0, 0, 0, 0, 0, 0]
execution time: 0.00045 sec.
Results in self.misset
>>> g.misset
[frozenset({'a02', 'a01', 'a07', 'a03'}),
 frozenset({'a04', 'a01', 'a08', 'a05'}),
 frozenset({'a09', 'a04', 'a08', 'a05'}),
 ...
 ...
 frozenset({'a06', 'a02', 'a12', 'a10'}),
 frozenset({'a06', 'a11', 'a08', 'a03', 'a05'}),
 frozenset({'a03', 'a06', 'a11', 'a12', 'a08'})]
```

We cannot resist in looking in this 3-regular graph for non isomorphic kernels (MISs, see previous tutorial). To do so we must first, convert the given *graph* instance into a *digraph* instance. Then, compute its automorphism generators, and finally, identify the isomorphic kernel orbits.

```
>>> dg = g.graph2Digraph()
>>> dg.automorphismGenerators()
*----- saving digraph in nauty dre format  -------------*
Actions index:
1 :  a01
2 :  a02
3 :  a03
4 :  a04
5 :  a05
6 :  a06
7 :  a07
8 :  a08
9 :  a09
10 :  a10
11 :  a11
12 :  a12
{'1': 'a01',  '2': 'a02', '3': 'a03', '4': 'a04',  '5': 'a05',
 '6': 'a06',  '7': 'a07', '8': 'a08', '9': 'a09', '10': 'a10',
'11': 'a11', '12': 'a12'}
# automorphisms extraction from dre file #
# Using input file: randomRegularGraph.dre
echo '<randomRegularGraph.dre -m p >randomRegularGraph.auto x' | dreadnaut
# permutation = 1['1', '11', '7', '5', '4', '9', '3', '10', '6', '8', '2', '12']
>>> dg.showOrbits(g.misset)
*--- Isomorphic reduction of choices
...
current representative:  frozenset({'a09', 'a11', 'a12', 'a08'})
length   :  4
number of isomorph choices 2
isormorph choices
['a06', 'a02', 'a12', 'a10']  # <<== the random MIS shown in Fig. 4
['a09', 'a11', 'a12', 'a08']
...
*---- Global result ----
Number of choices:  22
Number of orbits :  11
Labelled representatives:
['a06', 'a04', 'a10', 'a05']
['a09', 'a07', 'a10', 'a04', 'a02']
['a06', 'a11', 'a12', 'a08', 'a03']
['a04', 'a01', 'a10', 'a05']
['a07', 'a02', 'a12', 'a03']
['a09', 'a11', 'a12', 'a07']
['a06', 'a04', 'a08', 'a05']
['a06', 'a04', 'a02', 'a10']
['a01', 'a11', 'a07', 'a03']
['a01', 'a11', 'a08', 'a03', 'a05']
['a09', 'a11', 'a12', 'a08']
Symmetry vector
stabilizer size  :  [1, 2]
frequency        :  [11, 0]
```

In our random 3-regular graph instance (see Fig. 34), we may thus find eleven non isomorphic kernels with orbit sizes equal to two. We illustrate below the isomorphic twin of the random MIS example shown in Fig. 35.

All graphs and symmetric digraphs admid MISs, hence also kernels.

It is worthwhile noticing that the **maximal matchings** of a graph correspond bijectively to its line graph's **kernels** (see the `graphs.LineGraph` class).



Fig. 36: *Two isomorphic kernels of the random 3-regular graph instance*

```
>>> from graphs import CycleGraph
>>> c8 = CycleGraph(order=8)
>>> maxMatching = c8.computeMaximumMatching()
>>> c8.exportGraphViz(fileName='maxMatchingcycleGraph',
...                          matching=maxMatching)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to maxMatchingcyleGraph.dot
Matching:  {frozenset({'v1', 'v2'}), frozenset({'v5', 'v6'}),
            frozenset({'v3', 'v4'}), frozenset({'v7', 'v8'}) }
circo -Tpng maxMatchingcyleGraph.dot -o maxMatchingcyleGraph.png
```



Fig. 37: *Perfect maximum matching in the 8-cycle graph*

In the context of digraphs, ie *oriented* graphs, the kernel concept gets much richer and separates from the symmetric MIS concept.

12.2 Initial and terminal kernels

In an oriented graph context, the internal stability condition of the kernel concept remains untouched; however, the externa

1. A **dominant** stability condition, where each non selected node is *dominated* by at least one member of the kernel;
2. An **absorbant** stability condition, where each non selected node is *absorbed* by at least one member of the kernel.

A both *internally* **and** *dominant*, resp. *absorbent stable* choice is called a *dominant* or **initial**, resp. an *absorbent* or **terminal** kernel. From a topological perspective, the initial kernel concept looks from the outside of the digraph into its interior, whereas the terminal kernel looks from the interior of a digraph toward its outside. From an algebraic perspective, the initial kernel is a *prefix* operand, and the terminal kernel is a *postfix* operand in the *Berge* kernel equation (see *[BIS-2006a]* (page 105))

Furthermore, as the kernel concept involves conjointly a **positive logical refutation** (the *internal stability*) and a **positive logical affirmation** (the *external stability*), it appeared rather quickly necessary in our operational developments to adopt a bipolar characteristic [-1,1] valuation domain, modelling *negation* by change of numerical sign and including explicitely a third **median** logical value (0) expressing logical **indeterminateness** (neither positive, nor negative, see *[BIS-2000]* (page 106) and *[BIS-2004]* (page 106)).

In such a bipolar valued context, we call **prekernel** a choice which is **externally stable** and for which the **internal stability** condition is **valid or indeterminate**. We say that the independence condition is in this case only **weakly** valiadated. Notice that all kernels are hence prekernels, but not vice-versa.

In graphs or symmetric digraphs, where there is essentially no apparent ' *laterality* ', all kernels are *initial* **and** *terminal* at the same time. They correspond to what we call *holes* in the graph. An *universal* example is given by the **complete** digraph.

```
>>> from digraphs import CompleteDigraph
>>> u = CompleteDigraph(order=5)
>>> u
*------- Digraph instance description ------*
Instance class   : CompleteDigraph
Instance name    : complete
Digraph Order      : 5
Digraph Size       : 20
Valuation domain : [-1.00 ; 1.00]
...
>>> u.showPreKernels()
*--- Computing preKernels ---*
Dominant kernels :
['1'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['2'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['3'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['4'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['5'] independence: 1.0; dominance : 1.0; absorbency : 1.0
Absorbent kernels :
['1'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['2'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['3'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['4'] independence: 1.0; dominance : 1.0; absorbency : 1.0
['5'] independence: 1.0; dominance : 1.0; absorbency : 1.0
*----- statistics -----
graph name:  complete
number of solutions
 dominant kernels :  5
 absorbent kernels:  5
cardinality frequency distributions
cardinality     :  [0, 1, 2, 3, 4, 5]
dominant kernel :  [0, 5, 0, 0, 0, 0]
absorbent kernel:  [0, 5, 0, 0, 0, 0]
```

```
Execution time  : 0.00004 sec.
Results in sets: dompreKernels and abspreKernels.
```

In a complete digraph, each single node is indeed both an initial and a terminal kernel candidate and there is no definite *begin* or *end* of the digraph to be detected. *Laterality* is here entirely *relative* to a specific singleton chosen as reference point of view. The same absence of laterality is apparent in two other universal digraph models, the **empty** and the **indeterminate** digraph.

```
>>> ed = EmptyDigraph(order=5)
>>> ed.showPreKernels()
*--- Computing preKernels ---*
Dominant kernel :
['1', '2', '3', '4', '5']
   independence :  1.0
   dominance    :  1.0
   absorbency   :  1.0
Absorbent kernel :
['1', '2', '3', '4', '5']
   independence :  1.0
   dominance    :  1.0
   absorbency   :  1.0
...
```

In the empty digraph, the whole set of nodes gives indeed at the same time the **unique** *initial* **and** *terminal* kernel. Similarly, for the **indeterminate** digraph.

```
>>> from digraphs import IndeterminateDigraph
>>> id = IndeterminateDigraph(order=5)
>>> id.showPreKernels()
*--- Computing preKernels ---*
Dominant prekernel :
['1', '2', '3', '4', '5']
   independence :  0.0   # <<== indeterminate
   dominance    :  1.0
   absorbency   :  1.0
Absorbent prekernel :
['1', '2', '3', '4', '5']
   independence :  0.0   # <<== indeterminate
   dominance    :  1.0
   absorbency   :  1.0
```

Both these results make sense, as in a completely empty or indeterminate digraph, there is no *interior* of the digraph defined, only a *border* which is hence at the same time an initial and terminal kernel. Notice however, that in the latter indeterminate case, the complete set of nodes verifies only weakly the internal stability condition (see above).

Other common digraph models, allthough being clearly oriented, may show nevertheless no apparent laterality, like **odd chordless circuits**, ie *holes* surrounded by an *oriented cycle* -a circuit- of odd length. They do not admit in fact any initial or terminal kernel.

```
>>> from digraphs import CirculantDigraph
>>> c5 = CirculantDigraph(order=5,circulants=[1])
>>> c5.showPreKernels()
*----- statistics -----
digraph name:  c5
number of solutions
 dominant prekernels :  0
 absorbent prekernels:  0
```

Chordless circuits of **even** length 2 x k, with $k > 1$, contain however two isomorphic kernels of cardinality k which qualify conjointly as initial and terminal candidates.

```
>>> c6 = CirculantDigraph(order=6,circulants=[1])
>>> c6.showPreKernels()
*--- Computing preKernels ---*
Dominant preKernels :
['1', '3', '5'] independence: 1.0, dominance: 1.0, absorbency: 1.0
['2', '4', '6'] independence: 1.0, dominance: 1.0, absorbency: 1.0
Absorbent preKernels :
['1', '3', '5'] independence: 1.0, dominance: 1.0, absorbency: 1.0
['2', '4', '6'] independence: 1.0, dominance: 1.0, absorbency: 1.0
```

Chordless circuits of even length may thus be indifferently oriented along two opposite directions. Notice by the way that the duals of **all** chordless circuits of *odd* **or** *even* length, ie *filled* circuits also called **anti-holes** (see Fig. 21), never contain any potential kernel candidates.

```
>>> dc6 = -c6    # dc6 = DualDigraph(c6)
>>> dc6.showPreKernels()
*----- statistics -----
graph name:  dual_c6
number of solutions
 dominant prekernels :  0
 absorbent prekernels:  0
>>> dc6.exportGraphViz(fileName='dualChordlessCircuit')
*---- exporting a dot file dor GraphViz tools ---------*
Exporting to dualChordlessCircuit.dot
circo -Tpng dualChordlessCircuit.dot -o dualChordlessCircuit.png
```



Fig. 38: *The dual of the chordless 6-circuit*

12.3 Kernels in lateralized digraphs

Humans are living in an apparent physical space of plain transitive **lateral orientation**, fully empowered in finite geometrical 3D models with **linear orders**, where first, resp. last ranked, nodes deliver unique initial, resp. terminal, kernels. Similarly, in finite **preorders**, the first, resp. last, equivalence classes deliver the unique initial, resp. unique terminal, kernels. More generally, in finite **partial orders**, ie asymmetric and transitive digraphs, topological sort algorithms will easily reveal on the first, resp. last, level all unique initial, resp. terminal, kernels.

In genuine random digraphs, however, we may need to check for each of its MISs, whether *one*, *both*, or *none* of

the lateralized external stability conditions may be satisfied. Consider, for instance, the following random digraph instance of order 7 and generated with an arc probability of 30%.

```
>>> from randomDigraphs import RandomDigraph
>>> rd = RandomDigraph(order=7,arcProbability=0.3,seed=5)
>>> rd.exportGraphViz('randomLatrality')
*---- exporting a dot file dor GraphViz tools ---------*
Exporting to randomLaterality.dot
dot -Grankdir=BT -Tpng randomLaterality.dot -o randomLaterality.png
```



Fig. 39: *A random digraph instance of order 7 and arc probability 0.3*

The random digraph shown in Fig. 39 above has no apparent special properties, except from being connected.

```
1 >>> rd.showComponents()
2 *--- Connected Components ---*
3 1: ['a1', 'a2', 'a3', 'a4', 'a5', 'a6', 'a7']
4 >>> rd.computeChordlessCircuits()
5 []                    # no chordless circuits detected
6 >>> print('Transitivity degree: %.2f%%' %\
7 ...                  (rd.computeTransitivityDegree()*100))
8 Transitivity degree: 48.39%
```

The given digraph instance is neither asymmetric (a3 <–> a6) nor symmetric (a2 –> a1, a1 -/> a2); there are no chordless circuits (see Line 5 above); and, the digraph is not transitive (a5 -> a2 -> a1, but a5 -/> a1). More than half of the required transitive closures are missing (see Line 8).

Now, we know that its potential prekernels must be among its set of maximal independent choices.

```
1  >>> rd.showMIS()
2  *---  Maximal independent choices ---*
3  ['a2', 'a4', 'a6']
4  ['a6', 'a1']
5  ['a5', 'a1']
6  ['a3', 'a1']
7  ['a4', 'a3']
8  ['a7']
9  ...
10 >>> rd.showPreKernels()
11 *--- Computing preKernels ---*
12 Dominant preKernels :
13 ['a2', 'a4', 'a6']
14    independence :  1.0
15    dominance    :  1.0
16    absorbency   :  -1.0
17    covering     :  0.500
18 ['a4', 'a3']
19    independence :  1.0
20    dominance    :  1.0
21    absorbency   :  -1.0
22    covering     :  0.600  # <<==
23 Absorbent preKernels :
24 ['a3', 'a1']
25    independence :  1.0
26    dominance    :  -1.0
27    absorbency   :  1.0
28    covering     :  0.500
29 ['a6', 'a1']
30    independence :  1.0
31    dominance    :  -1.0
32    absorbency   :  1.0
33    covering     :  0.600  # <<==
34 ...
```

Among the six MISs contained in this random digraph (see above Lines 3-8) we discover two initial and two terminal kernels (Lines 12-34). Notice by the way the covering values (between 0.0 and 1.0) shown by the `digraphs.Digraph.showPreKernels()` method (Lines 17, 22, 28 and 33). The higher this value, the more the corresponding kernel candidate makes apparent the digraph's *laterality*. We may hence redraw the same digraph in Fig. 40 by looking into its interior via the *best covering* initial kernel candidate: the dominant choice {'3','4'} (coloured in yellow), and looking out of it via the *best covered* terminal kernel candidate: the absorbent choice {'1','6'} (coloured in blue).

```
>>> rd.exportGraphViz(fileName='orientedLaterality',\
...                   bestChoice=set(['a4', 'a3']),\
...                   worstChoice=set(['a6', 'a1']))
*---- exporting a dot file dor GraphViz tools ---------*
Exporting to orientedLaterality.dot
dot -Grankdir=BT -Tpng orientedLaterality.dot -o orientedLaterality.png
```

In algorithmic decision theory, initial and terminal prekernels may provide convincing best, resp. worst, choice recommendations (see *Computing a best choice recommendation* (page 44)).

12.4 Computing good and bad choice recommendations

To illustrate this idea, let us finally compute good and bad choice recommendations in the following random bipolarly-valued **outranking** digraph.

```
>>> from outrankingDigraphs import *
>>> g = RandomBipolarOutrankingDigraph(seed=5)
```



Fig. 40: *A random digraph oriented by best covering initial and best covered terminal kernel*

```
>>> g
*------- Object instance description ------*
Instance class    : RandomBipolarOutrankingDigraph
Instance name     : randomOutranking
# Actions         : 7
# Criteria        : 7
Size              : 26
Determinateness   : 34.275
Valuation domain  : {'min': -100.0, 'med': 0.0, 'max': 100.0}
>>> g.showHTMLPerformanceTableau()
```

Performance table randomOutranking

criterion	g1	g2	g3	g4	g5	g6	g7
a1	64.90	1.31	13.88	98.24	94.10	14.57	31.00
a2	NA	NA	61.75	87.24	69.06	6.51	81.85
a3	11.32	27.95	12.67	28.93	96.66	30.14	48.07
a4	46.91	91.63	0.18	96.15	89.37	60.31	31.58
a5	NA	76.57	87.14	53.92	29.88	0.34	48.12
a6	54.38	15.96	20.95	67.78	36.12	67.79	70.47
a7	57.39	79.71	21.55	20.48	16.60	33.79	5.70

Fig. 41: *The performance tableau of a random outranking digraph instance*

The underlying random performance tableau (see Fig. 41) shows the performance grading of 7 potential decision

actions with respect to 7 decision criteria supporting each an increasing performance scale from 0 to 100. Notice the missing performance data concerning decision actions ‘a2’ and ‘a5’. The resulting **strict outranking** - ie a weighted majority supported - *better than without considerable counter-performance* - digraph is shown in Fig. 42 below.

```
>>> gcd = ~(-g)   # Codual: the converse of the negation
>>> gcd.exportGraphViz(fileName='tutOutRanking')
*---- exporting a dot file dor GraphViz tools ---------*
Exporting to tutOutranking.dot
dot -Grankdir=BT -Tpng tutOutranking.dot -o tutOutranking.png
```



Fig. 42: *A random strict outranking digraph instance*

All decision actions appear strictly better performing than action ‘a7’. We call it a **Condorcet looser** and it is an evident terminal prekernel candidate. On the other side, three actions: ‘a1’, ‘a2’ and ‘a4’ are not dominated. They give together an initial prekernel candidate.

```
1  >>> gcd.showPreKernels()
2  *--- Computing preKernels ---*
3  Dominant preKernels :
4  ['a1', 'a2', 'a4']
5     independence :  0.00
6     dominance    :  6.98
7     absorbency   :  -48.84
8     covering     :  0.667
9  Absorbent preKernels :
10 ['a3', 'a7']
11    independence :  0.00
12    dominance    :  -74.42
13    absorbency   :  16.28
14    covered      :  0.800
```

With such unique disjoint initial and terminal prekernels (see Line 4 and 10), the given digraph instance is hence

clearly *lateralized*. Indeed, these initial and terminal prekernels of the codual outranking digraph reveal best, resp. worst, choice recomendations one may formulate on the basis of a given outranking digraph instance.

```
>>> g.showRubisBestChoiceRecommendation()
***********************
Rubis best choice recommendation(s) (BCR)
 (in decreasing order of determinateness)
Credibility domain: [-100.00,100.00]
 === >> potential best choice(s)
* choice              : ['a1', 'a2', 'a4']
  +-irredundancy      : 0.00
  independence        : 0.00
  dominance           : 6.98
  absorbency          : -48.84
  covering (%)        : 66.67
  determinateness (%) : 57.97
  - most credible action(s) = { 'a4': 20.93, 'a2': 20.93, }
 === >> potential worst choice(s)
* choice              : ['a3', 'a7']
  +-irredundancy      : 0.00
  independence        : 0.00
  dominance           : -74.42
  absorbency          : 16.28
  covered (%)         : 80.00
  determinateness (%) : 64.62
  - most credible action(s) = { 'a7': 48.84, }
```

Notice that solving the valued *Berge* kernel equations (*[BIS-2006a]* (page 105)) provides furthermore a positive characterization of the most credible decision actions in each respective choice recommendation (see Lines 14 and 23 above). Actions 'a2' and 'a4' are equivalent candidates for a unique best choice, and action 'a7' is clearly confirmed as the worst choice.

In Fig. 43 below, we orient the drawing of the strict outranking digraph instance with the help of these best and worst choice recommendations.

```
>>> gcd.exportGraphViz(fileName='bestWorstOrientation',
...       bestChoice=['a2','a4'], worstChoice=['a7'])
*---- exporting a dot file dor GraphViz tools ---------*
Exporting to bestWorstOrientation.dot
dot -Grankdir=BT -Tpng bestWorstOrientation.dot -o bestWorstOrientation.png
```

The grey arrows in Fig. 43, like the one between actions 'a4' and 'a1', represent indeterminate preferential situations. Action 'a1' appears hence to be rather incomparable to all the other, except action 'a7'. It may be interesting to compare this result with a Copeland ranking of the underlying performance tableau (see *Ranking with multiple incommensurable criteria* (page 35)).

```
>>> g.showHTMLPerformanceHeatmap(colorLevels=5, ndigits=0,
...          Correlations=True, rankingRule='Copeland')
```

In the resulting linear ranking (see Fig. 44), action 'a4' is set at first rank, followed by action 'a2'. This makes sense as 'a4' shows three performances in the first quintile, whereas 'a2' is only partially evaluated and shows only two such excellent performances. But 'a4' also shows a very weak performance in the first quintile. Both decision actions, hence, don't show eventually a performance profile that would make apparent a clear preference situation in favour of one or the other. In this sense, the prekernels based best choice recommendations may appear more faithful with respect to the actually definite strict outranking relation than any 'forced' linear ranking result as shown in Fig. 27 above.

12.5 Tractability

Finally, let us give some hints on the **tractability** of kernel computations. Detecting all (pre)kernels in a digraph is a famously NP-hard computational problem. Checking external stability conditions for an independent choice



Fig. 43: *The strict outranking digraph oriented by its best and worst choice recommendations*

Heatmap of Performance Tableau 'randomOutranking'

criteria	g4	g7	g5	g6	g1	g2	g3
weights	9	10	6	5	4	8	1
tau(*)	+0.64	+0.40	+0.29	+0.17	+0.02	-0.05	-0.10
a4	96	32	89	60	47	92	0
a2	87	82	69	7	NA	NA	62
a6	68	70	36	68	54	16	21
a1	98	31	94	15	65	1	14
a5	54	48	30	0	NA	77	87
a3	29	48	97	30	11	28	13
a7	20	6	17	34	57	80	22

Color legend:

quantile	20.00%	40.00%	60.00%	80.00%	100.00%

(*) tau: *Ordinal (Kendall) correlation between marginal criterion and global ranking relation*
Ranking rule: **Copeland**
Ordinal (Kendall) correlation between global ranking and global outranking relation: **+0.848**

Fig. 44: *Heatmap with Copeland ranking of the peformance tableau*

is equivalent to checking its maximality and may be done in the linear complexity of the order of the digraph. However, checking all independent choices contained in a digraphs may get hard already for tiny sparse digraphs of order $n > 20$ (see *[BIS-2006b]* (page 105)). Indeed, the worst case is given by an empty or indeterminate digraph where the number of independent choices is indeed 2 to power n.

```
>>> e = EmptyDigraph(order=20)
>>> e.showMIS()    # by visiting all 2^20 independent choices
*---  Maximal independent choices ---*
[ '1',  '2',  '3',  '4',  '5',  '6',  '7',  '8',  '9', '10',
 '11', '12', '13', '14', '15', '16', '17', '18', '19', '20']
number of solutions:  1
execution time: 1.47640 sec.  # <<== !!!
```

Now, there exist more efficient specialized algorithms for directly enumerating MISs and dominant or absorbent kernels contained in specific digraph models without visiting all independent choices (see *[BIS-2006b]* (page 105)). Alain Hertz provided kindly such a MISs enumeration algorithm for the Digraph3 project (see `digraphs.Digraph.showMIS_AH()`). When the number of independent choices is big compared to the actual number of MISs, like in very sparse or empty digraphs, the performance difference may be dramatic.

```
>>> e.showMIS_AH()  # by visiting only maximal independent choices
*-----------------------------------*
* Python implementation of Hertz's  *
* algorithm for generating all MISs *
* R.B. version 7(6)-25-Apr-2006     *
*-----------------------------------*
===>>> Initial solution :
[ '1',  '2',  '3',  '4',  '5',  '6',  '7',  '8',  '9', '10',
 '11', '12', '13', '14', '15', '16', '17', '18', '19', '20']
*---- results ----*
[ '1',  '2',  '3',  '4',  '5',  '6',  '7',  '8',  '9', '10',
 '11', '12', '13', '14', '15', '16', '17', '18', '19', '20']
*---- statistics ----*
mis solutions    :  1
execution time   : 0.00026 sec. # <<== !!!
iteration history:  1
```

For more or less dense strict outranking digraphs of modest order, as facing usually in algorithmic decision theory applications, enumerating all independent choices remains however in most cases tractable, especially by using a very efficient Python generator (see `digraphs.Digraph.independentChoices()` below):

```
def independentChoices(self,U):
    """
    Generator for all independent choices with associated
    dominated, absorbed and independent neighborhoods
    of digraph instance self.
    Initiate with U = self.singletons().
    Yields [(independent choice, domnb, absnb, indnb)].
    """
    if U == []:
        yield [(frozenset(),set(),set(),set(self.actions))]
    else:
        x = list(U.pop())
        for S in self.independentChoices(U):
            yield S
            if x[0] <=  S[0][3]:
                Sxgamdom = S[0][1] | x[1]
                Sxgamabs = S[0][2] | x[2]
                Sxindep = S[0][3] &  x[3]
                Sxchoice = S[0][0] | x[0]
                Sx = [(Sxchoice,Sxgamdom,Sxgamabs,Sxindep)]
                yield Sx
```

And, checking maximality of independent choices via the external stability conditions during their emuneration

(see `digraphs.Digraph.computePreKernels()` below):

```
def computePreKernels(self):
    """
    computing dominant and absorbent preKernels:
    Result in self.dompreKernels and self.abspreKernels
    """
    actions = set(self.actions)
    n = len(actions)
    dompreKernels = set()
    abspreKernels = set()
    for choice in self.independentChoices(self.singletons()):
        restactions = actions - choice[0][0]
        if restactions <= choice[0][1]:
            dompreKernels.add(choice[0][0])
        if restactions <= choice[0][2]:
            abspreKernels.add(choice[0][0])
    self.dompreKernels = dompreKernels
    self.abspreKernels = abspreKernels
```

provides the effective advantage of computing all initial and/or terminal kernels in a single loop (see Line 10 and *[BIS-2006b]* (page 105)).

Back to *Tutorials of the Digraph3 resources* (page 3)

13 Abut permutation graphs

- *Permutation graphs* (page 92)
- *Properties of permutation graphs* (page 94)
- *Recognizing permutation graphs* (page 95)

13.1 Permutation graphs

A graph is called a **permutation** or *inversion* graph if there exists a permutation of its list of vertices such that the graph is isomorphic to the inversions operated by the permutation in this list.

Source: Martin Ch. Golumbic, Agorithmic Graph Theory and Perfect Graphs 2nd Ed., Annals of Discrete Mathematics 57, Elsevier, Chapter 7, pp 157-170.

```
>>> from graphs import PermutationGraph
>>> g = PermutationGraph(permutation = [4, 3, 6, 1, 5, 2])
>>> g
*------- Graph instance description ------*
Instance class   : PermutationGraph
Instance name    : permutationGraph
Graph Order      : 6
Permutation      : [4, 3, 6, 1, 5, 2]
Graph Size       : 9
Valuation domain : [-1.00; 1.00]
Attributes       : ['name', 'vertices', 'order', 'permutation',
                    'valuationDomain', 'edges', 'size', 'gamma']
>>> g.exportGraphViz()
*---- exporting a dot file for GraphViz tools ---------*
Exporting to permutationGraph.dot
fdp -Tpng permutationGraph.dot -o permutationGraph.png
```



Fig. 45: *The default permutation graph*

By using color sorting queues, the minimal vertex coloring for a permutation graph is computable in $O(nlog(n))$ (see *[GOL-2004]* (page 106)).

```
>>> g.computeMinimalVertexColoring(Comments=True)
vertex 1: lightcoral
vertex 2: lightcoral
vertex 3: lightblue
vertex 4: gold
vertex 5: lightblue
vertex 6: gold
>>> g.exportGraphViz(fileName='coloredPermutationGraph',\
...                  WithVertexColoring=True)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to coloredPermutationGraph.dot
fdp -Tpng coloredPermutationGraph.dot -o coloredPermutationGraph.png
```



Fig. 46: *Minimal vertex coloring of the permutation graph*

The correspondingly colored **matching diagram** of the nine **inversions** -the actual *edges* of the permutation graph-, which are induced by the given permutation [4, 3, 6, 1, 5, 2], may as well be drawn with the graphviz *neato* layout and explicitely positioned horizontal lists of vertices (see `graphs.Graph.exportPermutationGraphViz()`).

```
>>> g.exportPermutationGraphViz(WithEdgeColoring=True)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to perm_permutationGraph.dot
neato -n -Tpng perm_permutationGraph.dot -o perm_permutationGraph.png
```



Fig. 47: *Colored matching diagram of the permutation* [4, 3, 6, 1, 5, 2]

13.2 Properties of permutation graphs

A permutation graph is **transitively orientable**. The `graphs.PermutationGraph.transitiveOrientation()` method renders a digraph where each edge of the permutation graph is converted into an arc oriented in increasing alphabetic order of the adjacent vertices' keys (see *[GOL-2004]* (page 106)).

Following from the permutation graph construction, this orientation is always transitive and delivers a *weak ordering* of the vertices.

```
>>> dg = g.transitiveOrientation()
>>> dg
*------- Digraph instance description ------*
Instance class   : WeakOrder
Instance name    : oriented_permutationGraph
Digraph Order      : 6
Digraph Size       : 9
Valuation domain : [-1.00; 1.00]
Determinateness  : 100.000
Attributes       : ['name', 'order', 'actions', 'valuationdomain',
                    'relation', 'gamma', 'notGamma', 'size']
>>> print('Transitivity degree: %.3f' % dg.computeTransitivityDegree() )
Transitivity degree: 1.000
>>> dg.exportGraphViz()
*---- exporting a dot file for GraphViz tools ---------*
Exporting to oriented_permutationGraph.dot
0 { rank = same; 1; 2; }
1 { rank = same; 5; 3; }
2 { rank = same; 4; 6; }
dot -Grankdir=TB -Tpng oriented_permutationGraph.dot -o oriented_permutationGraph.
↪png
```

The dual of a permutation graph is *again* a permutation graph and as such also transitively orientable. Now, a given graph *g* is a permutation graph **if and only if** both *g* **and** *gd* = -*g* are *transitively orientable*.

```
>>> gd = -g
>>> dgd = gd.transitiveOrientation()
>>> print('Dual transitivity degree: %.3f' %\
...             dgd.computeTransitivityDegree() )
Dual transitivity degree: 1.000
```



Fig. 48: *Hasse diagram of the transitive orientation of the permutation graph*

13.3 Recognizing permutation graphs

The last property gives a polynomial test procedure (in $O(n^3)$ due to the transitivity check) for recognizing permutation graphs. Let us consider, for instance, the following random graph of *order* 8 generated with an *edge probability* of 40% and a *random seed* equal to 4335.

```
>>> from graphs import *
>>> g = RandomGraph(order=8,edgeProbability=0.4,seed=4335)
>>> g
*------- Graph instance description ------*
Instance class    : RandomGraph
Instance name     : randomGraph
Seed              : 4335
Edge probability  : 0.4
Graph Order       : 8
Graph Size        : 10
Valuation domain  : [-1.00; 1.00]
Attributes        : ['name', 'order', 'vertices', 'valuationDomain', 'seed',
                     'edges', 'size', 'gamma', 'edgeProbability']
>>> g.exportGraphViz()
```

If the graph instance *g* is a permutation graph, *g* and its dual *dg* = -*g* must be *transitively orientable*, ie **comparability graphs** (see *[GOL-2004]* (page 106)). With the `graphs.Graph.isComparabilityGraph()` test, we may easily check this fact. This method proceeds indeed by trying to construct a ranked implication class decomposition of a given graph instance and, if successful, stores the ranked edge orientations into the *self.edgeRanks* attribute (see *[GOL-2004]* (page 106) p.129-132).

```
>>> print(g.isComparabilityGraph())
True
>>> gd = -g
>>> print(gd.isComparabilityGraph())
True
```

Let us recheck this fact by explicitely constructing transitively oriented digraph instances with the `graphs.Graph.computeTranditivelyOrientedDigraph()` method.

```
>>> og = g.computeTransitivelyOrientedDigraph(PartiallyDetermined=True)
>>> print('Transitivity degree: %.3f' % (og.transitivityDegree))
```



Fig. 49: *Random graph of order 8 generated with edge probility 0.4*

```
3  Transitivity degree: 1.000
4  >>> ogd = gd.computeTransitivelyOrientedDigraph(PartiallyDetermined=True)
5  >>> print('Transitivity degree: %.3f' % (ogd.transitivityDegree))
6  Transitivity degree: 1.000
```

The `PartiallyDetermined=True` flag (see Lines 1 and 5) is required here in order to orient *only* the actual edges of the graphs. Relations between vertices not linked by an edge will be put to the *indeterminate* characteristic value 0. This will allow us to compute later on convenient disjunctive digraph fusions.

As both graphs are indeed transitively orientable (see Lines 3 and 6 above), we may conclude that the given random graph is actally a *permutation graph* instance. Yet, we still need to find now its corresponding *permutation*. We therefore implement a recipee given by Martin Golumbic *[GOL-2004]* (page 106) p.159.

We will first **fuse** both *og* and *ogd* orientations above with an **epistemic disjunction** (see the `digraphsTools.omax()` operator), hence, the partially determined orientations requested above.

```
1  >>> from digraphs import FusionDigraph
2  >>> f1 = FusionDigraph(og,ogd,operator='o-max')
3  >>> s1 = f1.computeCopelandRanking()
4  >>> print(s1)
5  ['v5', 'v7', 'v1', 'v6', 'v8', 'v4', 'v3', 'v2']
```

We obtain by the *Copeland* ranking rule (see *Ranking with multiple incommensurable criteria* (page 35) and the `digraphs.Digraph.computeCopelandRanking()` method) a complete linear ordering of the vertices (see Line 5 above).

We reverse now the orientation of the edges in *og* (see *-og* in Line 1 below) in order to generate, again by disjunctive fusion, the *inversions* that are produced by the permutation we are looking for. Computing again a ranking with the *Copeland* rule, will show the correspondingly permuted list of vertices (see Line 4 below).

```
1  >>> f2 = FusionDigraph((-og),ogd,operator='o-max')
2  >>> s2 = f2.computeCopelandRanking()
3  >>> print(s2)
4  ['v8', 'v7', 'v6', 'v5', 'v4', 'v3', 'v2', 'v1']
```

Vertex ‘v8’ is put from position 5 to position 1, vertex ‘v7’ is put from position 2 to position 2, vertex ‘v6’ from

position 4 to position 3, 'vertex 'v5' from position 1 to position 4, etc . . . . We generate these position swaps for all vertices and obtain thus the required permutation (see Line 5 below).

```
>>> permutation = [0 for j in range(g.order)]
>>> for j in range(g.order):
...     permutation[s2.index(s1[j])] = j+1
>>> print(permutation)
[5, 2, 4, 1, 6, 7, 8, 3]
```

It is worthwhile noticing by the way that *transitive orientations* of a given graph and its dual are usually **not unique** and, so may also be the resulting permutations. However, they all correspond to isomorphic graphs (see *[GOL-2004]* (page 106)). In our case here, we observe two different permutations and their reverses:

```
s1: ['v1', 'v4', 'v3', 'v2', 'v5', 'v6', 'v7', 'v8']
s2: ['v4', 'v3', 'v2', 'v8', 'v6', 'v1', 'v7', 'v5']
(s1 -> s2): [2, 3, 4, 8, 6, 1, 7, 5]
(s2 -> s1): [6, 1, 2, 3, 8, 5, 7, 4]
```

And:

```
s3: ['v5', 'v7', 'v1', 'v6', 'v8', 'v4', 'v3', 'v2']
s4: ['v8', 'v7', 'v6', 'v5', 'v4', 'v3', 'v2', 'v1']
(s3 -> s4): [5, 2, 4, 1, 6, 7, 8, 3]
(s4 -> s3) = [4, 2, 8, 3, 1, 5, 6, 7]
```

The `graphs.Graph.computePermutation()` method does directly operate all these steps: - computing transitive orientations, - ranking their epistemic fusion and, - delivering a corresponding permutation.

```
>>> g.computePermutation()
['v1', 'v2', 'v3', 'v4', 'v5', 'v6', 'v7', 'v8']
['v2', 'v3', 'v4', 'v8', 'v6', 'v1', 'v7', 'v5']
[2, 3, 4, 8, 6, 1, 7, 5]
```

We may finally check that the permutations [2, 3, 4, 8, 6, 1, 7, 5] and [4, 2, 8, 3, 1, 5, 6, 7], we have generated above, will correctly generate corresponding isomorphic permutation graphs.

```
>>> gtesta = PermutationGraph(permutation=[2, 3, 4, 8, 6, 1, 7, 5])
>>> gtestb = PermutationGraph(permutation=[4, 2, 8, 3, 1, 5, 6, 7])
>>> gtesta.exportGraphViz('gtesta')
>>> gtestb.exportGraphViz('gtesta')
```

And, we recover indeed two *isomorphic copies* of the original random graph (see Fig. 49).

Back to *Tutorials of the Digraph3 resources* (page 3)

14 On tree graphs and graph forests

- *Generating random tree graphs* (page 97)
- *Recognizing tree graphs* (page 100)
- *Spanning trees and forests* (page 102)
- *Maximum determined spanning forests* (page 103)

14.1 Generating random tree graphs

Using the `graphs.RandomTree` class, we may, for instance, generate a random tree graph with 9 vertices.



Fig. 50: *Isomorphic permutation graphs*

```
1  >>> t = RandomTree(order=9,seed=100)
2  >>> t
3  *------- Graph instance description ------*
4  Instance class   : RandomTree
5  Instance name    : randomTree
6  Graph Order      : 9
7  Graph Size       : 8
8  Valuation domain : [-1.00; 1.00]
9  Attributes       : ['name', 'order', 'vertices', 'valuationDomain',
10                     'edges', 'prueferCode', 'size', 'gamma']
11 *---- RandomTree specific data ----*
12 Prüfer code  : ['v3', 'v8', 'v8', 'v3', 'v7', 'v6', 'v7']
13 >>> t.exportGraphViz('tutRandomTree')
14 *---- exporting a dot file for GraphViz tools ---------*
15 Exporting to tutRandomTree.dot
16 neato -Tpng tutRandomTree.dot -o tutRandomTree.png
```

A tree graph of order *n* contains *n-1* edges (see Line 8 and 9) and we may distinguish vertices like *v1*, *v2*, *v4*, *v5* or *v9* of degree 1, called the **leaves** of the tree, and vertices like *v3*, *v6*, *v7* or *v8* of degree 2 or more, called the **nodes** of the tree.

The structure of a tree of order $n > 2$ is entirely characterized by a corresponding *Prüfer* **code** -ie a *list of vertices keys*- of length *n-2*. See, for instance in Line 12 the code ['v3', 'v8', 'v8', 'v3', 'v7', 'v6', 'v7'] corresponding to our sample tree graph *t*.

Each position of the code indicates the parent of the remaining leaf with the smallest vertex label. Vertex *v3* is thus the parent of *v1* and we drop leaf *v1*, *v8* is now the parent of leaf *v2* and we drop *v2*, vertex *v8* is again the parent of leaf *v4* and we drop *v4*, vertex *v3* is the parent of leaf *v5* and we drop *v5*, *v7* is now the parent of leaf *v3* and we may drop *v3*, *v6* becomes the parent of leaf *v8* and we drop *v8*, *v7* becomes now the parent of leaf *v6* and we may drop *v6*. The two eventually remaining vertices, *v7* and *v9*, give the last link in the reconstructed tree (see *[BAR-1991]* (page 106)).

It is as well possible to first, generate a random *Prüfer* code of length *n-2* from a set of *n* vertices and then, construct the corresponding tree of order *n* by reversing the procedure illustrated above (see *[BAR-1991]* (page 106)).

```
>>> verticesList = ['v1','v2','v3','v4','v5','v6','v7']
>>> n = len(verticesList)
>>> from random import seed, choice
```



Fig. 51: *Random Tree instance of order* 9

```
>>> seed(101)
>>> code = []
>>> for k in range(n-2):
...     code.append( choice(verticesList) )
>>> print(code)
['v5', 'v7', 'v2', 'v5', 'v3']
>>> t = RandomTree(prueferCode=['v5', 'v7', 'v2', 'v5', 'v3'])
>>> t
*------- Graph instance description ------*
Instance class   : RandomTree
Instance name    : randomTree
Graph Order      : 7
Graph Size       : 6
Valuation domain : [-1.00; 1.00]
Attributes       : ['name', 'order', 'vertices', 'valuationDomain',
                    'edges', 'prueferCode', 'size', 'gamma']
*---- RandomTree specific data ----*
Prüfer code  : ['v5', 'v7', 'v2', 'v5', 'v3']
>>> t.exportGraphViz('tutPruefTree')
*---- exporting a dot file for GraphViz tools ---------*
Exporting to tutPruefTree.dot
neato -Tpng tutPruefTree.dot -o tutPruefTree.png
```



Fig. 52: *Tree instance from a random Prüfer code*

Following from the bijection between a labelled tree and its *Prüfer* code, we actually know that there exist n^{n-2} different tree graphs with the same n vertices.

Given a genuine graph, how can we recognize that it is in fact a tree instance ?

14.2 Recognizing tree graphs

Given a graph g of order n and size s, the following 5 assertions *A1*, *A2*, *A3*, *A4* and *A5* are all equivalent (see *[BAR-1991]* (page 106)):

- *A1*: g is a tree;
- *A2*: g is without (chordless) cycles and $n = s + 1$;
- *A3*: g is connected and $n = s + 1$;

- *A4*: Any two vertices of g are always connected by a *unique path*;
- *A5*: g is connected and *dropping* any single edge will always disconnect g.

Assertion *A3*, for instance, gives a simple test for recognizing a tree graph. In case of a *lazy evaluation* of the test in Line 3 below, it is opportune, from a computational complexity perspective, to first, check the order and size of the graph, before checking its potential connectedness.

```
1 >>> from graphs import RandomGraph
2 >>> g = RandomGraph(order=6,edgeProbability=0.3,seed=62)
3 >>> if g.order == (g.size +1) and g.isConnected():
4 ...     print('The graph is a tree ?', True)
5 ... else:
6 ...     print('The graph is a tree ?',False)
7 ...
8 The graph is a tree ? True
```

The random graph of order 6 and edge probability 30%, generated with seed 62, is actually a tree graph instance, as we may readily confirm from its *graphviz* drawing in Fig. 36 (see also the `graphs.Graph.isTree()` method for an implemented alternative test).

```
1 >>> g.exportGraphViz(
2 *---- exporting a dot file for GraphViz tools ---------*
3 Exporting to test62.dot
4 fdp -Tpng test62.dot -o test62.png
```



Fig. 53: *Recognizing a tree instance*

Yet, we still have to recover its corresponding *Prüfer* code. Therefore, we may use the `graphs.RandomTree.tree2Pruefer()` method.

```
1 >>> from graphs import RandomGraph
2 >>> RandomTree.tree2Pruefer(g)
3 ['v6', 'v1', 'v2', 'v1', 'v2', 'v5']
```

Let us now turn toward a major application of tree graphs, namely *spanning trees* and *forests* related to graph traversals.

14.3 Spanning trees and forests

With the `graphs.RandomSpanningTree` class we may generate, from a given **connected** graph *g* instance, **uniform random** instances of a **spanning tree** by using *Wilson* 's algorithm *[WIL-1996]* (page 106)

Note: Wilson's algorithm *only* works for connected graphs[4].

```
>>> from graphs import *
>>> g = RandomGraph(order=9,edgeProbability=0.4,seed=100)
>>> spt = RandomSpanningTree(g)
>>> spt
*------- Graph instance description ------*
Instance class    : RandomSpanningTree
Instance name     : randomGraph_randomSpanningTree
Graph Order       : 9
Graph Size        : 8
Valuation domain : [-1.00; 1.00]
Attributes        : ['name','vertices','order','valuationDomain','edges',
                     'size','gamma','dfs','date','dfsx','prueferCode']
*---- RandomTree specific data ----*
Prüfer code  : ['v7', 'v9', 'v5', 'v1', 'v8', 'v4', 'v9']
>>> spt.exportGraphViz(fileName='randomSpanningTree',\
...                    WithSpanningTree=True)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to randomSpanningTree.dot
[['v1', 'v5', 'v6', 'v5', 'v1', 'v8', 'v9', 'v3', 'v9', 'v4',
  'v7', 'v2', 'v7', 'v4', 'v9', 'v8', 'v1']]
neato -Tpng randomSpanningTree.dot -o randomSpanningTree.png
```



Fig. 54: *Random spanning tree*

More general, and in case of a not connected graph, we may generate with the `graphs.RandomSpanningForest` class a *not necessarily uniform* random instance of a **spanning forest** -one or more random tree graphs- generated from a **random depth first search** of the graph components' traversals.

```
>>> g = RandomGraph(order=15,edgeProbability=0.1,seed=140)
>>> g.computeComponents()
[{'v12', 'v01', 'v13'}, {'v02', 'v06'},
 {'v08', 'v03', 'v07'}, {'v15', 'v11', 'v10', 'v04', 'v05'},
 {'v09', 'v14'}]
```

[4] *Wilson* 's algorithm uses *loop-erased random walks*. See https://en.wikipedia.org/wiki/Loop-erased_random_walk .

```
>>> spf = RandomSpanningForest(g,seed=100)
>>> spf.exportGraphViz(fileName='spanningForest',WithSpanningTree=True)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to spanningForest.dot
[['v03', 'v07', 'v08', 'v07', 'v03'],
 ['v13', 'v12', 'v13', 'v01', 'v13'],
 ['v02', 'v06', 'v02'],
 ['v15', 'v11', 'v04', 'v11', 'v15', 'v10', 'v05', 'v10', 'v15'],
 ['v09', 'v14', 'v09']]
neato -Tpng spanningForest.dot -o spanningForest.png
```



Fig. 55: *Random spanning forest instance*

14.4 Maximum determined spanning forests

In case of valued graphs supporting weighted edges, we may finally construct a **most determined** spanning tree (or forest if not connected) using *Kruskal* 's *greedy* **minimum-spanning-tree algorithm**[5] on the *dual* valuation of the graph *[KRU-1956]* (page 106).

We consider, for instance, a randomly valued graph with five vertices and seven edges bipolarly valued in [-1.0; 1.0].

```
1  >>> from graphs import *
2  >>> g = RandomValuationGraph(seed=2)
3  >>> g
4  *------- Graph instance description ------*
5  Instance class    : RandomValuationGraph
6  Instance name     : randomGraph
7  Graph Order       : 5
8  Graph Size        : 7
9  Valuation domain  : [-1.00; 1.00]
10 Attributes        : ['name', 'order', 'vertices', 'valuationDomain',
11                      'edges', 'size', 'gamma']
```

To inspect the edges' actual weights, we first transform the graph into a corresponding digraph (see Line 1 below) and use the `digraphs.Digraph.showRelationTable()` method (see Line 2 below) for printing its **symmetric adjacency matrix**.

[5] *Kruskal* 's algorithm is a *minimum-spanning-tree* algorithm which finds an edge of the least possible weight that connects any two trees in the forest. See https://en.wikipedia.org/wiki/Kruskal%27s_algorithm .

```
>>> dg = g.graph2Digraph()
>>> dg.showRelationTable()
* ---- Relation Table -----
  S    |  'v1'     'v2'    'v3'    'v4'    'v5'
------|-----------------------------------------
 'v1' |  0.00    0.91    0.90    -0.89   -0.83
 'v2' |  0.91    0.00    0.67     0.47    0.34
 'v3' |  0.90    0.67    0.00    -0.38    0.21
 'v4' | -0.89    0.47   -0.38     0.00    0.21
 'v5' | -0.83    0.34    0.21     0.21    0.00
Valuation domain: [-1.00;1.00]
```

To compute the most determined spanning tree or forest, we may use the `graphs.BestDeterminedSpanningForest` class constructor.

```
>>> mt = BestDeterminedSpanningForest(g)
>>> mt
*------- Graph instance description ------*
Instance class    : BestDeterminedSpanningForest
Instance name     : randomGraph_randomSpanningForest
Graph Order       : 5
Graph Size        : 4
Valuation domain : [-1.00; 1.00]
Attributes        : ['name', 'vertices', 'order', 'valuationDomain', 'edges',
                     'size', 'gamma', 'dfs', 'date', 'averageTreeDetermination']
*---- best determined spanning tree specific data ----*
Depth first search path(s) :
[['v1', 'v2', 'v4', 'v2', 'v5', 'v2', 'v1', 'v3', 'v1']]
Average determination(s) : [Decimal('0.655')]
```

The given graph is connected and, hence, admids a single spanning tree (see Fig. 39) of **maximum mean determination** = (0.47 + 0.91 + 0.90 + 0.34)/4 = **0.655** (see Lines 9, 6 and 10 in the relation table above).

```
>>> mt.exportGraphViz(fileName='bestDeterminedspanningTree',\
...                   WithSpanningTree=True)
*---- exporting a dot file for GraphViz tools ---------*
Exporting to spanningTree.dot
[['v4', 'v2', 'v1', 'v3', 'v1', 'v2', 'v5', 'v2', 'v4']]
neato -Tpng bestDeterminedSpanningTree.dot -o bestDeterminedSpanningTree.png
```



Fig. 56: *Best determined spanning tree*

One may easily verify that all other potential spanning trees, including instead the edges {*v3*, *v5*} and/or {*v4*, *v5*} - will show a lower average determination.

Back to *Tutorials of the Digraph3 resources* (page 3)

15 Links and appendices

15.1 References

15.2 Footnotes

References

[CPSTAT-L5] 18. Bisdorff (2017) *Simulating from abitrary empirical random distributions*. MICS Computational Statistics course, Lecture 5. FSTC/ILIAS University of Luxembourg, Winterr Semester 2017 (PDF 2x2 reduced presentation slides 211kB downloadable here)

[BIS-2016] 18. Bisdorff (2016). *On linear ranking from trillions of pairwise outranking situations*. Research Note 16-1, FSTC/ILIAS Decision Systems Group, University of Luxembourg pp. 1-6 (dowloadable PDF file 625.3 kB (https://leopold-loewenheim.uni.lu/bisdorff/documents/DA2PL-RB.pdf))

[ADT-L2] 18. Bisdorff (2014) *Who wins the election*? MICS Algorithmic Decision Theory course, Lecture 2. FSTC/ILIAS University of Luxembourg, Summer Semester 2014 (PDF 2x2 reduced presentation slides 195 kB downloadable here)

[ADT-L7] 18. Bisdorff (2014) *Best multiple criteria choice: the Rubis outranking method*. MICS Algorithmic Decision Theory course, Lecture 7. FSTC/ILIAS University of Luxembourg, Summer Semester 2014 (PDF 2x2 reduced slides 310kB downloadable here)

[BIS-2013] 18. Bisdorff (2013) "On Polarizing Outranking Relations with Large Performance Differences" *Journal of Multi-Criteria Decision Analysis* (Wiley) **20**:3-12 (downloadable preprint PDF file 403.5 Kb (https://leopold-loewenheim.uni.lu/bisdorff/documents/MCDA-10-0059-PrePeerReview.pdf))

[BIS-2012] 18. Bisdorff (2012). "On measuring and testing the ordinal correlation between bipolar outranking relations". In Proceedings of DA2PL'2012 *From Multiple Criteria Decision Aid to Preference Learning*, University of Mons 91-100. (downloadable preliminary version PDF file 408.5 kB (https://leopold-loewenheim.uni.lu/bisdorff/documents/DA2PL-RBisdorffMons.pdf))

[BIS-2008] 18. Bisdorff, P. Meyer and M. Roubens (2008) "RUBIS: a bipolar-valued outranking method for the choice problem". 4OR, *A Quarterly Journal of Operations Research* Springer-Verlag, Volume 6, Number 2 pp. 143-165. (Online) Electronic version: DOI: 10.1007/s10288-007-0045-5 (downloadable preliminary version PDF file 271.5Kb (https://leopold-loewenheim.uni.lu/bisdorff/documents/HyperKernels.pdf))

[ISOMIS-08] 18. Bisdorff and J.L. Marichal (2008). Counting non-isomorphic maximal independent sets of the n-cycle graph. *Journal of Integer Sequences*, Vol. 11 Article 08.5.7 (openly accessible here (https://www.cs.uwaterloo.ca/journals/JIS/VOL11/Marichal/marichal.html))

[NR3-2007] W.H. Press, S.A. Teukolsky, W.T. Vetterling and B.P. Flannery (2007) "Single-Pass Estimation of Arbitrary Quantiles" Section 5.8.2 in *Numerical Recipes: The Art of Scientific Computing 3rd Ed.*, Cambridge University Press, pp 435-438.

[CHAM-2006] J.M. Chambers, D.A. James, D. Lambert and S. Vander Wiel (2006) "Monitoring Networked Applications with Incremental Quantile Estimation". *Statistical Science*, Vol. 21, No.4, pp.463-475. DOI: 10 12140/088342306000000583.

[BIS-2006a] 18. Bisdorff, M. Pirlot and M. Roubens (2006). "Choices and kernels from bipolar valued digraphs". *European Journal of Operational Research*, 175 (2006) 155-170. (Online) Electronic version: DOI:10.1016/j.ejor.2005.05.004 (downloadable preliminary version PDF file 257.3Kb (https://sma.uni.lu/bisdorff/documents/BisdorffPirlotRoubens05.pdf))

[BIS-2006b] 18. Bisdorff (2006). On enumerating the kernels in a bipolar-valued digraph. Annales du Lamsade 6, Octobre 2006, pp. 1 - 38. Université Paris-Dauphine. ISSN 1762-455X (downloadable version PDF file 532.2 Kb (https://leopold-loewenheim.uni.lu/bisdorff/documents/EnumKernels.pdf)).

[BIS-2004] 18. Bisdorff (2004) *On a natural fuzzification of Boolean logic*. In Erich Peter Klement and Endre Pap (editors), Proceedings of the 25th Linz Seminar on *Fuzzy Set Theory, Mathematics of Fuzzy Systems*. Bildungszentrum St. Magdalena, Linz (Austria), February 2004. pp. 20-26 (PDF file (133.4 Kb) for downloading)

[GOL-2004] 13. Ch. Golumbic, *Agorithmic Graph Theory and Perfect Graphs* 2nd Ed., Annals of Discrete Mathematics 57, Elsevier.

[FMCAA] 15. Häggström (2002) *Finite Markov Chains and Algorithmic Applications*. Cambridge University Press.

[BIS-2000] 18. Bisdorff (2000), Logical foundation of fuzzy preferential systems with application to the ELECTRE decision aid methods, *Computers and Operations Research*, 27:673-687 (downloadable version PDF file 159.1Kb (https://leopold-loewenheim.uni.lu/bisdorff/documents/foundationElectre.pdf)).

[WIL-1996] 4. (a) Wilson (1996), *Generating random spanning trees more quickly than the cover time*, Proceedings of the Twenty-eighth Annual ACM *Symposium on the Theory of Computing* (Philadelphia, PA, 1996), 296-303, ACM, New York, 1996.

[BAR-1991] J.-P. Barthélemy and A. Guenoche (1991), *Trees and Proximities Representations*, Wiley, ISBN: 978-0471922636.

[KRU-1956] 10. (a) Kruskal (1956), *On the shortest spanning subtree of a graph and the traveling salesman problem*, Proceedings of the American Mathematical Society. 7: 48–50.