

On weakly ordering by choosing from valued pairwise outranking situations

Raymond Bisdorff

Université du Luxembourg
FSTC/ILAS

ORBEL 28, Mons, January 2014

Content

1. Illustration

Sample outranking relation

Ranking-by-choosing

Partial ranking result

2. The setting

Weakly complete relations

The Rubis choice procedure

Properties

3. Ranking-by-choosing

Algorithm

Properties

Empirical Validation

○○
○○
○

○○○○
○○○
○○

○
○○○
○○○○○

1. Illustration

Sample outranking relation

Ranking-by-choosing

Partial ranking result

2. The setting

Weakly complete relations

The Rubis choice procedure

Properties

3. Ranking-by-choosing

Algorithm

Properties

Empirical Validation



Sample performance tableau

Let $X = \{a_1, \dots, a_7\}$ be seven potential decision actions evaluated on three cost criteria (g_1, g_4, g_5) of equi-significance $1/6$ and two benefit criteria (g_2, g_3) of equi-significance $1/4$. The given performance tableau is shown below.

Objectives	Costs			Benefits	
Criteria	$g_1(\downarrow)$	$g_4(\downarrow)$	$g_5(\downarrow)$	$g_2(\uparrow)$	$g_3(\uparrow)$
weights×12	2.0	2.0	2.0	3.0	3.0
indifference	3.41	4.91	-	-	2.32
preference	6.31	8.31	-	-	5.06
veto	60.17	67.75	-	-	48.24
a_1	22.49	36.84	7	8	43.44
a_2	16.18	19.21	2	8	19.35
a_3	29.41	54.43	3	4	33.37
a_4	82.66	86.96	8	6	48.50
a_5	47.77	82.27	7	7	81.61
a_6	32.50	16.56	6	8	34.06
a_7	35.91	27.52	2	1	50.82



Sample performance tableau

Let $X = \{a_1, \dots, a_7\}$ be seven potential decision actions evaluated on three cost criteria (g_1, g_4, g_5) of equi-significance $1/6$ and two benefit criteria (g_2, g_3) of equi-significance $1/4$. The given performance tableau is shown below.

Objectives	Costs			Benefits	
Criteria	$g_1(\downarrow)$	$g_4(\downarrow)$	$g_5(\downarrow)$	$g_2(\uparrow)$	$g_3(\uparrow)$
weights $\times 12$	2.0	2.0	2.0	3.0	3.0
indifference	3.41	4.91	-	-	2.32
preference	6.31	8.31	-	-	5.06
veto	60.17	67.75	-	-	48.24
a_1	22.49	36.84	7	8	43.44
a_2	16.18	19.21	2	8	19.35
a_3	29.41	54.43	3	4	33.37
a_4	82.66	86.96	8	6	48.50
a_5	47.77	82.27	7	7	81.61
a_6	32.50	16.56	6	8	34.06
a_7	35.91	27.52	2	1	50.82



Sample performance tableau

Let $X = \{a_1, \dots, a_7\}$ be seven potential decision actions evaluated on three cost criteria (g_1, g_4, g_5) of equi-significance $1/6$ and two benefit criteria (g_2, g_3) of equi-significance $1/4$. The given performance tableau is shown below.

Objectives	Costs			Benefits	
Criteria	$g_1(\downarrow)$	$g_4(\downarrow)$	$g_5(\downarrow)$	$g_2(\uparrow)$	$g_3(\uparrow)$
weights \times 12	2.0	2.0	2.0	3.0	3.0
indifference	3.41	4.91	-	-	2.32
preference	6.31	8.31	-	-	5.06
veto	60.17	67.75	-	-	48.24
a_1	22.49	36.84	7	8	43.44
a_2	16.18	19.21	2	8	19.35
a_3	29.41	54.43	3	4	33.37
a_4	82.66	86.96	8	6	48.50
a_5	47.77	82.27	7	7	81.61
a_6	32.50	16.56	6	8	34.06
a_7	35.91	27.52	2	1	50.82



Sample outranking relation

The resulting bipolar outranking relation S is shown below.

Table : r -valued bipolar outranking relation

$r(S) \times 12$	a_1	a_2	a_3	a_4	a_5	a_6	a_7
a_1	—	0	+8	+12	+6	+4	−2
a_2	+6	—	+6	+12	0	+6	+6
a_3	−8	−6	—	0	−12	+2	−2
a_4	−12	−12	0	—	−8	−12	0
a_5	−2	0	+12	+12	—	−6	0
a_6	+2	+4	+8	+12	+6	—	+2
a_7	+2	−2	+2	+6	0	+2	—

1. a_6 is a Condorcet winner,
2. a_2 is a weak Condorcet winner,
3. a_4 is a weak Condorcet loser.



Sample outranking relation

The resulting bipolar outranking relation S is shown below.

Table : r -valued bipolar outranking relation

$r(S) \times 12$	a_1	a_2	a_3	a_4	a_5	a_6	a_7
a_1	—	0	+8	+12	+6	+4	−2
a_2	+6	—	+6	+12	0	+6	+6
a_3	−8	−6	—	0	−12	+2	−2
a_4	−12	−12	0	—	−8	−12	0
a_5	−2	0	+12	+12	—	−6	0
a_6	+2	+4	+8	+12	+6	—	+2
a_7	+2	−2	+2	+6	0	+2	—

1. a_6 is a **Condorcet winner**,
2. a_2 is a weak Condorcet winner,
3. a_4 is a weak Condorcet loser.



Sample outranking relation

The resulting bipolar outranking relation S is shown below.

Table : r -valued bipolar outranking relation

$r(S) \times 12$	a_1	a_2	a_3	a_4	a_5	a_6	a_7
a_1	—	0	+8	+12	+6	+4	−2
a_2	+ 6	—	+ 6	+ 12	0	+ 6	+ 6
a_3	−8	−6	—	0	−12	+2	−2
a_4	− 12	− 12	0	—	− 8	− 12	0
a_5	−2	0	+12	+12	—	−6	0
a_6	+ 2	+ 4	+ 8	+ 12	+ 6	—	+ 2
a_7	+2	−2	+2	+6	0	+2	—

1. a_6 is a Condorcet winner,
2. a_2 is a **weak** Condorcet winner,
3. a_4 is a weak Condorcet loser.



Sample outranking relation

The resulting bipolar outranking relation S is shown below.

Table : r -valued bipolar outranking relation

$r(S) \times 12$	a_1	a_2	a_3	a_4	a_5	a_6	a_7
a_1	—	0	+8	+12	+6	+4	−2
a_2	+6	—	+6	+12	0	+6	+6
a_3	−8	−6	—	0	−12	+2	−2
a_4	−12	−12	0	—	−8	−12	0
a_5	−2	0	+12	+12	—	−6	0
a_6	+2	+4	+8	+12	+6	—	+2
a_7	+2	−2	+2	+6	0	+2	—

1. a_6 is a Condorcet winner,
2. a_2 is a weak Condorcet winner,
3. a_4 is a **weak** Condorcet loser.



Ranking by RUBIS best and worst choosing

- Let X_1 be the set X of potential decision actions we wish to rank.
- While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i) RUBIS choice recommendations and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
- Both iterations determine, hence, two – usually slightly different – opposite weak orderings on X :
 1. a ranking- γ -best-choosing order and
 2. a ranking-by-worst-rejecting order



Ranking by RUBIS best and worst choosing

- Let X_1 be the set X of potential decision actions we wish to rank.
- While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i) RUBIS choice recommendations and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
- Both iterations determine, hence, two – usually slightly different – opposite weak orderings on X :
 1. a ranking-y-best-choosing order and,
 2. a ranking-by-worst-rejecting order.



Ranking by RUBIS best and worst choosing

- Let X_1 be the set X of potential decision actions we wish to rank.
- While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i) RUBIS choice recommendations and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
- Both iterations determine, hence, two – usually slightly different – opposite weak orderings on X :
 1. a ranking-y-best-choosing order and,
 2. a ranking-by-worst-rejecting order.



Ranking by RUBIS best and worst choosing

- Let X_1 be the set X of potential decision actions we wish to rank.
- While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i) RUBIS choice recommendations and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
- Both iterations determine, hence, two – usually slightly different – opposite weak orderings on X :
 1. a ranking-y-best-choosing order and,
 2. a ranking-by-worst-rejecting order.



Ranking by RUBIS best and worst choosing

- Let X_1 be the set X of potential decision actions we wish to rank.
- While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i) RUBIS choice recommendations and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
- Both iterations determine, hence, two – usually slightly different – opposite weak orderings on X :
 1. a ranking-y-best-choosing order and,
 2. a ranking-by-worst-rejecting order.



Fusion of best and worst choice rankings

Ranking by **recursively choosing**: Ranking by **recursively rejecting**:

1st Best Choice ['a02', 'a05']

2nd Best Choice ['a06']

3rd Best Choice ['a07']

4th Best Choice ['a01']

5th Best Choice ['a03', 'a04']

Last Choice ['a03', 'a04']

2nd Last Choice ['a05', 'a07']

3rd Last Choice ['a01']

4th Last Choice ['a06']

5th Last Choice ['a02']

We may fuse both rankings, the first and the converse of the second, with the help of the **epistemic conjunction** operator (\oplus) to make apparent a valued relation R which represents a **weakly complete and transitive closure** of the given bipolar valued outranking.


Let ϕ and ψ be two logical formulas:

$$\phi \oplus \psi = \begin{cases} (\phi \wedge \psi) & \text{if } (\phi \wedge \psi) \text{ is true;} \\ (\phi \vee \psi) & \text{if } (\neg\phi \wedge \neg\psi) \text{ is true;} \\ \text{Indeterminate} & \text{otherwise.} \end{cases}$$



Table : Weakly complete transitive closure of S

$r(R)$	a_2	a_5	a_6	a_1	a_7	a_3	a_4
a_2	—	0	+6	+6	+6	+6	+12
a_5	0	—	0	0	0	+12	+12
a_6	-4	0	—	+2	+2	+8	+12
a_1	0	0	-4	—	0	+8	+12
a_7	-2	0	-2	0	—	+2	+6
a_3	-6	-12	-2	-8	-2	—	0
a_4	-12	-8	-12	-12	0	0	—




Notice the contrasted ranks of action a_5 (first best as well as second last), indicating a lack of comparability, which becomes apparent in the conjunctive epistemic fusion R of both weak orderings shown in the Table above and illustrated in the corresponding Hasse diagram.



Table : Weakly complete transitive closure of S

$r(R)$	a_2	a_5	a_6	a_1	a_7	a_3	a_4
a_2	—	0	+6	+6	+6	+6	+12
a_5	0	—	0	0	0	+12	+12
a_6	-4	0	—	+2	+2	+8	+12
a_1	0	0	-4	—	0	+8	+12
a_7	-2	0	-2	0	—	+2	+6
a_3	-6	-12	-2	-8	-2	—	0
a_4	-12	-8	-12	-12	0	0	—



Notice the contrasted ranks of **action** a_5 (first best as well as second last), indicating a lack of comparability, which becomes apparent in the conjunctive epistemic fusion R of both weak orderings shown in the Table above and illustrated in the corresponding Hasse diagram.



1. Illustration

Sample outranking relation

Ranking-by-choosing

Partial ranking result

2. The setting

Weakly complete relations

The Rubis choice procedure

Properties

3. Ranking-by-choosing

Algorithm

Properties

Empirical Validation



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(xRy) = 1.0$ means xRy valid for sure;
 2. $r(xRy) = 0.0$ means both xRy and $x \nprec R y$ undetermined;
 3. $r(xRy) < 0.0$ means $x \nprec R y$ more or less valid;
 4. $r(xRy) = -1.0$ means $x \nprec R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$;
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$;
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$.



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(xRy) = +1.0$ means xRy valid for sure,
 2. $r(xRy) > 0.0$ means xRy more or less valid,
 3. $r(xRy) = 0.0$ means both xRy and $x \not R y$ indeterminate,
 4. $r(xRy) < 0.0$ means xRy more or less valid,
 5. $r(xRy) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(xRy) = +1.0$ means xRy valid for sure,
 2. $r(xRy) > 0.0$ means xRy more or less valid,
 3. $r(xRy) = 0.0$ means both xRy and $x \not R y$ indeterminate,
 4. $r(xRy) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(xRy) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg \phi) = -r(\phi)$
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg \phi) = -r(\phi)$
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(xRy) = +1.0$ means xRy valid for sure,
 2. $r(xRy) > 0.0$ means xRy more or less valid,
 3. $r(xRy) = 0.0$ means both xRy and $x \not R y$ indeterminate,
 4. $r(xRy) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(xRy) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.

$$1. r(\neg \phi) = -r(\phi)$$

$$2. r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$$

$$3. r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$$



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg \phi) = -r(\phi)$
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$.
 2. $r(\phi \vee \psi) = \max\{r(\phi), r(\psi)\}$.
 3. $r(\phi \wedge \psi) = \min\{r(\phi), r(\psi)\}$.



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$.
 2. $r(\phi \vee \psi) = \max(r(\phi), r(\psi))$,
 3. $r(\phi \wedge \psi) = \min(r(\phi), r(\psi))$.



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$.
 2. $r(\phi \vee \psi) = \max(r(\phi), r(\psi))$,
 3. $r(\phi \wedge \psi) = \min(r(\phi), r(\psi))$.



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$.
 2. $r(\phi \vee \psi) = \max(r(\phi), r(\psi))$,
 3. $r(\phi \wedge \psi) = \min(r(\phi), r(\psi))$.



Bipolar characteristic function r

- $X = \{x, y, z, \dots\}$ is a finite set of m decision alternatives;
- We define a binary relation R on X with the help of a bipolar characteristic function r taking values in the rational interval $[-1.0; 1.0]$.
- **Bipolar semantics:** For any pair $(x, y) \in X^2$,
 1. $r(x R y) = +1.0$ means $x R y$ valid for sure,
 2. $r(x R y) > 0.0$ means $x R y$ more or less valid,
 3. $r(x R y) = 0.0$ means both $x R y$ and $x \not R y$ indeterminate,
 4. $r(x R y) < 0.0$ means $x \not R y$ more or less valid,
 5. $r(x R y) = -1.0$ means $x \not R y$ valid for sure.
- **Boolean operations:** Let ϕ and ψ be two relational propositions.
 1. $r(\neg\phi) = -r(\phi)$.
 2. $r(\phi \vee \psi) = \max(r(\phi), r(\psi))$,
 3. $r(\phi \wedge \psi) = \min(r(\phi), r(\psi))$.



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted concordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderlogs



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted condordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderings.



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted condordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderings.



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted condordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderings.



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted condordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderings.



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted condordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderings.



Weakly complete binary relations

Let R be an r -valued binary relation defined on X .

Definition

We say that R is **weakly complete** on X if, for all $(x, y) \in X^2$, **either** $r(x R y) \geq 0.0$ **or** $r(y R x) \geq 0.0$.

Examples

1. Marginal semi-orders observed on each criterion,
2. Weighted condordance relations,
3. Polarised outranking relations,
4. Ranking-by-choosing results,
5. Weak and linear orderings.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. If \mathcal{R} is a system of weakly complete (resp. \mathcal{R} -internal) relations, then any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. The *convex* combination of any finite set of such weakly complete relations remains a weakly complete relation.
2. The *disjunctive* combination of any finite set of such weakly complete relations remains a weakly complete relation.
3. The *epistemic-conjunctive* (resp. *-disjunctive*) combination of any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. The **convex** combination of any finite set of such weakly complete relations remains a weakly complete relation.
2. The **disjunctive** combination of any finite set of such weakly complete relations remains a weakly complete relation.
3. The **epistemic-conjunctive** (resp. **-disjunctive**) combination of any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. The **convex** combination of any finite set of such weakly complete relations remains a weakly complete relation.
2. The **disjunctive** combination of any finite set of such weakly complete relations remains a weakly complete relation.
3. The **epistemic-conjunctive** (resp. **-disjunctive**) combination of any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. The **convex** combination of any finite set of such weakly complete relations remains a weakly complete relation.
2. The **disjunctive** combination of any finite set of such weakly complete relations remains a weakly complete relation.
3. The **epistemic-conjunctive** (resp. **-disjunctive**) combination of any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. The **convex** combination of any finite set of such weakly complete relations remains a weakly complete relation.
2. The **disjunctive** combination of any finite set of such weakly complete relations remains a weakly complete relation.
3. The **epistemic-conjunctive** (resp. **-disjunctive**) combination of any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Universal properties

Let \mathcal{R} denote the set of all possible weakly complete relations definable on X .

Property (\mathcal{R} -internal operations)

1. The **convex** combination of any finite set of such weakly complete relations remains a weakly complete relation.
2. The **disjunctive** combination of any finite set of such weakly complete relations remains a weakly complete relation.
3. The **epistemic-conjunctive** (resp. **-disjunctive**) combination of any finite set of such weakly complete relations remains a weakly complete relation.

Examples: Concordance of linear, weak orders or semiorders, bipolar outranking (concordance-discordance) relations.



Useful properties

We say that a binary relation $R \in \mathcal{R}$ verifies the *coduality principle* ($> \equiv \not\leq$), if the converse of its negation equals its asymmetric part : $\min(r(x R y), -r(y R x)) = -r(y R x)$. Let \mathcal{R}^{cd} denote the set of all possible relations $R \in \mathcal{R}$ that verify the coduality principle.

Property (Coduality principle)

The convex and epistemic-disjunctive (resp. -conjunctive) combinations of a finite set of relations in \mathcal{R}^{cd} verify again the coduality principle.

Example: Marginal linear-, weak- and semi-orders, concordance and bipolar outranking relations, all verify the coduality principle.



Useful properties

We say that a binary relation $R \in \mathcal{R}$ verifies the *coduality principle* ($> \equiv \not\leq$), if the converse of its negation equals its asymmetric part : $\min(r(x R y), -r(y R x)) = -r(y R x)$. Let \mathcal{R}^{cd} denote the set of all possible relations $R \in \mathcal{R}$ that verify the coduality principle.

Property (Coduality principle)

The convex and epistemic-disjunctive (resp. -conjunctive) combinations of a finite set of relations in \mathcal{R}^{cd} verify again the coduality principle.

Example: Marginal linear-, weak- and semi-orders, concordance and bipolar outranking relations, all verify the coduality principle.



Useful properties

We say that a binary relation $R \in \mathcal{R}$ verifies the *coduality principle* ($> \equiv \not\leq$), if the converse of its negation equals its asymmetric part : $\min(r(x R y), -r(y R x)) = -r(y R x)$. Let \mathcal{R}^{cd} denote the set of all possible relations $R \in \mathcal{R}$ that verify the coduality principle.

Property (Coduality principle)

The convex and epistemic-disjunctive (resp. -conjunctive) combinations of a finite set of relations in \mathcal{R}^{cd} verify again the coduality principle.

Example: Marginal linear-, weak- and semi-orders, concordance and bipolar outranking relations, all verify the coduality principle.



Useful properties

We say that a binary relation $R \in \mathcal{R}$ verifies the *coduality principle* ($> \equiv \not\leq$), if the converse of its negation equals its asymmetric part : $\min(r(x R y), -r(y R x)) = -r(y R x)$. Let \mathcal{R}^{cd} denote the set of all possible relations $R \in \mathcal{R}$ that verify the coduality principle.

Property (Coduality principle)

The convex and epistemic-disjunctive (resp. -conjunctive) combinations of a finite set of relations in \mathcal{R}^{cd} verify again the coduality principle.

Example: Marginal linear-, weak- and semi-orders, concordance and bipolar outranking relations, all verify the coduality principle.



Pragmatic principles of the RUBIS choice

\mathcal{P}_1 : Elimination for well motivated reasons:

Each eliminated alternative has to be outranked by (resp. is outranking) at least one alternative in the RUBIS choice (RC).

\mathcal{P}_2 : Minimal size:

The RC must be as limited in cardinality as possible.

\mathcal{P}_3 : Stable and efficient:

The RC must not contain a self-contained sub-RC.

\mathcal{P}_4 : Effectively better (resp. worse):

The RC must not be ambiguous in the sense that it is not both a best choice as well as a worst choice recommendation.

\mathcal{P}_5 : Maximally significant:

The RC is, of all potential best (resp. worst) choices, the one that is most significantly supported by the marginal “*at least as good as*” relations.



Pragmatic principles of the RUBIS choice

\mathcal{P}_1 : Elimination for well motivated reasons:

Each eliminated alternative has to be outranked by (resp. is outranking) at least one alternative in the RUBIS choice (RC).

\mathcal{P}_2 : Minimal size:

The RC must be as limited in cardinality as possible.

\mathcal{P}_3 : Stable and efficient:

The RC must not contain a self-contained sub-RC.

\mathcal{P}_4 : Effectively better (resp. worse):

The RC must not be ambiguous in the sense that it is not both a best choice as well as a worst choice recommendation.

\mathcal{P}_5 : Maximally significant:

The RC is, of all potential best (resp. worst) choices, the one that is most significantly supported by the marginal “*at least as good as*” relations.



Pragmatic principles of the RUBIS choice

\mathcal{P}_1 : Elimination for well motivated reasons:

Each eliminated alternative has to be outranked by (resp. is outranking) at least one alternative in the RUBIS choice (RC).

\mathcal{P}_2 : Minimal size:

The RC must be as limited in cardinality as possible.

\mathcal{P}_3 : Stable and efficient:

The RC must not contain a self-contained sub-RC.

\mathcal{P}_4 : Effectively better (resp. worse):

The RC must not be ambiguous in the sense that it is not both a best choice as well as a worst choice recommendation.

\mathcal{P}_5 : Maximally significant:

The RC is, of all potential best (resp. worst) choices, the one that is most significantly supported by the marginal “*at least as good as*” relations.



Pragmatic principles of the RUBIS choice

\mathcal{P}_1 : Elimination for well motivated reasons:

Each eliminated alternative has to be outranked by (resp. is outranking) at least one alternative in the RUBIS choice (RC).

\mathcal{P}_2 : Minimal size:

The RC must be as limited in cardinality as possible.

\mathcal{P}_3 : Stable and efficient:

The RC must not contain a self-contained sub-RC.

\mathcal{P}_4 : Effectively better (resp. worse):

The RC must not be ambiguous in the sense that it is not both a best choice as well as a worst choice recommendation.

\mathcal{P}_5 : Maximally significant:

The RC is, of all potential best (resp. worst) choices, the one that is most significantly supported by the marginal “*at least as good as*” relations.



Pragmatic principles of the RUBIS choice

\mathcal{P}_1 : Elimination for well motivated reasons:

Each eliminated alternative has to be outranked by (resp. is outranking) at least one alternative in the RUBIS choice (RC).

\mathcal{P}_2 : Minimal size:

The RC must be as limited in cardinality as possible.

\mathcal{P}_3 : Stable and efficient:

The RC must not contain a self-contained sub-RC.

\mathcal{P}_4 : Effectively better (resp. worse):

The RC must not be ambiguous in the sense that it is not both a best choice as well as a worst choice recommendation.

\mathcal{P}_5 : Maximally significant:

The RC is, of all potential best (resp. worst) choices, the one that is most significantly supported by the marginal “*at least as good as*” relations.



Qualifications of a choice in X

Let S be an r -valued outranking relation defined on X and let Y be a non empty subset of X , called a **choice** in X .

- Y is called **outranking** (resp. **outranked**) iff for all non retained alternative x there exists an alternative y retained such that $r(y S x) > 0.0$ (resp. $r(x S y) > 0.0$).
- Y is called **independent** iff for all $x \neq y$ in Y , we observe $r(x S y) \leq 0.0$.
- Y is an **outranking kernel** (resp. **outranked kernel**) iff Y is an outranking (resp. outranked) and independent choice.
- Y is an outranking (resp. outranked) **hyper-kernel** iff Y is an outranking (resp. outranked) choice containing chordless circuits of odd order $p \geq 1$.



Qualifications of a choice in X

Let S be an r -valued outranking relation defined on X and let Y be a non empty subset of X , called a **choice** in X .

- Y is called **outranking** (resp. **outranked**) iff for all non retained alternative x there exists an alternative y retained such that $r(y S x) > 0.0$ (resp. $r(x S y) > 0.0$).
- Y is called **independent** iff for all $x \neq y$ in Y , we observe $r(x S y) \leq 0.0$.
- Y is an **outranking kernel** (resp. **outranked kernel**) iff Y is an outranking (resp. outranked) and independent choice.
- Y is an outranking (resp. outranked) **hyper-kernel** iff Y is an outranking (resp. outranked) choice containing chordless circuits of odd order $p \geq 1$.



Qualifications of a choice in X

Let S be an r -valued outranking relation defined on X and let Y be a non empty subset of X , called a **choice** in X .

- Y is called **outranking** (resp. **outranked**) iff for all non retained alternative x there exists an alternative y retained such that $r(y S x) > 0.0$ (resp. $r(x S y) > 0.0$).
- Y is called **independent** iff for all $x \neq y$ in Y , we observe $r(x S y) \leq 0.0$.
- Y is an **outranking kernel** (resp. **outranked kernel**) iff Y is an outranking (resp. outranked) and independent choice.
- Y is an outranking (resp. outranked) **hyper-kernel** iff Y is an outranking (resp. outranked) choice containing chordless circuits of odd order $p \geq 1$.



Qualifications of a choice in X

Let S be an r -valued outranking relation defined on X and let Y be a non empty subset of X , called a **choice** in X .

- Y is called **outranking** (resp. **outranked**) iff for all non retained alternative x there exists an alternative y retained such that $r(y S x) > 0.0$ (resp. $r(x S y) > 0.0$).
- Y is called **independent** iff for all $x \neq y$ in Y , we observe $r(x S y) \leq 0.0$.
- Y is an **outranking kernel** (resp. **outranked kernel**) iff Y is an outranking (resp. outranked) and independent choice.
- Y is an outranking (resp. outranked) **hyper-kernel** iff Y is an outranking (resp. outranked) choice containing chordless circuits of odd order $p \geq 1$.



Translating the pragmatic RUBIS principles in terms of choice qualifications

\mathcal{P}_1 : Elimination for well motivated reasons.

The RC is an **outranking choice** (resp. **outranked choice**).

\mathcal{P}_{2+3} : Minimal and stable choice.

The RC is a **hyper-kernel**.

\mathcal{P}_4 : Effectivity.

The RC is a choice which is **strictly more outranking than outranked** (resp. **strictly more outranked than outranking**).

\mathcal{P}_5 : Maximal significance.

The RC is the **most determined** one in the set of potential outranking (resp. outranked) hyper-kernels observed in a given r -valued outranking relation.



Translating the pragmatic RUBIS principles in terms of choice qualifications

\mathcal{P}_1 : Elimination for well motivated reasons.

The RC is an **outranking choice** (resp. **outranked choice**).

\mathcal{P}_{2+3} : Minimal and stable choice.

The RC is a **hyper-kernel**.

\mathcal{P}_4 : Effectivity.

The RC is a choice which is **strictly more outranking than outranked** (resp. **strictly more outranked than outranking**).

\mathcal{P}_5 : Maximal significance.

The RC is the **most determined** one in the set of potential outranking (resp. outranked) hyper-kernels observed in a given r -valued outranking relation.



Translating the pragmatic RUBIS principles in terms of choice qualifications

\mathcal{P}_1 : Elimination for well motivated reasons.

The RC is an **outranking choice** (resp. **outranked choice**).

\mathcal{P}_{2+3} : Minimal and stable choice.

The RC is a **hyper-kernel**.

\mathcal{P}_4 : Effectivity.

The RC is a choice which is **strictly more outranking than outranked** (resp. **strictly more outranked than outranking**).

\mathcal{P}_5 : Maximal significance.

The RC is the **most determined** one in the set of potential outranking (resp. outranked) hyper-kernels observed in a given r -valued outranking relation.



Translating the pragmatic RUBIS principles in terms of choice qualifications

\mathcal{P}_1 : Elimination for well motivated reasons.

The RC is an **outranking choice** (resp. **outranked choice**).

\mathcal{P}_{2+3} : Minimal and stable choice.

The RC is a **hyper-kernel**.

\mathcal{P}_4 : Effectivity.

The RC is a choice which is **strictly more outranking than outranked** (resp. **strictly more outranked than outranking**).

\mathcal{P}_5 : Maximal significance.

The RC is the **most determined** one in the set of potential outranking (resp. outranked) hyper-kernels observed in a given r -valued outranking relation.



Properties of the RUBIS choice

Property (decisiveness)

Every r -valued (strict) outranking relation admits at least one outranking and one outranked hyper-kernel.

Definition

Let S and S' be two r -valued outranking relations defined on X .

1. We say that S' upgrades action $x \in X$, denoted $S^{x\uparrow}$, if $r(x S' y) \geq r(x S y)$, and $r(y S' x) \leq r(y S x)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.
2. We say that S' downgrades action $x \in X$, denoted $S^{x\downarrow}$, if $r(y S' x) \geq r(y S x)$, and $r(x S' y) \leq r(x S y)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.



Properties of the RUBIS choice

Property (decisiveness)

Every r -valued (strict) outranking relation admits at least one outranking and one outranked hyper-kernel.

Definition

Let S and S' be two r -valued outranking relations defined on X .

1. We say that S' **upgrades** action $x \in X$, denoted $S^{x\uparrow}$, if $r(x S' y) \geq r(x S y)$, and $r(y S' x) \leq r(y S x)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.
2. We say that S' **downgrades** action $x \in X$, denoted $S^{x\downarrow}$, if $r(y S' x) \geq r(y S x)$, and $r(x S' y) \leq r(x S y)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.



Properties of the RUBIS choice

Property (decisiveness)

Every r -valued (strict) outranking relation admits at least one outranking and one outranked hyper-kernel.

Definition

Let S and S' be two r -valued outranking relations defined on X .

1. We say that S' **upgrades** action $x \in X$, denoted $S^{x\uparrow}$, if $r(x S' y) \geq r(x S y)$, and $r(y S' x) \leq r(y S x)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.
2. We say that S' **downgrades** action $x \in X$, denoted $S^{x\downarrow}$, if $r(y S' x) \geq r(y S x)$, and $r(x S' y) \leq r(x S y)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.



Properties of the RUBIS choice

Property (decisiveness)

Every r -valued (strict) outranking relation admits at least one outranking and one outranked hyper-kernel.

Definition

Let S and S' be two r -valued outranking relations defined on X .

1. We say that S' **upgrades** action $x \in X$, denoted $S^{x\uparrow}$, if $r(x S' y) \geq r(x S y)$, and $r(y S' x) \leq r(y S x)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.
2. We say that S' **downgrades** action $x \in X$, denoted $S^{x\downarrow}$, if $r(y S' x) \geq r(y S x)$, and $r(x S' y) \leq r(x S y)$, and $r(y S' z) = r(y S z)$ for all $y, z \in X - \{x\}$.



Properties of the RUBIS choice

Let A be a subset of X . Let $RBC(S|_A)$ (resp. $RBC(S'_A)$) be the RUBIS best choice wrt to S (resp. S') restricted to A and let $RWC(S|_A)$ (resp. $RWC(S'_A)$) be the RUBIS worst choice wrt to S (resp. S') restricted to A .

Property

1. $S|_A = S'_A \Rightarrow RBC(S|_A) = RBC(S'_A)$ (*RBC local*),
2. $S|_A = S'_A \Rightarrow RWC(S|_A) = RWC(S'_A)$ (*RWC local*),
3. $x \in RBC(S|_A) \Rightarrow x \in RBC(S|_A^{x\uparrow})$ (*RBC weakly monotonic*),
4. $x \in RWC(S|_A) \Rightarrow x \in RWC(S|_A^{x\downarrow})$ (*RWC weakly monotonic*),
5. *The RUBIS choice does not satisfy the Super Set Property (SSP)!*



Properties of the RUBIS choice

Let A be a subset of X . Let $RBC(S|_A)$ (resp. $RBC(S'_|_A)$) be the RUBIS best choice wrt to S (resp. S') restricted to A and let $RWC(S|_A)$ (resp. $RWC(S'_|_A)$) be the RUBIS worst choice wrt to S (resp. S') restricted to A .

Property

1. $S|_A = S'_|_A \Rightarrow RBC(S|_A) = RBC(S'_|_A)$ (*RBC local*),
2. $S|_A = S'_|_A \Rightarrow RWC(S|_A) = RWC(S'_|_A)$ (*RWC local*),
3. $x \in RBC(S|_A) \Rightarrow x \in RBC(S|_A^{x\uparrow})$ (*RBC weakly monotonic*),
4. $x \in RWC(S|_A) \Rightarrow x \in RWC(S|_A^{x\downarrow})$ (*RWC weakly monotonic*),
5. *The RUBIS choice does not satisfy the Super Set Property (SSP)!*



Properties of the RUBIS choice

Let A be a subset of X . Let $RBC(S|_A)$ (resp. $RBC(S'_|_A)$) be the RUBIS best choice wrt to S (resp. S') restricted to A and let $RWC(S|_A)$ (resp. $RWC(S'_|_A)$) be the RUBIS worst choice wrt to S (resp. S') restricted to A .

Property

1. $S|_A = S'_|_A \Rightarrow RBC(S|_A) = RBC(S'_|_A)$ (*RBC local*),
2. $S|_A = S'_|_A \Rightarrow RWC(S|_A) = RWC(S'_|_A)$ (*RWC local*),
3. $x \in RBC(S|_A) \Rightarrow x \in RBC(S|_A^{x\uparrow})$ (*RBC weakly monotonic*),
4. $x \in RWC(S|_A) \Rightarrow x \in RWC(S|_A^{x\downarrow})$ (*RWC weakly monotonic*),
5. *The RUBIS choice does not satisfy the Super Set Property (SSP)!*



Properties of the RUBIS choice

Let A be a subset of X . Let $RBC(S|_A)$ (resp. $RBC(S'_A)$) be the RUBIS best choice wrt to S (resp. S') restricted to A and let $RWC(S|_A)$ (resp. $RWC(S'_A)$) be the RUBIS worst choice wrt to S (resp. S') restricted to A .

Property

1. $S|_A = S'_A \Rightarrow RBC(S|_A) = RBC(S'_A)$ (*RBC local*),
2. $S|_A = S'_A \Rightarrow RWC(S|_A) = RWC(S'_A)$ (*RWC local*),
3. $x \in RBC(S|_A) \Rightarrow x \in RBC(S|_A^{x\uparrow})$ (*RBC weakly monotonic*),
4. $x \in RWC(S|_A) \Rightarrow x \in RWC(S|_A^{x\downarrow})$ (*RWC weakly monotonic*).
5. *The RUBIS choice does not satisfy the Super Set Property (SSP)!*



Properties of the RUBIS choice

Let A be a subset of X . Let $RBC(S|_A)$ (resp. $RBC(S'_|_A)$) be the RUBIS best choice wrt to S (resp. S') restricted to A and let $RWC(S|_A)$ (resp. $RWC(S'_|_A)$) be the RUBIS worst choice wrt to S (resp. S') restricted to A .

Property

1. $S|_A = S'_|_A \Rightarrow RBC(S|_A) = RBC(S'_|_A)$ (*RBC local*),
2. $S|_A = S'_|_A \Rightarrow RWC(S|_A) = RWC(S'_|_A)$ (*RWC local*),
3. $x \in RBC(S|_A) \Rightarrow x \in RBC(S|_A^{x\uparrow})$ (*RBC weakly monotonic*),
4. $x \in RWC(S|_A) \Rightarrow x \in RWC(S|_A^{x\downarrow})$ (*RWC weakly monotonic*).
5. *The RUBIS choice does not satisfy the Super Set Property (SSP)!*



Properties of the RUBIS choice

Let A be a subset of X . Let $RBC(S|_A)$ (resp. $RBC(S'_A)$) be the RUBIS best choice wrt to S (resp. S') restricted to A and let $RWC(S|_A)$ (resp. $RWC(S'_A)$) be the RUBIS worst choice wrt to S (resp. S') restricted to A .

Property

1. $S|_A = S'_A \Rightarrow RBC(S|_A) = RBC(S'_A)$ (*RBC local*),
2. $S|_A = S'_A \Rightarrow RWC(S|_A) = RWC(S'_A)$ (*RWC local*),
3. $x \in RBC(S|_A) \Rightarrow x \in RBC(S|_A^{x\uparrow})$ (*RBC weakly monotonic*),
4. $x \in RWC(S|_A) \Rightarrow x \in RWC(S|_A^{x\downarrow})$ (*RWC weakly monotonic*).
5. *The RUBIS choice does not satisfy the Super Set Property (SSP)!*



1. Illustration

Sample outranking relation

Ranking-by-choosing

Partial ranking result

2. The setting

Weakly complete relations

The Rubis choice procedure

Properties

3. Ranking-by-choosing

Algorithm

Properties

Empirical Validation



Ranking-by-Choosing Algorithm

1. Let X_1 be the set X of potential decision actions we wish to rank on the basis of a given outranking relation S .
2. While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i), RUBIS choice recommendation and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
3. Both independent iterations determine, hence, two – usually slightly different – opposite weak orderings on X : a **ranking-y-best-choosing** – and a **ranking-by-worst-choosing** order.
4. We **fuse** both rankings, the first and the converse of the second, with the help of the epistemic conjunction operator (\otimes) to make apparent a weakly complete ranking relation \succsim_S on X . We denote \succ_S the codual of \succsim_S .



Ranking-by-Choosing Algorithm

1. Let X_1 be the set X of potential decision actions we wish to rank on the basis of a given outranking relation S .
2. While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i), RUBIS choice recommendation and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
3. Both independent iterations determine, hence, two – usually slightly different – opposite weak orderings on X : a **ranking-y-best-choosing** – and a **ranking-by-worst-choosing** order.
4. We **fuse** both rankings, the first and the converse of the second, with the help of the epistemic conjunction operator (\otimes) to make apparent a weakly complete ranking relation \succsim_S on X . We denote \succ_S the codual of \succsim_S .



Ranking-by-Choosing Algorithm

1. Let X_1 be the set X of potential decision actions we wish to rank on the basis of a given outranking relation S .
2. While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i), RUBIS choice recommendation and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
3. Both independent iterations determine, hence, two – usually slightly different – opposite weak orderings on X : a **ranking-y-best-choosing** – and a **ranking-by-worst-choosing** order.
4. We **fuse** both rankings, the first and the converse of the second, with the help of the epistemic conjunction operator (\otimes) to make apparent a weakly complete ranking relation \succsim_S on X . We denote \succ_S the codual of \succsim_S .



Ranking-by-Choosing Algorithm

1. Let X_1 be the set X of potential decision actions we wish to rank on the basis of a given outranking relation S .
2. While the remaining set X_i ($i = 1, 2, \dots$) of decision actions to be ranked is not empty, we extract from X_i the best (B_i), respectively worst (W_i), RUBIS choice recommendation and set $X_{i+1} = X_i - B_i$, respectively $X_{i+1} = X_i - W_i$.
3. Both independent iterations determine, hence, two – usually slightly different – opposite weak orderings on X : a **ranking-y-best-choosing** – and a **ranking-by-worst-choosing** order.
4. We **fuse** both rankings, the first and the converse of the second, with the help of the epistemic conjunction operator (\otimes) to make apparent a weakly complete ranking relation \succsim_S on X . We denote \succ_S the codual of \succsim_S .



Transitive S-closure

Definition

We call a ranking procedure **transitive** if the ranking procedure renders a (partial) strict ordering \succ_S on X with a given r -valued outranking relation S such that for all $x, y, z \in X$: $r(x \succ_S y) > 0$ and $r(y \succ_S z) > 0$ imply $r(x \succ_S z) > 0$.

Property

Both the RUBIS ranking-by-best-choosing, as well as the RUBIS ranking-by-worst-choosing procedures, are transitive ranking procedures.

Corollary

- i) The fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice of a given r -valued outranking relation S is a transitive ranking procedure.*
- ii) The RUBIS ranking-by-choosing represents a transitive closure of the codual of S .*



Transitive S-closure

Definition

We call a ranking procedure **transitive** if the ranking procedure renders a (partial) strict ordering \succ_S on X with a given r -valued outranking relation S such that for all $x, y, z \in X$: $r(x \succ_S y) > 0$ and $r(y \succ_S z) > 0$ imply $r(x \succ_S z) > 0$.

Property

Both the RUBIS ranking-by-best-choosing, as well as the RUBIS ranking-by-worst-choosing procedures, are transitive ranking procedures.

Corollary

- i) The fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice of a given r -valued outranking relation S is a transitive ranking procedure.*
- ii) The RUBIS ranking-by-choosing represents a transitive closure of the codual of S .*



Transitive S-closure

Definition

We call a ranking procedure **transitive** if the ranking procedure renders a (partial) strict ordering \succ_S on X with a given r -valued outranking relation S such that for all $x, y, z \in X$: $r(x \succ_S y) > 0$ and $r(y \succ_S z) > 0$ imply $r(x \succ_S z) > 0$.

Property

Both the RUBIS ranking-by-best-choosing, as well as the RUBIS ranking-by-worst-choosing procedures, are transitive ranking procedures.

Corollary

- i) The fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice of a given r -valued outranking relation S is a transitive ranking procedure.*
- ii) The RUBIS ranking-by-choosing represents a transitive closure of the codual of S .*



Weak monotonicity

Definition

We call a ranking procedure **weakly monotonic** if for all $x, y \in X$:

$$(x \succ_S y) \Rightarrow (x \succ_{S^{\uparrow}} y) \text{ and } (y \succ_S x) \Rightarrow (y \succ_{S^{\downarrow}} x),$$

Property

The ranking by RUBIS best choice and the ranking by RUBIS worst choice are, both, weakly monotonic ranking procedures.

Corollary

The ranking-by-choosing, resulting from the fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice, is hence a weakly monotonic procedure.



Weak monotonicity

Definition

We call a ranking procedure **weakly monotonic** if for all $x, y \in X$:

$$(x \succ_S y) \Rightarrow (x \succ_{S^{\uparrow}} y) \text{ and } (y \succ_S x) \Rightarrow (y \succ_{S^{\downarrow}} x),$$

Property

The ranking by RUBIS best choice and the ranking by RUBIS worst choice are, both, weakly monotonic ranking procedures.

Corollary

The ranking-by-choosing, resulting from the fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice, is hence a weakly monotonic procedure.



Weak monotonicity

Definition

We call a ranking procedure **weakly monotonic** if for all $x, y \in X$:

$$(x \succ_S y) \Rightarrow (x \succ_{S^{\uparrow}} y) \text{ and } (y \succ_S x) \Rightarrow (y \succ_{S^{\downarrow}} x),$$

Property

The ranking by RUBIS best choice and the ranking by RUBIS worst choice are, both, weakly monotonic ranking procedures.

Corollary

The ranking-by-choosing, resulting from the fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice, is hence a weakly monotonic procedure.



Condorcet consistency

Definition

We call a ranking procedure **Condorcet-consistent** if the ranking procedure renders the same linear (resp. weak) order \succ_S on X which is, the case given, modelled by the strict majority cut of the codual of a given r -valued outranking relation S .

Property

Both the RUBIS ranking-by-best-choosing, as well as the RUBIS ranking-by-worst-choosing procedures, are Condorcet consistent.

Corollary

The fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice of a given r -valued outranking relation S is, hence, also Condorcet consistent.



Condorcet consistency

Definition

We call a ranking procedure **Condorcet-consistent** if the ranking procedure renders the same linear (resp. weak) order \succ_S on X which is, the case given, modelled by the strict majority cut of the codual of a given r -valued outranking relation S .

Property

Both the RUBIS ranking-by-best-choosing, as well as the RUBIS ranking-by-worst-choosing procedures, are Condorcet consistent.

Corollary

The fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice of a given r -valued outranking relation S is, hence, also Condorcet consistent.



Condorcet consistency

Definition

We call a ranking procedure **Condorcet-consistent** if the ranking procedure renders the same linear (resp. weak) order \succ_S on X which is, the case given, modelled by the strict majority cut of the codual of a given r -valued outranking relation S .

Property


Both the RUBIS ranking-by-best-choosing, as well as the RUBIS ranking-by-worst-choosing procedures, are Condorcet consistent.

Corollary


The fusion of the ranking by RUBIS best choice and the converse of the ranking by RUBIS worst choice of a given r -valued outranking relation S is, hence, also Condorcet consistent.

Introductory example


Comparing ranking-by-choosing result with Kohler's and Tideman's:



0.88%



0.90%



0.87%



Sample performance tableau

Let $X = \{a_1, \dots, a_7\}$ be seven potential decision actions evaluated on three cost criteria (g_1, g_4, g_5) of equi-significance $1/6$ and two benefit criteria (g_2, g_3) of equi-significance $1/4$. The given performance tableau is shown below.

Objectives	Costs			Benefits	
Criteria	$g_1(\downarrow)$	$g_4(\downarrow)$	$g_5(\downarrow)$	$g_2(\uparrow)$	$g_3(\uparrow)$
weights \times 12	2.0	2.0	2.0	3.0	3.0
indifference	3.41	4.91	-	-	2.32
preference	6.31	8.31	-	-	5.06
veto	60.17	67.75	-	-	48.24
a_1	22.49	36.84	7	8	43.44
a_2	16.18	19.21	2	8	19.35
a_3	29.41	54.43	3	4	33.37
a_4	82.66	86.96	8	6	48.50
a_5	47.77	82.27	7	7	81.61
a_6	32.50	16.56	6	8	34.06
a_7	35.91	27.52	2	1	50.82



Quality of ranking result


Comparing rankings of a sample of 1000 random r -valued outranking relations defined on 20 actions and evaluated on 13 criteria obtained with RUBIS **ranking-by-choosing**, **Kohler's**, and **Tideman's** (ranked pairs) procedure.

Mean extended Kendall τ correlations with r -valued outranking relation:

Ranking-by-choosing: **+.906**

Tideman's ranking: **+.875**

Kohler's ranking: **+.835**





Quality of ranking-by-choosing result

r-valued determination of ranking result:

- Mean outranking significance:
0.351 (67.5% of total criteria support),
- Mean Ranking-by-choosing significance:
0.268 (63.4% of total criteria support),
- Mean covered part of significance:
 $0.268/0.351 = 76\%$.



Quality of ranking-by-choosing result

r-valued determination of ranking result:

- Mean outranking significance:
0.351 (67.5% of total criteria support),
- Mean Ranking-by-choosing significance:
0.268 (63.4% of total criteria support),
- Mean covered part of significance:
 $0.268/0.351 = 76\%$.



Quality of ranking-by-choosing result

r-valued determination of ranking result:


- Mean outranking significance:
0.351 (67.5% of total criteria support),
- Mean Ranking-by-choosing significance:
0.268 (63.4% of total criteria support),
- Mean covered part of significance:
 $0.268/0.351 = 76\%$.



Scalability of ranking procedures

Ranking execution times (in sec.) for 1000 random 20x13 outrankings:

- **Kohler's** procedure on the **right y-axis** (less than **1/100** sec.),
- Tideman's procedure on the **left y-axis** (less than **1/3** sec.),
- the RUBIS ranking-by-choosing procedure on the x-axis (mostly less than **2** sec.). But, heavy right tail (up to **11** sec.!).






Scalability of ranking procedures

Ranking execution times (in sec.) for 1000 random 20x13 outrankings:

- **Kohler's** procedure on the **right y-axis** (less than **1/100** sec.),
- **Tideman's** procedure on the **left y-axis** (less than **1/3** sec.),
- the RUBIS ranking-by-choosing procedure on the x-axis (mostly less than **2** sec.). But, heavy right tail (up to **11** sec.!).






Scalability of ranking procedures

Ranking execution times (in sec.) for 1000 random 20x13 outrankings:

- **Kohler's** procedure on the **right y-axis** (less than **1/100** sec.),
- **Tideman's** procedure on the **left y-axis** (less than **1/3** sec.),
- the **RUBIS ranking-by-choosing** procedure on the **x-axis** (mostly less than **2** sec.). But, heavy right tail (up to **11** sec. !).





Practical application

- Spiegel (DE) On-line Students' Survey (2004) about the quality of 41 German universities in 15 academic disciplines;
- XMCD A 2.0 encoding of performace tableau;
- Ranking-by-choosing result.



1. Illustration

Sample outranking relation

Ranking-by-choosing

Partial ranking result

2. The setting

Weakly complete relations

The Rubis choice procedure

Properties

3. Ranking-by-choosing

Algorithm

Properties

Empirical Validation

Bibliography

- [1] D. Bouyssou, *Monotonicity of 'ranking by choosing'; A progress report.* Social Choice Welfare (2004) 23: 249-273.
- [2] R. Bisdorff, M. Pirlot and M. Roubens, *Choices and kernels from bipolar valued digraphs.* European Journal of Operational Research, 175 (2006) 155-170.
- [3] R. Bisdorff, P. Meyer and M. Roubens, *RUBIS : a bipolar-valued outranking method for the choice problem.* 4OR, A Quarterly Journal of Operations Research, Springer-Verlag, Volume 6 Number 2 (2008) 143-165.
- [4] R. Bisdorff, *On measuring and testing the ordinal correlation between bipolar outranking relations.* In Proceedings of DA2PL'2012 - From Multiple Criteria Decision Aid to Preference Learning, University of Mons (2012) 91-100.
- [5] R. Bisdorff, *On polarizing outranking relations with large performance differences.* Journal of Multi-Criteria Decision Analysis, Wiley, Number 20 (2013) DOI: 10.1002/mcda.1472 3-12.