

## PRACTICE PROBLEMS

Consider the following schema:

SALE (CUST\_NAME, ITEM\_NAME, WHEN)

CUST (CUST\_NAME, INDUSTRY)

ITEM (ITEM\_NAME, CATEGORY, PRICE)

Write both relational algebra and relational calculus expressions which will answer the following questions:

- (1) Which customers bought something on 12-18-04?
- (2) Which customers from the airline industry bought something on 12-18-04?
- (3) Which customers have bought something from a category other than “transportation”?
- (4) Which customers bought something costing more than \$1,000,000 that was not in the category “doohicky”?
- (5) Which customers from the airline industry did not buy something on 12-18-04?
- (6) Which customers from the airline industry bought an item from the category “spare part” on 12-18-04?
- (7) What categories has the customer “Widgets ‘R’Us” never purchased an item in? (8) Which customers are associated with more than one industry?
- (9) What category has the most expensive item?
- (10) Which customers have bought every item in the “spare part” category?
- (11) Which customers have bought exactly the same set of items as “Chris’ Lobster Shack”?

## ANSWERS FOR PRACTICE PROBLEMS

1

RA:

PROJECT (CUST\_NAME) (SELECT (WHEN = 12-18-04) (SALE))

RC:

{s.CUST\_NAME | SALE(s) and s.WHEN = 12-18-04}

2

RA:

PROJECT (CUST\_NAME) (SELECT (WHEN = 12-18-04 and INDUSTRY = 'airline')  
(SALE \* CUST))

RC:  
{s.CUST\_NAME | SALE(s) and s.WHEN = 12-18-04 and EXISTS (c)(CUST(c)  
and c.CUST\_NAME = s.CUST\_NAME and c.INDUSTRY = 'airline')}

3

RA:  
PROJECT (CUST\_NAME) (SELECT (CATEGORY != 'transportation') (SALE \*  
ITEM))

RC:  
{s.CUST\_NAME | SALE(s) and EXISTS (i)(ITEM(i) and i.ITEM\_NAME =  
s.ITEM\_NAME and i.CATEGORY != 'transportation')}

4

RA:  
PROJECT (CUST\_NAME) (SELECT (CATEGORY != 'doohicky' and PRICE >  
1000000) (SALE \* ITEM))

RC:  
{s.CUST\_NAME | SALE(s) and EXISTS (i)(ITEM(i) and i.ITEM\_NAME =  
s.ITEM\_NAME and i.CATEGORY != 'dohicky' and i.PRICE > 1000000)}

5

RA:  
THOSE\_WHO\_DID <- PROJECT (CUST\_NAME) (SELECT (WHEN = 12-18-04 and  
INDUSTRY = 'airline') (SALE \* CUST))

ANSWER <- PROJECT (CUST\_NAME) (SELECT (INDUSTRY = 'AIRLINE')  
(CUST)) -THOSE\_WHO\_DID

RC:  
{c.CUST\_NAME | CUST(c) and c.INDUSTRY = 'airline'  
and NOT EXISTS(s)(SALE(s) and s.CUST\_NAME = c.CUST\_NAME and s.WHEN =  
12-18-04)}

6

RA:  
PROJECT (CUST\_NAME) (SELECT (CATEGORY = 'spare part' and INDUSTRY =  
'airline' and WHEN = 12-18-04) (SALE \* CUST \* ITEM))

RC:  
{c.CUST\_NAME | CUST(c) and c.INDUSTRY = 'airline' and EXISTS  
(s)(SALE(s) and s.CUST\_NAME = c.CUST\_NAME and s.WHEN = 12-18-04 and  
EXISTS (i)(ITEM(i) and i.ITEM\_NAME = s.ITEM\_NAME and i.CATEGORY =  
'spare part'))}

7

RA:

```
WRU_CATS <- PROJECT (CATEGORY) (SELECT (CUST_NAME = 'Widgets R Us')
(SALE * ITEM))
```

```
ANSWER <- PROJECT (CATEGORY) (ITEM) - WRU_CATS
```

RC:

```
{i.CATEGORY | ITEM(i) AND FORALL(s)(SALE (s) and s.CUST_NAME =
'Widgets R Us' => NOT EXISTS (ii)(ITEM(ii) and ii.CATEGORY =
i.CATEGORY and s.ITEM_NAME = ii.ITEM_NAME))}
```

Note that this is the same as:

```
{i.CATEGORY | ITEM(i) AND FORALL (s)(SALE (s) and s.CUST_NAME =
'Widgets R Us' => "the item purchased in the sale s was not in the
same category as i")}
```

which is the same as:

```
{i.CATEGORY | ITEM(i) AND FORALL (s)("if s was a sale to the customer
'Widegets R Us' then the item purchased in the sale s was not in the same category as i")}
```

8

RA:

```
PAIRS (C1, I1, C2, I2) <- CUST X CUST
ANSWER <- PROJECT (C1) (SELECT (C1 = C2 and I1 != I2) (PAIRS))
```

RC:

```
{c.CUST_NAME | CUST (c) and EXISTS (cc) (CUST(cc) and c.CUST_NAME =
cc.CUST_NAME and c.INDUSTRY != cc.INDUSTRY)}
```

9

RA:

```
PAIRS (I1, C1, P1, I2, C2, P2) <- ITEM X ITEM
```

This next step gives us all items with someone who costs more:

```
ONES_WITH_LARGER (ITEM_NAME, CATEGORY) <- PROJECT (I1, C1)
(SELECT (P1 < P2) (PAIRS))
```

And all items minus all items with someone who costs more gives our answer:

```
ANSWER <- PROJECT (CATEGORY) (PROJECT (ITEM_NAME, CATEOGRY)
(ITEM) - ONES_WITH_LARGER)
```

RC:

$\{i.CATEGORY \mid \text{ITEM}(i) \text{ and NOT EXISTS } (ii)(\text{ITEM}(ii) \text{ and } i.PRICE < ii.PRICE)\}$

10

RA:

First, we get all person/part combos for every type of spare part:

```
ALL_PAIRS <- PROJECT (CUST_NAME) (CUST) X PROJECT (ITEM_NAME)
(SELECT (CATEGORY = 'Spare Part') (ITEM))
```

Now, we use that to get everyone who has NOT bought every spare part

```
NOT_ALL <- PROJECT (CUST_NAME) (ALL_PAIRS - PROJECT (CUST_NAME,
ITEM_NAME) (SALE))
```

And the answer is everyone else!

```
ANSWER <- PROJECT (CUST_NAME) (CUST) - NOT_ALL
```

RC:

It is easier in RC:

```
{c.CUST_NAME | CUST(c) and forall (i)(ITEM(i) and i.CATEGORY = 'spare part' =>
EXISTS (s)(SALE(s) and s.CUST_NAME = c.CUST_NAME and i.ITEM_NAME =
s.ITEM_NAME))}
```

This is the same as:

```
{c.CUST_NAME | CUST(c) and forall (i)(ITEM(i) and i.CATEGORY = 'spare part'
=> "the customer c.CUST_NAME has bought i.ITEM_NAME")}
```

Or

```
{c.CUST_NAME | CUST(c) and forall (i)("if i is a spare part from the
ITEM table, then the customer c.CUST_NAME has bought i.ITEM_NAME")}
```

11

RA:

This is not too different from #10, but it's even harder.

First, we need to get all person/item combos, where the item is one from Chris' Lobster Shack:

```
ALL_COMBOS <- PROJECT (CUST_NAME) (CUST) X PROJECT (ITEM_NAME)
(SELECT (CUST_NAME = 'Chris' Lobster Shack') (SALE))
```

We use that to find the people who are missing one of the items from Chris' Lobster Shack:

```
NOT_ALL <- PROJECT (CUST_NAME) (ALL_PAIRS - PROJECT (CUST_NAME,
ITEM_NAME) (SALE))
```

Now we can get everyone who has bought all of those items:

```
GOT_EM_ALL <- PROJECT (CUST_NAME) (CUST) - NOT_ALL
```

But, we're not done. We may have people who bought some extra items.

So we need everyone who bought something that Chris did not.

```
CHRIS_MISSED <- PROJECT (ITEM_NAME) (ITEM) - PROJECT (ITEM_NAME)
(SELECT (CUST_NAME = 'Chris' Lobster Shack') (SALE)))
```

```
EXTRA <- PROJECT (CUST_NAME) (SALE * CHRIS_MISSED)
```

And subtract out those people to get the answer:

```
ANSWER <- GOT_EM_ALL - EXTRA
```

RC:

We want something like:

{c.CUST\_NAME | CUST (c) and "Chris has bought everything that c.CUST\_NAME has  
and c.CUST\_NAME has bought everything that Chris has"}

The RC for this is:

{c.CUST\_NAME | CUST (c) and

FORALL (s)(SALE(s) and s.CUST\_NAME = c.CUST\_NAME =>

EXISTS (ss)(SALE(ss) and ss.ITEM\_NAME = s.ITEM\_NAME and  
ss.CUST\_NAME = 'Chris' Lobster Shack'))

and

FORALL (s)(SALE(s) and s.CUST\_NAME = 'Chris' Lobster Shack' =>

EXISTS (ss)(SALE(ss) and ss.ITEM\_NAME = s.ITEM\_NAME and  
ss.CUST\_NAME = s.CUST\_NAME)))}