

RIG InMoov Project

Generated by Doxygen 1.8.11

Contents

1	Introduction	1
1.1	Dependencies	1
1.2	Quick Start	1
1.3	Installation	2
1.4	Build System	2
1.5	Arduino Protocol	3
1.5.1	Servo Boards	3
1.5.2	Signals	3
1.5.2.1	CANCEL_SIGNAL	3
1.5.2.2	WAIT_RESPONSE	4
1.5.2.3	START_RESPONSE	4
1.5.2.4	END_RESPONSE	4
1.5.2.5	DUMP_SIGNAL	4
1.5.3	Examples	4
1.5.4	Values	4
2	Simulation	7
2.1	Dependencies	7
2.2	Building	7
2.3	Usage	8
2.4	Background	8
2.5	Debugging	8

3 Namespace Documentation	9
3.1 servo_demo Namespace Reference	9
3.1.1 Detailed Description	10
3.1.2 Function Documentation	11
3.1.2.1 calibrate(s=1)	11
3.1.2.2 cmd()	11
3.1.2.3 connect(port)	11
3.1.2.4 count()	12
3.1.2.5 demo()	12
3.1.2.6 dump(servos=6)	12
3.1.2.7 gesture(initial, servos, starts, ends, steps, delay)	12
3.1.2.8 grab(delay=0.02)	13
3.1.2.9 ok(delay=0.01)	13
3.1.2.10 peace(delay=0)	13
3.1.2.11 reset()	13
3.1.2.12 rockon(delay=0.01)	13
3.1.2.13 servowrite(commands, delay)	14
3.1.2.14 sweep(initial, servos, starts, ends, steps)	14
3.1.2.15 unsweep(servos, ends, steps)	15
3.1.2.16 wiggle(n=90, delay=0.01, wiggles=1)	15
3.1.3 Variable Documentation	15
3.1.3.1 ser	15

4	File Documentation	17
4.1	arduino/lib/serial.ino File Reference	17
4.1.1	Detailed Description	17
4.2	arduino/sketch/flex/flex.ino File Reference	17
4.2.1	Detailed Description	18
4.3	arduino/sketch/flex_double/flex_double.ino File Reference	18
4.3.1	Detailed Description	19
4.4	arduino/sketch/servo/servo.ino File Reference	19
4.4.1	Detailed Description	20
4.4.2	Enumeration Type Documentation	20
4.4.2.1	anonymous enum	20
4.4.3	Function Documentation	20
4.4.3.1	dump()	20
4.4.3.2	loop()	20
4.4.3.3	serialGetByte()	21
4.4.3.4	serialPrint(const char *s)	21
4.4.3.5	serialPrintInt(uint8_t i)	21
4.4.3.6	serialPrintIntPretty(const char *pre, uint8_t i, const char *post)	21
4.4.3.7	serialWait()	21
4.4.3.8	setServoFromID(int servo_id, uint8_t servo_angle)	21
4.4.3.9	setServoFromIndex(uint8_t servo_index, uint8_t servo_angle)	21
4.4.3.10	setup()	22
4.4.4	Variable Documentation	22
4.4.4.1	current_pos	22
4.4.4.2	servo	22
4.5	arduino/sketch/servo/settings/servo_rhand.h File Reference	22
4.5.1	Detailed Description	23
4.5.2	Macro Definition Documentation	23
4.5.2.1	BUFSIZE	23
4.5.2.2	SERVOS	23
4.5.3	Enumeration Type Documentation	24
4.5.3.1	anonymous enum	24
4.5.4	Function Documentation	24
4.5.4.1	getServoIDFromIndex(uint8_t servo_index)	24
4.5.4.2	getServoIndexFromID(uint8_t servo_id)	24
4.5.4.3	getServoPinFromIndex(uint8_t servo_index)	24
4.5.5	Variable Documentation	24
4.5.5.1	default_pos	24
4.5.5.2	limit	25
4.5.5.3	pin_offset	25
4.5.5.4	reverse	25
	Index	27

Chapter 1

Introduction

This is the official documentation for the Conestoga Robotics Innovation Group's InMoov project. It is not meant to be read linearly or all at once. Rather, readers should skim relevant pages and skip information that requires more context. More in depth information is provided for those that wish to modify the source code. Examples are provided when possible for quick reference and experimentation. Note that colored phrases are links for both html and pdf. This project has a [git](#) repository located [here](#). You can download the project with the following command after installing git on your system.

```
1 git clone github.com/rbong/rig-inmoov
```

1.1 Dependencies

The embedded system (servo and flex sensor glove code) currently depends on [Python](#) for an example script, [Arduino](#) for the actual code, [Doxygen](#) and [texlive](#) (if you wish to remake the documentation), [Make](#) (if you wish to build the project), and [ROS/LibSerial](#) for the simulation.

1.2 Quick Start

To quickly upload to the right hand without using **make**, do the following. Copy the **arduino/sketch/servo** folder to your [Arduino sketchbook folder](#) or any new folder. Copy [servo/settings/servo_rhand.h](#) to **servo/settings.h** in the sketch directory. Open the Arduino software. [Select your board and the port](#) it is connected to. Open (**File>Open**) [servo.ino](#), and hit upload. Other Arduino files on the bot can be built in a similar way, or the **make** system command can be used. See [Installation](#) for using make.

To transmit commands to the board, run this from the command line.

```
1 python -i example/servo_demo.py
```

You can now run commands defined in [servo_demo](#).

The python script needs the pyserial library. Its website is located [here](#).

See [servo_demo.connect](#) to connect to the board.

To demo some movements, run this.

```
1 demo ()
```

Note that some movements require input before continuing (press enter).

See [servo_demo.cmd](#) for sending any movement commands. Send strings of bytes as defined in [Arduiono](#) and [Examples](#).

The example script can also be used to calibrate the motors. Read the [servo_demo](#) documentation for more.

To run the 3D simulation of the project, please refer to [Simulation](#).

1.3 Installation

You can build this documentation with the command

```
1 make documentation
```

from the root directory.

To upload the right hand servo code to the connected Arduino, run

```
1 make servo.ino SETTINGS=servo_rhand ARDUINO_DO=-upload BOARD=nano PORT='/dev/ttyUSB0'
```

Assuming the board is the arduino nano. For the arduino uno, BOARD would be uno and PORT would be `/dev/ttyACM0`. If multiple boards are connected, or if a board connects and disconnects quickly, the port number may increment. For example, `/dev/ttyUSB1`. If you wish to modify **Makefile**, please refer to [the make manual](#).

This also requires that the latest version of **Arduino** is installed. Some systems don't have a package for the latest version, such as Ubuntu. The previous version of **Arduino** does not have command line capabilities and cannot be automated. Fortunately, the build system creates a valid arduino directory structure that we can open in the graphical **Arduino** IDE. In this case, you can run

```
1 make servo.ino SETTINGS=servo_rhand
```

And **Arduino** will open. Open a project and navigate to **rig-inmoov/build/servo** and open the [servo.ino](#) file inside.

1.4 Build System

Arduino Directory Structure

The Arduino IDE abstracts many tools for working with Arduino hardware. We choose to use it because of its ease of use and cross system compatibility. However, the **Arduino** IDE only recently started coming with control tools for the command line (a process which **make** uses to compile and upload the project). Some versions of Linux do not come with the newest version of Arduino. Replicating the process performed by the **Arduino** IDE requires complex tools not appropriate for this project.

What follows is a description of what **make** performs to build and upload the embedded code (as defined in **Makefile**) for those not able to use the newest version of **Arduino**.

To share code among certain boards, general code is kept in subdirectories under **rig-inmoov/arduino/sketch**. Inside each subdirectory is an `.ino` file of the same name, which is the source for the sketch. There is also a **settings** folder in which various headers are kept. These headers are to be moved to **settings.h** inside the sketch folder. For example, code to be shared among servos is kept in [arduino/sketch/servo/servo.ino](#), the configuration for the right hand is kept in [arduino/sketch/servo/settings/servo_rhand.h](#), and you would move it to **arduino/sketch/servo/settings.h** (or another folder which you moved [servo.ino](#) into) to use it. You would then open [servo.ino](#) in the **Arduino** IDE.

Some sketches require shared code that use Arduino libraries, which means that they need to be contained in `.ino` files. Arduino includes any `.ino` files inside a sketch subdirectory. We keep such files in **arduino/lib**.

The reason that we do not use `.ino` files for settings files is that `.ino` files do not have a guaranteed order of inclusion.

1.5 Arduino Protocol

The Arduinos controlling the various parts of the bot communicate over their serial ports. All information is sent and recieved using 8 bit unsigned raw integers instead of text. This allows extremely fast and simple code, but limits programs to 255 signals, identifiers, and values.

1.5.1 Servo Boards

The Arduino servo boards only have one function; to pass commands to their servos.

Servo ID

Unless otherwise instructed, the servo boards accept two values at a time. First, it accepts a servo ID, and a value to write to the pin associated with that servo.

Servo IDs start at 0 and should be uniquely identified on every board, allowing a maximum of 255 servos on each bot, not including signals. They should be assigned different values because if commands are routed through a central board, it allows the protocol to remain the same. If an invalid servo ID is passed to any given board, the board will still read another value from the serial port to avoid syncing issues, but it will do nothing to its servos.

Servo Values

The value passed to the servo can be from 0-180. If it exceeds 180 and is not a valid signal, the board will change the angle to 180. On positional rotation servos, this number represents the servo's target angle. On continuous rotation servos, 90 represents stillness, 180 represents full speed in one direction, and 0 represents full speed in the other.

Each board has callibrations for each servo that scale the angles from 0-180 to some minimum angle and some maximum angle. The host program has no need to know these values. When the board reports current values, they are scaled.

To ensure that the board is reading the correct information (servo ID or servo position), there is a cancel signal.

1.5.2 Signals

All boards accept some pre-defined signals that break the default flow. It can receive these signals at any time and will terminate its current servo command. In addition, the board may print some signals to output. Both kinds of signals, incoming and outgoing, are assigned starting from 255 and going down. In the arduino code, incoming signals are denoted by `*_SIGNAL`, and the outgoing signals are denoted by `*_RESPONSE`. We will use this convention.

1.5.2.1 CANCEL_SIGNAL

This signal exists to cancel all pending input and synchronize the host and master. If a host connects to an Arduino and does not know its current state, it can send this signal and know that the board is waiting on a servo ID.

1.5.2.2 WAIT_RESPONSE

This response indicates that the board has no bytes left to read and is ready for input. A host does not need to wait for this response, but it may want to if it is experiencing difficulties or the board may have crashed.

1.5.2.3 START_RESPONSE

1.5.2.4 END_RESPONSE

These responses mark the beginning and end of a reply to some signal.

1.5.2.5 DUMP_SIGNAL

This signal makes the board return various information about itself and its servos. As of writing, it returns **START_RESPONSE**, an ID, its number of servos, the IDs of each servo followed by the value last sent to that servo, and **END_RESPONSE**. If a serial connection has access to other boards and is able to send them commands, it may send more servo IDs and servo positions before **END_RESPONSE**. Board IDs start from 181 and go up. It is recommended that if we build more modular bots such as this one in the future using the same protocol, they receive unique board identifiers. The response is likely to change in the near future as we add sensors and other types of devices. Be sure to regularly check this document.

1.5.3 Examples

```
1 CANCEL_SIGNAL 0 180 1 135 2 90
```

This would send the servo with ID 0 a value of 180, servo 1 135, and servo 2 90. The board would then respond with **WAIT_RESPONSE**.

```
1 CANCEL_SIGNAL 0 180 1 135 22 CANCEL_SIGNAL 4 45
```

This would send the servo with ID 0 a value of 180, servo 1 135, begin to read a command for servo 22 but cancel, then send 45 to servo 4.

```
1 CANCEL_SIGNAL 0 0 1 45 2 90 3 135 4 180 DUMP_SIGNAL
```

On a board with ID **BOARD_ID** and 5 servos identified as 0-4, this would return the response

```
1 START_RESPONSE BOARD_ID 4 0 0 1 45 2 90 3 135 4 180 END_RESPONSE WAIT_RESPONSE
```

```
1 CANCEL_SIGNAL 0 0 0 45 0 90 0 135 0 180
```

If this stream of bytes were sent instantly, it would essentially move servo 0 directly to 180 degrees (if it was a positional servo) because of the speed of the commands. However, if we inserted a slight delay, we could slowly move the servo from its starting position to its ending position.

```
1 CANCEL_SIGNAL 0 0 1 0 0 45 1 45 0 90 1 90 0 135 1 135 0 180 1 180
```

This would move servo 0 and servo 1 from their start to end positions. If we were to send these bytes immediately, they would essentially both move instantaneously to 180 degrees (if they were positional servos). However, if we were to insert a delay, they would both appear to move together slowly to their end location despite the delay between commands. Putting this functionality on the Arduino boards themselves would cause the boards to lock and use up resources, but formulating commands like this allows computation to occur on other systems.

1.5.4 Values

Board IDs

Right hand servo board	181
Right hand flex sensor board	182

Servo IDs

Right hand wrist	0
Right hand thumb	1
Right hand index finger	2
Right hand middle finger	3
Right hand ring finger	4
Right hand pinky finger	5

Signals

CANCEL_SIGNAL	255
WAIT_RESPONSE	254
DUMP_SIGNAL	253
START_RESPONSE	252
END_RESPONSE	251

Chapter 2

Simulation

The simulation for the RIGbot runs in ROS. It accepts commands in the same protocol described in [index.Arduino](#). You must first use git to download the project, detailed in [Introduction](#).

This section only details basic usage and slight modification. For the information required to add any new features, model modifications, or bug fixes, you may need to read the beginner level [ROS tutorials](#) and the [urdf tutorials](#).

2.1 Dependencies

The simulation depends on [ROS](#). We use the **Jade** version, as it is the long term release. It is recommended you [install the full system](#) because of the number of the large number of ROS packages. On Ubuntu, this is achieved with the following commands.

```
1 sudo sh -c 'echo "deb http://packages.ros.org/ros/ubuntu $(lsb_release -sc) main" >
  /etc/apt/sources.list.d/ros-latest.list'
2 sudo apt-key adv --keyserver hkp://pool.sks-keyservers.net:80 --recv-key 0xB01FA116
3 sudo apt-get update
4 sudo apt-get install ros-jade-desktop-full
```

If you experience problems, please read the full wiki article.

2.2 Building

To build the simulation, simply run the following from the root directory of the project.

```
1 make simulation
```

You may also want to build manually. Before running any ROS commands, you must run this command.

```
1 source /opt/ros/jade/setup.bash
```

There are also `.zsh` and `.sh` files for users of **zsh** or **sh**. It is recommended you append this command to your shell's `.rc` file (ex. `~/.bashrc`). Make sure to fill in the absolute path to **rig-inmoov/catkin-ws**.

The following only needs to be run once.

```
1 cd catkin_ws/src
2 catkin_init_workspace
```

Finally, we can build the project.

```
1 cd catkin_ws
2 catkin_make
```

2.3 Usage

After running all the necessary setup commands, you can finally run the simulation.

```
1 roslaunch robot_description display.launch port:=/dev/ttyACM0
```

This requires that an input board such as the flex sensor glove is connected. Replace "port" with the port your desired board is connected on (search for the naming convention for your board online). The output from launch commands is captured in `~/ros/log/`.

You can also set and change the port later with the following command.

```
1 rosparam set /serial_publisher/port /path/to/port
```

The serial publisher does not need to be running.

If the serial publisher crashes because it loses connection, you can re-launch it with this command without ending the visualizer.

```
1 rosruncatkin_ws/src/robot_descriptionserial_publisher
```

2.4 Background

We have two custom programs used to maintain the simulation. The first is **serial_publisher**, compiled from **catkin_ws/src/robot_description/src/serial_publisher.cpp**. This program accepts input from a serial port and translates it to a **ROS topic**.

The other program is **state_publisher**, compiled from **state_publisher.cpp** in the same directory. This program listens to the topic and translates it into joint positions, which **rviz** (the visualizer component of ROS) listens to. It expects input of the same protocol as described in Introduction.

The modularity of these programs makes it easy to write publishers for new protocols (such as bluetooth) using just **serial_publisher.cpp** as reference. It also makes it easy to add new parts to **state_publisher**. New programs need to be added to **catkin_ws/src/robot_description/CMakeLists.txt**.

The rviz visualizer is loaded with a **urdf** file, stored in **catkin_ws/src/robot_description/model.xml**, that describes how the different 3D models that make up movable parts are positionally related to one another.

2.5 Debugging

There are two example launch files used for debugging, stored in **catkin_ws/src/robot_description/launch** along with **display.launch**. The first is **debug.launch**, which launches **state_publisher** and **serial_publisher** in gdb, and the second, **memdebug.launch**, launches both programs in Valgrind. It is recommended that you use the three launch files as reference when modifying and creating program systems.

Chapter 3

Namespace Documentation

3.1 servo_demo Namespace Reference

Documentation for the [servo_demo.py](#) script.

Functions

- def [connect](#) (port)
Sets the global [ser](#) variable.
- def [sweep](#) (initial, servos, starts, ends, steps)
Produces complex command chains.
- def [unsweep](#) (servos, ends, steps)
Produces a command chain that resets all servos to 0.
- def [servowrite](#) (commands, delay)
Writes commands to the serial port.
- def [gesture](#) (initial, servos, starts, ends, steps, delay)
Sets the servos to a position, waits for input, then resets them to 0.
- def [reset](#) ()
Immediately sets the servos to 0.
- def [cmd](#) ()
Sends the input to the serial port until a blank line is given.
- def [dump](#) (servos=6)
Retrieves information about the board.
- def [peace](#) (delay=0)
Makes a peace sign.
- def [ok](#) (delay=0.01)
Makes an ok sign.
- def [grab](#) (delay=0.02)
Makes a fist.
- def [rockon](#) (delay=0.01)
Makes a rock on sign.
- def [wiggle](#) (n=90, delay=0.01, wiggles=1)
Wiggles the fingers.
- def [count](#) ()
Counts to 5 on the fingers.

- def `demo` ()
Performs all movements.
- def `getarrow` ()
- def `calibrate` (s=1)
Calibrate a servo.
- def `calibrate_all` ()

Variables

- int `CANCEL_SIGNAL` = 255
- int `DUMP_SIGNAL` = 253
- int `START_RESPONSE` = 252
- int `END_RESPONSE` = 251
- int `RHAND_ID` = 181
The identification byte of the right hand board.
- `ser` = `serial.Serial()`
The serial connection for input and output.

3.1.1 Detailed Description

Documentation for the `servo_demo.py` script.

An example script for controlling the right hand. This script requires python with a library called pyserial. After installing python 3, pyserial can be installed by calling

```
1 pip install pyserial
```

Or through your package manager. Example:

```
1 sudo apt-get install python-pyserial
```

Once you have the library installed, you must have your **PYTHONPATH** variable set to the location of the library.

```
1 export PYTHONPATH=/usr/lib/python2.7/site-packages
```

Replace 2.7 with your version of python (type in `/usr/lib/python` and press tab once or twice).

This may vary from system to system. See the [python](#) and [pyserial](#) websites for help.

To run the script, execute

```
1 python -i servo_demo.py
```

or in python

```
1 import servo_demo
```

This will allow you to call the functions from a command interpreter. It is recommended you experiment with all functions and view the source to understand how you might produce commands. Also try `demo()` while connected.

The movements included are quickly written and for demo purposes only.

See also

[Introduction](#) for the [servo](#) codes.

3.1.2 Function Documentation

3.1.2.1 `def servo_demo.calibrate (s = 1)`

Calibrate a servo.

Takes one argument, which is the id of a server. [Introduction](#) has the servo codes.

Use the left and right arrow keys to adjust the value of the servo. Use any other key to exit.

Enter the maximum values into the [limit](#) array in your settings file.

Note that if a servo isn't moving the correct way, for example if a finger isn't flat at 0 and curved at 180, you must set [reverse](#) to 1 at the servo index.

Definition at line 373 of file `servo_demo.py`.

3.1.2.2 `def servo_demo.cmd ()`

Sends the input to the serial port until a blank line is given.

Must enter integers between 0-255.

See also

[Introduction](#)

Definition at line 227 of file `servo_demo.py`.

3.1.2.3 `def servo_demo.connect (port)`

Sets the global [ser](#) variable.

Call this to connect to the board.

```
1 connect ('/dev/ttyUSB0')
```

Replace `/dev/ttyUSB0` with the name of the port your board is connected to. Usually this is `/dev/ttyUSB*` for the arduino nano or `/dev/ttyACM*` for the arduino uno. This is the same port used in [Installation](#).

Note that you must be part of the dialout group in Linux. Enter this command to add yourself to a group.

```
1 usermod -a -G dialout $USER
```

You must logout to apply group changes. If you cannot logout, you can run the script as root.

```
1 sudo su
2 export PYTHONPATH=/usr/lib/python2.7/site-packages
3 python -i example/servo_demo.py
```

Definition at line 70 of file `servo_demo.py`.

3.1.2.4 `def servo_demo.count ()`

Counts to 5 on the fingers.

See also

[sweep\(\)](#)

Definition at line 319 of file `servo_demo.py`.

3.1.2.5 `def servo_demo.demo ()`

Performs all movements.

Definition at line 327 of file `servo_demo.py`.

3.1.2.6 `def servo_demo.dump (servos = 6)`

Retrieves information about the board.

The command sends the [DUMP_SIGNAL](#) to the serial port and reads back the response. The response is described in [servo.ino](#).

When you write your own similar function, timing is important.

We may need to increase the response delay on the Arduino if you are unable to receive a response. View the source of this function to understand how it works, but keep in mind it is untested. Also keep in mind that the function is very non-general as it always reads the same amount of bytes instead of looking for the end signal.

Note

While this function could be used to change dynamically between gestures instead of resetting the servos to 0, this function did not exist when this script was first written.

Definition at line 239 of file `servo_demo.py`.

3.1.2.7 `def servo_demo.gesture (initial, servos, starts, ends, steps, delay)`

Sets the servos to a position, waits for input, then resets them to 0.

See also

[sweep\(\)](#) [servowrite\(\)](#)

Definition at line 210 of file `servo_demo.py`.

3.1.2.8 `def servo_demo.grab (delay = 0.02)`

Makes a fist.

See also

[gesture\(\)](#)

Definition at line 293 of file servo_demo.py.

3.1.2.9 `def servo_demo.ok (delay = 0.01)`

Makes an ok sign.

See also

[gesture\(\)](#)

Definition at line 289 of file servo_demo.py.

3.1.2.10 `def servo_demo.peace (delay = 0)`

Makes a peace sign.

See also

[gesture\(\)](#)

Definition at line 285 of file servo_demo.py.

3.1.2.11 `def servo_demo.reset ()`

Immediately sets the servos to 0.

Definition at line 223 of file servo_demo.py.

3.1.2.12 `def servo_demo.rockon (delay = 0.01)`

Makes a rock on sign.

See also

[gesture\(\)](#)

Definition at line 297 of file servo_demo.py.

3.1.2.13 `def servo_demo.servowrite (commands, delay)`

Writes commands to the serial port.

If **delay** is 0, immediately writes a list of ints to [ser](#) as bytes. Otherwise, writes a list of ints to [ser](#) as bytes one at a time.

Inserting a delay controls the speed of the movements.

See also

[connect\(\)](#)

Definition at line 193 of file `servo_demo.py`.

3.1.2.14 `def servo_demo.sweep (initial, servos, starts, ends, steps)`

Produces complex command chains.

The output returned from the function is formatted in such a way that the commands can be transmitted to the serial port at variable speeds.

The parameters must all be lists of the same length whose indexes correspond with **servos**.

Parameters

<i>initial</i>	An array of initial commands to append to.
<i>servos</i>	The servos to control.
<i>starts</i>	The current positions of the servos.
<i>ends</i>	The desired end positions.
<i>steps</i>	The values to use to decrement/increment. Converted to absolute value.

Returns

Upon success, returns the generated list of commands. The commands are surrounded by the [CANCEL_↔ SIGNAL](#) for syncing. The servos will always reach their exact final destination, unless if **steps** at the index of the servo is 0. Upon error, raises '**Invalid sweep command**'. This indicates non-matching list lengths.

Example

```
1 sweep ([], [1,2], [180,0], [90,180], [90,45])
```

Returns

```
1 [CANCEL_SIGNAL, 1, 180, 2, 0, 1, 90, 2, 45, 2, 90, 2, 135, 2, 180, CANCEL_SIGNAL]
```

The protocol this follows is described in [servo.ino](#). By intertwining commands in this way, a delay can be inserted between bytes and fluid motion is still preserved.

Definition at line 101 of file `servo_demo.py`.

3.1.2.15 `def servo_demo.unsweep (servos, ends, steps)`

Produces a command chain that resets all servos to 0.

See also

[sweep\(\)](#)

Definition at line 185 of file servo_demo.py.

3.1.2.16 `def servo_demo.wiggle (n = 90, delay = 0.01, wiggles = 1)`

Wiggles the fingers.

See also

[sweep\(\)](#)

Definition at line 301 of file servo_demo.py.

3.1.3 Variable Documentation

3.1.3.1 `servo_demo.ser = serial.Serial()`

The serial connection for input and output.

Must be initialized.

See also

[connect\(\)](#)

Definition at line 68 of file servo_demo.py.

Chapter 4

File Documentation

4.1 arduino/lib/serial.ino File Reference

```
#include <SoftwareSerial.h>
```

Functions

- SoftwareSerial **cmd_serial** (CMD_RX_PIN, CMD_TX_PIN)
- void **serialSetup** ()
- bool **serialCmdAvailable** ()
- void **serialCmdWait** ()
- void **serialCmdWrite** (uint8_t c)
- void **serialDebugWrite** (uint8_t c)
- uint8_t **serialCmdRead** ()
- int **serialCmdGetByte** ()
- uint8_t **serialDebugRead** ()
- int **serialDebugAvailable** ()
- void **serialDebugPrint** (const char *s)
- void **serialDebugPrintInt** (int i)
- void **serialDebugPrintIntPretty** (const char *pre, int i, const char *post)

4.1.1 Detailed Description

This is the serial communication shared code.

In the near future, this will be shared between Arduino programs for common serial communication tasks.

4.2 arduino/sketch/flex/flex.ino File Reference

```
#include "settings.h"
```

Enumerations

- enum {
CANCEL_SIGNAL = 255, **MIN_SIGNAL** = 250, **MAX_SIGNAL** = 249, **START_RESPONSE** = 252,
END_RESPONSE = 251, **CALIB_RESPONSE_LEN** = FLEXS * 2, **MIN_LIM** = 0, **MAX_LIM** = 1 }

Functions

- void **setup** ()
- void **loop** ()
- int **analogGetInt** (uint8_t flex_index)
- int **getAdjustedFlex** (uint8_t flex_index, int flex_amount)
- int **getFlexMax** (uint8_t flex_index)
- int **getFlexMin** (uint8_t flex_index)
- void **softSerialServoCmd** (uint8_t servo_id, int servo_angle)

Variables

- int **current_pos** [6] = { 0 }

4.2.1 Detailed Description

This is the code for the flex sensor board.

Programs generated with this file translate values read from variable resistance (flex sensors) hooked up to voltage divider into values from 0-180 for the servo controller to read.

4.3 arduino/sketch/flex_double/flex_double.ino File Reference

```
#include "settings.h"
```

Enumerations

- enum {
CANCEL_SIGNAL = 255, **MIN_SIGNAL** = 250, **MAX_SIGNAL** = 249, **START_RESPONSE** = 252,
END_RESPONSE = 251, **CALIB_RESPONSE_LEN** = FLEXS * 2, **MIN_LIM** = 0, **MAX_LIM** = 1 }

Functions

- void **setup** ()
- void **loop** ()
- int **analogGetInt** (uint8_t flex_index)
- int **getAdjustedFlex** (uint8_t flex_index, int flex_amount)
- int **getFlexMax** (uint8_t flex_index)
- int **getFlexMin** (uint8_t flex_index)
- void **softSerialServoCmd** (uint8_t servo_id, int servo_angle)
- void **softSerialServoDebug** (uint8_t servo_id, int servo_angle)

Variables

- int **current_pos** [6] = { 0 }

4.3.1 Detailed Description

This is the code for the flex sensor board.

Programs generated with this file translate values read from variable resistance (flex sensors) hooked up to voltage divider into values from 0-180 for the servo controller to read. It also transmits signals back into the computer through its USB cable to control both the physical arm and the simulation.

4.4 arduino/sketch/servo/servo.ino File Reference

```
#include <Servo.h>
#include "settings.h"
#include <stdint.h>
```

Enumerations

- enum {
MIN_LIM = 0, **MAX_LIM** = 1, **CANCEL_SIGNAL** = 255, **WAIT_RESPONSE** = 254,
DUMP_SIGNAL = 253, **START_RESPONSE** = 252, **END_RESPONSE** = 251, **DUMP_RESPONSE_LEN** =
SERVOS * 2 + 4 }

Functions

- void **setup** ()
- void **loop** ()
- void **serialPrint** (const char *s)
- void **serialPrintInt** (uint8_t i)
- void **serialPrintIntPretty** (const char *pre, uint8_t i, const char *post)
- int **serialGetByte** ()
- void **setServoFromIndex** (uint8_t servo_index, uint8_t servo_angle)
- void **setServoFromID** (int servo_id, uint8_t servo_angle)
- void **dump** ()
- void **serialWait** ()

Variables

- Servo **servo** [SERVOS]
- uint8_t **current_pos** [SERVOS] = { 0 }
- char **buf** [BUFSIZE]

The print buffer.

4.4.1 Detailed Description

This is the common code for all Arduino servo boards.

The program is written to be a simple module that can pass values to servos. Each board needs its own settings file. Because of limitations of the Arduino command line interface, these are included as **settings.h**. The Makefile manages which configuration is currently located in the same directory as this file and named **settings.h**. A better build system in the future could use the tools **avrdude** or **ino**. Other Arduino boards in the project, such as flex sensor boards, use an identical folder structure and include process.

See rhand.h for an example of a settings header, and [Arduino Protocol](#) for information servo IDs and other relevant values.

4.4.2 Enumeration Type Documentation

4.4.2.1 anonymous enum

Enumerator

DUMP_RESPONSE_LEN The length of the response to the dump signal.

Definition at line 44 of file servo.ino.

4.4.3 Function Documentation

4.4.3.1 void dump ()

Writes various information about the board to the serial port. Triggered on reception of [DUMP_SIGNAL](#). Transmits the ID of the board, the number of servos, each servo ID, and the current position of the servos.

See also

[Arduino Protocol](#), [START_RESPONSE](#), [END_RESPONSE](#), [current_pos](#), [getServoIDFromIndex\(\)](#)

Definition at line 265 of file servo.ino.

4.4.3.2 void loop ()

The **loop** function is called continually until the program exits. It performs actions based on [Arduino Protocol](#). Recieves two unsigned 8-bit integers, a servo id and a servo angle, then calls [setServoFromID\(\)](#). If the [DUMP_SIGNAL](#) is recieved at any time, calls [dump\(\)](#) and continues. If the [CANCEL_SIGNAL](#) is recieved, it does nothing and continues. If, at the beginning of the function, there is no pending input, it transmits [WAIT_RESPONSE](#), then does nothing until input is available.

Definition at line 100 of file servo.ino.

4.4.3.3 int serialGetByte ()

Retrieves a byte from the serial port.

Returns

If a normal value is recieved, returns that value as an integer. If [CANCEL_SIGNAL](#) is recieved, returns -1.

Definition at line 180 of file servo.ino.

4.4.3.4 void serialPrint (const char * s)

Prints a string to the serial port if [VERBOSE](#) is enabled.

Definition at line 142 of file servo.ino.

4.4.3.5 void serialPrintInt (uint8_t i)

Prints an integer to the serial port as a string if [VERBOSE](#) is enabled.

Definition at line 153 of file servo.ino.

4.4.3.6 void serialPrintIntPretty (const char * pre, uint8_t i, const char * post)

Prints an integer as a string surrounded by two strings to the serial port if [VERBOSE](#) is enabled.

Definition at line 165 of file servo.ino.

4.4.3.7 void serialWait ()

Waits for serial input to become available then returns.

Definition at line 291 of file servo.ino.

4.4.3.8 void setServoFromID (int servo_id, uint8_t servo_angle)

Writes an angle to a pin associated with a servo ID.

See also

[setServoFromIndex\(\)](#), [getServoIndexFromID\(\)](#)

Definition at line 244 of file servo.ino.

4.4.3.9 void setServoFromIndex (uint8_t servo_index, uint8_t servo_angle)

Writes an angle to a pin associated with a servo index. Servos are controlled by sending varying pulse widths over their signal wire. The adjusted angle will be sent to the servo. Updates [current_pos](#) with the non-adjusted angle. If the servo index is invalid, the function does nothing and exits, but if the angle is out of range, it is changed to a valid value.

Parameters

<i>servo_index</i>	The servo to write to.
<i>servo_angle</i>	The angle to write after adjusting. It may be reversed.

See also

[reverse](#)

Definition at line 205 of file servo.ino.

4.4.3.10 void setup ()

The **setup** function is called at the beginning of the program. In it, we assign a pin to each [servo](#).

Definition at line 61 of file servo.ino.

4.4.4 Variable Documentation

4.4.4.1 uint8_t current_pos[SERVOS] = { 0 }

The current position of each servo. These are updated whenever a servos value is changed and retrieved upon [DUMP_SIGNAL](#).

Definition at line 39 of file servo.ino.

4.4.4.2 Servo servo[SERVOS]

The representation of the servos. Used to keep track of pin assignments and send output.

See also

[getServoIndexFromID\(\)](#), Arduino

Definition at line 33 of file servo.ino.

4.5 arduino/sketch/servo/settings/servo_rhand.h File Reference

Macros

- `#define` [SERVOS](#) 6
- `#define` [BUFSIZE](#) 32

Enumerations

- enum {
 [VERBOSE](#) = 0, [BOARD_ID](#) = 181, [DEBUG_RX_PIN](#) = 1, [DEBUG_TX_PIN](#) = 0,
 [CMD_RX_PIN](#) = 1, [CMD_TX_PIN](#) = 0, [SERIAL_BAUDRATE](#) = 9600 }

Functions

- int [getServoIndexFromID](#) (uint8_t servo_id)
- int [getServoIDFromIndex](#) (uint8_t servo_index)
- int [getServoPinFromIndex](#) (uint8_t servo_index)

Variables

- uint8_t [limit](#) [[SERVOS](#)][2]
- uint8_t [default_pos](#) [[SERVOS](#)] = { 0, 0, 0, 0, 0, 0 }
- uint8_t [reverse](#) [[SERVOS](#)] = { 1, 1, 1, 1, 1, 1 }
- uint8_t [pin_offset](#) = 2

4.5.1 Detailed Description

This is an example **settings.h** for [servo.ino](#).

Every Arduino board on the bot is to be a simple servo controller that accepts commands from serial input, and so they are all to share the code located in [servo.ino](#). Each board needs its own header like this one to define custom information about the board and each servo on the board. This is such a settings file and will be documented as an example.

4.5.2 Macro Definition Documentation

4.5.2.1 #define BUFSIZE 32

Size of the print buffer (must be large enough to hold [DUMP_RESPONSE_LEN](#)).

Definition at line 18 of file servo_rhand.h.

4.5.2.2 #define SERVOS 6

Number of servos to assign.

Definition at line 14 of file servo_rhand.h.

4.5.3 Enumeration Type Documentation

4.5.3.1 anonymous enum

Enumerator

VERBOSE Whether to print debug output to the serial port.

BOARD_ID The unique identification for this board.

Definition at line 54 of file servo_rhand.h.

4.5.4 Function Documentation

4.5.4.1 int getServoIDFromIndex (uint8_t servo_index)

This function gets servo ID using its array index. If the servo index is out of bounds, it returns -1. This must correspond with [getServoIndexFromID\(\)](#).

Definition at line 87 of file servo_rhand.h.

4.5.4.2 int getServoIndexFromID (uint8_t servo_id)

This function gets array index of a servo using its ID. If the servo does not belong to this board, it returns -1. It is recommended that boards with complex ID assignments use a switch statement or a similar solution to save resources. This function must correspond with [getServoIDFromIndex\(\)](#).

See also

[Values](#)

Definition at line 74 of file servo_rhand.h.

4.5.4.3 int getServoPinFromIndex (uint8_t servo_index)

This function returns the desired pin of a servo given its index number, allows complex pin assignment. If the servo index is not valid, returns -1.

Definition at line 100 of file servo_rhand.h.

4.5.5 Variable Documentation

4.5.5.1 uint8_t default_pos[SERVOS] = { 0, 0, 0, 0, 0, 0 }

The default position to set each servo to. Its index corresponds with [servo](#).

Definition at line 42 of file servo_rhand.h.

4.5.5.2 `uint8_t limit[SERVOS][2]`

Initial value:

```
= {  
  { 125, 160 }, { 50, 160 }, { 55, 155 },  
  { 35, 155 }, { 45, 145 }, { 55, 145 },  
}
```

This is the callibration for each servo- its minimum then maximum angle (for positional servos) or its minimum then maximum speed (for continuous rotation servos). Its index corresponds with [servo](#).

Definition at line 34 of file `servo_rhand.h`.

4.5.5.3 `uint8_t pin_offset = 2`

Pin value to begin assigning pins at. Unique to this settings file.

See also

[getServoPinFromIndex\(\)](#)

Definition at line 52 of file `servo_rhand.h`.

4.5.5.4 `uint8_t reverse[SERVOS] = { 1, 1, 1, 1, 1, 1 }`

Indicates whether to reverse the angles for each servo, for servos that turn the wrong way. Its index corresponds with [servo](#).

Definition at line 47 of file `servo_rhand.h`.

Index

arduino/lib/serial.ino, [17](#)
arduino/sketch/flex/flex.ino, [17](#)
arduino/sketch/flex_double/flex_double.ino, [18](#)
arduino/sketch/servo/servo.ino, [19](#)
arduino/sketch/servo/settings/servo_rhand.h, [22](#)

BOARD_ID
 servo_rhand.h, [24](#)
BUFSIZE
 servo_rhand.h, [23](#)

calibrate
 servo_demo, [11](#)
cmd
 servo_demo, [11](#)
connect
 servo_demo, [11](#)
count
 servo_demo, [11](#)
current_pos
 servo.ino, [22](#)

DUMP_RESPONSE_LEN
 servo.ino, [20](#)

default_pos
 servo_rhand.h, [24](#)

demo
 servo_demo, [12](#)

dump
 servo.ino, [20](#)
 servo_demo, [12](#)

gesture
 servo_demo, [12](#)
getServoIDFromIndex
 servo_rhand.h, [24](#)
getServoIndexFromID
 servo_rhand.h, [24](#)
getServoPinFromIndex
 servo_rhand.h, [24](#)

grab
 servo_demo, [12](#)

limit
 servo_rhand.h, [24](#)

loop
 servo.ino, [20](#)

ok
 servo_demo, [13](#)

peace
 servo_demo, [13](#)
pin_offset
 servo_rhand.h, [25](#)

reset
 servo_demo, [13](#)
reverse
 servo_rhand.h, [25](#)
rockon
 servo_demo, [13](#)

SERVOS
 servo_rhand.h, [23](#)

ser
 servo_demo, [15](#)

serialGetByte
 servo.ino, [20](#)

serialPrint
 servo.ino, [21](#)

serialPrintInt
 servo.ino, [21](#)

serialPrintIntPretty
 servo.ino, [21](#)

serialWait
 servo.ino, [21](#)

servo
 servo.ino, [22](#)

servo.ino
 current_pos, [22](#)
 DUMP_RESPONSE_LEN, [20](#)
 dump, [20](#)
 loop, [20](#)
 serialGetByte, [20](#)
 serialPrint, [21](#)
 serialPrintInt, [21](#)
 serialPrintIntPretty, [21](#)
 serialWait, [21](#)
 servo, [22](#)
 setServoFromID, [21](#)
 setServoFromIndex, [21](#)
 setup, [22](#)

servo_demo, [9](#)
 calibrate, [11](#)
 cmd, [11](#)
 connect, [11](#)
 count, [11](#)
 demo, [12](#)
 dump, [12](#)
 gesture, [12](#)

- grab, [12](#)
- ok, [13](#)
- peace, [13](#)
- reset, [13](#)
- rockon, [13](#)
- ser, [15](#)
- servowrite, [13](#)
- sweep, [14](#)
- unsweep, [14](#)
- wiggle, [15](#)
- servo_rhand.h
 - BOARD_ID, [24](#)
 - BUFSIZE, [23](#)
 - default_pos, [24](#)
 - getServoIDFromIndex, [24](#)
 - getServoIndexFromID, [24](#)
 - getServoPinFromIndex, [24](#)
 - limit, [24](#)
 - pin_offset, [25](#)
 - reverse, [25](#)
 - SERVOS, [23](#)
 - VERBOSE, [24](#)
- servowrite
 - servo_demo, [13](#)
- setServoFromID
 - servo.ino, [21](#)
- setServoFromIndex
 - servo.ino, [21](#)
- setup
 - servo.ino, [22](#)
- sweep
 - servo_demo, [14](#)
- unsweep
 - servo_demo, [14](#)
- VERBOSE
 - servo_rhand.h, [24](#)
- wiggle
 - servo_demo, [15](#)