

J1 Conn_01x15_Pin

1	GND
2	PA0
3	PA15
4	PA2
5	PA3
6	PA6
7	PA5
8	PA8
9	PA7
10	PBD
11	PBL
12	PA14/SWCLK
13	PA9
14	PA10
15	+3V3

J2 Conn_01x15_Pin

1	GND
2	NRST
3	PA15
4	PC14
5	BOOT0
6	PB7
7	PB6
8	PB5
9	PA15
10	PB3
11	PB4
12	GND
13	PA14/SWCLK
14	PA13
15	PA13/SWDIO
SWD	

[illegible]

3V3 Voltage Regulator

The diagram illustrates a 3V3 Voltage Regulator circuit. It features an input filter (5V_FILT) and a battery input (+BATT). A diode (D5, MBR120ESF1G) and a MOSFET (Q1, DMG1013T-7) are used for switching. The regulator IC (U2, LM3676SD-3.3) is configured with VIN, EN, SW, FB, L1, and C12/C13. The output is +3V3. The circuit also includes a feedback network with R8 (100k) and R9 (100k), and a compensation network with C13 (4.7 μF) and C12 (10 μF). The output filter capacitor C12 is specified as 6.3V and All are X5R Dielectric.

The diagram shows three possible connections for the PWR_FLAG pin, each represented by a red diamond symbol with a downward arrow. The connections are labeled below the arrows: 5V_FILT, +3V3, and GND.

Rev: C
Id: 1/1