

Network Balance and Transitivity

Maraam A. Dwidar

Network Analysis Reading Group - UT Austin

March 2, 2017

Roadmap

- ▶ Heider's balance theory
- ▶ Balance theory in social network analysis
- ▶ Transitivity
- ▶ Application
- ▶ Linking balance and transitivity





Heider's Balance Theory

- ▶ Two major types of relations
 - ▶ Attitudes (liking or evaluating)
 - ▶ PLO vs. $P\sim LO$
 - ▶ More specific relations, such as similarity, possession, causality, proximity, or belonging
 - ▶ PUX vs. $P\sim UX$
- ▶ A *balanced state* is defined in terms of certain combinations of these relations

Heider's Balance Theory

- ▶ Heider's definition of a *balanced state* is stated separately for two and for three entities:
 - ▶ Two entities: A balanced state exists if the relation between them is positive (or negative) in all respects
 - ▶ Three entities: A balanced state exists if all three relations are positive in all respects, or if two are negative and one is positive
- ▶ Heider's theory asserts that there is a tendency for units to achieve a balanced state

Depicting Balance



Balance in Social Network Analysis

- ▶ Cartwright and Harary (1956) extend the concept of balance to larger networks, where:
 - ▶ A **cycle** is a sequence of links that begins and ends at the same node
 - ▶ For signed graphs, the sign of a cycle is given by the product of the signs of the links that comprise the cycle
 - ▶ Here, the balance of a signed graph depends on the signs of its cycles
 - ▶ And, a signed graph is balanced if every cycle is positive
- ▶ This definition allows us to assess balance for social networks with any number of actors


Transitivity in Networks

- ▶ Transitivity refers to the extent to which the relation that relates two nodes in a network that are connected by an edge is transitive
- ▶ Perfect transitivity implies that if x is connected (through an edge) to y , and y is connected to z , then x is also connected to z

Quantifying Transitivity in Networks

- ▶ We can quantify transitivity in an undirected network as follows:
 - ▶ Here, a **loop of length three** is a sequence of nodes x, y, z, x such that (x, y) , (y, z) , and (z, x) are edges of the graph
 - ▶ A **path of length two** is a sequence of nodes x, y, z such that (x, y) and (y, z) are edges
 - ▶ Note: Paths and loops are sequences (x, y, z, x is different from y, z, x, y)
- ▶ The **transitivity coefficient** T of a network is the ratio of the number of loops of length three and the number of paths of length two
 - ▶ $T = 1$ implies perfect transitivity, a network whose components are all cliques


Quantifying Transitivity in Networks



- Here, we have 6 loops of length three and 10 paths of length two, so $T = 6/10 = 0.6$

Application

- Using our network of faculty on dissertation committees and the command `transitivity(igraph_obj)`, our $T = 0.42$



Linking Balance and Transitivity

- ▶ Balance is a theory of network relationships
- ▶ Transitivity is a property of networks