

FunSQL

A library for compositional construction
of SQL queries

<https://github.com/MechanicalRabbit/FunSQL.jl>

Clark C. Evans,
Kyrylo Simonov

JuliaCon 2021

FunSQL? Who Needs It?

Query Algebra

Correlated Queries

Aggregate & Window Functions

Conclusion

Find all patients born in or after 1970.



```
SELECT p.person_id  
FROM person p  
WHERE p.year_of_birth >= 1970
```



```
function find_patients(conn)  
  sql = ""  
  SELECT p.person_id  
  FROM person p  
  WHERE p.year_of_birth >= 1970  
  ""  
  DBInterface.execute(conn, sql)  
end
```

Find all patients born between *and*

```
function find_patients(conn; start_year = nothing, end_year = nothing)
  sql = ""
  SELECT p.person_id
  FROM person p
  ""
  predicates = String[]
  if start_year != nothing
    push!(predicates, "p.year_of_birth >= $start_year")
  end
  if end_year != nothing
    push!(predicates, "p.year_of_birth <= $end_year")
  end
  if !isempty(predicates)
    sql *= "\nWHERE " * join(predicates, " AND ")
  end
  DBInterface.execute(conn, sql)
end
```



```
function find_patients(conn; start_year = nothing,  
                        end_year = nothing,  
                        state = nothing,  
                        condition_concepts = [],  
                        latest_visit_threshold = nothing)
```

```
    sql = ???
```

```
    DBInterface.execute(conn, sql)
```

```
end
```

FunSQL? Who Needs It?

Query Algebra

Correlated Queries

Aggregate & Window Functions

Conclusion



A fragment of OMOP CDM
<https://github.com/OHDSI/CommonDataModel>

```
using FunSQL: SQLTable
```

```
const person =  
  SQLTable(name = :person,  
    columns = [:person_id, :year_of_birth, :location_id])
```

```
const location =  
  SQLTable(name = :location,  
    columns = [:location_id, :city, :state, :zip])
```

```
const visit_occurrence =  
  SQLTable(name = :visit_occurrence,  
    columns = [:visit_occurrence_id, :person_id, :visit_concept_id,  
      :visit_start_date, :visit_end_date])
```

```
const condition_occurrence =  
  SQLTable(name = :condition_occurrence,  
    columns = [:condition_occurrence_id, :person_id, :condition_concept_id,  
      :condition_start_date, :condition_end_date])
```



Find all patients born in or after 1970.

FROM person p



FROM person p
WHERE p.year_of_birth >= 1970




SELECT p.person_id
FROM person p
WHERE p.year_of_birth >= 1970

using FunSQL: From, Get, Select, Where, render

q = From(person)



q = From(person) |>
Where(Get.year_of_birth .>= 1970)



q = From(person) |>
Where(Get.year_of_birth .>= 1970) |>
Select(Get.person_id)

sql = render(q, dialect = :postgresql)

```

q1 = From(person)
q2 = q1 |> Where(q1.year_of_birth .>= 1970)
q   = q2 |> Select(q2.person_id)

```



```

q = From(person) |>
  Where(Get.year_of_birth .>= 1970) |>
  Select(Get.person_id)

```



```

BornInOrAfter(Y) = Get.year_of_birth .>= Y

```

```

q = From(person) |>
  Where(BornInOrAfter(1970)) |>
  Select(Get.person_id)

```

bound references

unbound references

person	
PK	person_id
	year_of_birth
FK	location_id

```
SELECT p.person_id  
FROM person p  
WHERE p.year_of_birth >= 1970
```

```
WHERE p.year_of_birth >= 1970 AND  
      p.year_of_birth <= 2000
```

```
WHERE p.year_of_birth  
      BETWEEN 1970 AND 2000
```

```
SELECT AVG(p.year_of_birth)  
FROM person p
```

using FunSQL: Agg, Fun

"Fun" notation

Fun.">="(Get.year_of_birth, 1970)

or

Get.year_of_birth .>= 1970

broadcasting

Fun.and(Get.year_of_birth .>= 1970,
 Get.year_of_birth .<= 2000)

Fun.between(Get.year_of_birth, 1970, 2000)


Agg.avg(Get.year_of_birth)

Show patients with their state of residence.

FROM person p



FROM person p
JOIN location l
 ON (p.location_id = l.location_id)




SELECT p.person_id, l.state
FROM person p
JOIN location l
 ON (p.location_id = l.location_id)

using FunSQL: Join

q = From(person)



q = From(person) |>
 Join(:location => location,
 Get.location_id .==
 Get.location.location_id)



q = From(person) |>
 Join(:location => location,
 Get.location_id .==
 Get.location.location_id) |>
 Select(Get.person_id, Get.location.state)



```

qp = From(person)
ql = From(location)
q  = qp |> Join(ql, qp.location_id .== ql.location_id)

```



Get

- person_id
- year_of_birth
- location_id*
- city
- state

```

q = From(person) |>
  Join(:location => From(location),
    Get.location_id .== Get.location.location_id)

```

Get

- person_id
- year_of_birth
- location_id
- location**
 - location_id
 - city
 - state

person

PK	person_id
	year_of_birth
FK	location_id

location



PK	location_id
	city
	state

Find patients

- *born in or after 1970*
- *living in Illinois*

```
qp = From(person) |>  
  Where(Get.year_of_birth .>= 1970)
```

```
ql = From(location) |>  
  Where(Get.state .== "IL")
```



```
qp |> Join(ql, qp.location_id .== ql.location_id) |>  
  Select(qp.person_id)
```



FROM person p



FROM person p
WHERE p.year_of_birth >= 1970



FROM person p
WHERE p.year_of_birth >= 1970
JOIN location l
 ON (p.location_id = l.location_id)

From(person)




From(person) |>
Where(Get.year_of_birth .>= 1970)




From(person) |>
Where(Get.year_of_birth .>= 1970) |>
Join(:location => From(location),
 Get.location_id .==
 Get.location.location_id)


FROM ...



**FROM ...
JOIN ...
WHERE ...
GROUP BY ...
HAVING ...
ORDER BY ...**



**SELECT ...
FROM ...
JOIN ...
WHERE ...
GROUP BY ...
HAVING ...
ORDER BY ...**



**FROM (
SELECT ...
FROM ...
JOIN ...
WHERE ...
GROUP BY ...
HAVING ...
ORDER BY ...)**

From(*table*)

```
SELECT ???  
FROM $table
```

|>
Where(*condition*)

```
SELECT ???  
FROM ()  
WHERE $condition
```

|>
Join(, *on*)

```
SELECT ???  
FROM ()  
JOIN ()  
ON $on
```

|>
Select(*list...*)

```
SELECT $(list...)  
FROM ()
```

SELECT ???
FROM person

SELECT ???
FROM location

SELECT ???
FROM () p
WHERE p.year_of_birth >= 1970

SELECT ???
FROM () l
WHERE l.state = 'IL'

```
q1 = From(person)
q2 = q1 |> Where(q1.year_of_birth .>= 1970)
q3 = From(location)
q4 = q3 |> Where(q3.state .== "IL")
q5 = q2 |> Join(q4, q2.location_id .==
               q4.location_id)
q6 = q5 |> Select(q5.person_id)
```

SELECT ???
FROM () p
JOIN () l
ON p.location_id = l.location_id

SELECT p.person_id
FROM () p

```
SELECT person_id, year_of_birth, location_id
FROM person
```

```
SELECT location_id, state
FROM location
```

```
SELECT p.person_id, p.location_id
FROM ( ) p
WHERE p.year_of_birth >= 1970
```

```
SELECT l.location_id
FROM ( ) l
WHERE l.state = 'IL'
```

```
q1 = From(person)
q2 = q1 |> Where(q1.year_of_birth .>= 1970)
q3 = From(location)
q4 = q3 |> Where(q3.state .== "IL")
q5 = q2 |> Join(q4, q2.location_id .==
               q4.location_id)
q6 = q5 |> Select(q5.person_id)
```

```
SELECT p.person_id
FROM ( ) p
JOIN ( ) l
  ON p.location_id = l.location_id
```

```
SELECT p.person_id
FROM ( ) p
```

```
SELECT person_id, year_of_birth, location_id
FROM person
```

```
SELECT location_id, state
FROM location
```

```
SELECT p.person_id, p.location_id
FROM person p
WHERE p.year_of_birth >= 1970
```

```
SELECT l.location_id
FROM location l
WHERE l.state = 'IL'
```

```
q1 = From(person)
q2 = q1 |> Where(q1.year_of_birth .>= 1970)
q3 = From(location)
q4 = q3 |> Where(q3.state .== "IL")
q5 = q2 |> Join(q4, q2.location_id .==
               q4.location_id)
q6 = q5 |> Select(q5.person_id)
```

```
SELECT p.person_id
FROM ( ) p
JOIN ( ) l
ON p.location_id = l.location_id
```

```
SELECT p.person_id
FROM ( ) p
```

Find patients

- *born in or after 1970*
- *living in Illinois*

```
q1 = From(person)
q2 = q1 |> Where(q1.year_of_birth .>= 1970)
q3 = From(location)
q4 = q3 |> Where(q3.state .== "IL")
q5 = q2 |> Join(q4, q2.location_id .==
                  q4.location_id)
q6 = q5 |> Select(q5.person_id)
```


```
SELECT p.person_id
FROM (SELECT p.person_id, p.location_id
        FROM person p
        WHERE p.year_of_birth >= 1970) p
JOIN (SELECT l.location_id
        FROM location l
        WHERE l.state = 'IL') l
ON p.location_id = l.location_id
```

using FunSQL: Define

const ObservationYear = 2000

```
FromPerson() =  
  From(person) |>  
  Define(:approx_age => ObservationYear .- Get.year_of_birth)
```

```
FromAdult() =  
  FromPerson() |>  
  Where(Get.approx_age .>= 18)
```



```
julia> q = FromAdult() |> Select(Get.person_id, Get.approx_age)
```

```
julia> q = FromAdult() |> Select(Get.person_id, Get.approx_age)
let person = SQLTable(:person, ...),
q1 = From(person),
q2 = q1 |> Define(Fun."-(Lit(2000), Get.year_of_birth) |> As(:approx_age)),
q3 = q2 |> Where(Fun.">="(Get.approx_age, Lit(18))),
q4 = q3 |> Select(Get.person_id, Get.approx_age)
q4
end
```

FunSQL? Who Needs It?

Query Algebra

Correlated Queries

Aggregate & Window Functions

Conclusion

Find all patients born in or after \$YEAR.

```
sql = """
SELECT p.person_id
FROM person p
WHERE p.year_of_birth >= :YEAR
"""
```

```
params = (YEAR = 1970,)
```

using FunSQL: Var, pack

```
q = From(person) |>
  Where(Get.year_of_birth .>= Var.YEAR) |>
  Select(Get.person_id)
```


```
sql = render(q, dialect = :sqlite)
```

```
params = pack(sql, (YEAR = 1970,))
```

```
DBInterface.execute(sql, params)
```

Find patients with at least one medical condition.

```
SELECT p.*  
FROM person p  
WHERE EXISTS (SELECT NULL  
              FROM condition_occurrence c  
              WHERE c.person_id = p.person_id)
```




Find patients with at least one medical condition.

```
SELECT p.*  
FROM person p  
WHERE EXISTS (SELECT NULL  
              FROM condition_occurrence c  
              WHERE c.person_id = p.person_id)
```


```
qp = From(person)  
qc = From(condition_occurrence)  
qcorr = qc |> Where(qc.person_id .== qp.person_id)  
q = qp |> Where(Fun.exists(qcorr))
```

ERROR: Cannot find person_id



Find patients with at least one medical condition.


```
SELECT p.*
FROM person p
WHERE EXISTS (SELECT NULL
              FROM condition_occurrence c
              WHERE c.person_id = p.person_id)
```




CorrelatedCondition : $X \mapsto$

```
SELECT NULL
FROM condition_occurrence c
WHERE c.person_id = X
```

```
SELECT p.*
FROM person p
WHERE EXISTS CorrelatedCondition(p.person_id)
```



```
From(condition_occurrence) |>  
Where(Get.person_id .== Var.X)
```



```
CorrelatedCondition(X) =  
  From(condition_occurrence) |>  
  Where(Get.person_id .== Var.X) |>  
  Bind(:X => X)
```


```
CorrelatedCondition(6)
```

```
SELECT c.*  
FROM condition_occurrence c  
WHERE c.person_id = :X
```

```
SELECT c.*  
FROM condition_occurrence c  
WHERE c.person_id = 6
```

```
CorrelatedCondition(X) =  
  From(condition_occurrence) |>  
  Where(Get.person_id .== Var.X) |>  
  Bind(:X => X)
```

```
CorrelatedCondition(6)
```



```
From(person) |>  
Where(Fun.exists(  
  CorrelatedCondition(Get.person_id))
```

```
SELECT c.*  
FROM condition_occurrence c  
WHERE c.person_id = 6
```

```
SELECT p.*  
FROM person p  
WHERE EXISTS (SELECT NULL  
              FROM condition_occurrence c  
              WHERE c.person_id = p.person_id)
```

FunSQL? Who Needs It?

Query Algebra


Correlated Queries

Aggregate & Window Functions


Conclusion

Number of patients by the year of birth.

FROM person p




FROM person p
GROUP BY p.year_of_birth




SELECT p.year_of_birth, COUNT(*)
FROM person p
GROUP BY p.year_of_birth

using FunSQL: Agg, Group

From(person)




From(person) |>
Group(Get.year_of_birth)



From(person) |>
Group(Get.year_of_birth) |>
Select(Get.year_of_birth, Agg.count())


Average year of birth.

FROM person p




SELECT AVG(p.year_of_birth)
FROM person p

From(person)




From(person) |>
Group()




From(person) |>
Group() |>
Select(Agg.avg(Get.year_of_birth))

Patients who saw a doctor within the last 12 months.

FROM visit_occurrence v




FROM visit_occurrence v
GROUP BY v.person_id




SELECT v.person_id
FROM visit_occurrence v
GROUP BY v.person_id
HAVING CURRENT_DATE -
MAX(v.visit_start_date) <= 365

From(visit_occurrence)



From(visit_occurrence) |>
Group(Get.person_id)



From(visit_occurrence) |>
Group(Get.person_id) |>
Where(Fun.current_date() .-
Agg.max(Get.visit_start_date) .<= 365)

visit_occurrence	
PK	visit_occurrence_id
FK	person_id
	visit_concept_id
	visit_start_date
	visit_end_date

|>
Group(*by...*)

```
SELECT $(by...), ???  
FROM ()  
GROUP BY $(by...)
```

Patients who saw a doctor within the last 12 months.

```
From(visit_occurrence) |>  
Group(Get.person_id) |>  
Where(Fun.current_date() .-  
      Agg.max(Get.visit_start_date) .<= 365)
```

```
SELECT person_id, visit_start_date  
FROM visit_occurrence
```

```
SELECT v.person_id,  
       MAX(v.visit_start_date) AS max  
FROM ( ) v  
GROUP BY v.person_id
```

```
SELECT g.person_id  
FROM ( ) g  
WHERE CURRENT_DATE - g.max <= 365
```

Patients who saw a doctor within the last 12 months.

```
From(visit_occurrence) |>  
Group(Get.person_id) |>  
Where(Fun.current_date() .-  
      Agg.max(Get.visit_start_date) .<= 365)
```


```
SELECT person_id, visit_start_date  
FROM visit_occurrence
```

```
SELECT v.person_id,  
FROM visit_occurrence v  
GROUP BY v.person_id  
HAVING CURRENT_DATE -  
        MAX(v.visit_start_date) <= 365
```


```
SELECT g.person_id  
FROM ( ) g  
WHERE CURRENT_DATE - g.max <= 365
```

For each visit, show the time passed since the previous visit.

FROM visit_occurrence v




FROM visit_occurrence v
WINDOW w **AS** (**PARTITION BY** v.person_id
 ORDER BY v.visit_start_date)




SELECT v.visit_occurrence_id,
 v.visit_start_date -
 LAG(v.visit_end_date) **OVER** (w)
FROM visit_occurrence v
WINDOW w **AS** (**PARTITION BY** v.person_id
 ORDER BY v.visit_start_date)

using FunSQL: Partition

From(visit_occurrence)



From(visit_occurrence) |>
Partition(Get.person_id,
 order_by = [Get.visit_start_date])



From(visit_occurrence) |>
Partition(Get.person_id,
 order_by = [Get.visit_start_date]) |>
Define(:gap => Get.visit_start_date .-
 Agg.lag(Get.visit_end_date)) |>
Select(Get.visit_occurrence_id, Get.gap)

visit_occurrence	
PK	visit_occurrence_id
FK	person_id
	visit_concept_id
	visit_start_date
	visit_end_date

```
 |>  
Partition(by..., order_by = [])
```

```
SELECT ???  
FROM ()  
WINDOW w AS (PARTITION BY $(by...)  
                  ORDER BY $(order_by...))
```

Merge overlapping visits.

```
From(visit_occurrence) |>
Partition(Get.person_id,
          order_by = [Get.visit_start_date],
          frame = (mode = :rows, start = -Inf, finish = -1)) |>
Define(:boundary => Agg.max(Get.visit_end_date)) |>
Define(:bump => Fun.case(Get.visit_start_date .<= Get.boundary, 0, 1)) |>
Partition(Get.person_id,
          order_by = [Get.visit_start_date, .- Get.bump],
          frame = :rows) |>
Define(:group => Agg.sum(Get.bump)) |>
Group(Get.person_id, Get.group) |>
Define(:start_date => Agg.min(Get.visit_start_date),
      :end_date => Agg.max(Get.visit_end_date)) |>
Select(Get.person_id, Get.start_date, Get.end_date)
```

visit_occurrence	
PK	visit_occurrence_id
FK	person_id
	visit_concept_id
	visit_start_date
	visit_end_date


FunSQL? Who Needs It?

Query Algebra


Correlated Queries

Aggregate & Window Functions

Conclusion



```
function find_patients(conn; start_year = nothing,  
                        end_year = nothing,  
                        state = nothing,  
                        condition_concepts = [],  
                        latest_visit_threshold = nothing)  
  q = FindPatients(; start_year, end_year, state,  
                    condition_concepts, latest_visit_threshold)  
  sql = render(q, dialect = :postgresql)  
  DBInterface.execute(conn, sql)  
end
```



```
FindPatients(; start_year = nothing, end_year = nothing,  
             state = nothing,  
             condition_concepts = [],  
             latest_visit_threshold = nothing) =  
  From(person) |>  
  FilterByYearOfBirth(; start_year, end_year) |>  
  FilterByState(; state) |>  
  FilterByConditions(; condition_concepts) |>  
  FilterByLatestVisit(; latest_visit_threshold) |>  
  Select(Get.person_id)
```

```
FilterByYearOfBirth(; start_year, end_year) =  
  if start_year != nothing && end_year != nothing  
    Where(Fun.between(Get.year_of_birth, start_year, end_year))  
  elseif start_year != nothing  
    Where(Get.year_of_birth .>= start_year)  
  elseif end_year != nothing  
    Where(Get.year_of_birth .<= end_year)  
  else  
    identity  
  end
```

```
FilterByState(; state) =  
  if state != nothing  
    Join(:location => From(location) |>  
      Where(Get.state .== state),  
      Get.location_id .== Get.location.location_id)  
  else  
    identity  
  end
```

```
ConditionsByPerson(person_id; condition_concepts) =  
  From(condition_occurrence) |>  
  Where(Fun.and(Fun.in(Get.condition_concept_id, condition_concepts...),  
                Get.person_id .== Var.person_id)) |>  
  Bind(:person_id => person_id)  
  
FilterByConditions(; condition_concepts) =  
  if !isempty(condition_concepts)  
    Where(Fun.exists(ConditionsByPerson(Get.person_id, condition_concepts)))  
  else  
    identity  
  end
```

```
FilterByLatestVisit(; latest_visit_threshold) =  
  if latest_visit_threshold != nothing  
    Join(:visit_group => From(visit_occurrence) |>  
      Group(Get.person_id),  
      Get.person_id .== Get.visit_group.person_id) |>  
    Define(:latest_visit_date => Agg.max(Get.visit_start_date, over = Get.visit_group)) |>  
    Where(Fun.current_date() .- Get.latest_visit_date .<= latest_visit_threshold)  
  else  
    identity  
  end
```

DONE

- Select
- Where
- (Inner/Left/Right) Join
- Group, aggregate and window functions
- Parameterized Queries
- Correlated Queries
- Append (UNION ALL)
- SQLite, PostgreSQL, RedShift, Microsoft SQL Server

TODO (June 2021)

- CTE and WITH clause
- WITH RECURSIVE
- INSERT, UPDATE, DELETE
- CREATE TABLE
- Introspection
- Tracking expression types