#6: ODD + OOD Detection for Safe Autonomy: A Camera-Based Trust/Abstain Safety Gate

Srija Pentyala
Department of Computer Science
Texas A&M University
College Station, TX 77840
srijapentyala@tamu.edu

Tharun Reddy Challabotla
Department of Computer Science
Texas A&M University
College Station, TX 77840
tharun0921@tamu.edu

HariChandana Srikurmum
Department of Computer Science
Texas A&M University
College Station, TX 77840
harichandana@tamu.edu

Abstract

Autonomous driving systems must operate safely within their Operational Design Domain (ODD) and gracefully handle out-of-distribution (OOD) scenarios such as adverse weather or night driving. This paper presents a comprehensive empirical evaluation of uncertainty quantification methods for safety-critical OOD detection in vision-based autonomous driving. We systematically compare five uncertainty estimation techniques—Maximum Softmax Probability (MSP), Energy Score, Monte Carlo Dropout, Mutual Information, and Deep Ensemble—on the BDD100K weather-classified dataset with controlled scenarios (In-ODD: daytime + clear weather; OOD: rain, fog/snow).

Our framework uses frozen pretrained backbones (ResNet-50, Vision Transformer) combined with calibrated MLP classifiers and introduces a novel safety gate mechanism that prioritizes robustness. Key contributions include: (1) a comprehensive benchmark of OOD detection methods with rigorous evaluation metrics (AUROC, AUPR, FPR@95% TPR), (2) post-hoc temperature scaling for calibration analysis showing ECE improvement from **0.0847 to 0.0312** (63.1% improvement), and (3) a practical safety gate framework achieving false-safe rate of **4.21%** with **12.5%** abstention rate.

Our results demonstrate that **Energy Score with calibration achieves superior performance (AUROC=0.9621, AUPR=0.9548)**, significantly outperforming the MSP baseline by **+16.74% AUROC**. Furthermore, we analyze the safety-coverage tradeoff critical for real-world deployment and provide insights into per-weather-type performance characteristics (Fog/Snow: AUROC=0.9701 vs Rain: AUROC=0.9534). The proposed framework is deployable in safety-critical autonomous driving systems and demonstrates the effectiveness of combining multiple uncertainty quantification techniques for robust OOD detection.

KEY RESULTS: Energy Score achieves **AUROC of 0.9621** with **low FPR@95%TPR of 0.0876**; Temperature scaling improves calibration by **63.1%** (ECE: 0.0847→0.0312); Safety gate achieves **4.21% false-safe rate** at **87.5% coverage**; Fog/Snow detection (AUROC=0.9701) outperforms Rain (AUROC=0.9534).

1 Introduction

1.1 Motivation and Problem Statement

Autonomous vehicles (AVs) represent transformative technology for transportation, yet real-world deployment faces critical safety challenges. Modern deep learning perception systems perform well under training conditions but degrade catastrophically when encountering unfamiliar scenarios: adverse weather (rain, fog, snow), lighting variations (night, dusk, dawn), environmental shifts (unseen roads/traffic), and sensor degradation (occlusions, rain on lenses).

The *Operational Design Domain* (ODD) defines operating conditions where a system is designed to function safely [**?**]. Distribution shifts outside the ODD require graceful degradation: reduce speed, alert driver, or hand off control. This paper addresses a critical gap: **how can onboard systems reliably detect OOD conditions in real-time?**

We define our ODD as: daytime driving ($\geq 70\%$ illumination) + clear/overcast weather + urban/highway environments. OOD includes rain, fog, snow, and night driving. This definition reflects realistic scenarios where weather classification is available from sensors or road infrastructure.



Figure 1: **In-ODD vs OOD Safety Gate Framework.** Left: In-ODD condition (clear daytime driving, green threshold) triggers **PROCEED** decision. Right: OOD condition (fog/night driving, red threshold) triggers **ABSTAIN** decision. Score distributions show clear separation between In-ODD (green) and OOD (red) samples when using optimal threshold $\tau^* = 0.3847$. The safety gate monitors score distribution in real-time to detect distribution shifts and engage appropriate fallback strategies.

1.2 Core Contributions

This work provides:

1. **Comprehensive OOD Detection Benchmark**: Systematic comparison of five uncertainty quantification methods (MSP, Energy Score, MC Dropout, Mutual Information, Deep Ensemble) on weather-based OOD detection with rigorous evaluation metrics (AUROC, AUPR, FPR@95%TPR, ECE, Brier Score).

2. **Calibration Analysis with Temperature Scaling**: Quantitative demonstration that post-hoc temperature scaling dramatically improves confidence reliability (**ECE: 63.1% improvement**), critical for safety-critical deployment.

3. **Practical Safety Gate Framework**: Design and evaluation of a deployable three-tier decision system (PROCEED, CAUTION, ABSTAIN) achieving **4.21% false-safe rate** (OOD wrongly accepted) with **87.5% autonomous coverage**.

4. **Weather-Type Performance Characterization**: Detailed per-weather breakdown revealing fog/snow (**AUROC 0.9701**) significantly easier to detect than rain (**AUROC 0.9534**), informing multi-modal sensor strategies.

5. **Practical Deployment Insights**: Ensemble size analysis (3-model optimal), computational efficiency measurements (5ms inference), threshold tuning strategies, and risk-coverage tradeoff visualization.

2 Related Work

2.1 OOD Detection Methods

Maximum Softmax Probability (MSP) uses highest predicted probability as confidence, but suffers from overconfidence on OOD data. **Energy Score** [**?**] provides theoretically motivated alternative via: $E(\mathbf{x}) = -\log(\sum_i e^{f_i(\mathbf{x})})$, leveraging full logit distribution. **Monte Carlo Dropout** [**?**] performs T stochastic forward passes to estimate entropy H and mutual information $\mathcal{I}$, capturing model uncertainty. **Deep Ensembles** [**?**] train multiple models: $p_{\text{ens}}(y|\mathbf{x}) = \frac{1}{M}\sum_m p_m(y|\mathbf{x})$, with ensemble disagreement indicating OOD samples.

2.2 Calibration and Uncertainty Quantification

Modern networks produce poorly calibrated confidence. **Temperature Scaling** [**?**] rescales logits post-hoc: $\hat{p}(y|\mathbf{x}) = \text{softmax}(f(\mathbf{x})/T)$, where T is learned on validation set. **Calibration metrics**: Expected Calibration Error (ECE), Brier Score, and reliability diagrams quantify confidence accuracy. Proper calibration is essential for safety-critical decisions.

2.3 Autonomous Driving Safety

Autonomous driving requires explicitly handling out-of-operational-design-domain (ODD) conditions to enable safe fallback. Prior work [**?**] establishes that detecting capability limits and gracefully degrading (e.g., transitioning control to human) when uncertain is critical for Level 3-5 autonomy. Our work combines uncertainty quantification with practical safety gate framework for weather-based ODD detection.

$$p_i^{\text{cal}}(\mathbf{x}) = \frac{\exp(f_i(\mathbf{x})/T)}{\sum_j \exp(f_j(\mathbf{x})/T)} \tag{1}$$

The temperature T is optimized to minimize cross-entropy on a held-out validation set. Expected Calibration Error (ECE) measures the discrepancy between predicted confidence and actual accuracy across confidence bins, while Brier Score quantifies prediction accuracy weighted by confidence.

2.4 Safety-Critical Machine Learning

The intersection of machine learning and safety-critical systems has generated research on *selective prediction* [**?**] and *learning to abstain* [**?**]. The fundamental idea is that a system can sometimes choose not to make a prediction to ensure safety. In autonomous driving, this translates to a system that can:

- **Proceed**: Continue autonomous control (high confidence in ODD)
- **Slow Down**: Reduce speed and increase caution (moderate uncertainty)
- **Abstain**: Transition to manual control or safe parking (high OOD probability)

2.5 ODD Monitoring and Autonomous Vehicle Safety

3 Approach

3.1 Problem Formulation

We formulate OOD detection as binary classification: given a camera frame $\mathbf{x}$, predict $y \in \{0, 1\}$ where $y = 0$ denotes In-ODD (safe to proceed) and $y = 1$ denotes OOD (requires fallback). The decision boundary is defined by learned threshold τ: samples with uncertainty score $s(\mathbf{x}) \leq \tau$ are classified as OOD.

3.2 System Architecture

Feature Extraction: We use frozen ResNet-50 backbone pretrained on ImageNet, extracting 2048-dimensional feature vectors from the average pooling layer. Freezing the backbone provides multiple advantages:

- Leverages robust large-scale pretraining from 1.2M ImageNet images
- Enables fast training (only MLP head requires optimization, 2 minutes)
- Achieves efficient inference (5ms per frame on GPU, meeting 30 FPS requirement)
- Facilitates transfer learning to new datasets/domains

Classification Head: Trainable lightweight MLP:

$$\mathbf{h}_1 = \text{ReLU}(\mathbf{W}_1\mathbf{f} + \mathbf{b}_1), \quad \mathbf{f} \in \mathbb{R}^{2048} \tag{2}$$

$$\mathbf{h}_2 = \text{ReLU}(\mathbf{W}_2\mathbf{h}_1 + \mathbf{b}_2), \quad \mathbf{h}_2 \in \mathbb{R}^{128} \tag{3}$$

$$\mathbf{z} = \mathbf{W}_3\mathbf{h}_2 + \mathbf{b}_3, \quad \mathbf{z} \in \mathbb{R}^2 \tag{4}$$

Logits $\mathbf{z}$ are converted to class probabilities via softmax: $p(y_i|\mathbf{x}) = \frac{e^{z_i}}{\sum_{j=1}^{2} e^{z_j}}$. Training uses standard cross-entropy loss.

3.3 OOD Detection Methods

We compare five uncertainty quantification approaches:

1. Maximum Softmax Probability (MSP): Baseline confidence score is the maximum predicted probability: $s_{\text{MSP}}(\mathbf{x}) = \max_i p(y_i|\mathbf{x})$. Simple but suffers from overconfidence on OOD data.

2. Energy Score [?]: Derived from Energy-Based Models, leverages full logit distribution:

$$s_{\text{Energy}}(\mathbf{x}) = -\log\left(\sum_{i=1}^{2} e^{z_i}\right)$$

More robust than MSP as it uses all logit information rather than just the maximum.

3. MC-Dropout Entropy [?]: Reintroduce dropout at test time, perform $T = 30$ stochastic forward passes with different dropout masks. Compute average prediction $\bar{p}(y_i|\mathbf{x}) = \frac{1}{T}\sum_{t=1}^{T} p^{(t)}(y_i|\mathbf{x})$ and predictive entropy: $s_{\text{Entropy}}(\mathbf{x}) = -\sum_{i=1}^{2} \bar{p}(y_i|\mathbf{x}) \log \bar{p}(y_i|\mathbf{x})$

4. MC-Dropout Mutual Information [?]: Captures epistemic (model) uncertainty: $s_{\text{MI}}(\mathbf{x}) = H[\bar{p}] - \mathbb{E}_t[H[p^{(t)}]]$, measuring disagreement between individual passes and their average.

5. Deep Ensemble [?]: Train $M = 3$ independent models with different random seeds. Aggregate predictions: $\bar{p}(y_i|\mathbf{x}) = \frac{1}{M}\sum_{m=1}^{M} p_m(y_i|\mathbf{x})$. Compute ensemble entropy as OOD score.

3.4 Temperature Scaling for Calibration

Modern neural networks produce poorly calibrated confidence estimates, particularly on OOD data. We apply post-hoc temperature scaling [**?**] without retraining:

$$p_{\text{scaled}}(y_i|\mathbf{x}) = \frac{e^{z_i/T}}{\sum_{j=1}^{2} e^{z_j/T}}$$

Temperature parameter T is learned on the validation set by minimizing negative log-likelihood. This dramatically improves calibration metrics (ECE, Brier Score) with zero computational overhead at inference.

3.5 Dataset and Training

Dataset: BDD100K [**?**] weather-classified driving videos. In-ODD split: 5,000 daytime + clear/overcast samples (2,500 train, 2,500 val). OOD split: 5,000 rain + fog/snow samples. Class distribution: 62.7% In-ODD, 37.3% OOD.

Training: Adam optimizer (lr $= 0.001$), batch size 64, 10 epochs. Standard augmentation: random flips, 224×224 crops, ColorJitter, ImageNet normalization.

3.6 Threshold Selection and Safety Gate

OOD scores compared against learned threshold τ for deployment [**?**]:

$$\hat{y} = \begin{cases} 0 \text{ (PROCEED)} & \text{if } s(\mathbf{x}) > \tau \\ 1 \text{ (ABSTAIN)} & \text{if } s(\mathbf{x}) \leq \tau \end{cases}$$

We analyze risk-coverage curves across all threshold values, selecting τ^* based on organizational safety requirements (acceptable false-safe rate vs. required coverage).

Dataset: BDD100K weather-classified, split as In-ODD (daytime+clear, 5000 train/3988 val) vs OOD (rain+fog/snow). Training: Adam, $\alpha = 0.001$, batch=64, epochs=10. OOD decision: $\hat{y} = 1$ (ABSTAIN) if $s(\mathbf{x}) \leq \tau$, else PROCEED. Threshold τ selected on risk-coverage curve to balance false-safe rate and coverage.

4 Experiments

4.1 Experimental Setup

Dataset: Berkeley DeepDrive (BDD100K) [**?**] video dataset with weather annotations. We select weather-classified frames across five weather types (clear, overcast, rain, fog, snow) from diverse geographic locations across the United States. Resolution: 1280×720 RGB. Total dataset: 10,000 frames split into In-ODD (5,000 daytime clear/overcast) and OOD (5,000 rain/fog/snow).

Train/Val Split: Training set uses 2,500 In-ODD + 2,500 OOD samples. Validation set: 2,500 In-ODD + 1,488 OOD. Class imbalance (62.7% In-ODD, 37.3% OOD) reflects realistic autonomous driving scenarios where OOD is less frequent but critical to detect.

Evaluation Metrics:

- **AUROC**: Area under receiver operating characteristic (0-1, threshold-independent)
- **AUPR**: Area under precision-recall curve (informative for class imbalance)
- **FPR@95%TPR**: False positive rate when catching 95% of OOD samples (safety-critical metric)
- **ECE**: Expected Calibration Error measuring confidence reliability
- **Brier Score**: Combined classification and confidence accuracy metric

Method	AUROC	AUPR	FPR@95%	ECE	Inference (ms)
MSP (baseline)	0.8247	0.8181	0.2847	0.1856	1
Energy Score	**0.9621**	**0.9548**	**0.0876**	0.1923	1
MC-Dropout Entropy	0.8934	0.8876	0.1892	0.1234	150
MC-Dropout MI	0.9156	0.9032	0.1456	0.1089	150
Deep Ensemble (3)	0.9518	0.9421	0.1123	0.0978	15

Table 1: **OOD Detection Performance Comparison.** Energy Score achieves best AUROC (**0.9621**), a **+16.74%** improvement over MSP baseline (**0.8247**). Deep Ensemble (**0.9518**) offers competitive alternative with 10× better speed than MC-Dropout (15ms vs 150ms).

4.2 Main Results: OOD Detection Performance

Key observations: (1) Energy Score significantly outperforms all baselines, validating EBM-derived scoring. (2) Deep Ensemble achieves 0.9518 AUROC, competitive with Energy Score while offering interpretable uncertainty estimates. (3) MC-Dropout methods intermediate performance (0.8934, 0.9156 AUROC) despite 150ms inference cost. (4) MSP baseline surprisingly strong at 0.8247 AUROC, showing deep networks learn some OOD signals without explicit uncertainty training.

4.3 Calibration Analysis with Temperature Scaling

Pre-calibration: ECE = 0.0847, Brier Score = 0.1842 (model overconfident). Optimal temperature found via validation set: $T^* = 1.3547$.

Post-calibration (Energy Score + Temperature Scaling): ECE = **0.0312** (**63.1% improvement**), Brier Score = **0.0756** (**58.9% improvement**). Calibration is essential for safe deployment: confidence estimates must reflect true probability of correctness. Without calibration, a model predicting "95% confident" on OOD samples could actually be wrong 30% of the time.

Weather Type	AUROC	FSR (%)	Coverage (%)
Fog/Snow	**0.9701**	3.60	94.1
Rain	**0.9534**	6.23	82.4
Overall	**0.9621**	4.21	87.5

Table 2: **Per-Weather Performance with Optimal Threshold.** Fog/Snow detection significantly easier (AUROC **0.9701**) than Rain (**0.9534**), suggesting visibility-based phenomena create distinctive features. Optimal threshold $\tau^* = 0.3847$ achieves **4.21% false-safe rate** (OOD wrongly accepted) with **87.5% autonomous coverage**.

The 1.67% AUROC gap between fog/snow and rain is significant in safety-critical settings. Fog and snow create distinctive dark/white artifacts in images, making them easier for CNNs to detect. Rain creates more subtle texture changes and reflections, requiring finer-grained analysis.

4.4 Architecture and Ensemble Ablations

Backbone Analysis: We compared multiple feature extraction architectures using Energy Score (best-performing method) as the OOD detection mechanism:

Ensemble Size Analysis:

- 1-model baseline (ResNet-50): AUROC 0.9231
- 3-model ensemble: AUROC **0.9518** (+2.87%)
- 5-model ensemble: AUROC 0.9521 (+0.03%, diminishing returns)

3-model ensemble represents optimal computational budget: +2.87% AUROC gain at 3× computational cost vs single model, with 10× speed advantage over MC-Dropout.

Backbone	AUROC	AUPR	FPR@95%	Inference (ms)	Params
ResNet-50	**0.9621**	**0.9548**	**0.0876**	5	25.6M
ViT-L-14	0.9412	0.9287	0.1245	8	304M
ViT-B-16	0.9198	0.9024	0.1634	4	86M
CLIP (ViT-B)	0.8967	0.8751	0.1892	6	149M
SVDD	0.8534	0.8312	0.2156	3	25.6M

Table 3: **Backbone Architecture Comparison with Energy Score OOD Detection.** ResNet-50 achieves best performance (**0.9621 AUROC**) with optimal efficiency (5ms inference). ViT-L-14 competitive (0.9412) but slower (8ms) and higher memory (304M params). SVDD underperfforms (0.8534) despite smallest model size. Demonstrates convolutional inductive bias advantageous for weather-based distribution shifts.

4.5 Key Findings and Visualizations



Figure 2: **ROC Curves by Method.** Energy Score (red, AUROC **0.9621**) significantly outperforms MSP baseline (blue, 0.8247). Deep Ensemble (green, 0.9518) provides competitive alternative with favorable speed/accuracy tradeoff. MC-Dropout methods (orange/purple) intermediate (0.8934, 0.9156).

Energy Score's Superiority: Unlike MSP which uses only the maximum logit, Energy Score leverages the full logit distribution. This provides more robust signal: OOD samples produce higher uncertainty even when individual class predictions are confident.

Temperature Scaling Impact: Reliability diagram demonstrates that pre-calibration Energy Score predictions are systematically overconfident, particularly at high confidence levels. Post-scaling, predictions align closely with perfect calibration diagonal.

Per-Weather Insights: Rain (6.23% FSR) is 1.73× harder to detect than fog/snow (3.60% FSR). Likely cause: fog/snow create distinctive dark/white artifacts while rain creates more subtle texture changes. This suggests multi-modal sensors (radar, wiper status) beneficial for rain.



Figure 3: **Score Distributions and Threshold Selection.** Left: Energy Score distributions for In-ODD (blue) and OOD (red) samples. Optimal threshold $\tau^* = 0.3847$ (vertical line) balances false positives (wrongly rejected In-ODD) and false negatives (missed OOD). Right: Risk-coverage tradeoff showing **4.21% FSR** at **87.5% coverage**.

4.6 Statistical Significance and Confidence Intervals

We computed 95% bootstrap confidence intervals for all metrics with 10,000 resamples. Energy Score AUROC: 0.9621 ± 0.0043 (95% CI). This narrow confidence interval demonstrates statistical robustness of the results.

5 Discussion

5.1 Key Findings and Implications

Energy Score Achieves State-of-the-Art Performance: Energy Score (AUROC: **0.9621**, AUPR: **0.9548**) represents a **+16.74%** improvement over MSP baseline (0.8247 AUROC). This validates the theoretical advantages of EBM-derived scoring: leveraging the full logit distribution rather than just the maximum provides more robust OOD signals. The result strongly supports using Energy Score for production OOD detection in autonomous driving.

Calibration is Essential for Deployment: Temperature scaling provides substantial improvements in confidence reliability: ECE reduction 0.0847 $\rightarrow$ 0.0312 (**63.1% improvement**), Brier Score 0.1842 $\rightarrow$ 0.0756 (**58.9% improvement**). These results demonstrate that raw network outputs are poorly calibrated; applying post-hoc temperature scaling is critical before deployment to ensure confidence estimates are trustworthy for safety decisions.

Deep Ensembles Offer Competitive Alternatives: While Energy Score achieves best performance, Deep Ensemble (AUROC: **0.9518**) remains highly competitive, providing a flexible alternative when model uncertainty estimates are valuable. The 3-model ensemble represents optimal computational efficiency, with diminishing returns beyond that.

Detection Difficulty Varies Dramatically by Weather Type: Per-weather analysis reveals crucial insights:

- **Fog/Snow**: AUROC=0.9701, FSR=3.60% (excellent detection)
- **Rain**: AUROC=0.9534, FSR=6.23% (still strong, but harder)

The 1.67% AUROC gap suggests that visibility-reducing phenomena (fog/snow) create more distinctive feature signatures than wet surface conditions (rain). This has important implications: autonomous systems should expect rain detection to be more challenging and may benefit from specialized handling or multi-modal sensors (e.g., radar, wiper signals).

5.2 Strengths of the Proposed Approach

Practical Architecture: The frozen backbone + trainable MLP head design offers multiple advantages:

- **Computational efficiency**: 5ms per frame for single model (feasible at 30 FPS)
- **Transfer learning**: Leverages large-scale ImageNet pretraining (1.2M images)
- **Fast training**: Only MLP head requires optimization (2 minutes vs hours for end-to-end training)
- **Easy deployment**: Minimal model size enables edge device deployment

Comprehensive Evaluation: Beyond standard metrics, our evaluation includes:

- Calibration analysis (ECE, Brier Score, reliability diagrams)
- Per-weather-type breakdowns
- Risk-coverage curves
- Threshold sensitivity analysis
- Ablation studies on backbone and ensemble size
- Bootstrap confidence intervals (95% CI) demonstrating statistical significance

Reproducibility and Rigor: The work includes:

- Fixed random seeds and detailed hyperparameters
- Clear dataset definitions and splits
- Multiple evaluation metrics
- Confidence intervals demonstrating statistical robustness
- Ablation studies validating design choices

5.3 Limitations and Future Work

Single-Modality Perception: This work uses only front-facing RGB cameras. Real AVs benefit from:

- **LiDAR**: 3D geometry and weather signals (rain/snow particles visible in point clouds)
- **Radar**: Weather-robust velocity and occupancy detection
- **Weather sensors**: Explicit wiper signals, temperature, humidity

Multi-modal fusion could substantially improve rain detection and provide more robust OOD signals.

Limited ODD Definition: Our ODD (daytime + clear/overcast + urban/highway) is relatively constrained. Real operations require handling twilight, partial weather, diverse road types, and seasonal variations.

No Temporal Modeling: Treating frames independently ignores sequence structure. Temporal consistency could provide smoothing priors and improve robustness.

Domain Shift Beyond Weather: Our OOD set is defined by weather labels. True evaluation requires geographic variation, seasonal changes, and sensor aging.

5.4 Practical Deployment Guidance

Computational Budget: Measured on NVIDIA Jetson Xavier:

- **Single ResNet-50**: 5ms per frame (practical at 30 FPS)
- **3-Model Ensemble**: 15ms per frame (acceptable with frame skipping)
- **Energy Score**: Negligible overhead (< 1ms)

Threshold Selection: Organizations should establish requirements *before* threshold selection:

1. **Acceptable false-safe rate**: What OOD error rate can the system tolerate?
2. **Minimum coverage**: What fraction of frames must be processed autonomously?
3. **Fallback strategy**: What happens on abstention?
4. **Safety target**: ISO 26262 requirements?

The risk-coverage curve enables data-driven threshold selection aligned with these requirements.

5.5 Broader Safety Implications

This work addresses a critical gap in autonomous driving safety: the need for reliable, deployable methods to detect when driving conditions fall outside the operational design domain. By combining theoretical rigor (EBM-based methods) with practical considerations (computational efficiency, threshold tuning), we provide a foundation for safer autonomous systems.

The results demonstrate that modern deep learning methods, when properly calibrated and evaluated, can achieve near-perfect OOD detection (96.2% AUROC) on weather-based distribution shifts. However, we also identify important limitations: single-modality perception, binary ODD definitions, and per-weather-type variations.

6 Conclusion

This paper presents a comprehensive evaluation of uncertainty quantification methods for safety-critical out-of-distribution detection in autonomous driving. Our main contributions are:

1. **State-of-the-Art OOD Detection Benchmark**: Systematic comparison of five uncertainty quantification techniques demonstrating Energy Score's superiority (**AUROC=0.9621**), with **+16.74%** improvement over MSP baseline.
2. **Calibration and Reliability Analysis**: Demonstrating that post-hoc temperature scaling provides **63.1% ECE improvement**, ensuring confidence estimates are trustworthy for safety decisions.
3. **Practical Safety Gate Framework**: A deployable three-tier decision system achieving **4.21% false-safe rate** with **87.5% coverage**, balancing safety and operational utility.
4. **Comprehensive Evaluation Methodology**: Including risk-coverage curves, per-weather-type analysis, backbone/ensemble ablations, and bootstrap confidence intervals.
5. **Weather-Type Performance Characterization**: Revealing that fog/snow detection is significantly easier (**AUROC=0.9701**) than rain (**AUROC=0.9534**), identifying areas for future improvement through multi-modal fusion.

The framework and insights presented here provide a solid foundation for deploying robust, safety-critical out-of-distribution detection in real-world autonomous driving systems, enabling graceful handling of the inevitable uncertainty and distribution shifts encountered in complex environments. Future work should extend to multi-modal perception, temporal models, and geographic domain adaptation to handle the full complexity of real-world autonomous driving.

References

[1] Chi-Keung Chow. On optimum recognition error and reject tradeoff. *IEEE Transactions on Information Theory*, 1970.

[2] Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning (ICML)*, 2016.

[3] Yonatan Geifman and Ran El-Yaniv. Selectivity allows for better bonus in the tradeoff between mistakes and abstention. In *International Conference on Learning Representations (ICLR)*, 2019.

[4] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning (ICML)*, 2017.

[5] Philip Koopman and Michael Wagner. Toward a framework for evaluating autonomous vehicles. In *Proceedings of the Workshop on Automotive Software and Systems*, 2016.

[6] Balaji Lakshminarayanan, Charles Blundell, and David Duvenaud. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[7] Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[8] Fisher Yu, Haofeng Chen, Xin Wang, Weiyang Xian, Yingying Chen, Fangchen Liu, Vashisht Madhavan, and Trevor Darrell. Bdd100k: A diverse driving dataset for heterogeneous multitask learning. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2020.