International Journal Publication

Publication		
Title	Using Binary Trees for the Evaluation of Influence Diagrams	
Authors	R. Cabañas, M. Gómez-Olmedo, and A. Cano	
Year	2016	
DOI	https://doi.org/10.1142/S0218488516500045	

Journal details (in 2016)		
Name	International Journal of Uncertainty, Fuzziness and Knowledge-Based Sys-	
	tems	
Category	Computer Science, Articial Intelligence	
Repository	Journal Citation Reports (JCR)	
Impact	1.214	
Cuartil	Q3	

International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems Vol. 24, No. 1 (2016) 59–89 © World Scientific Publishing Company DOI: 10.1142/S0218488516500045



Using Binary Trees for the Evaluation of Influence Diagrams*

Rafael Cabañas, Manuel Gómez-Olmedo and Andrés Cano

Department of Computer Science and Artificial Intelligence, University of Granada,

CITIC-UGR, C/Daniel Saucedo Aranda s/n, Granada, 18071, Spain

*rcabanas@decsai.ugr.es

† mgomez@decsai.ugr.es

‡ acu@decsai.ugr.es

Received 14 June 2015 Revised 8 January 2016

This paper proposes the use of binary trees for representing and managing the potentials involved in Influence Diagrams. This kind of tree allows representing context-specific independencies that are finer-grained compared to those encoded using other representations. This enhanced capability can be used to improve the efficiency of the inference algorithms used for Influence Diagrams. Moreover, binary trees allow computing approximate solutions when exact inference is not feasible. In this work we describe how binary trees can be used to perform this approximate evaluation and we compare them with other structures present in the literature.

Keywords: Probabilistic graphical models; influence diagrams; approximate computation; variable elimination; context-specific independencies.

1. Introduction

Influence Diagrams (IDs)^{2,3} provide a framework to model decision problems with uncertainty for a single decision maker. The goal of evaluating an ID is to obtain the best option for the decision maker (optimal policy) and its utility. The evaluation of IDs modelling complex decision problems becomes unfeasible due to its computational cost. It is thus necessary to use alternative methods for IDs evaluation such as LIMIDs,⁴ or simulation techniques.^{5,6} Other solutions propose using alternative representations for potentials such as numerical trees (NTs)^{7–9} trying to offer efficient data structures for storing and managing quantitative information (probabilities and utilities). This data structure takes advantage of context-specific independencies¹⁰ so that identical values can be grouped into a single one offering

^{*}A preliminary version of this paper was presented at PGM'12 Workshop.¹