Pay-Equity Audit with Supervised Learning

A reference pay model to detect unexplained gaps by sex and race

Group: Thomas Pasquier–Guillard, Lélia Hervy, Robin Cacarié

Supervised Learning & Model Engineering with Ilana Sebag, for Albert School

October 2026

Dataset: Ron Kohavi and Barry Becker, "Scaling Up the Accuracy of Naive-Bayes Classifiers: a Decision-Tree Hybrid", *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining*, 1996.
Data: adult
Code: https://github.com/rcacarie-png/Adult-Income-Prediction

Abstract

We take the role of a government agency that checks whether pay is fair with respect to sex and race, under the principle of *equal pay for equal work*. We train a *reference pay model* that predicts the probability of earning more than \$50K from job-related factors only, and never sees sex, race, national origin or their proxies. The audit then compares, for each group, the actual share of high earners with the share expected from its qualifications. The final model is a tuned LightGBM with isotonic calibration (test ROC-AUC 0.893, average precision 0.777, expected calibration error 0.009). On the untouched test set, women earn more than \$50K **5.4 points less often** than their profiles predict (95% CI -6.3 to -4.6), and Black employees **3.4 points less often** (-4.9 to -1.9).
A model trained on all columns is more accurate but hides these gaps entirely, which is why removing protected attributes is the right mitigation for this use case.

1 Problem framing

Business question: A pay-equity regulator must decide which employers to investigate. Comparing the raw share of high earners between men and women is not enough: groups may differ in education, occupation or working time, which legitimately affect pay. The question is therefore: *do people with the same job-related profile have the same chance of earning more than \$50K, whatever their sex or race?*

Approach: We learn $p(\text{income} > 50\text{K} \mid \text{job-related factors})$ on the population. For a group g of size n_g, with actual labels y_i and calibrated probabilities $\hat{p}_i$, we define

$$\text{unexplained gap}_g \;=\; \underbrace{\tfrac{1}{n_g}\textstyle\sum_{i\in g} y_i}_{\text{actual rate}} \;-\; \underbrace{\tfrac{1}{n_g}\textstyle\sum_{i\in g} \hat{p}_i}_{\text{expected rate}}. \tag{1}$$

A significantly negative gap means the group earns less than its qualifications predict: a reason to open an investigation, *not* a proof of discrimination. This framing has three methodological consequences that structure the whole project:

1. **Protected attributes and their proxies must not be inputs**, otherwise the model learns the discrimination and the expected rate already contains it.
2. **Probabilities must be calibrated**, because the expected rate is an average of probabilities: inflated probabilities would make every group look underpaid.

3. **Ranking quality matters** (ROC-AUC, average precision), because the expected rate must follow the real differences in qualifications.

Individual employees whose profile makes >$50K more likely than not but who earn less are additionally flagged as *potentially underpaid*, for inspectors to review.

2 Data and exploratory analysis

Overview: The 1994 US census extract contains 48,842 people, 6 numeric and 8 categorical columns. 23.9% earn more than $50K: the classes are imbalanced, and a model that always predicts "≤50K" reaches 76.1% accuracy with zero recall, so accuracy is not a useful metric here. Missing values concern only `workclass` (5.7%), `occupation` (5.8%, almost always together with `workclass`) and `native-country` (1.8%). Missingness is informative: only 9.5% of people with an unknown occupation earn >50K, against 24.8% otherwise. We therefore encode it as an explicit `"Missing"` category instead of imputing the most frequent value. `capital-gain` and `capital-loss` are zero for 91.7% and 95.3% of people.

Sensitive attributes: The raw gaps are large: 30.4% of men earn >50K against 10.9% of women; 25.4% of White people against 12.1% of Black people. Table 1 shows that the sex gap *remains between people with the same education or the same occupation*: legitimate factors do not explain it, which motivates the audit.

Table 1: Share earning >$50K by sex, within the same education level or occupation (full data).

Education	Women	Men	Occupation	Women	Men
High-school graduate (9)	6.5%	20.3%	Adm-clerical	8.2%	24.9%
Some college (10)	7.0%	26.4%	Exec-managerial	24.1%	57.3%
Bachelors (13)	21.0%	50.3%	Prof-specialty	26.0%	56.0%
Masters (14)	34.3%	64.5%	Sales	6.9%	37.7%

Choice of columns: Table 2 summarises which columns the reference model may use. Beyond the protected attributes, `relationship` is an almost perfect proxy for sex (19,715 of the 19,716 "Husband" are men, 2,328 of the 2,331 "Wife" are women), and marital status is not a job-related factor, so both are excluded even though they are among the strongest predictors. `fnlwgt` is a census sampling weight with no relationship to income (>50K rate between 21.6% and 25.4% across its deciles), and `education` duplicates `education-num` exactly.

Table 2: Column decisions for the reference pay model.

Column(s)	Decision	Reason
`sex`, `race`, `native-country`	excluded	protected attributes: used only to *group* the audit
`relationship`, `marital-status`	excluded	proxy for sex / not a job-related factor
`fnlwgt`	excluded	census sampling weight, no link with income
`education`	excluded	exact duplicate of `education-num`
`age`, `education-num`, `workclass`, `occupation`, `hours-per-week`	kept	legitimate pay factors: experience, qualification, job, working time
`capital-gain`, `capital-loss`	kept, tested	investment income, part of the target (see the leakage audit)

Leakage audit: Every kept column is known at prediction time, with one caveat: the target is *total* income, which includes capital gains. `capital-gain` is therefore a partial target leak. We keep it, because ignoring investment income would attribute it to the employer, and we verify in Section 5.4 that the conclusions do not depend on it.

Split: We use a stratified 60/20/20 split (`random_state=42`): 29,304 training, 9,769 validation and 9,769 test people, each with a 23.9% positive rate. The training set is used for fitting and cross-validation, the validation set for model choice, calibration choice and threshold, and the test set is opened **once**, at the end, for the final evaluation and the audit.

3 Methodology

3.1 Feature engineering and pipeline

A custom scikit-learn transformer, `AdultFeatureEngineer`, drops the excluded columns and adds five features (Table 3). Numeric columns are then imputed with the median and standardised; categorical columns are imputed with `"Missing"` and one-hot encoded, with rare categories (<0.5%) grouped together and unknown categories handled at prediction time. All steps and the model are wrapped in a single `Pipeline`, so every preprocessing step is fitted on the training data (or the training folds) only, and the excluded columns can never reach the model, even at serving time.

Table 3: Engineered features and their signal on the training set.

Feature	Definition	Justification and signal (>50K rate)
`capital_net`	gain − loss	net investment result in one number
`has_capital`	gain > 0 or loss > 0	owning investments: 57.5% vs 18.9%
`log_capital_gain`	$\log(1 + \text{gain})$	tames the long tail for the linear model
`works_overtime`	hours > 40	39.7% vs 17.2%
`is_part_time`	hours < 35	7.2% vs 27.4%; 27.6% of women vs 11.9% of men

The working-time features matter for the audit: women work part-time much more often, a legitimate reason for lower annual income that the model must account for.

3.2 Metrics and class imbalance

We report precision, recall and F1 at the decision threshold, and two threshold-free ranking metrics: ROC-AUC and **average precision** (AP, the area under the precision–recall curve, called `pr_auc` in our code; a random model scores the prevalence, 0.24). AP is our main selection metric, since it focuses on the rare class.

On the Logistic Regression baseline, we compared three remedies (Table 4). All three give the same trade-off: recall rises from 0.43 to about 0.76, precision falls from 0.74 to about 0.51, F1 improves, and ROC-AUC and AP do not move. The remedies shift the operating point (they are close to lowering the threshold), they do not improve the ranking. We keep **class weights** (`class_weight="balanced"`): same result, all real data is kept (undersampling discards two thirds of the majority class), no synthetic people (SMOTE interpolates one-hot columns into unrealistic profiles), and the same parameter exists for all three models. Resampling, when used, is applied inside an `imblearn` pipeline, during `fit` only.

Table 4: Class-imbalance remedies on Logistic Regression (validation set, threshold 0.5).

Remedy	Precision	Recall	F1	ROC-AUC	AP	Fit time (s)
None	0.744	0.431	0.546	0.853	0.692	0.5
Class weights	0.508	0.756	0.607	0.854	0.691	0.5
Random undersampling	0.510	0.760	0.611	0.854	0.689	0.2
SMOTE	0.510	0.757	0.609	0.854	0.692	1.0

We treat the class weight as fixed rather than as a hyperparameter: it did not change the ranking, and the precision/recall trade-off is controlled later by the threshold. Its side effect on the probabilities is corrected by calibration (Section 4.3).

3.3 Models, tuning and experiment tracking

We compare Logistic Regression (linear, interpretable), Random Forest (bagged deep trees, captures interactions) and LightGBM (gradient boosting), all with class weights and the same pipeline. Hyperparameters are tuned with **Optuna** (TPE sampler, seed 42): 15 trials for Logistic Regression and the Random Forest, 30 for LightGBM. Each trial is scored by **5-fold stratified cross-validation on the training set** (`scoring="average_precision"`), refitting the whole pipeline in each fold; the validation set is never used during the search, so the selection does not overfit it. Search spaces cover the complexity parameters of each model (Appendix A).

Every run is logged in **MLflow** (experiment `adult-pay-equity`, SQLite backend): parameters, metrics, confusion matrices and fitted pipelines for the imbalance and model comparisons; one parent run per model with one nested child run per Optuna trial (parameters, CV mean and standard deviation, the five fold scores, run time) and the optimisation history; and a final run with the test metrics, the audit tables and the calibrated model. Runs are tagged by stage (`imbalance`, `models`, `tuning`, `tuned`, `final_test`).

4 Results

4.1 Modelling progression

Table 5: Model comparison. CV: 5-fold AP on the training set (mean $\pm$ std). Validation metrics at threshold 0.5, before calibration.

Model	Version	CV AP	Val. AP	Val. ROC-AUC	Precision	Recall	F1
Logistic Regression	default	0.684 ± 0.005	0.691	0.854	0.508	0.756	0.607
	tuned	0.684 ± 0.005	0.692	0.854	0.508	0.756	0.607
Random Forest	default	0.738 ± 0.010	0.750	0.879	0.556	0.749	0.638
	tuned	0.737 ± 0.010	0.752	0.879	0.529	0.780	0.630
LightGBM	default	0.761 ± 0.008	0.772	0.890	0.544	0.804	0.649
	tuned	$\mathbf{0.764 \pm 0.010}$	**0.776**	**0.893**	0.544	0.804	**0.649**

What each step bought: Moving from Logistic Regression to the Random Forest brings the largest gain (AP $+0.06$, ROC-AUC $+0.025$): trees capture some interactions that a linear score cannot, for example the return on education depends on occupation and age. LightGBM adds a further gain (AP $+0.02$) with the best recall, and trains in about 1 s against 5 s for the forest. Both tree models overfit mildly (train vs validation ROC-AUC: 0.916 vs 0.879 for the forest, 0.911 vs 0.890 for LightGBM); Logistic Regression does not.

What tuning bought: Very little: AP rises by $+0.005$ for LightGBM, $+0.001$ for the forest and ≈ 0 for Logistic Regression on validation, which is smaller than the cross-validation standard deviation. Tuning mostly reduced overfitting: training AP drops from 0.802 to 0.788 for LightGBM and from 0.807 to 0.783 for the forest while validation AP slightly rises. The best LightGBM uses many small steps (600 trees, learning rate 0.023) and moderate trees (22 leaves, 51% of features per tree). The CV and validation rankings agree, and validation scores are about 0.01 *above* the CV scores for every model (tuned or not), so the selection over many trials did not produce an optimistic estimate. **The model family mattered more than the hyperparameters.**

Final choice: We select the tuned **LightGBM**: best validation AP and ROC-AUC, consistent CV and validation results, fast training, and exact, fast SHAP explanations for trees.





Figure 1: Optuna search: CV average precision of each trial, best so far, and the untuned model (dashed).

4.2 Explainability

We explain the final model with SHAP (`TreeExplainer`, log-odds scale) on 2,000 validation people. Globally (Figure 2a), the most important features are **age** (mean |SHAP| 1.09), **education** (0.47), **capital gain** and `capital_net` (0.29, 0.22), **hours per week** (0.20) and **occupations** (`Other-service`, `Exec-managerial`, `Adm-clerical`). Four of the five engineered features are in the top 15. These are exactly the factors that pay should legitimately depend on: experience, qualification, working time, investment income and type of job. The directions make sense: older, more educated people working longer hours are pushed towards >50K; service and clerical occupations push down. SHAP describes what the model uses, not what causes income.

Locally, the instructive cases are the model's mistakes (Figure 2b and Appendix B). The "missed high earner" is a 46-year-old woman with an 11th-grade education working 35 hours a week in `Other-service`: every job-related factor points to ≤50K, her high income is genuinely unusual for her profile. The "false alarm" is a self-employed 50-year-old with a professional degree whom everything predicts above $50K: exactly what a "potentially underpaid" flag looks like, but with no employer to blame, which shows that flags are starting points for an inspector, not conclusions.



(a) Global: SHAP beeswarm (navy = high feature value). **(b)** Local: the "false alarm" (really ≤50K, predicted 0.91).


Figure 2: SHAP explanations of the final LightGBM.

4.3 Calibration diagnostics

Table 6: Calibration of the final model (validation set). ECE with 10 equal-width bins.

Probabilities	Brier score	ECE	Mean predicted	Observed rate	AP
Raw (class-weighted LightGBM)	0.132	0.135	0.374	0.239	0.776
Sigmoid calibration	0.105	0.031	0.236	0.239	0.776
Isotonic calibration	**0.103**	**0.010**	0.236	0.239	0.775

The raw model is **over-confident towards >50K**: it predicts 37% on average while the true rate is 24%, and its reliability curve lies below the diagonal (Figure 3a). This is the expected side effect of class weights, which make each positive count about three times more during training. **We would not trust these probabilities as-is**: the audit would declare almost every group underpaid. We recalibrate with `CalibratedClassifierCV(cv=5)`, which learns the mapping on out-of-fold predictions of the training set, so neither the validation nor the test set is used. Isotonic regression clearly beats the sigmoid (ECE three times lower), and with 29,000 training people it has enough data not to overfit, so we keep it; AP is unchanged since calibration preserves the ranking. Bin counts (Appendix B) show that the low-probability region, which drives the group averages, is estimated on thousands of people, while bins between 0.5 and 0.9 contain only 90 to 460 people; there the model is, if anything, slightly cautious (observed 0.75 for 0.65 predicted).



(a) Reliability curves (validation). **(b)** Precision, recall and F1 vs threshold (calibrated).

Figure 3: Calibration and choice of the decision threshold.

4.4 Decision rule and final test

Individual flags use the calibrated probability with a threshold of **0.5** ("more likely than not"). Since a flag may trigger an inspection and inspectors are limited, precision matters more than recall: at 0.5, 82% of people expected to earn >50K really do (recall 0.51), whereas the F1-optimal threshold (0.39) would trade precision down to 0.68 for a recall of 0.65. The group audit does not depend on the threshold, as it uses the probabilities directly.

Table 7: Final model (tuned LightGBM, isotonic calibration, threshold 0.5): validation vs untouched test set.

Set	Accuracy	Precision	Recall	F1	ROC-AUC	AP	Brier	ECE
Validation	0.857	0.824	0.509	0.629	0.893	0.775	0.103	0.010
Test	0.854	0.818	0.501	0.621	0.893	0.777	0.103	0.009

Test and validation results are nearly identical: the choices made on validation did not overfit it, and these are honest estimates for new people from the same population. Following the homeworks, we should refit on train + validation before testing; we did not, because the validation set was used to choose the calibration and the threshold, and refitting would change the model after those choices for a small gain from 20% more data.

5 Fairness and pay-equity audit

Two questions must be kept apart: *is the pay fair?* (measured by the unexplained gap) and *is our model fair?* (it must give the same output to the same profile, whatever the person's group). All results below are on the test set.

5.1 Classic fairness metrics of the model

Table 8: Group metrics of the final model by sex (test set) and fairness gaps (0 = equal).

Sex	n	Base rate	Selection rate	TPR	FPR	Precision
Women	3,259	0.111	0.078	0.465	0.029	**0.664**
Men	6,510	0.304	0.181	0.507	0.039	**0.851**

Gaps:

- demographic parity: 0.10,
- equal opportunity: 0.042,
- equalized odds: 0.042.

Demographic parity (same share predicted >50K) is not satisfied, purely because job-related profiles differ (hours, part-time work, occupations); the model's selection gap (10 points) is much smaller than the real gap (19 points). *Equal opportunity* and *equalized odds* are nearly satisfied: true and false positive rates differ by at most 4 points.

The telling number is **precision**: among people the model expects to earn >50K, 85% of men do, but only 66% of women. For our model, a false positive is a person whose qualifications predict a high income but who does not receive it: a lower precision for women is evidence about the *pay*, not a defect of the model. By race, the largest gaps (0.12) come from the 96-person `Amer-Indian-Eskimo` group and are not reliable; Black employees have a *higher* precision (0.86) than White employees (0.82).

5.2 Pay-equity audit

Table 9: Pay-equity audit on the test set. Gap = actual − expected rate, in percentage points, with a 95% bootstrap CI (1,000 resamples). Underpaid: share of employees expected to earn >50K who do not. Groups under 100 people are not interpreted.

Group	n	Actual	Expected	Gap [95% CI]	Underpaid
Women	3,259	11.1%	16.5%	**−5.4** [−6.3, −4.6]	34%
Men	6,510	30.4%	27.1%	+3.3 [+2.4, +4.2]	15%
Black	968	13.3%	16.7%	**−3.4** [−4.9, −1.9]	14%
White	8,312	25.3%	24.4%	+0.9 [+0.2, +1.6]	18%
Asian-Pac-Islander	311	26.4%	25.4%	+1.0 [−2.9, +5.0]	29%
Amer-Indian-Eskimo	96	13.5%	16.4%	too small to conclude	
Other	82	12.2%	14.8%	too small to conclude	

Women earn more than \$50K **5.4 points less often** than their job-related profiles predict, and a third of the women expected to earn >50K do not, against 15% of men. Black employees earn **3.4 points less** than expected; for them the gap is spread over moderate probabilities rather than concentrated among the individuals the model expects to be high earners (only 14% of them are flagged). Both gaps are significant. White employees are slightly above expectation (significant only because the group is large); the Asian-Pacific-Islander gap is not significant.




Figure 4: Unexplained gap by group with 95% bootstrap confidence intervals (test set, groups ≥ 100 people).

5.3 Mitigation: before / after

Our mitigation is a **pre-processing** technique: removing the protected attributes and their proxies from the model's inputs. To measure its effect, the "before" model uses the same tuned LightGBM, calibration and threshold, but is trained on *all* columns, including sex, race, national origin, marital status and relationship.

Table 10: Before / after the mitigation, on the untouched test set.

	Before: all columns	After: job-related only
ROC-AUC / AP	0.930 / 0.834	0.893 / 0.777
F1 (threshold 0.5)	0.721	0.621
Demographic parity difference (sex)	0.187	0.103
Equalized odds difference (sex)	0.114	0.042
Unexplained gap, women	+0.2 pts	−5.4 pts
Unexplained gap, Black employees	+1.1 pts	−3.4 pts

The mitigation costs predictive performance (ROC-AUC -0.04, F1 -0.10) but almost halves the demographic-parity gap and nearly divides the equalized-odds gap by three. Above all, it changes the audit: the "before" model is more accurate *because it has learned the discrimination*. It expects lower pay for women and Black employees, finds them paid exactly as expected, and would declare every employer fair. A reference model must describe what people *should* earn for their work, not what they *do* earn given their sex and race.

We rejected **post-processing** (e.g. fairlearn's `ThresholdOptimizer`). It equalises error rates with group-specific thresholds, which suits a model that *decides* about people (hiring, credit), but here the extra "errors" for women are the underpayment signal: equalising them would erase the evidence, and it would require sex and race at prediction time.

5.4 Robustness checks

Proxy check: A classifier predicting sex from the model's inputs reaches ROC-AUC 0.79, mainly through occupation and hours. This is intended under "equal pay for equal work" (part-time work legitimately lowers annual income), but it means the gap only measures unequal pay *for comparable jobs*: discrimination in access to well-paid occupations is "explained" by occupation and remains invisible. Our gaps are therefore a **lower bound**.

Sensitivity to the capital columns: Retraining without `capital-gain`, `capital-loss` and their engineered features lowers ROC-AUC from 0.893 to 0.846, but the conclusions hold and the gaps become slightly larger: -6.6 pts for women (CI -7.6 to -5.5) and -3.8 pts for Black employees (-5.6 to -2.0), because investment income is more frequent among men. Keeping these columns is the conservative choice for employers.

6 Serving

The calibrated pipeline is exported with `cloudpickle` together with its settings, and served by a **FastAPI** application (`serving/audit_api.py`) with Pydantic input validation. `GET /health` checks the service; `POST /predict` returns each employee's expected probability; `POST /audit` takes a company's employee records and returns, per sex and race group, the actual and expected rates, the gap with its bootstrap CI, and the potentially underpaid employees. Tests with FastAPI's `TestClient` confirm that two employees with the same job profile but different sex and race receive exactly the same probability (0.652), and that invalid inputs (e.g. age 7) are rejected with HTTP 422. On a simulated company of 2,000 test-set employees, the API reports a significant gap for women (-6.0 pts, CI -7.8 to -4.0) and flags 52 potentially underpaid employees.

7 Discussion and limitations

What could invalidate the conclusions:

- **Unexplained is not proven.** Factors absent from the data (seniority, exact job title, region, firm size, performance) could legitimately explain part of the gaps.
- **The reference is the population.** The model learns the average pay of a population that includes the discrimination we audit, and occupation can itself reflect discrimination: both bias the gaps towards zero.
- **The data.** The census describes individuals, not companies; the target is total income rather than salary, binarised at a coarse \$50K threshold; and the data dates from 1994. The method transfers, the size of the gaps does not.
- **Small groups.** Two race groups have fewer than 100 test people; their gaps cannot be interpreted. Calibration was checked globally; checking it within each group would further strengthen the audit.

Conclusion: A calibrated reference model trained on job-related factors only is an effective screening tool for a pay-equity regulator. On this data, it reveals significant unexplained gaps for women (-5.4 pts) and Black employees (-3.4 pts), robust to the removal of the leaky capital columns, that a model trained on all columns would completely hide. We recommend using it to prioritise investigations, with the gap and its confidence interval as the trigger and the individual flags as the starting point for inspectors.

Contribution statement

Member	Contributions
Lélia Hervy	Wrote most of the code: exploration, feature engineering, pipeline, imbalance comparison, model comparison, tuning, calibration, SHAP, fairness and pay-equity audit, API; merged the analysis into the final notebook and scripts; maintains the repository.
Thomas Pasquier–Guillard	Defined the research question (pay fairness with respect to sex and race, "equal pay for equal work"); reviewed and modified the code.
Robin Cacarié	Proposed framing the project around a real problem (the pay-equity regulator); created the GitHub repository; reviewed and modified the code.

All members contributed to the report and the oral defense, and can explain every part of the project.


Use of AI assistants: We used Claude (Anthropic) as a coding assistant to generate and explain code, check the consistency of results against the course material, and help draft this report. We reviewed, ran and modified all code ourselves, verified every number against our own runs, and discussed and validated every methodological choice as a team.

A Hyperparameter search spaces


Model	Search space	Best (CV AP)
Logistic Regression	$C \in [10^{-3}, 100]$ (log)	$C = 71$ (0.684)
Random Forest	`n_estimators` 100–400, `max_depth` 5–30, `min_samples_leaf` 1–50 (log), `max_features` $\in$ {sqrt, 0.3, 0.5}	400 trees, depth 14, leaf 6, 0.5 (0.737)
LightGBM	`n_estimators` 100–800, `learning_rate` 0.01–0.2 (log), `num_leaves` 8–128 (log), `min_child_samples` 5–100 (log), `subsample` 0.5–1, `colsample_bytree` 0.5–1, `reg_lambda` 10^{-3}–10 (log)	600 trees, lr 0.023, 22 leaves, min child 5, subsample 0.89, colsample 0.51, λ 0.049 (0.764)

All models use `class_weight="balanced"` and `random_state=42`.

B Additional figures




(a) Class-imbalance remedies (validation).




(b) Precision–recall curves of the three models (validation).

Figure 5: Class-imbalance remedies and model comparison.




(a) Mean |SHAP| (global importance).




(b) Missed high earner (really >50K, predicted 0.08).

Figure 6: Additional SHAP explanations.



(a) People per probability bin.



(b) Actual vs expected rate by group.

Figure 7: Calibration support and audit rates (test set).




Figure 8: Final model on the test set: confusion matrix, ROC and precision–recall curves.




Figure 9: Unexplained gap by sex before and after the mitigation (test set): the model trained on all columns finds no gap.