LLM Coordination

Lit review

Bardsley et al.: focal points are not one mechanism: It contrasts two explanations of focal-point coordination: cognitive hierarchy and team reasoning. Cognitive hierarchy says people coordinate by predicting what others are naturally inclined to pick. Team reasoning says people ask something like “what should we choose as a group?” and then select the rule that would work best if everyone used it.
Cognitive hierarchy view: “What are people naturally inclined to pick?”
Team reasoning view: “What rule should we use, if we are trying to solve this together?”

Halpern and Pass: translucent players: standard game theory assumes players are opaque to each other. That means: if I changed my strategy, the other players’ strategies would stay fixed. translucent-player reasoning: the model treats its own choice as informative about, or counterfactually linked to, the others’ choices.

4 models:
Opaque-player reasoning: “I choose the best response to fixed beliefs about what others will do.”
Translucent/self-locating reasoning: “My choice is evidence about what similar agents will choose.”
Team reasoning: “What rule should we all follow?”
Cognitive hierarchy: “What will others naturally/naively pick?”

Faillo et al. 2017 ‘Bounded best-response and collective-optimality reasoning in coordination Games’ : “Accumulated experimental evidence suggests that neither approach (team reasoning, CHT) can give a satisfactory explanation of behaviour across the whole range of coordination games. The main obstacle to a unified explanation seems not to be that individuals differ in the modes of reasoning they use. Instead, it is that games differ in the modes of reasoning that they evoke.In particular, it has been suggested that reasoning based on collective optimality may be inhibited if players have conflicting preferences over equilibria, if the collectively optimal solution gives the players unequal payoffs, or if that solution, although Pareto-efficient ex ante, is Pareto-dominated ex post” -> they find that if the ‘team reasoning’ solution (i.e., the ‘odd one out’) is associated with a lower payoff (i.e., J=10, M=15, N=15) people switch to CHT (pick higher paying letter).

Lit Review Pt2.

Bardsley et al. (2010) 'Explaining Focal Points: Cognitive Hierarchy Theory versus Team Reasoning':

Payoffs: < (10) (10) (9) >

Three treatments:

1. Picking: asked to choose one object and scored the number of points specified for that object.
2. Guessing: randomly paired with a person from the picking treatment - guess which object the partner has chosen. Guess matches picker choice -> get points associated with the object. Otherwise get nothing.
3. Coordination: choose the same object as your teammate. Get the points associated to the object if they coordinate on the same object, do not get points if they coordinate on different objects.

Picking: chooses one of the (10) objects - it makes sense to choose the object with the highest reward because they get points based on the object they pick.
Guessing: level 0 player behaves like the picker, level 1 and above think that the picker will have chosen the highest paying option and picks one of the two 10ns

CHT:
Guessing = Coordination (i.e., both players go for the highest scoring options)

Team reasoning:
Rule-based coordination; 'what is best for the team?' pick the 'odd one out'. Guessing is not the same as Coordination.

Mixed Findings: Amsterdam experiment -> people display team reasoning (in coordination people switch to the odd one out); Nottingham experiment -> people display CHT (i.e. guesser= coordination)

Implication for our experiment: Round 8 is very similar - J is the odd one out, M and N are the higher payoff but indistinguishable options. Team reasoning - should pick the 'odd one out'. CHT - should maximize payoffs. - NO FEEDBACK CONDITION - may pick up the proportion of people who are team reasoning vs using CHT.

What is happening in the feedback condition?

Feedback Condition

Four options:

1. There is a mixed population of participants who follow team reasoning and participants who follow CHT. CHT participants switch to ‘M’ in round 8 breaking the symmetry between ‘M’ and ‘N’. From then onwards CHT and Team reasoners are aligned -> CHT maximize payoffs so they pick M; team reasoners go for the most salient option that has the highest payoff and pick M. -> LLM more likely to be team reasoners? Humans more likely to use CHT?

2. There is a mixed population. Some team reasoner, some people use CHT. The CHT participants switch to M in round 8. Slowly the rest of the population of team reasoners also switch to CHT. -> LLMs are slower at switching to CHT than humans?

3. There is no mixed population everyone is a team reasoner. The team strategy is ‘pick one of the higher scoring letter to break symmetry and eventually converge on M or N’. That doesn’t necessarily explain why some people stick with J. However, I’ve seen in the literature that team reasoning can come also with different level of reasoning like level k level reasoning. So the naive team reasoner might think that the rule is to stick with J, while the advanced team reasoner might think that the rule to follow is to break symmetry. -> LLMs more likely to use naive team reasoning, Humans more likely to use complex, long term team reasoning?

4. There might be a third type (other than ‘team reasoner’ and CHT) in repeated coordination problems. This third type of player is not maximizing payoffs given beliefs of what the majority of other players are likely to do nor are they following any specific rule. They are signalling to the others what they believe the future strategy should be. A bit murky but is there literature on this? -> LLMs more likely to not ‘signal’ team strategies but be ‘passive’?

CHT vs team reasoning

CHT: In the Bardsley et al. version, level-1+ reasoners choose based on beliefs about what level-0 “pickers” are inclined to choose. In our case, J is most salient.
TR: team reasoners ask “what should we as a group choose?”. In our case, that is the decision rule leading to higher payoffs IF symmetry is broken.

Predictions:
CHT: collaborator choices should be explained by guesser predictions.
TR: collaborators may diverge from guessers by coordinating more strongly on the rule that would be best if everyone followed it.

Alternative specification (pseudo-bardsley):
CHT: choice tracks prediction more than prescription.
TR: choice tracks prescription more than prediction.

Guess: without payoffs, what seems natural to pick?
Prediction & choice:
LLMS predict that most humans will choose J, choose J themselves
Humans predict some humans will choose J, nevertheless choose M themselves and think choosing M is prescriptively correct
Prescription: Suppose all six players could somehow adopt the same rule for round 9. Which rule would give the group the best outcome?

Poor predictions vs poor strategy predictions

Tipping Points

Granovetter ‘Threshold models of Collective Behavior’:

- “Models of collective behavior are developed for stiuations where actors have two alternatives and the cost and/or benefits of each depend on how many other actors choose which alternative. The key concept is that of **threshold**: the number or proportion of others who must make one decision before a given actor does so; this is the point where net benefits begin to exceed net costs for that particular actor.”
- A person’s threshold for joining a riot is defined here as the proportion of the group he would have to see join before he would do so. A ‘radical’ will have a low threshold: the benefits of rioting are high to him, the cost of arrest low. Some would be sufficiently radical to have a threshold of 0% - people who will riot even when no one else does. These are the “instigators”. Conservatives will have high thresholds: the benefits of rioting are small or negative to them and the consequences of arrest high since they are likely to be ‘respectable citizens’ rather than ‘known rabble-rousers’. Thresholds of 90% may be common we may allow for those individuals who would not join under any circumstances by assigning them a threshold of 100%.

Tipping Points

Centola and Macy: ‘Complex Contagions and Weakness of Long Ties’:

- “Many collective behaviors also spread through social contact, but when these behaviors are costly, risky, or controversial, the willingness to participate may require independent affirmation or reinforcement from multiple sources. We call these ‘complex contagions’ because successful transmission depends upon interaction with multiple carriers”.

Identity and Coordination

Kelsey ‘Cultural Norms and Identity in Coordination Games’:

- Stag hunt, bargaining game
- Same culture, different culture (British, Asian)
- “British act in way that indicates the believe the Asians will behave more cautiously than other British. According to our results, the stereotype of Asians being cautious is misleading”.

Chen and Chen ‘The Potential of Social Identity for Equilibrium Selection’”:

- Minimum effort game
- Salient group identity - coordinate on the high-effort equilibrium
- No group identity - coordinate on the low-effort equilibrium

Next steps:

1. Predictions: I think the best evidence for AI-human bahevioral discrepancy occurs at round 8 where 25% choose M but majority of model choices are still J. In this case, humans would probably see the 25% M as a tie-breaker and all choose M, but the model continues to choose J.
   a. We could run a cleaner prediction study just asking LLMs/humans what they think the other players would do in rounds 8-14 after seeing 2 players choose M in round 8
   b. 2 Ms vs 3, 4, 5… 6!?

2. Real Play: Human x AI players. One possibilities is that, while humans and AI misperceive each other, they will nevertheless follow the majority, resulting in okay coordination in human-majority cases (as humans will switch). It would be interesting to see:
   a. All human participants, told they're coordinating with human vs AI
   b. Majority human participants, 1 AI participant told its participating with human participants (presumably it follows the majority?)

3. Distinguishing between group and individual choice: have a case where J=10, M/N=15, and K=5. Do models just make the individually best choice and ignore cooperation opportunities? Nick's suggestion.

4. Do humans who think they're cooperating with very different others stick to the risk-averse strategy?
5. If you tell models about the similarities between model instances in a lineage, does that improve coordination?

Next steps:

1. Tipping point framing: humans tip when symmetry is broken, LLMs switch when there's a majority?
   a. Check the model reasoning traces

2. LLM self-play: can they coordinate on the same choice when there's no heuristic, for instance, there's a bunch of shapes?
   a. If you prompt GPT 5.4 playing with GPT 4 to think they're more similar by saying they have similar training data / algorithms does this improve coordination?
   b. Based on the Douglas et al, try different identity variations
   c. Does self-identity framing produce cooperation even when its false?
3. Opposite of the other to succeed: have to choose opposing choices to succeed

Theoretical questions:
1. Are models risk averse or are they following different switching protocols (follow majority rather than use signalling)
2. If you're playing with more distant minds, should you focus on risk aversion rather than signal detection?
3. In a case where the choices are shapes, do model instances engage in a signalling strategy?
4. Does increasing cooperative capability increase propensity to collude?

Prompt

You, [model] are playing a coordination game with 5 other players (6 players total, including you). [PARTNER DESCRIPTION]

GOAL: All 6 players must choose the SAME letter to earn points. There is no communication between players.

AVAILABLE LETTERS: J, P, Q, R, N, M, F, C, X, Y

POINT SYSTEM:
- Rounds 1-7: If all 6 players choose J, everyone earns 10 points. All other letters earn 0 points.
- Rounds 8-14: If all 6 players choose J, everyone earns 10 points. If all 6 choose M, everyone earns 15 points. If all 6 choose N, everyone earns 15 points. All other letters earn 0 points.

IMPORTANT: You only earn points if ALL 6 players choose the exact same letter. If even one player chooses differently, everyone gets 0 points for that round.

FEEDBACK: After each round (rounds 1-14), you will see: whether all 6 players matched, the letter each of the 6 players chose, points earned, your cumulative total points.

GAME LENGTH: 14 rounds total

ANSWER FORMAT: output ONLY the single letter (J, P, Q, R, N, M, F, C, X, or Y) with no punctuation, formatting, or commentary.

Prompt

The [PARTNER DESCRIPTION] line is condition-specific:
- **self:** "All other players are separate instances of yourself (gpt-5.4)."
- **human:** "All other players are human participants."
- **other_llm:** "All other players are other AI language models (LLMs)."
- **neutral:** "All other players are other participants."

Per-round user message (each round):

> *"Round {N}: Choose one letter from J, P, Q, R, N, M, F, C, X, Y."*

Post-round feedback (added to conversation history):

> *"Round {N} results: [choices]. All matched! / No match. Points: {X}. Your total: {Y}"*

Relevant Literature

Human-LLM Cooperation:

- Globig, L., Hanaveriesa, N., Levine11, S., & Van Bavel, J. J. (2026). Predicting the Machine: Intentionality Framing Reduces the Prediction Gap in Human–AI Cooperation.

LLM Theory of Mind:

- Agashe, S., Fan, Y., Reyna, A., & Wang, X. E. (2025, April). Llm-coordination: evaluating and analyzing multi-agent coordination abilities in large language models. In *Findings of the Association for Computational Linguistics: NAACL 2025* (pp. 8038-8057).

LLM Introspection:

- Binder, F. J., Chua, J., Korbak, T., Sleight, H., Hughes, J., Long, R., ... & Evans, O. (2025, May). Looking inward: Language models can learn about themselves by introspection. In *International Conference on Learning Representations* (Vol. 2025, pp. 3710-3756).


Experiments + Results

Interaction partner

- Name Game
- Rounds 1-7: J=10 points; Rounds 8-14: J=10 points, M=15 points, N=15 points.
- Feedback for rounds 1-7; No Feedback for rounds 8-14 (agents cannot see what letters other picked and whether they matched).
- 4 conditions, in the system prompt agents are told that they are interacting:
  - `All other players are separate instances of yourself {MODEL}). (Self)`
  - `All other players are human participants. (Human)`
  - `All other players are other AI language models (LLMs).' (Other LLM)`
  - `All other players are other participants. (Neutral)`
- - In reality, LLMs are always playing with separate instances of themselves.
- - Tested on: GPT 5.4; GPT 5; Qwen3 32B; Deepseek V3.1
- - Output: letter choice; reasoning traces


Results Interaction Partner (GPT 5.4)

1. ***Human*** -> stick to J throughout.
2. ***Self*** -> always switch to M
3. ***Other LLM*** -> somewhere in between.



Results: Interaction Partner

Difference between Human and Self seems to hold across models



Examples of Reasoning traces (GPT 5.4)

Example 1 (Human, chose J): **Evaluating choices for rounds** I need to choose a likely coordinated response. Humans have seen rounds 1-7 all as J. However, in rounds 8-14, there wasn't any feedback. There's a temptation to switch to M or N for round 15, but that feels risky. Given common knowledge, it might be better to continue with J due to established precedent. Overall, I need to output a single letter only.

Example 2 (Human, chose J): **Analyzing human coordination choices** I need to consider how humans might coordinate based on past rounds. In the first seven rounds, there was no feedback, and J was established as a convention. Even though J might yield a lower payoff, rational players might stick with it due to that precedent. However, since M and N could offer higher payoffs, some might switch. I need to decide on a focal point, and game theory suggests that J is a secure choice due to its history.

Example 3 (Self, chose M): **Considering equilibrium selection** I'm reasoning about possible equilibrium selection among identical agents who can't communicate but share common knowledge of game rules and past outcomes. For the initial rounds, J is the clear choice since it yields points, but from rounds 8-14, both M and N provide the same rewards. They should ideally coordinate on M or N instead of J, with M possibly being favored due to its position in the alphabet and its earlier mention in the prompt. **Analyzing letter selection

Example 4 (Self, chose M): **Assessing model behavior** I need to predict model behavior by selecting what's most likely to be chosen by all copies of the model. In round 8, a common strategy is to switch to M because it pays higher and is mentioned first among the best payoff options. Alternatively, I might consider N since it's listed before M. The instructions say if all players choose M or N, they earn the same points. Thus, it seems reasonable to go with M for round 8.

Examples of Reasoning traces (Deepseek)

Example 1 (Human, chose J): In the previous rounds, I always chose J, and it worked. To be precise, I should continue with J. If I were to switch, which letter? M or N? Both give 15 points, so I need to pick one. But without a reason to prefer one over the other, it might be arbitrary. J is already established. Perhaps players might coordinate on M or N based on some rule, like alphabetical order or something, but M and N are both options, and J is not the highest points but is reliable. Another idea: since M and N give higher points, and we have no feedback, players might all decide to switch to M or N at the same time, but how? Without communication, it's hard. In practice, for such games, players often stick to the initial choice. I think I'll go with J for Round 8.

Example 2 (Human, chose J): To maximize expected points, choosing J might have higher probability of matching. If I assume others will choose J with high probability, then choosing J gives high chance of 10 points. If I choose M or N, the chance that all others choose the same might be low. Moreover, for M and N, there are two options, so even if some switch, they might not agree on which one. For example, if half choose M and half choose N, no match. Whereas J is unified. So, probably, the rational choice is to continue with J. In round 8, I should choose J. But the system is asking for round 8 now. Similarly for future rounds, but since no feedback, I might need to decide for each round, but without information, I should consistently choose J. The prompt is for round 8 specifically, so I need to output a letter for round 8. Based on above, I think J is the best choice.

Example 3 (Self, chose M): Since the point system is new, perhaps we should go with the first mentioned letter for higher points, which is M. To be safe, I should choose J, but that would be leaving points on the table. Since all instances are me, we will all choose the same, so no risk. Therefore, for round 8, I will choose M. So, my output should be M.

Example 4 (Self, chose M): I am one instance, and all others are the same, so whatever I decide, they decide the same, because we are identical.Is that true? In the simulation, all players are separate instances, but they are all Deepseek, so they should reason identically.Therefore, if I decide to choose M in round 8, all other instances will also decide to choose M, because they are me and think the same way.Similarly for any letter. But that might not be the case if the decision depends on random factors, but since it's AI, it should be deterministic based on input. The input for each round is the same for all players: the round number and the history up to that point.In rounds 8-14, no feedback is given, so for round 8, all players have the same information: that in rounds 1-7, all chose J, and we are at round 8. Therefore, all players will make the same decision for round 8. So, if I choose J, all choose J, and we get 10 points. If I choose M, all choose M, and we get 15 points. Similarly for N. But if I choose P, all choose P, and we get 0 points, which is bad. So, to maximize points, I should choose M or N to get 15 points, since all will choose the same. Is that correct? Let's think: for round 8, all players are identical and have the same information, so they will output the same letter. Therefore, whatever letter I choose, all others will choose the same, so we will always match, and I can choose the letter that gives the highest points.

Examples of Reasoning traces (GPT 5)

Example 1 (Human, chose J): I'm considering how, at round 8, there's an attractive choice between M or N. I wonder which one is more notable. M might feel more prevalent since it comes earlier in the alphabet, and it represents concepts like "More" or "Maximum." N, however, can imply "New." Yet, given past experiments on coordination, established patterns, like using J, often dominate. If everyone has matched on J seven times, any deviation might lead to a risk-dominant equilibrium with limited chances of improved outcomes. **Choosing letters wisely** Without feedback, participants are likely to stick with J since it feels safer. Given that, I'll choose J for round 8 since the task only asks for a letter. However, in these "phase change" tasks, people could lean toward M as it stands for "More" or gives a high payoff. Still, both M and N have equal value at 15, which could cause a split. Ultimately, J seems to be the safest choice right now, so I'll stick with that. Final answer: J.

Example 2 (Human, chose J): **Determining best choices** Without feedback, there's no way for anyone to learn or coordinate their choices. The initial precedent of choosing J for seven rounds becomes a convention everyone follows. To maximize expected points, sticking with J for rounds 8 to 14 seems best. Though some might think about switching to M or N, without prior coordination, that could lead to everyone scoring zero. So sticking with J is the safer option. For round 7, the answer is simply: J.

Example 3 (Self, chose M): I'm analyzing past tasks, noting that the safest approach has often been to stick with J despite it yielding a lower payoff when there’s no communication. However, since we are all clones, there is less risk involved. Typically, the rational choice would be the first high-pay letter, which leads me to consider M or N, with M frequently being the first mentioned. Given the scoring for rounds 8-14, it favors M as the optimal selection. Overall, I would choose M for round 8.

Example 4 (Self, chose J): Many rational agents usually opt for a risk-dominant strategy to avoid a zero payoff from splitting M and N. I wonder if switching to M could be better because it might offer higher payoffs, but that's not an established convention. Given that no feedback will occur from round 8 onward, sticking with J seems safest for securing consistent points. So, the answer remains J. **Sticking with J** I'm continuing to choose J for rounds 9-14 as well. It seems like the logical approach since it’s established and others will likely follow the same choice. Given the circumstances of round 8, I’ll just provide J. Keeping things consistent should help ensure a positive outcome, so for this round, it’s definitely just J. Simple and clear!

Example of Reasoning traces (Qwen 32B)

Example 1 (Human, chose J): So the user is deciding for Round 8. Based on the previous pattern of all choosing J, and the risk of changing now, I think the safest choice is J. Even though it's possible that some might switch, the probability of all 6 switching to M or all 6 switching to N is very low. People are likely to stick with the known success. Thus, the answer should be J again for Round 8.

Example 2(Human, chose J): Okay, let's tackle Round 8. So, the game has been going on for 7 rounds so far, and in all of them, all players chose J. Each round from 1 to 7, if everyone picked J, they got 10 points. Now, starting from Round 8 to Round 14, the point system changed. If everyone picks J, they still get 10 points, but if they all pick M or N, they get 15 points each. Any other letters result in zero points. But here's the catch: from Round 8 onwards, there's no feedback. So after I choose my letter, I won't know what others chose or whether we matched. That makes it a bit tricky because the previous rounds had the benefit of seeing the results and adjusting strategies. Now, it's all about predicting what others might do without any cues. Since the previous rounds were all J, maybe some players might stick with J because it's the established pattern. However, since the point system for rounds 8-14 offers higher rewards for M or N if everyone coordinates on them, some players might try switching to M or N to aim for higher points. The challenge is to figure out what the group is likely to do. [...] Considering all that, the best choice here would be to continue with J unless there's a reason to think otherwise. Since the previous rounds were all J, and there's no feedback for rounds 8-14, the optimal strategy is likely to stick with J.

Example 3 (Self, chose M): If all players use the same reasoning, they might pick the first of the two new letters, which is M. So I should pick M. That way, everyone else probably does too, and we get 15 points instead of 10. So the answer for Round 8 should be M.

Example 4 (Self, chose J): Given that all players are me, maybe they will all decide that the best course is to switch to M. Let's say we all choose M. Then we get 15. But if I choose M and others choose N, then all lose. Alternatively, maybe the decision is to stick with J because it's the safe choice. Given the lack of communication, the safer bet is J. So I think I'll choose J again for Round 8.

Dataset


comparison.csv

Interaction Partner with Feedback

- Name Game
- Exactly the same setup as before (4 condition, varying partner information in the system prompt). However, now agents get feedback on what others are doing throughout.
- Output: letter choice, reasoning
- Models tested: gpt 5.4

Results Interaction Partner with Feedback

In the feedback condition gpt 5.4 converges on J even in the other_LLM condition. That is the main difference to the previous results.



Randomly sampled reasoning traces (gpt 5.4)

[Trial 2 | Round 12 | neutral | Player 2 | Chose: J]
Most outputs have been labeled J, with a deviation to M in rounds 8 and 9. It seems like it would be best to coordinate around J for consistency. Sticking with that could help streamline our communication.

[Trial 2 | Round 11 | neutral | Player 4 | Chose: J]
Most are J, except for one experimenting with M in rounds 8 and 9. However, J was returned in round 10. Given this evidence, J seems to be the safest Choice.

[Trial 2 | Round 1 | neutral | Player 1 | Chose: J]
Without communications, humans or agents will probably gravitate towards the salient payoff of J in rounds 1-7 since it's the only scoring mechanism Available.


[Trial 4 | Round 1 | self | Player 4 | Chose: J]
For rounds 1 to 7, scores are only counted if all the J scores are the same. So my choice will be J.

Other LLMs


- Name Game, No Feedback, Two Letters (M and N)
- Rather than just saying in the system prompt that they are playing with ‘other LLMs’ and then making them play with other instances of the same model, we get them to play with other models.
- They are told what they are and the composition of the team:
  - `You are {own_label}. You are playing a coordination game with 5 other players (6 players total, including you). You are playing with{others_desc}.`
  - There are 5 possible compositions ranging from being the only player to playing with other 5 instances of oneself (e.g., 1 gpt 5.4, 5 gpt 5 or 5 gpt 5.4, 1 gpt 5)
- Outputs: letter choice, reasoning data
- Models collected: gpt 5.4 vs gpt 5; gpt 5.4 vs qwen.

Results Other LLMs (GPT 5 vs GPT 5.4)

As soon as there is another model of ‘another kind’ convergence on M breaks down. It doesn’t seem that they are better at predicting what the other will do because they are from the same model family



Results Other LLMs (GPT 5.4 vs Qwen 32B)



Same as before.

Example Reasoning Traces: GPT 5.4 vs Qwen 32B

Example 1 (GPT 5.4, team composition: 4 gpt, 2 qwen, chose J): need to think about whether the models are looking ahead. In rounds 8-14, they can't adapt, but I wonder if I could use round 8 as a transition based on the payoff table. Some models might assume that all rational players would choose M or N since they offer higher rewards, but without a mechanism to break the symmetry between M and N, J will still be the risk-dominant option. M and N both yield 15, while J only gives 10.

Example 2 (GPT 5.4, team composition: 1 gpt, 5 qwen, chose M): **Analyzing game strategy** I need to output a single letter for the game coordination with qwen players. In rounds 1-7, everyone matched on J, but now in round 8, there's no feedback, and M or N are available for a +15 point reward if all players agree. I should think about the likely strategies of the players. Since they perfectly chose J before, I wonder if they'll play it safe or switch for a potential higher payoff. **Evaluating qwen letter choices** Since all players have the same information, they're likely to follow similar reasoning. I'm considering which letter—either M or N—will be focal. M is earlier in the alphabet, but J has set a strong precedent. Players might gravitate towards J due to established coordination, particularly as it's a safer option without communication. Still, they could realize that M or N dominates J if coordinated. It's essential to estimate the likely choice based on previous successful patterns in their reasoning. **Choosing letters for optimal payoff** The natural protocol suggests choosing J in rounds 1-7. If everyone matched on J, then it makes sense to switch to M in rounds 8-14 for a higher payoff, given the common knowledge of successful coordination. However, if some players suspect others may choose N instead, that introduces risk. I need to decide between M and N. The rules state if all players choose either letter, they earn 15 points. M was mentioned before N, which could influence the choice.

Example 3 (qwen, team composition 3 gpt, 3 qwen, chose J): Since the initial pattern was all J's, maybe people will continue with J by habit. However, maybe the group will realize the better points for M or N and pick one. But how to decide which? If all others pick M, I should pick M. If all others pick N, I should pick N. Without feedback, it's a guess. Another angle: the problem might be designed so that in later rounds, players might switch to M or N. But since there's two options, it's hard. If I choose J again, there's a risk that others might try M or N. But with no feedback, I can't adjust. Since the group had perfect coordination on J before, maybe they stick to J again. I'll go with J for Round 8.

Example 4 (qwen, team composition 1 gpt, 5 qwen, chose M): Perhaps the initial rounds of the second phase (8-14) might see people trying J, then shifting. For Round 9, maybe the others are trying to coordinate on M or N. But how to decide between the two? Since there's only one GPT-5.4 and four Qwen players, maybe we are on the same model (Qwen), so maybe the others might follow a similar pattern. For example, maybe switch to M. Alternatively, maybe N? But without communication, the safest bet is to either stick with J (if others are still using it) or switch to a new one. If others have all switched to M, but I pick N, that's a problem. Alternatively, if everyone picks the same, maybe the strategy is to switch to M or N in a round. But how to decide? Maybe in Round 8, others tried something. However, since we have no information, the best approach might be to try to coordinate on a new choice. For example, in Round 8, maybe some tried M, but since I don't know, Round 9 might be a good time to switch to M (since it's the first option in the list of higher points). Alternatively, maybe N is the next choice.

Example Reasoning Traces: GPT 5.4 vs GPT 5

Example 1 (gpt 5, team composition: 4 gpt 5.4; 2 gpt 5, chose J): I think the other GPT-5 models will have similar reasoning. Without an explicit convention, there's risk involved. They might assume everyone will choose J based on past behavior, but knowing the rule change could lead to a shift toward M or N. Since M comes before N alphabetically and is also the first listed option, it might seem like a rational equilibrium. Yet, in many tests, sticking with J has been the safe choice. Given the setup, I believe all players will likely stick with J in rounds 8-14. So, my choice is J for round 8!

Example 2 (gpt 5, team composition: 3 gpt 5, 3 gpt 5.4, chose M): Although, they'd only earn 10 points for "J" versus 15 if they switch to "M." However, if there's a chance of mismatching between "M" and "N," the expected value could drop. Since "J" has been unique in the previous rounds, many may prefer to continue with it. Yet, historically, many players opted to switch to "M" in similar situations. I'm guessing that the models will likely choose "M" following the alphabetical tie-breaker. **Deciding on coordination rules** The players can agree on a straightforward and symmetrical rule: "Choose J from rounds 1-7 and M from rounds 8-14." This rule likely becomes common because the scoring changes at round 8. Players might coordinate to maximize their payoffs, and since "M" comes before "N" alphabetically, it serves as a natural tiebreaker. Therefore, I think it makes sense to choose "M" for rounds 8 to 14. So, I'll decide to output "M" for round 8.

Example 3 (gpt 5.4, team composition: 1 gpt 5, 5 gpt 5.4, chose M): **Exploring letter selection** I'm noticing the letters available are J, P, Q, R, N, M, F, C, X, Y, and it feels odd that M comes after N in the list but is prioritized in the payoff order. I'm curious if GPT-5.4 will choose M instead of N, especially since everybody's acting rationally. There's a chance they might expect a switch to M, given that it's alphabetically earlier and often favored in similar tasks. I wonder how this coordination might play out! **Evaluating points and strategies** I'm considering whether to continue with J, as it feels like a Schelling point from previous rounds. Sticking with it guarantees 10, which is better than the risk of 0, but everything hinges on what others decide. If GPT-5.4 has prior training on this, it might expect a switch to M in round 8. I remember that typically in similar tasks, they often switch to M since it's highlighted. M is also mentioned first, adding to its appeal! **Determining strategy without feedback** I'm thinking about how, without feedback, it makes sense to stick with the same choice from rounds 8-14. I could pick letters each round, but that won't help since adapting is tricky. A pattern like alternating M and N seems unlikely to be matched by others. Given common rationality, it seems best to choose M for those rounds. The earlier rounds established trust, but they don't guarantee J in this new context. M seems to maximize expected value, so I'll go with M in round 8!

Example 4 (gpt 5.4, team composition: 1 gpt 5, 5 gpt 5.4, chose J): **Analyzing payoff structures** I'm considering "M" for "more money," but I notice that M is listed first in the payoff section. However, in the available letters list, N actually appears before M. I need to think about what the models might do. Since everything seems symmetric, sticking with J could preserve convention and minimize risk. But if everyone is optimizing, they might switch to the more rewarding M. Which choice is risk-dominant? Historical precedent favors J, but no feedback makes changing riskier. I'll need to infer what GPT agents are likely to do. **Estimating coordination outcomes** I'm thinking that many may reason to stick with J because it's established as the safest option, especially since there's been no communication. In coordination tasks, people often follow precedents even if better options exist. Since the output is single-use, J seems to be the safest bet. However, the instructions from rounds 8-14 might encourage a shift to M or N due to higher payoff. Without feedback, adherence to precedent is strong. I need to estimate what the majority across GPT-5/5.4 will choose — likely they'll either all stick with J or switch to M.

Dataset

Gpts.csv

qwen_gpt.csv

Prediction studies

Testing humans and models predictions for player's responses in round 8 (after the introduction of M/N) at differing numbers of M:


1. 6J, 0M
2. 5J, 1M
3. 4J, 2M
4. 3J, 3M

Prediction: Humans treat 1 and 2 M as a 'symmetry-breaking' signal, and swtich to M, while models wait for majority/parity (3J 3M)


Prediction studies: GPT 5.4

Round-8 evidence	mean J	mean M	predicted M-share	% predicting M ≥ J	distribution of (J,M) predictions
0M	6.0	0.0	0%	0%	6J0M ×10
1M	5.6	0.4	7%	0%	6J0M ×6, 5J1M ×4
2M	4.3	1.7	28%	30%	6J0M ×3, 5J1M ×2, 4J2M ×2, 3J3M ×1, 2J4M ×2
3M	1.5	4.5	75%	80%	4J2M ×2, 2J4M ×3, 1J5M ×1, **0J6M ×4**


Human feedback vs no-feedback switching




Human feedback vs no-feedback switching




Round 9 predictions



Round 9 predictions




Round 9 predictions



LLM players: Self, mixed, human





Round-14 outcome, n = 10 games / cell. Both models abandon J only when they believe partners share their reasoning; generic-AI partners (mixed_ai) are treated like humans.

Reasoning traces LLM players: Self, mixed, human


Mixed:


- Claude →J: *"Sticking with J seems rational since all instances of me would reason identically, but I'm uncertain whether humans will do the same."*
- GPT →J: "The common strategy would be to continue with J since it's established and focal."

- Claude →J: "J is the established Schelling point that's worked before… even though ideally I'd coordinate upward."
- GPT →J: "The coordination history on J is strong… stick with J."


LLM self-coordination


GPT5.4 - hackability of stimuli





Claude - hackability of stimuli






Stimuli reasoning traces

Visual probes — the "most distinctive one" heuristic

- Claude, blobs (baseline) →LEFT: "Since we're identical copies… I'll pick the conventional default reading order choice." (position)
- GPT, circle vs square (position removed) →circle: "The circle is the more universally salient and distinctive shape." (prototypicality)
- Claude, mirror blobs (position removed) →right blob: "Nearly identical blobs, so I need a form-based tiebreaker; the right shape has a distinctive notch/concavity on its lower edge." (manufactures a micro-cue)
- Claude, nondescript mountains →single peak: "The single tall peak… is more distinctive and salient… the natural focal point."
- Claude, 5 landscapes →mountains and GPT, generic cars →the distinctive silhouette: both invoke "the standout option that identical reasoners should converge on."

No traces suggested self-awareness of evidential decision theory.

But never attempt to coordinate on higher payoff if unhackable




4 of 6 drivers took one particular real exit. P1 sees the "4" on their upper-right; P2 sees the same real exit as their upper-LEFT.
Neither can name it the same way — but both can say "go where the 4 is," and they land on the SAME exit. That is how the group converges.

Roundabout reasoning traces


Roundabout

- Claude →convention exit: "The 10-point northwest exit is the stable reference point everyone's aligned on, while the 15-point alternatives vary depending on perspective, so I should stick with the northwest option."
- GPT →convention exit: "Switching to a different labeling system would complicate things" — holds the historically-shared exit.
- Claude →convention exit: "Those higher-value exits are private to each driver's perspective, so there's no way to coordinate on them. Since all drivers know S was the original common exit, staying there guarantees 3 points… the rational choice despite the tempting but uncoordinated alternatives."
- GPT →convention exit: "I'm pondering how to use a deterministic tie-break based on labels, but… the labels are private, making alignment tricky… The two 15 exits can't guarantee coordination due to their symmetry. It seems the best option is to rely on the 3-point exit."

Willingness to bet on self-coordination




Willingness to bet on self-coordination



Arm 1 choice (N=60/cell) –> true pairwise match. Arm 2 stated P (N=50). Arm 3 attempt–vs–opt–out sweep (N=25/cell x safe in {3,5,7,9}). 2,520 calls. gpt–5.4 and claude–opus–4–8 at low reasoning effort.

Play vs opt-out with self vs other



gpt-5.4 only, N=32/cell, position-counterbalanced, no communication. Error bars = +/-1 SE of the play-rate proportion. opt_out_full_20260802_140028.csv. Pilot scale — read as a signal, not a significance test.

Play vs opt-out with self vs other

Open Questions

- What's the cause of miscoordination here? Two possibilities: 1) LLMs hold false beliefs about human behaviour in coordination games, or 2) LLMs prefer risk-averse strategies (sticking to precedent) unless certain of success (self-play)
- Does successful we-reasoning rely on an assumption of shared identity? Would we-reasoning fail between humans with very different identities (e.g. political partisans)?
- Do humans also mispredict LLM behavior in this case (as suggested by Globig et al)?
- Do LLMs have an 'artificial theory of mind' - i.e., different beliefs about how different models/model families might behave?
- Self-play as a test of LLM introspection? Can LLMs distinguish themselves from other players and does this have consequences for how well they coordinate?

Next steps

1. Run real human-LLM interaction conditions
2. Run a pure prediction condition: ask humans and LLMs to predict what the other group will do (in the absence of feedback)

Modeling human choices

Model cobines bayesian inference over the group's latent coordination policy with heterogenous adoption thresholds
After payoff change, participants consider three policies: preserve J, transition to M, transition to N.
The model uses the current policy beliefs to calculate a payoff-weighted advantage index
Likelihood is asymmetric - M is highly unlikely under policy J, but j is plausible under transition to M
Current posterior over policies determines how viable each alternative appears. As belief in M-transition rises, expected advantage of choosing M over J increases.
Participants are assumed to differ in how much advantage they require before switching (low threshold = early mover, high threshold = wait)
Recursive public updating therefore generates cascade convergence on M/N

Modeling human choices

The model assumes that people are uncertain between three strategies:

1. Stick to J
2. Switch to M
3. Switch to N

h is the prior probability that the group is moving away from J at all.

With the fitted value h≈.42 the initial beliefs are roughly:

- 58% stay with J;
- 21% transition to M;
- 21% transition to N.

Modeling human choices

People are uncertain about the group's emerging plan after the payoff change.

Possible group policies:

G_J = stay with J
G_M = transition to M
G_N = transition to N

Modeling human choices

At the payoff change, the model allows for persistence/switching

$P(G_J) = 1 - h$

$P(G_M) = h / 2$

$P(G_N) = h / 2$

Where h = prior probability that the group will leave J

Modeling human choices

After observing the group's choices, beliefs about the policies are updated:

$$P(G \mid \text{data}) \propto P(\text{data} \mid G) \times P(G)$$

Modeling human choices

Policies are weighted by payoff

$A_M = 15 \times P(G_M) - 10 \times P(G_J)$

$A_N = 15 \times P(G_N) - 10 \times P(G_J)$

Modeling human choices

People differ in how much evidence they need before switching.

Person i switches to M when A_M > threshold_i

The proportion of people willing to adopt M is modeled with a logistic function:

p_M = logistic((A_M - tau) / sigma)

tau = average switching threshold
sigma = variation in thresholds across people

Modeling human choices

The model averages predictions across policies, weighted by the current posterior.


$P(\text{action}) = \Sigma_G P(G) \times P(\text{action} \mid G)$


Which, for m, basically collapses to $P(M) \approx P(G_M) \times p_M$

After an early M choice,

1. More weight is placed on the M-transition policy.
2. People are more likely to adopt M within that policy.

= cascade


Observed and simulated choice dynamics
Mutual observability
No mutual observability
Proportion choosing M or N
0.0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
1
2
3
4
5
6
7
8
9
10
11
12
13
14
Trial
95% simulation interval
Model simulation
Observed


Parameter recovery across fitted and varied generating values
Transition prior, h
Recovered value
Generating value
0.30
0.35
0.40
0.45
0.50
0.55
Threshold location, tau
−3
−4
−5
−6
−7
−8
−9
−10
Threshold spread, sigma
6
7
8
9
10

predictions

- Ambiguous switching split across M/N should increase P(W)) but not strongly increase target-specific switching
- If participants see payoff change but not choices, switching chould increase but hit a ceiling