

Performance Estimation, Testing, and Control of Cyber-Physical Systems Employing Non-Ideal Communications Networks

Extended Abstract

Richard Candell
Université de Bourgogne

Abstract—Wireless technology is a key enabler of the promises of Industry 4.0 (Smart Manufacturing). As such, wireless technology will be adopted as a principal mode of communication within the factory beginning with the factory enterprise and eventually being adopted for use within the factory workcell. Factory workcell communication has particular requirements on latency, reliability, scale, and security that must first be met by the wireless communication technology used. Wireless is considered a non-ideal form of communication in that when compared to its wired counterparts, it is considered less reliable (lossy) and less secure. These possible impairments lead to delay and loss of data in industrial automation system where determinism, security, and safety is considered paramount. This thesis investigates the wireless requirements of the factory workcell and applicability of existing wireless technology, it presents a modeling approach to discovery of architecture and data flows using SysML, it provides a method for the use of graph databases to the organization and analysis of performance data collected from a testbed environment, and finally provides an approach to using machine learning in the evaluation of cyberphysical system performance.

INTRODUCTION

Smart Manufacturing provides a vision of future manufacturing systems that incorporate highly dynamic physical systems, robust and responsive communications systems, and computing paradigms to maximize efficiency, enable mobility, and realize the promises of the digital factory. Wireless technology is a key enabler of that vision. Wireless communication is inherently more prone to latency and delay than wired counterparts. In addition, wireless communication implies the utilization of the electromagnetic spectrum which is a publicly accessible medium with constrained capacity and more prone to cyber-attack. While transmitted data can be digitally protected through authentication and encryption, wireless devices are prone to interference and jamming by both rogue and friendly emitters exacerbating the reliability and latency concern impacting factory performance without compromising data security. Wireless communication in factories is often constrained by battery life and most certainly constrained by the availability of the electromagnetic spectrum. As the reliance on wireless devices within the factory continues, steps toward developing a more robust wireless factory communications network must be developed. These steps include:

- ★ The automation system must become situationally aware and adaptive to knowledge of the trends in electromagnetic spectrum occupancy and acute events; and
- ★ Intelligence of the automation system must move closer to the physical system. This means moving the intelligence for control to the actuator; and
- ★ Performance test methods must be developed and incorporated into the industrial fringe devices. The test methods must be dependable and at the same time easy to use by factory personal not trained in the technicalities of wireless communication; and
- ★ Existing Wireless communications protocols must be analyzed and adapted, and new protocols must be developed to balance reliability, latency, and scalability; and
- ★ Security of the network must be maintained and must include availability as a paramount characteristic.

This thesis includes development of test approaches for measuring the performance of industrial wireless networks deployed within smart manufacturing work-cells. Thus the primary goal of this thesis is the discovery of methods and approaches to the evaluation of industrial uses cases performance for those use case in which wireless communication technology is used as the principal mode of communication. The primary motivation of the research is to discover practical test and evaluation methods for assessing performance of an industrial workcell thereby improving security, safety, and reliability in general. Findings and results of the thesis work are included within the thesis and published as journal articles and conference proceedings. Resulting data is also made available.

CONTRIBUTIONS AND ORGANIZATION

This thesis is presented in three major parts. In Part I, the thesis provides a historical introduction to the context of smart manufacturing. It presents the premises of industrial wireless technology, key challenges to using wireless within a factory environment, and the accepted indicators that are currently used in the application of wireless within factory environments. Then, the existing state of the art is presented to orient the reader for the thesis contribution. This state of the art includes a discussion of the industrial wireless technology landscape, standards, and a tentative mapping of

those technologies to application domains. A discussion of the systems modeling approaches is then provided with a focus on the Systems Markup Language. Then a discussion of approaches to the use of databases follows. In Part II, *Thesis Contributions*, the technical contributions of this thesis are presented. Finally, in Part III, the thesis provides a detailed discussion of the four major contributions of this thesis work. Concluding remarks and future direction are provided as an opinion of the thesis candidate. The thesis contributions are presented as follows:

Requirements [1] [2] [3] [4] An examination of the wireless technology landscape is conducted. Existing and future wireless technologies are assessed for their appropriate applicability to industrial use cases.

Modeling [5] [6] In an effort to better understand the architectural composition of the workcell using industrial wireless communication, modeling techniques are used to identify and decomposed the parts, interfaces, and data flows. SysML is adopted for this process and a proposed modeling library is created and presented. The model with conceptual diagram is made publicly available independent of the tool that was used to create the model.

Application of Graph Database [7] A method is developed for collecting, cleaning, organizing, and presenting the cyberphysical performance indicators of experiments run within the NIST Industrial Wireless Testbed. The method developed utilizes the Neo4j graph database and is presented as a novel approach as compared to traditional approaches using relational database, spreadsheets, and raw file processing.

Machine Learning [8] [9] A machine learning technique is developed and applied to the prediction of signal-to-interference levels within a wireless factory workcell network employing a robot arm within a force-seeking apparatus. The machine learning method allows a trained network to accurately determine the signal-to-interference level using the physical state of the robot arm rather than the state of the wireless link itself.

An additional contribution by the author for which he was not primary author but took a substantial role is cited here [10]. In this work, the author designed, constructed, and executed an experiment in collaboration with the main author in which a typical two-dimensional gantry apparatus was controlled by a local controller which received G-code commands wirelessly over a Wi-Fi network. The industrial wireless channel was replicated using a radio frequency (RF) channel emulator where various scenarios were considered and various wireless channel parameters were studied. The movement of the gantry system tool was tracked using a vision tracking system to quantify the impact of the wireless channel on the system performance. Numerical results were presented including the total run time of an industrial process and the dwell times at various positions through the process. This contribution is not discussed within the thesis.

REFERENCES

- [1] R. Candell and M. Kashef, "Industrial wireless: Problem space, success considerations, technologies, and future direction," in *2017 Resilience Week (RWS)*, Sep. 2017, pp. 133–139.
- [2] K. Montgomery, R. Candell, Y. Liu, and M. Hany, "Wireless User Requirements for the Factory Work-cell," Tech. Rep., 2019. [Online]. Available: <https://www.nist.gov/publications/wireless-user-requirements-factory-workcell>
- [3] R. Candell, M. Hany, K. B. Lee, Y. Liu, J. Quimby, and K. Remley, "Guide to industrial wireless systems deployments," National Institute of Standards and Technology, Gaithersburg, MD, Tech. Rep., Apr. 2018. [Online]. Available: <http://nvlpubs.nist.gov/nistpubs/ams/NIST.AMS.300-4.pdf>
- [4] R. Candell, M. Kashef, Y. Liu, K. B. Lee, and S. Foufou, "Industrial wireless systems guidelines: Practical considerations and deployment life cycle," in *IEEE Industrial Electronics Magazine*, vol. 12, no. 4, pp. 6–17, Dec. 2018.
- [5] R. Candell, M. Kashef, Y. Liu, and S. Foufou, "A sysml representation of the wireless factory work cell," *The International Journal of Advanced Manufacturing Technology*, pp. 1–22, 2019.
- [6] R. Candell, "A SysML Model of the Wireless Factory Work-cell," *NIST Journal of Research*, 2018.
- [7] R. Candell, M. Kashef, Y. Liu, K. Montgomery, and S. Foufou, "A graph database approach to wireless iiot work-cell performance evaluation," in *Proceedings of the 2020 IEEE International Conference on Industrial Technology*, Feb. 2020.
- [8] R. Candell, K. Montgomery, M. Kashef, Y. Liu, and S. Foufou, "Wireless interference estimation using machine learning in a robotic force-seeking scenario," in *2019 IEEE 28th International Symposium on Industrial Electronics (ISIE)*, Jun. 2019, pp. 1334–1341.
- [9] —, "Machine learning based wireless interference estimation in a robotic force-seeking application," *Engineering Applications of Artificial Intelligence*, 2020, to appear.
- [10] *On the Impact of Wireless Communications on Controlling a Two-Dimensional Gantry System*, ser. International Manufacturing Science and Engineering Conference, vol. Volume 1: Additive Manufacturing; Manufacturing Equipment and Systems; Bio and Sustainable Manufacturing, 06 2019, v001T02A005. [Online]. Available: <https://doi.org/10.1115/MSEC2019-2896>