

# Phylotrack: C++ and Python libraries for *in silico* phylogenetic tracking

Emily Dolson<sup>1,2¶</sup>, Santiago Rodruiguez-Papa<sup>1</sup>, and Matthew Andres Moreno<sup>3,4</sup>

<sup>1</sup> Department of Computer Science and Engineering, Michigan State University, East Lansing, MI, USA  
<sup>2</sup> Ecology, Evolution, and Behavior, Michigan State University, East Lansing, MI, USA <sup>3</sup> Department of Ecology and Evolutionary Biology, University of Michigan, Ann Arbor, MI, USA <sup>4</sup> Center for the Study of Complex Systems, University of Michigan, Ann Arbor, MI, USA ¶ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Frederick Boehm](#) ↗

## Reviewers:

- [@RussellGarwood](#)
- [@CFGrote](#)

Submitted: 14 July 2023

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

*In silico* evolution instantiates the processes of heredity, variation, and differential reproductive success (the three “ingredients” for evolution by natural selection) within digital populations of computational agents. Consequently, these populations undergo evolution ([Pennock, 2007](#)), and can be used as virtual model systems for studying evolutionary dynamics. This experimental paradigm — used across biological modeling, artificial life, and evolutionary computation — complements research done using *in vitro* and *in vivo* systems by enabling the user to conduct experiments that would be impossible in the lab or field ([E. Dolson & Ofria, 2021](#)). One key benefit is complete, exact observability. For example, it is possible to perfectly record the full set of parent-child relationships over the history of a population, yielding precise and accurate phylogenies (ancestry trees). This information reveals the sequences of events behind gain, loss, or maintenance of specific traits, and also facilitates making inferences about the underlying evolutionary dynamics of a given system [moosers1997inferring;E. Dolson et al. ([2020](#));Moreno et al. ([in press](#))].

The Phylotrack project provides libraries for tracking and analyzing phylogenies in *in silico* evolution. The project is composed of 1) Phylotracklib: a header-only C++ library, developed under the umbrella of the Empirical project ([Ofria et al., 2020](#)), and 2) Phylotrackpy: a Python wrapper around Phylotracklib, created with Pybind11 ([Jakob et al., 2017](#)). Both components supply a public-facing API to attach phylogenetic tracking to digital evolution systems, as well as a stand-alone interface for measuring a variety of popular phylogenetic topology metrics ([Tucker et al., 2017](#)). The underlying algorithm design prioritizes efficiency, allowing Phylotrack to support large agent populations with rapid generational turnover. The underlying C++ implementation ensures fast, memory-efficient performance, with multiple explicit features (e.g., phylogeny pruning and abstraction, etc.) for reducing the memory footprint of phylogenetic information.

## Statement of Need

*In silico* evolution work enjoys a rich history of phylogenetic measurement and analysis, and many systems facilitate tracking phylogenies ([Bohm et al., 2017](#); [De Rainville et al., 2012](#); [Garwood et al., 2019](#); [Ofria & Wilke, 2004](#); [Ray, 1992](#)). However, to our knowledge, no other general-purpose perfect phylogeny tracking library exists; prior work has used bespoke system- or framework-specific implementations. In contrast, Phylotrack provides ready-built tracking flexible enough to attach to any population of digital replicating entities.

Two other general-purpose libraries for phylogenetic record-keeping do exist: hstrat and

Automated Phylogeny Over Geological Timescales (APOGeT). However, they provide different modes of phylogenetic instrumentation than Phylotrack does. Whereas Phylotrack uses a graph-based approach to perfectly record asexual phylogenies, the hstrat library implements hereditary stratigraphy, a recently developed method that allows robust decentralized phylogenetic tracking in parallel and distributed systems at the cost of a tunable reduction in accuracy (Moreno et al., 2022b) (see (Moreno et al., in review) for a more thorough comparison). APOGeT, in turn, focuses on tracking speciation in sexually-reproducing populations (Godin-Dubois et al., 2019).

Vast amounts of bioinformatics-oriented phylogenetics software is also available. These programs' purposes typically include - inferring phylogenies from extant organisms (and sometimes fossils) (Challa & Neelapu, 2019), - sampling phylogenies from theoretical models of population and species dynamics (Stadler, 2011), - cross-referencing phylogenies with other data (e.g., spatial species distributions) (Emerson & Gillespie, 2008), and - analyzing and manipulating tree structures (Cock et al., 2009; Sand et al., 2014; Smith, 2020; Sukumaran & Holder, 2010).

Phylotrack overlaps with these goals only in that it also provides tree statistic implementations. We chose to include this feature to facilitate fast during-simulation calculations of these metrics. Notably, the problem of tracking a phylogeny within an agent-based program is substantially different from the more traditional problem of reconstructing a phylogeny. Users new to working with recorded phylogenies should refer to the Phylotrackpy documentation for notes on subtle structural differences from reconstructed phylogenies.

Phylotrack has contributed to a variety of published research projects. Phylotracklib has been integrated into packages such as Modular Agent-Based Evolver (MABE) 2.0 (Bohm et al., 2019), Symbulation (Vostinar & Ofria, 2019), and even a fork of the Avida digital evolution platform (E. Dolson et al., 2020; Ofria & Wilke, 2004). Through these integrations, Phylotracklib has enabled research on open-ended evolution (E. L. Dolson et al., 2019), the origin of endosymbiosis (Johnson et al., 2022), the importance of phylogenetic diversity for machine learning via evolutionary computation (Hernandez et al., 2022; Shahbandegan et al., 2022), and more. Phylotrackpy is newer, but it has already served as a point of comparison in the development of other phylogenetic tools (Moreno et al., 2022a, in press).

## Features

**Lineage Recording:** The core functionality of Phylotrack is recording asexual phylogenies. To achieve this goal, Phylotrack need only be notified of each agent creation and destruction event. To reduce memory overhead, extinct branches are pruned from phylogenies by default, but this feature can be disabled. The level of abstraction (i.e. what constitutes a taxonomic unit) can be customized via a user-provided function. Supplemental data about each taxonomic unit can be stored efficiently.

Lineage recording in phylotrackpy is efficient. The worst-case time complexity is  $O(1)$  (Moreno et al., in review). Space complexity is harder to meaningfully calculate, but should be  $O(N)$  on average in most evolutionary scenarios (where  $N$  is population size) (Moreno et al., in review).

**Serialization:** Phylotrack outputs data in the Artificial Life Standard Phylogeny format (Lalejini et al., 2019) to facilitate interoperability with an associated ecosystem of software converters, analyzers, visualizers. As these tools support conversion to bioinformatics-standard formats (e.g., Newick, phyloXML, etc.), Phylotrack phylogenies can also be analyzed with tools designed for biological data. Phylogeny data can be restored from file, enabling post-hoc calculation of phylogenetic topology statistics.

**Phylogenetic Topology Statistics:** Support is provided for - Average phylogenetic depth across taxa - Average origin time across taxa - Most recent common ancestor origin time - Shannon diversity (Spellerberg & Fedor, 2003) - Colless-like index (Mir et al., 2018) - Mean, sum, and variance of evolutionary distinctiveness (Isaac et al., 2007; Tucker et al., 2017) - Mean, sum,

91 and variance pairwise distance (Clarke & Warwick, 1998, 2001; Tucker et al., 2017; Webb et  
92 al., 2002) - Phylogenetic diversity (Faith, 1992) - Sackin's index (Shao & Sokal, 1990)

## 93 Future Work

94 The primary current limitation of Phylotrack is its incompatibility with sexually-reproducing  
95 populations (unless tracking is done per-gene). We plan to extend Phylotrack in a future  
96 release to allow multiple parents per taxon.

## 97 Acknowledgements

98 This research was supported in part by Michigan State University through the computational  
99 resources provided by the Institute for Cyber-Enabled Research.

## 100 References

- 101 Bohm, C., G., N. C., & Hintze, A. (2017). *MABE (modular agent based evolver): A framework*  
102 *for digital evolution research*. 14, 76–83. [https://doi.org/10.7551/ecal\\_a\\_016](https://doi.org/10.7551/ecal_a_016)
- 103 Bohm, C., Lalejini, A., Schossau, J., & Ofria, C. (2019). MABE 2.0: An introduction to  
104 MABE and a road map for the future of MABE development. *Proceedings of the Genetic*  
105 *and Evolutionary Computation Conference Companion*, 1349–1356. [https://doi.org/10.](https://doi.org/10.1145/3319619.3326825)  
106 [1145/3319619.3326825](https://doi.org/10.1145/3319619.3326825)
- 107 Challa, S., & Neelapu, N. R. R. (2019). Phylogenetic trees: Applications, construction, and  
108 assessment. *Essentials of Bioinformatics, Volume III: In Silico Life Sciences: Agriculture*,  
109 167–192. [https://doi.org/10.1007/978-3-030-19318-8\\_10](https://doi.org/10.1007/978-3-030-19318-8_10)
- 110 Clarke, K. R., & Warwick, R. M. (1998). Quantifying structural redundancy in ecological  
111 communities. *Oecologia*, 113(2), 278–289. <https://doi.org/10.1007/s004420050379>
- 112 Clarke, K. R., & Warwick, R. M. (2001). A further biodiversity index applicable to species  
113 lists: Variation in taxonomic distinctness. *Marine Ecology Progress Series*, 216, 265–278.  
114 <https://doi.org/10.3354/meps216265>
- 115 Cock, P. J., Antao, T., Chang, J. T., Chapman, B. A., Cox, C. J., Dalke, A., Friedberg, I.,  
116 Hamelryck, T., Kauff, F., Wilczynski, B., & others. (2009). Biopython: Freely available  
117 python tools for computational molecular biology and bioinformatics. *Bioinformatics*,  
118 25(11), 1422–1423. <https://doi.org/10.1093/bioinformatics/btp163>
- 119 De Rainville, F.-M., Fortin, F.-A., Gardner, M.-A., Parizeau, M., & Gagné, C. (2012). DEAP: A  
120 Python framework for evolutionary algorithms. *Proceedings of the 14th Annual Conference*  
121 *Companion on Genetic and Evolutionary Computation*, 85–92. [https://doi.org/10.1145/](https://doi.org/10.1145/2330784.2330799)  
122 [2330784.2330799](https://doi.org/10.1145/2330784.2330799)
- 123 Dolson, E. L., Vostinar, A. E., Wiser, M. J., & Ofria, C. (2019). The MODES toolbox:  
124 Measurements of open-ended dynamics in evolving systems. *Artificial Life*, 25(1), 50–73.  
125 [https://doi.org/10.1162/artl\\_a\\_00280](https://doi.org/10.1162/artl_a_00280)
- 126 Dolson, E., Lalejini, A., Jorgensen, S., & Ofria, C. (2020). Interpreting the tape of life: Ancestry-  
127 based analyses provide insights and intuition about evolutionary dynamics. *Artificial Life*,  
128 26(1), 1–22. [https://doi.org/10.1162/artl\\_a\\_00313](https://doi.org/10.1162/artl_a_00313)
- 129 Dolson, E., & Ofria, C. (2021). Digital evolution for ecology research: A review. *Frontiers in*  
130 *Ecology and Evolution*, 9, 852. <https://doi.org/10.3389/fevo.2021.750779>

- Emerson, B. C., & Gillespie, R. G. (2008). Phylogenetic analysis of community assembly and structure over space and time. *Trends in Ecology & Evolution*, 23(11), 619–630. <https://doi.org/10.1016/j.tree.2008.07.005>
- Faith, D. P. (1992). Conservation evaluation and phylogenetic diversity. *Biological Conservation*, 61(1), 1–10. [https://doi.org/10.1016/0006-3207\(92\)91201-3](https://doi.org/10.1016/0006-3207(92)91201-3)
- Garwood, R. J., Spencer, A. R. T., & Sutton, M. D. (2019). REvoSim: Organism-level simulation of macro- and microevolution. *Palaeontology*, 62(3), 339–355. <https://doi.org/10.1111/pala.12420>
- Godin-Dubois, K., Cussat-Blanc, S., & Duthen, Y. (2019, August). APOGeT: Automated phylogeny over geological timescales. <https://doi.org/10.13140/rg.2.2.33781.93921>
- Hernandez, J. G., Lalejini, A., & Dolson, E. (2022). What can phylogenetic metrics tell us about useful diversity in evolutionary algorithms? In W. Banzhaf, L. Trujillo, S. Winkler, & B. Worzel (Eds.), *Genetic programming theory and practice XVIII* (pp. 63–82). Springer Nature Singapore. [https://doi.org/10.1007/978-981-16-8113-4\\_4](https://doi.org/10.1007/978-981-16-8113-4_4)
- Isaac, N. J. B., Turvey, S. T., Collen, B., Waterman, C., & Baillie, J. E. M. (2007). Mammals on the EDGE: Conservation priorities based on threat and phylogeny. *PLOS ONE*, 2(3), e296. <https://doi.org/10.1371/journal.pone.0000296>
- Jakob, W., Rhineland, J., & Moldovan, D. (2017). *pybind11 – seamless operability between C++11 and Python*.
- Johnson, K., Welch, P., Dolson, E., & Vostinar, A. E. (2022, July 18). *Endosymbiosis or bust: Influence of ectosymbiosis on evolution of obligate endosymbiosis*. ALIFE 2022: The 2022 conference on artificial life. [https://doi.org/10.1162/isal\\_a\\_00488](https://doi.org/10.1162/isal_a_00488)
- Lalejini, A., Dolson, E., Bohm, C., Ferguson, A. J., Parsons, D. P., Rainford, P. F., Richmond, P., & Ofria, C. (2019). Data standards for artificial life software. *ALIFE 2019: The 2019 Conference on Artificial Life*, 507–514. [https://doi.org/10.1162/isal\\_a\\_00213](https://doi.org/10.1162/isal_a_00213)
- Mir, A., Rotger, L., & Rosselló, F. (2018). Sound colless-like balance indices for multifurcating trees. *PLOS ONE*, 13(9), e0203401. <https://doi.org/10.1371/journal.pone.0203401>
- Moreno, M. A., Dolson, E., & Ofria, C. (2022a). Hereditary stratigraphy: Genome annotations to enable phylogenetic inference over distributed populations. *ALIFE 2022: The 2022 Conference on Artificial Life*, 65–66. [https://doi.org/10.1162/isal\\_a\\_00550](https://doi.org/10.1162/isal_a_00550)
- Moreno, M. A., Dolson, E., & Ofria, C. (2022b). Hstrat: A python package for phylogenetic inference on distributed digital evolution populations. *Journal of Open Source Software*, 7(80), 4866. <https://doi.org/10.21105/joss.04866>
- Moreno, M. A., Dolson, E., & Rodriguez-Papa, S. (in press). Toward phylogenetic inference of evolutionary dynamics at scale. *ALIFE 2023: The 2023 Conference on Artificial Life*.
- Moreno, M. A., Rodriguez-Papa, S., & Dolson, E. (in review). *Lineage tracking algorithms and the streaming curation problem*.
- Ofria, C., Moreno, M. A., Dolson, E., Lalejini, A., Rodriguez Papa, S., Fenton, J., Perry, K., Jorgensen, S., hoffmanriley, grenewode, Baldwin Edwards, O., Stredwick, J., cgnitash, theycallmeHeem, Vostinar, A., Moreno, R., Schossau, J., Zaman, L., & djrain. (2020). *Empirical: C++ library for efficient, reliable, and accessible scientific software* (Version 0.0.4). <https://doi.org/10.5281/zenodo.4141943>
- Ofria, C., & Wilke, C. O. (2004). Avida: A software platform for research in computational evolutionary biology. *Artificial Life*, 10(2), 191–229. <https://doi.org/10.1162/106454604773563612>

- 176 Pennock, R. T. (2007). Models, simulations, instantiations, and evidence: The case of digital  
177 evolution. *Journal of Experimental & Theoretical Artificial Intelligence*, 19(1), 29–42.  
178 <https://doi.org/10.1080/09528130601116113>
- 179 Ray, T. (1992). Evolution, ecology and optimization of digital organisms. *Santa Fe Insti-*  
180 *tute Working Paper*, 92. [https://homeostasis.scs.carleton.ca/~soma/adapsec/readings/](https://homeostasis.scs.carleton.ca/~soma/adapsec/readings/tierra-92-08-042.pdf)  
181 [tierra-92-08-042.pdf](https://homeostasis.scs.carleton.ca/~soma/adapsec/readings/tierra-92-08-042.pdf)
- 182 Sand, A., Holt, M. K., Johansen, J., Brodal, G. S., Mailund, T., & Pedersen, C. N. (2014).  
183 tqDist: A library for computing the quartet and triplet distances between binary or general  
184 trees. *Bioinformatics*, 30(14), 2079–2080. <https://doi.org/10.1093/bioinformatics/btu157>
- 185 Shahbandegan, S., Hernandez, J. G., Lalejini, A., & Dolson, E. (2022). Untangling phy-  
186 logenetic diversity's role in evolutionary computation using a suite of diagnostic fitness  
187 landscapes. *Proceedings of the Genetic and Evolutionary Computation Conference Com-*  
188 *panion*, 2322–2325. <https://doi.org/10.1145/3520304.3534028>
- 189 Shao, K.-T., & Sokal, R. R. (1990). Tree balance. *Systematic Zoology*, 39(3), 266–276.  
190 <https://doi.org/10.2307/2992186>
- 191 Smith, M. R. (2020). TreeDist: Distances between phylogenetic trees. R package version  
192 2.6.1. In *Comprehensive R Archive Network*. <https://doi.org/10.5281/zenodo.3528124>
- 193 Spellerberg, I. F., & Fedor, P. J. (2003). A tribute to claude shannon (1916–2001) and a plea  
194 for more rigorous use of species richness, species diversity and the 'shannon–wiener' index.  
195 *Global Ecology and Biogeography*, 12(3), 177–179. [https://doi.org/10.1046/j.1466-822X.](https://doi.org/10.1046/j.1466-822X.2003.00015.x)  
196 [2003.00015.x](https://doi.org/10.1046/j.1466-822X.2003.00015.x)
- 197 Stadler, T. (2011). Simulating Trees with a Fixed Number of Extant Species. *Systematic*  
198 *Biology*, 60(5), 676–684. <https://doi.org/10.1093/sysbio/syr029>
- 199 Sukumaran, J., & Holder, M. T. (2010). DendroPy: A python library for phylogenetic  
200 computing. *Bioinformatics*, 26(12), 1569–1571. [https://doi.org/10.1093/bioinformatics/](https://doi.org/10.1093/bioinformatics/btq228)  
201 [btq228](https://doi.org/10.1093/bioinformatics/btq228)
- 202 Tucker, C. M., Cadotte, M. W., Carvalho, S. B., Davies, T. J., Ferrier, S., Fritz, S. A., Grenyer,  
203 R., Helmus, M. R., Jin, L. S., Mooers, A. O., Pavoine, S., Purschke, O., Redding, D. W.,  
204 Rosauer, D. F., Winter, M., & Mazel, F. (2017). A guide to phylogenetic metrics for  
205 conservation, community ecology and macroecology. *Biological Reviews*, 92(2), 698–715.  
206 <https://doi.org/10.1111/brv.12252>
- 207 Vostinar, A. E., & Ofria, C. (2019). Spatial structure can decrease symbiotic cooperation.  
208 *Artificial Life*, 24(4), 229–249. [https://doi.org/10.1162/artl\\_a\\_00273](https://doi.org/10.1162/artl_a_00273)
- 209 Webb, C. O., Ackerly, D. D., McPeck, M. A., & Donoghue, M. J. (2002). Phylogenies  
210 and community ecology. *Annual Review of Ecology and Systematics*, 33(1), 475–505.  
211 <https://doi.org/10.1146/annurev.ecolsys.33.010802.150448>