

Department of Computer Science

Gujarat University



Certificate

Roll No: 39

Seat No: _____

This is to certify that Ms. TULSIYANI MANISHA DILIPKUMAR student of MCA Semester – III has duly completed her term work for the semester ending in December 2020, in the subject of OPERATING SYSTEM towards partial fulfillment of her Degree of Masters in Computer Applications.

10/12/2020
Date of Submission

Internal Faculty

Head of Department

Department Of Computer Science
Rollwala Computer Centre
Gujarat University

MCA -III

Subject: - OPERATING SYSTEM

Name :- TULSIYANI MANISHA DILIPKUMAR

Roll No.: - 39

Exam Seat No.: -

Assignment - I

Page No. : 1
Date : 1 / 1

Glossary

- (1) Base address :- An address that is used as the origin in the calculation of addresses in the execution of a computer program.
- (2) batch processing:- pertaining to the technique of executing a set of computer programs such that each is completed before the next program of the set is started.
- (3) Binary semaphore :- A semaphore that takes on only the values 0 & 1 . A binary semaphore allows only one process or thread to have access to a shared critical resource at a time.
- (4) block:- (1) A collection of contiguous records that are recorded as a unit; the units are separated by interblock gaps.
(2) A group of bits that are transmitted as a unit.
- (5) B-tree:- A technique for organizing indexes. In order to keep access time to the minimum, it stores the data keys in a balanced hierarchy that continually realigns itself as items are inserted & deleted. Thus, all nodes always have a similar number of keys.

Teacher's Signature

- (6) Busy waiting: The repeated execution of a loop of code while waiting for an event to occur.
- (7) Cache memory: A memory that is smaller & faster than main memory & that is interposed between the processor & main memory. The cache acts as a buffer for recently used memory locations.
- (8) Central processing unit (CPU): That portion of a computer that fetches & executes instructions. It consists of an Arithmetic & logic unit (ALU), a control unit, & registers. Often simply referred to as a processor.
- (9) Cluster: A group of interconnected, whole computers working together as a unified computing resource that can create the illusion of being one machine. The term whole computer means a system that can run on its own apart from the cluster.
- (10) concurrent: pertaining to processes or threads that take place within a common interval of time during which they may have to alternately share common resources.
- (11) consumable resources: A resource that can be created & destroyed. When a resource is acquired by a process, the resource ceases to exist. Examples of consumable resources are interrupt, signals,

Teacher's Signature _____

Messages & information in I/O buffers

- (12) Database :- A collection of interrelated data often with controlled redundancy, organized according to a schema to serve one or more applications ; the data are stored so that they can be used by different programs without concern for the data structure or organization. A common approach is used to add new data & to modify & retrieve existing data.
- (13) Deadlock :- (1) An impasse that occurs when multiple processes are waiting for the availability of a resource that will not become available because it is being held by another process that is in a similar wait state.
(2) An impasse that occurs when multiple processes are waiting for an action by or a response from another process that is in a similar wait state.
- (14) Demand Paging :- The transfer of a page from secondary memory to main memory storage at the moment of need.
- (15) Device Driver :- An operating system module that deals directly with a device or I/O module.
- (16) Direct access :- The capability to obtain data from a storage device or to enter data into a storage device in a sequence independent of their relative

Teacher's Signature

position, by means of addresses that indicate the physical location of the data.

- (17) DMA (Direct Memory Access) :- A form of I/O in which a special module, called a DMA module, controls the exchange of data between Main Memory & an I/O device. The processor sends a request for the transfer of a block of data to the DMA module & is interrupted only after the entire block has been transferred.
- (18) Disable interrupt :- A condition, usually created by the operating system, during which the processor will ignore interrupt request signals of a specified class.
- (19) Disk allocation table :- A table that indicates which blocks on secondary storage are free & available for allocation of files.
- (20) Distributed operating system :- A common operating system shared by a network of computers. The distributed operating system provides support for interprocess communication, process migration, mutual exclusion, & the prevention or detection of deadlock.
- (21) dispatch :- To allocate time on a processor to jobs or tasks that are ready for execution.

Teacher's Signature

- (22) Dynamic relocation: A process that assigns new absolute addresses to a computer program during execution so that the program may be executed from a different area of main storage.
- (23) enable interrupt: A condition, usually created by the operating system, during which the processor will respond to interrupt request signals of a specified class.
- (24) External fragmentation: occurs when memory is divided into variable-size partitions corresponding to the blocks of data assigned to the memory.
e.g.: segments in main memory. As segments are moved into & out of the memory, gaps will occur between the occupied portions of memory.
- (25) file: A set of related records treated as a unit.
- (26) field:
(i) Defined logical data that are part of a record.
(ii) The elementary unit of a record that may contain a data item, a data aggregate, a pointer, or a link.
- (27) FAT : (File allocation table) : A table that indicates the physical location on secondary storage of the space allocated to a file. There is one file allocation table for each file.

Teacher's Signature

- (28) File management system: A set of system software that provides services to users & applications in the use of files, including file access, file directory maintenance, & access control.
- (29) Indexed access: pertaining to the organization & accessing of the records of a storage structure through a separate index to the locations of the stored records.
- (30) Indexed file: A file in which records are accessed according to the value of key fields. An index is required that indicates the location of each record on the basis of each key value.
- (31) Index sequential access: pertaining to the organization & accessing of the records of a storage structure through an index of the keys that are stored in arbitrarily partitioned sequential files.
- (32) Indexed sequential file: A file in which records are ordered according to the values of a key field. The main file is supplemented with an index file that contains a partial list of key values; the index provides a lookup capability to quickly reach the vicinity of a desired record.

Teacher's Signature _____

- (22) Instruction cycle: The time period during which one instruction is fetched from memory & executed when a computer is given an instruction in machine language.
- (24) Internal fragmentation: occur when memory is divided into fixed size partitions (e.g. page frames in main memory, physical blocks on disk). If a block of data is assigned to one or more partitions, then there may be wasted space in the last partition. This will occur if the last portion of data is smaller than the last partition.
- (25) Interrupt: A suspension of a process, such as the execution of a computer program, caused by an event external to that process & performed in such a way that the process can be resumed.
- (26) Interrupt handler: A routine, generally part of the operating system. When an interrupt occurs, control is transferred to the corresponding interrupt handler, which takes some action in response to the condition that caused the interrupt.
- (27) Job: A set of computational steps packaged to run as a unit.

- (28) kernel :- A portion of the operating system that includes the most heavily used portions of software. Generally, the kernel is maintained permanently in main memory. The kernel runs in a privileged mode & responds to calls from processes & interrupt from devices.
- (29) Kernel Mode :- A privileged mode of execution reserved for the kernel of the operating system. Typically, kernel mode allows access to regions of main memory that are unavailable to processes executing in a less-privileged mode & also enables execution of certain machine instructions that are restricted to the kernel mode. Also referred to as system mode or privileged mode.
- (30) LIFO (last in first out) :- A queuing technique in which the next item to be retrieved is the item most recently placed in the queue.
- (31) livelock :- A condition in which two or more processes continuously change their state in response to changes in the other processes without doing any useful work. This is similar to deadlock in that no progress is made, but it differs in that neither process is blocked or waiting for anything.

Teacher's Signature

- (42) logical address: A reference to a memory location independent of the current assignment of data to memory. A translation must be made to a physical address before the memory access can be achieved.
- (43) logical record: A record independent of its physical environment, portions of one logical record may be located in different physical records or several logical records or parts of logical records may be located in one physical record.
- (44) Main Memory: Memory that is internal to the computer system, is program addressable & can be loaded into registers for subsequent execution or processing.
- (45) Malicious software: Any software designed to cause damage to or use up the resources of a target computer, malicious software (malware) is frequently concealed within or masquerades as legitimate software. In some cases, it spreads itself to other computers via e-mails or infected disks. Types of malicious software include viruses, Trojan horses, worms & hidden software for launching denial-of-service attacks.
- (46) Memory cycle time: The time it takes to read one word from or write one word to memory. This is the inverse of the rate at which words can be read from or written to memory.

Teacher's Signature _____

- (47) Memory partitioning :- The subdividing of storage into independent sections.
- (48) Microkernel :- A small privileged operating system core that provides process scheduling, memory management, & communication services & relies on other processes to perform some of the functions traditionally associated with the operating system kernel.
- (49) Multiprocessing :- A mode of operation that provides for parallel processing by two or more processors of a multiprocessor.
- (50) Multiprogramming :- A mode of operation that provides for the interleaved execution that provides for the execution of two or more computer programs by a single processor. The same as multitasking, using different terminology.
- (51) Multiprogramming level :- The number of processes that are partially or fully resident in main memory.
- (52) Multitasking :- A mode of operation that provides for the concurrent performance or interleaved execution of two or more computer tasks. The same as multiprogramming using different terminology.

- (53) Mutual exclusion: A condition in which there is a set of processes, only one of which is able to access a given resource or perform a given function at any time.
- (54) Operating system: Software that controls the execution of programs & that provides services such as resource allocation, scheduling, input/output control & data management.
- (55) page: In virtual storage, a fixed length block that has a virtual address & that is transferred as a unit between main memory & secondary memory.
- (56) page fault: occurs when the page containing a referenced word is not in main memory. This causes an interrupt & requires that the proper page be brought into main memory.
- (57) page frame: A fixed-size contiguous block of main memory used to hold a page.
- (58) paging: The transfer of pages between main memory & secondary memory.
- (59) physical address: The absolute location of a unit of data in memory (e.g.: word or byte in main memory, block on secondary memory.)

- (60) pipe :- A circular buffer allowing two processes to communicate on the producer-consumer model. Thus, it is a first-in-first-out queue, written by one process & read by another. In some systems, the pipe is generalized to allow any item in the queue to be selected for consumption.
- (61) preemption :- Reclaiming a resource from a process before the process has finished using it.
- (62) prefetching :- The retrieval of pages other than the one demanded by a page fault. The hope is that the additional pages will be needed in the near future, conserving disk I/O.
- (63) process :- A program in execution. A process is controlled & scheduled by the operating system. same as task.
- (64) process control block :- The manifestation of a process in an operating system. It is a data structure containing information about the characteristics & state of the process.
- (65) process state :- All the information that the operating system needs to manage a process & that the processor needs to properly execute the process. The process state includes the content of the various processor registers, such as the program counter & data

registers; it also includes information of use to the operating system, such as the priority of the process & whether the process is waiting for the completion of a particular I/O event - same as execution context.

- (66) processor: In a computer, a functional unit that interprets & executes instructions. A processor consists of at least an instruction control unit & an arithmetic unit.
- (67) program counter: Instruction address register.
- (68) programmed I/O: A form of I/O in which the CPU issues an I/O command to an I/O module & must then wait for the operation to be completed before proceeding.
- (69) real time system: An operating system that must schedule & manage real time tasks.
- (70) real time task: A task that is executed in connection with some process or function or set of events external to the computer system & that must meet one or more deadlines to interact effectively & correctly with the external environment.
- (71) Registers: High speed memory internal to the CPU, some registers are user visible, that is available to the programmer via the machine instruction set.

Teacher's Signature

registers; it also includes information of use to the operating system, such as the priority of the process & whether the process is waiting for the completion of a particular I/O event - same as execution context.

- (66) processor: In a computer, a functional unit that interprets & executes instructions. A processor consists of at least an instruction control unit & an arithmetic unit.
- (67) program counter: Instruction address reg or register.
- (68) programmed I/O: A form of I/O in which the CPU issues an I/O command to an I/O module & must then wait for the operation to be completed before proceeding.
- (69) real time system: An operating system that must schedule & manage real time tasks.
- (70) real time task: A task that is executed in connection with some process or function or set of events external to the computer system & that must meet one or more deadlines to interact effectively & correctly with the external environment.
- (71) Registers: High speed memory internal to the CPU, some registers are user visible, that is available to the programmer via the machine instruction set.

other registers are used only by the CPU, for control purposes.

(72) relative address: An address calculated as a displacement from a base address.

(73) response time: In a data system, the elapsed time between the end of transmission of an enquiry message & the beginning of the receipt of a response message, measured at the enquiry terminal.

(74) round robin: A scheduling algorithm in which processes are activated in a fixed cyclic order; that is, all processes are in a circular queue. A process that can not proceed because it is waiting for some event (e.g.: termination of a child process or an input/output operation) returns control to the scheduler.

(75) scheduling: To select jobs or tasks that are to be dispatched. In some operating systems, other units of work, such as input/output operations, may also be scheduled.

(76) secondary Memory: Memory located outside the computer system itself; that is, it cannot be processed directly by the processor. It must first be copied into main memory. Examples include disk & tape.

Teacher's Signature

- (37) segment: In virtual memory, a block that has a virtual address. The blocks of a program may be of unequal length & may even be of dynamically varying lengths.
- (38) segmentation: The division of a program or application into segments as part of a virtual memory scheme.
- (39) Semaphore: An integer value used for signaling among processes. Only three operations may be performed on a semaphore, all of which are atomic: initialize, decrement & increment. Depending on the exact definition of the semaphore, the decrement operation may result in the blocking of a process, & the increment operation may result in the unblocking of a process. Also known as counting semaphore or a general semaphore.
- (40) sequential file: A file in which records are ordered according to the values of one or more key fields & processed in the same sequence from the beginning of the file.
- (41) shell: The portion of the operating system that interprets interactive user commands & job control language commands. It functions as an interface between the user & the operating system.

- (8) Stack: An ordered list in which items are appended to and deleted from the same end of the list, known as the top. That is, the next item appended to the list is put on the top, & the next item to be removed from the list is the item that has been in the list the shortest time. This method is characterized as last in first out.
- (9) starvation: A condition in which a process is indefinitely delayed because other processes are always given preference.
- (10) strong semaphore: A semaphore in which all processes waiting on the same semaphore are queued & will eventually proceed in the same order as they executed the wait (P) operation (FIFO order).
- (11) swapping: A process that interchanges the contents of an area of main storage with the contents of an area in secondary memory.
- (12) SMP (symmetric multiprocessing): A form of multiprocessing that allows the operating system to execute on any available processor or on several available processors simultaneously.

- (87) synchronous operation - An operation that occurs regularly or predictably with respect to the occurrence of a specified event in another process. for e.g. the calling of an input/output routine that receives control at a pre-coded location in a computer program.
- (88) synchronization - situation in which two or more processes coordinate their activities based on a condition.
- (89) system bus - A bus used to interconnect major computer components (CPU, memory, I/o)
- (90) thread - A dispatchable unit of work. It includes a processor context (which includes the program counter & stack pointer) & its own data area ~~for~~ for a stack (to enable subroutine branching). A thread executes sequentially & is interruptible so that the processor can turn to another thread. A process may consist of multiple threads.
- (91) thread switch - The act of switching processor control from one thread to another within the same process.
- (92) Time sharing - The concurrent use of a device by a number of users.

- (93) time slice: The maximum amount that a process can execute before being interrupted.
- (94) trap: An unprogrammed conditional jump to a specified address that is automatically activated by hardware; the location from which the jump was made is recorded.
- (95) Trojan horse: secret undocumented routine embedded within a useful program. Execution of the program results in execution of the secret routine.
- (96) User mode: The least-privileged mode of execution. Certain regions of main memory & certain machine instructions cannot be used in this mode.
- (97) Virtual address: The address of a storage location in virtual memory.
- (98) Virtual memory: The storage space that may be regarded as addressable main storage by the user of a computer system in which virtual addresses are mapped into real addresses. The size of virtual storage is limited by the addressing scheme of the computer system & by the amount of secondary memory available & not by the actual number of main storage locations.

Teacher's Signature

- (99) virus: secret undocumented routine embedded within a useful program. execution of the program results in execution of the secret routine.
- (100) weak semaphore: A semaphore in which all processes waiting on the same semaphore proceed in an unspecified order (i.e the order is unknown or indeterminate)
- (101) word: An ordered set of bytes or bits that is the normal unit in which information may be stored, transmitted, or operated on within a given computer. Typically, if a processor has a fixed length instruction set, then the instruction length equals the word length.
- (102) worm: program that can travel from computer to computer across network connections may contain a virus or bacteria.

Teacher's Signature

Assignment -2

Page No.:

Date: / /

* Banker's Algorithm

process	Allocation	Maximum	Need	Available
	A B C	A B C	A B C	A B C
P ₀	0 1 0	7 5 3	7 4 3	3 3 2
P ₁	2 0 0	3 2 2	1 2 2	
P ₂	1 0 2	9 0 2	6 0 0	
P ₃	2 1 1	2 2 2	0 1 1	
P ₄	0 0 2	4 3 3	4 3 1	

→ Need ≤ available \Rightarrow available = available + allocation

P₀ 7 4 3 \leq 3 3 2 \rightarrow condition false.

P₁ 1 2 2 \leq 3 3 2 \rightarrow condition true.

$$\begin{aligned} \text{available} &= 3 3 2 + 2 0 0 \\ &= 5 3 2 \end{aligned}$$

P₂ 6 0 0 \leq 5 3 2 \rightarrow condition false.

P₃ 0 1 1 \leq 5 3 2 \rightarrow condition true

$$\begin{aligned} \text{available} &= 5 3 2 + 2 1 1 \\ &= 7 4 3 \end{aligned}$$

P₄ 4 3 1 \leq 7 4 3 \rightarrow condition true.

$$\begin{aligned} \text{available} &= 7 4 3 + 0 0 0 \\ &= 7 4 3 \end{aligned}$$

Teacher's Signature _____

$P_0 \quad 7 \ 4 \ 3 \leq 7 \ 4 \ 5 \rightarrow$ condition true

$$\begin{aligned} \text{available} &= 7 \ 4 \ 5 + 0 \ 1 \ 0 \\ &= 7 \ 5 \ 5 \end{aligned}$$

$P_2 \quad 6 \ 0 \ 0 \leq 7 \ 5 \ 5 \rightarrow$ condition true

$$\begin{aligned} \text{available} &= 7 \ 5 \ 5 + 3 \ 0 \ 2 \\ &= 10 \ 5 \ 7 \end{aligned}$$

safe sequence is $\rightarrow (P_1, P_3, P_4, P_0, P_2)$

* Optimal

① $7, 0, 1, 2, 0, 2, 0, 4, 2, 3, 0, 2, 0, 2, 2, 1, 2, 0, 1, 7, 0, 1.$

7	0	1	2	0	3	0	4	2	3	0	3	0	3	2	1
7	7	7	2	2	2	2	2	2	3	0	3	0	3	2	1
0	0	0	0	0	4	4	4	4	3	3	3	3	3	0	0
1	1	1	1	3	3	3	3	3	3	3	3	3	3	1	1

2	0	1	7	0	1
7					
0					
1					

no. of frames = 3

page fault = 9.

Teacher's Signature

(2) ~~7, 0, 1, 2, 0, 7, 0, 4, 2, 7, 0, 7, 2, 7~~

7	0	1	2	0	3	0	4	2	3	0	3	2	3
7	7	7	7		3		3						
	0	0	0		0		0						
	1	1			1		4						
		2			2		2						

no. of frames = 4.

page fault = 6.

* FIFO.

(1) ~~1, 3, 0, 7, 5, 6, 3~~

1	3	0	3	5	6	3							
1	1	1		5	5	5							
3	3	0		3	6	6							
	0			0	0	0							

no. of frames = 3

page fault = 6.

Teacher's Signature

(2)

7, 0, 1, 2, 0, 3, 0, 4, 2, 3, 0, 3, 0, 3, 2, 1, 2, 0, 1, 7, 0,

7	0	1	2	0	3	0	4	2	3	0	3
7	7	7	2	2	2	2	4	4	4	0	
0	0	1	0	3	3	1	1	2	2	2	

2	1	2	0	1	7	0	1
0	0				7	7	7
1	1				1	0	0
2					2	2	1

page fault = 15

No. of frames = 3

* LRU

7, 0, 1, 2, 0, 3, 0, 4, 2, 2, 0, 3, 0, 3, 2, 1, 2, 0, 1, 7, 0,

7	0	1	2	0	3	0	4	2	3	0	3	2	1
7	7	7	2	2	4	4	4	4	4	0			
0	0	0	0	0	0	0	0	0	1	3			

2	0	1	7	0	1
1			1		
0			0		

No. of frames = 3

page fault = 12

Teacher's Signature

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

**R OLL NO : 39
NAME : TULSIYANI MANISHA DILIPKUMAR
SUBJECT : OPERATING SYSTEM**

NO.	TITLE	PAGE NO.	DATE	SIGN
1	Basic salary of a person is input through the keyboard. His dearness allowance is 40% of basic salary and house rent is 20% of basic salary. Write a program to calculate the gross pay.	1	10/12/2020	
2	The distance between two cities is input through the keyboard. (in km). Write a program to convert this distance into metres, feet, inches and centimeters and display the results.	2	10/12/2020	
3	The length and breadth of a rectangle and radius of a circle are entered through the keyboard, calculate the perimeter and area of rectangle and area and circumference of the circle.	3	10/12/2020	
4	If a five digit number is entered through the keyboard, calculate the sum of its digits.	4	10/12/2020	
5	The file /etc/passwd contains info about all users. Write a program which would receive the logname during execution, obtain information about it from the file and display the information on screen in some appropriate format. (Hint : use cut) eg. Logname : , UID : , GID : , Default working directory : , Default working shell :	5	10/12/2020	
6	The script will receive the filename or filename with its full path, the script should obtain information about this file as given by "ls -l" and display it in proper format. eg. Filename : , File access permissions : , Number of links : , Owner of the file : , Group to which belongs : Size of file : , File modification date : , File modification time :	6	10/12/2020	
7	If cost price and selling price of an item are entered through the keyboard, write a program to determine whether the seller has made profit or loss. Also determine how much profit/loss is made.	7	10/12/2020	
8	Check whether the entered no. is odd or even.	8	10/12/2020	
9	Check whether the entered no. is prime or not.	9	10/12/2020	

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

R OLL NO : 39

N A M E : TULSIYANI MANISHA DILIPKUMAR

S U B J E C T : OPERATING SYSTEM

10	Check whether the entered year is a leap year or not.	10	10/12/2020	
11	The script receives two file names as arguments, the script must check whether the files are same or not, if they are similar then delete the second file.	11	10/12/2020	
14	Write a shell script to display the date with the format :- 25th October 2005 is a Tuesday.	12	10/12/2020	
15	Write a shell script to display the appropriate message like : Good Morning / Good Afternoon / Good Evening	13	10/12/2020	
16	Write a shell script to display the menu driven interface :- 1) list all files of the current directory 2) print the current directory 3) print the date 4) print the users otherwise display "Invalid Option".	14	10/12/2020	
17	Create a menu driven calculator which asks for two integers and perform basic arithmetic operations.	15	10/12/2020	
18	Find the factorial of any number.	16	10/12/2020	
19	Display the fibonacci series upto some number.	17	10/12/2020	
20	Two numbers are entered through the keyboard, find the power, one number raised to another.	18	10/12/2020	
21	Write a script which has the functionality similar to head and tail commands.	19	10/12/2020	
22	Write a script which reports name and size of all files in a directory. whose sizes exceed 1000. The filenames should be printed in the descending order of their sizes. The total no. of files must be reported.	20	10/12/2020	
24	Print the prime nos. from 1 to 300.	21	10/12/2020	
25	Program must display all the combinations of 1, 2, and 3.	22	10/12/2020	
26	Write a script for renaming each file in the directory such that it will have the current shell PID as an extension. The shell script should ensure that the directories do not get renamed.	23	10/12/2020	
27	A file called wordfile consists of several words. Write a shell script which will receive a list of filenames, the first of which would be wordfile. The shell script should report all occurrences of each word in wordfile in the rest of the files supplied as arguments.	24	10/12/2020	
28	Write a shell script which deletes all the lines containing the word "unix" in the files supplied as arguments to it.	25	10/12/2020	
29	The word "unix" is present in only some of the files supplied as arguments to the shell script. You script should search each	26	10/12/2020	

D E P A R T M E N T O F C O M P U T E R S C I E N C E
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3

R O L L N O : 39

N A M E : TULSIYANI MANISHA DILIPKUMAR

S U B J E C T : OPERATING SYSTEM

	of these files in turn and stop at the first file that it encounters containing the word unix. The filename should be displayed on the screen.			
30	The word "unix" is present in only some of the files supplied as arguments to the shell script. You script should search each of these files in turn and stop at the first file that it encounters containing the word unix. The filename should be displayed on the screen.	27	10/12/2020	
31	The script displays a list of all files in the current directory to which you have read, write and execute permissions.	28	10/12/2020	
32	The script receives any number of filenames as arguments. It should check whether every argument supplied is a file or directory. If it is a directory it should be reported. If it is a filename then name of the file as well as the number of lines present in it should be reported.	29	10/12/2020	
33	A script will receive any number of filenames as arguments. It should check whether such files already exist. If they do, then it should be reported, if not then check if a subdirectory "mydir" exists or not in the current directory, if it doesn't exist then it should be created and in it the files supplied as arguments should be created.	30	10/12/2020	
34	Accept the marks of 5 subjects and calculate the percentage and grade.	31	10/12/2020	
35	Print armstrog nos. from 1 to 500.	32	10/12/2020	
36	Accept the measure (angles) of a triangle and displa the type of triangle. (eg. acute, right, obtuse)	33	10/12/2020	
37	Display all the numbers from 1 to 100 which are divisible by 7.	34	10/12/2020	
38	Find the largest and smallest of 3 different numbers.	35	10/12/2020	
39	Find HCF and LCM of a given no.	36	10/12/2020	
40	Display the dates falling on Sundays of the current month.	37	10/12/2020	
41	Write a shell script to list the students according to their choice of games ... Eg. Cricket : Aamir Football : Ajay Tennis : Sharukh, Salman	38	10/12/2020	
42	Write a shell script to generate summary from the sales.dat file. Sales made by 3 salesman by selling 3 products are entered in a file. Add atleast 10 records. The format is as shown below: Salesman:Product1:Product2:Product3	39	10/12/2020	

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

R O LL NO : 39

N A M E : TULSIYANI MANISHA DILIPKUMAR

S U B J E C T : OPERATING SYSTEM

<p>Sample data: Mr. Abhishek Sharma:21:29:12 Mr. Akash Srivastava:11:15:28 Mr. Abhilash Dwivedi:31:04:13</p> <p>Calculate the followings :</p> <ul style="list-style-type: none"> • Total sales of the company • Highest sold product • Best salesman (who sold the most) • Worst salesman (who sold the least) 			
<p>43 Create a file “medals.dat” which contains the details of medals won by each country in Olympics. The data in the file may be as given below : (Country name is Primary key.) Country Gold Silver Bronze</p> <hr/> <p>India 21 12 15 Pakistan 12 10 08 USA 10 14 19 Srilanka 00 09 07 and so on.....</p> <ul style="list-style-type: none"> • Write a shell script which will ask the user to enter the Country name, further modify the no. of medals for that country. • Delete all the countries who get zero Gold medals. • Calculate the total no. of medals won by each country. • Find the country with highest Gold medals. 	40	10/12/2020	
<p>44 Write a shell script to generate summary from a file : “student.dat” with following format :</p> <p>Student_no : student_name : gender : marks1 : marks2 :marks3 Each field must be separated by a delimiter ‘-‘</p> <p>Process the following queries:</p> <ul style="list-style-type: none"> • Calculate the total marks of each student • Calculate the percentage of marks for each student • Count the total number of male and female students • Count the total number of students who pass and those who fail. 	41	10/12/2020	
<p>45 A reputed MCA institute of Gujarat has students from various states. A sample file “students.dat” is shown as under :</p>	42	10/12/2020	

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

R OLL NO : 39

N A M E : TULSIYANI MANISHA DILIPKUMAR

S U B J E C T : OPERATING SYSTEM

State	M	F
Gujarat	18	12
Maharashtra	12	04
M.P.	08	04
U.P.	05	00
Rajasthan	07	00

Total Male candidates are 50 and Female are 20. Write a shell script to generate a Statewise Candidate Distribution Report as under :

STATEWISE CANDIDATES LISTING

%FEMALE	STATE TOTAL	%MALE
30	GUJARAT	36
16	MAHARASHTRA	24

..... and so on.....

46

Write a Shell script to generate summary from a file "books.dat" which contains the following details :

Field	Description
No	Numeric (4) – uniquely identifies each book.
Title	Alphanumeric(30) – title of the book
Author	Character(20) – Author of the book
Publisher	Character(20) – Publisher (PHI , TMH,BPB...)
Edition	Numeric (2)

Sample Data:

**b1001 Programming in Java Balaguruswamy TMH
Second**

b1002 Computer Networks Tanenbaum Pearson Fifth

b1003 Operating Systems Chaudhari Jaico First

After creating the file do the followings :

43

10/12/2020

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

R OLL NO : 39

N A M E : TULSIYANI MANISHA DILIPKUMAR

S U B J E C T : OPERATING SYSTEM

	<ul style="list-style-type: none"> • Your script must replace all the BPB publisher with TMH. • List the titles with the name ‘Java’. • List the books written ‘Balaguruswamy • List the books which are not the first edition 															
47	<p>Create a file “election.dat” which contains the Election details for a specific city.</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding-bottom: 5px;">Field</th><th style="text-align: left; padding-bottom: 5px;">Description</th></tr> </thead> <tbody> <tr> <td>Idno</td><td>Numeric - Unique</td></tr> <tr> <td>Name</td><td>Character – Voter’s Name</td></tr> <tr> <td>Sex</td><td>Character – M / F</td></tr> <tr> <td>Age</td><td>Numeric</td></tr> <tr> <td>Ward</td><td>Numeric – Ward no. / Division no. of the city.</td></tr> </tbody> </table> <p>Sample data:</p> <p style="margin-left: 40px;">e101 - abhishek - M - 35 - 44 e102 - ashutosh - M - 97 - 14 e103 - anamika - F - 21 - 50</p> <p>Suppose the same file is to be modified after 4 years. Write a shell script to simulate this process.</p> <p>Your program must update the age of all People (Add 4 years to age). In case if the age exceeds 99 then delete the record from the file, assuming that the person is dead.</p> <p>Display the election.dat and final output of your program.</p>	Field	Description	Idno	Numeric - Unique	Name	Character – Voter’s Name	Sex	Character – M / F	Age	Numeric	Ward	Numeric – Ward no. / Division no. of the city.	44	10/12/2020	
Field	Description															
Idno	Numeric - Unique															
Name	Character – Voter’s Name															
Sex	Character – M / F															
Age	Numeric															
Ward	Numeric – Ward no. / Division no. of the city.															
48	<p>In a college, students are allowed to select any one elective subject during his studies. Create two files by entering the data as mentioned below (you may skip the heading line if required) :</p> <p>File : elective.dat</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding-bottom: 5px;">Code</th><th style="text-align: left; padding-bottom: 5px;">Game</th></tr> </thead> <tbody> <tr> <td>101</td><td>AI</td></tr> <tr> <td>102</td><td>Computer Graphics</td></tr> <tr> <td>103</td><td>Parallel Processing</td></tr> </tbody> </table>	Code	Game	101	AI	102	Computer Graphics	103	Parallel Processing	45	10/12/2020					
Code	Game															
101	AI															
102	Computer Graphics															
103	Parallel Processing															

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

ROLL NO : 39

NAME : TULSIYANI MANISHA DILIPKUMAR

SUBJECT : OPERATING SYSTEM

104 Data Mining

File : students.dat

RollNo. Name Code

1	Sonal	101
2	Madhu	101
3	Mahim	103
4	Esha	104

Write a shell script to list the students according to their choice of electives ...

Eg. AI :- Sonal, Madhu

Computer Graphics: -

Parallel Processing :- Mahim

Data Mining :- Esha

49	<p>Create two files: subjects.dat and students.dat containing the subject details and the student details.</p>	46	10/12/2020	
	<p>Sample data is as shown below:</p> <p>subjects.dat</p> <p>Course_id-Semester_id-Subject_id-Subject_name</p> <p>CS-1-1-FCO</p> <p>CS-1-2-FOP</p> <p>CS-1-3-SL</p> <p>CS-2-1-DS</p> <p>CS-2-2-DBMS</p> <p>CS-3-1-OS</p> <p>CS-3-2-JAVA</p> <p>faculty.dat</p> <p>Faculty_id:Semester_id:Subject_id</p> <p>F1-2-1</p> <p>F2-3-2</p> <p>F3-1-3</p> <p>F1-1-1</p> <p>Write a shell script to list the faculties and their respective subjects. Sample Output will be :</p>			

**DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3**

R O LL NO : 39

N A M E : TULSIYANI MANISHA DILIPKUMAR

S U B J E C T : OPERATING SYSTEM

	F1 : FCO, DS F2 : JAVA F3 : SL			
50	<p>Create two files employee.dat and departments.dat and add atleast 10 records in the following format :</p> <p>employee.dat</p> <p>emp_id:department_id:birthdate</p> <p>e101:M1:11-01-1960 e102:C1:21-03-1973 e103:M2:21-03-1973 e104:C1:21-03-1973 e105:B1:08-10-1965 e101:M1:11-11-1964</p> <p>departments.dat</p> <p>departmend_id:department_name</p> <p>B1:Botany C1:Chemistry M1:Mathematics M2:Management</p> <p>Write a shell script to do the followings:</p> <p>1) List all the employee_ids department-wise 2) List the employee_ids born after 1970 3) List the employee_ids according to birthdate in sorted order</p>	47	10/12/2020	

DEPARTMENT OF COMPUTER SCIENCE
ROLLWALA COMPUTER CENTRE
GUJARAT UNIVERSITY
M.C.A. -3

ROLL NO : 39
NAME : TULSIYANI MANISHA DILIPKUMAR
SUBJECT : OPERATING SYSTEM