

产 品 规 格 书

PRODUCT SPECIFICATION

产品名称：扁平型振动马达

产品型号：1020-15-003-001

APPROVED 本司确定	DRAWN 编制	CHECKED 审核	APPROVAL 批准	DATE 日期
		MICHAEL		

MATERIAL or METHODS

Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

1. Construction Form (结构形式)

No. 序号	ITEM 项目	Contents 内容
1-1	Motor Construction	Φ10-Flat Coreless Vibration Motor
1-2	Coil Construction	Flat Coreless Coil
1-3	Rectifying Method	Precious Brush and Commutator

2. Standard Operating Condition (标准运行条件)

No. 序号	ITEM 项目	Contents 内容
2-1	Rated Voltage	DC 3.0V
2-2	Rated Load	Vibration Weight
2-3	Rotation Direction	CCW or CW
2-4	Motor Position	Any Position Available
2-5	Voltage Range for Use	DC 2.5~3.5V
2-6	Allowable Temperature Range	Working Temperature:-20°C-70°C
2-7	Storage Environment	-30°C-80°C

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

Add: Measuring Condition (测试条件)

- 1.Measuring Temperature: $25^{\circ}\text{C}\pm 2^{\circ}\text{C}$ 测试温度: $25^{\circ}\text{C}\pm 2^{\circ}\text{C}$
- 2.Measuring Relative Humidity: 45-75%RH 测试相对湿度: 45-5%RH

3. Electrical Characteristics (电性能)

No. 序号	Item 项目	Measuring Condition 测试条件	Specification 规格
3-1	Rated Speed	At Rated Voltage and Rated Load	Min 10,000rpm
3-2	Rated Current	At Rated Voltage and Rated Load	80mA or less
3- 3	Starting Voltage	At Rated Load and Step Voltage	DC2.3V or less
3- 4	Insulation Resistance	DC100V between Lead wire and Case	10M Ω Min
3- 5	Insulation Voltage	DC50V between Lead wire and Motor Case	No Destruction
3- 6	Terminal Resistance	Measure between Terminals	75 Ω Max

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001


ISSUE: O
NUMBER:

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:


4. Mechanical Specification (机械要求)

No 序号	Item 项目	Measuring Condition 测试条件	Specification 规格
4-1	Configuration 外观尺寸	Vernier-Calipers 游标卡尺	As Specified in Outline Drawing. 参考相关外形尺寸图。
4-2	Appearance 外观	Visual Examination 目测	Should be no Evidence of Mechanical Damage,Crack,Rust and Stain. 不得有明显的机械划痕, 裂缝, 锈迹, 污点。
4-3	Weight 重量	Balance 天平	0.9g Approx 约 0. 9g
4-4	Mechanical Noise 机械噪音	 <p>At Rated Voltage and Rated Load back ground Noise:50dB 额定电压及负荷</p>	<p>50dB(A) Max (在 Motor 表面 100mm 处,3.0V)</p> <p>将电机固定, 使其保持不动。</p>

MATERIAL or METHODS Specifications

ISSUE: O
NUMBER:

MODEL: 1020-15-003-001

		下测试背景噪音 不超过 50 分贝。	
4-5	Vibration Test 振动量测定	 <p>模型块:80g 测定装置:VM-83</p>	0.8G(AVG) (Vm=DC 3.0V)
4-6	Down-lead' s loose Strength 引线抗拉强度		9.8N or More 9.8N 以上

5. Reliability Test (可靠性试验)

No. 序号	Item 项目	Contents 内容
5-1	Life Test 寿命测试	1)Voltage: DC3.0V 测试电压: DC3.0V 2)Load: Vibrator 负荷:偏心锤 3)Temperature: 20°C±2°C 温度: 20°C±2°C 4)Relative Humidity: 60-70%RH 相对湿度: 60-70%RH Test Mode: Turn On the Motor for 2sec and than stop for 1sec, 100,000 Cycle.
5-2	High Temperature Exposure	Exposure to 80 °C ± 2 °C for 96hours, then return to Ordinary Temperature and Humidity for 2hours. 在温度80°C±2°C条件下放置96小时后, 在正常温度和湿度下放置2小时。
5-3	Low Temperature Exposure	Exposure to -30 °C for 96hours, then return to Ordinary Temperature and Humidity for 2hours. 在温度-30°C条件下放置96小时后, 在正常温度和湿度下放置2小时。
5-4	Humidity Test 湿度测试	Exposure to 40°C±2°C,90-95%RH(Relative Humidity) for 96hours, then return to Ordinary Temperature and Humidity for 2hours. 在温度40°C±2°C,90%RH(相对湿度)条件下放置96小时后, 在正常温度和 湿度下放置2小时。

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

6. Performance and Characteristics (性能与特性)

Should be satisfied with the requirements of table1 after Reliability test 5-1-5-7.

通过以上可靠性试验 5-1-5-7 以后应满足表 1 的要求。

表 1: 评估表

No. 序号	ITEM 项目	Contents 内容
6-1	Rated Current	Initial Data: $\pm 30\%$ Max 最大不超过初始值的 $\pm 30\%$
6-2	Rated Speed	Initial Data: $\pm 30\%$ Max 最大不超过初始值的 $\pm 30\%$
6-3	Life Test	Initial Data: $\pm 40\%$ Max 最大不超过初始值的 $\pm 40\%$
6-4	Starting Voltage	DC 2.3V Max
6-5	Others	1)Should not fail in starting 应正常启动 2)Should not be unusual mechanical noise 无异响噪音

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

MATERIAL or METHODS

Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

7. Cautions (注意事项)

1) Allowable Range for Use 工作范围

Pay attention to Voltage and Current ranges for use, and Use the vibration motor in the Condition accordance with this specifications, or else the life and performance should be considerably reduced.

注意电压及电流的使用范围，并且要按本规格书的要求使用电机，否则电机的使用寿命和性能将发生显著的下降。

2) Storage 储存

Standard Storage Temperature: -5-30°C

Standard Storage Relative Humidity: ≤75%

Avoids Storing in high temperature, High humidity or corrosive Gas Environment.

标准储存温度: -5-30°C

标准储存相对湿度: ≤75%

避免放置在高温，潮湿及有腐蚀性气体的环境中。

3) Handling of Motor 电机使用

Do not press the product with more than 0.5Kgf or drop it, It can cause the transformation of performance or external appearance.

不许在电机上面施加0.5Kgfl以上的压力或使其跌落，这样可能会影响其性能或使外观发生变形。

Do not drop into fluid. (such as Water, Alcohol, etc.)

要防止与液体接触。(水，酒精，等)

Do not expose this product to high temperature for extended periods of time, It may cause a decline in performance.

长时间放置在高温环境时有可能影响其电机的性能。

Please refrain from operating the Motors near Magnetic devices.

要避免放置在磁性物体附近。

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

8 Mechanical Drawing (机械图)

8-1 Material Lead/导线材质: UL AWM 1571 AWG32

MATERIAL or METHODS
Specifications

ISSUE: O
NUMBER:

MODEL: 1020-15-003-001




Figure 1 Motor Housing Configuration

图 1 电机外形结构图

MATERIAL or METHODS Specifications

MODEL: 1020-15-003-001

ISSUE: O
NUMBER:

样品承认书 APPROVAL SHEET (RoHs)

客户名称 Customer		产品型号 Specification	1020-10-003-001
项目名称 project name		样品数量 QT 'Y Sample	
送样日期 Date of Issue	2012 年 月 日	承认项目 Approval	<input type="checkbox"/> 工程承认 <input type="checkbox"/> 量产承认

承认:

	OK	NG		OK	NG
1、规格尺寸:	<input type="checkbox"/>	<input type="checkbox"/>	2、电压使用范围:	<input type="checkbox"/>	<input type="checkbox"/>
3、震动指标:	<input type="checkbox"/>	<input type="checkbox"/>	4、温 升 :	<input type="checkbox"/>	<input type="checkbox"/>
5、概 述:					

注: 1、请在选择项相应的□内打上“√”。 2、需特别要求时在概述栏作简要注明。

客户承认签核 Customer Approval:

核 准 PROOFREAD	确 认 CONFIRM	承 认 APPROVAL
DATE OF ISSUE 日 期	Month 月	Day 日
		Year 年

内部签核 Signature

核 准 PROOFREAD	确 认 CONFIRM	存档编号
朱坤明	朱华东	

PLEASE APPROVAL AND FAX BACK TO OUR COMPANY. THANKS!!