

ARCILLA, Rachel Anne B. BSIT 2-3 ~~PBA~~

Part A - Variable Identification Table

Variable Name	Data Type	Variable Type	Stored In
owner	Vstring	Instance	Heap
balance	double	Instance	Heap
owner	String	Local	Stack
balance	double	Local	Stack
acc1	Account	Local	Stack
acc2	Account	Local	Stack
acc3	Account	Local	Stack
args	String[]	Local	Stack

Part B - Explanation

Statement	What happens?	Memory Impact
string owner;	declares owner as an instance variable under Account	A space for a string is reserved in every Account object
double balance;	Declares balance as an instance variable under Account	A space for a double variable is reserved in every Account object.
this.owner = owner;	Assigns the value of the local variable owner to the object's owner. The keyword "this" specifically points to the instance owner.	The argument is first stored in the local parameter (stack) and then that value is copied into the object's owner field in the heap
this.balance = balance;	Assigns the value of the local parameter balance to the object's balance using "this"	the argument is stored in the stack and then copied into the object's balance field in the heap.
Account acc1 = new Account("Carlos", 5000);	Declares acc1 that will hold a reference to a new Account object that has "Carlos" as its owner and 5000 as his balance	acc1 holds the reference to the object in the heap and "Carlos" and 5000 are stored in that object

Account acc2 = new Account("Diana", 7000);	Similarly, it declares acc2 to hold the address of the new object with "Diana" and 7000 as its values.	The heap now has 2 separate Account objects. acc2 in the stack points to the new object that contains "Diana" and 7000.
Account acc3 = acc1;	acc3 is declared and the same reference as acc1 is stored in it	acc3 and acc1 points to the same Account object in the heap that has "Carlos" and 5000 in it despite being different variables.
acc2.balance = 8000;	8000 is now assigned to the balance of the second account object.	The balance field of the 2nd field is updated, replacing 7000 in the heap.
acc3.owner = "Miguel";	"Miguel" is assigned to the owner field that acc3 (and acc1) points to.	The owner field of the first object is now "Miguel" instead of "Carlos" in the heap.
System.out.println(acc1. owner + " " + acc1. balance);	This displays the values stored in the first object that acc1 points to.	It reads the values. No memory changes.
System.out.println(acc2. owner + " " + acc2. balance);	Displays the values stored in the second object that acc2 points to.	It reads the values. No memory changes.
System.out.println(acc3. owner + " " + acc3. balance);	Displays the values stored in the same object that acc1 points to.	Reads the values stored. No memory changes.
PART C - output		
Miguel 5000.0		
Diana 8000.0		
Miguel 5000.0		